

Description

The invention relates to a method for dispensing flexible web material from rolls that are wound on cores comprising the steps: retaining first and second rolls of material in roll dispensing and reserve roll positions, respectively; releasing the second roll from retention in the reserve roll position into the roll dispensing position upon removal of the core of the first roll subsequent its exhaustion.

The invention relates further to a dispenser for rolls of flexible web material wound on cores comprising a housing for receiving a first and a second roll in a roll dispensing position and a reserve roll position, respectively, and lever means pivotally mounted on the housing having a lower end which contacts the core of the roll in the roll dispensing position and an upper end to retain the second roll in the reserve roll position and to free this roll after a pivotal movement caused by the removal of the exhausted core contacting the lower end.

A corresponding dispenser is known from the Swiss patent 404 124 which also allows the above mentioned method steps. The roll in the roll dispensing position is guided by the housing and by the lower parts of lateral levers which belong to the releasing mechanism for the second roll in the reserve roll position. The roll in the roll dispensing position rests on two little trays which leave a gap for removing an exhausted core.

The removal of the exhausted cores is carried out manually and at the same time the lower parts of the levers move inwardly in order to release the roll from the reserve roll position into the roll dispensing position. The gap for removing the exhausted cores within the housing is rather big in order to allow a comfortable removal. This has the effect that cores are accidentally removed which carry a substantial quantity of web material. A pre-mature removal is almost inevitable if the roll core is not completely round but slightly oval. Then the size of the core still carrying web material is occasionally smaller than the gap in the housing and a removal takes place during use which leads to an unnecessary waste.

In the US-patent 3,211,504 a dispenser is disclosed in which split cores are used having axially aligned core sections. The two rolls of the dispenser are placed one over the other or one beside the other and upon exhaustion of the temporarily used roll a sliding door encapsles the place of this roll and gives access to a new roll beside or above the exhausted roll. The cores have to be open because each roll in the position of the first use is threaded onto a finger which tilts the two core sections upon exhaustion and the movement of the finger is used for causing the door to slide.

In this known dispenser there is no handling of a roll from a reserve roll position into a dispensing position so that a simple refilling during routine maintenance is impossible. When an operator finds one exhausted roll and one partly

used roll he has to remove the split cores, place the partly used roll into the position of the first use and has then to re-load the free space for the reserve roll.

It is an object of this invention to propose a method for dispensing flexible web material from rolls that are wound on cores and to propose a corresponding dispenser which allow a complete use of the whole web material wound on a core thus preventing any waste, and an easy re-loading by placing a reserve roll into the reserve roll position without the need of relocating a partly used roll.

As to the method the invention proposes to use axially aligned core sections which define an intact core within each roll of material while web material remains wound on these sections, to sense the intactness of the roll core of the first roll in the roll dispensing position by contacting the core and to utilize a buckling action of the sensed core which occurs upon exhaustion of web material for the automatic removal of this core.

As to the dispenser the invention proposes that each core has axially aligned core sections defining an intact core while web material remains wound on these sections and allowing the core to buckle upon exhaustion of web material, that the housing has opposed parallel track means extending between the roll dispensing and reserve roll positions to guidingly receive roll core supports projecting from opposite ends of the cores, that abutment means is associated with the track means to retain a first roll in the roll dispensing position and that the lower end of the lever means senses the intactness of the core in the roll dispensing position.

The dispenser and dispensing method of the instant invention overcome the above mentioned problems found to be present in the prior art dispensers for toilet paper rolls having cores. Under this invention web material dispensing from multiple rolls provided with transversely split cores is achieved. Assurance that the core sections will effectively discharge from the dispenser and then only after all toilet paper has been unwound from the core sections results.

In its broadest aspects, the method invention of the dispensing flexible web material from rolls of web material wound on axially aligned core sections which together define an intact core while web material remains wound on these sections, contemplates the capability of handling multiple rolls such that all web material is used or exhausted from the roll in the dispensing position before a reserve roll drops or moves to this dispensing position. Also the method contemplates that the empty core sections which made up the intact roll core will always drop out automatically whether or not a reserve roll is present elsewhere within the dispenser.

When the material is exhausted from the intact roll core the core sections of this roll at the roll dispensing position undergo a buckling action. This action is utilized to effect disengagement of the core sections from the roll dispensing position

and also to effect release of the second roll from its retention in the reserve roll position, allowing the second roll to move into the roll dispensing position.

Generally describing the dispenser apparatus, it employs a spring loaded pivot lever that performs two functions. First, the lever holds the reserve roll away from the roll in a dispensing position, at least when the core sections of this latter roll approach becoming empty. Thus there is no friction between the reserve roll and roll from which toilet paper is being dispensed at the time that this latter roll is near exhaustion of toilet paper.

Secondly, the lever applies a slight pressure against the top edge of one of the roll core sections in a direction that tends to lift this roll core off of its support such as to eliminate friction between the roll core section and its support point. This also imparts a force to the end of the roll core section that effectively twists and promotes the buckling action between the core sections to effect their disengagement from retention with the dispenser guide tracks.

Thus, a preferred embodiment of the dispenser of this invention comprises a housing providing opposed parallel track means extending between roll dispensing and reserve roll positions within the housing, these tracks guidingly receiving roll core supports projecting from opposite ends of the rolls from which material is to be dispensed. A first roll is retained in the track means in a roll dispensing position and a lever means pivotally mounted on the housing provides a lower sensing end to sense the intactness of the roll core in this dispensing position and an upper support end to retain a second roll in the reserve roll position. This lever means serves to retain the second roll the lever support end in a reserve position as long as an intact core is sensed to be present in the dispensing position. This sensing end of the lever tends to buckle the core sections as it presses against the end of the roll core upon exhaustion of web material from the intact roll core so that the core sections disengage from the track means of the dispenser allowing the lever means to shift such that the support end frees the second roll from retention in the reserve position for it to move down into the roll dispensing position.

According to a certain embodiment of the invention a biasing force promotes separation of the core sections and this force is directed against the core end in a direction that tends to lift the core in conjunction with the buckling action of the core section. According to a further embodiment of the invention a web material dispenser for split core rolls is proposed wherein the roll retained by its roll core supports projecting from opposite ends of this roll in the roll dispensing position is blocked against removal from this position until all web material is exhausted from the split core thereby obviating pilferage of full or partly used rolls from the dispenser.

The above and other objects of the invention

will become apparent from consideration of the following detailed description of a preferred embodiment thereof given in conjunction with the following drawings.

Figure 1 is a perspective view of the dispenser in accordance with the invention with the conventional cabinet cover removed.

Figure 2 is a partial sectional view taken through the guide track channels that guidingly receive the roll core supports showing a fragment of a roll moving toward the roll dispensing position at the bottom of these channels.

Figure 3 is a sectional view similar to Figure 2, but showing a first roll in the roll dispensing position and a second roll retained in the reserve roll position.

Figure 4 is a sectional view comparable to Figure 3, but showing the intact core of the first roll exhausted of web material and in broken lines the buckling action occurring between the core sections.

Figure 5 is a sectional view similar to Figure 4 showing the second roll having moved from the reserve position in Figure 4 into the roll dispensing position.

In describing the dispenser 10 for rolls of flexible web material as shown on the drawings it should be pointed out that to facilitate illustrating structural features of the invention the usual cover that would conventionally be provided has not been shown on the drawings. Reference may be made to Jespersen patent 3,437,388 for an exemplification of how a conventional cover completing the dispenser cabinet may be pivotally mounted in relation to the housing forming the chassis for the working components of the dispenser. In the drawings of this application only the dispenser housing 12 forming this chassis has been shown to better illustrate the functional components of the dispenser 10.

Reference has also been made hereinabove to this Jespersen patent 3,437,388 as an example of a dispenser for flexible web material which is wound into rolls on axially aligned core sections such that in the roll form these core sections define an intact roll core as long as web material remains wound on such sections. This is the type of roll which the dispenser and dispensing method of the instant invention are intended to accommodate.

With reference to the terminology employed herein, it is to be understood that in referring to rolls of flexible web material wound on axially aligned core sections it is intended that the term core section be construed to include a tubular or cylindrical portion, usually made of paper board, on which the flexible material in the form of toilet paper is conventionally wound together with its end cap which may be molded of plastic and inserted into the tubular portion to provide the roll core support spindle projecting outwardly from the end of the roll.

Two such core sections A and B forming an intact roll core are shown in section on Figure 3 and 4.

Likewise, the term core section is to be interpreted as contemplating a core within a roll of web material where the roll core supports projecting from opposite ends of the roll are provided other than by inserted end caps.

Also as used herein it is to be understood that although the aligned core sections making up an intact core while web material remains wound thereon are preferably separate and discrete sections so that they are free to separate or fall apart when the material is total unwound from the aligned core sections, it is to be understood that the aligned core sections might be retained in the form of an intact roll core by the maintenance of a partial or minor connection between adjoining aligned core sections. For example, the junction or joint between the aligned core sections might be a weakened junction formed such as by perforations or other means which would facilitate the buckling action between the core sections desired to take place in accordance with this invention upon exhaustion of web material from the intact roll core that is made up of these aligned core sections.

Indeed, an end of the toilet paper web may be glued to one of the core sections at the start of winding the roll. Then in using paper from the roll when the end of the roll is reached the act of withdrawing the last bit of paper from the roll will physically pull the core section out of dispenser 10.

Referring to Figure 1 on the drawings in describing the dispenser 10, the housing 12 provides a first side wall 14, a second side wall 16 and a back wall 18. It will be understood that in use of dispenser 10 the housing 12 forming the chassis for the working components of the dispenser will be appropriately mounted on a wall at the desired location for dispenser use. Thus, the back 18 of housing 12 will be provided with appropriate openings (not shown) to accommodate the fasteners employed in affixing dispenser 10 to the desired wall location.

As has been mentioned above, the conventional cover which with housing 12 completes the dispenser 10 cabinet is not shown. Side walls 14 and 16 are shown provided with aligned holes 20, these holes serving as pivot point to mount the dispenser cover such as suggested in the dispenser of Jespersen patent 3,437,388.

Side wall 14 of housing 12 is provided with an inwardly facing channel 22. Likewise, the second and opposite side wall 16 is provided with an inwardly facing channel 24. As may be best visualized from Figures 3 and 4, this pair of inwardly facing channels 22 and 24 serve to guidingly receive the spindles which form part of the roll core sections and serve as the roll core supports where they project from opposite ends of the rolls when the rolls are loaded into the dispenser 10.

Preferably the channels 22 and 24 are of different widths to accommodate different diameter spindles forming the roll core supports for the rolls that are loaded into the dispenser. These

different channel widths to mate with different diameter roll core support spindles ensures the proper unwinding direction or orientation in loading the rolls into dispenser 10. However, in the structure of dispenser 10 where the pair of rolls loaded into the dispenser are maintained out of contact with each other in the manner as will be explained, the particular direction of winding or unwinding of the rolls used in the dispenser is not totally critical to dispenser operation.

In any event, the feature of different width guide tracks accommodating different diameter roll core support spindles is known and discussed in the above discussed Jespersen patent 3,437,388.

Each of the guide track channels 22 and 24 in the side walls 14 and 16 of housing 12 is provided at its lower end with a saddle member, this member being numbered 26 at the bottom of channel 22 and 28 at the lower end of channel 24. It may be noted that the bottom of housing 12 is open at 30 such that the roll D retained in the roll dispensing position at the bottom of dispenser 10 projects downwardly through open bottom 30 as shown on Figure 3 for the web material on roll D to be accessible from dispenser 10 to the intending user.

Referring to Figure 3, the make up of roll D may be described as exemplifying the type of rolls of flexible web material contemplated for dispensing in the dispenser 10 of this invention. Thus, roll D has the flexible web material wound on axially aligned core sections A and B which together define an intact roll core C with a junction J at the separating line between the core sections A and B.

In the form of roll core illustrated, the roll core supports for core C are provided by an end cap E inserted in the outer end of the tubular portion to complete core section A and an end cap F inserted in the tubular portion to complete core section B. It will be seen from Figure 3 how the core support spindle of end cap E engages in the saddle member 26 at the bottom of channel 22 and the core support spindle of end cap F engages in the saddle member 28 at the bottom of channel 24 to support roll D in the roll dispensing position within the housing 12 of dispenser 10. As so supported, the toilet paper material on roll D projects down through the open bottom 30 of housing 12.

As illustrated on the drawings, the open bottom 30 is defined within the side walls 14 and 16 and back wall 18 of housing 12, these walls extending down beneath saddle members 26 and 28. Generally, with the dispenser cover (not shown) in place, the cover in association with housing 12 might take the configuration shown in the above discussed Jespersen patent 3,437,388. With such a configuration the toilet paper material on roll D is exposed through the open bottom 30 of dispenser 10.

It will be understood that the roll R partially shown on Figures 3 and 4 as it is retained in the reserve roll position within housing 12 would

have a similar make up to that hereinabove described with reference to roll D.

The operating control for the dispenser 10 as between the two rolls D and R loaded into the housing 12 is provided by a control lever 40. This lever is pivotally mounted in channel 22 of side wall 14 on pivot pin 42. This pivotal mounting enables pin 42 to simply pass through the sides of channel 22 to effect the desired mounting of control lever 40.

Lever 40 has a lower sensing end 44 which serves to sense an intact roll core such as that of roll D as shown on Figure 3 when this first roll is retained at the roll dispensing position within housing 12. An upper support end 46 on pivotally mounted lever 40 serves to retain a second roll in the reserve roll position within housing 12 such as roll R shown on Figure 3.

A leaf spring 48 which may be riveted at 50 to the outer wall of channel 22 serves to bias control lever 40 toward the position as shown on Figure 2. This biasing force of spring 48 thus urges the sensing end 44 of lever 40 toward the roll dispensing position within housing 12 and consequently urge support end 46 of lever 40 away from the reserve roll position within housing 12.

It will be noted that the lower sensing end 44 of control lever 40 is contoured and inclined so as to apply a buckling force to the end of the roll core C in a direction tending to lift this intact core, particularly under the biasing force provided by leaf spring 48 acting on lever 40.

Further the terminal portion 52 of the lower sensing end 44 on lever 40 is shaped to be off center from the longitudinal center line of lever 40. This shaping of the terminal portion 52 tends to apply the buckling force that is to operate on the core sections in promoting the buckling action at a point laterally spaced from a vertical plane which includes the rotational axis of the first roll or roll D when it is retained in the roll dispensing position within housing 12 of dispenser 10.

The shaping of the terminal portion 52 disposes the point on such portion 52 that engages with the end of core C of roll D to be in line with the edge of one side of the opposite channel 24, having in mind that channel 24 is of a lesser width than that of channel 22 in which lever 40 is pivotally mounted. This edge of track 24 on the opposite side 16 of housing 12 is the edge on the channel 24 side which is closest to the back wall 18 of housing 12, as these parts are shown on Figure 1.

Locating the point on terminal portion 52 which is to engage the core end opposite the edge of channel 24 that is closest to the back wall 18 insures that core C is held at only two points, these points being directly opposite each other. This two point retention of core C on roll D provides retention of the core in an unstable condition such that when web material is exhausted from the core, the two point support at the opposite core ends promotes the buckling

action between the core sections A and B, thereby further insuring their disengagement from the track channels 22 and 24 and the saddle members 26 and 28 of these channels.

To avoid possible three point roll core support and assure the above described two point support between a point on terminal portion 52 of lever 40 and that directly opposite edge of channel 24, the edge of the side of channel 24 that is furthest from the back wall 18 may have a slightly depressed area 54 (Figure 1). The depressed area 54 is at the point where the core end adjacent channel 24 would otherwise touch this channel side edge located furthest from back wall 18 when the roll core is pushed endwise by the biasing force exerted by lever 40 through its lower sensing end 44. Thus, the depressed area 54 assures that the roll core is held at only two points to establish the above described unstable condition which promotes the buckling action when the web material is exhausted from the aligned roll core sections A and B of roll D.

The upper support end 46 of control lever 40 is formed with a reverse bend in the embodiment shown such as to provide a surface 56 which is inwardly inclined relative to the plane of the first side wall 14 of housing 12. This inclined surface 56 physically engages with the roll core support spindle such as shown in Figures 3 and 4 with reference to roll R retained in the reserve roll position within housing 12 of dispenser 10.

As will be apparent from the showing on these figures, the inward inclination of surface 56 on the upper support end 46 of lever 40 tends to utilize the weight of roll R acting down through the spindle resting on inclined surface 56 in a manner tending to urge lever 40 and its upper support end 46 outwardly of track 22. Thus, this weight of roll R promotes the lower sensing end 44 of lever 40 to press inwardly against the end of the core C made up of sections A and B thereby tending to buckle the core sections upon exhaustion of web material from the intact roll core of roll D so as to disengage the core sections from the track channels 22 and 24 and their saddle members 26 and 28.

The second side wall 16 of housing 12 is provided with a spring biased latch 60 which may be riveted at 62 to the outer wall of channel 24 for this latch 60 to lie within channel 24. The spring biased latch 60 has its lower end 64 spaced above saddle member 28 at the bottom of channel 24. Thus, it is spaced sufficiently above such saddle member that the spindle of end cap F on core section B may freely rest on saddle member 28 beneath the end 64 of latch 60 as shown on Figures 3 and 4.

It will be understood that as the spindle of end cap F moves down along the guide track channel 24 this spindle will act to depress latch 60 until it moves beneath the latch end 64. In this position reverse movement along the guide track 24 is blocked by latch 60. This blocking action serves to prevent the right end of roll D (as shown on Figure 3) from being raised up within the hous-

ing 12 of dispenser 10 thus preventing pilferage of full or partial toilet paper rolls from the dispenser 10.

It will be recognized that the left end of roll D is likewise prevented from being raised back up within channel 22 by the lower sensing end 44 of lever 40 overlying the spindle on end cap E forming a part of core section A, again as shown on Figures 3 and 4.

The second side wall 16 of housing 12 is also provided with a brake spring 70. This spring may have its upper end suitably riveted at 72 to side wall 16. Spring 70 is positioned adjacent the roll dispensing position within housing 12 to project inwardly and apply frictional resistance to one end of the first roll which is retained in the roll dispensing position. The function of brake spring 70 is to retard rotation of roll D or the roll disposed in the dispensing position so that it does not freely revolve or spin as the web material, such as toilet paper, is withdrawn from dispenser 10 by the intending user.

Operation of the dispenser 10 as hereinabove ascribed may now be explained. In Figure 1 the dispenser housing 12 is shown in its empty or unloaded condition. The sectional view of Figure 2 shows the initial or first roll D as it is being loaded with its core support spindles (not shown) guidingly engaging with the track channels 22 and 24 as the roll passes down into the dispensing position at the lower end of housing 12.

In Figure 3 roll D is shown with its support spindles on the core sections A and B resting on the saddle members 26 and 28 of channels 22 and 24, respectively. In this position, roll D has the material thereof exposed through the open bottom 30 of housing 12 for ready access to the intending user. Further in Figure 3 the second or reserve roll R has been loaded into the housing 12 by its spindles being entered into the upper ends of channels 22 and 24, respectively.

But, the position of roll D as it passed down into the dispensing position location has shifted lever 40 such that the upper support end 46 of such lever has been moved into channel 22 to form a stop within channel 22. As shown on Figure 3 the left spindle of roll R has come into engagement with this stop by the spindle resting on the inclined surface 56 of upper support end 46 of lever 40.

It will be recognized that the brake spring 70, best seen on Figure 1, has been activated by the downward movement of roll D such that spring 70 is applying frictional resistance to retard free rotation of roll D. Likewise, the downward movement of the spindles on roll D into engagement with the saddle members 26 and 28 has caused the spindle on end cap F to pass beneath the latch end 64 on spring biased latch 60. Accordingly, with the lower sensing end 44 of lever 40 overlying the left spindle on roll D and the end 64 of spring biased latch 60 overlying the right spindle of roll D, any attempt to raise the roll D is effectively blocked by these two elements overlying the core support spindles at the opposite ends of roll D.

The above described condition of rolls D and R

as shown on Figure 3 where they are both retained in their respective dispensing and reserve roll positions will continue while utilization of web material from roll D is taking place by the toilet paper web being withdrawn by intending users. Also during this use of web material from roll D the control lever 40, especially under the biasing force of leaf spring 48, will be continuously sensing the intact roll core C made up of the axially aligned core sections A and B. Thus the second roll R in the reserve roll position is continuously retained in this position during the sensing of an intact roll core C.

As will be seen from Figure 3, the diameter of rolls R and D in relation to the length of lever 40, where such lever extends above its pivot pin 42, is such as to maintain these full rolls R and D out of contact with each other. Thus, with this particular full size roll and length of pivotally mounted lever 40, rolls R and D will be continuously maintained out of contact with each other as web material is being withdrawn from roll D.

However, it is contemplated that the continuing retention of roll R in the reserve roll position, as long as the intact roll core of roll D is sensed, could include a situation where a full reserve roll R initially rests on top of a full roll D when the latter roll is retained in the roll dispensing position. This might occur by reason of different initial full roll diameters and/or a different length of pivoted lever 40. In such a situation, the continuing retention of roll R in the reserve roll position while resting on roll D will, in effect, be caused by the roll R itself sensing that roll D has an intact roll core. This sensing would occur even though the left spindle of roll R has not yet come into engagement with the stop formed by the upper support end 46 of lever 40 disposed within channel 22.

Then as material is withdrawn from roll D with consequent reduction in the diameter of roll D, roll R will move down with its spindles in guide track channels 22 and 24 until the spindle in channel 22 comes into engagement with and thereafter rests upon the upper support end 46 of lever 40. Thereafter, withdrawal of material from roll D, causing continued reduction in the diameter of roll D, leaves roll R continuing to be retained in the reserve roll position, but now sensing of the intact core of roll D is done by pivoted lever 40.

Thus, the sensing of the intact core C of roll D is employed to continue retention of roll R in the reserve roll position with the two rolls out of contact with each other at least when the core sections of roll D approach becoming empty so that in this latter stage of exhausting roll D there is no friction between the reserve roll R and roll D. The important concept is that sensing of the intact core of roll D be utilized to continue retention of roll R in the reserve roll position and at least retain the two rolls out of contact with each other during the stage when roll D nears exhaustion of its web material.

When the web material is fully withdrawn and roll D becomes exhausted the condition shown on Figure 4 exists. At this time the reserve roll or

second roll R is still retained in the reserve roll position at the upper end of housing 12. However, the lower sensing end 44 of lever 40 as it presses against the end of the intact roll core C urges buckling of the core sections A and B upon the occurrence of exhaustion of web material from the intact core C. This effects disengagement of the core sections A and B from retention in the roll dispensing position. More specifically, it urges the core sections A and B to progress through the broken line showing for one core section A at the left on Figure 4. Thus, the force applied by the sensing end 44 not only applies a buckling force to the core end, but by reason of the contour and shaping of sensing end 44 at 52 it directs this buckling force against the core end in a direction tending to lift the core off of the saddle member 26, thereby freeing it from the friction which previously existed between the roll core support spindle and saddle member 26 during normal use of web material from roll D.

As the intact core C undergoes the buckling action between its core sections A and B following exhaustion of web material from the intact roll core, the core sections disengage from the track channels 22 and 24 and their saddle members 26 and 28, falling out of the open bottom 30 of housing 12. This frees lever 40, especially under the urging of leaf spring 48, to move to a position as is shown in Figure 2.

This movement effectively shifts the sensing end 44 of lever 40 into the roll dispensing position area and likewise shifts the support end 46 of lever 40 away from the reserve roll position area thereby opening track guide channel 22 such that the spindles of roll R are now freed for this roll to move down into the dispensing position at the bottom of housing 12.

This condition for roll R is shown on Figure 5. From this figure it will be noted that the lever 40 has again been shifted by its lower sensing end 44 detecting the intact core within roll R. This shifting of lever 40 again moves the upper support end 46 of lever 40 into a position to block track channel 22. Thereafter, in loading a new roll into the dispensing housing 12, by entering its outwardly projecting roll core support spindles into the opposite channels 22 and 24, this new roll can only pass down these channels to a point where one of its spindles encounters the upper support end 46 of lever 40 which is blocking the channel 22. Again this new roll will be held in reserve until such time as the roll located in the roll dispensing position resting on the saddle members 26 and 28 has been exhausted. Upon exhaustion of material from this latter roll, the process of the buckling action acting on the core sections to discharge them from the track channels and saddle members will repeat itself whereafter the new roll retained in the reserve position will be released.

While the foregoing is believed to constitute a complete description of a preferred embodiment of the invention, it is to be recognized that various modifications, changes, alterations, etc. may well appear to those skilled in the art. Therefore, the

invention is not considered to be limited by the specifics of the disclosed embodiment, but rather to be embrasive of all subject matter falling within the terms of the hereinafter appended claims.

Claims

1. Method for dispensing flexible web material from rolls (R, D) that are wound on cores (C) comprising the steps:

retaining first and second rolls (R, D) of material in roll dispensing and reserve roll positions, respectively;

releasing the second roll (R) from retention in the reserve roll position into the roll dispensing position upon removal of the core (C) of the first roll (D) subsequent its exhaustion, the improvement comprising:

using axially aligned core sections (A, B) which define an intact core (C) within each roll (R, D) of material while web material remains wound on these sections (A, B);

sensing the intactness of the roll core (C) of the first roll (D) in the roll dispensing position by contacting the core (C); and

utilizing a buckling action of the sensed core (C) which occurs upon exhaustion of web material for the automatic removal of this core (C).

2. Method according to claim 1, further comprising the steps of supporting the core (C) of the second roll (R) for a guided movement from the reserve roll position to the roll dispensing position.

3. Method according to claim 1 or 2, further comprising the step of securing the end of the flexible web material to one of the core sections (A; B) at the start of winding a roll (R, D).

4. Method according to any one of claims 1 to 3, wherein the sensing includes applying a buckling force to the core end to promote separation of the core sections (A, B).

5. Method according to claim 4 wherein the applying of the buckling force to the core end includes directing this force against the core end in a direction tending to lift the intact core (C) in conjunction with the buckling action.

6. Dispenser (10) for rolls (R, D) of flexible web material wound on cores (C) comprising a housing (12) for receiving a first and a second roll (R, D) in a roll dispensing position and a reserve roll position, respectively, and lever means (40) pivotally mounted on the housing (12) having a lower end which contacts the core (C) of the roll (D) in the roll dispensing position and an upper end to retain the second roll in the reserve roll position and to free this roll (R) after a pivotal movement caused by the removal of the exhausted core contacting the lower end, characterized in that each core (C) has axially aligned core sections (A, B) defining an intact core (C) while web material remains wound on these sections and allowing the core (C) to buckle upon exhaustion of web material, that the housing (12) has opposed parallel track means (22, 24) extending between the roll dispensing and reserve roll positions to guidingly

second roll R is still retained in the reserve roll position at the upper end of housing 12. However, the lower sensing end 44 of lever 40 as it presses against the end of the intact roll core C urges buckling of the core sections A and B upon the occurrence of exhaustion of web material from the intact core C. This effects disengagement of the core sections A and B from retention in the roll dispensing position. More specifically, it urges the core sections A and B to progress through the broken line showing for one core section A at the left on Figure 4. Thus, the force applied by the sensing end 44 not only applies a buckling force to the core end, but by reason of the contour and shaping of sensing end 44 at 52 it directs this buckling force against the core end in a direction tending to lift the core off of the saddle member 26, thereby freeing it from the friction which previously existed between the roll core support spindle and saddle member 26 during normal use of web material from roll D.

As the intact core C undergoes the buckling action between its core sections A and B following exhaustion of web material from the intact roll core, the core sections disengage from the track channels 22 and 24 and their saddle members 26 and 28, falling out of the open bottom 30 of housing 12. This frees lever 40, especially under the urging of leaf spring 48, to move to a position as is shown in Figure 2.

This movement effectively shifts the sensing end 44 of lever 40 into the roll dispensing position area and likewise shifts the support end 46 of lever 40 away from the reserve roll position area thereby opening track guide channel 22 such that the spindles of roll R are now freed for this roll to move down into the dispensing position at the bottom of housing 12.

This condition for roll R is shown on Figure 5. From this figure it will be noted that the lever 40 has again been shifted by its lower sensing end 44 detecting the intact core within roll R. This shifting of lever 40 again moves the upper support end 46 of lever 40 into a position to block track channel 22. Thereafter, in loading a new roll into the dispensing housing 12, by entering its outwardly projecting roll core support spindles into the opposite channels 22 and 24, this new roll can only pass down these channels to a point where one of its spindles encounters the upper support end 46 of lever 40 which is blocking the channel 22. Again this new roll will be held in reserve until such time as the roll located in the roll dispensing position resting on the saddle members 26 and 28 has been exhausted. Upon exhaustion of material from this latter roll, the process of the buckling action acting on the core sections to discharge them from the track channels and saddle members will repeat itself whereafter the new roll retained in the reserve position will be released.

While the foregoing is believed to constitute a complete description of a preferred embodiment of the invention, it is to be recognized that various modifications, changes, alterations, etc. may well appear to those skilled in the art. Therefore, the

invention is not considered to be limited by the specifics of the disclosed embodiment, but rather to be embrasive of all subject matter falling within the terms of the hereinafter appended claims.

Claims

1. Method for dispensing flexible web material from rolls (R, D) that are wound on cores (C) comprising the steps:

retaining first and second rolls (R, D) of material in roll dispensing and reserve roll positions, respectively;

releasing the second roll (R) from retention in the reserve roll position into the roll dispensing position upon removal of the core (C) of the first roll (D) subsequent its exhaustion, the improvement comprising:

using axially aligned core sections (A, B) which define an intact core (C) within each roll (R, D) of material while web material remains wound on these sections (A, B);

sensing the intactness of the roll core (C) of the first roll (D) in the roll dispensing position by contacting the core (C); and

utilizing a buckling action of the sensed core (C) which occurs upon exhaustion of web material for the automatic removal of this core (C).

2. Method according to claim 1, further comprising the steps of supporting the core (C) of the second roll (R) for a guided movement from the reserve roll position to the roll dispensing position.

3. Method according to claim 1 or 2, further comprising the step of securing the end of the flexible web material to one of the core sections (A; B) at the start of winding a roll (R, D).

4. Method according to any one of claims 1 to 3, wherein the sensing includes applying a buckling force to the core end to promote separation of the core sections (A, B).

5. Method according to claim 4 wherein the applying of the buckling force to the core end includes directing this force against the core end in a direction tending to lift the intact core (C) in conjunction with the buckling action.

6. Dispenser (10) for rolls (R, D) of flexible web material wound on cores (C) comprising a housing (12) for receiving a first and a second roll (R, D) in a roll dispensing position and a reserve roll position, respectively, and lever means (40) pivotally mounted on the housing (12) having a lower end which contacts the core (C) of the roll (D) in the roll dispensing position and an upper end to retain the second roll in the reserve roll position and to free this roll (R) after a pivotal movement caused by the removal of the exhausted core contacting the lower end, characterized in that each core (C) has axially aligned core sections (A, B) defining an intact core (C) while web material remains wound on these sections and allowing the core (C) to buckle upon exhaustion of web material, that the housing (12) has opposed parallel track means (22, 24) extending between the roll dispensing and reserve roll positions to guidingly



receive roll core supports (E, F) projecting from opposite ends of the cores (C), that abutment mean (26, 28) is associated with the track means (22, 24) to retain the first roll (D) in the roll dispensing position and that the lower end (44) of the lever means (40) senses the intactness of the core in the roll dispensing position.

7. Dispenser according to claim 6, wherein the lower sensing end (44) of the lever means (40) is biased towards the core end by spring means (48) to promote buckling of the core (C) upon exhaustion of web material.

8. Dispenser according to claim 6 or 7 wherein the track means is provided by an inwardly facing channel (22, 24) on each side wall (14, 16) of the housing (12) and the abutment means is provided by a saddle member (26, 28) adjacent the lower end of each channel (22, 24), the channel serving to guidingly receive spindles (E, F) forming part of the roll core sections (A, B) that provide the roll core supports, the spindles (E, F) engaging in the saddle members (26, 28) to retain the first roll (D) in the roll dispensing position.

9. Dispenser according to any one of claims 6 to 8 wherein the lever means includes a lever (40) pivoted intermediate the sensing end (44) and the support end (46) on the first of the side walls (14).

10. Dispenser according to claim 9 wherein the lever (40) is pivotally mounted within one of the channels (22).

11. Dispenser according to any one of claims 6 to 10 including a spring biased latch (64) mounted on the second side wall (16) of the housing (12) to block reverse movements along the track means (24) of the roll core support (F) at one end of the first roll (D).

12. Dispenser according to any one of claims 6 to 11 including a brake spring (70) mounted on one of the side walls (16) of the housing (12) positioned adjacent the roll dispensing position to project inwardly and apply frictional resistance to the end of the first roll (D) retained in the roll dispensing position.

13. Dispenser according to any one of claims 7 to 12 wherein the sensing end (44) of the lever (40) is contoured to apply the buckling force to the core end in a direction tending to lift the intact core (C) in conjunction with the buckling of the core sections (A, B) and the support end (46) of the lever is formed with a surface (56) inwardly inclined relative to the first side wall (14) to engage with a roll core support (E) at one end of the second roll (R) to retain this roll (R) in the reserve roll position.

14. Dispenser according to any one of claims 9 to 13 wherein the sensing end (44) of the lever (40) has a terminal portion off center from the lever's longitudinal center line to apply the buckling force at a point laterally spaced from a vertical plane that includes the rotational axis of the first roll (D) retained in the dispensing position.

Patentansprüche

1. Verfahren zur Abgabe eines flexiblen Band-

materials von Rollen (R, D), die auf Kerne (C) gewickelt sind, mit den Schritten:

Bereithalten einer ersten und zweiten Materialrolle (R, D) in einer Rollenabgabe- und einer Reservenrollenlage;

Ablassen der zweiten Rolle (R) von der Halterung aus der Reservenrollenlage in die Rollenabgabelage nach der Entfernung des Kerns (C) der ersten Rolle (D) im Abschluß an ihren Aufgebrauch, dessen Verbesserung folgende Schritte umfaßt:

Verwendung von in axialer Richtung ausgerichteten Kernabschnitten (A, B), die innerhalb jeder Materialrolle (R, D) einen unversehrten Kern (C) bilden, solange Bandmaterial auf diese Abschnitte (A, B) aufgewickelt ist;

Abtasten der Unversehrtheit des Rollenkerns (C) der ersten Rolle (D) in der Rollenabgabelage durch Berühren des Kerns (C); und

Ausnutzen einer Faltwirkung des abgetasteten Kerns (10), die bei Aufgebrauch des Bandmaterials eintritt, zur automatischen Entfernung dieses Kerns (C).

2. Verfahren nach Anspruch 1, mit den weiteren Schritten des Unterstützens des Kerns (C) der zweiten Rolle (R) für eine geführte Bewegung von der Reserverollenlage zu der Rollenabgabelage.

3. Verfahren nach Anspruch 1 oder 2, mit dem weiteren Schritt des Befestigens des Endes des flexiblen Bahnmaterials an einem der Kernabschnitte (A; B) zu Beginn des Wickelns einer Rolle (R, D).

4. Verfahren nach einem der Ansprüche 1 bis 3, bei dem das Abtasten das Aufbringen einer Knickkraft auf das Kernende einschließt, um die Trennung der Kernabschnitte (A, B) zu unterstützen.

5. Verfahren nach Anspruch 4, bei dem das Aufbringen der Knickkraft auf das Kernende die Steuerung dieser Kraft gegen das Kernende in eine Richtung einschließt, die das Anheben des intakten Kerns (C) in Verbindung mit der Knickwirkung zur Folge hat.

6. Spender (10) für Rollen (R, D) eines flexiblen Bandmaterial, das auf Kerne (C) gewickelt ist, mit einem Gehäuse (12) zur Aufnahme einer ersten und einer zweiten Rolle jeweils in einer Rollenabgabelage und einer Reserverollenlage und mit Hebelmitteln (40), die schwenkbar an dem Gehäuse (12) gelagert sind und ein unteres Ende aufweisen, das den Kern (C) der Rolle (D) in der Rollenabgabelage berührt, sowie ein oberes Ende aufweisen, um die zweite Rolle in der Reserverollenlage zu halten und um diesen Rolle (R) nach einer Schwenkbewegung freizugeben, die durch die Entfernung des aufgebrauchten Kerns während der Berührung mit dem unteren Ende hervorgerufen wird, dadurch gekennzeichnet, daß jeder Kern (C) aus in axialer Richtung ausgerichteten Kernabschnitten (A, B) besteht, die zusammen einen unversehrten Kern (C) bilden, solange Bandmaterial auf diese Abschnitte aufgewickelt ist, und die dem Kern (C) das Einknicken bei Aufgebrauch des Bandmaterials erlauben, daß das Gehäuse (12) mit sich gegenüberliegenden, parallelen Spurmitteln (22, 24) versehen ist, die



sich zwischen der Rollenabgabe- und der Reserverollenlage zur geführten Aufnahme von Rollen- kernstützen (E, F) erstrecken, die von den sich gegenüberliegenden Enden des Kernes (C) abste- hen, daß die Spurmitten (22, 24) mit Anschlagmit- teln (26, 28) versehen sind, um die erste Rolle (D) in der Rollenabgabelage zu halten, und daß das untere Ende (44) der Hebelmittel (40) die Unver- sehrtheit des Kernes in der Rollenabgabelage abta- stet.

7. Spender nach Anspruch 6, bei dem das untere Abtastende (44) der Hebelmittel (40) mit Hilfe von Federmitteln (49) gegen das Kernende vorgespannt ist, um das Knicken des Kernes (C) bei Aufgebrauch des Bandmaterials zu unterstützen.

8. Spender nach Anspruch 6 oder 7, bei dem die Spurmitten mit einem nach innen weisenden Kanal (22, 24) an jeder Seitenwand (14, 16) des Gehäuses (12) versehen sind, und die Anschlag- mittel durch ein Sattelglied (26, 28) in der Nähe des unteren Endes jedes Kanals (22, 24) gebildet sind, wobei der Kanal zur führenden Aufnahme von Spindeln (E, F) dient, die einen Teil der Kernabschnitte (A, B) bilden und die Rollenker- nstützen sind und wobei die Spindeln (E, F) in das Sattelglied (26, 28) eingreifen, um die erste Rolle (D) in der Rollenabgabelage zu halten.

9. Spender nach einem der Ansprüche 6 bis 8, bei dem die Hebelmittel einen Hebel (40) ein- schließen, der zwischen dem Tastende (44) und dem Stützende (46) an der ersten der beiden Seitenwände (14) schwenkbar gelagert ist.

10. Spender nach Anspruch 9, bei dem der Hebel (40) innerhalb des einen der beiden Kanäle (22) schwenkbar gelagert ist.

11. Spender nach einem der Ansprüche 6 bis 10, unter Einschluß einer federbelasteten Falle (64), die an der zweiten Seitenwand (16) des Gehäuses (10) angebracht ist, um eine Rückwärts- bewegung entlang den Spurmitten (24) für die Rollenker- nstütze (F) an einem Ende der ersten Rolle (D) zu verhindern.

12. Spender nach einem der Ansprüche 6 bis 11, unter Einschluß einer Bremsfeder (70), die an einer der beiden Seitenwände (16) des Gehäuses (12) angebracht ist und in der Nähe der Rollenab- gabelage positioniert ist, um nach innen hervor- zuziehen und einen Reibungswiderstand auf das Ende der ersten Rolle (D) aufzubringen, die in der Rollenabgabelage gehalten ist.

13. Spender nach einem der Ansprüche 7 bis 12, bei dem das Tastende (44) des Hebels (40) so geformt ist, daß eine Knickkraft auf das Kernende in einer Richtung aufgebracht wird, die die Nei- gung hat, den unversehrten Kern (C) in Verbin- dung mit dem Knicken der Kernabschnitte (A, B) anzuheben, und bei dem das Stützende (46) des Hebels mit einer Fläche (56) versehen ist, die relativ zu der ersten Seitenwand (14) einwärts geneigt ist, um mit einer Rollenker- nstütze (E) an einem Ende der zweiten Rolle (R) zusammenzu- wirken, damit diese Rolle (R) in der Reserverollen- lage gehalten wird.

14. Spender nach einem der Ansprüche 9 bis 13, bei dem das Tastende (44) des Hebels (40)

einen Endabschnitt aufweist, der außerhalb der Mittelachse in Längsrichtung des Hebels liegt, um die Knickkraft an einem Punkt aufzubringen, der seitlich von einer vertikalen Ebene einen Abstand hat, die die Rotationsachse der in der Abgabelage gehaltenen ersten Rolle (D) enthält.

Revendications

1. Procédé pour distribuer un matériau en bande flexible à partir de rouleaux (R, D) qui sont enroulés sur des bobines (C), comprenant les opérations consistant à: maintenir les premier et second rouleaux de matériau (R, D) dans des positions de distribution de rouleau et de rouleau de réserve respectivement; dégager le second rouleau (R) de sa retenue dans sa position de rouleau de réserve vers la position de distribution de rouleau après retrait de la bobine (C) du premier rouleau (D) lorsqu'il est vide, le perfec- tionnement comprenant:

l'utilisation de sections de bobine (A, B) ali- gnées axialement, qui définissent une bobine d'un seul tenant (C) à l'intérieur de chaque rou- leau de matériau (R, D) alors que le matériau en bande reste enroulé sur lesdites sections (A, B);

la détection de l'intégrité de la bobine de rouleau (C) du premier rouleau (D) dans la posi- tion de distribution de rouleau par contact avec la bobine (C); et

l'utilisation d'une action de flambage de la bobine (C) soumise à la détection, qui apparaît quand le matériau en bande est terminé, en vue du retrait automatique de cette bobine (C).


2. Procédé selon la revendication 1, compre- nant en outre les opérations consistant à suppor- ter la bobine (C) du second rouleau (R) en vue d'un mouvement guidé depuis la position de rouleau de réserve jusqu'à la position de distribu- tion de rouleau.

3. Procédé selon la revendication 1 ou 2, compre- nant en outre l'opération consistant à fixer l'extrémité du matériau en bande flexible à l'une des sections (A; B) de la bobine au début de l'enroulement d'un rouleau (R, D).

4. Procédé selon l'une quelconque des revendi- cations 1 à 3, dans lequel la détection comprend l'application d'une force de flambage à l'extré- mité de la bobine pour faciliter la séparation des sections (A, B) de la bobine.

5. Procédé selon la revendication 4, dans lequel l'application de la force de flambage sur l'extré- mité de la bobine comprend l'opération consis- tant à diriger cette force contre l'extrémité de la bobine dans une direction qui tend à soulever la bobine d'un seul tenant (C) en conjonction avec l'action de flambage.

6. Distributeur (10) pour des rouleaux (R, D) de matériau en bande flexible enroulé sur les bobines (C) comprenant un logement (12) pour recevoir un premier et un second rouleau (R, D) dans une position de distribution de rouleau et une position de rouleau de réserve respec- tivement, et des moyens à levier (40) montés de façon pivotante dans le logement (12), compre-



l'extrémité inférieure qui est en contact avec la bobine (C) du rouleau (D) dans la position de distribution de rouleau et une extrémité supérieure qui retient le second rouleau dans la position de rouleau de réserve et libère ce rouleau (R) après un mouvement de pivotement provoqué par le retrait de la bobine vide qui est en contact avec l'extrémité inférieure, caractérisé en ce que chaque bobine (C) comprend des sections de bobine (A, B) alignées axialement et définissant une bobine d'un seul tenant (C) alors que le matériau en bande reste enroulé sur ces sections et permettant à la bobine (C) de flamber lorsque le matériau en bande est terminé, en ce que le logement (12) comprend des moyens à piste parallèles et opposés (22, 24) s'étendant entre les positions de distribution de rouleau et de rouleau de réserve pour recevoir de façon guidée les supports (E, F) des bobines des rouleaux qui font saillies aux extrémités opposées des bobines (C), en ce que les moyens de butée (26, 28) sont associées aux moyens à piste (22, 24) pour retenir le premier rouleau (D) dans la position de distribution de rouleau et en ce que l'extrémité inférieure (44) du moyen à levier (40) détecte l'intégrité de la bobine dans la position de distribution du rouleau.

7. Distributeur selon la revendication 6, dans lequel l'extrémité de détection inférieure (44) du moyen à levier (40) est sollicitée en direction de l'extrémité de la bobine par des moyens à ressort (48) pour faciliter le flambage de la bobine (7) lorsque le matériau en bande est terminé.

8. Distributeur selon la revendication 6 ou 7, dans lequel les moyens à piste sont munis d'un canal (22, 24) tourné vers l'intérieur sur chaque paroi latérale (14, 16) du logement (12) et le moyen de butée est constitué par un organe en forme de selle (26, 28) adjacent à l'extrémité inférieure de chaque canal (22, 24), le canal servant à recevoir de façon guidée des broches (E, F) formant une partie des sections (A, B) de la bobine de rouleau qui constituent les supports de la bobine de rouleau, les broches (E, F) venant s'engager dans les organes en forme de selle (26, 28) pour retenir le premier rouleau (D) dans la position de distribution de rouleau.

9. Distributeur selon l'une quelconque des

revendications 6 à 8, dans lequel le moyen à levier comprend un levier (40) monté de façon pivotante entre l'extrémité de détection (44) et l'extrémité de support (46) sur la première des parois latérales (14).

10. Distributeur selon la revendication 10, dans lequel le levier (40) est monté de façon pivotante à l'intérieur de l'un des canaux (22).

11. Distributeur selon l'une quelconque des revendications 6 à 10, comprenant un verrou (64) sollicité par un ressort et monté sur la seconde paroi latérale (16) du logement (12) pour empêcher des mouvements en sens inverse le long des moyens à piste (24) du support (F) de la bobine de rouleau à une extrémité du premier rouleau (D).

12. Distributeur selon l'une quelconque des revendications 6 à 11, comprenant un ressort de freinage (70) monté sur l'une des parois latérales (16) du logement (12), disposé en un point adjacent à la position de distribution de rouleau de manière à faire saillie à l'intérieur et appliquer une résistance par frottement à l'extrémité du premier rouleau (D) retenu dans la position de distribution de rouleau.

13. Distributeur selon l'une quelconque des revendications 7 à 12, dans lequel l'extrémité de détection (44) du levier (40) est conformée pour appliquer la force de flambage à l'extrémité de la bobine dans une direction qui tend à soulever la bobine d'un seul tenant (C) en conjonction avec le flambage des sections de bobine (A, B), et l'extrémité de support (46) du levier comprend une surface (56) inclinée vers l'intérieur par rapport à la première paroi latérale (14) de manière à venir en contact avec un support (E) de bobine de rouleau à une extrémité du second rouleau (R) pour retenir ce rouleau (R) dans la position de rouleau de réserve.

14. Distributeur selon l'une quelconque des revendications 9 à 13, dans lequel l'extrémité de détection (44) du levier (40) comprend une portion d'extrémité qui est décalée par rapport à l'axe central longitudinal du levier pour appliquer la force de flambage en un point qui est espacé latéralement d'un plan vertical contenant l'axe de rotation du premier rouleau (D) retenu dans la position de distribution.



65

10

