



159159

CAPACITIVE DIGITAL TO ANALOG AND ANALOG TO DIGITAL CONVERTERS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 60/715,078, filed on September 8, 2005, which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

[0002] The present invention relates to digital to analog (D/A) and analog to digital (A/D) converters, and more particularly to capacitive and/or resistive D/A and A/D converters.

BACKGROUND OF THE INVENTION

[0003] Digital to analog (D/A) converters can include arrays of capacitors that are selectively switched to convert a digital signal to an analog counterpart. However, mismatch between capacitors may cause the D/A converter to be non-monotonic. Monotonicity in a D/A converter means that as the digital input to the converter increases over a full-scale range, the analog output never exhibits a decrease between one conversion step and a subsequent conversion step. In other words, the slope of the transfer characteristic is never negative in a monotonic converter.

[0004] Referring now to FIG. 1A, a D/A converter 10 is shown. The D/A converter 10 includes a binary capacitor array 14, switches 16 and 18, an



000000

operational amplifier (opamp) 20, and a capacitor C_f in a feedback arrangement with the opamp 20. Each of the capacitors in the array 14 have different values. More particularly, each capacitor in the array 14 is twice the value of the preceding capacitor. Switches SW selectively switch the capacitors in the array 14 between a voltage reference and a reference potential such as ground.

[0005] In use, the D/A converter 10 has sampling and integration stages. In the sampling stage, the switch 16 closes and selective ones of the capacitors are charged to the voltage reference as determined by the switches. In the integrating phase, the switch 16 is opened and the analog output is generated. For example, a four bit array may close a first or most significant bit (MSB) switch and a least significant bit (LSB) switch to represent 9/16 of a voltage reference.

[0006] Referring now to FIG. 1B, a non-monotonic output of a D/A converter is shown. For example, the analog output exhibits a decrease from one conversion step to the subsequent conversion step as shown at in FIG. 1B at 44. The non-monotonic output may be due to capacitor mismatch. For example, the capacitor $2^{N-1}C$ may be different than $2^{N-2}C + 2^{N-3}C + \dots + 2C + C$. Ideally, $2^{N-1}C - (2^{N-2}C + 2^{N-3}C + \dots + 2C + C) = C$. In other words, the difference between the MSB capacitor and the rest of the capacitors should be equal to a smallest or LSB capacitor

[0007] Referring now to FIG. 2, a D/A converter 50 including a linear capacitor array 54 is shown. The linear capacitor array 54 includes $2^N - 1$ capacitors that are selectively switched between a voltage reference and

reference potential such as ground. While the linear capacitor array 54 inherently monotonic, the number of switches required grows exponentially with the bit resolution. For example, a 16-bit digital to analog converter includes $2^{16}-1$ pairs of switches, which may be impractical.

SUMMARY OF THE INVENTION

[0008] A digital-to-analog converter (DAC) comprises a capacitive DAC that comprises N first capacitances that are connected in parallel and that have first ends and second ends, wherein N is an integer greater than one, and N first switches that selectively connect a selected one of the second ends of the N first capacitances to a common node and non-selected ones of the second ends of the N first capacitances to one of a voltage potential and a reference potential. Capacitance values of the N first capacitances are substantially equal. A second DAC communicates with the common node.

[0009] A digital-to-analog converter (DAC) comprises first converting means for converting a digital signal to an analog signal and that comprises N first capacitance means for providing capacitance that are connected in parallel and that have first ends and second ends, wherein N is an integer greater than one and N first switching means for selectively connecting one of the second ends of the N first capacitance means to a common node and others of the second ends to one of a voltage potential and a reference potential. Capacitance values of the N first capacitance means are substantially equal. Second

converting means converts a digital signal to an analog signal and that communicates with the common node.

[0010] A method for providing a digital-to-analog converter (DAC) comprises connecting N first capacitances of a first capacitive DAC in parallel, wherein the N first capacitances have first ends and second ends, N is an integer greater than one, and capacitance values of the N first capacitances are substantially equal. The method includes selectively connecting a selected one of the second ends of the N first capacitances to a common node; selectively connecting others of the second ends to one of a voltage potential and a reference potential; and connecting a second DAC to the common node.

[0011] A pipelined analog-to-digital converter (ADC) comprises a first stage that receives an input voltage signal and that comprises an analog-to-digital converter (ADC) that includes an amplifier having an input and an output; N capacitances that are connected in parallel and that include first ends that selectively communicate with the input and second ends; N switches that selectively connect the second ends of the N capacitances to the voltage input during a first phase, one of the second ends of the N capacitances to the output of the amplifier during a second phase, and others of the second ends of the N capacitances to one of a voltage reference and a reference potential during the second phase. A second stage communicates with the output the amplifier.

[0012] In other features, the first phase is a sampling phase and the second phase is a residue amplification phase. When the input voltage is between zero and a first ratio of a first of the N capacitances divided by a sum of

the N capacitances, the first of the N capacitances is connected to the output of the amplifier and others of the N capacitances are connected to the reference potential during the second phase. When the input voltage is between the first ratio and a second ratio of a sum of the first and a second of the N capacitances divided by a sum of the N capacitances, the first of the N capacitances is connected to the voltage reference, the second of the N capacitances is connected to the output of the amplifier and others of the N capacitances are connected to the reference potential during the second phase. When the input voltage is between the second ratio and a third ratio of a sum of the first, the second and a third of the N capacitances divided by a sum of the N capacitances, the first and the second of the N capacitances are connected to the voltage reference, the third of the N capacitances is connected to the output of the amplifier and others of the N capacitances are connected to the reference potential during the second phase.

[0013] A pipelined analog-to-digital converter (ADC) comprises first stage means for receiving an input voltage signal and that comprises converting means for converting signals that includes: amplifying means for amplifying and having an input and an output; N capacitance means for providing capacitance, that are connected in parallel and that include first ends that selectively communicate with the input and second ends; and N switching means for selectively connecting the second ends of the N capacitance means to the voltage input during a first phase, one of the second ends of the N capacitance means to the output of the amplifier during a second phase, and others of the

second ends of the N capacitance means to one of a voltage reference and a reference potential during the second phase; and second stage means for communicating with the output of the amplifying means of the first stage means.

[0014] In other features, the first phase is a sampling phase and the second phase is a residue amplification phase. When the input voltage is between zero and a first ratio of a first of the N capacitances divided by a sum of the N capacitances, the N switching means connect the first of the N capacitances to the output of the amplifier and others of the N capacitances to the reference potential during the second phase. When the input voltage is between the first ratio and a second ratio of a sum of the first and a second of the N capacitances divided by a sum of the N capacitances, the N switching means connect the first of the N capacitances to the voltage reference, the second of the N capacitances to the output of the amplifier and others of the N capacitances to the reference potential during the second phase. When the input voltage is between the second ratio and a third ratio of a sum of the first, the second and a third of the N capacitances divided by a sum of the N capacitances, the N switching means connect the first and the second of the N capacitances to the voltage reference, the third of the N capacitances to the output of the amplifier and others of the N capacitances to the reference potential during the second phase.

[0015] A method for generating a residue voltage in a pipelined analog-to-digital converter (ADC) comprises providing first and second stages, wherein the first stage receives a voltage input and includes a capacitive ADC including N

capacitances; selectively connecting the second ends of the N capacitances to the voltage input during a first phase; selectively connecting one of the second ends of the N capacitances to the output of the amplifier during a second phase; selectively connecting others of the second ends of the N capacitances to one of a voltage reference and a reference potential during the second phase; selectively connecting the first ends of the N capacitances to an amplifier input; and connecting an amplifier output to the second stage.

[0016] In other features, the first phase is a sampling phase and the second phase is a residue amplification phase. The method further comprises selectively connecting the first of the N capacitances to the output of the amplifier and others of the N capacitances to the reference potential during the second phase when the input voltage is between zero and a first ratio of a first of the N capacitances divided by a sum of the N capacitances. The method further comprises selectively connecting the first of the N capacitances to the voltage reference, the second of the N capacitances to the output of the amplifier and others of the N capacitances to the reference potential during the second phase when the input voltage is between the first ratio and a second ratio of a sum of the first and a second of the N capacitances divided by a sum of the N capacitances. The method further comprises selectively connecting the first and the second of the N capacitances to the voltage reference, the third of the N capacitances to the output of the amplifier and others of the N capacitances to the reference potential during the second phase when the input voltage is

between the second ratio and a third ratio of a sum of the first, the second and a third of the N capacitances divided by a sum of the N capacitances.

[0017] A digital to analog converter (DAC) comprises X capacitive DACs that are connected in series and wherein X is an integer greater than one. Each of the X capacitive DACs comprise M switches wherein M is an integer greater than one; a signal input; a signal output; and M capacitances that communicate with the M switches, respectively, and that have first and second ends and substantially equal capacitance values. The M switches selectively connect the first ends of the M capacitances to the signal output. The M switches connect the second end of a selected one of the M capacitances to the signal input. A first DAC has a signal output that communicates with the signal input of one of the X capacitive DACs.

[0018] In other features, an amplifier has an input and an output. A feedback capacitance communicates with the input and the output of the amplifier. The first ends of the M capacitances of another one of the X DACs communicates with a reference potential during a first phase of the another one of the X DACs. The input of the amplifier selectively communicates with the first ends of the M capacitances of the another one of the X DACs during a second phase of the another one of the X DACs.

[0019] In other features, an amplifier has an input and an output. The first ends of the M capacitances of another one of the X DACs communicate with a reference potential during a first phase of the another one of the X DACs. The input of the amplifier selectively communicates with the first ends of the M

capacitances of the another one of the X DACs during a second phase of the another one of the X DACs. The second ends of the of the M capacitances of the another one of the X DACs communicate with the output of the amplifier during the second phase of the another one of the X DACs. The first DAC comprises Y resistive DACs wherein Y is an integer greater than zero.

[0020] In other features, at least one of the Y resistive DACs comprises a signal output; N resistances connected in series between the voltage reference and the reference potential; N nodes between select ones of the N resistances and the reference potential; and N second switches that selectively connect the signal output of the one of the Y resistive DACs to one of the N nodes. A control module selectively generates switching signals to control the X capacitive DACs and the first DAC.

[0021] In other features, a successive approximation analog-to-digital converter comprises the DAC. The successive approximation analog-to-digital converter of comprises an amplifier having an input that selectively communicates with one of the X capacitive DACs. A successive approximation module communicates with an output of the amplifier. A decoding module communicates with an output of the successive approximation module and selectively generates switching signals for the X capacitive DACs and the first DAC.

[0022] In other features, the first DAC comprises a capacitive DAC. The capacitive DAC comprises a signal output and an amplifier having an input and an output that communicates with the signal output. M second capacitances

are connected in parallel and have first ends and second ends. The first ends selectively communicate with a reference potential during a first phase of the capacitive DAC. The first ends selectively communicate with the input of the amplifier during a second phase of the capacitive DAC. M second switches selectively connect the second ends of the M second capacitances to one of the voltage reference and the reference potential during the first phase of the capacitive DAC and selectively connect the second ends of the M second capacitances to the output during the second phase of the capacitive DAC.

[0023] A digital to analog converter (DAC) comprises X capacitive converting means for converting a digital signal to an analog signal and that are connected together in series and wherein X is an integer greater than one. Each of the X capacitive converting means comprise M switching means for switching wherein M is an integer greater than one. M capacitance means for providing capacitance communicate with the M switching means, respectively, and have first and second ends and substantially equal capacitance values. The M switching means selectively connect the first ends of the M capacitance means to the signal output. The M switching means connect the second end of a selected one of the M capacitance means to the signal input. First converting means converts a digital signal to an analog signal and has a signal output that communicates with the signal input of one of the X capacitive converting means.

[0024] In other features, amplifying means for amplifying and has an input and an output. Feedback capacitance means provides capacitance and communicates with the input and the output of the amplifying means. The first

ends of the M capacitance means of another one of the X converting means communicates with a reference potential during a first phase of the another one of the X converting means. The input of the amplifying means selectively communicates with the first ends of the M capacitance means of the another one of the X converting means during a second phase of the another one of the X converting means.

[0025] In other features, amplifying means for amplifying has an input and an output. The first ends of the M capacitance means of another one of the X converting means communicates with a reference potential during a first phase of the another one of the X converting means. The input of the amplifying means selectively communicates with the first ends of the M capacitance means of the another one of the X converting means during a second phase of the another one of the X converting means. The second ends of the M capacitance means of the another one of the X converting means communicate with the output of the amplifying means during the second phase of the another one of the X converting means. The first DAC comprises Y resistive converting means for converting a digital signal to an analog signal and wherein Y is an integer greater than zero.

[0026] In other features, at least one of the Y resistive converting means comprises a signal output and N resistance means for providing resistance and that is connected in series between the voltage reference and the reference potential. N nodes are located between select ones of the N resistance means and the reference potential. N second switching means

selectively connect the signal output of the one of the Y resistive converting means to one of the N nodes. Control means selectively generates switching signals to control the X capacitive converting means and the first DAC.

[0027] In other features, a successive approximation analog-to-digital converter comprises the DAC. The successive approximation analog-to-digital converter comprises amplifying means for amplifying and having an input that selectively communicates with one of the X capacitive DACs and approximation means for successive approximating and that communicates with an output of the amplifying means. Decoding means communicates with an output of the successive approximation module for selectively generating switching signals for the X capacitive DACs and the first DAC.

[0028] In other features, the first DAC comprises a capacitive converting means for converting a digital signal to an analog signal. The capacitive converting means comprises a signal output and amplifying means for amplifying and having an input and an output that communicates with the signal output. M second capacitance means provides capacitance and is connected in parallel and has first ends and second ends. The first ends selectively communicate with a reference potential during a first phase of the capacitive DAC. The first ends selectively communicate with the input of the amplifying means during a second phase of the capacitive DAC. M second switching means selectively connect the second ends of the M second capacitance means to one of the voltage reference and the reference potential during the first phase

of the capacitive DAC and selectively connect the second ends of the M second capacitance means to the output during the second phase of the capacitive DAC.

[0029] A method for operating a digital to analog converter (DAC) comprises connecting X capacitive DACs in series and wherein X is an integer greater than one, wherein each of the X capacitive DACs comprise M capacitances that have first and second ends and substantially equal capacitance values; selectively connecting the first ends of the M capacitances to the signal output; connecting the second end of a selected one of the M capacitances to the signal input; and connecting a signal output of a first DAC to the signal input of one of the X capacitive DACs.

[0030] In other features, the method comprises providing an amplifier having an input and an output and a feedback capacitance that communicates with the input and the output of the amplifier. The method comprises connecting the first ends of the M capacitances of another one of the X DACs with a reference potential during a first phase of the another one of the X DACs. The method comprises selectively connecting the input of the amplifier to the first ends of the M capacitances of the another one of the X DACs during a second phase of the another one of the X DACs.

[0031] In other features, the method comprises providing an amplifier having an input and an output; selectively connecting the first ends of the M capacitances of another one of the X DACs with a reference potential during a first phase of the another one of the X DACs; selectively connecting the input of the amplifier with the first ends of the M capacitances of the another one of the X

DACs during a second phase of the another one of the X DACs; and selectively connecting the second ends of the of the M capacitances of the another one of the X DACs communicate with the output of the amplifier during the second phase of the another one of the X DACs.

[0032] In other features, the first DAC comprises Y resistive DACs wherein Y is an integer greater than zero. The method comprises selectively generating switching signals to control the X capacitive DACs and the first DAC. The method comprises using the X capacitive DACs to successively approximate an analog input signal. The first DAC comprises a capacitive DAC.

[0033] Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred embodiment of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

[0035] FIG. 1A is an electrical schematic of a binary capacitor array D/A converter according to the prior art;

[0036] FIG. 1B is a graph of a D/A converter;

[0037] FIG. 2 is an electrical schematic of a linear capacitor array D/A converter according to a prior art;

[0038] FIGs. 3A-3C are electrical schematics of a capacitive-resistive D/A converter in exemplary configurations;

[0039] FIG. 4A illustrates the D/A converter of FIG. 3B during a sampling phase for a first digital value;

[0040] FIG. 4B illustrates the D/A converter of FIG. 3B during an integrating phase for a first digital value;

[0041] FIG. 4C is an exemplary truth table for the circuit of FIG. 3B;

[0042] FIG. 4D is an exemplary truth table for the circuit of FIG. 3C;

[0043] FIG. 5 illustrates the D/A converter of FIG. 3B during a sampling phase for a second digital value;

[0044] FIG. 6 illustrates the D/A converter of FIG. 3B during a sampling phase for a third digital value;

[0045] FIG. 7 illustrates the D/A converter of FIG. 3B during a sampling phase for a fourth digital value;

[0046] FIG. 8A is an electrical schematic of a capacitive-capacitive D/A converter;

[0047] FIG. 8B is an electrical schematic of a capacitive-capacitive D/A converter in a sample and integrate configuration;

[0048] FIG. 8C illustrates the D/A converter of FIG. 8B during a sampling phase for a first digital value;

[0049] FIG. 8D illustrates the D/A converter of FIG. 8B during an integrating phase for a first digital value;

[0050] FIG. 8E illustrates the D/A converter of FIG. 8B during a sampling phase for a second digital value;

[0051] FIG. 8F illustrates the D/A converter of FIG. 8B during a sampling phase for a third digital value;

[0052] FIG. 8G illustrates the D/A converter of FIG. 8B during a sampling phase for a fourth digital value;

[0053] FIG. 8H is an exemplary timing diagram showing sampling and integrating phases for LSB and MSB portions;

[0054] FIG. 8I is an exemplary timing diagram showing sampling and integrating phases for LSB and MSB portions;

[0055] FIG. 8J is an exemplary truth table for the D/A converter of FIG. 8B;

[0056] FIG. 9A illustrates an N-stage capacitive D/A converter;

[0057] FIG. 9B illustrates an N-stage capacitive-resistive D/A converter;

[0058] FIG. 9C is an exemplary timing diagram showing non-overlapping sampling and integrating phases for additional stages;

[0059] FIG. 9D is an exemplary timing diagram showing overlapping sampling and integrating phases for additional stages;

[0060] FIG. 10 is an electrical schematic of a successive approximation A/D converter according to the present invention;

[0061] FIG. 11A is an electrical schematic of a pipelined A/D converter according to the present invention;

[0062] FIG. 11B-11D illustrate ideal and non-ideal residue voltages;

[0063] FIG. 12A illustrates an A/D converter that generates an ideal residue voltage according to the present invention;

[0064] FIG. 12B illustrates the A/D converter of FIG. 12A in a sampling phase;

[0065] FIG. 12C illustrates the A/D converter of FIG. 12A in a residue amplification stage for a first voltage input value;

[0066] FIG. 12D is an exemplary truth table for the A/D converter of FIG. 12A;

[0067] FIG. 13 illustrates the A/D converter of FIG. 12A in a residue amplification stage for a second voltage input value;

[0068] FIG. 14 illustrates the A/D converter of FIG. 12A in a residue amplification stage for a third voltage input value;

[0069] FIG. 15 illustrates the A/D converter of FIG. 12A in a residue amplification stage for a fourth voltage input value;

[0070] FIG. 16 is a graph illustrating variable interstage gain and an ideal residue voltage of the circuit of FIG. 12A;

[0071] FIG. 17A is a functional block diagram of a hard disk drive;

[0072] FIG. 17B is a functional block diagram of a digital versatile disk (DVD);

[0073] FIG. 17C is a functional block diagram of a high definition television;

[0074] FIG. 17D is a functional block diagram of a vehicle control system;

[0075] FIG. 17E is a functional block diagram of a cellular phone;

[0076] FIG. 17F is a functional block diagram of a set top box; and

[0077] FIG. 17G is a functional block diagram of a media player.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0078] The following description of the preferred embodiment(s) is merely exemplary in nature and is in no way intended to limit the invention, its application, or uses. For purposes of clarity, the same reference numbers will be used in the drawings to identify similar elements. As used herein, the term module, circuit and/or device refers to an Application Specific Integrated Circuit (ASIC), an electronic circuit, a processor (shared, dedicated, or group) and memory that execute one or more software or firmware programs, a combinational logic circuit, and/or other suitable components that provide the described functionality. As used herein, the phrase at least one of A, B, and C should be construed to mean a logical (A or B or C), using a non-exclusive logical or. It should be understood that steps within a method may be executed in different order without altering the principles of the present invention.

[0079] Referring now to FIG. 3A and 3B, capacitive-resistive D/A converters 100, 100-1 and 100-2 are shown. For simplicity, an N=4 bit example is shown in FIGs. 3A-3C. Skilled artisans will appreciate that N can be set to

other numbers of bits. Various types of output circuits 102 may be used. Additional connections 104, which may or may not be switched connections, may be used depending upon the function that is desired. For example in FIG. 3B, the DAC 100-1 is shown in a sample and integrate configuration and in FIG. 3C, a DAC 100-2 is shown with a sample and hold configuration.

[0080] In this example, the two most significant bits (MSBs) are allocated to a capacitive portion 110 and the two least significant bits (LSBs) are allocated to a resistive portion 120. In the Figures that follow, the capacitor C_i will be shown with dotted lines to indicate both sample and hold and sample and integrate configurations.

[0081] The capacitive portion 110 includes capacitors C_1 , C_2 , C_3 and C_4 . In the preferred embodiment, the capacitors C_1 , C_2 , C_3 and C_4 have a substantially equal capacitance value. The capacitors may have substantially the same capacitance value, in other words $C_1 = C_2 = C_3 = C_4$. As will be described further below, the capacitors are selectively switched by switches SW_{4MSB} , SW_{3MSB} , SW_{2MSB} , and SW_{1MSB} (collectively switches SW_M) between a voltage reference V_{ref} , a reference potential such as ground, and a common node 130 between the resistive portion 120 and the capacitive portion 110.

[0082] The resistive portion 110 includes resistors R_1 , R_2 , R_3 and R_4 . In the preferred embodiment, the resistors R_1 , R_2 , R_3 and R_4 have a substantially equal resistance value. The resistors may have the same resistance value, in other words $R_1 = R_2 = R_3 = R_4$. As will be described further below, the resistors are connected in series between V_{ref} and a reference potential such as ground.

A node between the resistors is selected by switches SW_{4LSB} , SW_{3LSB} , SW_{2LSB} , and SW_{1LSB} (collectively switches SW_L) and connected to the common node 130 to create a voltage divider.

[0083] The sample and integrate circuit was described above. In the sample and hold configuration, the second ends of the capacitances C_1 , C_2 , C_3 and C_4 are switched to the output of the amplifier during the second phase of the capacitive portion 110. The feedback capacitance C_f may be omitted.

[0084] Referring now to FIG. 4A, the D/A converter of FIG. 3B is shown during a sampling phase for a first digital value (0011). Initially, the switch 16 is closed, the switch 18 is opened and the capacitors C_2 , C_3 and C_4 are switched by respective switches to the reference potential, which may be ground. The capacitor C_1 is connected to the common node. The capacitive portion 110 will be in this configuration when the desired binary value is between 0000 and 0011. One of the resistive switches SW_{4LSB} , SW_{3LSB} , SW_{2LSB} , and SW_{1LSB} is closed to create a voltage divider. In the example shown in FIG. 4A, the switch SW_{4LSB} is closed to provide $\frac{3}{4}V_{ref}$. A charge is accumulated on the capacitor C_1 that is equal to $V_{RDAC}C_1$, where V_{RDAC} is the voltage provided by the resistive portion 120.

[0085] Referring now to FIG. 4B, the D/A converter of FIG. 3B is shown during an integrating phase for the first digital value (0011). In this phase, the switch 16 is opened, the switch 18 is closed and the voltage value is applied to the amplifier 20. Using a charge equalization approach, the total charge before changing the position of the switches 16 and 18 is equal to the total charge after changing the position of the switches 16 and 18:

$$Q_T = VC_f = V_{RDAC}C_1;$$

$$V = V_{RDAC} \frac{C_1}{C_f}.$$

The value of C_f can be set equal to C_1 , C_2 , C_3 and C_4 or be used to scale the output voltage and not be equal to C_1 , C_2 , C_3 and C_4 . In the example above,

$V_{RDAC} = \frac{3}{4}V_{ref}$. As can be appreciated, the value can also be adjusted to

$V_{RDAC} = 0, V_{RDAC} = \frac{1}{4}V_{ref}$, or $V_{RDAC} = \frac{1}{2}V_{ref}$ by selecting the switch SW_{1LSB} , SW_{2LSB} or

SW_{3LSB} , respectively. Scaling can be performed by adjusting the value of C_f relative to C_1 , C_2 , C_3 and C_4 . For example, if $C_f = C_1 + C_2 + C_3 + C_4$, then the output ranges 0 to near V_{ref} rather than 0 to near 4 V_{ref} in this example.

[0086] Referring now to FIG. 4C, a truth table for the exemplary converter of FIG. 3B is shown. In this example, C_f is equal to C_1 , C_2 , C_3 and C_4 although other values may be used for scaling. Referring now to FIG. 4D, a truth table for the exemplary converter of FIG. 3C is shown.

[0087] Referring now to FIG. 5, the D/A converter of FIG. 3B is shown during an integrating phase for a second digital value (0111). Initially, the switch 16 is closed, the switch 18 is opened and the capacitors C_3 and C_4 are switched by respective switches to the reference potential, which may be ground. The capacitor C_2 is connected to the common node 130 and the capacitor C_1 is connected to V_{ref} . The capacitive portion 110 will be in this configuration when the desired binary value is between 0100 and 0111. One of the resistive switches SW_{4LSB} , SW_{3LSB} , SW_{2LSB} , and SW_{1LSB} is closed to create a voltage divider. In the example shown in FIG. 5, the switch SW_{4LSB} is closed to provide

$\frac{3}{4}V_{ref}$. A charge is accumulated on the capacitor C_2 that is equal to $V_{RDAC}C_2$, where V_{RDAC} is the voltage provided by the resistive portion. A charge is also accumulated on capacitor C_1 equal to $V_{ref}C_1$.

[0088] During an integrating phase for the second digital value (0111). the switch 16 is opened, the switch 18 is closed and the voltage value is applied to the amplifier 20. Using a charge equalization approach, the total charge before changing the position of the switches 16 and 18 is equal to the total charge after changing the position of the switches 16 and 18:

$$Q_T = VC_f = V_{RDAC}C_2 + V_{ref}C_1;$$

$$V = V_{RDAC} \frac{C_2}{C_f} + V_{ref} \frac{C_1}{C_f}.$$

The value of C_f can be set equal to C_1 , C_2 , C_3 and C_4 or be used to scale the output voltage and not be equal to C_1 , C_2 , C_3 and C_4 . If C_f , C_1 and C_2 are the same, $V = V_{RDAC} + V_{ref}$.

[0089] Referring now to FIG. 6, the D/A converter of FIG. 3B is shown during an integrating phase for a third digital value (1011). Initially, the switch 16 is closed, the switch 18 is opened and the capacitor C_4 is switched by a respective switch to the reference potential, which may be ground. The capacitor C_3 is connected to the common node 130 and the capacitors C_1 and C_2 are connected to V_{ref} . The capacitive portion 110 will be in this configuration when the desired binary value is between 1000 and 1011. One of the resistive switches SW_{4LSB} , SW_{3LSB} , SW_{2LSB} , and SW_{1LSB} is closed to create a voltage divider. In the example shown in FIG. 6, the switch SW_{4LSB} is closed to provide

$\frac{3}{4}V_{ref}$. A charge is accumulated on the capacitor C_3 that is equal to $V_{RDAC}C_3$, where V_{RDAC} is the voltage provided by the resistive portion. A charge is also accumulated on capacitors C_1 and C_2 that is equal to $V_{ref}(C_1 + C_2)$.

[0090] During an integrating phase for the third digital value (1011), the switch 16 is opened, the switch 18 is closed and the voltage value is applied to the amplifier 20. Using a charge equalization approach, the total charge before changing the position of the switches 16 and 18 is equal to the total charge after changing the position of the switches 16 and 18:

$$Q_T = VC_f = V_{RDAC}C_3 + V_{ref}(C_1 + C_2);$$

$$V = V_{RDAC} \frac{C_3}{C_f} + V_{ref} \frac{C_1 + C_2}{C_f}.$$

The value of C_f can be set equal to C_1 , C_2 , C_3 and C_4 or be used to scale the output voltage and not be equal to C_1 , C_2 , C_3 and C_4 . If C_f , C_1 , C_2 and C_3 are the same, $V = V_{RDAC} + 2V_{ref}$.

[0091] Referring now to FIG. 7, the D/A converter of FIG. 3B is shown during an integrating phase for a third digital value (1111). Initially, the switch 16 is closed and the switch 18 is opened. The capacitor C_4 is connected to the common node 130 and the capacitors C_1 , C_2 and C_3 are connected to V_{ref} . The capacitive portion 110 will be in this configuration when the desired binary value is between 1100 and 1111. One of the resistive switches SW_{4LSB} , SW_{3LSB} , SW_{2LSB} , and SW_{1LSB} is closed to create a voltage divider. In the example shown in FIG. 7, the switch SW_{4LSB} is closed to provide $\frac{3}{4}V_{ref}$. A charge is accumulated

on the capacitor C_4 that is equal to $V_{RDAC}C_4$, where V_{RDAC} is the voltage provided by the resistive portion. A charge is accumulated on capacitors C_1 , C_2 and C_3 that is equal to $V_{ref}(C_1 + C_2 + C_3)$.

[0092] During an integrating phase for the fourth digital value (1111), the switch 16 is opened, the switch 18 is closed and the voltage value is applied to the amplifier 20. Using a charge equalization approach, the total charge before changing the position of the switches 16 and 18 is equal to the total charge after changing the position of the switches 16 and 18:

$$Q_T = VC_f = V_{RDAC}C_4 + V_{ref}(C_1 + C_2 + C_3);$$

$$V = V_{RDAC} \frac{C_4}{C_f} + V_{ref} \frac{C_1 + C_2 + C_3}{C_f}.$$

The value of C_f can be set equal to C_1 , C_2 , C_3 and C_4 or be used to scale the output voltage and not be equal to C_1 , C_2 , C_3 and C_4 . If C_f , C_1 , C_2 , C_3 and C_4 are the same, $V = V_{RDAC} + 3V_{ref}$.

[0093] Referring now to FIG. 8A and 8B, a nested segmented capacitive-capacitive D/A converter 108 according to the present invention is shown. In FIG. 8A, the output circuit 102 is shown. In FIG. 8B, an exemplary sample and integrate configuration is shown. The capacitive portion 110 operates as described above. For purposes of clarity, the capacitors C_1 , C_2 , C_3 and C_4 have been relabeled C_{1M} , C_{2M} , C_{3M} and C_{4M} . A second capacitive portion 150 is associated with the two least significant bits and includes capacitors C_{1L} , C_{2L} , C_{3L} and C_{4L} . The voltage provided by the LSB capacitive portion 150 is

V_{CDAC} . The second capacitive portion 150 also has a sampling and integrating phase as will be described below.

[0094] Referring now to FIGs. 8C and 8D, an equivalent circuit of the D/A converter of FIG. 8B during a sampling phase is shown for $V_{CDAC} = \frac{V_{ref}}{4}$.

During sampling phase, the switch 152 is closed and the capacitors C_{4L} , C_{3L} and C_{2L} are connected to a reference potential such as ground. The capacitor C_{1L} is charged to V_{ref} . A charge is accumulated on the capacitor C_{1L} that is equal to $V_{ref}C_{1L}$.

[0095] During the integrating phase, the switch 152 is opened and the capacitors C_{4L} , C_{3L} , C_{2L} and C_{1L} are connected in feedback. The total charge before the switch 152 is opened is the same as the total charge after the switch 152 is opened. Therefore:

$$Q_T = VC_T = V_{ref}C_{1L} = V(C_{1L} + C_{2L} + C_{3L} + C_{4L});$$

$$V = V_{ref} \frac{C_{1L}}{C_{1L} + C_{2L} + C_{3L} + C_{4L}}.$$

Assuming that C_{1L} , C_{2L} , C_{3L} and C_{4L} are equal, $V = \frac{V_{ref}}{4}$.

[0096] Referring now to FIG. 8E, an equivalent circuit of the D/A converter of FIG. 8B during a sampling phase is shown for $V_{CDAC} = \frac{V_{ref}}{2}$. During sampling phase, the switch 152 is closed and the capacitors C_{4L} and C_{3L} are connected to a reference potential such as ground. The capacitors C_{1L} and C_{2L} are charged to V_{ref} . A charge is accumulated on the capacitors C_{1L} and C_{2L} that is equal to $V_{ref}(C_{1L} + C_{2L})$.

[0097] During the integrating phase, the switch 152 is opened and the capacitors C_{4L} , C_{3L} , C_{2L} and C_{1L} are connected in feedback. The total charge before the switch 152 is opened is the same as the total charge after the switch 152 is opened. Therefore:

$$Q_T = VC_T = V_{ref}(C_{1L} + C_{2L}) = V(C_{1L} + C_{2L} + C_{3L} + C_{4L});$$

$$V = V_{ref} \frac{C_{1L} + C_{2L}}{(C_{1L} + C_{2L} + C_{3L} + C_{4L})}.$$

Assuming that C_1 , C_2 , C_3 and C_4 are equal, $V = \frac{V_{ref}}{2}$.

[0098] Referring now to FIG. 8F, an equivalent circuit of the D/A converter of FIG. 8B during a sampling phase is shown for $V_{CDAC} = \frac{3V_{ref}}{4}$. During sampling phase, the switch 152 is closed and the capacitor C_{4L} is connected to a reference potential such as ground. The capacitors C_{1L} , C_{2L} and C_{3L} are charged to V_{ref} . A charge is accumulated on the capacitors C_{1L} , C_{2L} and C_{3L} that is equal to $V_{ref}(C_{1L} + C_{2L} + C_{3L})$.

[0099] During the integrating phase, the switch 152 is opened and the capacitors C_{4L} , C_{3L} , C_{2L} and C_{1L} are connected in feedback. The total charge before the switch 152 is opened is the same as the total charge after the switch 152 is opened. Therefore:

$$Q_T = VC_T = V_{ref}(C_{1L} + C_{2L} + C_{3L}) = V(C_{1L} + C_{2L} + C_{3L} + C_{4L});$$

$$V = V_{ref} \frac{C_{1L} + C_{2L} + C_{3L}}{(C_{1L} + C_{2L} + C_{3L} + C_{4L})}.$$

Assuming that C_{1L} , C_{2L} , C_{3L} and C_{4L} are equal, $V = \frac{3V_{ref}}{4}$.

[0100] Referring now to FIG. 8G, an equivalent circuit of the D/A converter of FIG. 8B during a sampling phase is shown for $V_{CDAC} = V_{ref}$. The switch associated with this position may be omitted since this value can be already be obtained by using the next MSB. In this case one of the capacitors may always be connected to ground. If a switch is used, during sampling phase the switch 152 is closed and the capacitors C_{1L} , C_{2L} , C_{3L} and C_{4L} are charged to V_{ref} . A charge is accumulated on the capacitors C_{1L} , C_{2L} , C_{3L} and C_{4L} that is equal to $V_{ref}(C_{1L} + C_{2L} + C_{3L} + C_{4L})$.

[0101] During the integrating phase, the switch 152 is opened and the capacitors C_{4L} , C_{3L} , C_{2L} and C_{1L} are connected in feedback. The total charge before the switch 152 is opened is the same as the total charge after the switch 152 is opened. Therefore:

$$Q_T = VC_T = V_{ref}(C_{1L} + C_{2L} + C_{3L} + C_{4L}) = V(C_{1L} + C_{2L} + C_{3L} + C_{4L});$$

$$V = V_{ref} \frac{C_{1L} + C_{2L} + C_{3L} + C_{4L}}{(C_{1L} + C_{2L} + C_{3L} + C_{4L})}.$$

[0102] Assuming that C_{1L} , C_{2L} , C_{3L} and C_{4L} are equal, $V = V_{ref}$.

[0103] Referring now to FIGs. 8H and 8I, non-overlapping and overlapping timing diagrams are shown for sampling and integrating phases for LSB and MSB capacitive portions. The timing of the sampling and integrating phases can be non-overlapping as shown in FIG. 8H. Alternately, the sampling phase of the LSB capacitive portion can fully and/or partially overlap the integrating phase of the MSB capacitive portion as shown in FIG. 8I.

[0104] Referring now to FIG. 8J, a truth table for the D/A converter is shown. As can be appreciated, the LSB switches can be connected in feedback and/or to ground during the MSB-integrating phase and/or can begin the next LSB sampling phase as described herein.

[0105] Referring now to FIG. 9A-9D, additional capacitive and/or resistive DAC portions may be added. In FIG. 9A, an N stage capacitive D/A converter 170 is shown. The converter 170 includes capacitive portions BG_1 , BG_2 , ..., and BG_x , which are associated with LSB, next LSB, ..., and MSB groups. For example, a 6 bit example can include capacitive portions BG_1 , BG_2 and BG_3 . Each capacitive portion may include four capacitors as shown and described above. Each of the capacitive portions includes sampling and integrating stages that may be non-overlapping and/or overlapping as described above and below.

[0106] In FIG. 9B, an N stage capacitive-resistive D/A converter 180 is shown. One or more of the last stages is a resistive portion as described above. In this example, there are X-Y capacitive portions and Y resistive portions, where X and Y are integers greater than zero. When resistive portions are used, the sampling and integrating phases for the last capacitive stage and the final resistive stage can be the same as described above. In FIG. 9C, an exemplary timing diagram shows non-overlapping sampling and integrating phases for additional capacitive stages. In FIG. 9D, an exemplary timing diagram showing fully and/or partially overlapping sampling and integrating phases for additional capacitive stages is shown.

[0107] Referring now to FIG. 10, a successive approximation A/D converter 200 is shown. The converter 200 includes a successive approximation register (SAR) 204 or module that contains logic for resolving the digital bits as will be described further below. An output of the SAR 204 is input to decoder module 209 that may include a modified thermometer decoder 210 that communicates with and controls switches SW_{4MSB} , SW_{3MSB} , SW_{2MSB} , and SW_{1MSB} based on MSBs of the output of the SAR. An output of the SAR 204 is input to a thermometer decoder 220 that communicates with and controls switches SW_{4LSB} , SW_{3LSB} , SW_{2LSB} , and SW_{1LSB} based on LSBs in the output of the SAR 204.

[0108] During acquisition, the switch 16 is connected to ground. Ends of the capacitors are connected by switches SW_{MSB} to V_{in} . After acquisition of V_{in} , the switch 16 is opened and the capacitors are disconnected by switches SW_{MSB} from V_{in} . The capacitor array is charged with a voltage based on V_{in} . The capacitors are then connected to ground by switches SW_{MSB} , which drives the common terminal negative to a voltage equal to $-V_{in}$.

[0109] As the first step in a binary search algorithm, the capacitive and resistive portions are configured to provide $1/2V_{ref}$ as described above. In other words, C_{4M} is connected to the common node, C_{3M} , C_{2M} and C_{1M} are connected to V_{ref} and the switch SW_{1LSB} is closed. For example, if V_{in} is equal to $3/4V_{ref}$, the common terminal will be driven to $(-3/4V_{ref} + 1/2V_{ref}) = -1/4V_{ref}$. When this voltage is compared to ground, the output of the comparator 20 yields a logic '1', implying that V_{in} is greater than $1/2V_{ref}$. If V_{in} is equal to $1/4V_{ref}$, the common terminal voltage is $(-1/4V_{ref} + 1/2V_{ref}) = +1/4V_{ref}$, and the output of the comparator

20 is a logic '0'. This process continues with the next MSB or LSB depending upon the value of the comparator output until all bits are resolved. While capacitive-resistive implementation is shown, capacitive-capacitive, N-stage capacitive or N-stage capacitive-resistive implementations are also contemplated.

[0110] Referring now to FIG. 11A, a pipelined A/D converter 250 is shown. The converter 250 includes a plurality of stages 252-1, 252-2, 252-3 (collectively 252) that are cascaded in series. Each of the coarse A/D converter stages 252 includes a sample and hold module 254 that samples and holds the analog output signal from a prior stage, a low resolution A/D subconverter module 256 that converts the held analog signal, a low-resolution D/A subconverter module 258 that converts the resulting digital output back into an analog representation, a difference module 260 and an analog interstage difference amplifier module 262 that amplifies the residue. The residue is the difference between the held analog signal and the reconstructed analog signal.

[0111] The first stage 252-1 of the pipelined A/D converter 250 operates on a most current analog input sample while the second stage 252-2 operates on the amplified residue of the previous input sample. The concurrency of operations results in a conversion speed that is determined only by the time it takes in one stage.

[0112] Referring now to FIG. 11B-11D, ideal and non-ideal residue voltages are shown. In FIG. 11B, an ideal residue voltage is shown. When the input reaches a first decision level of the A/D subconverter module 252, the

output of the subconverter module switches to its next higher level code causing the output of the D/A subconverter to switch to its next higher level. This in turn causes the amplified residue to drop back to zero.

[0113] In actual implementations, however, the components are not ideal and non-uniformity occurs. In FIG. 11C, the residue voltage exceeds the ideal value by a fixed amount. In FIG. 11D, the residue voltage exceeds the ideal residue voltage by a variable amount.

[0114] Referring now to FIG. 12A, an analog to digital converter 300 that generates a residue voltage with lower variation according to the present invention is shown. Capacitors C_1 , C_2 , C_3 and C_4 are selectively connected to V_{in} , a reference potential such as ground, a voltage reference (V_{ref}) and to an output of the opamp 20. In some implementations, C_1 , C_2 , C_3 and C_4 have substantially equal capacitance values.

[0115] Referring now to FIGs. 12B-12D, the analog to digital converter of FIG. 12A is shown further. In a sampling phase in FIG. 12B, the switch 16 is closed and the capacitors are connected to V_{in} . In a residue amplification stage in FIG. 12B for V_{in} between 0 and $\frac{C_1}{C_1 + C_2 + C_3 + C_4} V_{ref}$ ("A" in FIG. 12D), the switch 16 is opened, the capacitor C_1 is connected in feedback arrangement. The capacitors C_2 , C_3 , and C_4 are connected to the reference potential. A truth table is shown in FIG. 12D.

[0116] Referring now to FIG. 13, in a residue amplification stage for V_{in} between $\frac{C_1}{C_1 + C_2 + C_3 + C_4} V_{ref}$ and $\frac{C_1 + C_2}{C_1 + C_2 + C_3 + C_4} V_{ref}$ ("B" in FIG. 12D), the switch

16 is opened, the capacitor C_2 is connected in feedback arrangement and the capacitor C_1 is connected to V_{ref} . The capacitors C_3 and C_4 are connected to a reference potential.

[0117] Referring now to FIG. 14, in a residue amplification stage for V_{in} between $\frac{C_1 + C_2}{C_1 + C_2 + C_3 + C_4} V_{ref}$ and $\frac{C_1 + C_2 + C_3}{C_1 + C_2 + C_3 + C_4} V_{ref}$ ("C" in FIG. 12D), the switch 16 is opened, the capacitor C_3 is connected in feedback arrangement and the capacitors C_1 and C_2 are connected to V_{ref} . The capacitor C_4 is connected to a reference potential.

[0118] Referring now to FIGs. 15 and 16, in a residue amplification stage for V_{in} between $\frac{C_1 + C_2 + C_3}{C_1 + C_2 + C_3 + C_4} V_{ref}$ and V_{ref} ("D" in FIG. 12D), the switch 16 is opened, the capacitor C_4 is connected in feedback arrangement and the capacitors C_1 , C_2 and C_3 are connected to V_{ref} . Note that because the different capacitors are used as the feedback capacitor during residue amplification, the residue gain can perfectly track the capacitor mismatch. The residue voltage now looks as shown in FIG. 16. There is a variable inter-stage gain and a substantially constant maximum residue voltage.

[0119] Referring now to FIGs. 17A-17G, various exemplary implementations of the present invention are shown. Referring now to FIG. 17A, the present invention can be implemented in D/A or A/D converters in a hard disk drive 400. In some implementations, the signal processing and/or control circuit 402 and/or other circuits (not shown) in the HDD 400 may process data, perform

coding and/or encryption, perform calculations, and/or format data that is output to and/or received from a magnetic storage medium 406.

[0120] The HDD 400 may communicate with a host device (not shown) such as a computer, mobile computing devices such as personal digital assistants, cellular phones, media or MP3 players and the like, and/or other devices via one or more wired or wireless communication links 408. The HDD 400 may be connected to memory 409 such as random access memory (RAM), low latency nonvolatile memory such as flash memory, read only memory (ROM) and/or other suitable electronic data storage.

[0121] Referring now to FIG. 17B, the present invention can be implemented in D/A or A/D converters in a digital versatile disc (DVD) drive 410. The signal processing and/or control circuit 412 and/or other circuits (not shown) in the DVD 410 may process data, perform coding and/or encryption, perform calculations, and/or format data that is read from and/or data written to an optical storage medium 416. In some implementations, the signal processing and/or control circuit 412 and/or other circuits (not shown) in the DVD 410 can also perform other functions such as encoding and/or decoding and/or any other signal processing functions associated with a DVD drive.

[0122] The DVD drive 410 may communicate with an output device (not shown) such as a computer, television or other device via one or more wired or wireless communication links 417. The DVD 410 may communicate with mass data storage 418 that stores data in a nonvolatile manner. The mass data storage 418 may include a hard disk drive (HDD). The HDD may have the

configuration shown in FIG. 17A. The HDD may be a mini HDD that includes one or more platters having a diameter that is smaller than approximately 1.8". The DVD 410 may be connected to memory 419 such as RAM, ROM, low latency nonvolatile memory such as flash memory and/or other suitable electronic data storage.

[0123] Referring now to FIG. 17C, the present invention can be implemented in D/A or A/D converters in a high definition television (HDTV) 420. The HDTV 420 receives HDTV input signals in either a wired or wireless format and generates HDTV output signals for a display 426. In some implementations, signal processing circuit and/or control circuit 422 and/or other circuits (not shown) of the HDTV 420 may process data, perform coding and/or encryption, perform calculations, format data and/or perform any other type of HDTV processing that may be required.

[0124] The HDTV 420 may communicate with mass data storage 427 that stores data in a nonvolatile manner such as optical and/or magnetic storage devices. At least one HDD may have the configuration shown in FIG. 17A and/or at least one DVD may have the configuration shown in FIG. 17B. The HDD may be a mini HDD that includes one or more platters having a diameter that is smaller than approximately 1.8". The HDTV 420 may be connected to memory 428 such as RAM, ROM, low latency nonvolatile memory such as flash memory and/or other suitable electronic data storage. The HDTV 420 also may support connections with a WLAN via a WLAN network interface 429.

[0125] Referring now to FIG. 17D, the present invention may implement and/or be implemented in D/A or A/D converters in a control system of a vehicle 430, a WLAN interface, mass data storage of the vehicle control system and/or a power supply 433. In some implementations, the present invention implement a powertrain control system 432 that receives inputs from one or more sensors such as temperature sensors, pressure sensors, rotational sensors, airflow sensors and/or any other suitable sensors and/or that generates one or more output control signals such as engine operating parameters, transmission operating parameters, and/or other control signals.

[0126] The present invention may also be implemented in other control systems 440 of the vehicle 430. The control system 440 may likewise receive signals from input sensors 442 and/or output control signals to one or more output devices 444. In some implementations, the control system 440 may be part of an anti-lock braking system (ABS), a navigation system, a telematics system, a vehicle telematics system, a lane departure system, an adaptive cruise control system, a vehicle entertainment system such as a stereo, DVD, compact disc and the like. Still other implementations are contemplated.

[0127] The powertrain control system 432 may communicate with mass data storage 446 that stores data in a nonvolatile manner. The mass data storage 446 may include optical and/or magnetic storage devices for example hard disk drives HDD and/or DVDs. At least one HDD may have the configuration shown in FIG. 17A and/or at least one DVD may have the configuration shown in FIG. 17B. The HDD may be a mini HDD that includes

one or more platters having a diameter that is smaller than approximately 1.8". The powertrain control system 432 may be connected to memory 447 such as RAM, ROM, low latency nonvolatile memory such as flash memory and/or other suitable electronic data storage. The powertrain control system 432 also may support connections with a WLAN via a WLAN network interface 448. The control system 440 may also include mass data storage, memory and/or a WLAN interface (all not shown).

[0128] Referring now to FIG. 17E, the present invention can be implemented in D/A or A/D converters in a cellular phone 450 that may include a cellular antenna 451. In some implementations, the cellular phone 450 includes a microphone 456, an audio output 458 such as a speaker and/or audio output jack, a display 460 and/or an input device 462 such as a keypad, pointing device, voice actuation and/or other input device. The signal processing and/or control circuits 452 and/or other circuits (not shown) in the cellular phone 450 may process data, perform coding and/or encryption, perform calculations, format data and/or perform other cellular phone functions.

[0129] The cellular phone 450 may communicate with mass data storage 464 that stores data in a nonvolatile manner such as optical and/or magnetic storage devices for example hard disk drives HDD and/or DVDs. At least one HDD may have the configuration shown in FIG. 17A and/or at least one DVD may have the configuration shown in FIG. 17B. The HDD may be a mini HDD that includes one or more platters having a diameter that is smaller than approximately 1.8". The cellular phone 450 may be connected to memory 466

such as RAM, ROM, low latency nonvolatile memory such as flash memory and/or other suitable electronic data storage. The cellular phone 450 also may support connections with a WLAN via a WLAN network interface 468.

[0130] Referring now to FIG. 17F, the present invention can be implemented in D/A or A/D converters in a set top box 480. The set top box 480 receives signals from a source such as a broadband source and outputs standard and/or high definition audio/video signals suitable for a display 488 such as a television and/or monitor and/or other video and/or audio output devices. The signal processing and/or control circuits 484 and/or other circuits (not shown) of the set top box 480 may process data, perform coding and/or encryption, perform calculations, format data and/or perform any other set top box function.

[0131] The set top box 480 may communicate with mass data storage 490 that stores data in a nonvolatile manner. The mass data storage 490 may include optical and/or magnetic storage devices for example hard disk drives HDD and/or DVDs. At least one HDD may have the configuration shown in FIG. 17A and/or at least one DVD may have the configuration shown in FIG. 17B. The HDD may be a mini HDD that includes one or more platters having a diameter that is smaller than approximately 1.8". The set top box 480 may be connected to memory 494 such as RAM, ROM, low latency nonvolatile memory such as flash memory and/or other suitable electronic data storage. The set top box 480 also may support connections with a WLAN via a WLAN network interface 496.

[0132] Referring now to FIG. 17G, the present invention can be implemented in D/A or A/D converters in a media player 500. In some implementations, the media player 500 includes a display 507 and/or a user input 508 such as a keypad, touchpad and the like. In some implementations, the media player 500 may employ a graphical user interface (GUI) that typically employs menus, drop down menus, icons and/or a point-and-click interface via the display 507 and/or user input 508. The media player 500 further includes an audio output 509 such as a speaker and/or audio output jack. The signal processing and/or control circuits 504 and/or other circuits (not shown) of the media player 500 may process data, perform coding and/or encryption, perform calculations, format data and/or perform any other media player function.

[0133] The media player 500 may communicate with mass data storage 510 that stores data such as compressed audio and/or video content in a nonvolatile manner. In some implementations, the compressed audio files include files that are compliant with MP3 format or other suitable compressed audio and/or video formats. The mass data storage may include optical and/or magnetic storage devices for example hard disk drives HDD and/or DVDs. At least one HDD may have the configuration shown in FIG. 17A and/or at least one DVD may have the configuration shown in FIG. 17B. The HDD may be a mini HDD that includes one or more platters having a diameter that is smaller than approximately 1.8". The media player 500 may be connected to memory 514 such as RAM, ROM, low latency nonvolatile memory such as flash memory and/or other suitable electronic data storage. The media player 500 also may

support connections with a WLAN via a WLAN network interface 516. Still other implementations in addition to those described above are contemplated.

[0134] Those skilled in the art can now appreciate from the foregoing description that the broad teachings of the present invention can be implemented in a variety of forms. Therefore, while this invention has been described in connection with particular examples thereof, the true scope of the invention should not be so limited since other modifications will become apparent to the skilled practitioner upon a study of the drawings, the specification and the following claims.

Claims

1. A digital to analog converter (DAC) comprising:
X capacitive DACs that are connected together in series, wherein X is an integer greater than one, and wherein each of said X capacitive DACs comprise:
M switches wherein M is an integer greater than one;
a signal input;
a signal output; and
M capacitances that communicate with said M switches, respectively, and that have first and second ends and substantially equal capacitance values,
wherein said M switches selectively connect said first ends of said M capacitances to said signal output, and
wherein said M switches connect said second end of a selected one of said M capacitances to said signal input; and
a first DAC that has a signal output that communicates with said signal input of one of said X capacitive DACs.

2. The DAC of Claim 1 further comprising:
an amplifier having an input and an output;
a feedback capacitance that communicates with said input and said output
of said amplifier,

wherein said first ends of said M capacitances of another one of said X
capacitive DACs communicates with a reference potential during a first phase of said
another one of said X capacitive DACs, and

wherein said input of said amplifier selectively communicates with said
first ends of said M capacitances of said another one of said X capacitive DACs
during a second phase of said another one of said X capacitive DACs.

3. The DAC of Claim 1 further comprising:
an amplifier having an input and an output,
wherein said first ends of said M capacitances of another one of said X
capacitive DACs communicate with a reference potential during a first phase of said
another one of said X capacitive DACs,

wherein said input of said amplifier selectively communicates with said
first ends of said M capacitances of said another one of said X capacitive DACs
during a second phase of said another one of said X capacitive DACs, and

wherein said second ends of said of said M capacitances of said another
one of said X capacitive DACs communicate with said output of said amplifier during
said second phase of said another one of said X capacitive DACs.

4. The DAC of Claim 1 wherein said first DAC comprises Y resistive DACs wherein Y is an integer greater than zero.

5. The DAC of Claim 4 wherein at least one of said Y resistive DACs comprises:

a signal output;

N resistances connected in series between said voltage reference and said reference potential;

N nodes between select ones of said N resistances and said reference potential; and

N second switches that selectively connect said signal output of said one of said Y resistive DACs to one of said N nodes.

6. The DAC of Claim 1 further comprising a control module that selectively generates switching signals to control said X capacitive DACs and said first DAC.

7. A successive approximation analog-to-digital converter comprising the DAC of Claim 1.

8. The successive approximation analog-to-digital converter of Claim 7 further comprising:

an amplifier having an input that selectively communicates with one of said X capacitive DACs;

a successive approximation module that communicates with an output of said amplifier;

a decoding module that communicates with an output of said successive approximation module and that selectively generates switching signals for said X capacitive DACs and said first DAC.

9. The DAC of Claim 1 wherein said first DAC comprises a capacitive DAC.

10. The DAC of Claim 9 wherein said capacitive DAC comprises:

a signal output;

an amplifier having an input and an output that communicates with said signal output;

M second capacitances connected in parallel and having first ends and second ends, wherein said first ends selectively communicate with a reference potential during a first phase of said capacitive DAC and wherein said first ends selectively communicate with said input of said amplifier during a second phase of said capacitive DAC; and

M second switches that selectively connect said second ends of said M second capacitances to one of said voltage reference and said reference potential

during said first phase of said capacitive DAC and that selectively connect said second ends of said M second capacitances to said output during said second phase of said capacitive DAC.

11. A method for operating a digital to analog converter (DAC) comprising:
 - connecting X capacitive DACs in series and wherein X is an integer greater than one, wherein each of said X capacitive DACs comprise M capacitances that have first and second ends and substantially equal capacitance values;
 - selectively connecting said first ends of said M capacitances to said signal output;
 - connecting said second end of a selected one of said M capacitances to said signal input; and
 - connecting a signal output of a first DAC to said signal input of one of said X capacitive DACs.

12. The method of Claim 11 further comprising:

- providing an amplifier having an input and an output and a feedback capacitance that communicates with said input and said output of said amplifier;
- connecting said first ends of said M capacitances of another one of said X capacitive DACs with a reference potential during a first phase of said another one of said X capacitive DACs; and
- selectively connecting said input of said amplifier to said first ends of said M capacitances of said another one of said X capacitive DACs during a second phase of said another one of said X capacitive DACs.

13. The method of Claim 11 further comprising:

- providing an amplifier having an input and an output;
- selectively connecting said first ends of said M capacitances of another one of said X capacitive DACs with a reference potential during a first phase of said another one of said X capacitive DACs;
- selectively connecting said input of said amplifier with said first ends of said M capacitances of said another one of said X capacitive DACs during a second phase of said another one of said X capacitive DACs; and
- selectively connecting said second ends of said of said M capacitances of said another one of said X capacitive DACs communicate with said output of said amplifier during said second phase of said another one of said X capacitive DACs.

14. The method of Claim 11 wherein said first DAC comprises Y resistive DACs wherein Y is an integer greater than zero.

15. The method of Claim 11 further comprising selectively generating switching signals to control said X capacitive DACs and said first DAC.

16. The method of Claim 11 further comprising using said X capacitive DACs to successively approximate an analog input signal.

17. The method of Claim 11 wherein said first DAC comprises a capacitive DAC.