*LLDP-MIB DEFINITIONS ::= BEGIN
IMPORTS
MODULE-IDENTITY, OBJECT-TYPE,
NOTIFICATION-TYPE, TimeTicks,
Integer32, mib-2
FROM SNMPv2-SMI
TEXTUAL-CONVENTION,
TruthValue, TimeStamp
FROM SNMPv2-TC;

*-- IEEE 802.1AB-2016 - Clause 12

*LLDP MIB

*OBJECT IDENTIFIER ::= { iso(1)
org(3) dod(6) internet(1)
mgmt(2) mib-2(1) 127 }

*-- Textual Conventions

*LldpPortNumber ::= TEXTUAL-CONVENTION
DISPLAY-HINT "d"
STATUS current
DESCRIPTION
"This TC describes the local port number.

*-- Top-level Components of this MIB

*-- Configuration

*lldpConfiguration OBJECT IDENTIFIER ::= { lldp 1 }

*-- Statistics

*lldpStatistics OBJECT IDENTIFIER ::= { lldp 2 }

*-- LLDP Local System Data

*lldpLocalSystemData OBJECT IDENTIFIER ::= { lldp 3 }

*-- LLDP Remote Systems Data

*lldpRemoteSystemsData OBJECT IDENTIFIER ::= { lldp 4 }

*-- LLDP Extensions

*lldpExtensions OBJECT IDENTIFIER ::= { lldp 5 }

*-- Port Component Table

*lldpPortConfigTable OBJECT-TYPE
SYNTAX SEQUENCE OF LldpPortConfigEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains one or more rows per port information associated with the local system known to this agent."
::= { lldpConfiguration 1 }

*lldpPortConfigEntry OBJECT-TYPE
SYNTAX LldpPortConfigEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Information about a particular port component."
INDEX { lldpPortConfigPortNum }
::= { lldpPortConfigTable 1 }

*LldpPortConfigEntry ::= SEQUENCE {
lldpPortConfigPortNum LldpPortNumber,
lldpPortConfigAdminStatus INTEGER,
lldpPortConfigNotificationEnable TruthValue,
lldpPortConfigTLVsTxEnable BITS
}

*lldpPortConfigPortNum OBJECT-TYPE
SYNTAX LldpPortNumber
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The port number identifier associated with the local system."
::= { lldpPortConfigEntry 1 }

*lldpPortConfigAdminStatus OBJECT-TYPE
SYNTAX INTEGER {
txOnly(1),
rxOnly(2),
txAndRx(3),
disabled(4)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The administratively desired status of the local system."
::= { lldpPortConfigEntry 2 }

*lldpPortConfigNotificationEnable OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The lldpPortConfigNotificationEnable controls, on a per port basis, whether or not notifications from the agent are enabled."
::= { lldpPortConfigEntry 3 }

*lldpPortConfigTLVsTxEnable OBJECT-TYPE
SYNTAX BITS {
portDesc(0),
sysName(1),
sysDesc(2),
sysCap(3)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The lldpPortConfigTLVsTxEnable defines which optional TLVs are transmitted by the agent."
::= { lldpPortConfigEntry 4 }

*-- Management Address Configuration Table

*lldpConfigManAddrTable OBJECT-TYPE
SYNTAX SEQUENCE OF LldpConfigManAddrEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains one or more rows per management address information associated with the local system known to this agent."
::= { lldpConfiguration 2 }

*lldpConfigManAddrEntry OBJECT-TYPE
SYNTAX LldpConfigManAddrEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Information about a particular management address component."
INDEX { lldpConfigManAddrPortsTxEnable }
::= { lldpConfigManAddrTable 1 }

*LldpConfigManAddrEntry ::= SEQUENCE {
lldpConfigManAddrPortsTxEnable BITS
}

*lldpConfigManAddrPortsTxEnable OBJECT-TYPE
SYNTAX BITS {
lldpPortNumber(0)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The lldpConfigManAddrPortsTxEnable defines which optional TLVs are transmitted by the agent."
::= { lldpConfigManAddrEntry 1 }

*-- Statistics

*lldpStatsTxPortTable OBJECT-TYPE
SYNTAX SEQUENCE OF LldpStatsTxPortEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains one or more rows per port information associated with the local system known to this agent."
::= { lldpStatistics 1 }

*lldpStatsTxPortEntry OBJECT-TYPE
SYNTAX LldpStatsTxPortEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Information about a particular port component."
INDEX { lldpStatsTxPortNum }
::= { lldpStatsTxPortTable 1 }

*LldpStatsTxPortEntry ::= SEQUENCE {
lldpStatsTxPortNum LldpPortNumber,
lldpStatsTxPortFramesTotal Counter32
}

*lldpStatsTxPortNum OBJECT-TYPE
SYNTAX LldpPortNumber
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The port number identifier associated with the local system."
::= { lldpStatsTxPortEntry 1 }

*lldpStatsTxPortFramesTotal OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpStatsTxPortFramesTotal indicates the number of LLDP frames transmitted by the agent."
::= { lldpStatsTxPortEntry 2 }

*-- Statistics

*lldpStatsRxPortTable OBJECT-TYPE
SYNTAX SEQUENCE OF LldpStatsRxPortEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains one or more rows per port information associated with the local system known to this agent."
::= { lldpStatistics 2 }

*lldpStatsRxPortEntry OBJECT-TYPE
SYNTAX LldpStatsRxPortEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Information about a particular port component."
INDEX { lldpStatsRxPortNum }
::= { lldpStatsRxPortTable 1 }

*LldpStatsRxPortEntry ::= SEQUENCE {
lldpStatsRxPortNum LldpPortNumber,
lldpStatsRxPortFramesDiscardedTotal Counter32,
lldpStatsRxPortFramesErrors Counter32,
lldpStatsRxPortFramesTotal Counter32,
lldpStatsRxPortTLVsDiscardedTotal Counter32,
lldpStatsRxPortTLVsUnrecognizedTotal Counter32,
lldpStatsRxPortAgeoutsTotal Counter32
}

*lldpStatsRxPortNum OBJECT-TYPE
SYNTAX LldpPortNumber
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The port number identifier associated with the local system."
::= { lldpStatsRxPortEntry 1 }

*lldpStatsRxPortFramesDiscardedTotal OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpStatsRxPortFramesDiscardedTotal indicates the number of LLDP frames received by the agent."
::= { lldpStatsRxPortEntry 2 }

*lldpStatsRxPortFramesErrors OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpStatsRxPortFramesErrors indicates the number of LLDP frames received by the agent."
::= { lldpStatsRxPortEntry 3 }

*lldpStatsRxPortFramesTotal OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpStatsRxPortFramesTotal indicates the number of LLDP frames received by the agent."
::= { lldpStatsRxPortEntry 4 }

*lldpStatsRxPortTLVsDiscardedTotal OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpStatsRxPortTLVsDiscardedTotal indicates the number of LLDP TLVs received by the agent."
::= { lldpStatsRxPortEntry 5 }

*lldpStatsRxPortTLVsUnrecognizedTotal OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpStatsRxPortTLVsUnrecognizedTotal indicates the number of LLDP TLVs received by the agent."
::= { lldpStatsRxPortEntry 6 }

*lldpStatsRxPortAgeoutsTotal OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpStatsRxPortAgeoutsTotal indicates the number of LLDP frames received by the agent."
::= { lldpStatsRxPortEntry 7 }

*-- Local System Data

*lldpLocalSystemDataTable OBJECT-TYPE
SYNTAX SEQUENCE OF LldpLocalSystemDataEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains one or more rows per port information associated with the local system known to this agent."
::= { lldpLocalSystemData 1 }

*lldpLocalSystemDataEntry OBJECT-TYPE
SYNTAX LldpLocalSystemDataEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Information about a particular port component."
INDEX { lldpLocalSystemDataPortNum }
::= { lldpLocalSystemDataTable 1 }

*LldpLocalSystemDataEntry ::= SEQUENCE {
lldpLocalSystemDataPortNum LldpPortNumber,
lldpLocalSystemDataChassisIdSubtype INTEGER,
lldpLocalSystemDataChassisId OCTET STRING,
lldpLocalSystemDataSysName DisplayString,
lldpLocalSystemDataSysDesc DisplayString,
lldpLocalSystemDataSysCapSupported BITS,
lldpLocalSystemDataSysCapEnabled BITS
}

*lldpLocalSystemDataPortNum OBJECT-TYPE
SYNTAX LldpPortNumber
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The port number identifier associated with the local system."
::= { lldpLocalSystemDataEntry 1 }

*lldpLocalSystemDataChassisIdSubtype OBJECT-TYPE
SYNTAX INTEGER {
chassisComponent(1),
interfaceAlias(2),
portComponent(3),
macAddress(4),
networkAddress(5),
interfaceName(6),
local(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpLocalSystemDataChassisIdSubtype indicates the type of chassis identifier."
::= { lldpLocalSystemDataEntry 2 }

*lldpLocalSystemDataChassisId OBJECT-TYPE
SYNTAX OCTET STRING
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpLocalSystemDataChassisId indicates the chassis identifier."
::= { lldpLocalSystemDataEntry 3 }

*lldpLocalSystemDataSysName OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpLocalSystemDataSysName indicates the system name."
::= { lldpLocalSystemDataEntry 4 }

*lldpLocalSystemDataSysDesc OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpLocalSystemDataSysDesc indicates the system description."
::= { lldpLocalSystemDataEntry 5 }

*lldpLocalSystemDataSysCapSupported OBJECT-TYPE
SYNTAX BITS {
other(0),
repeater(1),
bridge(2),
wlanAccessPoint(3),
router(4),
telephone(5),
docsisCableDevice(6),
stationOnly(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpLocalSystemDataSysCapSupported indicates the system capabilities supported."
::= { lldpLocalSystemDataEntry 6 }

*lldpLocalSystemDataSysCapEnabled OBJECT-TYPE
SYNTAX BITS {
other(0),
repeater(1),
bridge(2),
wlanAccessPoint(3),
router(4),
telephone(5),
docsisCableDevice(6),
stationOnly(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpLocalSystemDataSysCapEnabled indicates the system capabilities enabled."
::= { lldpLocalSystemDataEntry 7 }

*-- Remote Systems Data

*lldpRemoteSystemsDataTable OBJECT-TYPE
SYNTAX SEQUENCE OF LldpRemoteSystemsDataEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains one or more rows per port information associated with the local system known to this agent."
::= { lldpRemoteSystemsData 1 }

*lldpRemoteSystemsDataEntry OBJECT-TYPE
SYNTAX LldpRemoteSystemsDataEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Information about a particular port component."
INDEX { lldpRemoteSystemsDataPortNum }
::= { lldpRemoteSystemsDataTable 1 }

*LldpRemoteSystemsDataEntry ::= SEQUENCE {
lldpRemoteSystemsDataPortNum LldpPortNumber,
lldpRemoteSystemsDataChassisIdSubtype INTEGER,
lldpRemoteSystemsDataChassisId OCTET STRING,
lldpRemoteSystemsDataSysName DisplayString,
lldpRemoteSystemsDataSysDesc DisplayString,
lldpRemoteSystemsDataSysCapSupported BITS,
lldpRemoteSystemsDataSysCapEnabled BITS
}

*lldpRemoteSystemsDataPortNum OBJECT-TYPE
SYNTAX LldpPortNumber
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The port number identifier associated with the local system."
::= { lldpRemoteSystemsDataEntry 1 }

*lldpRemoteSystemsDataChassisIdSubtype OBJECT-TYPE
SYNTAX INTEGER {
chassisComponent(1),
interfaceAlias(2),
portComponent(3),
macAddress(4),
networkAddress(5),
interfaceName(6),
local(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpRemoteSystemsDataChassisIdSubtype indicates the type of chassis identifier."
::= { lldpRemoteSystemsDataEntry 2 }

*lldpRemoteSystemsDataChassisId OBJECT-TYPE
SYNTAX OCTET STRING
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpRemoteSystemsDataChassisId indicates the chassis identifier."
::= { lldpRemoteSystemsDataEntry 3 }

*lldpRemoteSystemsDataSysName OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpRemoteSystemsDataSysName indicates the system name."
::= { lldpRemoteSystemsDataEntry 4 }

*lldpRemoteSystemsDataSysDesc OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpRemoteSystemsDataSysDesc indicates the system description."
::= { lldpRemoteSystemsDataEntry 5 }

*lldpRemoteSystemsDataSysCapSupported OBJECT-TYPE
SYNTAX BITS {
other(0),
repeater(1),
bridge(2),
wlanAccessPoint(3),
router(4),
telephone(5),
docsisCableDevice(6),
stationOnly(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpRemoteSystemsDataSysCapSupported indicates the system capabilities supported."
::= { lldpRemoteSystemsDataEntry 6 }

*lldpRemoteSystemsDataSysCapEnabled OBJECT-TYPE
SYNTAX BITS {
other(0),
repeater(1),
bridge(2),
wlanAccessPoint(3),
router(4),
telephone(5),
docsisCableDevice(6),
stationOnly(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpRemoteSystemsDataSysCapEnabled indicates the system capabilities enabled."
::= { lldpRemoteSystemsDataEntry 7 }

*-- Extensions

*lldpExtensionsTable OBJECT-TYPE
SYNTAX SEQUENCE OF LldpExtensionsEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains one or more rows per port information associated with the local system known to this agent."
::= { lldpExtensions 1 }

*lldpExtensionsEntry OBJECT-TYPE
SYNTAX LldpExtensionsEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Information about a particular port component."
INDEX { lldpExtensionsPortNum }
::= { lldpExtensionsTable 1 }

*LldpExtensionsEntry ::= SEQUENCE {
lldpExtensionsPortNum LldpPortNumber,
lldpExtensionsPortDesc DisplayString,
lldpExtensionsSysName DisplayString,
lldpExtensionsSysDesc DisplayString,
lldpExtensionsSysCapSupported BITS,
lldpExtensionsSysCapEnabled BITS
}

*lldpExtensionsPortNum OBJECT-TYPE
SYNTAX LldpPortNumber
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The port number identifier associated with the local system."
::= { lldpExtensionsEntry 1 }

*lldpExtensionsPortDesc OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpExtensionsPortDesc indicates the port description."
::= { lldpExtensionsEntry 2 }

*lldpExtensionsSysName OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpExtensionsSysName indicates the system name."
::= { lldpExtensionsEntry 3 }

*lldpExtensionsSysDesc OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpExtensionsSysDesc indicates the system description."
::= { lldpExtensionsEntry 4 }

*lldpExtensionsSysCapSupported OBJECT-TYPE
SYNTAX BITS {
other(0),
repeater(1),
bridge(2),
wlanAccessPoint(3),
router(4),
telephone(5),
docsisCableDevice(6),
stationOnly(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpExtensionsSysCapSupported indicates the system capabilities supported."
::= { lldpExtensionsEntry 5 }

*lldpExtensionsSysCapEnabled OBJECT-TYPE
SYNTAX BITS {
other(0),
repeater(1),
bridge(2),
wlanAccessPoint(3),
router(4),
telephone(5),
docsisCableDevice(6),
stationOnly(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpExtensionsSysCapEnabled indicates the system capabilities enabled."
::= { lldpExtensionsEntry 6 }

*-- Notifications

*lldpNotifications OBJECT IDENTIFIER ::= { lldp 6 }

*lldpNotificationsTable OBJECT-TYPE
SYNTAX SEQUENCE OF LldpNotificationsEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains one or more rows per port information associated with the local system known to this agent."
::= { lldpNotifications 1 }

*lldpNotificationsEntry OBJECT-TYPE
SYNTAX LldpNotificationsEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Information about a particular port component."
INDEX { lldpNotificationsPortNum }
::= { lldpNotificationsTable 1 }

*LldpNotificationsEntry ::= SEQUENCE {
lldpNotificationsPortNum LldpPortNumber,
lldpNotificationsPortDesc DisplayString,
lldpNotificationsSysName DisplayString,
lldpNotificationsSysDesc DisplayString,
lldpNotificationsSysCapSupported BITS,
lldpNotificationsSysCapEnabled BITS
}

*lldpNotificationsPortNum OBJECT-TYPE
SYNTAX LldpPortNumber
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The port number identifier associated with the local system."
::= { lldpNotificationsEntry 1 }

*lldpNotificationsPortDesc OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpNotificationsPortDesc indicates the port description."
::= { lldpNotificationsEntry 2 }

*lldpNotificationsSysName OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpNotificationsSysName indicates the system name."
::= { lldpNotificationsEntry 3 }

*lldpNotificationsSysDesc OBJECT-TYPE
SYNTAX DisplayString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpNotificationsSysDesc indicates the system description."
::= { lldpNotificationsEntry 4 }

*lldpNotificationsSysCapSupported OBJECT-TYPE
SYNTAX BITS {
other(0),
repeater(1),
bridge(2),
wlanAccessPoint(3),
router(4),
telephone(5),
docsisCableDevice(6),
stationOnly(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpNotificationsSysCapSupported indicates the system capabilities supported."
::= { lldpNotificationsEntry 5 }

*lldpNotificationsSysCapEnabled OBJECT-TYPE
SYNTAX BITS {
other(0),
repeater(1),
bridge(2),
wlanAccessPoint(3),
router(4),
telephone(5),
docsisCableDevice(6),
stationOnly(7)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The lldpNotificationsSysCapEnabled indicates the system capabilities enabled."
::= { lldpNotificationsEntry 6 }

*-- Notifications