

RETRANSMISSION PROCESS CONTROL METHOD**Field of invention**

- 5 This invention relates to signalling of control information related to retransmissions in a wireless communication network.

List of acronyms

10	AG	Absolute Grant
	CDMA	code division multiple access
	DL	downlink
	E-AGCH	EDCH Absolute Grant Channel
	EDCH	Enhanced Uplink DCH
15	E-RGCH	EDCH Relative Grant Channel
	HARQ	Hybrid Automatic Repeat reQuest
	HSUPA	High Speed Uplink Packet Access
	Node B	Base station
	RG	Relative Grant
20	RLC	Radio Link Control
	RNC	Radio Network Controller
	RR	Rate Request
	RRC	Radio Resource Control
	TFC	Transport Format Combination
25	TTI	Transmission Time Interval
	UE	User Equipment, a mobile station
	UL	uplink

30 Technological background

A communication system is a facility that enables communication between two or more entities such as user terminal equipment and/or network

08. 11. 2006

2

(76)

entities and other nodes associated with a communication system. The communication may comprise, for example, communication of voice, electronic mail (email), text messages, data, multimedia and so on.

- 5 The communication may be provided by fixed line and/or wireless communication interfaces. A feature of wireless communication systems is that they provide mobility for the users thereof. An example of a communication system providing wireless communication is a public land mobile network (PLMN). An example of the fixed line system is a public
10 switched telephone network (PSTN).

A cellular telecommunication system is a communications system that is based on the use of radio access entities and/or wireless service areas. The access entities are typically referred to as cells. Examples of cellular
15 telecommunication standards includes standards such as GSM (Global System for Mobile communications), GPRS (General Packet Radio Servers), AMPS (American Mobile Phone System), DAMPS (Digital AMPS), WCDMA (Wideband Code Division Multiple Access), UMTS (Universal Mobile Telecommunication System) and CDMA 2000 (Code Division
20 Multiple Access 2000).

A communication system typically operates in accordance with a given standard or specification which sets out what the various elements of a system are permitted to do and how that should be achieved. For example,
25 the standard of specification may define if the user, or more precisely user equipment is provided with a circuit switched service or a packet switched service or both. Communication protocols and/or parameters which should be used for the connection are also typically defined. For example, the manner in which communication shall be implemented between the user
30 equipment and the elements of the communication network is typically based in a predefined communication protocol. In other words, a specific set of "rules" on which the communication can be based needs to be

defined to enable the user equipment to communicate via the communication system.

At the time of writing of this patent application, enhancements of the uplink
5 DCH (Enhanced DCH, EDCH) are being standardized for packet data traffic for release 6 of the 3GPP standards. Some of the associated 3GPP standards are at least (but not limited to) the following: 3GPP TR 25.896, 3GPP TR 25.808, and 3GPP TS 25.309.

10 Enhancements are reached according to currently discussed standard versions by distributing some of the packet scheduler functionality to the Node B network nodes in order to have faster scheduling of bursty non real-time traffic than the layer 3 mechanisms in RNC facilitate. The idea is that with faster link adaptation it is possible to more efficiently share the uplink
15 power resources between packet data users: when packets have been transmitted from one user the scheduled resource can be made available immediately to another user. This avoids the peaked variability of noise rise, when high data rates are being allocated to users running bursty high data-rate applications.

20 In the currently specified architecture, the packet scheduler is located in the RNC and therefore is limited in its ability to adapt to the instantaneous traffic, because of bandwidth and delay constraints on the RRC signalling interface between the RNC and the UE. Hence, to accommodate the
25 variability, the packet scheduler must be conservative in allocating uplink power to take into account the influence from inactive users in the following scheduling period - a solution which turns out to be spectrally inefficient for high allocated data rates and long release timer values.

30 In current specifications for EDCH, much of the packet scheduler functionality is transferred to the Node B, i.e. there is a Node B scheduler that takes care of allocating uplink resources. For transmission of data, the UE selects a E-TFC that suits the amount of data to be transmitted in its

RLC buffer, subject to constraints on the maximum transmission power of the UE and the maximum allowed power. If needed, UE can request for higher bit rate by sending Rate Request messages (RR) in the uplink, and the Node B decides whether to grant or not additional resources by answering with rate grant messages in the downlink. The grant messages are of two kinds: Relative Grants (RG) and Absolute Grant (AG). Relative grants are relative to the actual used resource by the UE. The absolute grant allocates resources to the UE in an absolute manner in terms of power. When to use AG or RG to adjust the resources allocated to the UE is fully subject to the decision done in the network. The AG and RG messages are transmitted in the downlink using specific physical channels designed for this purpose, namely E-AGCH and E-RGCH.

Also the current EDCH specifications bring a similar L1/MAC layer HARQ retransmission mechanism between UE and Node B in the uplink as in HSDPA for the downlink. The fast HARQ is based on N-process SAW (Stop-And-Wait) HARQ, where HARQ combining is performed at Node B L1 (layer 1). For the 2ms TTI (transmission time interval), 8 SAW HARQ processes are defined in the current standard versions, and for the 10ms TTI 4 processes are defined in the current standard versions.

According to certain current proposals, each HARQ process is to be scheduled independently for the 2ms TTI. There is a fixed timing relationship between the DL (downlink) and the UL (uplink) which tells to which HARQ process the received AG or RG command (AG/RG) applies as shown in Figure 1. For each AG or RG command received, the UE knows exactly to which HARQ process it applies due to the known timing relationship.

These proposals have certain problems. For example, scheduling each HARQ process independently requires a lot of signalling and can be considered more susceptible to signalling errors.

It has been proposed to have an 8 bit process allocation string defined at Layer 3: each bit tells whether the UE is allowed to transmit in uplink for that particular HARQ process or not. This known proposal would enable considering the scheduling commands applicable to all active HARQ retransmission processes and thus reduce required amount of signaling and susceptibility to signaling errors and still have the means for the network to control which HARQ retransmission processes are allowed to transmit. However, layer 3 signalling is too slow to allow a fast activation. Besides the Node B scheduler is located at Layer 2 in the Node B. Interaction with Layer 3 at RNC for scheduling issues is not optimal.

Summary of the invention

Embodiments of the present invention aim to overcome one or several of the above problems.

In a first aspect of the invention, there is provided a method for controlling an uplink transmission from a mobile station to a network node over a wireless communication link therebetween, wherein the method comprises: indicating whether a retransmission process should be activated or deactivated; and transmitting said indication from the network node to the mobile station on a transmission resource control channel.

In a second aspect of the invention, there is provided a mobile station for a wireless communication network, comprising: a receiver for receiving a transmission resource control channel, means for receiving retransmission process control information from the transmission resource control channel, and a controller for activating and deactivating retransmission processes as a response to retransmission process control information received by the means for receiving control information.

In a third aspect of the invention, there is provided a network node for a wireless communication network, comprising: a transmitter for transmitting a transmission resource control channel to mobile stations, and means for embedding retransmission process control information in data frames transmitted on the transmission resource control channel.

In a fourth aspect of the invention, there is provided a mobile station for a wireless communication network, comprising: a receiver for receiving a transmission resource control channel, a retransmission process control information receiver for receiving retransmission process control information from the transmission resource control channel, and a controller for activating and deactivating retransmission processes as a response to retransmission process control information received by the means for receiving control information.

In a fifth aspect of the invention, there is provided a network node for a wireless communication network, comprising: a transmitter for transmitting a transmission resource control channel to mobile stations, and a processor for embedding retransmission process control information in data frames transmitted on the transmission resource control channel.

In example embodiments, a method for controlling transmission over a wireless communication link is provided. The method comprises the step of indicating on a transmission resource control channel whether a retransmission process should be activated or deactivated.

In example embodiments, the transmission resource control channel can be an E-AGCH channel.

In the method of an example embodiment, a bit transmitted on a transmission resource control channel can indicate that a corresponding retransmission process should be activated if the process is not active, and deactivated if the process is active.

In the method of an example embodiment, a bit transmitted on a transmission resource control channel can indicate whether a predefined group of other bits on the transmission resource control channel indicate a transmission resource grant or whether

the predefined group of other bits on the transmission resource control channel carry retransmission process activation commands.

In the method of an example embodiment, a group of bits transmitted on the transmission resource control channel can indicate that a retransmission process should change state.

In the method of an example embodiment, a group of bits transmitted on the transmission resource control channel can indicate a retransmission process state or state change for a specific retransmission process and a retransmission process state or state change for other retransmission processes.

In example embodiments, the step of indicating can be performed by a wireless network node such as a Node B or a base station.

In example embodiments, a mobile station for a wireless communication network is provided. The mobile station comprises a receiver for receiving a transmission resource control channel, means for receiving retransmission process control information from the transmission resource control channel, and a controller for activating and deactivating retransmission processes as a response to retransmission process control information received by the means for receiving control information. The transmission resource control channel can be an E-AGCH channel.

In example embodiments, a network node for a wireless communication network is provided. The network node comprises a transmitter for transmitting a transmission resource control channel to mobile stations, and means for embedding retransmission process control information in data frames transmitted on the transmission resource control channel.

In example embodiments, the network node can be a Node B network node.

In example embodiments, the network node can be a base station.

Brief description of the drawings

Embodiments of the present invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 illustrates timing relationships between transmission resource access grants and HARQ processes according to prior art,

Figure 2 illustrates a mobile station and a network element according to an embodiment of the invention,

Figure 3 illustrates signaling between a Node B and a mobile station, and

Figure 4 illustrates signaling and process control between a Node B and a mobile station.

Detailed description of embodiments

Figure 2 illustrates a mobile station 20 and a network node 100 of a wireless communication system 110 according to an embodiment of the invention.

The mobile station has a user interface 210 which can be for example a display and a keyboard, a processor 220, a receiver 230 for receiving a transmission resource control channel, means 240 for receiving retransmission process control information from the transmission resource control channel, and a controller 250 for activating and deactivating retransmission processes as a response to retransmission process control information received by the means for receiving control information. Various

components can be implemented using software program code executed in the processor 220 of the mobile station. For example, the means 240 for receiving retransmission process control information can be implemented as software program code which is adapted to extract retransmission process control information from an incoming data flow of a transmission resource control channel.

The transmission resource control channel can be for example an E-AGCH channel.

10

The network node 100 comprises a transmitter 115 for transmitting a transmission resource control channel to mobile stations, and means 120 for embedding retransmission process control information in data frames transmitted on the transmission resource control channel.

15

The network node can be for example a Node B network node. If the particular wireless network in which an embodiment of the invention is implemented does not have the concept of a Node B, the network node can be a base station.

20

The basic idea underlying the invention is to use a layer 1 mechanism for HARQ retransmission process activation, using a transmission resource control channel as a signalling channel. The transmission resource control channel can advantageously be the E-AGCH channel, or for example the E-RGCH channel.

25

According to an embodiment of the invention, certain bits in the transmission resource control channel are used to signal whether one or more HARQ processes should be activated or deactivated.

30

In one embodiment of the invention, a bit transmitted on the transmission resource control channel is used to indicate to an UE (a mobile station) whether a particular HARQ process should be activated or deactivated. This embodiment depends on a well-defined timing relation between UL and DL,

which allows the UE to relate the indicating bit transmitted on the transmission resource control channel to a particular HARQ process. As a result, one bit per process is required in the transmission resource control channel to tell the UE whether a particular HARQ process should be
5 activated or de-activated.

Figure 3 illustrates signalling in an exemplary embodiment of the invention. Figure 3 illustrates signalling between a Node B network node 100 and a mobile station (UE) 20. In step 305 Node B transmits an indication that a
10 particular HARQ process should change state. In step 310 the UE changes the state of i.e. activates or deactivates the HARQ process.

In a further embodiment, a bit on the transmission resource control channel denotes how a predefined number of other bits on the transmission
15 resource control channel are to be interpreted. For example, if that specific bit is set to one value (such as 0), the related bits of the transmission resource control channel have their prior art meaning related to specifying an absolute (or relative) transmission resource grant. If that specific bit is set
20 to another value (such as 1) the related bits of the transmission resource control channel carry HARQ retransmission process activation commands; for example, whether each of a corresponding number of HARQ processes should be activated or deactivated.

Figure 4 illustrates signalling and HARQ process control an exemplary
25 embodiment of the invention. In step 405, a Node B transmits a control bit and a bit sequence on an E-AGCH channel. In step 410 the mobile station (UE) determines whether the control bit is set to 1. If the control bit was set to 1, the mobile station interprets the received bit sequence as HARQ process control commands and adjusts at least one HARQ process
30 accordingly in step 415. If the control bit was set to 0, the mobile station interprets the received bit sequence as a transmission resource grant and adjusts its transmissions accordingly in step 420.

In a still further embodiment of the invention, a group of bits on the transmission resource control channel are used to indicate which HARQ process should change state. In a system having 8 HARQ retransmission processes, 3 bits can be used in the transmission resource control channel to indicate whether the corresponding HARQ process should toggle its state: if it was activated it should be de-activated; and if it was de-activated it should be activated.

According to a further embodiment of the invention, a group of bits on the transmission resource control channel have specified meaning as to whether a specific HARQ process is to be activated or deactivated, and/or whether all other HARQ processes are to be deactivated or activated. For example, a group of two bits can specify the following:

15	bit 1	bit 2	meaning
	0	0	activate all processes
	0	1	activate all processes
	1	0	deactivate this process
	1	1	activate this process

20

The meaning of the group of bits can be specified in many different ways. For example, in another embodiment, a group of two bits can specify the following:

25	bit 1	bit 2	meaning
	0	0	activate all processes
	0	1	activate this process and deactivate all other processes
	1	0	activate this process
	1	1	deactivate this process

30

In a further embodiment, certain bits transmitted in the transmission resource control channel can indicate, whether AG and/or RG commands relate to a single HARQ process or to all HARQ processes. For example,

certain values of a group of bits specifying activity states of one or more HARQ processes may indicate that following AG and/or RG commands apply to all active HARQ processes.

- 5 The invention has certain advantages. For example, the invention allows fast activation of HARQ processes, allowing Node B to control the activation of the HARQ processing. This allows fast accommodation to variability in transmission resource needs, as the Node B scheduler is according to current 3GPP standard versions also located in the Node B.

10

- The signalling bits for controlling HARQ retransmission processes as described in this specification can be encoded and signalled in a transmission resource control channel in many different ways among other messages in the transmission resource control channel. Many different
15 ways of encoding and signalling the bits can be devised by a man skilled in the art, and the invention is not limited to any specific messaging structure for carrying such bits.

- The invention also provides a mobile station (UE) capable of receiving
20 transmission control information within a transmission resource control channel and controlling HARQ retransmission processes based on the received transmission control information as described in the previous paragraphs.

- 25 The invention also provides a communication network element capable of transmitting transmission control information within a transmission resource control channel in order to control uplink HARQ retransmission processes in a mobile station (UE).

- 30 It is noted that while the preceding description illustrates various embodiments of the invention within a 3G cellular telecommunications system, the invention is not limited to a so called 3G cellular system, but can

be implemented in different types of cellular telecommunication systems as well.

5 It is also noted herein that while the above describes exemplifying embodiments of the invention, there are several variations and modifications which may be made to the disclosed solution without departing from the scope of the present invention as defined in the appended claims.

Claims

1. A method for controlling an uplink transmission from a mobile station to a network node over a wireless communication link therebetween,
5 wherein the method comprises: indicating whether a retransmission process should be activated or deactivated; and transmitting said indication from the network node to the mobile station on a transmission resource control channel.
- 10 2. A method according to claim 1, wherein the transmission resource control channel is an enhanced absolute grant channel (E-AGCH channel).
3. A method according to claim 1, wherein a bit transmitted on a transmission resource control channel indicates that a corresponding
15 retransmission process should be activated if the retransmission process is not active, and deactivated if the retransmission process is active.
4. A method according to claim 1, wherein a bit transmitted on a transmission resource control channel indicates whether a predefined group
20 of other bits on the transmission resource control channel indicate a transmission resource grant or whether the predefined group of other bits on the transmission resource control channel carry retransmission process activation commands.
- 25 5. A method according to claim 1, wherein a group of bits transmitted on the transmission resource control channel indicates that a retransmission process should change states.
6. A method according to claim 1, wherein a group of bits transmitted on
30 the transmission resource control channel indicates a retransmission process state or state change for a specific retransmission process and a retransmission process state, or state change for other retransmission processes.

7. A method according to claim 1, wherein the step of indicating is performed by a wireless network node.
8. A mobile station for a wireless communication network, comprising:
5 a receiver for receiving a transmission resource control channel,
means for receiving retransmission process control information from the transmission resource control channel, and
a controller for activating and deactivating retransmission processes as a response to retransmission process control information received by the
10 means for receiving control information.
9. A mobile station according to claim 8, wherein the transmission resource control channel is an enhanced absolute grant channel (E-AGCH channel).
- 15 10. A network node for a wireless communication network, comprising:
a transmitter for transmitting a transmission resource control channel to mobile stations, and
means for embedding retransmission process control information in
20 data frames transmitted on the transmission resource control channel.
11. A network node according to claim 10, wherein the transmission resource control channel is enhanced absolute grant channel (E-AGCH channel).
- 25 12. A network node according to claim 10, wherein the network node is a Node B network node.
13. A network node according to claim 10, wherein the network node is a
30 base station.
14. A mobile station for a wireless communication network, comprising:
a receiver for receiving a transmission resource control channel,

a retransmission process control information receiver for receiving retransmission process control information from the transmission resource control channel, and

5 a controller for activating and deactivating retransmission processes as a response to retransmission process control information received by the means for receiving control information.

15 15. A mobile station according to claim 14, wherein the transmission resource control channel is an enhanced absolute grant channel (E-AGCH channel).

16. A network node for a wireless communication network, comprising:
a transmitter for transmitting a transmission resource control channel to mobile stations, and
15 a processor for embedding retransmission process control information in data frames transmitted on the transmission resource control channel.

17. A network node according to claim 16, wherein the transmission resource control channel is an enhanced absolute grant channel (E-AGCH channel).

18. A network node according to claim 16, wherein the network node is a Node B network node.

25 19. A network node according to claim 16, wherein the network node is a base station.