



(51) International Patent Classification:
H03K 19/21 (2006.01)

(21) International Application Number:
PCT/US2010/031650

(22) International Filing Date:
19 April 2010 (19.04.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/174,408 30 April 2009 (30.04.2009) US
12/435,672 5 May 2009 (05.05.2009) US

(71) Applicant (for all designated States except US): **TELA INNOVATIONS, INC.** [US/US]; 655 Campbell Technology Pkwy, Suite 150, Campbell, CA 95008 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BECKER, Scott, T.** [US/US]; 655 Campbell Technology Pkwy, Suite 150, Campbell, CA 95008 (US).

(74) Agent: **WRIGHT, Kenneth, D.**; Martine Penilla & Gen-carella, LLP, 710 Lakeway Drive, Suite 200, Sunnyvale, CA 94085 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(88) Date of publication of the international search report:
10 March 2011

(54) Title: CIRCUITRY AND LAYOUTS FOR XOR AND XNOR LOGIC




Fig. 2A

(57) Abstract: An exclusive-or circuit includes a pass gate controlled by a second input node. The pass gate is connected to pass through a version of a logic state present at a first input node to an output node when so controlled. A transmission gate is controlled by the first input node. The transmission gate is connected to pass through a version of the logic state present at the second input node to the output node when so controlled. Pullup logic is controlled by both the first and second input nodes. The pullup logic is connected to drive the output node low when both the first and second input nodes are high. An exclusive-nor circuit is defined similar to the exclusive-or circuit, except that the pullup logic is replaced by pulldown logic which is connected to drive the output node high when both the first and second input nodes are high.