

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 August 2004 (05.08.2004)


PCT

(10) International Publication Number
WO 2004/066511 A2

- (51) International Patent Classification⁷: **H04B**
- (21) International Application Number: PCT/US2004/000526
- (22) International Filing Date: 9 January 2004 (09.01.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/440,073 14 January 2003 (14.01.2003) US
10/729,332 5 December 2003 (05.12.2003) US
- (71) Applicant (for all designated States except US): **INTER-DIGITAL TECHNOLOGY CORPORATION** [US/US]; 300 Delaware Avenue, Suite 527, Wilmington, DE 19801 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **KWAK, Joseph** [US/US]; 482 Degas Road, Bolingbrook, IL 60440 (US).
- (74) Agent: **WEINSTEIN, Louis**; Volpe And Koenig, P.C., United Plaza, Suite 1600, 30 South 17th Street, Philadelphia, PA 19103 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR NETWORK MANAGEMENT USING PERCEIVED SIGNAL TO NOISE AND INTERFERENCE INDICATOR



A: RF POWER, RF S/N+1 FROM EACH AP

B: BB S/N+I FROM EACH AP, (BB POWER MAINTAINED CONSTANT BY AGC)

C & D: BIT ERROR RATE (BER) @ EACH DATA RATE

E: FRAME ERROR RATE (FER) @ EACH DATA RATE

(57) Abstract: Method and apparatus of network management using a perceived signal to noise indicator (PSNI), in preference to received signal strength indicator to provide physical layer measurements in a multitude of stations in the network, either by way of radio frequency power, or observed signal to noise plus interference from each access point, to report the measurements, to collect the measurements, and using the reported PSNI values as a signal quality indicator of delivered bit error rate or frame error rate to evaluate, reconfigure, and manage multiple stations in order to optimize the network or network performance.

WO 2004/066511 A2



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*