

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International BureauRTMP/Is
copy

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G09F 11/26, 23/02, A47F 9/04	A1	(11) International Publication Number: WO 96/27180 (43) International Publication Date: 6 September 1996 (06.09.96)
(21) International Application Number: PCT/NO96/00046 (22) International Filing Date: 29 February 1996 (29.02.96) (30) Priority Data: 950791 1 March 1995 (01.03.95) ✓ NO (71)(72) Applicants and Inventors: VONHOLM, Christian [NO/NO]; Arne Ulstrupvei 3F, N-1322 Høvik (NO). KNUTSEN, Stian, Valentin [NO/NO]; Nessisen 11A, N-1360 Nesbru (NO). (74) Agent: ONSAGERS PATENTKONTOR A/S; P.O. Box 265 Sentrum, N-0103 Oslo (NO).	(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MR , MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG , SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIP patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: METHOD FOR APPLICATION OF INFORMATION/ADVERTISING INDICIA ON CONVEYER BELTS**(57) Abstract**

Method for application of information/advertising indicia (1) on conveyer belts (2a) in, e.g., cashier counters (2), consisting of a special print (1) applied by the use of a heat/pressure press (3), wherein the lower plate (7) and upper plate (8) obtains a temperature in the range of 70-130 °C and the lower plate (7) and upper plate (8) are brought together, wherein the conveyer belt comprising information/advertising indicia (1) on top is placed between the lower plate (7) and upper plate (8) by the use of pressure in the range of 6-9 bar, which results in that the information/advertising indicia (1) becomes an integrated part of the surface of the conveyer belt (2a) by applying said means of heat/pressure press (3), without reducing the quality or longevity of the conveyer belt (2a).