

(43) International Publication Date
21 May 2015 (21.05.2015)

- (51) International Patent Classification:
F16L 37/113 (2006.01) *E21B 17/08* (2006.01)
- (21) International Application Number:
PCT/EP2014/074604
- (22) International Filing Date:
14 November 2014 (14.11.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
20131518 15 November 2013 (15.11.2013) NO
- (71) Applicant: **MARITIME PROMECO AS** [NO/NO];
Butangen 20, N-4639 Kristiansand S (NO).
- (72) Inventors: **BJØRNEKLETT, Børge**; Vollsveien 216, N-1359 Eiksmarka (NO). **HANSSON, Per Martin Erik**;
Sandlyckans väg 104, S-429 32 Kullavik (SE). **SOLBERG, Stian**; Grønland 54, N-3045 Drammen (NO).
- (74) Agent: **ZACCO NORWAY AS**; P.O. Box 2003 Vika,
Haakon VII's gt. 2, 0125 Oslo (NO).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: A RISER CONNECTOR ASSEMBLY




Fig. 19

(57) Abstract: A riser connector assembly (6) for connecting two riser sections (5a, b) in an end-to-end relationship comprises a first connector assembly portion (6a), a second connector assembly portion (6b), and a locking ring (11) rotatably connected to the first connector assembly portion (6a). Locking members are configured and arranged to selectively and releasably interlock by relative rotation between the first connector assembly portion (6a) and the locking ring (11) and the second connector assembly portion (6b). The locking ring (11) is rotatable between a first position where all said locking members are interlocked, a second position where the first locking members (20, 21) and the third locking members (25, 26) are interlocked but the second locking members (19) and the fourth locking members (24) not interlocked, and a third position where none of said locking members are interlocked and the locking ring (11) is removable from the first connector assembly portion (6a). At least one of the assembly portions (6a, b) comprises alignment means (27).



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

(88) **Date of publication of the international search report:**
17 December 2015