

DESCRIPTION

SPIRAL TYPE SEAWATER DESALINATION APPARATUS

5 TECHNICAL FIELD

[0001] The present invention relates to a spiral type seawater desalination apparatus capable of reducing the fluctuation in reverse osmosis membrane elements housed in a pressure vessel.

10

BACKGROUND ART

[0002] An evaporation method by which seawater is evaporated, and a reverse osmosis method by which seawater is pressurized to pass through a type of a filtration
15 membrane called a reverse osmosis membrane (RO membrane) to filter fresh water while the salt content of the seawater is concentrated and discharged, have been used as conventional methods to obtain fresh water from seawater that is raw water.

20 The later reverse osmosis method is superior to the evaporation method in energy efficiency. However, the reverse osmosis method has such problems that a careful pretreatment (a treatment using "an ultrafiltration membrane (UF membrane)" or "a microfiltration membrane (MF
25 membrane)" that reduces a turbid content in seawater that is raw water) is required so as not to clog the RO membrane with microorganisms and deposits in seawater, and that maintenance or the like is costly.

[0003] Examples of reverse osmosis membrane apparatuses
30 include: a "hollow string membrane" type reverse osmosis membrane apparatus molded into a hollow string-like shape with a substantially pasta-sized width, and filters from outside to inside; and a "spiral membrane" type reverse

osmosis membrane apparatus in which a sheet of a filtration membrane is overlaid with a strong mesh support to keep its strength with their edges bonded to form an envelope, the envelope is then wound in a Swiss roll fashion, and
5 pressure is applied from its cross-section direction. For the pressure application, for example, high-pressure pumps such as turbine pumps and plunger pumps are used.

[0004] The reverse osmosis method has difficulty to obtain water quality as high as that obtained by the
10 evaporation method. Therefore, a plurality of reverse osmosis membrane apparatuses needs to be combined to obtain high purity water quality.

An embodiment of a seawater desalination apparatus of a conventional spiral reverse osmosis membrane apparatus is
15 represented in Fig. 8 (Patent Document 1: Japanese Patent Application Laid-open No. 2001-137672).

[0005] As shown in Fig. 8, a reverse osmosis membrane module unit is constituted with a plurality of reverse osmosis membrane modules 103 (three modules in this
20 embodiment) provided in parallel through a permeated water pipe 104. Each of the reverse osmosis membrane modules 103 has a plurality of reverse osmosis membrane elements 101 that is serially connected to each other and is housed in a cylindrical pressure vessel 102.

25 In Fig. 8, numeral 105 denotes raw water (supplying water), 106 denotes permeated water, 107 denotes concentrated water, and 115 denotes a brine seal.

[0006] As shown in Fig. 9, for example, each of the reverse osmosis membrane elements 101 has a structure in
30 which an envelope-shaped reverse osmosis membrane 113 including a passage material 112 is wound spirally with a mesh spacer 114 around a collecting pipe 111, and the brine seal 115 is provided at one end of the reverse osmosis

membrane element 101. Each of the reverse osmosis membrane elements 101 leads supplying water (sea water) 116 with a predetermined pressure supplied from the front-side brine seal 115 into the space between adjacent surfaces of the envelope-shaped reverse osmosis membrane 113 through the mesh spacer 114 in turn. Permeated water (fresh water) 117 passed through the reverse osmosis membrane 113 by reverse osmosis is brought out from a rear seal 118 through the collecting pipe 111. Concentrated water 119 is also brought out from the rear side of the reverse osmosis membrane element 101.

[0007] When using such a spiral reverse osmosis membrane element 101 for seawater desalination, about six to eight of the reverse osmosis pressure membrane elements 101 are housed in a single pressure vessel 102 to be used.

[0008] A Christmas tree type reverse osmosis (RO) device constructed with a plurality of elements has also been developed (Patent Document 2: Japanese Patent Application Laid-open No. 2007-125527).

[0009] The reasons the elements are housed in the pressure vessel 102 are described below.

1) When the number of reverse osmosis membrane elements 101 housed in a single pressure vessel 102 is increased to reduce the number of pressure vessels 102, the number of high pressure branched pipes is reduced, which cuts construction costs.

2) Reducing the number of pressure vessels 102 installed leads to the reduction of an installation area required.

3) By reducing the number of pressure vessels 102, a supplying water amount flown into a single reverse osmosis membrane element 101 averagely increases. Because of this, concentration polarization phenomenon, by which the concentration is elevated at a membrane surface, can be

suppressed to improve desalination performance.

[0010] Patent Document 1: Japanese Patent Application
Laid-open No. 2001-137672

5 Patent Document 2: Japanese Patent Application Laid-
open No. 2007-125527

DISCLOSURE OF INVENTION

PROBLEM TO BE SOLVED BY THE INVENTION

10 [0011] When the number of reverse osmosis membrane
elements 101 housed in a single pressure vessel 102 is
increased (ten elements, for example), the difference
between the water quality flown in the front reverse
osmosis membrane element (1-th) and the water quality flown
15 in the rearmost reverse osmosis membrane element (10-th)
increases. This results in a problem as shown in Fig. 10.
The amount of the produced water obtained from the rearmost
reverse osmosis membrane (10-th) is extremely smaller than
the amount of the produced water obtained from the front
20 reverse osmosis membrane (1-th).

[0012] As shown in Fig. 10, the membrane of the front
reverse osmosis membrane element (1-th) produces a larger
amount of permeated water than the membranes of other
elements. As a result, only the front membrane is
25 extremely likely to be stained. On the other hand, the
membrane of the rearmost reverse osmosis membrane element
(10-th) produces the extremely small amount of permeated
water, which leads to a problem that the membrane cannot be
utilized effectively.

30 [0013] Therefore, the fluctuation of the using condition
of the individual reverse osmosis membrane element 101
increases, so that the reverse osmosis membrane element 101
becomes inefficient as a whole. Thus, it is currently

general to house, in a single pressure vessel 102, equal to or less than eight elements, more preferably equal to or less than six elements.

[0014] For the above reason, a spiral type seawater
5 desalination apparatus capable of reducing the fluctuation in the reverse osmosis membrane elements 101, of increasing the housing number of reverse osmosis membrane elements 101 housed in a single pressure vessel 102, and of increasing the production efficiency of seawater desalination, has
10 been desired to be developed.

[0015] The present invention has been made in view of the problems, and an object thereof is to provide a spiral type seawater desalination apparatus capable of reducing the fluctuation in reverse osmosis membrane elements housed
15 in a pressure vessel.

MEANS FOR SOLVING PROBLEM

[0016] According to an aspect of the present invention, an spiral type seawater desalination apparatus includes: a
20 spiral type pressure vessel in which a plurality of reverse osmosis membrane elements having spiral reverse osmosis membranes to obtain permeated water by reducing a salt content from raw water is connected through a permeated water pipe; a raw water supplying line that supplies the
25 raw water into the pressure vessel; a concentrated water discharging line through which concentrated water concentrated in the pressure vessel is discharged to exterior; a plug that blocks the permeated water pipe at a center of the reverse osmosis membrane elements in the
30 pressure vessel; a front-side permeated water line and a rear-side permeated water line through which front-side permeated water and rear-side permeated water are discharged to exterior, respectively, which are separated

fore and aft, respectively, at the permeated water pipe blocked by the plug; a pressure regulating valve that is mounted in the raw water supplying line supplying the raw water and regulates a supply pressure of the raw water; a
5 flow regulating valve that is mounted in the concentrated water discharging line through which the concentrated water is discharged, and regulates a discharge flow rate of the concentrated water; and a pressure regulating valve that is mounted in the front-side permeated water line through
10 which the front-side permeated water is discharged, and regulates a flow rate of the front-side permeated water.

[0017] Advantageously, the spiral type seawater desalination apparatus further includes a second reverse osmosis membrane apparatus that is mounted in the front-
15 side permeated water line and produces permeated water through a reverse osmosis membrane using the front-side permeated water with high pressure.

[0018] Advantageously, in the spiral type seawater desalination apparatus, concentrated water obtained from
20 the second reverse osmosis membrane apparatus is returned to the raw water supplying line.

[0019] Advantageously, the spiral type seawater desalination apparatus further includes an energy recovery apparatus that is mounted in the front-side permeated water
25 line and recovers energy of the front-side permeated water with high pressure. The pressure regulating valve that is mounted in the front-side permeated water line is replaced with a flow regulating valve.

[0020] Advantageously, in the spiral type seawater desalination apparatus, a three-way valve is interposed
30 between the flow regulating valve that is mounted in the front-side permeated water line and the energy recovery apparatus.

[0021] Advantageously, the spiral type seawater desalination apparatus further includes: a pressure conversion apparatus that converts pressure energy of the front-side permeated water into pressure energy of the rear-side permeated water; and a second reverse osmosis membrane apparatus that produces permeated water through a reverse osmosis membrane using the rear-side permeated water whose pressure is increased.

[0022] Advantageously, in the spiral type seawater desalination apparatus, a three-way valve is interposed between the flow regulating valve that is mounted in the front-side permeated water line and the pressure conversion apparatus.

15 EFFECT OF THE INVENTION

[0023] According to the present invention, the fluctuation in reverse osmosis membrane elements can be reduced, and the number of reverse osmosis membrane elements housed in a single pressure vessel can be increased (ten elements, for example), which enables to increase the production efficiency of seawater desalination.

[0024] When substantially the same number of reverse osmosis membrane elements as before (six to eight elements) are housed in the pressure vessel to be used, the fluctuation in the reverse osmosis membrane elements housed in a single pressure vessel can be reduced. The amount of the produced water obtained from the front element is reduced so that the element becomes hard to be stained, and the rearmost element is also used more effectively, which enables to prolong the life of a membrane and to reduce the washing frequency of the membrane. Furthermore, the number of pressure vessels in a whole desalination plant can be reduced by as much as the room is made in the front element.

BRIEF DESCRIPTION OF DRAWINGS

[0025] [Fig. 1] Fig. 1 is a schematic of a spiral type seawater desalination apparatus according to a first
5 embodiment.

[Fig. 2] Fig. 2 is a schematic of a spiral type seawater desalination apparatus according to a second embodiment.

[Fig. 3] Fig. 3 is a schematic of a spiral type
10 seawater desalination apparatus according to a third embodiment.

[Fig. 4] Fig. 4 is a schematic of a spiral type seawater desalination apparatus according to a fourth embodiment.

15 [Fig. 5] Fig. 5 is a schematic of another spiral type seawater desalination apparatus according to the third embodiment.

[Fig. 6] Fig. 6 is a schematic of another spiral type seawater desalination apparatus according to the fourth
20 embodiment.

[Fig. 7] Fig. 7 is a graph of the amount of the produced water obtained from each element in the spiral type seawater desalination apparatus according to the first embodiment.

25 [Fig. 8] Fig. 8 is a schematic of the seawater desalination apparatus of a spiral reverse osmosis membrane apparatus according to a conventional art.

[Fig. 9] Fig. 9 is a part exploded schematic of the spiral reverse osmosis membrane apparatus according to a
30 conventional art.

[Fig. 10] Fig. 10 is a graph of the amount of the produced water obtained from each element in the spiral type seawater desalination apparatus according to a

conventional art.

BEST MODE(S) FOR CARRYING OUT THE INVENTION

[0026] The present invention will be described in detail
5 with reference to the accompanying drawings. The present
invention is not limited to the embodiments. Constituting
elements of the embodiments include elements readily
convertible by a person skilled in the art, or elements
being substantially the same as those.

10

First Embodiment

[0027] A spiral type seawater desalination apparatus
according to an embodiment of the present invention will be
described with reference to the accompanying drawings. Fig.
15 1 is a schematic of a spiral type seawater desalination
apparatus according to a first embodiment.

As shown in Fig. 1, a spiral type seawater
desalination apparatus (desalination apparatus) 10A
includes: a spiral type pressure vessel (pressure vessel)
20 15 in which a plurality of reverse osmosis membrane
apparatuses (hereinafter, "desalination elements" or
"elements") 13-1 to 13-10 having spiral reverse osmosis
membranes (RO membranes) to obtain permeated water 12 that
is fresh water by reducing a salt content from raw water
25 (seawater) 11 that is supplying water, is connected through
a permeated water pipe 14, and is housed in a connected
state; a raw water supplying line L_1 through which the raw
water 11 is supplied into the pressure vessel 15; a
concentrated water discharging line L_2 through which
30 concentrated water 16 concentrated in the pressure vessel
15 is discharged; a plug 17 that blocks the permeated water
pipe 14 at the center of the reverse osmosis membrane
apparatuses 13-1 to 13-10 in the pressure vessel 15; a

front-side permeated water line L_3 and a rear-side permeated water line L_4 through which front-side permeated water 12-1 and rear-side permeated water 12-2 are discharged to the exterior, respectively, which are separated fore and aft, respectively, of the permeated water pipe 14 blocked by the plug 17; a pressure regulating valve 20 that is mounted in the raw water supplying line L_1 and regulates the supply pressure of the raw water 11 (70 kg/cm²); a flow regulating valve 21 that is mounted in the concentrated water discharging line L_2 and regulates the discharge flow rate of the concentrated water; and a flow regulating valve 22 that is mounted in the front-side permeated water line L_3 and regulates the pressure of the front-side permeated water 12-1 (10 kg/cm² to 15 kg/cm²). In Fig. 1, numerals 23 to 25 denote flowmeters.

The elements are substantially the same as the elements in Fig. 9 as described above. Each of the elements leads the raw water 11 with a predetermined pressure supplied from the front-side brine seal into between the space between adjacent surfaces of the envelope-shaped RO membrane through a mesh spacer in turn. Permeated water (fresh water) 12 passed through the RO membrane by reverse osmosis is brought out from the rear seal through the permeated water pipe 14. The membranes are shown as sloped lines for convenience of drawing.

[0028] In the present embodiment, the plug 17 provided at the center of the pressure vessel 15 separates supplying water into an upstream side (raw water supplying water side) and a downstream side (concentrated water discharging side).

Therefore, the front-side permeated water 12-1 and the rear-side permeated water 12-2 can be obtained separately from the pressure vessel 15 through reverse osmosis

membrane apparatuses (elements) 13-1 to 13-5 arranged at the front side and reverse osmosis membrane apparatuses (elements) 13-6 to 13-10 arranged at the rear side of the plug 17.

5 Providing the plug 17 allows applying a different back pressure to the permeated water 12 obtained from the front elements and the rear elements.

 The flow regulating valve 22 is mounted in the front-side permeated water line L_3 for the front-side permeated
10 water 12-1 obtained from the front elements that produce the permeated water 12 readily.

[0029] The desalination operation is performed as follows.

 (Step 1) A pump 18 is started to supply the raw water 11
15 into the pressure vessel 15. The flow rate of the concentrated water 16 is regulated by the flow regulating valve 21 that is mounted in the concentrated water discharging line L_2 so as to be a set value (70 kg/cm^2 , for example).

20 (Step 2) The pressure at the inlet of the RO membrane in the pressure vessel 15 (60 kg/cm^2 to 70 kg/cm^2 , for example) is regulated by the pressure regulating valve 20 that is mounted in the raw water supplying line L_1 , so that the permeated water 12 reaches a design value.

25 (Step 3) The back pressure (10 kg/cm^2 to 15 kg/cm^2 , for example) is applied, so that the flow rate of the rear-side permeated water 12-2 obtained from the pressure vessel 15 through the rear-side permeated water line L_4 reaches a set value, by regulating the flow rate by the flow regulating
30 valve 22 that is mounted in the front-side permeated water line L_3 .

[0030] The back pressure is applied to the front-side permeated water 12-1. As a result of this, it is difficult

for the front-side permeated water 12-1 obtained from the front elements (13-1 to 13-5) to be discharged. Therefore, as shown in Fig. 7, the fluctuation between the front elements (13-1 to 13-5) and the rear elements (13-5 to 13-10) can be reduced.

Because of this, the fluctuation of each element can be alleviated as compared with that in Fig. 10 that indicates the case where successive connecting type elements are installed as is conventionally done.

Furthermore, even if seven or more elements are housed in the pressure vessel 15, membranes can be utilized effectively because the amount of the permeated water (amount of the produced water) increases.

[0031] According to the present invention, the number of RO membranes to be housed in a single pressure vessel 15 can be increased, which enables to reduce the construction costs and the installation area.

Even if a similar number of elements as before (six to eight elements) are housed in the pressure vessel 15, by enabling to reduce the fluctuation in the reverse osmosis membrane elements 13-1 to 13-10 housed in a single pressure vessel 15, the front element 13-1 produces less water to be unlikely stained, and the rearmost element 13-10 is used effectively. As a result, the prolonging life of a membrane and the reduction of the washing frequency of the membrane can be expected. Furthermore, the number of pressure vessels 15 housed can be reduced by as much as the room is made in the front element 13-1.

Second Embodiment

[0032] A spiral type seawater desalination apparatus according to an embodiment of the present invention will be described with reference to the accompanying drawings. Fig.

2 is a schematic of a spiral type seawater desalination apparatus according to a second embodiment.

As shown in Fig. 2, a spiral type seawater desalination apparatus 10B includes, in addition to the apparatus shown in Fig. 1, a second reverse osmosis membrane apparatus 30 that is mounted in the front-side permeated water line L₃ and provides second permeated water 12-3 using the front-side permeated water 12-1 with a high pressure (15 kg/cm²). In the figure, numeral 26 denotes a flowmeter, 31 denotes the concentrated water obtained from the second reverse osmosis membrane, and 32 denotes a flow regulating valve that regulates the flow rate of the concentrated water obtained from the second reverse osmosis membrane. A first reverse osmosis membrane apparatus relative to the second reverse osmosis membrane apparatus 30 means the reverse osmosis membrane elements 13-1 to 13-10 housed in the pressure vessel 15 (hereinafter the same meaning shall apply).

In this apparatus, the front-side permeated water 12-1 has a high pressure (15 kg/cm²), so that desalination is performed at the second reverse osmosis membrane apparatus 30 by utilizing the pressure effectively.

The more desalinized second permeated water 12-3 can be obtained by performing desalination by the second reverse osmosis membrane apparatus 30. The second reverse osmosis membrane apparatus 30 may be either of a hollow string membrane type or a spiral type.

[0033] In the present embodiment, the pressure regulating valve 20 installed in the front-side permeated water line L₃ for the front-side permeated water 12-1 applies a back pressure, so that the permeated water 12 obtained from the front elements 13-1 to 13-5 is difficult to be discharged. As a result of this, the fluctuation of

the elements between the front side and the rear side can be reduced.

[0034] In the first embodiment, the back pressure of the front-side permeated water 12-1 is consumed at the valve.

5 However, in the present embodiment, the second reverse osmosis membrane apparatus 30 treats the front-side permeated water 12-1 once again by using its back pressure. Therefore, the more desalinized high-purity second permeated water 12-3 can be obtained.

10 [0035] Typically, two pumps are required to apply pressure when a treatment is performed using reverse osmosis membrane apparatuses in two steps. In the present embodiment, only a single pump 18 is required, so that the system efficiency is improved.

15 [0036] The concentrated water 31 obtained from the second reverse osmosis membrane apparatus 30 is dilute compared with the raw water 11. Therefore, the raw water 11 that is supplying water is diluted by circulating the concentrated water 31 to the inlet side of the pump 18. As
20 a result, a process in which energy consumption is lower during desalination can be attained.

Third Embodiment

[0037] A spiral type seawater desalination apparatus
25 according to an embodiment of the present invention will be described with reference to the accompanying drawings. Fig. 3 is a schematic of a spiral type seawater desalination apparatus according to a third embodiment.

As shown in Fig. 3, a spiral type seawater
30 desalination apparatus 10C includes, in addition to the apparatus shown in Fig. 1, an energy recovery apparatus 41 that is mounted in the front-side permeated water line L_3 and recovers the energy of the front-side permeated water

12-1 with a high pressure (15 kg/cm²).

[0038] The front-side permeated water 12-1 has a high pressure (15 kg/cm²), so that the energy recovery apparatus 41 utilizes pressure energy effectively.

5 The energy recovery apparatus 41 is installed in the front-side permeated water line L₃ connected to the front elements 13-1 to 13-5 from which the permeated water 12 is obtained readily. The recovered energy can be utilized for, for example, the operation performed by the first reverse
10 osmosis membrane apparatus.

[0039] Examples of the energy recovery apparatus 41 that can be used include a known recovery apparatus such as a Pelton Wheel energy recovery apparatus, a Turbocharger energy recovery apparatus, a Pressure Exchanger (PX) energy
15 recovery apparatus, and a Dual Work Exchanger Energy Recovery (DWEER) energy recovery apparatus.

[0040] The PX energy recovery apparatus alleviates the load of the pump 18 by switching the direction of the piston flow of the front-side permeated water 12-1 in the
20 cylinder of a plurality of revolver-shaped cylindrical rotary bodies to transmit the flow to the raw water 11, thereby utilizing the exchanged pressure (15 kg/cm²).

[0041] The DWEER energy recovery apparatus uses a plurality of cylindrical pressure vessels. In each
25 cylinder, the front-side permeated water 12-1 and the raw water 11 are partitioned by partition walls, and the flow direction is switched alternately to transmit one pressure (15 kg/cm²) to the other. Thus, the load of the pump 18 is alleviated by utilizing the exchanged pressure (15 kg/cm²).

30

Fourth Embodiment

[0042] A spiral type seawater desalination apparatus according to an embodiment of the present invention will be

described with reference to the accompanying drawings. Fig. 4 is a schematic of a spiral type seawater desalination apparatus according to a fourth embodiment.

As shown in Fig. 4, a spiral type seawater
5 desalination apparatus 10D includes, in addition to the apparatus shown in Fig. 1, an energy conversion apparatus 50 mounted in the front-side permeated water line L₃ that converts the energy of the front-side permeated water 12-1 with a high pressure (15 kg/cm²) into the energy of the
10 rear-side permeated water 12-2.

[0043] The energy of the front-side permeated water 12-1 with a high pressure (15 kg/cm²) is converted into the energy of the rear-side permeated water 12-2 obtained from the rear elements by installing the energy conversion
15 apparatus 50 that converts the pressure directly. By utilizing the pressure (15 kg/cm²), the converted energy may be used for the treatment by the second reverse osmosis membrane apparatus 30.

[0044] Examples of the energy conversion apparatus 50
20 that can be used include a PX energy recovery apparatus and a DWEER energy recovery apparatus.

[0045] The PX energy recovery apparatus switches the direction of the piston flow of the front-side permeated water 12-1 in the cylinder of a plurality of revolver-
25 shaped cylindrical rotary bodies to transmit the flow to the rear-side permeated water 12-2. The exchanged pressure (15 kg/cm²) is utilized for the desalination by the second reverse osmosis membrane apparatus 30.

Treating the rear-side permeated water 12-2 improves
30 desalination performance as a whole process, because the water quality of the rear-side permeated water 12-2 (a salt concentration of 300 mg/L) is worse than the water quality of the front-side permeated water 12-1 (150 mg/L).

[0046] The DWEER energy recovery apparatus uses a plurality of cylindrical pressure vessels. In each cylinder, the front-side permeated water 12-1 and the rear-side permeated water 12-2 are partitioned by partition walls, and the flow direction is switched alternately to transmit one pressure (15 kg/cm²) to the other.

[0047] As shown in Fig. 5 and Fig. 6, the desalination apparatuses 10C and 10D include three-way valves 42 between the front-side permeated water 12-1 and the energy recovery apparatus 41 (or the energy conversion apparatus 50) to ease the control of the start-up. In Fig. 5 and Fig. 6, numeral 27 denotes the flowmeter of discharging water 43.

When starting the pump 18, the whole flow is set to be flown to the discharging water 43 side, and after the rear-side permeated water 12-2 is obtained, the flow is set to flow gradually into the energy recovery apparatus 41 (or the energy conversion apparatus 50) by operating the three-way valves 42.

In this case, at Step 2, the pressure regulating valve 20 installed at the raw water 11 side controls the sum of the permeated water 12 and the discharging water 43 to be a set value.

[0048] As a result of this, also when the energy recovery apparatus 41 or the energy conversion apparatus 50 is installed, the desalination with high energy efficiency is available.

INDUSTRIAL APPLICABILITY

[0049] As described above, with the desalination apparatus according to the present invention, the fluctuation in reverse osmosis membrane elements can be reduced, and the number of reverse osmosis membrane elements housed in a single pressure vessel can be

increased, which improves the production efficiency of seawater desalination.

EXPLANATIONS OF LETTERS OR NUMERALS

- 5 [0050] 10A to 10D spiral type seawater desalination apparatus
- 11 raw water (seawater)
- 12 permeated water
- 12-1 front-side permeated water
- 10 12-2 rear-side permeated water
- 13 (13-1 to 13-10) reverse osmosis membrane apparatus having spiral reverse osmosis membrane (RO membrane) (desalination element)
- 14 permeated water pipe
- 15 15 pressure vessel
- 16 concentrated water
- 17 plug
- 20 pressure regulating valve
- 21, 22 flow regulating valve

CLAIMS

1. A spiral type seawater desalination apparatus comprising:

5 a spiral type pressure vessel in which a plurality of reverse osmosis membrane elements having spiral reverse osmosis membranes to obtain permeated water by reducing a salt content from raw water is connected through a permeated water pipe;

10 a raw water supplying line that supplies the raw water into the pressure vessel;

a concentrated water discharging line through which concentrated water concentrated in the pressure vessel is discharged to exterior;

15 a plug that blocks the permeated water pipe at a center of the reverse osmosis membrane elements in the pressure vessel;

20 a front-side permeated water line and a rear-side permeated water line through which front-side permeated water and rear-side permeated water are discharged to exterior, respectively, which are separated fore and aft, respectively, at the permeated water pipe blocked by the plug;

25 a pressure regulating valve that is mounted in the raw water supplying line supplying the raw water and regulates a supply pressure of the raw water in association with a flow rate of the front- and rear-side permeated waters respectively discharged from the front- and rear-side permeated water lines;

30 a flow regulating valve that is mounted in the concentrated water discharging line through which the concentrated water is discharged, and regulates a discharge flow rate of the concentrated water in association with a flow rate of the concentrated water; and

35 a pressure regulating valve that is mounted in the front-side permeated water line through which the front-side permeated water is discharged, and regulates a flow rate of the front-side permeated water in association with a flow rate of the rear-side permeated water.

2. The spiral type seawater desalination apparatus according to claim 1, further comprising:

a second reverse osmosis membrane apparatus that is mounted in the front-side permeated water line and produces permeated water through a reverse osmosis membrane using the front-side permeated water with high pressure.

3. The spiral type seawater desalination apparatus according to claim 2, wherein concentrated water obtained from the second reverse osmosis membrane apparatus is returned to the raw water supplying line.

4. The spiral type seawater desalination apparatus according to claim 1, further comprising:

an energy recovery apparatus that is mounted in the front-side permeated water line and recovers energy of the front-side permeated water with high pressure, wherein

the pressure regulating valve that is mounted in the front-side permeated water line is replaced with a flow regulating valve.

5. The spiral type seawater desalination apparatus according to claim 4, wherein a three-way valve is interposed between the flow regulating valve that is mounted in the front-side permeated water line and the energy recovery apparatus.

6. The spiral type seawater desalination apparatus according to claim 1, further comprising:

a pressure conversion apparatus that converts pressure energy of the front-side permeated water into pressure energy of the rear-side permeated water; and

a second reverse osmosis membrane apparatus that produces permeated water through a reverse osmosis membrane using the rear-side permeated water whose pressure is increased.

7. The spiral type seawater desalination apparatus

according to claim 6, wherein a three-way valve is interposed between the flow regulating valve that is mounted in the front-side permeated water line and the pressure conversion apparatus.