

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 October 2001 (11.10.2001)


PCT

(10) International Publication Number
WO 01/75474 A2

- (51) International Patent Classification⁷: **G01S 7/527**, (72) **Inventors: SADOK, Mokhtar, M.**; 23 South Maple Street, Vergennes, VT 05491 (US). **DURKEE, Scott, Robert**; P.O. Box 89, Lime Kiln Road, New Haven, VT 05472 (US).
G01F 23/00
- (21) International Application Number: PCT/US01/10174
- (22) International Filing Date: 30 March 2001 (30.03.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/539,153 30 March 2000 (30.03.2000) US
- (71) Applicant: **SIMMONDS PRECISION PRODUCTS, INC.** [US/US]; 3 Coliseum Centre, 2550 West Tyvola Road, Charlotte, NC 28217 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR DISCRIMINATING ULTRASONIC ECHOES USING WAVELET FUNCTION PROCESSING



(57) Abstract: A method of and apparatus for discriminating among ultrasonic echoes reflected from various objects in a tank containing liquid is disclosed. Ultrasonic signals are generated from an ultrasonic transducer into liquid contained in a tank. Ultrasonic echoes are received by the transducer from various objects in the tank including a surface of the liquid in response to the generated ultrasonic signal and are converted into electrical echo signals representative thereof. Data samples of the electrical echo signals are generated and processed by a signal processor using wavelet function processing to generate wavelet coefficients thereof in a wavelet domain. The wavelet coefficients of the echo data samples are used to discriminate the ultrasonic echoes reflected from the various objects in or part of the tank. In one embodiment, echoes reflected from the liquid surface are discriminated from echoes reflected from other objects based on the wavelet coefficients of the echo data samples of each. In another embodiment, energy of each of the ultrasonic echoes determined from the wavelet coefficients thereof is used to discriminate the ultrasonic echoes from the various reflective surfaces.



patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*