

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International BureauRTMP
COPY

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B43L 19/00, A45D 40/26	A1	(11) International Publication Number: WO 97/21554 (43) International Publication Date: 19 June 1997 (19.06.97)
(21) International Application Number: PCT/US96/19885 (22) International Filing Date: 12 December 1996 (12.12.96) (30) Priority Data: 9525696.2 ✓ 15 December 1995 (15.12.95) ✓ GB (71) Applicant (for all designated States except US): THE GILLETTE COMPANY [US/US]; Prudential Tower Building, Boston, MA 02199 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): LIGHTFOOT, Mark, Roger [GB/GB]; 41 Markby Way, Lower Earley, Reading, Berkshire RG6 3BG (GB). (74) Agents: GALLOWAY, Peter, D.; Ladas & Parry, 26 West 61st Street, New York, NY 10023 (US) et al.	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: FLUID APPLICATORS

(57) Abstract

An applicator for applying a fluid to a surface comprises an applicator tip element (5) connected to the end of a substantially rigid stem (1) by a part (3) capable of flexing resiliently as the applicator tip element is stroked across a surface. The application element is conveniently formed as a pad or a moulded member of porous material e.g. foam, which can be attached in various ways, e.g. by means of adhesive, heat welding or mechanical fixing, to the resiliently flexible connection part.

