DEVICE FOR THE HANDLING OF SURGICAL INSTRUMENTS

Subject of the Invention

The present invention relates to a device which allows surgical instruments, such as an endoscope, to be handled, that is to say positioned and displaced, during a surgical operation.

Prior Art

For many years there have been aids taking the form of mechanical devices capable of carrying surgical instruments intended for assisting the surgeon during operations.

Improvements have been made to these aids, so that these devices can be displaced and can, where appropriate, actuate these surgical instruments, particularly scopes.

These devices are essentially intended for keeping the surgeon's hands free, so that he no longer has to break off performing an act in order, for example, to displace the scope or has to entrust the handling of the latter to an assistant.

However, most of the various known devices do not afford accuracy in the positioning of the instrument and stability in holding and/or displacing it which are sufficient for uses in the medical field, such as surgical acts.

In particular, an endoscope stabilization device is known, as published in the document US-5184601, which comprises an independent bracket provided with a multiple-axis robot which makes it possible to execute rotational movements about vertical axes in order to cover a horizontal plane (XY) parallel to the patient. This device has the disadvantages of requiring a combination of a plurality of movements, in order to displace a scope in the directions and orientations desired by the surgeon, and of obstructing

the surgeon's range of action by the presence of arms which are displaced in the horizontal plane (XY) above the patient.

The document WO94/26167 also discloses a positioning device intended for carrying an instrument for laparoscopic surgery uses which provides a spherical centre of rotation of the said instrument, this centre being formed, for example, by the point of penetration into the patient's stomach. It is found, however, that this device will not make it possible to execute a translational movement along the axis of the instrument, which movement must be made possible so that a scope can be used.

The document WO95/16396 describes a device for the handling of a surgical instrument with the aid of a plurality of successive arms which execute rotations about vertical axes, as proposed above, the device making it possible to obtain an incremental displacement of the head of the scope as a result of a complex and detailed calculation of the various movements of the actuators. However, these movements are obtained by means of three successive changes of Cartesian co-ordinates, thus making the display of the movements relatively complex. In order to provide a decision-making aid to the handling of the instrument, a voice control may also be proposed. This voice control does not, however, make it possible to carry out small rapid and/or high-rate displacements.

The documents EP-A-0293760 and US-A-5 540 649 relate to the same handling device which comprises a vertical foot experiencing a first vertical rotational movement. The second movement is a rotation along an axis orthogonal to the vertical axis. This makes it possible to carry out a displacement of the entire device over the patient himself, thus limiting the surgeon's range of action.

Objects of the Invention

The present invention aims to propose a device for the handling of surgical instruments which is of relatively simple design and has the smallest possible overall size.

Another object of the present invention is to propose a device which as far as possible allows the surgeon's hands to be kept free.

Another object of the present invention is as far as possible to reduce the obstruction of the surgeon's field of action.

Another object of the present invention is to propose a device which makes it possible to have a combination of simple movements reproducing the three fundamental movements involved in exploring the field of vision.

Another object of the present invention is to propose a control device which is simple and of very small overall size, such that it allows other instruments to be handled.

Other objects and advantages will be gathered from a reading of the following descriptive note.

Main characteristic elements of the present invention

The present invention relates to a device for the handling of a surgical instrument, said device being composed of a fixed support element associated with at least:

- a first moveable element articulated on the fixed support element about a first axis essentially parallel to the plane in which the patient is arranged, thus generating a first movement;
- a second moveable element articulated on the end of the first element about a second axis essentially parallel to the plane in which the patient is arranged, thus generating a second movement;
- a deformable third element fastened on one side to the end of the second moveable element and capable

of executing a third rotational movement about a third axis;

- a gripping element fastened to the deformable element on the opposite side to that of the second element;
- a device for securing a surgical instrument to the gripping element; and
- action means making it possible to execute rotational movements about the various axes.

This means, in general terms, that the first and second movements take place about essentially horizontal axes, particularly when the plane in which the patient is arranged is itself horizontal. Preferably, the two horizontal axes are parallel to one another, and their projections in the plane of the patient are orthogonal to the axis of the patient.

Preferably, the first and second moveable elements take the form of articulated arms, whilst the deformable element takes the form of a deformable and articulated quadrilateral.

The second articulated moveable element has two points of articulation, one of which can slide in a slideway and the other of which can be blocked or free.

According to a particular embodiment, the gripping element is arranged in a slideway integral with the deformable element.

The support element is fastened to a rail integral with the operating table with the aid of a fastening device.

According to a first embodiment, this fastening device comprises at least two boxes which execute a first movement orthogonal to the patient's bed and a longitudinal second movement parallel to the patient's bed. A screw makes it possible to carry out the movement of the first box in the second box so as to obtain the first movement which is orthogonal to the patient's bed. The second movement, which is longitudinal, is carried out with the aid of a third box which comprises rolling bearings which slide on a

slideway. The fastening of the device is carried out when one or more screws are tightened, the rail at the same time being clamped between the clamps and a suitable element.

According to another embodiment, the longitudinal movement is carried out with the aid of a plurality of, preferably four rolling bearings using the rail of the operating table as a slideway, a lower clamp making it possible by means of a handwheel to immobilize the assembly as a whole on the said rail.

The fastening device may be reversed by rotation about a vertical axis and is adjusted by sliding along the fastening rail integral with the operating table.

Moreover, according to a preferred embodiment, the handling device comprises a control device which consists of a mini-keyboard with at least six keys for two or three fingers and the inner part of which is of triangular shape. This control device is completely independent and comprises a transmitter which transmits the commands to the main case, this transmitter taking the form of a small case of triangular shape.

Description of the Figures

Figure 1 shows a perspective view of the operating table, on which the patient will be laid and to which the handling device according to the present invention is fastened.

Figures 2 and 3 show a sectional side view of the device for the handling of surgical instruments according to the present invention, for two uses in surgical operations.

Figures 4 and 5 show sectional front views of the device, as shown in Figures 2 and 3.

Figure 6 shows a sectional side view corresponding to that of Figure 2, but making it possible to visualize the various movements of the handling device.

Figures 7 and 8 show a sectional side view and a sectional top view of a fastening device making it possible to fasten the handling device to the patient's bed according to a first embodiment.

Figures 9, 10 and 11 show a second embodiment of the device for fastening the handling device to the patient's bed.

Description of several preferred embodiments of the invention

The handling device according to the present invention is shown in Figure 1 in perspective and is integral with the bed on which the patient will lie down.

The particular advantage of this handling device is that it possesses a range of displacement such that it can be used for two large groups of surgical operations: on the one hand, gynaecological surgical operations and, on the other hand, abdominal surgical operations. It is sufficient, in order to change from one area to the other, simply to overturn the appliance in relation to a vertical plane perpendicular to the axis along which the patient is laid. This means that the appliance is, of course, reversible and that it is sufficient to orient it in the front or rear position in relation to the patient.

Figure 2 more specifically shows the device arranged so as to make it possible to carry out an operation of a gynaecological nature. This means essentially that the endoscope will penetrate into the patient in a position such that it makes it possible to obtain a display of the area where the surgeon will have to operate.

Figure 3 shows the device arranged so as to make it possible to carry out an operation of an abdominal nature. In this case, the endoscope will penetrate into the patient in a position such that it makes it possible to have a display towards the patient's head.

Other kinds of surgical operations, such as orthopaedic operations, are also conceivable.

In Figures 1 to 6, the patient's body is arranged along an axis PP', with the patient's head directed towards P'. 0 represents the point of penetration of the instrument into the patient's stomach. This point generally represents the patient's navel.

As is apparent from the various Figures, this handling device comprises at least the following elements:

- a support (1) (after vertical and longitudinal adjustment) will be fastened to a rail (2) integral with the operating table (3), this fastened support being associated with:
  - a first moveable arm (4) articulated on the fastened support about an essentially horizontal axis H1 perpendicular to the vertical plane passing through the longitudinal axis POP' of the patient;
  - a second moveable arm (5) articulated on the end of the first arm about a second essentially horizontal axis H2, likewise perpendicular to the same plane POP';
  - a deformable element (6) fastened on one side to the end of the second arm (5) and capable of executing a rotational movement about an axis C;
  - a horizontal gripping arm (7) fastened to the opposite side of the quadrilateral (6);
  - a device (8) for securing an instrument (9) to the gripping arm (7);
  - actuators which make it possible to execute rotational movements about the various axes H1, H2 and C mentioned;
  - means for controlling and synchronizing these movements; and
  - a control placed in the palm of the practitioner's hand, enabling him to have access to the various movements by means of a plurality of keys.

The handling device thus makes it possible to displace an instrument (9) by means of movements about two axes of rotation (H1 and H2), parallel to one another and to the patient's bed, and about a third axis of rotation (C).

It can be seen that, according to the present invention, the first rotational movement does not take place about an axis which is perpendicular to the operating table and which, more particularly, is vertical. This thereby makes it possible for the surgeon's range of action to be kept free in a particularly advantageous way.

The combination of the movements makes it possible to obtain the three fundamental movements for exploring the field of vision, as are shown in Table 1.

Table 1

Eye movements	**Movement imparted to the scope**		
	Guidance	**Direction**	**Symbol (+ direction)**
Accommodation (near/far)	Zoom	in/out	ς (i/o)
Vertical rotation (up/down)	Rotation	up/down	ρ (u/d)
Horizontal rotation (left/right)	Lateral	left/right	λ (l/r)

The movements produced will therefore correspond to:

ς (i/o): displacement along the axis of the scope (SS')

ρ (u/d): rotation of the scope in the plane POP' about 0.

λ (l/r): rotation of the scope in the plane S'00' about 0.

Preferably, the second arm (5), for its part, takes the form of one of the sides (BB') of an articulated parallelogram (ABB'A'), as shown in more

detail in Figure 6. The point of articulation (B') can slide along a slideway (51) integral with the arm (5); the position relative to the arm (5) and the length of the arm (BB') may therefore vary.

Two illustrative situations may arise:

- the point of articulation (B) is blocked; the arms and elements (5, 6 and 7) are therefore simply driven about the axis H1 as a result of the rotation of the support (1), and the movement of S' and S is therefore close to ρ:
- the point of articulation (B) is free, but the position of (B') in its slideway is blocked by a solenoid (52): in this case, the movement of the parallelogram (6) driven about the axis H1 as a result of the rotation of the support (1) induces a displacement in the gripping arm (7), and therefore of S' and S, which is close to ς.

This embodiment makes it possible to ensure the movements ρ and ς by means of a single servomotor.

The gripping arm (7) is always horizontal. This makes it possible to limit to the maximum the obstruction caused by the latter in the surgeon's range of action. It is connected to the mechanism and to the patient's bed on the opposite side to the surgeon.

The surgical instrument (9), such as an endoscope, is connected to the gripping arm (7) by means of a passive (non-motorized) joint, so as to reproduce the image which it perceives, and in such a way that it is always oriented correctly relative to the reference axes of the room, that is to say the vertical directions must appear vertical on the monitor. The rotation of the second arm (5) and the deformation of the articulated parallelogram (6) are ensured by two servomotors incorporated in the arm (5).

The fastening of the scope (9) to the gripping arm (7) at S' may be ensured by means of a passive joint consisting at least of two components articulated along the axis (j) perpendicular to the axis (d) of the gripping arm (7) and to SS'.

The component holding the scope is fastened to the latter in a position such that the verticality reference of the image is in the vertical plane passing through (j). The image of the scope will thus appear vertical to an imaginary observer situated at the patient's head and looking parallel to the axis PP'.

The component secured to the gripping arm (7) at S' is snapped onto this gripping arm (7) so as to be capable of rotating freely about the axis (d). This component is designed to be capable of being unsnapped from the gripping arm (7) simply by action on a small lever.

Alternatively, this assembly may usefully be produced in one piece from an elastic material.

The control device of the handling device may consist of a mini-keyboard with six keys for two or three fingers (little finger and ring finger, plus the middle finger in the case of the three-finger version) placed in the palm of the practitioner's hand by means of a suitable holder surrounding the practitioner's hand, characterized in that the inner part (in the palm of the hand) of triangular shape is inscribed within the "trapezium" of the hand between the ball of the thumb and the fold of the four fingers, thus in no way impeding the movements of the hand.

Preferably, the arm (7) gripping the instrument (9) can be adjusted in a slideway (71), so as to arrange S' and therefore S in such a way that they are located in the plane POP'. This constitutes the adjustment of the neutral point of S at the start of the operation. By virtue of this particular feature, the handling device can be adapted to one type of operation or the other: abdominal or gynaecological (see Figures 1 and 2), simply by rotating the fastening device through 180°, reversing it and then adjusting the gripping arm (7) in its slideway (71).

In general terms, the handling device is fastened to a rail (2), itself integral with the

operating table (3), with the aid of a fastening device (100).

According to a first embodiment, a device (100) for fastening the handling device to the operating table is shown in Figures 7 and 8. This device (100) thus makes it possible accurately to adjust the position of the support (1) longitudinally (parallel to the rail (2) of the operating table (3)) and vertically (or, more generally, perpendicularly to the plane in which the patient is arranged).

This device comprises essentially two boxes (101 and 102) produced from metal sheets which are folded and welded to one another and closed, the purpose of which being to make the fastening of the device according to the invention more rigid. The first box (101) makes it possible to fasten the support (1) by the clamping of two knurled thumb screws (105). This box is integral with two nuts (103). A screw (104), which may be actuated manually or even be motorized, allows the box (101) to move within the second box (102) when the screw (104) is turned. This makes it possible to carry out the vertical movement. The originality of this device is the characteristic whereby the two boxes (101 and 102) slide with considerable play because they are produced with the aid of non-machined folded and welded metal sheets. This play will be cancelled by the entire assembly being fixed together particularly rigidly as a result of the clamping of the two knurled thumb screws (105) in the support (1) when the desired vertical position is reached.

The horizontal movement is carried out with the aid of the two nuts (109) integral with the box (102). A screw (110) makes it possible to displace the entire support (1), integral with the two boxes (101 and 102), parallel to the rail (2) of the operating table as far as the required position.

A box (106) likewise produced from folded and welded metal sheets, and which comprises two clamps

(111) secured to the rail (2) of the operating table, is also provided. Rolling bearings (113) likewise fastened to the box (102) slide on a slideway (112) supporting the assembly consisting of the support (1) and of the boxes (101 and 102) during the longitudinal displacement. The originality of this device affords the possibility that, when the screw (108) is tightened, the rail (2) is clamped between the clamps (111) and the element (107). Simultaneously, the nuts (109) are locked between the box (106) and the same element (107), thus cancelling the considerable play of these non-machined components and thereby making the entire assembly particularly rigid.

According to a second embodiment shown in more detail in Figures 9, 10 and 11, the rail (2) is used directly as a slideway by the provision of four orthogonal rolling bearings (121) in the upper part of the rail (2). When the lower clamp (122) is released (in position A, as shown in Figure 10), the lower part of the rail (2) bears directly on a wheel (123) actuable by means of a geared motor (124). This wheel (123) allows displacement along the rail (2). When the lower clamp (122) is blocked by means of the wheel (125) and its screw (in position B, as shown in more detail in Figure 11), the support assembly (1) will be completely immobilized, the geared motor (124) and its wheel (123) being disengaged.



CLAIMS

THIS SHEET HAS BEEN REPLACED

1. Device for the handling of a surgical instrument, characterized in that it comprises a fixed support (1) associated with at least:

- a first moveable element (4) articulated on the fixed support (1) about a first axis (H1) essentially parallel to the plane (PP') in which the patient is arranged and capable of executing a first movement;
- a second moveable element (5) articulated on the end of the first moveable element (4) about a second axis (H2) essentially parallel to the plane (PP') in which the patient is arranged and capable of executing a second movement;
- a deformable element (6) fastened on one side to the end of the second moveable element (5) and capable of executing a third rotational movement about a third axis (C);
- a gripping element (7) fastened to the deformable element (6) on the opposite side to that of the second element;
- a device (8) for securing a surgical instrument (9) to the gripping element (7); and
- action means (10 and 11) making it possible to execute rotational movements about the various axes (H1, H2 and C).

2. Device according to Claim 1, characterized in that the first (4) and second (5) moveable elements take the form of articulated arms, whilst the deformable element (6) takes the form of a deformable and articulated quadrilateral.

3. Device according to Claim 2 ,characterized in that the second moveable element (5) has a point of articulation which can slide in a slideway (51) integral with the deformable element (6), whilst the other point of articulation can be either blocked or free.

This Sheet Has Been Replaced



4. Device according to any one of the preceding claims, characterized in that the gripping element (7) is arranged in a slideway (71) integral with the deformable element (6).

5. Device according to any one of the preceding claims, characterized in that the support element (1) is fastened to a rail (2), integral with the operating table (3), with the aid of a fastening device (100).

6. Device according to Claim 5, characterized in that the fastening device (100) comprises two boxes (101 and 102) executing two movements, a movement orthogonal to the plane (PP') in which the patient is arranged and the movement parallel to the plane (PP') of the patient, the orthogonal movement being carried out with the aid of a screw (104) allowing the first box (101) to be introduced into the second box (102), the longitudinal movement being carried out with the aid of a third box (106) which comprises rolling bearings (113) sliding on a slideway (112), the fastening of the device being carried out when one or more screws (108) are tightened, at the same time with the rail (2) being clamped between the clamps (111) and a suitable element (107).

7. Device according to Claim 5 or 6, characterized in that the longitudinal movement is carried out with the aid of a plurality of, preferably four rolling bearings (121) using the rail (2) as a slideway, a lower clamp (122) making it possible by means of a wheel (125) to immobilize the assembly as a whole on the said rail (2).

8. Device according to any one of the preceding claims 5 to 7, characterized in that the fastening device (100) is reversed as a result of rotation about a vertical axis and is adjusted by sliding along the fastening rail (26a) integral with the operating table (26).

9. Device according to any one of the preceding claims, characterized in that the means (8) for securing the surgical instrument (9) to the gripping

* C L M S *
THIS SHEET HAS BEEN REPLACED
This Sheet Has Been Replaced

element (7) consists of a passive joint which, for its part, comprises at least two components articulated along two axes perpendicular, on the one hand, to the axis of the surgical instrument (9) and, on the other hand, to the axis of the first element (4), and in which the surgical instrument is fastened in a position such that the verticality reference of the image in the vertical plane is ensured.

10. Device according to any one of the preceding claims, characterized in that it comprises a control device (50) which consists of a mini-keyboard (51) with at least six keys (52) for two or three fingers and the inner part of which is of triangular shape.

11. Device according to Claim 10, characterized in that the control device is completely independent and comprises a transmitter which transmits the commands to the main case, this transmitter taking the form of a small case of triangular shape.

12. Use of the device for the handling of a surgical instrument according to any one of the preceding claims for operations of a gynaecological, abdominal or else orthopaedic nature.

THIS SHEET HAS BEEN REPLACED

* C L M S *

This Sheet Has Been Replaced




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10




FIG.11

* C L M S *

REPLACEMENT SHEET
06 JUL 2000

CLAIMS

1. Device for the handling of a surgical instrument, comprising a fixed support (1), a first moveable element (4) linked to said fixed support (1), a second moveable element (5) articulated on one of the ends of the first moveable element (4) and a device for gripping (8) of a surgical instrument (9), characterised in that:

- the first moveable element (4) is articulated on the fixed support (1) about a first axis (H1) essentially parallel to the plane in which the patient is arranged (PP') and capable of executing a first movement;
- the second moveable element (5) is articulated on the end of the first moveable element (4) about a second axis (H2) essentially parallel to the plane in which the patient is arranged (PP') and capable of executing a second movement;

and in that it further comprises:

- a deformable element (6) fastened on one side to the end of the second movable element (5) and capable of executing a third rotational movement about a third axis (C);
- a gripping element (7) fastened on the opposite side to that of the second element to the deformable element (6) and to which a device for gripping (8) is fastened; and
- action means (10 and 11) making it possible to execute rotational movements about the various axes (H1, H2 and C).

* C L M S *

REPLACEMENT SHEET
06 JUL 2000

2. Device according to claim 1, characterized in that the first (4) and the second (5) moveable elements take the form of articulated arms, whilst the deformable element (6) takes the form of a deformable and articulated quadilateral.

3. Device according to claim 2, characterized in that the second moveable element (5) has a point of articulation which can slide in a slideway (51) integral with the deformable element (6), whilst the other point of articulation can be either blocked or free.

4. Device according to any one of the preceding claims, characterized in that the gripping element (7) is arranged in a slideway (71) integral with the deformable element (6).

5. Device according to any one of the preceding claims, characterized in that the support element (1) is fastened to a rail (2), integral with the operating table (3), with the aid of a fastening device (100).

6. Device according to claim 5, characterized in that the fastening device (100) comprises two boxes (101 and 102) executing two movements, a movement orthogonal to the plane in which the patient is arranged (PP') and the movement parallel to the plane of the patient PP', the orthogonal movement being carried out with the aid of a screw (104) allowing the first box (101) to be introduced into the second box (102), the longitudinal movement being carried out with the aid of a third box (106) which comprises rolling bearings (113) sliding on a slideway (112), the fastening of the device being carried out when one or more screws (108) are tightened, at the same time with the rail (2) being clamped between the clamps (111) and a suitable element (107).

7. Device according to claim 5 or 6, characterized in that the longitudinal movement is carried

out with the aid of a plurality of, preferably four rolling bearings (121) using the rail (2) as a slideway, a lower clamp (122) making it possible by means of a wheel (125) to immobilize the assembly as a whole on said rail (2).

8. Device according to any one of the preceding claims 5 to 7, characterized in that the fastening device (100) is reversed as a result of rotation about a vertical axis and is adjusted by sliding along the fastening rail (26a) integral with the operating table (26).

9. Device according to any one of the preceding claims, characterized in that the means for securing (8) the surgical instrument (9) to the gripping element (7) consists of a passive joint which, for its part, comprises at least two components articulated along two axes perpendicular, on the one hand, to the axis of the surgical instrument (9) and, on the other hand, to the axis of the first element (4), and in which the surgical instrument is fastened in a position such that the verticality reference of the image in the vertical plane is ensured.

10. Device according to any one of the preceding claims, characterized in that it comprises a control device (50) which consists of a mini-keyboard (51) with at least six keys (52) for two or three fingers and the inner part of which is of triangular shape.

11. Device according to claim 10, characterized in that the control device is completely independent and comprises a transmitter which transmits the commands to the main case, this transmitter taking the form of a small case of triangular shape.

REPLACEMENT SHEET
06 JUL 2000