

TONER CARTRIDGE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a toner cartridge and a
5 toner refilling device for refilling a developing device with
toner in an image forming apparatus such as electrostatic
copier and facsimile apparatus.

2. Description of the Prior Art

A toner cartridge generally comprises a storing case
10 having a toner dropping opening in the lower surface and
containing toner inside, and a sheet-form seal member closing
the toner dropping opening being peelably adhered to the lower
surface of the storing case.

The toner cartridge is inserted and set in the storing
15 recess of the image forming apparatus main body, and the seal
member is peeled off. As a result, the toner dropping opening
is opened, and the toner in the storing case drops in to
refill the developing device of the image forming apparatus
disposed beneath the storing case.

20 When the toner in the developing device is spent up, the
toner cartridge is drawn out of the storing recess, and a new
toner cartridge is set in the storing recess, so that the used
toner cartridge may be replaced with a new one.

In the storing case of the spent toner cartridge,
25 however, a slight amount of toner is left over, including the



toner depositing on the seal member. Therefore, when drawing out the spent toner cartridge from the storing recess, the remaining toner drops from the toner dropping opening, and the dropping toner scatters about inside and outside the image forming apparatus main body.

To avoid this, it is proposed to use a toner cartridge provided with a slit for inserting the seal member in when stripping off seal member (Japanese Laid-open Utility Model Hei. 3-86371). In this toner cartridge, when the seal member passes through the slit, the toner depositing on the upper surface of the seal member is scraped off by the slit. In this toner cartridge, however, since the slit itself is opened to the outside, when drawing out the spent toner cartridge from the storing recess, the toner depositing on the slip drops and scatters.

Other toner cartridge has been presented (Japanese Laid-open Utility Model Hei. 3-56951), in which a cleaning compartment is provided adjacently to the end of the storing case, and a cleaning roller for cleaning the toner depositing on the upper surface of the seal member when peeling off the seal member is provided in this cleaning compartment. In this toner cartridge, same as in the toner cartridge disclosed in the Japanese Laid-open Utility Model Hei. 3-86371, when drawing out the spent toner cartridge, the toner depositing on the slit may scatter.



In a different toner cartridge hitherto presented, before drawing out the spent toner cartridge, a plate-form shutter member is inserted into the storing recess of the image forming apparatus main body along the lower surface of the toner cartridge, and the toner cartridge is drawn out in a state of preventing dropping of toner by the shutter member. When replacing the toner cartridge, however, the shutter member must be inserted, and it took time and labor in replacing.

The toner scatters away from the toner cartridge also when, aside from the case of drawing out the spent toner cartridge as mentioned above, the seal member is peeled off by mistake if a new toner cartridge is not set correctly in the storing recess of the image forming apparatus main body.

SUMMARY OF THE INVENTION

It is hence a first object of the invention to present a toner cartridge capable of securely preventing scatter of toner when replacing, and replacing easily.

It is a second object of the invention to present a toner refilling device capable of preventing the toner cartridge from being opened unexpectedly, and preventing toner scattering securely.

To achieve the first object, one aspect of the invention presents a toner cartridge having a toner cartridge main body with a toner dropping opening, and detachably set in a storing

This Sheet Has Been Replaced



recess of an image forming apparatus main body comprising:

an inner seal member in a sheet form for closing said toner dropping opening as being peelably attached to the lower surface of said toner cartridge main body,

5 take-up means for releasing the toner dropping opening by taking up while peeling said inner seal member when required,

an outer seal member in a sheet form capable of opening and closing the toner dropping opening beneath said inner seal member, as being slidably provided along the lower surface of
10 said toner cartridge main body, and

outer seal member operating means being provided so as to be engaged with engaging means of the image forming apparatus main body, so as to automatically close said outer seal member when said toner cartridge main body is drawn out from the
15 storing recess in the state of being engaged with the engaging member.

According to this toner cartridge, when the toner cartridge is spent and drawn out from the storing recess of the image forming apparatus main body, the outer seal is
20 automatically closed by the outer seal member operating means. Therefore, when drawing out the spent toner cartridge, the toner does not scatter. Besides, since the outer seal is automatically closed, the replacement work of toner cartridge is very easy.

25 In other preferred aspect, said outer seal member

This Sheet Has Been Replaced



operating means comprises a slide member which crosses said toner dropping opening in a state of fixing one end of said outer seal, and is movable along the lower surface of the toner cartridge main body. This slide member is arrested of
5 its relative move to the image forming apparatus main body when the toner cartridge main body is drawn out from the storing recess in the state of being engaged with the engaging means of the image forming apparatus main body. As a result, when drawing out the toner cartridge main body, the slide
10 member relatively moves to the toner cartridge main body, and releases the outer seal.

To achieve the second object, other aspect of the invention presents a toner refilling device for refilling a predetermined part of an image forming apparatus main body
15 with toner, by a toner cartridge containing toner, being detachably set in a storing recess of the image forming apparatus main body, comprising:

a toner cartridge main body containing toner and forming a dropper dropping opening in the lower surface,
20 a seal member in a sheet form for closing said toner dropping opening as being peelably adhered to the lower surface of said toner cartridge main body,

take-up means provided inside said toner cartridge main body for releasing said toner dropping opening by taking up
25 while peeling said seal member when required,

This Sheet Has Been Replaced



driving force transmitting means containing a drive coupling part that can be coupled with an external driving member for transmitting the driving force of the driving member to said take-up means, and

5 route cut-off means for usually cutting off the driving force transmitting route from the driving member to the take-up means through said driving force transmitting means, and connecting only when the toner cartridge is set in the storing recess.

10 According to this toner refilling device, only when the toner cartridge is set in the storing recess, the driving force transmitting route from the driving member to the take-up means is connected, and while the toner cartridge is not set, the driving force transmitting route is cut off by the
15 route cut-off means. Therefore, when the toner cartridge is not set, the take-up means cannot be driven, thereby avoiding unnecessary peeling of the seal member, so that scatter of toner may be prevented.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Fig. 1A and Fig. 1B are schematic sectional views sequentially showing the steps of mounting of a toner cartridge on the storing recess of an image forming apparatus main body in a first embodiment of the invention.

Fig. 2A and Fig. 2B are schematic sectional views
25 sequentially showing the steps of peeling off the inner seal



member of the toner cartridge mounted on the storing recess.

Fig. 3A and Fig. 3B are schematic sectional views sequentially showing the steps of drawing out the spent toner cartridge from the storing recess.

5 Fig. 4 is a schematic sectional view showing the state just before completion of withdrawal of toner cartridge.

Fig. 5 is a general perspective view of a toner cartridge main body.

Fig. 6 is a perspective exploded view of a toner
10 cartridge main body.

Fig. 7 is a perspective view of an upper casing for composing the upper part of an outer container.

Fig. 8 is a perspective view of an inner container.

Fig. 9 is a perspective view of a lower casing for
15 composing the lower part of the outer container.

Fig. 10 is a longitudinal sectional view of the toner cartridge main body showing the fitting parts of the upper and lower casings.

Fig. 11 is a longitudinal sectional view showing the
20 fitting parts of the upper and lower casings.

Fig. 12 is an essential sectional view of the toner cartridge main body showing the fixed state of the inner container by the upper and lower casings.

Fig. 13 is a partially sectional exploded perspective
25 view of a take-up shaft and a drive coupling shaft.



Fig. 14 is a partially sectional perspective view of a slide member.

Fig. 15 is an essential sectional view of the slide member.

5 Fig. 16 is a longitudinal sectional view of the toner cartridge main body showing the guided state of the slide member.

Fig. 17 is an essential perspective view of the toner cartridge main body showing the state just before the outer
10 seal member is moved to the closing position by the slide member.

Fig. 18 is an essential sectional view of the toner cartridge main body showing the state of the slide member engaged by the closing position stopper member.

15 Fig. 19A and Fig. 19B are schematic sectional views sequentially showing the steps of closure of the storing recess of the image forming apparatus main body by a lid.

Fig. 20 is a partial sectional side view of a slide member moving member.

20 Fig. 21 is an exploded perspective view of the slide member moving member.

Fig. 22 is a schematic sectional view of a driving force transmitting mechanism before the lid of the storing recess is closed.

25 Fig. 23 is a schematic sectional view of the driving



force transmitting mechanism showing the state of the drive coupling shaft being about to be coupled with the take-up shaft in cooperation with the closing action of the lid.

Fig. 24 is a schematic sectional view of the driving
5 force transmitting mechanism showing the state of the drive coupling shaft coupled with the take-up shaft.

Fig. 25 is a schematic sectional view of the driving force transmitting mechanism corresponding to the state in Fig. 22.

10 Fig. 26 is a schematic sectional view of the driving force transmitting mechanism corresponding to the state in Fig. 23.

Fig. 27 is a schematic sectional view sequentially showing the steps corresponding to Fig. 24.

15 Fig. 28A and Fig. 28B are schematic sectional views sequentially showing the steps of insertion of the toner cartridge into the storing recess of the image forming apparatus main body in a second embodiment of the invention.

Fig. 29 is a schematic sectional view showing the step of
20 peeling off the inner seal member of the mounted toner cartridge.

Fig. 30 is a perspective view of a toner cartridge main body.

Fig. 31 is an exploded perspective view of the toner
25 cartridge main body.



Fig. 32 is a perspective view of an upper casing for composing the upper part of an outer container.

Fig. 33 is a perspective view of a lower casing for composing the lower part of the outer container.

5 Fig. 34 is an exploded perspective view of take-up means.

Fig. 35 is a partially sectional perspective view of a slide member.

Fig. 36 is an essential sectional view showing the engaged state of the slide member

10 Fig. 37 is an exploded plan view of a toner cartridge relating to a third embodiment of the invention.

Fig. 38A, Fig. 38B, and Fig. 38C are plan, side and bottom views of the toner cartridge.

Fig. 39A and Fig. 39B are schematic sectional views
15 showing a step of peeling off the inner seal member in an installed state of toner cartridge in a fourth embodiment of the invention, and an intermediate step of withdrawal of a spent toner cartridge.

Fig. 40A and Fig. 40B are schematic sectional views
20 showing the state immediately before and the state immediately after completion of withdrawal of toner cartridge.

Fig. 41 is a schematic perspective view of slide member moving means.

Fig. 42 is a schematic diagram of a toner refilling
25 device in a fifth embodiment of the invention.



Fig. 43 is a schematic diagram showing the set state of toner cartridge.

Fig. 44 is an essential schematic diagram of a toner refilling device in a sixth embodiment of the invention.

5 Fig. 45A and Fig. 45B are essential schematic longitudinal sectional views of a toner refilling device in a seventh embodiment of the invention, Fig. 45A showing the state before setting of toner cartridge, and Fig. 45B showing the set state.

10 Fig. 46 is an essential schematic sectional view of a toner refilling device in an eighth embodiment of the invention.

Fig. 47A, Fig. 47B, and Fig. 47C are essential schematic sectional views of a toner refilling device in a ninth
15 embodiment of the invention, Fig. 47A showing the state before setting of toner cartridge, Fig. 47B showing the set state of toner cartridge, and Fig. 47C showing the state of completion of take-up of seal member.

Fig. 48A and Fig. 48B are essential schematic sectional
20 views of a toner refilling device in a tenth embodiment of the invention, Fig. 48A showing the state before setting of toner cartridge, and Fig. 48B showing the set state of toner cartridge.

Fig. 49A and Fig. 49B are essential schematic sectional
25 views of a toner refilling device in an eleventh embodiment of

This Sheet Has Been Replaced



the invention, Fig. 49A showing the state before setting of toner cartridge, and Fig. 49B showing the set state of toner cartridge.

Fig. 50 is an essential schematic exploded perspective view of a toner refilling device in a twelfth embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the accompanying drawings, some of the preferred embodiments of the invention are described in detail below.

Embodiment 1

The first embodiment of the invention is described below by reference to Fig. 1 through Fig. 23.

General Outline Structure

Fig. 1A shows the state of introduction of front end of a toner cartridge TC into a storing recess 500 provided in an image forming apparatus main body G. Referring to Fig. 1A, this toner cartridge TC comprises i) a toner cartridge main body 1 of double container type consisting of an inner container 10 containing toner T, and an outer container 20 containing the inner container 10, ii) toner dropping openings 10a, 20a formed respectively in the inner container 10 and outer container 20, iii) an inner seal member 30 in sheet form for covering the toner dropping opening 10a of the inner container 10, being peelably adhered to the lower surface of



the inner container 10, iv) an outer seal member 40 in sheet form for opening and closing the toner dropping opening 20a of the outer container, v) a take-up shaft 50 as take-up means for taking up the inner seal member 30 while peeling off from the inner container 10 as shown in Fig. 2B as required, and vi) a slide member 60 for presenting outer seal member operating means for opening and closing the toner dropping opening 20a of the outer container 30 by the outer seal member 40, by sliding along the lower surface of the outer container 20, with one end of the outer seal member 40 in fixed state.

The take-up shaft 50 is designed to be driven by a hand-turning handle H as external driving member, through a drive force transmitting mechanism 90 provided in the image forming apparatus main body G as shown in Fig. 24.

As shown in Fig. 1A and Fig. 1B, the toner cartridge main body 1 is moved in and out of the storing recess 500 along its longitudinal direction. In the bottom near the inlet in the storing recess 500, there is a slide member moving member 80 for opening and closing the outer seal member 40 as being engaged with the slide member 60. The outer seal member 40 is moved to the closing position shown in Fig. 1A and the opening position shown in Fig. 2A, along with the relative move of the slide member 60 engaged with the slide member moving member 80, to the toner cartridge main body 1. In this toner cartridge TC, in the unused state, the outer seal member 40 is



set in the closed state. The slide member 60 automatically releases the outer seal member 40, depending on the insertion action of the toner cartridge TC, as sequentially shown in Fig. 1A, Fig. 1B, and Fig. 2A. The slide member 60 also
5 automatically closes the outer seal member 40, depending on the drawing action of the toner cartridge TC, as sequentially shown in Fig. 3A and Fig. 3B.

Both ends of the toner cartridge main body TC in the longitudinal direction are referred to as lead-in end 1a and
10 drawing end 1b, respectively.

Toner Cartridge Main Body

Referring to Fig. 5 to Fig. 12, the toner cartridge main body 1 is explained below.

First, referring to Fig. 5 and Fig. 6, the outer
15 container 20 is divided into upper and lower halves, an upper casing 200 and a lower casing 250. The both casings 200, 250 are mutually fitted and fixed. Besides, the both casings 200, 250 are fixed in the state of positioning the inner container 10, by inserting a tongue 107 (see Fig. 8) of the inner
20 container 20 into their fitting parts.

The upper casing 200 and lower casing 250 are formed in one body by resin. Referring to Fig. 1A and Fig. 8, the inner container 10 is also formed in one body by resin, and a plug 106 is thermally fused to a toner feed tube 105 formed on the
25 inner container 10.



Referring to Fig. 1A, the upper surface 101 of the inner container 10, and the upper surface 201 of the upper casing 200 of the outer container 20 are parallel at a specific interval, and between these upper surfaces 101, 201, there is
5 a storing space 70 for storing a part of the outer seal member 40 in a nearly upright state as shown in Fig. 2A when required.

When the toner dropping opening 20a of the outer container 20 is released by the outer seal member 40, a part
10 of the outer seal member 40 is guided by the take-up shaft 50 in a state turned upside down, and is stored in the storing space 70. The storing space 70 is formed between the upper surface 101 of the inner container 10, and the upper surface 201 of the upper casing 200 of the outer container 20, and the
15 outer seal member 40 is guided by the upper surfaces 101, 201 and take-up shaft 50, and therefore the number of parts may be saved as compared with the case of installing guide member separately, and the manufacturing cost can be lowered.

Moreover, a part of the outer seal member 40 releasing
20 the toner dropping opening 20a of the outer container 20 is stored in a nearly upright state as shown in Fig. 2A, and therefore when an outer seal member 40 of high rigidity is employed, bending mark is not formed on the outer seal member 40. By such outer seal 40 without bending mark, the toner
25 dropping opening 20a of the outer container is closed, and the



sealing is secure, so that toner scattering may be prevented securely.

Upper Casing

Referring to Fig. 7, the upper casing 200 is in a box
5 form having a nearly rectangular shape in a plan view, and its lower surface is opened. The upper casing 200 comprises the upper surface 201, and side surfaces 202, 203 and end surfaces 204, 205 for composing the peripheral wall parts, extending downward from the four corners of the top surface 201. The
10 side surfaces 202, 203 run along the longitudinal direction of the toner cartridge main body 1, and the end surfaces 204, 205 run along the widthwise direction of the toner cartridge main body 1.

The side surfaces 202, 203 are provided with plural pawls
15 206 to be hooked on specific parts of the lower casing 250, plural bumps 207 disposed between the pawls 206 and a shaft support part 208 for supporting the take-up shaft 50, which are formed so as to extend downward. Concerning the shaft bearing part formed on the side surface 203, it is omitted in
20 the drawing because it is same in composition as the shaft bearing part 208 provided on the side surface 202.

The pawls 206 are in an L-sectioned shape, and consist of an elastically deformable support part 206a extending downward in a continuous form with concave surfaces 202a, 203a formed
25 in the side surfaces 202, 203, and a pawl main body 206b



bending at right angle from the lower end of the support part 206a and extending outward. the outer surface of the support part 206a is flush with the concave surfaces 202a, 203a.

5 In the portion corresponding to the withdrawal side end 1b of the side surface 203, a protrusion 203b projecting from the other parts is formed, and a semicircular notch 203c for introducing the larger end 50d to be described later of the take-up shaft 50 is formed in this protrusion 203b. Although not shown, a partition plate is provided against the inner
10 surface of the protrusion 203b, and a shaft support in the same composition as the shaft support 208 is formed, extending downward from the partition plate.

A semicircular notch 204a for inserting the toner feed tube 105 is formed in the end surface 204 disposed at a
15 position corresponding to the lead-in side end 1a of the toner cartridge main body 1.

Inner Container

Referring to Fig. 8, the inner container 10 is in a box form having an approximately rectangular form in a plan view.
20 The inner container 10 comprises the rectangular upper surface 101, each pair of side surfaces 102 and end surfaces 103 extending downward from the four sides of the upper surface 101, and a lower edge 104 in a plate form, continuously extending outward from the lower end of the side surfaces 102
25 and end surfaces 103 and running around the whole



circumference of the inner container 10.

At the end surface 103 disposed at a position corresponding to the lead-in side end 1a of the toner cartridge main body 1 of the inner container 10, the toner feed tube 104 for feeding toner inside the inner container 10 when manufacturing the toner cartridge is formed in a projected form. The front end of the toner feed tube 105 is designed to project outward of the outer container 20 as shown in Fig. 1A, in the assembled state of the inner container 10 and outer container 20. The inside of the toner feed tube 105 communicates with the inside of the inner container 10, and is isolated from the outside by the plug 106 introduced into the tube from the front end side. The plug 106 is intended to clog the toner feed tube 105 by thermal fusion after the toner is supplied in the inner container 10 from the toner feed tube 105.

The toner cartridge main body 1 is is a double container structure consisting of the inner and outer containers 10, 20, and can be filled with toner from a single toner feed tube 105. Therefore, the structure is simple, and the sealing performance is high.

Plural tongues 107 extending outward are formed in the parts of the lower edge 104 along the longitudinal direction. These tongues 107 are, as shown in Fig. 12, when fitting the protrusions 107 of the upper casing 200 and recesses 257 of



the lower casing 250 to be described later, pinched by these fitting parts. As a result, the inner container 10 is fixed, as being positioned in the outer container 20.

Thus, the outer container 20 consists of upper and lower casings 200, 250 fixed by fitting, and the inner container 10 is positioned and fixed by these upper and lower casings 200, 250, the hence the toner cartridge 1 can be assembled only by fitting together without using screws or the like.

Lower Casing

Referring then to Fig. 9, the lower casing 250 is in an approximately rectangular form in a plan view. The upper surface of the lower casing 250 is open, and the toner dropping opening 20a of the outer container 20 is formed in its lower surface.

The lower casing 250 comprises a lower edge 251 formed around the toner dropping opening 20a, and side surfaces 252, 253 and end surfaces 254, 255 extending upward from the vicinity of the four sides of the lower edge 251 to compose peripheral walls. The side surfaces 252, 253 run along the longitudinal direction of the toner cartridge main body 1, and the end surfaces 254, 255 run along the widthwise direction of the toner cartridge main body 1.

The side surfaces 252, 253 comprise plural hook slits 265 (see Fig. 10) for hooking the pawls 206 of the upper casing 200, plural recesses 257 located between the hook slits 256

This Sheet Has Been Replaced



for fitting the protrusions 207 of the upper casing 200, and a shaft support part 258 for supporting the take-up shaft 50 in collaboration with the shaft support part 208 of the upper casing. In the side surface 253, a box-shaped protrusion 253b is formed in a projected form, corresponding to the protrusion 203b of the upper casing 200. The side surfaces 202, 203 of the upper casing 200 and the side surfaces 252, 253 of the lower casing 250 are mutually formed in a zigzag form as shown in Fig. 11.

The lower edge 251 possesses an inner edge 251a disposed at the inner side of the side surfaces 252, 253 and end surfaces 254, 255, and an outer edge 251b disposed at the outer side, thereby composing peripheral walls. In the part of the inner edge 251a corresponding to the withdrawal side end 1b of the toner cartridge main body 1, there are a pair of bosses 259 to be fitted with a pair of tubular parts (not shown) formed in the upper casing 200, respectively, and also a pair of protrusions 260 for presenting opening position stopper means for defining the outer seal member 40 in the opening position through the slide member 60 are formed in a projecting state having the toner dropping opening 20a held in the widthwise direction. A finger hook 1c for hooking a finger when drawing out is formed in the part of the outer edge 251b of the lower edge 251 corresponding to the withdrawal side end 1b.

This Sheet Has Been Replaced



Moreover, as shown in Figs. 9, 17 and 18, in the part of the inner edge 251a corresponding to the lead-inside end 1a of the toner cartridge main body 1, there are a pair of protrusions 261 for presenting closed position stopper means for defining the outer seal member 40 in the closing position through the slide member 60, being provided in a state of holding the toner dropping opening 20a in the widthwise direction, while a guide part 262 forming a cam surface for guiding engagement and disengagement of the slide member 60 with the protrusions 261 is provided in a state of projecting to the toner dropping opening 20a side. The protrusions 261 for presenting the closing position stopper means are engaged with protrusions 60c described later of the slide member 60 in the central dent 261a (see Fig. 18), and define the outer seal member 40 in the closing position. Referring to Fig. 17, the guide part 262 is in an angle form, and when it abuts against the lower surface of the main body 60a of the slide member 60, the protrusions 60c of the slide member 60 are guided into the dent 261a. The protrusions 261 for presenting the closing position stopper means also compose move defining means for defining the move of the slide member 60, so as to prevent the seal member 40 from being released in the state of the toner cartridge TC being dismounted from the storing recess 500.

In the end surface 254 corresponding to the lead-in side end 1a of the toner cartridge main body 1, a notch 254a in a



semicircular section is formed. Between this notch 254a and notch 204a of the upper casing 200, the toner feed tube 105 is inserted and fixed.

Inner Seal Member

5 The inner seal member 30 is a slender sheet, and covers the toner dropping opening 10a of the inner container 10, in a thermally fused state to the lower surface of the lower edge 104 of the inner container 10. The base end 30a of the inner seal member 30 is affixed to the take-up shaft 50 as shown in
10 Fig. 1A.

Take-up Means

Referring to Fig. 13, the take-up shaft 50 possesses a main body 50a having a slit 50b for fixing the base end 30a of the inner seal member 30 provided in the widthwise direction,
15 a pair of smaller ends 50c formed coaxially on both ends of the main body 50a, being supported by the shaft support parts 208, 258 of the upper and lower casings 200, 250, and a larger end 50d formed continuously to one smaller end 50c. At the larger end 50d is formed a drive coupling recess 50e for
20 inserting and coupling a drive coupling shaft 91 contained in the driving force transmission mechanism 90. At the front end of the drive coupling shaft 91, a plane 91a parallel to the axial direction is formed, and, deep inside the drive coupling recess 50e corresponding to it, there is a plane 50f to be
25 matched with the plane 91a of the drive coupling shaft 91 in



specified rotation phase.

Slide Member

In Fig. 14, one end 40a of the outer seal member 40 is affixed to the upper surface of the slide member 60. The slide member 60 comprises a main body 60a straddling over the toner dropping opening 20a of the outer container 20 in the widthwise direction, a pair of guided parts 60b formed at both ends of the main body 60a, and the protrusions 60c formed in the lower surface of the guided parts 60b.

The pair of guided parts 60b of the slide member 60 are, as shown in Fig. 16, invading into a pair of guide grooves 75 formed between the lower surface of the lower edge 104 of the inner container 10, and the upper surface of the lower edge 251 of the lower casing 250 of the outer container 20. The slide member 60 is guided by the guide grooves 75, and slides and moves in the longitudinal direction of the outer container 20. Along with the sliding move of the slide member 60, the outer seal member 40 opens and closes the toner dropping opening 20a of the outer container 20.

Thus, the upper slide member 60 for opening and closing the outer seal member 40 is guided by the guide grooves 75 formed between the inner container 10 and outer container 20. Therefore, without requiring particular guide member, the number of parts may be curtailed. Besides, as shown in Fig. 16, since the both edges 40c, 40d of the outer seal member 40



are disposed in both guide grooves 75, sealing by the outer seal member 40 is secure.

Referring to Fig. 15, a pair of protrusions 61, 62 are formed in the lower surface of the main body 60a of the slide member 60. One protrusion 61 possesses a top 61a for pushing down the slide member moving means 80 in the disengagement position, an outer seal member releasing part 61b, and an outer seal member closing part 61c comprising mutually opposing slopes formed across the top 61a.

The slide member 60, as the outer seal member releasing part 61b engaged with the slide member moving member 80, moves the outer seal member 40 to the opening position, depending on the insertion motion of the toner cartridge TC into the storing recess 500. Or, when the outer seal member opening part 61c is engaged with the slide member moving member 80, the slide member 60 moves the outer seal member 40 to the closing position, depending on the drawing motion of the toner cartridge TC from the storing recess 500.

The protrusion 260 as the opening position stopper means formed in the lower edge 251 of the lower casing 250 abuts against the slide member 60 just before move of the outer seal member 40 to the opening position is completed, and arrests relative move of the slide member 60 to the toner cartridge main body 1. As a result, the slide member moving means 80 engaged with the outer seal member opening part 61b



rides over the top 61a, and is engaged with the outer seal member closing part 61c.

Likewise, the protrusion 261 as the closing position stopper means formed in the lower edge 251 of the lower casing 250 abuts against the slide member 60 just before move of the outer seal member 40 to the closing position is completed, and arrests the relative move of the slide member 60 to the toner cartridge main body 1. As a result, the slide member moving member 80 engaged with the outer seal member closing part 61c rides over the top 61a, and is engaged with the outer seal member opening part 61b.

Storing Recess

Referring to Fig. 19A and Fig. 19B, the storing recess 500 is disposed above the developing device (not shown) of the image forming apparatus main body G, and is loaded and unloaded with the toner cartridge TC. In the bottom of the storing recess 500, there is an opening 500a for dropping the toner discharged from the toner cartridge TC into the developing device.

For loading and unloading the toner cartridge TC into the storing recess 500, the opening 500b provided at the inlet of the storing recess 500 is released as shown in Fig. 19A, or closed as shown in Fig. 19B, by a lid 510 which is rotated about a shaft 510a formed in a specified position of the image forming apparatus main body G.



In the inside wall 500c of the storing recess 500, a lead-in groove 500d opened at one end in order to lead in the take-up shaft 50 as the toner cartridge TC is introduced into the storing recess 500, and an insertion part 500e for moving in and out the drive coupling shaft 91 in the storing recess 500, being provided in the deepest inside part of the lead-in groove 500d are formed. In the bottom near the inlet in the storing recess 500, the slide member moving member 80 is disposed.

10 Slide Member Moving Member

Referring to Fig. 20 and Fig. 21, the slide member moving member 80 comprises a fixed member 81 fixed by screws 84 in the bottom near the inlet in the storing recess 500, a rotary member 82 for presenting a movable member moving between the upper position to be engaged with the slide member 60 and the lower position for clearing the engagement, in a state being supported by the fixed member 81, and a compression coil spring 83 as thrusting means for thrusting the rotary member 82 to the upper position.

20 The fixed member 81 has an L-shaped section, and a pair of screw insertion holes 81a for inserting a pair of screws 84 are formed at the rear end of the fixed member 81. In the lower surface of the fixed member 81, a pair of shaft support parts 81b are projecting in order to support the pair of shaft parts 82a of the rotary member 82, respectively. In the front

25



end middle part of the fixed member 81, a screw hole 81c is formed for driving a screw 85 as the spring holding member for inserting the compression coil spring 83. Also at the front end of the fixed member 81, there are a pair of notches 81d through which a pair of engaging protrusions 82b of the rotary member 82 penetrate.

At both ends in the widthwise direction of the base end part of the rotary member 82, a pair of shaft parts 82a projecting sideways are formed, and the pair of engaging protrusions 82b bent in an angle form are formed at the front end of the rotary member 82. In the middle of the front end of the rotary member 82, a recess 82c is formed for inserting the screw 85 through which the compression coil spring 83 is inserted.

Referring to Fig. 20, the compression coil spring 83 is interspaced between the head 85a of the screw 85 fixed to the fixed member 81 and the lower surface of the rotary member 82, and thrusts the rotary member 82 in the clockwise direction. That is, the engaging protrusion 82b of the movable member 82 is thrust in the direction projecting into the storing recess 500 by the compression coil spring 83. Besides, when the top 61a of the slide member 60 passes over the engaging protrusion 82b, the movable member 82 turns counterclockwise while compressing the compression coil spring 83, and the engaging protrusion 82b retreats from the storing recess 500.

. This Sheet Has Been Replaced



The engaging protrusion 82b comprises an outer seal member opening part 82d and an outer seal member closing part 82e consisting of a pair of slopes inclined reversely to each other. The outer seal member opening part 82d is engaged with
5 the outer seal member opening part 61b of the slide member 60, while the outer seal member closing part 82e is engaged with the outer seal member closing part 61c of the slide member 60.

Driving Force Transmission Mechanism for Transmitting
Driving Force to Take-up Shaft

10 Fig. 22 to Fig. 24 are schematic sectional views sequentially showing the steps of coupling the drive coupling shaft 91 to the take-up shaft along with the closing action of the lid 510. Fig. 25 to Fig. 27 are schematic sectional views corresponding to Fig. 22 to Fig. 24, respectively. With
15 reference to these diagrams, the driving force transmission mechanism 90 is explained. The driving force transmission mechanism 90 is disposed on the side surface 500c near the inlet of the storing recess 500. The driving force transmission mechanism 90 comprises the drive coupling shaft
20 91 coupled detachably to the take-up shaft 50, a compression coil spring 92 as thrusting means for thrusting the drive coupling shaft 91 in the axial direction, a lock member 93 for holding the drive coupling shaft 91 in the specified position, a torsion spring 94 as thrusting means for thrusting the lock
25 member 93 in the locked state, and a lock member driving part

This Sheet Has Been Replaced



95 provided in the back side of the lid 510 for unlocking the lock member 93.

The drive coupling shaft 91 is free to move in the axial direction between the coupling position (see Fig. 24 and Fig. 5 27) of the take-up shaft 50 inserted in the drive coupling recess 50e, in the state of advancing into the storing recess 500, and the disengaging position (see Fig. 22 and Fig. 25) for clearing the coupling as retreating from the storing recess 500. Referring to Fig. 22, in the middle part of the 10 drive coupling shaft 91, a flange 91c moving in the axial direction together with the drive coupling shaft 91 is formed. The rear end of the drive coupling shaft 91 is projecting outward from the image forming apparatus main body G. Referring to Fig. 24, by inserting and coupling the coupling protrusion H1 of the hand turning handle H into the coupling 15 recess 91b formed in this rear end, the take-up shaft 50 is driven through the hand turning handle H and coupling drive shaft 91.

Referring to Fig. 13, as mentioned above, the flat part 20 91a to be engaged with the flat part 50f formed in the drive coupling recess 50e is formed at the front end of the drive coupling shaft 91. The mutually engaged flat parts 50f, 91a compose the torque transmission surface.

Referring to Fig. 22, the compression coil spring 92 is 25 interspaced between the inner surface of the image forming



apparatus main body G and the flange 91c of the drive coupling shaft 91, and thrusts the drive coupling shaft 91 to the coupling position (the take-up shaft 50 side).

5 The lock member 93 is composed of a plate member rotatably fitted around the shaft 93a mounted on the image forming apparatus main body G. The base end of the lock member 93 is rotatably supported by the shaft 93a. The lock member 93, of which front end abuts against the front end of the drive coupling shaft 91, is free to rotate about the shaft 10 93a, between the lock position (see Fig. 22 and Fig. 25) for holding the drive coupling shaft 91 in the disengaging position, and the unlocking position (see Fig. 24 and Fig. 27).

Referring to Fig. 25, the torsion spring 94 is wound 15 around the shaft 93a, and its one end is hooked on the shaft 96 fixed on the image forming apparatus main body G, while the other end is hooked on the hook hole 93b provided in the middle part in the longitudinal direction of the lock member 93. This torsion spring 94 thrusts the lock member 93 to the 20 lock position (in the counterclockwise direction in Fig. 23).

Referring to Fig. 25, the lock member driving part 95 is in a plate form, and is projecting to the rear side of the lid 510. This lock member driving part 95 moves the lock member 93 from the lock position shown in Fig. 25 to the unlocking 25 position shown in Fig. 27 in cooperation with the closing

action of the lid 510 sequentially shown in Fig. 25 to Fig.

27. The lock member driving part 95 also possesses an insertion hole 95a for inserting the coupling drive shaft 91 with the lock member 93 moved to the unlocking position.

5 The operation of the driving force transmission mechanism 90 is explained below.

As shown in Fig. 2A, when the toner cartridge TC is set in the storing recess 500 of the image forming apparatus main body G, the take-up shaft 50 is introduced to the position
10 confronting the front end of the drive coupling shaft 91. In this state, by the lock member 93 in the lock position shown in Fig. 22 and Fig. 25, the drive coupling shaft 91 is held in the disengaged position.

When the lid 510 is closed, as sequentially shown in Fig.
15 23 and Fig. 24, and in Fig. 26 and Fig. 27, the lock member driving part 95 provided on the lid 510 draws away the lock member 93 to the unlocking position shown in Fig. 24 and Fig. 27, in cooperation with the closing action of the lid 510. As a result, the coupling drive shaft 91 thrust by the
20 compression spring 92 penetrates through the insertion hole 95a of the lock member driving part 95, and is coupled with the drive coupling recess 50e of the take-up shaft 50 of the toner cartridge TC. Consequently, it is possible to drive the take-up shaft 50 by the handle H.

25 Thus, in cooperation with the closing action of the lid



510, driving and coupling to the take-up shaft 50 is effected, and driving and coupling is not effected unless the lid 510 is closed. Therefore, unless the lid 510 is closed, the inner seal member 30 is not peeled off, so that toner scatter may be
5 securely prevented.

Besides, with the lid 510 closed, the drive coupling shaft 91 in the coupling position penetrates through the insertion hole 95a of the lock member driving part 95, and by this drive coupling shaft 91, opening of the lid 510 is
10 blocked through the lock member driving part 95. Therefore, with the drive coupling shaft 91 coupled to the drive coupling recess 50e of the toner cartridge TC, opening of the lid 510 is prevented, so that toner scatter may be prevented more securely.

15 Moreover, by picking the rear end of the drive coupling shaft 91 by finger, and moving to the right in Fig. 24 by resisting the compression coil spring 92, it is set aside to the disengaging position shown in Fig. 22, and only when the take-up shaft 50 is set in a drive prohibited state, the toner
20 cartridge TC can be drawn out from the storing recess.

Attaching and Detaching of Toner Cartridge in Storing Recess

Referring now to Figs. 1A, 1B, 2A, 2B, 3A, 3B, and 4, the operation for detaching and attaching of toner cartridge TC in
25 the storing recess 500 is described below.



In the first place, a new toner cartridge Tc for replacement is as shown in Fig. 1, and the toner dropping opening 10a of the inner container 10 is closed by the inner seal member 30, and the toner dropping opening 20a of the outer container 20 is closed by the outer seal member 40. In this state, the slide member 60 is moved to the position shifted to the lead-in side end 1a of the toner cartridge main body 1.

When the lead-in side end 1a of the toner cartridge main body 1 is inserted into the storing recess 500, as shown in Fig. 1A, the slide member 60 and slide member moving means 80 are engaged with each other. Specifically, as shown by single dot chain line in Fig. 15, the outer seal member opening part 61b of the slide member 60 is engaged with the outer seal member opening part 82d of the pair of engaging protrusions 82b of the slide member moving member 80.

Furthermore, when the toner cartridge main body 1 is inserted into the inner side of the storing recess 500, the slide member moving member 80 moves the slide member 60 relatively to the toner cartridge main body 1, in cooperation with this insertion action, and the outer seal member 40 is released as shown in Fig. 1B.

Just before setting of the toner cartridge 1 in the storing recess 500 is complete, the right end of the slide member 60 in Fig. 2A abuts against the protrusion 260 as the



opening position stopper means (see Fig. 9; this protrusion 260 is omitted in Fig. 1). As a result, the relative move of the slide member 60 to the toner cartridge main body 1 is defined. In this state, by further inserting the toner
5 cartridge main body 1, the engaging protrusion 82b of the rotary member 82 of the slide member moving member 80 rides over the top 61a of the protrusion 61 of the slide member moving member 60, and the outer seal member closing part 82e of the slide member moving member 80 is engaged with the outer
10 seal closing part 61c of the slide member 60 as indicated by double dot chain line in Fig. 15, thereby becoming the state as shown in Fig. 2B. In this state, moreover, by closing the lid 510, the take-up shaft 50 is coupled with the drive coupling shaft 91.

15 Consequently, turning the handle H, the take-up shaft 50 is driven, and the inner seal member 30 is taken up on the take-up shaft 50 while peeling off as shown in Fig. 2B. As a result, the toner dropping opening 10a of the inner container 10 is opened, and the toner T drops into the specified part of
20 the developing device (not shown) beneath through the toner dropping openings 10a, 20a.

To draw out the spent toner cartridge TC, on the other hand, upon completion of insertion of the toner cartridge TC, the outer seal member closing part 82e of the slide member
25 moving member 80 is already engaged with the outer seal member



closing part 61c of the slide member 60. Therefore, in cooperation with the drawing action of the toner cartridge TC, the slide member 60 is moved relatively toward the lead-in side end 1a to the toner cartridge main body 1 as shown in Fig. 3A, and is moved to the closing position as shown in Fig. 3B.

Referring to Fig. 18, the slide member 60 reaching the closing position is guided by the slope of the guide 262, and abuts against a pair of protrusions 261 as closing position stopper means. As a result, the relative move of the slide member 60 to the toner cartridge main body 1 is defined. In this state, by further drawing out the toner cartridge main body 1, the engaging protrusion 82b of the slide member moving means 80 rides over the top 61a of the protrusion 61 of the slide member 60, and cancels the engagement with the slide member 60. Then the toner cartridge TC is completely removed from the storing recess 500.

Thus, when detaching for replacement, since the toner dropping openings 10a, 20a are automatically closed by the outer seal member 40 which is not stained with toner, and the toner scatter can be securely prevented, and the replacement work is very easy at the same time.

Still more, in the state that the toner cartridge TC is dismounted from the storing recess 500 of the image forming apparatus main body 1, the toner dropping openings 10a, 20a

This Sheet Has Been Replaced



are securely closed by the outer seal member 40. That is, the outer seal member 40 serves also as the shutter when transporting the toner cartridge TC, and hence any particular shutter is not needed.

5 Embodiment 2

Fig. 28A to Fig. 36 relate to the second embodiment of the invention.

Principal differences between Embodiment 2 and Embodiment 1 are as follows.

- 10 1) In Embodiment 1, the toner dropping openings 10a, 20a of the toner cartridge TC before being settled in the storing recess 500 were closed by the outer seal member 40. In Embodiment 2, by contrast, the toner dropping openings 10a, 20a of the toner cartridge TC before being settled in the
- 15 storing recess 500 are opened as shown in Fig. 28A representing the settling step. Meanwhile, when settling of the toner cartridge TC in the storing recess 500 is complete, the slide member 60 is arrested of relative move to the toner cartridge main body 1 by opening position stopper means (not
- 20 shown), and the slide member 60 rides over the engaging protrusion 82b of the slide member moving member 80, and moves from the rightward position of the engaging protrusion 82b (see Fig. 28A) to the leftward position (see Fig. 28B). When the toner cartridge TC is spent and drawn out of the storing
- 25 recess 500, although not shown in the drawings, the toner



dropping openings 10a, 20a are closed by the outer seal member 40, same as in Embodiment 1, by the action of the slide member moving member 80 and slide member 60.

ii) In Embodiment 1, the take-up shaft 50 as the
5 take-up means projected to the side of the toner cartridge main body 1, and was provided with the drive coupling shaft 91 disposed coaxially with the take-up shaft 50.

By contrast, in Embodiment 2, instead of the take-up shaft 50 in Embodiment 1, a take-up shaft 51 forming a first
10 gear 51a at one end is used, and instead of the drive coupling shaft 91 in Embodiment 1, a drive coupling shaft 52 forming a second gear 52a rotated in engagement with the first gear 51a at one end is used. A screw gear mechanism is composed of the first and second gears 51a, 52a. The drive coupling shaft 52
15 is disposed along the direction parallel to the direction orthogonal to the take-up shaft 51. The right end of the drive coupling shaft 52 in Fig. 28A is confronting the handle insertion tube 1d (see Fig. 28A to Fig. 33) provided at the withdrawal side end 1b of the toner cartridge main body 1.
20 After putting the toner cartridge TC into the storing recess 500, to peel off the inner seal member 30, as shown in Fig. 29, the hand turning handle H inserted in the handle insertion tube 1d is coupled with the drive coupling shaft 52 so as to rotate in unison, and the hand turning handle H is rotated to
25 drive the take-up shaft 51.



iii) In Embodiment 2, referring to Fig. 30 to Fig. 32, the upper casing 200 composing the upper part of the outer container 20 of the toner cartridge main body 1 forms the handle insertion tube 1d at the end of the withdrawal side end 1b. Besides, as shown in Fig. 33, at a specified position of the lower casing 250, a pair of support parts 263 for rotatably supporting the drive coupling shaft 52 are formed, and similar support parts (not shown) are formed at the corresponding parts of the upper casing 200.

Referring to Fig. 33, at the lower edge 251 of the lower casing 250, there are formed pawl members 264 for presenting a pair of slide member move suppressing means projecting into the toner dropping opening 20a from the edge of the withdrawal side end 1b side of the toner dropping opening 20a. These pawl members 264 arrest the slide member 60 with a specified holding force as shown in Fig. 36, and hold the outer seal member 50 in open state. The section of the main body 60a of the slide member 60 is rectangular as shown in Fig. 35.

The other constitution is same as in Embodiment 1, and its explanation is omitted by identifying the related parts with the same reference numbers.

In Embodiment 2, also, when removing for replacement, the toner dropping openings 10a, 20a are automatically closed by the outer seal member 40 not contaminated with the toner, and the toner scatter can be securely prevented, and the



replacement work is very easy.

Embodiment 3

Fig. 37 and Fig. 38 relate to the third embodiment.

Referring to the drawings, Embodiment 3 differs from

5 Embodiments 1 and 2 in the following points i) to iv).

i) The outer container 20 is divided into right and left casings 230, 280.

ii) A motor 55 for driving the take-up shaft 50 is disposed in the space between the inner container 10 and outer
10 container 20. A pair of terminals 56 for feeding power to this motor 55 through led wires 57 are exposed at the side surface of the left casing 230. These terminals 56 are designed to contact with the power feeding terminals (not shown) disposed at the side surface in the storing recess 50
15 with the toner cartridge TC settling in the storing recess 500.

iii) A tiltable T-shaped handle 290 is attached to the withdrawal side end 1b of the toner cartridge main body 1.

iv) On the upper surfaces of the right and left casings
20 230, 280, guide rails 231, 281 to be guided to specified parts in the storing recess 500 are provided.

The other constitution is same as in Embodiments 1 and 2, and its explanation is omitted by identifying with the same reference numbers. The internal structure is same as in
25 Embodiment 1, except that the structure for engaging the slide



member 60 is omitted, and hence it is not shown in the drawing.

In this embodiment, the inner seal member 30 can be taken up automatically by a motor, not manually.

5 Embodiment 4

Fig. 39A to Fig. 41 relate to the fourth embodiment of the invention.

Referring first to Fig. 39A, a sloped withdrawal guide 1e is formed in the bottom of the lead-in side end 1a of the
10 outer container 20 of the toner cartridge main body 1. As shown in Fig. 39A, after the inner seal member 30 is peeled off, the spent toner cartridge TC is drawn out as shown in Fig. 39B. At this time, the slide member 60 is moved relatively to the toner cartridge main body 1 by the slide
15 member moving member 800, and the outer seal member 40 is moved in the closing direction. So far, it is same as in Embodiment 2.

What Embodiment 4 differs from the other embodiments is the following points. As shown in Fig. 40A, just before
20 completion of withdrawal of the toner cartridge TC, this withdrawal guide 1e lifts the lead-in side end 1a of the toner cartridge main body 1, in the state of being guided by the abutting part 810f described below of the slide member moving member 800, and thereby smoothly canceling the engagement
25 between the slide member 60 and the slide member moving member

This Sheet Has Been Replaced



800 (see Fig. 40B).

Then, referring to Fig. 41, the slide member moving member 80 in Embodiment 4 comprises a fixed member 810, an engaging protruding member 820 of an angle section to be engaged with the slide member 60, disposed in the recess of the fixed member 810 being free to move back and forth by vertical motion, and a tension coil spring 830 with the both ends suspended on the fixed member 810 in a state of penetrating through the engaging protruding member 820, for thrusting the engaging protruding member 820 upward. A pair of abutting parts 810f are provided closely to both ends in the longitudinal direction of the engaging protruding member 820 of the fixed member 810.

Embodiment 5

Fig. 42 and Fig. 43 are schematic diagrams showing a toner refilling device in the fifth embodiment of the invention. Fig. 42 shows the state before the toner cartridge TC is set in the storing recess 500 of the image forming apparatus main body G, and Fig. 43 shows the complete setting state.

The toner cartridge TC has an approximately L-shaped section in a plan view, and comprises i) a toner cartridge main body 1 containing the toner, ii) a toner dropping opening 2 provided in the bottom 1a of the toner cartridge main body 1, iii) a seal member 3 in a sheet form for closing the toner



dropping opening, being peelably adhered to the lower surface of the toner cartridge main body 1 in fresh state of the toner cartridge TC, iv) a take-up shaft 4 as take-up means for fixing one end 3a of the seal member 3, peeling off the seal member 3, and taking it up, and v) driving force transmitting means for transmitting the driving force of a driver 7 as an external driving member to the take-up shaft 4.

The driving force transmitting means 5 comprises a driving gear member 5A coupled with the driver 7, and a worm wheel 5B for presenting a driven gear member that can rotate together with the take-up shaft 4. The driving gear member 5A consists of a disk 5A1 forming a fitting groove 5A4 as the drive coupling recess to be coupled with the driver 7, a worm shaft 5A2 fixing the disk 5A1 rotatably together at one end, and a worm 5A3 coaxially fixed on the worm shaft 5A2. The worm wheel 5B as the driven gear member is engaged with the worm 5A3, and is fixed coaxially at one end of the take-up shaft 4. The fitting groove 5A4 is a cross groove for fitting the driver 7, being formed in the central part of the end of the disk 5A1.

In the portion confronting the disk 5A1 of the withdrawal side end 1b of the toner cartridge main body 1, a driving member insertion hole 1c is formed for driving and coupling the driver 7 to the fitting groove 5A4 of the disc 5A1, as required, by inserting the driver 7 from outside of the toner



cartridge main body 1. What is characteristic of this embodiment is that a shutter member S composed of a sheet member is provided in the toner cartridge main body 1 as route cut-off means for opening and closing the driving member insertion hole 1c, and that a push rod 110 is provided in the storing recess 500 as the releasing means for pushing and releasing the shutter member S.

The shutter member S runs along the inner side of the toner cartridge main body 1 in a ladle shape, with one end fixed at the inner side of the toner cartridge main body 1 (hereinafter this one end is called the restricted end RE), while the other part in a slidable state along the inner side of the toner cartridge main body 1. The other end of the shutter member s (hereinafter called the free end FE) is usually closing the driving member insertion hole 1c of the toner cartridge main body 1, and releases the driving member insertion hole 1c along with the sliding motion. The toner cartridge main body 1 forms first to third guide pins P1 to P3 for guiding the slide of the shutter member S against the inner side of the toner cartridge main body 1, at three bent positions of the shutter member s in a ladle shape. In the toner cartridge main body 1, there is a space 8 for deflecting the shutter member S inward between the first guide pin P1 and second guide pin P2, and a push rod lead-in opening 1e for leading the push rod 110 into the space 8 is formed in the



back side 1d of the toner cartridge main body 1.

According to this embodiment, when the toner cartridge TC is inserted into the storing recess 500 of the image forming apparatus, as shown in Fig. 43, the push rod 110 deflects the shutter member S upon completion of setting, and the free end FE of the shutter member S slides and releases the driving member insertion hole 1c. As a result, the driver 7 can be coupled with the fitting groove 5A4 of the disk 5A1 through the driving member insertion hole 1c. That is, unless the toner cartridge TC is set completely in the storing recess 500, the seal member 3 cannot be peeled off, so that scattering of toner due to unexpected opening of the toner cartridge TC may be securely prevented.

Embodiment 6

The sixth embodiment shown in Fig. 44 is a modified example of the fifth embodiment. What this embodiment differs from Embodiment 5 is that the free end FE of the shutter member S is thrust in the direction of closing the driving member insertion hole 1c, by the tension coil spring 9 as thrusting means, interspaced between the free end FE of the shutter member S and the engaging part of the toner cartridge main body 1. The other constitution is same as in Embodiment 5, and the same reference numbers are used in the drawing and the explanation is omitted.

According to the embodiment, the driving member insertion



hole 1c can be closed when drawing out the toner cartridge TC from the storing recess 500. Therefore, if the toner cartridge TC is once set, and immediately removed and set again, unnecessary release of the toner cartridge TC may be prevented at the time of setting again.

Embodiment 7

Fig. 45A and Fig. 45B relate to the seventh embodiment of the invention. Referring to these diagrams, what is characteristic of this embodiment is that the drive transmission route is cut off by sliding the driving gear member 5A to the position for canceling the engagement with the worm wheel 5B as the driven gear member. In this embodiment, the route cut-off means is composed of the sliding driving gear member 5A.

The driving gear member 5A is supported by the toner cartridge main body 1, in a manner free to slide between the engaging position with the worm wheel 5B as the driven gear member (see Fig. 45A), and the engagement clearing position (see Fig. 45B). The driving gear member 5A consists of a worm shaft 5A2, and a worm 5A3 coaxially fixed nearly to the central position of the worm shaft 5A2. At one end of the worm shaft 5A2, a fitting hole 5A5 is provided as a drive coupling recess that can be fitted with the coupling protrusion H1 of the hand turning handle H as driving member, while a flange 5A6 is provided at the other end.



The toner cartridge main body 1 is furnished with an elastic rib 1f as thrusting means for thrusting the driving gear member 5A to the engagement clearing position. This elastic rib 1f thrusts the driving gear member 5A to the position for clearing engagement through the flange 5A6. On the other hand, in the storing recess 500 of the image forming apparatus main body G, as shown in Fig. 45B, there is provided a protrusion 120 for presenting operating means for moving the driving gear member 5A to the engaging position, by pushing the flange 5A6 of the driving gear member 5A, upon completion of setting of the toner cartridge TC in the storing recess 500. The other constitution is same as the embodiment shown in Fig. 42, and the explanation is omitted.

According to this embodiment, while the toner cartridge is in fresh state, the driving gear member 5A is held in the position avoiding engagement with the worm wheel 5B by the elastic rib 1f as shown in Fig. 45A. Therefore, while the toner cartridge TC is not set in the storing recess 500 of the image forming apparatus main body G, undesired peeling of the seal member 3 is avoided. As a result, toner scatter can be securely prevented. On the other hand, when the toner cartridge TC is set in the storing recess 500, the protrusion 120 of the storing recess 500 moves the driving gear member 5A to the engaging position as shown in Fig. 45B, so that the seal member 3 can be taken up.



Embodiment 8

Fig. 46 shows a modified example of Embodiment 7. In this Embodiment 8, instead of the elastic rib 1f used in Embodiment 7, a compression coil spring 5C interspaced between the worm 5A3 and inner surface of toner cartridge main body 1 is used.

Embodiment 9

Fig. 47A to Fig. 47C relate to a further different modified example of Embodiment 7. In Embodiment 7, the driving gear member 5A is held in the engagement clearing position by the thrusting means. By contrast, in this modified example, as shown in Fig. 47A, by using a wedge protrusion 5A7 provided at a position closer to the flange 5A6 than the worm 5A3 of the worm shaft 5A2, the driving gear member 5A is held in the engagement clearing position. On the worm shaft 5A2, other wedge protrusion 5A8 is provided at the position closer to the flange 5A6 than the wedge protrusion 5A7.

According to this embodiment, while the toner cartridge TC is not set in the storing recess 500 of the image forming apparatus main body G, as shown in Fig. 47A, the wedge protrusion 5A7 abuts against the right side peripheral part of the worm shaft support hole 1g of the toner cartridge main body 1, and accordingly the driving gear member 5A is held in the engagement clearing position. Therefore, the take-up



shaft 4 cannot be driven.

When setting the toner cartridge TC in the storing recess 500 of the image forming apparatus main body G, the protrusion 120 pushes the flange 5A6, and penetrates the wedge protrusion 5A7 leftward into the worm shaft support hole 1g. In the complete setting state of the toner cartridge, as shown in Fig. 47B, the driving gear member 5A is moved to the position to be engaged with the worm wheel 5B. As a result, it is ready to take up, and the driving gear member 5A is driven by the handle H, and the seal member can be taken up on the take-up shaft 4. In the state shown in Fig. 47B, incidentally, the other wedge protrusion 5A8 abuts against the right side peripheral edge of the worm shaft support hole 1g, and the driving gear member 5A is held in the engagement position by a specified holding force.

When take-up of the seal member 3 by the take-up shaft is over, the worm wheel 5A3 is in locked state, and even after the locked state, by turning the driving gear member 5A continuously by the handle H, the driving gear member 5A receives a driving reaction from the worm wheel 5B. By this driving reaction, if it exceeds the holding force by the wedge protrusion 5A8, the driving gear member 5A is moved to the left in the axial direction as shown in Fig. 47C, to a position avoiding engagement. In this state, the wedge protrusion 5A8 is penetrating through the worm shaft support



hole 1g, and the wedge protrusion 5A8 prevents the driving gear member 5A from being to the engagement position as shown in Fig. 47B. Therefore, instead of completion of take-up of the seal member 3, if the handle H is turned continuously, the toner cartridge main body 1 will not be broken. Besides, due to sudden rise of the rotation load of the handle H, completion of take-up is noticed to the operator, so that occurrence of breakage may be prevented.

Embodiment 10

Fig. 48A and Fig. 48B relate to Embodiment 10. What differs between this embodiment and the embodiment in Fig. 45A is as follows. That is, in the embodiment in Fig. 45A, by the move of the driving gear member 5A, the engagement with the worm wheel 5b as the driven gear member is cleared, whereas in this embodiment, by the move of the driving gear member 5A, coupling of the driving gear member 5A and the handle H is disabled.

Referring to Fig. 48A and Fig. 48B, the driving gear member 5A is supported by the toner cartridge main body 1 so as to be capable of sliding between the position to be coupled with the hand turning handle H as shown in Fig. 48A, and the position disabled to be coupled as shown in Fig. 48B. The driving gear member 5A is, at whichever position, engaged with the worm wheel 5B. the driving gear member 5A is thrust at a position disabled to be coupled by the compression coil spring



5C. In this embodiment, unnecessary opening of the toner cartridge main body 1 is prevented, and toner scatter can be securely prevented.

Embodiment 11

5 Fig. 49A and Fig. 49B show a modified example of Embodiment 10. What is characteristic of this embodiment is that the fitting hole 5A5 for fitting the handle H is not formed unless the toner cartridge TC is set in the storing recess 500 of the image forming apparatus main body G. The
10 driving gear member 5A is composed of a box body with the square section hole 5D to be supported penetrating in the axial direction. On the outer circumference of the right side of the driving gear member 5A from the middle part in the axial direction, a worm 5A3 is formed, as being engaged with a
15 worm wheel as driven gear member not shown in the drawing. At the right end of the driving gear member 5A, a flange 5A9 to abut against the protrusion 120 is formed.

 In the hole to be supported 5D, a square section support member 1h rotatably supported by a rib 1i of the toner
20 cartridge main body 1 is penetrating. Accordingly, the driving gear member 5A can rotate together with the support member 1h, and is free to slide in the axial direction as mentioned above. The driving gear member 5A slides in the axial direction, and moves relatively leftward of the support
25 member 1h, and a part of the hole to be supported 5D is

This Sheet Has Been Replaced



opened, and the fitting hole 5A5 into the handle H is formed. While the toner cartridge TC is not set in the image forming apparatus main body G, as shown in Fig. 49A, the driving gear member 5A thrust by the compression coil spring 5C is moved to the right, and the hole to be supported 5D is closed by the support member 1h.

In this embodiment, too, the drive transmission route can be cut off when not required, and unnecessary take-up of the seal member can be prevented.

10 Embodiment 12

Fig. 50 shows a further different embodiment of the invention. In this embodiment, the worm wheel 5B as the driven gear member rotating together with the take-up shaft 4 is provided on the toner cartridge main body 1, and the driving gear member 5A to be engaged with the worm wheel 5B is provided on the image forming apparatus main body G.

Therefore, only when the toner cartridge TC is set in the storing recess 500, the both gear members 5A, 5B are engaged with each other so that the seal member can be taken up. In this embodiment, the route cut-off means is composed of both gear members 5A, 5B. In this embodiment, too, unnecessary take-up of the seal member 3 can be prevented, so that scatter of toner can be prevented securely.

The invention is not limited to these embodiments alone, but, for example, the gear mechanism included in the driving



force transmitting means 5 may be realized by worm gear mechanism, screw gear mechanism, other skew gear mechanism, bevel gear mechanism, or other crossed shaft gear mechanism.

5 In Embodiments 5 to 12, the toner cartridge main body 1 may be composed in a double container structure as in Embodiments 1 to 4, and the outer seal member 40 and slide member 60 may be provided.

Besides, other modifications of the design may be possible within a range not departing from the true spirit of
10 the invention.

15

20

This Sheet Has Been Replaced



25

WHAT IS CLAIMED IS:



1. A toner cartridge having a toner cartridge main body (1) with a toner dropping opening (10A), and extractably set in a storing recess (500) of an image forming apparatus main body (G) comprising:

an inner seal member (30) in a sheet form for closing said toner dropping opening (10A) as being peelably attached to the lower surface of said toner cartridge main body (1),

take-up means (50) for releasing the toner dropping opening (10a) by taking up while peeling said inner seal member (30) when required,

an outer seal member (40) in a sheet form capable of opening and closing the toner dropping opening (10a) beneath said inner seal member (30), as being slidably provided along the lower surface of said toner cartridge main body (1), and

outer seal member operating means (60) being provided so as to be engaged with engaging means (82e) for closing the outer seal member of the image forming apparatus main body (G), so as to automatically close said outer seal member (40) when said toner cartridge main body (1) is drawn out from the storing recess (500) in the state of being engaged with the engaging member (82e).

2. A toner cartridge of claim 1, wherein

said toner cartridge main body (1) consists of an inner container (10) containing toner, and an outer container (20)





containing said inner container (10).

3. A toner cartridge of claim 2, wherein
said outer container (20) is composed of a pair of
mutually separably coupled casings (200, 250).

5 4. A toner cartridge of claim 3, wherein
said pair of casings (200, 250) are fixed by fitting with
each other.

5. A toner cartridge of claim 4, wherein
said pair of casings consist of an upper casing (200) and
10 a lower casing (250),

a tongue (107) is formed on the side surface (102) of
said inner container (10), and

said tongue (107) of the inner container (10) is pinched
in the fitting parts of said upper and lower casings (200,
15 250), and said inner container (10) is fixed in a state
positioned to said outer container (20).

6. A toner cartridge of claim 2, wherein
said take-up means (50) is contained in a space
partitioned by the inner surface of said outer container (20)
20 and the outer surface of said inner container (10).

7. A toner cartridge of claim 2, wherein
said outer seal member (40) is contained inside of a
space (70) partitioned by the inner surface of said outer
container (20) and the outer surface of said inner container
25 (10) when using the toner cartridge.





8. A toner cartridge of claim 7, wherein
said outer seal member (40) is composed of an elastic
sheet member, and when it is contained roughly in a straight
state in the partitioned space (70), it opens said toner
5 dropping opening (10a), and when drawn out from the
partitioned space (70) in inverted state, it covers said toner
dropping opening (10a).

9. A toner cartridge of claim 8, wherein
said outer seal member (40) is guided and inverted by
10 said take-up means (50).

10. A toner cartridge of claim 2, wherein
a motor (55) for driving said take-up means (50) is
contained in a space partitioned by the inner surface of said
outer container (20) and the outer surface of said inner
15 container (10).

11. A toner cartridge of claim 2, further comprising:
a toner feed tube (105) formed at the end of said inner
container 10, with the inside communicating with the inside of
said inner container (10), and the front end penetrating
20 through the end of said outer container (20), and

a plug (106) for closing the front end of said toner feed
tube (105) after the toner is supplied from said toner feed
tube (105).

12. A toner cartridge of claim 1, wherein
25 said take-up means comprises a take-up shaft (50)





disposed orthogonally to the withdrawal direction of the toner cartridge, and

said take-up shaft (50) fixes one end of said inner seal member (30).

5 13. A toner cartridge of claim 12, wherein
 said take-up shaft (50) comprises a drive coupling part for coupling to an external driving member.

 14. A toner cartridge of claim 12, further comprising:
 driving force transmitting means (90) comprising a drive
10 coupling part (91b) to be coupled with an external driving member (H), for transmitting the driving force of the driving member (H) to said take-up shaft (50).

 15. A toner cartridge of claim 12, wherein
 said driving force transmitting means (90) comprises a
15 crossed axes gear mechanism.

 16. A toner cartridge of claim 14, wherein
 said driving force transmitting means (90) comprises a skew gear mechanism.

 17. A toner cartridge of claim 15, wherein
20 said skew gear mechanism includes a worm gear mechanism.

 18. A toner cartridge of claim 16, wherein
 said worm gear mechanism comprises:
 a worm rotatably mounted on a shaft member possessing the drive coupling part, possessing an rotation axial line along
25 the withdrawal direction of the toner cartridge, and





a worm wheel rotatably mounted on said take-up shaft (50) to be engaged with said worm.

19. A toner cartridge of claim 15, wherein
said skew gear mechanism includes a crossed helical gear
5 mechanism.

20. A toner cartridge of claim 1, wherein
said outer seal member operating means comprises a slide
member (60) which crosses said toner dropping opening (10a) in
a state of fixing one end of said outer seal member (40), and
10 is movable along the lower surface of said toner cartridge
main body (1).

21. A toner cartridge of claim 19, wherein
said toner cartridge main body (1) comprises guide means
(75) for guiding the move of said slide member (60), in a
15 state of slidably fitting the both ends of the slide member
(60).

22. A toner cartridge of claim 20, wherein
said guide means comprises guide grooves (75) formed
between the lower edge (104) of said inner container (10) and
20 the confronting lower edge (251) of said outer container (20),
in which both ends of said slide member (60) are inserted.

23. A toner cartridge of claim 21, wherein
both side edges (40c, 40d) of said outer seal member (40)
are guided by said guide groove (75).

25 24. A toner cartridge of claim 21, wherein

This Sheet Has Been Replaced





said guide groove (75) comprises slide member move restricting means (261) for restricting the move of said slide member (60) when said slide member (60) closes said outer seal member (40).

5 25. A toner cartridge of claim 19, wherein

said slide member (60) comprises closing engagement means (61c) for closing said outer seal member (40) adapted to be engaged with closing engaging means (82e) on the image forming apparatus main body (G), and, when drawing out the toner
10 cartridge, said outer seal member (40) is closed by sliding relatively to said toner cartridge main body (1) as said closing engagement means (61c) is pushed by the closing engaging means (82e).

26. A toner cartridge of claim 24, wherein
15 said toner cartridge main body (1) comprises:

closing position stopper means (261) for engaging said closing engagement means (61c) of the slide member (60) with the closing engaging means (82e) on the image forming apparatus main body (G), by restraining the move of said slide
20 member (60) in the state of said toner dropping opening (10a) being opened by said outer seal member (40), when the toner cartridge is set in the storing recess (500).

27. A toner cartridge of claim 25, wherein
said slide member (60) comprises opening engagement means
25 (61b) for opening said outer seal member (40) adapted to be





engaged with opening engaging means (82d) on the image forming apparatus main body (G), and, when setting the toner cartridge in the storing recess (500), said outer seal member (40) is released by sliding relatively to said toner cartridge main body (1) as said opening engagement means (61b) is pushed by the opening engaging means (82d).

28. A toner cartridge of claim 26, wherein said toner cartridge main body (1) comprises:
opening position stopper means (260) for engaging said opening engagement means (61b) of the slide member (60) with the opening engaging means (82d) on the image forming apparatus main body (G), by restraining the move of said slide member (60) in the state of releasing said toner dropping opening (10a) by said outer seal member (40) when drawing out the toner cartridge from the storing recess (500).

29. A toner refilling device for refilling a predetermined portion of an image forming apparatus main body (G) with toner, by a toner cartridge (TC) containing toner, being detachably set in the storing recess (500) of the image forming apparatus main body (G), comprising:

a toner cartridge main body (1) containing toner and forming a dropper dropping opening (10a) in the lower surface, an inner seal member (30) in a sheet form for closing said toner dropping opening (10a) as being peelably adhered to the lower surface of said toner cartridge main body (1),





take-up means (50) provided inside said toner cartridge main body (1) for releasing said toner dropping opening (10a) by taking up while peeling said inner seal member (30) when required,

5 an outer seal member (40) in a sheet form provided slidably along the lower surface of said toner cartridge main body (1), and capable of opening and closing said toner dropping opening (10a) beneath said inner seal member (30),

 closing engaging means (82e) for closing said outer seal
10 member (40), being provided on the image forming apparatus main body (G), and

 outer seal member operating means (60) for automatically closing said outer seal member (40), when the toner cartridge main body (1) is drawn out of the storing recess (500) in the
15 state of being engaged with the closing engaging means (82e).

30. A toner refilling device of claim 28, wherein

 said outer seal member operating means comprises a slide member (60) having closing engagement means (61c) for closing said outer seal member (40) to be engaged with said closing
20 engaging means (82e) on the image forming apparatus main body (G), said slide member (60) being movable along the lower surface of said toner cartridge main body (1), as crossing said toner dropping opening (10a) in a state of fixing one end of said outer seal member (40), and

25 said closing engaging means (82e) for closing said outer





seal member (40) is provided in a movable member (82), being free to move between a position advancing into the inside of the storing recess (500) of the image forming apparatus main body (G) and a position retreating from the inside thereof, and urged to the advancing position by urging means (83).

31. A toner refilling device of claim 29, wherein said movable member (82) is provided with a guide portion (262) for guiding the engagement of said closing engagement means of the slide member (60) with said closing engaging means (82e) when setting the toner cartridge in the storing recess (500).

32. A toner refilling device of claim 28, wherein said slide member (60) comprises an opening engagement means (61b) for opening said outer seal member (40) to be engaged with opening engaging means (82d) on the image forming apparatus main body (G) for releasing said outer seal member (40).

33. A toner refilling device of claim 31, wherein said closing engaging means (82e) and said opening engaging means (82d) are composed of a pair of angle-shaped slope surfaces.

34. A toner refilling device for refilling a predetermined part of an image forming apparatus main body (G) with toner, by a toner cartridge (TC) containing toner, being detachably set in the storing recess (500) of the image





forming apparatus main body (G), comprising:

a toner cartridge main body (1) containing toner and forming a dropper dropping opening (10a) in the lower surface,

5 a seal member (3) in a sheet form for closing said toner dropping opening (10a) as being peelably adhered to the lower surface of said toner cartridge main body (1),

take-up means (4) provided inside said toner cartridge main body (1) for releasing said toner dropping opening (10a) by taking up while peeling said seal member (3) when required,

10 driving force transmitting means (5) containing a drive coupling part (5A4) that can be coupled with an external driving member (7) for transmitting the driving force of the driving member (7) to said take-up means (4), and

route cut-off means S for usually cutting off the driving 15 force transmitting route from the driving member (7) to the take-up means (4) through said driving force transmitting means (5), and connecting only when the toner cartridge is set in the storing recess (500).

20 35. A toner refilling device of claim 33, further comprising:

releasing means for releasing the cutting off the driving force transmitting route by said route cut-off means, and wherein

25 1) said driving force transmitting means (5) is disposed on said toner cartridge main body (1), and





ii) said toner cartridge main body (1) has a driving member insertion hole (1c) for coupling the driving member (7) with said drive coupling part (5A4) of the driving force transmitting means (5) by inserting from outside of said toner cartridge main body (1) when required, and

iii) said route cut-off means comprises a shutter member (S) being capable of opening and closing said driving member insertion hole (1c), and being set in a closed state while the toner cartridge is brand-new, and

iv) said releasing means (110) is disposed on the image forming apparatus main body (G) so as to release said shutter member (S) upon completion of setting of the toner cartridge in the storing recess (500).

36. A toner refilling device of claim 34, wherein the shutter member comprises:
a sheet member (S) possessing
a restricted end (RE) fixed to said toner cartridge main body (1), and

a free end (FE) for releasing said driving member insertion hole (1c) by sliding along the inner surface of said toner cartridge main body (1), and

said releasing means comprises:

a push rod (110) for deflecting a part of said sheet member (S) upon completion of setting of the toner cartridge in the storing recess (500).

This Sheet Has Been Replaced





37. A toner refilling device of claim 35, further comprising:

urging means (9) for urging said free end (FE) of the sheet member (S) in the direction of closing said driving member insertion hole (1c) by said free end (FE), being
5 interposed between said free end (FE) of the sheet member (S) and the specified part of said toner cartridge main body (1).

38. A toner refilling device of claim 33, further comprising:

10 releasing means for releasing the cutting off the driving force transmitting route by said route cut-off means, and wherein

said driving force transmitting means (5) is disposed on said toner cartridge main body (1), and comprises:

15 a driven gear member (5B) rotatable with said take-up means (4), and

a driving gear member (5A) composing said route cut-off means, being movable between an engaging position with the driven gear member (5B) and an disengaging position, and

20 wherein

said releasing means comprises:

operating means (120) on the image forming apparatus main body (G) for moving the driving gear member (5A) to the engaging position upon completion of setting of the toner
25 cartridge in the storing recess (500).

This Sheet Has Been Replaced





39. A toner refilling device of claim 37, further comprising:

holding means (1f) for holding the driving gear member (5A) at the disengaging position.

5 40. A toner refilling device of claim 38, wherein said holding means comprises urging means (1f).

41. A toner refilling device of claim 39, wherein said urging means is comprises an elastic rib (1f) formed in the toner cartridge main body (1).

10 42. A toner refilling device of claim 39, wherein said urging means comprises a coil spring (5C) interposed between said toner cartridge main body (1) and said driving gear member (5A).

15 43. A toner refilling device of claim 38, wherein said holding means comprises a wedge protrusion (5A7) engaged with an insertion hole (1g) of said toner cartridge main body (1) with a specified engaging force, being disposed on a gear shaft of said driving gear member.

20 44. A toner refilling device of claim 42, wherein the gear shaft (5A2) of said driving gear member (5A) is provided with an other wedge protrusion (5A8) to be engaged with said insertion hole (1g) of said toner cartridge main body (1) with a specified engaging force, and

25 when taking up by said take-up means (4), the move in the axial direction by the driving reaction of said driving gear





member (5A) is restrained by the other wedge protrusion (5A8) engaged with the insertion hole (1g), and the driving reaction increased as the rotation of the driving gear member (5A) is restrained upon end of takeup of the seal member (3) clears
5 the engagement of the other wedge protrusion (5A8) to move the driving gear member (5A) in the axial direction, thereby canceling the engagement of the driving gear member (5A) and the driven gear member (5B).

45. A toner refilling device of claim 33, further
10 comprising:

releasing means for releasing the cutting off the driving force transmitting route by said route cut-off means, and wherein

i) said driving force transmitting means (5) includes a
15 member (5A) forming said drive coupling part (5A5) and composing said route cut-off means, said member (5A) being movable between the coupling position of the drive coupling part (5A5) with the external driving member (H) and the uncoupling position, and

20 ii) said releasing means comprises operating means (120) on the image forming apparatus main body (G) for moving the member (5A) forming the drive coupling part (5A5) to the coupling position, upon completion of setting of the toner cartridge in the storing recess (500).

25 46. A toner refilling device of claim 44, further





comprising:

holding means (5C) for holding the member (5A) forming said drive coupling part at the uncoupling position.

5 47. A toner refilling device of claim 45, wherein said holding means composes urging means (5C).

48. A toner refilling device of claim 46, wherein said urging means composes an elastic rib (1f) formed in said toner cartridge main body (1).

10 49. A toner refilling device of claim 46, wherein urging means composes a coil spring (5C).

50. A toner refilling device of claim 33, wherein said driving force transmitting means (5) includes a pair of members forming the drive coupling part, said members comprising:

15 a first member (5A) possessing an insertion hole (5D), and a second member (1h) movable in the axial direction relatively to said first member (5A), being inserted in said insertion hole (5D) of said first member (5A), and

20 said first member (5A) and second member (1h) form a drive coupling part (5A5) along the mutual relative axial move.

51. A toner refilling device of claim 49, wherein said drive coupling part (5A5) is composed of said insertion hole (5D) of said first member (5A).

25 52. A toner refilling device of claim 49, wherein





said drive coupling part (5A5) is composed of the front end of said second member (1h), projecting from said insertion hole (5D) of said first member (5A).

53. A toner refilling device of claim 33, wherein
5 the driving force transmitting means (5) comprises:

a driven side gear member (5B) rotatable together with the take-up means (4), being provided in said toner cartridge main body (1), and

a driving gear member (5A) to be engaged with the driven
10 gear member (5B) in a state of setting the toner cartridge in the storing recess (500), being provided in the image forming apparatus main body (G), and

said route cut-off means is composed of these driven gear member (5B) and driving gear member (5A).

15 54. A toner refilling device of claim 33, further comprising:

releasing means for releasing the cutting off the driving force transmitting route by said route cut-off means, and wherein

20 said driving force transmitting means (5) includes a member (91) forming a drive coupling part (91a) to the take-up means (50), said member (91) being movable between a coupling position of the drive coupling part (91a) with said take-up means (50), and an uncoupling position, and

25 said releasing means comprises interlocking means (90)





for moving the member (91) forming the drive coupling part to the coupling position, in cooperation with a closing action of a lid (510) for opening and closing the inlet provided at the inlet of the storing recess (500) of the image forming apparatus main body (G).

55. A toner refilling device of claim 53, wherein said interlocking means (90) comprises:

first urging means (92) for urging said member (91) forming said drive coupling part to the coupling position,

10 a lock member (93) for composing the route cut-off means, being movable between a locking position for holding said member (91) forming the drive coupling part at an uncoupling position by advancing into between said member (91) forming said drive coupling part and said take-up means (50), and the
15 unlocking position for retreating from the locking position,

second urging means (94) for urging said lock member (93) to the locking position, and

a lock member driving part (95) for moving said lock member (93) to the unlocking position, in cooperation with the
20 closing action of the lid (510), being provided in the lid (510).

56. A toner refilling device of claim 54, wherein

said lock member driving part (95) is provided with an insertion hole (95a) for inserting said member (91) forming
25 said drive coupling part in, in the state of moving said lock



member (93) to the unlocking position.

5

10

15

This Sheet Has Been Replaced



20



* C L M S *

25