

980621-6
(105)

REPLACED SHEETS		SO
☒ Description	: paged 1 to paged 7	
☒ Claim(s)	: paged 8 to paged 12	
☒ Drawing(s)	: paged 1/4 to paged 7/7	
☒ Abstract	: paged 13 to paged	

1

EL-6162

CONNECTOR

Background of the Invention

5

1. **Field of the Invention:** This invention relates to electrical connectors and particularly to printed circuit board connectors.

2. **Brief Description of Prior Developments:** Electrical connectors for connecting small panel-like electrical devices, such as circuit boards or liquid crystal displays (LCD) to another circuit board are known. One such connector employs an insulative body having a slot for receiving an LCD module. A linear array of connector terminals are mounted on the body. The spring portions disposed at one end of the terminals are located along the slot to engage circuit contact pads on the LCD. The other ends of the terminals are wrapped about the connector body and extend in a fixed position along a bottom edge of the connector body to form bottom contacts. Because the bottom contacts have no compliance, it is necessary to utilize a sheet of elastomeric material between the bottom of the connector body and the circuit board. The elastomeric body is provided with appropriate conductive traces to electrically connect the bottom contacts with appropriate contacts on the printed circuit board. The connector is held compressed against the elastomeric material by a compressive force, typically generated by the portion of the housing in which the LCD is mounted. It is common to apply an adhesive to hold the connector secure onto the LCD. The use of conductive elastomers and adhesives adversely affects the ease and cost of manufacturing devices, such as portable hand held electronic devices that have visual displays, such as cellular telephones.

This Sheet Has Been Replaced



Summary of the Invention

The electrical connector of the present invention includes an insulative body comprising a first portion and a second portion extending generally perpendicularly from the first second portion. The connector
5 also includes a conductive means comprising a retention section and a resilient section. The conductive means is retained by the second portion of the insulative body and the resilient section extending adjacent the first portion of the insulative body. The connector may be interposed between a planar electrical device and a printed circuit board.

Brief Description of the Drawings

The electrical connector of the present invention is further described with reference to the accompanying drawings in which:

Fig. 1 is a front elevational view of a connector embodying the invention;

15 Fig. 2 is a side elevational view of the connector shown in Fig. 1;

Fig. 3 is a back elevational view of the connector shown in Fig. 1;

Fig. 4 is a bottom view of the connector shown in Fig. 1;

Fig. 5 is a cross-sectional view taken along line AA of Fig. 3;

Fig. 6 is an enlarged view of area B of Fig. 1;

20 Fig. 7 is an enlarged view of area C of Fig. 4;

Figs. 8a - 8f are sequential illustrations of manufacturing and installation steps related to the connector of Fig. 1; and

Figs. 9a and 9b show positions of the connector of Fig. 1 during application and use.

Detailed Description of the Preferred Embodiments

25 The invention will be described in the context of a connector specifically adapted for electrically connecting planar electrical devices,

This Sheet Has Been Replaced



such as LCD's, to another circuit board. However, the invention is believed to have applicability in other connectors.

Fig. 1 shows a connector 10 having a body 12 formed of a molded polymeric insulating material. The body 12 includes a vertically
5 extending leg portion 14 and a generally horizontally extending top portion 16. The connector also includes a plurality of suitable conductive metal terminals 18, preferably formed by stamping.

Each terminal 18 includes a cantilevered spring contact portion 20 for engaging an electrical device, as will later be described. Terminals 18
10 further include a retention portion 22 (Fig. 5), where the terminal 18 is retained in the body 12. Each terminal further includes a downwardly extending resilient beam portion 24 extending along the rear of the body 12. As will later be described, the portion 24 generally forms a Euler's Beam structure. At the bottom of each terminal 18 is a PCB contact
15 portion 26 for engaging contact pads on a printed circuit board, as will later be explained. As can be seen in Fig. 5, the PCB contact section 26 is formed as a curved surface having an outside radius that contacts the printed circuit board. Adjacent the contact portion 26 is an opposed pair of retention ears 28 and 30 (Fig. 7), the upper portions 29 and 31 (Fig. 6)
20 of which are bent inwardly to form radiused surfaces, such as surface 32 (Fig. 8d).

As shown in Fig. 3, 4 and 8a-f, grooves 34 are formed in the back of the housing 12 for receiving the portions 24 of beams 18. Additionally, undercut portions 36 are formed in opposing relationship in each groove
25 34. The undercut portions 36 form shoulder surfaces 38 that are designed to engage the surfaces 32 of terminal 18, as will later be described.

This Sheet Has Been Replaced



In Fig. 8a, the connector 10 is shown in a intermediate stage of manufacture. In this stage, an array of terminals 18 in coplanar, side-by-side relationship may be formed by stamping from terminal sheet stock. As shown in the figure, the ends of the terminals 18 have been

5 preliminarily bent to form the contact portion 21 of the cantilevered spring arm 20 and the printed circuit board contact portion 26. The connector body 12 is preferably formed by overmolding or insert molding the connector body 12 onto the array of terminals 18, so that the terminals are securely held in the body 12.

10 Referring to Fig. 8b, the cantilevered spring portion 20 has been formed by bending. Also, the beam portion 24 is formed by applying a force in the direction of arrow F1 at or near the tip of the section 24 to bend the section 24 about a bend radius formed generally in the area of region 39. Eventually, the beam portion 24 is bent toward the full line
15 portion shown in Fig. 8c. At this time, force F1 is maintained on the end of the beam 24. At the same time, a force F2 is applied to the mid-section of the beam to extend the length of the beam to position the tip section 26 toward the dotted line position shown in Figs. 8c and 8d. At this time, the surface 32 of each of the ears 28, 30 is positioned in general
20 alignment with the shoulder surfaces 38. After the force F2 is removed, the beam retracts so that the surfaces 32 of the ears 28, 30 are retained against the shoulder surfaces 38. In this manner, the portion 26 is located and a desired amount of preload is imparted on it.

The terminal section 24 operates generally in the manner of a Euler's
25 buckling beam whereby, as the beam is buckled, it changes length. That is, when a force the direction of arrow F2 is applied, the beam lengthens in the direction of arrow L1. Conversely, when the force F2 is removed,

This Sheet Has Been Replaced



the spring force in the beam returns the beam to its original shape, thereby shortening the length of the beam and raising the contact section 26 toward the connector body 12.

Fig. 8e shows the connector 10 substantially in a rest position, with the printed circuit board contact portion 26 extending beneath the housing. Fig. 8f shows the connector in mated condition, wherein a force in the direction of arrow F3 holds the connector 10 against the substrate 40 causing the beam 24 to be buckled. The resulting deflection generates a normal force pressing contact portion 26 against PCB 40. In addition, a force applied in the direction of arrow F4 to the LCD 42 causes the contact section 20 to deflect, thereby generating a normal force pressing contact portion 21 against LCD 42.

As shown in Fig. 9a, in a typical application, a frame 44 is provided to support the LCD 42 and the connector 10. In this arrangement, the LCD 42 is supported on portions (not shown) of the frame 44 and the connector 10 is inserted into the frame 44 by pushing the leg 14 of the connector through an aperture or recess in the frame 44. To accomplish this, a force in the direction of arrow F6 is placed on the connector 10 to insert the connector into the frame. In doing so, a retention tang 46 formed on the back of the connector body 12 is forced past the retention edge 48 of the opening. In this condition, the cantilevered beam contact 20 and the buckling beam 24 are deflected to a maximum extent, as the bottom edge of the connector is pressed against the surface of the printed circuit board 40. This figure also illustrates the action of the connector if,

This Sheet Has Been Replaced



after assembly, a downward force is applied to the connector/LCD assembly, as by pressing downwardly on the LCD. An advantage of this construction is that the electrical connection at the level of contact portion 26 is maintained, even though a relatively high compressive force is repeatedly applied to connector 10. Fig. 9d shows the final mated position of the connector 10 wherein the retention tang 46 is retained against the surface 48 and the connector 10 has moved upward slightly away from the PCB 40, as a result of the spring force in beam 24.

It is to be further noted that the printed circuit board contact portion 26 undergoes a wiping and rolling action during this operation, to effect proper electrical connection with contact pads on PCB 40. This occurs as a result of the imposition of a vertical force on the beam section 24, which causes the section 26 to move along the surface of PCB 40 in the direction of arrow F5 (Fig. 9a). As this occurs, the contact portion 26 also rotates about a contact point between radius 32 and shoulder surface 38.

The connector disclosed has many advantages. The Euler's buckling beam arrangement provides a relatively long spring travel using only a small area of the footprint of the connector. It also provides simplified locating and pre-loading of the contact portion 26. It further allows a contact wiping and cleaning action, thereby providing good contact. Further, this approach eliminates the need for conductive elastomeric members between the connector and the PCB.

This Sheet Has Been Replaced



While the present invention has been described in connection with the preferred embodiments of the various figures, it is to be understood that other similar embodiments may be used or modifications and additions may be made to the described embodiment for performing
5 the same function of the present invention without deviating therefrom. Therefore, the present invention should not be limited to any single embodiment, but rather construed in breadth and scope in accordance with the recitation of the appended claims.

This Sheet Has Been Replaced



Claims**WHAT IS CLAIMED IS:**

1. An electrical connector comprising:
 - 5 (a) an insulative body comprising a first portion and a second portion extending generally perpendicularly from the first second portion; and
 - (b) a conductive means comprising a retention section where
10 said conductive means is retained by the second portion of the insulative body and a resilient section extending adjacent the first portion of the insulative body.
2. The electrical connector of claim 1 wherein the first portion of the
15 insulative body is a vertical leg.
3. The electrical connector of claim 2 wherein the second portion of the insulative body is a horizontal top.
4. The electrical connector of claim 1 wherein the conductive means
20 comprises a plurality of spaced metal terminals.
5. The electrical connector of claim 4 wherein the metal terminals are stamped metal terminals.
- 25 6. The electrical connector of claim 4 wherein the terminals include a retention means.

This Sheet Has Been Replaced





7. The electrical connector of claim 1 wherein the vertical leg has a rear side and the resilient section of the conductive means extends along said rear side of the vertical leg.
- 5 8. The electrical connector of claim 4 wherein each of said plurality of metal terminals are retained in one of a plurality of grooves in the insulative body.
9. The electrical connector of claim 1 wherein the resilient section of
10 the conductive means has a terminal contact portion.
10. The electrical connector of claim 8 wherein the lower terminal contact portion of the resilient section of the conductive means is formed as a curved surface.
- 15 11. The electrical connector of claim 8 wherein retention means are provided for the resilient section of the conductive means adjacent the lower terminal contact portion.
- 20 12. The electrical connector of claim 8 wherein the retention section of the conductive means includes a cantilevered spring contact.
13. The electrical connector of claim 8 wherein the cantilevered spring contact extends downwardly and rearwardly toward the first portion of the
25 insulative body.

This Sheet Has Been Replaced





10

EL-6162

14. The electrical connector of claim 12 wherein the terminal contact portion of the resilient section of the conductive means engages a printed circuit board.
- 5 15. The electrical connector of claim 14 wherein the cantilevered spring contact of the retention section of the conductive means engages a planar electrical device.
- 10 16. The electrical connector of claim 15 wherein the planar electrical device is a liquid crystal display.
17. The electrical connector of claim 1 wherein the resilient section of the conductive means generally forms a Euler's Beam structure.
- 15 18. The electrical connector of claim 1 wherein the resilient section of the conductive means changes length as it buckles.
19. An assembly comprising:
- 20 (a) a printed circuit board;
- (b) a planar electrical device positioned in spaced generally arrangement from the printed circuit board;
- 25 (c) an electrical connector comprising (i) an insulative body comprising a leg portion having a rear side and extending from adjacent the printed circuit board and a top section extending from said leg portion in generally parallel relation to said planar electrical device, and (ii) a conductive means comprising a retention means retained by the top portion of

This Sheet Has Been Replaced





5 the insulative body and having a forward spring extension interposed between the top portion of the insulative body and the planar electrical device and a resilient section extending along the rear side of the leg portion of the insulative body and having a terminal contact portion interposed between said leg portion and the printed circuit board.

10 20. The assembly claim 19 which further comprises a frame member which engages the rear side of the leg portion of the insulative body.

21. A method of providing an electrical connection between a planar electrical device and a printed circuit board comprising:

- 15 (a) providing an insulative body comprising a leg portion having a rear side and a top portion extending generally perpendicularly from said leg portion and having a front end and fixing a conductive means in parallel relation to the top portion such that said conductive means extends in both a forward and rearward direction beyond said top portion;
- 20 (b) bending the conductive means adjacent the front end of the top section to form a cantilevered spring contact;
- (c) bending the conductive means to form a resilient section having a terminal contact adjacent the leg portion of the insulative body and fixing said resilient section of said leg portion adjacent said terminal contact;
- 25 (d) then positioning the insulative body and conductive means such that the cantilevered spring contact engages a planar





12

EL-6162

electrical device and so that the terminal contact of the resilient section engages the printed circuit board.

This Sheet Has Been Replaced

