housed in the shoe must not be known to any person. That is, high security is required for the casino shoe. In particular, when opening the package, taking out the plurality of playing cards and loading them into the shoe, it is necessary to prevent a player and the dealer from knowing the contents of the playing cards.

[0006]

Moreover, the game must be interrupted while the new playing cards are loaded into the shoe. In a case where this interruption is long, game participants become bored and casino sales decreases. Therefore, it is desirable that the loading of the playing cards into the shoe can be performed smoothly.

[0007]

Embodiments of the present invention seek to provide a security electronic shoe for a casino which can load a playing card smoothly while ensuring security.

[0008]

A security electronic shoe for a casino according to an aspect of the present invention is a security electronic shoe for a casino configured to house a plurality of playing cards to be drawn one by one for a game, comprising: a housing portion configured to house a stacked plurality of playing cards; an opening portion configured to expose a leading playing card among the plurality of playing cards housed in the housing portion; a draw guide portion configured to guide draw of the leading playing card from the opening portion; and a weight configured to push a last playing card of the plurality of playing cards toward the opening portion, wherein a bottom portion of the housing portion slopes so as to descend toward the opening portion, the weight is configured to be movable on the bottom portion of the housing portion toward the opening portion in a state pushing the last playing card toward the opening portion, according to that the last playing card moves toward the opening portion, accompanying that the leading playing card is drawn in sequence, and the housing portion has a structure in which an upper surface and at least one side surface on a side facing in a direction of the draw are configured to be opened, and the plurality of playing cards can be loaded into the housing portion through the opened portion from at least the opened side surface.