

IMAGE ACQUISITION DEVICE

5 CROSS-REFERENCE TO RELATED APPLICATION

The present disclosure claims priority to Chinese Patent Application No. 201820512430.5, filed on April 10, 2018, which is incorporated herein by reference in its entirety.

10

TECHNICAL FIELD

The disclosure relates to information acquisition technologies, and in particular, to an image acquisition device.

BACKGROUND

20 An identity document acquisition device is a device capable of acquiring information on a user's identity document; however, existing identity document information acquisition devices are not compatible with acquisition of multiple types of identity documents. If there is a need to acquire an identity card, there is a need to acquire the identity card by using an identity card acquisition device (also called an identity card reader); and if there is a need to acquire a passport, there is a need to acquire the passport by using a passport acquisition device (also called a passport reader). Different identity document information acquisition devices are needed for different identity documents, so that the costs are high and the user experience is poor.

30

SUMMARY

To solve the technical problem above, embodiments of this disclosure provide image acquisition devices.

35 An image acquisition device provided according to embodiments of this disclosure includes: a main body structure, which is provided with an image acquisition means and at least two accommodating structures; the at least two

accommodating structures includes a first accommodating structure configured to place a first target object and a second accommodating structure configured to place a second target object, where

the first accommodating structure is arranged at a first position of the main body structure, the first position satisfying the condition that the first target object placed on the first accommodating structure is located within acquisition area coverage of the image acquisition means; and

the second accommodating structure is arranged at a second position of the main body structure, the second position satisfying the condition that the second target object placed on the second accommodating structure is located within the acquisition area coverage of the image acquisition means.

In the embodiments of this disclosure, the main body structure is provided with a recess structure, and the image acquisition means is arranged at the bottom of the recess structure.

In the embodiments of this disclosure, an opening of the recess structure faces a first side surface of the main body structure, and the first side surface is provided with the first accommodating structure.

In the embodiments of this disclosure, the first side surface is provided with the first accommodating structure, including:

a first hollow structure is provided at a first position on the first side surface corresponding to the opening of the recess structure, and a slot for fixing the first target object is provided at the periphery of the first hollow structure.

In the embodiments of this disclosure, the second accommodating structure is formed between the first side surface and a plane where the opening of the recess structure is located, where a carrier stage for fixing the second target object is provided at the periphery of the opening of the recess structure.

In the embodiments of this disclosure, a light supplement means is provided inside the recess structure.

In the embodiments of this disclosure, a light guide material is provided on a surface of the recess structure.

In the embodiments of this disclosure, a second side surface of the main body structure is provided with a base for fixing the main body structure on a bearing surface.

In the embodiments of this disclosure, the main body structure is further provided with a control means configured to control the image acquisition means, where the control means is a control button or a touch screen.

5 In the embodiments of this disclosure, the main body structure is further provided with a communication interface configured to enable the image acquisition device to communicate with an external device, and the communication port at least includes a Universal Serial Bus (USB) port.

The technical solutions provided in the embodiments of this disclosure may include the following beneficial effects:

10 According to the technical solutions in the embodiments of this disclosure, the image acquisition device includes: a main body structure, which is provided with an image acquisition means and at least two accommodating structures, the at least two accommodating structures including a first accommodating structure configured to place a first target object and a second accommodating structure configured to place a
15 second target object, where the first accommodating structure is arranged at a first position of the main body structure, the first position satisfying the condition that the first target object placed on the first accommodating structure is located within acquisition area coverage of the image acquisition means; and the second accommodating structure is arranged at a second position of the main body structure,
20 the second position satisfying the condition that the second target object placed on the second accommodating structure is located within the acquisition area coverage of the image acquisition means. By adopting the technical solutions in the embodiments of this disclosure, where a device is provided with at least two accommodating structures for respectively accommodating different types of target objects (e.g., identity
25 documents), a function of supporting acquisition of multiple types of identity documents is implemented, costs of an identity document information acquisition device are reduced, and user experience is improved.

It should be understood that the above general description and the following detailed description are merely exemplary and explanatory and are not intended to
30 limit the present disclosure.

BRIEF DESCRIPTION OF DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments consistent with this disclosure and, together with the specification, serve to explain the principles of this disclosure.

FIG. 1 is a schematic structural composition diagram of an image acquisition device in an embodiment of this disclosure;

FIG. 2 is a schematic structure diagram of an image acquisition device according to an embodiment of this disclosure;

FIG. 3 is a front view of an image acquisition device according to an embodiment of this disclosure;

FIG. 4 is a back view of an image acquisition device according to an embodiment of this disclosure;

FIG. 5 is a top view of an image acquisition device according to an embodiment of this disclosure;

FIG. 6 is a bottom view of an image acquisition device according to an embodiment of this disclosure;

FIG. 7 is a left view of an image acquisition device according to an embodiment of this disclosure;

FIG. 8 is a right view of an image acquisition device according to an embodiment of this disclosure.

DETAILED DESCRIPTION

To understand the features and technical content of the embodiments of this disclosure in more detail, the following describes implementations of the embodiments of the present disclosure in detail with reference to the accompanying drawings. The accompanying drawings are intended for reference only, and not intended to limit the embodiments of this disclosure.

FIG. 1 is a schematic structural composition diagram of an image acquisition device according to an embodiment of this disclosure. As show in FIG. 1, the image acquisition device includes: a main body structure 11, which is provided with an image acquisition means 12 and at least two accommodating structures, the at least two accommodating structures including a first accommodating structure 13 configured to place a first target object and a second accommodating structure 14

configured to place a second target object, where

the first accommodating structure 13 is arranged at a first position of the main body structure 11, the first position satisfying the condition that the first target object placed on the first accommodating structure 13 is located within acquisition area

5 coverage of the image acquisition means 12; and

the second accommodating structure 14 is arranged at a second position of the main body structure 11, the second position satisfying the condition that the second target object placed on the second accommodating structure 14 is located within the acquisition area coverage of the image acquisition means 12.

10 In the embodiment of this disclosure, the shape of the main body structure 11 is not limited and may be, for example, a cubic structure, an irregular polyhedron structure, or the like.

In the embodiment of this disclosure, the main body structure 11 is provided with the image acquisition means 12 and the at least two accommodating structures, for example, two accommodating structures, three accommodating structures, or the like. In the embodiment of this disclosure, different accommodating structures can accommodate target objects with different sizes, for example, the first accommodating structure 13 can accommodate the first target object and the second accommodating structure 14 can accommodate the second target object. In one example, the first target object is an identity card and the second target object is a passport. Certainly, the types of the first target object and the second target object are not limited thereto, and may further be other types of identity documents such as a driver's license, a social security card, and an all-in-one card.

25 In the embodiment of this disclosure, the position of the first accommodating structure 13 on the main body structure 11 needs to satisfy that the first target object placed on the first accommodating structure 13 is located within the acquisition area coverage of the image acquisition means 12. In such a way, when a user places the first target object on the first accommodating structure 13, the image acquisition means 12 can acquire an image of the first target object. Furthermore, the image acquisition means 12 in the embodiment of this disclosure has a facial photo acquisition function. The image acquisition means 12 provided in the embodiment of this disclosure can not only acquire an image of the first target object, but also preliminarily recognize the image of the first target object, thereby capturing a facial

image area, and then send the image in the facial image area (i.e., a facial photo) to other processing devices (e.g., a laptop and a desktop computer) for facial information recognition and comparison. Taking an application scenario of real-time facial comparison as an example, the image acquisition device sends a facial photo on an
5 acquired identity document to an identity authentication machine (called SenseID), and meanwhile, a real-time facial image is acquired by means of a camera on the SenseID, and the facial photo on the identity document is compared with the real-time facial image to obtain the facial recognition result (that is, whether the person currently photographed by the camera and the person in the photo on the identity
10 document are the same one). Similarly, the position of the second accommodating structure 14 on the main body structure 11 needs to satisfy that the second target object placed on the second accommodating structure 14 is located within the acquisition area coverage of the image acquisition means 12. In such a way, when a user places the second target object on the second accommodating structure 14, the
15 image acquisition means 12 can acquire an image of the second target object. Furthermore, the image acquisition means 12 in the embodiment of this disclosure has a facial photo acquisition function. The image acquisition means 12 provided in the embodiment of this disclosure can not only acquire an image of the second target object, but also preliminarily recognize the image of the second target object, thereby
20 capturing a facial image area, and then send the image in the facial image area to other processing devices (e.g., a laptop and a desktop computer) for facial information recognition and comparison.

The image acquisition device in the embodiment of this disclosure is described in detail below with reference to the specific examples.

25 FIG. 2 is a schematic structure diagram of an image acquisition device according to an embodiment of this disclosure. With reference to FIG. 2, the image acquisition device includes a main body structure 11, which is provided with an image acquisition means 12 (covered and not shown) and at least two accommodating structures, the at least two accommodating structures including a first accommodating
30 structure 13 configured to place a first target object and a second accommodating structure 14 configured to place a second target object, where the first accommodating structure 13 is arranged at a first position of the main body structure 11, the first position satisfying the condition that the first target object placed on the first

accommodating structure 13 is located within acquisition area coverage of the image acquisition means 12; and the second accommodating structure 14 is arranged at a second position of the main body structure 11, the second position satisfying the condition that the second target object placed on the second accommodating structure 14 is located within the acquisition area coverage of the image acquisition means 12.

In this example, the first accommodating structure 13 is particularly applicable to card-like identity documents, such as identity cards, social security cards and other identity documents of a standard size. The second accommodating structure 14 is particularly applicable to identity cards of other sizes, such as passports, driver's licenses and student ID cards. The image acquisition device in the embodiment of this disclosure supports a function of acquiring multiple types of identity document images, thereby facilitating the acquisition of the identity document images of different sizes and different shapes.

In this example, the main body structure 11 of the image acquisition device is approximately cubic and has six side surfaces as a whole, where the top surface is a first side surface and is provided with a section structure, and other side surfaces are approximately planar.

FIG. 3 to FIG. 8 are schematic diagrams of an image acquisition device according to an embodiment of this disclosure from different angles of view. FIG. 3 is a front view of an image acquisition device according to an embodiment of this disclosure. FIG. 4 is a back view of an image acquisition device according to an embodiment of this disclosure. FIG. 5 is a top view of an image acquisition device according to an embodiment of this disclosure. FIG. 6 is a bottom view of an image acquisition device according to an embodiment of this disclosure. FIG. 7 is a left view of an image acquisition device according to an embodiment of this disclosure. FIG. 8 is a right view of an image acquisition device according to an embodiment of this disclosure. With reference to FIG. 3 to FIG. 8, the main body structure 11 is provided with a recess structure, and the image acquisition means 12 is provided at the bottom of the recess structure. An opening of the recess structure faces the first side surfaces of the main body structure 11, and the first side surface is provided with a first accommodating structure 13. A first hollow structure is provided at a first position on the first side surface corresponding to the opening of the recess structure, and a slot for fixing the first target object is provided at the periphery of the first hollow

structure. A second accommodating structure 14 is formed between the first side surface and a plane where the opening of the recess structure is located, where a carrier stage for fixing the second target object is provided at the periphery of the opening of the recess structure. A second side surface of the main body structure 11 is provided with a base 15 configured to fix the main body structure 11 on a bearing surface. The main body structure 11 is further provided with a control means 16 configured to control the image acquisition means 12. The main body structure 11 is further provided with a communication interface 17 configured to enable the image acquisition device to communicate with an external device.

In one example, a light supplement means (not shown) is provided inside the recess structure. Furthermore, a light guide material is provided on a surface of the recess structure. In this way, the brightness of a photographing environment can be enhanced so that high quality images can be obtained by photographing under an environment with sufficient light.

In one example, the base 15 may be multiple rubber pads which are evenly distributed at the bottom of the image acquisition device and have an effect of preventing bottom abrasion of the image acquisition device and a function of stabilizing the image acquisition device.

In one example, the control means 16 may be a control button or a touch screen. For example, the control means 16 includes two control buttons, one is configured to power on or off the image acquisition device, and the other one is configured to switch photographing modes, for example, a first photographing mode is a mode of photographing a first target object, and a second photographing mode is a mode of photographing a second target object. Different photographing modes correspond to different optical parameters, such as focal length, so as to adaptively photograph different target objects to obtain clear images.

In one example, the communication interface 17 at least includes a USB interface, which is configured to send the acquired identity document image to other devices, such as an identity authentication machine (as also called SenseID) product, by means of a USB data cable, so that the SenseID compares the information of the identity document image with real-time facial information.

In the embodiment of this disclosure, the first accommodating structure 13 and the second accommodating structure 14 are distributed in a layered structure, and the

first accommodating structure 13 is located at the upper layer of the second accommodating structure 14. When a user wants to place a first target object (e.g., an identity card), the user only needs to directly place the first target object on the first accommodating structure 13, and when the user wants to place a second target object
5 (e.g., a passport), the user needs to insert the second target object into the second accommodating structure 14 from a space between the first side surface and the plane where the opening of the recess structure is located.

By adopting the image acquisition device in the embodiments of this disclosure, where one device is provided with at least two accommodating structures
10 for respectively accommodating different types of target objects (e.g., identity documents), a function of supporting acquisition of multiple types of identity documents is implemented, costs of an identity document information acquisition device are reduced, and user experience is improved.

The technical solutions recited in the embodiments of this disclosure can be
15 arbitrarily combined without causing conflicts.

The descriptions above are only specific implementations of this disclosure. However, the scope of protection of this disclosure is not limited thereto. Within the technical scope disclosed by this disclosure, any variation or substitution that can be easily conceived of by those skilled in the art should all fall within the scope of
20 protection of this disclosure.

INDUSTRIAL APPLICABILITY

25 According to the technical solutions in the embodiments of this disclosure, the image acquisition device includes: a main body structure, which is provided with an image acquisition means and at least two accommodating structures, the at least two accommodating structures including a first accommodating structure configured to place a first target object and a second accommodating structure configured to place a
30 second target object, where the first accommodating structure is arranged at a first position of the main body structure, the first position satisfying the condition that the first target object placed on the first accommodating structure is located within acquisition area coverage of the image acquisition means; and the second accommodating structure is arranged at a second position of the main body structure,

the second position satisfying the condition that the second target object placed on the second accommodating structure is located within the acquisition area coverage of the image acquisition means. In this way, one device provided with at least two accommodating structures for respectively accommodating different types of target objects (e.g., identity documents), so that a function of supporting acquisition of multiple types of identity documents is implemented, costs of an identity document information acquisition device are reduced, and user experience is improved.

CLAIMS

5 1. An image acquisition device, comprising: a main body structure provided with an image acquisition means and at least two accommodating structures, the at least two accommodating structures comprising a first accommodating structure configured to place a first target object and a second accommodating structure configured to place a second target object, wherein

10 the first accommodating structure is arranged at a first position of the main body structure, the first position satisfying the condition that the first target object placed on the first accommodating structure is located within acquisition area coverage of the image acquisition means; and

the second accommodating structure is arranged at a second position of the
15 main body structure, the second position satisfying the condition that the second target object placed on the second accommodating structure is located within the acquisition area coverage of the image acquisition means.

2. The image acquisition device according to claim 1, wherein the main body structure
20 is provided with a recess structure, and the image acquisition means is arranged at the bottom of the recess structure.

3. The image acquisition device according to claim 2, wherein an opening of the recess structure faces a first side surface of the main body structure, and the first side
25 surface is provided with the first accommodating structure.

4. The image acquisition device according to claim 3, wherein the first side surface is provided with the first accommodating structure, comprising:

a first hollow structure is provided at a first position on the first side surface
30 corresponding to the opening of the recess structure, and a slot for fixing the first target object is provided at the periphery of the first hollow structure.

5. The image acquisition device according to claim 3, wherein the second accommodating structure is formed between the first side surface and a plane where
35 the opening of the recess structure is located, wherein a carrier stage for fixing the

second target object is provided at the periphery of the opening of the recess structure.

6. The image acquisition device according to claim 1, wherein a light supplement means is provided inside the recess structure.

5

7. The image acquisition device according to claim 6, wherein a light guide material is provided on a surface of the recess structure.

8. The image acquisition device according to claim 1, wherein a second side surface
10 of the main body structure is provided with a base for fixing the main body structure on a bearing surface.

9. The image acquisition device according to any one of claims 1 to 8, wherein the main body structure is further provided with a control means configured to control the
15 image acquisition means, wherein the control means is a control button or a touch screen.

10. The image acquisition device according to any one of claims 1 to 8, wherein the main body structure is further provided with a communication interface configured to
20 enable the image acquisition device to communicate with an external device, and the communication port at least comprises a Universal Serial Bus (USB) interface.