

The invention relates to a process for electrochemically regenerating chromosulfuric acid in which a novel electrolysis cell is used.

5 In the electrochemical regeneration of chromosulfuric acid which has been used in oxidation processes, electrodes made of lead or lead alloys and electrolysis cells having lead walls, for example steel troughs lined with lead, are normally used.

10 The disadvantage of using lead or lead alloys is that the anodes lose their activity relatively fast and can be reutilized only to a limited extent and that a high hydrogen overvoltage (approximately 1.1 volt) appears at cathodes made of lead and lead alloys. It has also not yet been possible to carry out the electrolysis in sealed
15 cells and to extract, in addition to the Cr^{6+} , also the hydrogen evolved at [lacuna] cathode side. On the contrary, the hydrogen produced has to be sucked off the cells covered with foils and diluted with air in a ratio of about 50:1 so that work can be carried out safely
20 below the explosion limit of about 4% H_2 in air. This procedure is uneconomical and open to objection for reasons of occupational hygiene and environmental protection.

25 A membrane cell for alkali-metal chloride electrolysis which comprises two half shells, one half shell being pressed from titanium sheet and the other from stainless steel or nickel sheet, is known (cf. Bergner and Hannesen, GDCH-Jahrestagung Angew. Elektrochemie, October 1984). The electrodes are each composed of a slatted
30 metal sheet which is activated and welded into the half shell. At regular intervals, the electrodes are joined to the rear walls of the half shells by corrugated fasteners. The two half shells of a cell are separated from one another by a permeable membrane and seals.

35 Moreover, a process for the electrochemical oxidation of

Cr³⁺ to Cr⁶⁺ is known, wherein an electrolysis cell is used which is composed of an anode chamber and a cathode chamber, the two chambers being mutually separated by a semipermeable wall and the semipermeable wall being impermeable for Cr³⁺ ions (cf. US-PS 4,006,067). During the electrolysis, the porous anode is filled with the anolyte.

The object was to find a process in which the chromosulfuric acid is regenerated in a sealed cell system and the hydrogen produced can be extracted.

It was found that the membrane cell developed for alkali-metal chloride electrolysis is also suitable in principle for the electrochemical regeneration of chromosulfuric acid.

The invention consequently relates to a process for electrochemically regenerating chromosulfuric acid by anodic oxidation of Cr³⁺ ions to Cr⁶⁺ ions, in which the anolyte contains 20 to 200 g/dm³ total CrO₃ and 100 to 600 g/dm³ H₂SO₄ and the catholyte contains 50 to 500 g/dm³ H₂SO₄, which process comprises carrying out the regeneration in an electrolysis cell which comprises two tub-like metal half shells whose open sides face one another, a plate which is made of a titanium, zirconium, vanadium or tantalum expanded metal, is provided with holes or slots, is activated by a coating which has a high overvoltage with respect to oxygen, and is joined to the anode tub by corrugated fasteners being present in the anode tub as anode, a slatted metal sheet made of nickel or a nickel alloy which is joined to the cathode tub by corrugated fasteners being present in the cathode tub as cathode, anode tub and cathode tub being separated from one another by a current-permeable, hydraulically sealing partition and seals and being held together by a clamping device, the temperature being 40 to 110°C and the current density being 100 to 2500 A/m².

The electrolysis cell to be used for the process according to the invention is explained with reference to Figures 1 to 4. Figure 1 shows a perspective overall view of an electrolysis cell, Figure 2 shows a section along the line II-II in Figures 1, 3 and 4, Figure 3 shows a section along the line III-III in Figures 1, 2 and 4 and Figure 4 shows a plan view in the direction of the arrow IV in Figures 1, 2 and 3.

The electrolysis cell to be used for the process according to the invention is explained by reference to Figures 1 to 4. Figure 1 shows a perspective overall view of an electrolysis cell, Figure 2 shows a section along the line II-II in Figure 1, 3 and 4, Figure 3 shows a section along the line III-III in Figure 1, 2 and 4, and Figure 4 shows a plan view in the direction of the arrow IV in Figure 1, 2 and 3.

According to Figure 1, the cell comprises two tub-like metal half shells (1) and (2). The anode tub (1) contains a perforated or slotted plate (3) (perforated metal sheet, expanded metal or the like) which is joined to the anode tub (1) by means of corrugated fasteners (4). The plate (3) acts as anode. The cathode tub (2) contains a metal sheet (5) as cathode which is connected to the tub (2) by means of corrugated fasteners (6). The cathode is composed of a slatted metal sheet.

Anode tub (1) and cathode tub (2) are separated from one another by a current-permeable, hydraulically sealing partition (7) and seals (8) and (9). They are held together to form a unit by two steel frames (10) and (11) which are screwed to each other in an insulated manner. The screws (16) are insulated by means of plastic bushes (17) and plastic washers (18). Located at the bottom of the anode tub (1) is an inlet pipe (12) for the anolyte and located on the cathode tub (2) is an inlet pipe (14) for the catholyte. Located at the top of the tubs (1) and (2) are the drainage pipes (13) and (15).

Figure 2 shows, in addition, the position of the corrugated fasteners (4) and (6) and also the offset mounting of the inlet pipes (12) and (14).

5 From Figures 3 and 4 finally the encircling steel frame (11) can be seen.

The anode tub (1) and the corrugated fasteners (4) are composed of titanium, whereas the cathode tub (2) and the corrugated fasteners (6) are composed of nickel or a nickel alloy, for example Hastelloy.


10 It has now been found that the so-called "valve metals" titanium, tantalum, vanadium and zirconium used already in alkali-metal chloride electrolysis are also suitable as materials for the anode (3) under the corrosive conditions of chromic acid electrolysis. Under anodic
15 current loading, these metals form a coherent oxide film on their surface which protects the basic material. If the surface of the anodes is not activated, the oxide layer formed prevents further current flow. For chromic acid electrolysis, only electron-conducting oxides which
20 exhibit a high overvoltage with respect to oxygen, for example lead dioxide, manganese dioxide, tin dioxide, tantalum oxides or iridium oxides, are possible as suitable activation layers for these metals. One of the highest overvoltages for oxygen is exhibited by lead
25 dioxide, which is preferred. Thus, the electrochemical reaction



which proceeds anodically, yields current efficiencies of between 96% and 88% with current densities of 200 A/m² to
30 2500 A/m² at a titanium anode coated with PbO₂.

Suitable materials for the cathode (5) are nickel and nickel alloys, for example Hastelloy. If sulfuric acid is used as catholyte, protons are discharged and hydrogen

evolved, which leaves the cathode space as a gas, at the cathode in accordance with the reaction equation



5 Nickel is only resistant to 10 to 35% sulfuric acid, however, if it is cathodically polarized. It is therefore necessary to prevent the nickel cathodes being exposed at zero current to the sulfuric acid.

10 At a current density of 100 A/m², the hydrogen over-voltage at nickel is relatively low at a level of 0.42 V, and in comparison therewith it is fairly high at a level of 1.09 V at lead under the same conditions. This has the consequence that the use of nickel as cathode results in a correspondingly lower cell voltage.

15 Cation-active ion exchanger membranes made of perfluorinated polymers containing sulfonyl groups have proved very satisfactory as current-permeable, hydraulically sealing partition (7) between anode space and cathode space. They exhibit an excellent durability and selectivity in the electrolytes used up to temperatures of 20 110°C. The use of such membranes makes it possible to collect the cathodically evolved hydrogen separately and supply it to a further utilization.

25 The electrolysis cell to be used and assembled according to the invention can be operated after filling the cathode space with catholyte and the anode space with anolyte and after pressing current leads from a rectifier onto the anode tub rear wall and cathode tub rear wall. Catholyte and anolyte are each continuously fed in from stock containers by means of pumps at the lower end of 30 the electrode space. The electrolyte leaves the cell at the top end. The anolyte with the desired composition is supplied for further use, while the catholyte is continuously circulated via a buffer container and concentrated again from time to time.

The oxygen evolution (due to water decomposition) which proceeds to a small extent at the anode and is undesirable per se ensures an adequate mixing of the anolyte and promotes the diffusion of Cr^{3+} at the anode surface. This effect can be intensified by additionally injecting inert gas into the anode space.

Preferably, this electrolysis cell is not operated separately. On the contrary, in a cell assembly a plurality of cells is pressed together rear wall to rear wall by means of a clamping device. Consequently, the current fed in with copper rails at the beginning of the cell array is able to flow through all the cells and is drained at the end of the array by copper rails. Special contact strips ensure a good current transfer between the cells. If the cells are operated in this manner, the cell is a bipolar one. All the individual elements are connected in series.

The concentration in the anolyte is 20 to 200, preferably 100 to 200, in particular 130 to 170 g/dm³ total CrO_3 , and 100 to 600, preferably 300 to 600, in particular 450 to 550 g/cm³ H_2SO_4 . The catholyte contains 50 to 500, preferably 300 to 350 g/dm³ H_2SO_4 .

The electrolysis is carried out at a temperature of 40 to 110, preferably 80 to 110°C, and at a current density of 100 to 2500, preferably 500 to 2500 A/m².

The process according to the invention will now be explained by way of the following preliminary experiments and the example.

Preliminary experiment 1

The electrolysis was carried out in a round laboratory membrane cell which was composed of 2 glass shells and was flanged together so as to seal by means of two PTFE O-rings. The two glass shells form the cathode space and

anode space. They were separated by a polymer membrane made of a perfluorinated polymer which was clamped between the two O-rings.

5 The two circular electrodes were eccentrically mounted and direct current was supplied via these mountings. It was possible to vary anode and cathode in their distance from one another and from the membrane by means of spacing strips. Anolyte and catholyte were heated with heating rods to 90°C in the two cell halves and were kept
10 constant at this temperature during the electrolysis.

Anode space volume:	95 cm ³
Cathode space volume:	90 cm ³
Active anode area:	36 cm ²
Cathode area:	36 cm ²

15 The cathode was composed of non-activated nickel expanded metal, the anode of titanium expanded metal which was coated on all sides with electrodeposited PbO₂. The cathode-anode spacing was 8 mm.

Anolyte: 550 - 560 g/l H₂SO₄
20 200 g/l total CrO₃ = 104 g/l Cr
Catholyte: 440 - 445 g/l H₂SO₄ (35%)

At the same time, the catholyte was circulated by pumping through the cathode space at a throughput of 9 cm³/h which was constant for all current densities. The elec-
25 trolysis are data obtained shown in Table 1.

Table 1

	Current density (A/m ²)	500	1,500	2,500
	Throughput (cm ³ /h)	21	60	94
	Degree of oxidation (%)	50	52	52
5	Cell voltage (V)	2.25	2.56	2.90
	Current efficiency based on Cr ⁶⁺ formation (%)	96.0	91.5	88.5
	Energy requirement (kWh/kg CrO ₃)	1.95	2.40	2.90

- 10 Total running time: 249 days
 Total current consumption: 26,000 Ah = 7,429 kAh/m²
 CrO₃ produced: 28.97 kg = 8,277 kg/m²

Preliminary experiment 2

- 15 A titanium expanded metal anode activated with tantalum oxide/iridium oxide mixture was tested for its suitability in a second glass cell which corresponded completely to the cell described above in its construction.

- 20 Cathode: nickel expanded metal
 Anode: titanium expanded metal activated with Ta₂O₅/IrO₂
 Membrane: perfluorinated polymer
 Temperature: 90°C
 Anode-cathode spacing: 8 mm
 Electrolyte composition as in Preliminary experiment 1

- 25 A notable feature was the low cell voltage of 1.92 V for a current loading of 500 A/m² compared with that in Preliminary experiment 1. However, the current efficiency in relation to CrO₃ formation of on average only 61% with a comparatively low degree of oxidation of 44% was lower.
 30 This resulted in a relatively high energy requirement of

2.65 kWh/kg CrO_3 at 500 A/m². A heavier gas evolution (analyzed as O_2), which is attributable to the lower oxygen overvoltage of this activation coating compared with PbO_2 , was to be observed on the anode side. With increasing current loading, the current efficiency decreased still further and reached only about 49%, for example, at 1,500 A/m².

Example

Chromosulfuric acid was electrolytically regenerated in a membrane cell as described in Figures 1 to 4.

Anode space volume:	1,150 cm ³
Cathode space volume:	870 cm ³
Anode area:	285 cm ²
Cathode area:	285 cm ²
Anode material:	titanium expanded metal activated with PbO_2
Cathode material:	slat-type nickel lamella sheet
Cathode-anode spacing:	9 mm
Anolyte:	470 g/l H_2SO_4
	160 g/l total $\text{CrO}_3 \hat{=} 83.2 \text{ g/l Cr}$
Catholyte:	440 - 445 g/l H_2SO_4
Temperature:	85 - 95°C
Current density:	500 A/m ²
Throughput:	140 cm ³ /h
Degree of oxidation:	65%
Cell voltage:	2.65 V
Current efficiency:	91% based on Cr^{6+} formation
Energy requirement:	2.25 kWh/kg CrO_3



Patent Claims

1. A process for electrochemically regenerating chromo-sulfuric acid by anodic oxidation of Cr^{3+} ions to Cr^{6+} ions, in which the anolyte contains 20 to 200 g/dm^3 total CrO_3 and 100 to 600 g/dm^3 H_2SO_4 and the catholyte contains 50 to 500 g/dm^3 H_2SO_4 , which process comprises carrying out the regeneration in an electrolysis cell which comprises two tub-like metal half-shells whose open sides face one another, a plate which is made of a titanium, zirconium, vanadium or tantalum expanded metal, is provided with holes or slots, is activated by a coating which has a high overvoltage with respect to oxygen, and is joined to the anode tub by corrugated fasteners being present in the anode tub as anode, a slatted metal sheet made of nickel or a nickel alloy which is joined to the cathode tub by corrugated fasteners being present in the cathode tub as cathode, anode tub and cathode tub being separated from one another by a current-permeable, hydraulically sealing partition and seals and being held together by a clamping device, the temperature being 40 to 110°C and the current density being 100 to 2500 A/m^2 .
2. The process as claimed in claim 1, wherein an ion exchanger membrane which is composed of a perfluorinated polymer is used as current-permeable, hydraulically sealing partition.
3. The process as claimed in claim 1, wherein the electrolysis is carried out in a bipolar cell.