

(43) International Publication Date
6 February 2014 (06.02.2014)

- (51) International Patent Classification:
H04L 5/00 (2006.01) *H04L 25/02* (2006.01)
- (21) International Application Number:
PCT/IB2013/056357
- (22) International Filing Date:
2 August 2013 (02.08.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/679,335 3 August 2012 (03.08.2012) US
13/917,717 14 June 2013 (14.06.2013) US
- (71) Applicant: TELEFONAKTIEBOLAGET L M ERICSSON (PUBL) [SE/SE]; S-164 83 Stockholm (SE).
- (72) Inventors: FRENNE, Mattias; Arkeologvägen 20, S-754 43 Uppsala (SE). ERIKSSON, Erik; Landeryd, Skogss-tugan, S-585 93 Linköping (SE). SORRENTINO, Stefano; Hannebergsgatan 32, S-171 68 Solna (SE).
- (74) Agents: CASON, Todd et al.; 6300 Legacy, MS EVR 1-C-11, Plano, TX 75024 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,


AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: QUASI CO-LOCATED ANTENNA PORTS FOR CHANNEL ESTIMATION

**FIG. 11**

(57) **Abstract:** Systems and methods are disclosed for estimating one or more channel properties of a downlink from a cellular communications network based on quasi co-located antenna ports with respect to the one or more channel properties. In one embodiment, a wireless device receives a downlink subframe including a downlink control channel from the cellular communications network. The wireless device estimates one or more large-scale channel properties for an antenna port of interest in the downlink control channel based on a subset of reference signals that correspond to antenna ports in the cellular communications network that are quasi co-located with the antenna port of interest with respect to the one or more large-scale channel properties. As a result of using the quasi co-located antenna ports, estimation of the one or more large-scale channel properties is substantially improved.