

**SYSTEMS, METHODS, AND APPARATUSES FOR
DISINFECTION AND DECONTAMINATION**

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority from PCT Patent Application No. PCT/US2021/036501, filed on June 8, 2021, which is incorporated by reference herein in its entirety.

BACKGROUND

[0002] Infectious diseases such as human immunodeficiency virus and acquired immune deficiency syndrome (HIV/AIDS), tuberculosis (TB), severe acute respiratory syndrome (SARS-CoV-1), Ebola virus disease (EVD), and coronavirus disease 2019 (COVID-19) are contagious diseases transmissible through direct contact from person to person, through indirect contact by breathing airborne droplets spread from an infected person, and through contact with surfaces of contaminated objects.

[0003] With the COVID-19 pandemic outbreak, facemask or respirator wearing and practicing social distancing may mitigate airborne droplets spread by potential neighboring human carriers. Nevertheless, both of these practices are defensive actions that do not destroy or disinfect the germs or viruses in the airborne droplets. Currently, methods that are used to generate antimicrobial gases or vapor are large and impractical for general household or office use or for personal use in a limited localized space, and methods of generating ClO₂ from liquid and solid precursor chemicals are slow and/or generate low quality ClO₂ solutions.

[0004] Antimicrobial gas, such as chlorine dioxide (ClO₂), has demonstrated capability as an antimicrobial or inactivator for pathogens on hard surfaces. In gas form, ClO₂ has demonstrated capability to disinfect hard surfaces and porous materials within three-dimensional spaces. ClO₂ gas has also been shown to kill or otherwise inactivate airborne pathogens, and even protect against airborne contagion.

[0005] ClO₂ gas is also currently used as a deodorizer in vehicles, rooms, and other enclosed spaces. Typical products used for enclosed space odor removal include placing a cup or container housing one or more dry solid chemical constituents (typically consisting of a chlorite salt and an activator), adding water to activate the ClO₂ generation process, enclosing the ClO₂ generation materials in the space for an extended period of time before opening up the space, removing the spent ClO₂ solution, and allowing the space to air out to reduce ClO₂ concentration to safe levels.

[0006] The present disclosure relates to a safe and effective system and method for quickly and safely generating antimicrobial gas (e.g., ClO_2 gas). Antimicrobial gas may be generated from small amounts of concentrated liquid and solid precursor chemicals and actively dispersing the antimicrobial gas into an enclosed three-dimensional space. Additionally, the present disclosure relates to a safe and effective system and method for monitoring antimicrobial gas concentration in the enclosed three-dimensional space and generating additional antimicrobial gas as necessary to maintain the desired concentration in the space. When used at higher concentrations, the resultant antimicrobial gas will sanitize or disinfect the air and contact surfaces within the enclosed space. At low concentrations (e.g., < 0.1 ppm), the antimicrobial gas can be used to decrease or otherwise inactivate airborne pathogens and actively protect persons in the treated space against airborne contagions.

[0007] The present disclosure also relates to a safe and effective system and method of generating, monitoring, and controlling the concentration of antimicrobial gas that is generated on demand.

SUMMARY

[0008] In one aspect, a closed-loop system for generating and monitoring an antimicrobial is provided, the system comprising: a control sub-system comprising: a controller unit; a communications sub-system comprising: one or more of a wired communication mechanism and a wireless communication mechanism for connecting to an external network; a sensing sub-system comprising: one or more sensor oriented on a portion of the system open to air or contained in one or more plenum, wherein the one or more sensor is operatively connected to the control sub-system; a generation sub-system comprising: a reactor including a mixing chamber, wherein two or more reagents are combined in the mixing chamber to create an antimicrobial, and wherein the antimicrobial is applied to a volume under treatment; wherein the sensing sub-system samples air from the volume under treatment continuously or at intervals and measures the concentration of the antimicrobial present in the air from the volume under treatment; and wherein the generation sub-system generates the antimicrobial when the measured concentration of the antimicrobial in the air from the volume under treatment is below a predetermined threshold value. Additionally, or alternatively, the generation sub-system generates the antimicrobial in response to a difference between a target value and the sensing sub-system measurement.

[0009] In another aspect, a system for generating and monitoring an antimicrobial gas is provided, the system including: a microprocessor and/or a microcontroller; an external communications device; a computational system; an antimicrobial sensor and/or an environmental sensor; and an antimicrobial generator, wherein the external communications device, the

computational system, the antimicrobial generator, and the antimicrobial sensor and/or the environmental sensor are operatively connected to the microprocessor and/or the microcontroller. The system may further include a separate sensor sub-system comprising: a sensor sub-system microprocessor and/or a sensor sub-system microcontroller; a sensor sub-system external communications device; a sensor sub-system antimicrobial sensor and/or a sensor sub-system environmental sensor; and a sensor sub-system computational system. The system may further include a separate generation sub-system comprising: a generation sub-system microprocessor and/or a generation sub-system microcontroller; a generation sub-system external communications device; and a generation sub-system antimicrobial generator. In another aspect, a network of these systems for generating and monitoring an antimicrobial gas is provided.

[0010] In another aspect, a system for generating and monitoring ClO₂ gas is provided, the system comprising: a device housing including an inlet; a microcontroller; one or more reagent containers containing a reagent; a microfluidic liquid dispensing and metering system; a microfluidic device for generating a ClO₂ gas from the reagent(s); a device for separation of ClO₂ gas and post-generator waste in communication with the air pump air duct and an air duct to one or more outlets; on-device or in-device waste storage prior to disposal; and one or more sensing system for either ClO₂ gas or the environment in which the device is installed.

[0011] In another aspect, a ClO₂ gas generator is provided, comprising: a base including a pressure generator; one or more reagent containers holding liquid reagent(s), the containers being pressurized by the pressure generator; a chamber passage in communication with the pressure chamber and the reagent container; one or more control valves in communication with the pressure generator and reagent container; one or more control valves in communication with the chamber passage and a microfluidic chip; a sensor system for determining the quantity, mass, or volume of the reagents transiting the chamber passage; a microfluidic chip having a generation chamber in communication with a second chamber passage; a second chamber passage in communication with a ClO₂ gas-liquid separation chamber; and, a waste container for storage and/or inactivation of post-ClO₂ generator waste products. Alternatively, the one or more reagent container may include a liquid dispensing and metering system, which may include positive displacement pumps (e.g., peristaltic pumps), wherein for a set rotation of the pump shaft a known amount of liquid reagent is pumped, thus not requiring additional measurement of liquid reagent introduced to the chamber.

[0012] In another aspect, a network of systems for generating and monitoring ClO₂ gas, is provided, the network comprising: a plurality of systems for generating and monitoring ClO₂ gas, including: a device housing including an inlet; a microcontroller; one or more reagent containers

containing a reagent; a microfluidic device for generating a ClO₂ gas from the reagent; and a sensing system; wherein the microcontroller includes a communication device capable of communication between the plurality of systems, and wherein the communication device establishes distributed control of each system's microcontroller, wherein the microcontroller is controlled by machine learning algorithms to alter system performance.

[0013] In another aspect, a network of systems for generating and monitoring an antimicrobial gas is provided, the system including: a microprocessor and/or a microcontroller; an external communications device; a computational system; an antimicrobial sensor and/or an environmental sensor; and an antimicrobial generator, wherein the external communications device, the computational system, the antimicrobial generator, and the antimicrobial sensor and/or the environmental sensor are operatively connected to the microprocessor and/or the microcontroller. The system may further include a separate sensor sub-system comprising: a sensor sub-system microprocessor and/or a sensor sub-system microcontroller; a sensor sub-system external communications device; a sensor sub-system antimicrobial sensor and/or a sensor sub-system environmental sensor; and a sensor sub-system computational system. The system may further include a separate generation sub-system comprising: a generation sub-system microprocessor and/or a generation sub-system microcontroller; a generation sub-system external communications device; and a generation sub-system antimicrobial generator.

[0014] In another aspect, the microcontroller of the system will have the computational and local data storage ability to enable closed-loop control of the ClO₂ generation system, including but not limited to: local storage and microcontroller operations on data from sensor systems for ClO₂ levels to space environment variables like barometric pressure, humidity, temperature, occupancy, or sounds that may be used to alter generator system performance automatically or via user intervention; measurement, local storage, and microcontroller operations on data from microfluidic sub-systems such as mass/volume sensors of reagents, rotational or linear movement of positive displacement pumps, pressure generator performance, microfluidic chip-borne sensors, valve status to any other electronic sub-system to provide control as well as storage of system performance data for maintenance, alert, troubleshooting, inactive modes of operation, active modes of operation, and local setup.

[0015] In another aspect, the system has a communication device connected to the microcontroller and/or electronic components such that data from any electronic component within, on, or connected to the housing can be gathered, locally stored, operated on by the microcontroller, and transmitted to external data gathering systems on mobile to fixed devices.

[0016] In another aspect, linear, non-linear, proportional-integral-derivative control, machine learning, and/or artificial intelligence algorithms can be incorporated into the system microcontroller to alter system performance automatically or by user interactions. An example of local control includes alteration of system performance for detection of a virus or bacteria in the ambient air, altitude, temperature, air changes in the local space measured by changes in concentration in the air of spaces containing ClO₂, changes in occupancy by living beings, alterations for user preference, prediction of cycles of occupancy/vacancy, alerts as to normal or abnormal performance of the system, and the like.

[0017] In another aspect, a plurality of systems within a plurality of spaces which are arranged into a group connected via communication devices described above to each other for distributed control via coordination of each system's microcontroller, centralized unit control, and/or a combination of both local and distributed control.

[0018] In another aspect, linear, non-linear, proportional-integral-derivative control, machine learning, and/or artificial intelligence algorithms can be incorporated into the distributed network of systems by the aspects described above; example of distributed control include adjusting individual systems to achieve uniform and/or deliberately non-uniform distribution of ClO₂ in each individual generator's location across an entire building floor, multiple floors, or the entire building due to changes in ClO₂ concentration from HVAC, consumption or self-dissipation of ClO₂ gas, control of day/night generation cycles, sensing patterns across time, three-dimensional volumes, seasonal variations, to previously unknown factors which can be sensed either directly by the sensor systems in/on the system, inferred or traced to the signal measured, or directly traceable to the variations observed in ClO₂ concentrations across a collection of systems installed across distinctly separate to varying interconnection of real world spaces in which control of infectious species is desired.

[0019] In another aspect, the system for distribution and monitoring of ClO₂ gas in a three-dimensional space can be designed for a plurality of operating modes; the first operating mode is designed for occupied spaces, the second mode is designed for un-occupied spaces and may include one or more sub-modes to achieve desired outcomes; future user or engineered modes may be added. These modes may be changed by authorized users on the unit, via connected mobile devices, and/or by a centralized distributed control system connected to a plurality of units.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] FIG. 1A illustrates a schematic of an example system 100 for generating and monitoring an antimicrobial gas.

[0021] FIG. 1B illustrates a schematic of system 100 oriented within a volume under treatment 124.

[0022] FIG. 1C illustrates a schematic of system 100 oriented within a volume under treatment 124.

[0023] FIG. 2A illustrates a schematic of an example complimentary sensing sub-system 120 and generation sub-system 122 for generating and monitoring an antimicrobial gas.

[0024] FIG. 2B illustrates a schematic of sensing sub-system 120 and generation sub-system 122 within a volume under treatment 124.

[0025] FIG. 2C illustrates a schematic of sensing sub-system 120 and generation sub-system 122 used in conjunction with an HVAC system.

[0026] FIG. 2D illustrates a schematic of sensing sub-system 120 within a volume under treatment 124 engaging with generation sub-system 122 outside of the volume under treatment 124.

[0027] FIG. 2E illustrates a schematic of generation sub-system 122 within a volume under treatment 124 engaging with sensing sub-system 120 outside of the volume under treatment 124.

[0028] FIG. 3 illustrates a schematic of an example system 300 for generating and monitoring an antimicrobial gas.

[0029] FIG. 4 illustrates a schematic of an example system 400 for generating and monitoring an antimicrobial gas.

[0030] FIG. 5 illustrates an example blueprint of a network 500 of antimicrobial gas systems 300 and sensors distributed in rooms and spaces within a floor of a building.

[0031] FIG. 6 illustrates a schematic of an example system 600 for generating and monitoring an antimicrobial gas.

[0032] FIG. 7 illustrates a schematic of an example system 700 for generating and monitoring an antimicrobial gas.

[0033] FIG. 8 illustrates a cutaway perspective view of a system 800 generating antimicrobial vapor within a sealed environment 810 for disinfecting items therein.

[0034] FIG. 9 illustrates a system 900 for generation of an antimicrobial gas and/or solution.

[0035] FIG. 10 illustrates a system 1000 for generation of an antimicrobial gas and/or solution.

[0036] FIG. 11 illustrates a system 1100 for generation of an antimicrobial gas and/or solution.

- [0037] FIG. 12 illustrates a system 1200 for generation of an antimicrobial gas and/or solution.
- [0038] FIG. 13 illustrates a system 1300 for generation of an antimicrobial gas and/or solution.
- [0039] FIG. 14 illustrates a system 1400 for generation of an antimicrobial gas and/or solution.
- [0040] FIG. 15 illustrates a system 1500 for generation of an antimicrobial gas and/or solution.
- [0041] FIG. 16 illustrates a system 1600 for generation of an antimicrobial gas and/or solution.
- [0042] FIG. 17 illustrates a system 1700 for generation of an antimicrobial gas and/or solution.
- [0043] FIG. 18A illustrates a plan view of a reactor 1800 for generating an antimicrobial gas.
- [0044] FIG. 18B illustrates a front perspective view of reactor 1800 for generating an antimicrobial gas.
- [0045] FIG. 18C illustrates a top perspective view of reactor 1800 for generating an antimicrobial gas.
- [0046] FIG. 18D illustrates a front perspective view of reactor 1800 for generating an antimicrobial gas.
- [0047] FIG. 19A illustrates a side perspective view of a reactor 1900 for generating an antimicrobial gas.
- [0048] FIG. 19B illustrates a side elevational view of reactor 1900 for generating an antimicrobial gas.
- [0049] FIG. 19C illustrates a plan view of reactor 1900 for generating an antimicrobial gas.
- [0050] FIG. 19D illustrates an exploded side perspective view of reactor 1900 for generating an antimicrobial gas.
- [0051] FIG. 19E illustrates an exploded front perspective view of reactor 1900 for generating an antimicrobial gas.
- [0052] FIG. 19F illustrates a front perspective view of reactor 1900 for generating an antimicrobial gas.
- [0053] FIG. 19G illustrates a rear perspective view of reactor 1900 for generating an antimicrobial gas.

[0054] FIG. 19H illustrates a side perspective view of reactor input mechanism 1962 in a first position.

[0055] FIG. 19I illustrates a side perspective view of reactor input mechanism 1962 in a second position.

[0056] FIG. 20A illustrates a plan view of a reactor 2000 for generating an antimicrobial gas.

[0057] FIG. 20B illustrates a front perspective view of reactor 2000 for generating an antimicrobial gas.

[0058] FIG. 20C illustrates a top perspective view of reactor 2000 for generating an antimicrobial gas.

[0059] FIG. 20D illustrates a front perspective view of reactor 2000 for generating an antimicrobial gas.

[0060] FIG. 21A illustrates a plan view of a reactor 2100 for generating an antimicrobial gas.

[0061] FIG. 21B illustrates a top perspective view of reactor 2100 for generating an antimicrobial gas.

[0062] FIG. 21C illustrates a rear perspective view of reactor 2100 for generating an antimicrobial gas.

[0063] FIG. 21D illustrates a top perspective view of reactor 2100 for generating an antimicrobial gas.

[0064] FIG. 21E illustrates a rear perspective view of reactor 2100 for generating an antimicrobial gas.

[0065] FIG. 22A illustrates a plan view of a reactor 2200 for generating an antimicrobial gas.

[0066] FIG. 22B illustrates a top perspective view of reactor 2200 for generating an antimicrobial gas.

[0067] FIG. 22C illustrates a rear perspective view of reactor 2200 for generating an antimicrobial gas.

[0068] FIG. 22D illustrates a rear perspective view of reactor 2200 for generating an antimicrobial gas.

[0069] FIG. 22E illustrates a front perspective view of reactor 2200 for generating an antimicrobial gas.

[0070] FIG. 23A illustrates a sectional view of an example antimicrobial gas generator 2300.

- [0071] FIG. 23B illustrates a partial sectional view of antimicrobial gas generator 2300.
- [0072] FIG. 23C illustrates a sectional view of antimicrobial gas generator 2300.
- [0073] FIG. 23D illustrates a partial sectional view of antimicrobial gas generator 2300.
- [0074] FIG. 23E illustrates a sectional view of antimicrobial gas generator 2300.
- [0075] FIG. 23F illustrates a partial sectional view of antimicrobial gas generator 2300.
- [0076] FIG. 23G illustrates a partial sectional view of antimicrobial gas generator 2300.
- [0077] FIG. 24 illustrates a sectional view of an example antimicrobial gas generator 2400.
- [0078] FIG. 25A illustrates an elevation view of an example antimicrobial gas generator and sensor device 2500.
- [0079] FIG. 25B illustrates a perspective view of antimicrobial gas generator and sensor device 2500.
- [0080] FIG. 25C illustrates a sectional view of antimicrobial gas generator and sensor device 2500.
- [0081] FIG. 26A illustrates a perspective view of an example antimicrobial gas generator and sensor device 2600.
- [0082] FIG. 26B illustrates a sectional view of antimicrobial gas generator and sensor device 2600.
- [0083] FIG. 27A illustrates an elevation view of an example antimicrobial gas generator and sensor device 2700.
- [0084] FIG. 27B illustrates a perspective view of antimicrobial gas generator and sensor device 2700.
- [0085] FIG. 28A illustrates an elevation view of an example portable antimicrobial gas reactor 2800.
- [0086] FIG. 28B illustrates a schematic view of portable antimicrobial gas reactor 2800.
- [0087] FIG. 29A illustrates a plan view of an example packaged antimicrobial gas generator solution and packaged activator solution.
- [0088] FIG. 29B illustrates a sectional view of packaged antimicrobial gas generator solution and packaged activator solution.
- [0089] FIG. 30A illustrates an elevation view of an example of an antimicrobial gas generator 3000 in the form of a card shape or a sheet.
- [0090] FIG. 30B illustrates a sectional view antimicrobial gas generator 3000 containing an antimicrobial generating compound.

[0091] FIG. 31 illustrates an example of an antimicrobial generator 3100 in the form of a pouch with optional addition of water internal to the pouch.

[0092] FIG. 32A illustrates an example of an antimicrobial generator 3200 in the form of a solution treated single or multi-ply porous material.

[0093] FIG. 32B illustrates an example of antimicrobial generator 3200 with liquid reagents absorbed or adsorbed on substrates and blended with a porous matrix material with optional addition of an exterior film to control release.

[0094] FIG. 32C illustrates an example of antimicrobial generator 3200 with solid reagents blended in a porous material and optional addition of an exterior film to control release.

[0095] FIG. 32D illustrates an example of antimicrobial generator 3200 in the form of a perforated pouch.

[0096] FIG. 32E illustrates an example of antimicrobial generator 3200 where reagent materials of FIGS. 32A-32C are configured side by side with optional materials to support activation and control release.

[0097] FIG. 33A illustrates a cutaway view of an aerosol container 3386 including an interrupted dip tube.

[0098] FIG. 33B illustrates a cutaway view of aerosol container 3386 including reactor engaged with dip tube.

[0099] FIG. 33C illustrates a cutaway view of aerosol container 3386 including reactor engaged with dip tube.

[0100] FIG. 33D illustrates a cutaway view of aerosol container 3386 including reactor engaged with dip tube.

[0101] FIG. 34 illustrates a cutaway view of an aerosol container 3486 including a flexible bladder connected to a dip tube.

[0102] FIG. 35A illustrates a cutaway view of an aerosol container 3586 including a plurality of flexible bladders.

[0103] FIG. 35B illustrates a cutaway view of aerosol container 3586 including a plurality of flexible bladders.

[0104] FIG. 36 illustrates a schematic diagram of an apparatus 3600 for generating antimicrobial gas or vapor external to a sealed environment for disinfecting items therein.

[0105] FIG. 37 illustrates a schematic diagram of a system 3700 generating antimicrobial gas or vapor external to a sealed environment for disinfecting items therein.

- [00106] **FIG. 38A** illustrates a schematic diagram of a system **3800** generating antimicrobial gas or vapor within a sealed environment for disinfecting items in the sealed environment.
- [00107] **FIG. 38B** illustrates a schematic diagram of apparatus **3800** generating antimicrobial gas or vapor within a sealed environment for disinfecting items in the sealed environment.
- [00108] **FIG. 39A** illustrates an apparatus **3900** generating antimicrobial vapor within a sealed environment for disinfecting items therein.
- [00109] **FIG. 39B** illustrates apparatus **3900** generating antimicrobial vapor within a sealed environment for disinfecting items therein.
- [00110] **FIG. 39C** illustrates apparatus **3900** generating antimicrobial vapor within a sealed environment for disinfecting items therein.
- [00111] **FIG. 40** illustrates methods of generating antimicrobial gas or vapor within a sealed environment or external to the sealed environment to disinfect items within the sealed environment.
- [00112] **FIG. 41A** illustrates ClO₂ efficacy test data on controlled samples.
- [00113] **FIG. 41B** illustrates ClO₂ efficacy test data on controlled samples.
- [00114] **FIG. 42** illustrates an example of an apparatus **4200** that generates antimicrobial gas or vapor for disinfecting items in three-dimensional space.
- [00115] **FIG. 43** illustrates an example of an apparatus **4300** that generates antimicrobial gas or vapor for disinfecting items in three-dimensional space.
- [00116] **FIG. 44** illustrates an example procedure **4400** for the use of apparatus **4300** in **FIG. 43** to generate antimicrobial gas.
- [00117] **FIG. 45** illustrates a table showing temperature effects to solubility of ClO₂ gas in water and in air and required amount of ClO₂ gas for a defined room size.
- [00118] **FIG. 46** illustrates a uniformity of ClO₂ gas concentration distributed within a room.
- [00119] **FIG. 47** illustrates gas concentration profiles in room setting with furniture.
- [00120] **FIG. 48** illustrates relative humidity and generated ClO₂ gas concentration from a ClO₂ solution.
- [00121] **FIG. 49** illustrates a correlation of increase in disinfection efficacy with elevated humidity.

- [00122] FIG. 50 illustrates a method for generating an antimicrobial gas and dispersing the gas via an apparatus.
- [00123] FIG. 51A illustrates the time (minutes) to equilibrium for a target concentration of 0.1 ppm of ClO₂ to air.
- [00124] FIG. 51B illustrates the concentration (ppm of ClO₂ to air) measured at five ports over time (minutes).
- [00125] FIG. 52A illustrates the time (minutes) to equilibrium for a target concentration of 350 ppm of ClO₂ to air.
- [00126] FIG. 52B illustrates the concentration (ppm of ClO₂ to air) measured at 12 ports over time (minutes).
- [00127] FIG. 53A illustrates a diagram of an example system 5300 for generating ClO₂ vapor from small volumes of high concentration liquid precursors.
- [00128] FIG. 53B illustrates a diagram of example system 5300 for generating ClO₂ vapor from small volumes of high concentration liquid precursors.
- [00129] FIG. 54A illustrates results of ClO₂ generation using system 5300 or similar systems.
- [00130] FIG. 54B illustrates results of ClO₂ generation using system 5300 or similar systems.
- [00131] FIG. 54C illustrates requirements for ClO₂ generation using system 5300 or similar systems.
- [00132] FIG. 55A illustrates the mean D-values (hours) from replicate tests per organism performed at the range of 0.11 ± 0.04 ppmv.
- [00133] FIG. 55B illustrates the mean D-values (hours) from replicate tests per organism performed at the range of 5.3 ± 2.4 ppmv.
- [00134] FIG. 56 illustrates a diagram of an example system 5600 for various operational modes.
- [00135] FIG. 57 illustrates a control sub-system 5700.
- [00136] FIG. 58 illustrates a reactor 5800 for generating an antimicrobial gas.
- [00137] FIG. 59 illustrates a graph of concentration of antimicrobial gas versus time for a simulated operation of an antimicrobial gas system and device.
- [00138] FIG. 60 illustrates a schematic of a closed-loop system 6000 to maintain target concentrations of an antimicrobial gas in the air.
- [00139] FIG. 61A illustrates a perspective view of an example antimicrobial gas generator 6100.

[00140] FIG. 61B illustrates a sectional view of an example antimicrobial gas generator 6100.

DETAILED DESCRIPTION

Closed-Loop Antimicrobial Concept

[00141] A system is provided including an interconnection of platform component elements described below. FIGS. 1A-1C illustrate a system 100 for generating and monitoring an antimicrobial gas. FIGS. 2A-2E illustrate a system 200 for generating and monitoring an antimicrobial gas. Platform component elements may be used individually or in combination to implement a system and device to create, maintain, optimize and/or document the presence of a concentration of an antimicrobial agent in a volume under treatment 124.

[00142] The system (such as systems 100, 200) is capable of maintaining an antimicrobial agent in the atmosphere of volume under treatment 124, and may include: (1) controlled release of antimicrobials to maintain a target antimicrobial concentration in volume under treatment 124; (2) at least one type of sensor 108, within volume under treatment 124, and possibly several sensors 108 or several types of sensors 108, are used to sense the concentration of the antimicrobial; (3) a computational system 106 that can compare the measured difference between the antimicrobial concentration sensing and a target antimicrobial concentration in volume under treatment 124; (4) an antimicrobial generator 110 (which may be connected to computational system 106) capable of initial establishment and maintenance of a target antimicrobial concentration in volume under treatment 124; (5) where a computed difference between a target antimicrobial concentration and a sensed antimicrobial concentration is determined, a target control may adjust antimicrobial generation to maintain the target antimicrobial concentration; (6) at least one base safety assurance implementation at the physical components of system 100, 200, electronic hardware, and firmware to software levels of the product.

[00143] System 100, 200 may be designed for modes of operation to prevent transmission or infection between humans in occupied spaces, as well as modes of operation wherein unoccupied rooms can be treated. To maintain target antimicrobial concentrations, system 100, 200 may separate the durable reusable components from disposable components to maintain refill and physical-digital control across deployed system elements.

[00144] Regarding the antimicrobials, the self-degradation kinetics and kinetics of inactivation to log-kill microbes may depend upon more than just the concentration of the antimicrobials in the volume under treatment 124. Thus, system 100, 200 may include a broad spectrum of environment sensing to enable system 100, 200 to use machine learning and artificial

intelligence, including for example, enhanced target control, automated volume estimation, humidity measurement, and programmatic antimicrobial cycles.

[00145] Antimicrobial generator **110** designs may use matter displacement (including positive displacement pumps) to activate systems, many of which may have an electronic signal that can be harvested to enable enhanced safety assurance utilizing signals collected by a microprocessor/microcontroller **104** that may be part of computational system **106**.

[00146] System **100, 200** may use external communication **102** to form a connectivity network designed to utilize distributed system data of the aforementioned variables of interest to enable the network coordination of distributed product nodes, and the correspondingly required strategy of spatial and temporal identification constants durably and/or variably assigned to system **100, 200** products.

[00147] System **100, 200** may use a combination of platform components, to create an antimicrobial dashboard system. System **100, 200** may provide real-time as well as historical data on infection control, either for safety and health in a user's own spaces, or in high requirements markets such as healthcare facilities. The antimicrobial dashboard system may be used to map a data lake of environment sensing, target antimicrobial concentrations, and use of the connectivity network to deliver distributed system data on the distributed product nodes, which may be identified by unique spatial and temporal identifications, and combine all of this data into human-meaningful information.

[00148] Distributing the intelligence (e.g., computational system **106**), sensing (e.g., sensor **108**), and generation (e.g., antimicrobial generator **110**) may enable the development of a digital twin of space for antimicrobial control. This concept may enable additional network safety assurance implementations and may contain all of the information required to develop and deploy proactive strategies in system **100, 200** products such as a predictive antimicrobial control.

[00149] System **100, 200** includes the ability to combine platform components in multiple ways to achieve product implementation options that are designed specifically for rooms in buildings and provide digital control to low-concentration of an airborne antimicrobial. This antimicrobial may be used to fight transmission and infection caused by microbe-emitting beings and microbes that are circulated through the air currents in rooms, adjacent rooms via open infiltration/exfiltration passages, and shared HVAC systems.

[00150] As illustrated in **FIGS. 1A-1C**, system **100** may include platform components including external communications **102** devices, microprocessors/microcontrollers **104**, computational system **106**, antimicrobial and/or environmental sensors **108**, and antimicrobial generator **110**. System **100** may be entirely contained inside of volume under treatment **124**.

Optionally, system 100 may be contained within volume under treatment 124 and supplemented with one or more additional sensor sub-systems 120 configured to provide additional data, including antimicrobial concentration and/or environmental data.

[00151] As illustrated in FIGS. 2A-2E, system 200 may include both a sensor sub-system 120 and a generation sub-system 122. Sensor sub-system 120 may include external communication 102 devices, a microprocessor/microcontroller 104A, computational system 106, and antimicrobial and/or environmental sensors 108. Generation sub-system 122 may include external communication 102 devices, a microprocessor/microcontroller 104B, and antimicrobial generator 110. System 200 may be entirely contained inside of volume under treatment 124.

[00152] As illustrated in FIG. 2C, system 200 may, in a first aspect, include sensor sub-system 120 within volume under treatment 124, and generation sub-system 122 outside of volume under treatment 124. In the first aspect, generation sub-system 122 generates an antimicrobial and via a fluid connection to an HVAC air supply 126, directs antimicrobial into the interior of volume under treatment 124. The concentration of antimicrobial within volume under treatment 124 is sensed by sensor sub-system 120.

[00153] As illustrated in FIG. 2C, system 200 may, in a second aspect, include generation sub-system 122 within volume under treatment 124, and sensor sub-system 120 outside of volume under treatment 124. In the second aspect, generation sub-system 122 generates an antimicrobial within volume under treatment, and via a fluid connection to an HVAC air return 128, sensor sub-system 120 senses the concentration of antimicrobial within volume under treatment 124.

[00154] As illustrated in FIG. 2D, system 200 may include a sensor sub-system 120 within volume under treatment 124, and generation sub-system 122 outside of volume under treatment 124, wherein generation sub-system 122 is in fluid communication within volume under treatment 124 to place generated antimicrobial within volume under treatment 124.

[00155] As illustrated in FIG. 2E, system 200 may include a sensor sub-system 120 outside of volume under treatment 124, and generation sub-system 122 within volume under treatment 124, wherein sensor sub-system 120 is in fluid communication within volume under treatment 124 to sense generated antimicrobial concentrations within volume under treatment 124.

[00156] Volume under treatment 124 is conceptually a volume in which a user seeks to distribute an antimicrobial. The volume may be sealed permanently or temporarily to isolate the volume for a period of time. The volume may have openings through which atmosphere can be allowed to infiltrate and/or exfiltrate before, during, or after distributing an antimicrobial. The infiltration/exfiltration can be a characteristic of the volume that is either an uncontrolled variable

due to consequence of the volume configuration, or active control strategies of infiltration/exfiltration of atmosphere.

[00157] The target volumes may be the living spaces where human beings gather for work, activities, entertainment, and/or their domiciles. Therefore, product targets may be volumes that can be termed rooms, with groups of rooms forming floorplans, collections of floorplans that form a building, and collections of buildings that comprise a facility.

[00158] Modular platform components may be extended into other volumes under treatment **124**, including for example: (1) mobile vehicles such as the interiors of cars, trains, subways, airplanes, recreational vehicles, ride share vehicles, autonomous vehicles, cabins in ships, and the like; (2) leisure spaces such as restaurants, nightclubs, bars, churches, community centers, libraries, and the like; (3) hospital spaces such as hospital rooms, operating rooms, procedure rooms, patient examination rooms, vivariums, morgues, and the like; and (4) business spaces such as offices, conference rooms, hallways, cafeterias, coffee and lounge areas, and the like.

[00159] Target antimicrobial concentrations may be a setpoint desired for antimicrobial release into a volume under treatment **124**. The concentration of an antimicrobial in the air can be expressed in relative ratios such as percentages, parts-per-million (“ppm”), or parts-per-billion (“ppb”), and similar terms. As the term is used herein, ppm and ppb are based upon volume.

[00160] International standard terms are often used to describe antimicrobial concentrations similar to how industrial chemicals are regulated. Important to system **100**, **200** product designs is to treat the air in rooms where people live, work, and play. Regulatory terminology for antimicrobial concentrations in the air in volume under treatment **124** include: (1) recommended/permitted exposure limit, abbreviated “REL/PEL,” are concentration and time exposure limits safe for human occupation based upon historical studies and evidence; (2) immediately dangerous to life or health, abbreviated “IDLH,” is a concentration at which human exposure can begin to quickly cause an adverse reaction; (3) lethal concentration with 50% mortality, abbreviated “LC-50,” is a concentration at which a time-based exposure to an airborne concentration shown to have a mortality rate of 50% in animals exposed in a trial of time at concentration; and (4) lethal dose with 50% mortality, abbreviated “LD-50,” is an immediate dose extrapolated from animal trials where a mortality rate of 50% is observed from a single large dose, including air measured as near-immediate mortality at an airborne concentration.

[00161] The first target antimicrobial concentrations include:

[00162] (1) prevention mode in occupied volumes: simple target number typically predicated upon, but not necessarily constrained to, known and published REL/PEL from

regulatory bodies. The objective of the prevention mode is to maintain a known-safe concentration of an antimicrobial in the air in which humans can occupy for a meaningful length of time, typically defined by safety regulators in the context of a “work shift” between 8 to 10 hours. The objective of the concentration is to limit and/or eliminate the transmission potential and/or infection potential of microbes that are already present in a room, or are being emitted into the room by other living beings or room systems like HVAC;

[00163] (2) decontamination mode in unoccupied volumes: simple target number typically predicated on, but not necessarily constrained to, known and published IDLH from regulatory bodies. One objective of decontamination mode is to enable the use of higher concentration levels of an airborne antimicrobial that can shorten the time required to inactivate/kill microbes that need elimination faster, are more difficult to kill organisms (such as spores) or are typically easier to kill but that are partially protected in nutrient rich soils, fluids in obvious to hidden locations, and are suspected or confirmed in a specific volume under treatment **124**. Targeting the range near to or below the IDLH includes a likelihood that a person who accidentally or purposefully walks into volume under treatment **124** will notice effects associated with the IDLH such as watery eyes, nasal irritation, and other immediately dangerous but not lethal concentrations;

[00164] (3) emergency decontamination volumes: target number potentially selected where a highly dangerous concentration of and/or highly resistant species of microbe require an emergency decontamination of volume under treatment **124**. Once volume under treatment **124** is isolated and evacuated, system **100, 200** products could be set by authorized users to perform higher concentration “civil defense mode” concentrations that are at or exceed the LC-50 and LD-50, therefore requiring a degree of user interaction and implementing physical safety safeguards that such a mode will not be an automated mode.

[00165] Sensors **108** and sensor sub-system **120** can include a broad range of sensing technologies to determine the concentration of the antimicrobial in volume under treatment **124**.

[00166] Any one or a combination of these sensing technologies may be utilized for many different species of antimicrobials, including for example ClO_2 , which is part of the class of oxidizing antimicrobials, which may additionally include: hydrogen peroxide, dry hydrogen peroxide, ozone, nitric oxide.

[00167] System **100, 200** may incorporate any combination of the following sensors **108** to achieve digital control: (1) electrochemical sensors that utilize a depletable chemical which reacts with the antimicrobial, and an electrical circuit that measures the effect of this chemical reaction using measures of charge, voltage, current, conductivity, resistivity, and the like to provide a signal that is in proportion to the known capable range of the sensors. An example of

electrochemical sensors for ClO_2 include sensors from Analytical Technologies, Inc.; (2) MOx sensors (metal oxide semiconductor sensors) are widely used in air quality measurement, typically for airborne pollutants such as H_2S , volatile organic compounds, and are known to work to sense gaseous oxidizing species. Two examples of these MOx sensors include the Sensirion SGP40 and the Renesas ZMOD4410 family of sensors.

[00168] Advantages of MOx sensors over electrochemical sensors may include: (a) 10-year lifetimes with no chemicals to deplete; (b) calibration and training values last the lifetime of the sensor; (c) sensors can be “trained” to gas species of interest. The number of gases the sensor can be trained to is not limited by choices of chemical species in the sensor, therefore, as opposed to electrochemical sensors, one MOx sensor can be used to sense multiple antimicrobial species of interest, as well and complementary and potentially interfering gases, without requiring use of different chemicals, membranes, or other interaction/barrier methods to provide species specificity.

[00169] Alternative sensing solutions may be able to sense an antimicrobial species to the parts-per-billion to parts-per-trillion levels of concentration expected in the prevention mode in occupied volumes. These alternatives may include: (1) Colorimetry: using a chemical “dye” that interacts with the antimicrobial species of interest and causes a reaction that can be observed by electronic color sensors. The “color” can be in the spectrum of visible, infrared, UV, and other wavelengths of light. The fundamental output of such a system would be an electronic signal that is proportional to the “color change” expected for known chemical interactions that underpin such sensing technologies; (2) Fluorescence: if the antimicrobial species fluoresces, or can be bound to a chemical species that is selective and can be sensed via fluorescence, the magnitude of the fluorescence can be sensed and calibrated to known sources to translate fluorescence levels sensed into an electronic signal that is proportional to said fluorescence.

[00170] Electronic and/or computational controls (computational system **106**) act as the “heart” and “brains” of a system **100, 200** product. While there are electronic analog, field-programmable gate array (“FPGA”), and discrete circuitry methods that may work for control, the digital solutions designed for low power battery-powered connected products are particularly beneficial for wireless system **100, 200** products.

[00171] Microprocessors or microcontrollers **104** may form the control intelligence backbone of system **100, 200** products. Microprocessors may be used as these may be required for the embodiments of certain simple safety assurance systems.

[00172] Microprocessor unit **104** may be the central processing core electrically connected to all of the elements of the system **100, 200** platform components.

[00173] Antimicrobial generator **110** is any of a variety of subcomponents responsible for the generation and/or dispersion of an antimicrobial into volume under treatment **124**. A large variety of antimicrobial generators **110** is discussed herein, including:

[00174] (1) compressed matter release: an antimicrobial stored in a compressed state is released by a pressure reducing regulator. For example, a canister of antimicrobial gas connected to a pressure reducing regulator, which when opened, allows compressed antimicrobial gas to flow out of the canister to an uncompressed state. A mass flow controller in the path of the matter being transformed from a compressed to an uncompressed state can provide quantitative measurement of the quantity of antimicrobial released;

[00175] (2) two or more chemical activation: two or more precursors are combined to cause a chemical reaction that generates the desired antimicrobial. The two or more precursors can be mixed in passive or active structures, including microfluidic structures to accelerate reaction kinetics. Examples of systems contained herein utilizing this concept include, without limitation: reactors **1800**, **1900**, **2000**, **2100**, and **2200**; gas generators **2300**, **2400**, and **3000**; gas reactor **2800**; antimicrobial generators **3100** and **3200**; and aerosol containers **3486** and **3586**;

[00176] (3) electrochemical activation: voltage potential and/or current can be varied to control species release and kinetics of antimicrobial generation. In one aspect, termed a flow-through electrochemical cell, NaClO_2 can be flowed over electrodes and recycled until depleted by the electrochemical cleaving of Na from NaClO_2 . In another aspect, the precursor material can be contained in a static volume into which electrodes are co-located to generate the electrochemical cleaving of Na from NaClO_2 until the bulk fluid is depleted. In another aspect, ClO_2 is electrochemically generated from a solution of NaClO_2 as the anolyte that is separated from a catholyte by a membrane. Each anolyte and catholyte is in communication with at least one electrode, and a membrane plays an active role in increasing the yield or desired species of antimicrobial (e.g., ClO_2) while sequestering undesired species in the catholyte like Na (in this example for ClO_2). In another aspect, a thin layer of sodium chlorite is flowed in a closed, open, or one-sided membrane channel where material could be introduced to an electrochemical cell designed to generate ClO_2 only from the small quantity of NaClO_2 , after which the depleted precursor is transferred to a waste container and the process is repeated.

[00177] Systems **100**, **200** may be a platform that includes durable reusable components and disposable components. The disposable components may include refill cartridges. The refill cartridges may include precursors or direct antimicrobial in a concentrated form. Refill cartridges may include a reservoir. Refill cartridges may include platform components that are prone to failure from wear, including for example, pumps, sensors, and the like.

[00178] Systems **100, 200** may include digital and physical signals to achieve the changing of modes as described above. System **100, 200** may be used either in occupied or unoccupied volumes under treatment **124**.

[00179] As such, one class of refill cartridges can incorporate a mechanism (physical, electrical/digital, or both) to limit the base unit into which it is installed to operate in an occupied volume under treatment **124** mode (e.g., prevention mode in occupied volumes) and REL/PEL concentration levels.

[00180] Another class of refill cartridges can incorporate a mechanism (physical, electrical/digital, or both) to allow the base unit into which it is installed to operate in a decontamination mode (e.g., decontamination mode in unoccupied volumes). Additional features may include a mechanism limiting installation to a subset of users who are authorized to install the decontamination mode cartridge. These features may include a requirement to enter an appropriate electronic or digital authorization (e.g., a code, swipe a keycard, enter a biometric pass, or the like) to unlock a decontamination mode that would be inappropriate for occupied spaces. Such a decontamination mode may utilize IDLH or higher concentration levels and may be suitable for regular or exceptional “deep-clean” scenarios.

[00181] System **100, 200** may use a combination of platform components, to create an antimicrobial dashboard system. The dashboard system may combine distributed intelligence, distributed data across the system, and other platform components to enable beneficial system features, including for example: (1) a room, floor, building control dashboard for antimicrobial treatment; (2) provide notifications to phones that are nearby a base unit; (3) system **100, 200** coordination in physically adjacent volumes under treatment **124**; (4) antimicrobial output coordination of multiple units in a single contiguous volume (e.g., a large open space such as a concert hall); (5) data portability for integration into building management systems, such as hospital command centers; and (6) civil defense alert network for biological threats or attacks.

[00182] Each system **100, 200** unit may securely connect (IoT connections), for purposes of data collection and storage, software and firmware updates, and/or user interactions, to assign: (1) unique identifiers for each hardware unit; (2) unique identifiers for each refill unit; (3) and/or two different types of refill units (one for when in low-concentration occupied mode, and another for authorized user to change to unoccupied decontamination mode).

[00183] Additionally, each system **100, 200** unit may securely connect to each other (via external communication **102**) and may pass identification validation data as well as recorded operational performance data along to a data gathering point. Each unit may record its own data, and if necessary for redundancy and safety, neighboring unit data. In one aspect, each unit may

connect to a WiFi hub to achieve interconnectivity. In another aspect, all units may be required to connect to a central identification validation and data gathering point.

[00184] Computational system **106** may include local storage mediums for each system **100, 200** unit. Alternatively, one unit can have storage capability and may act as an accumulator for multiple units in a logical grouping. All units or all accumulators may be required to report up into a central data gathering point, which may also be a point of connection into cloud data.

[00185] In one aspect, system **100, 200** units may have safety features including: (1) input received from each unit, including location, environmental sensor suite, antimicrobial sensor data, quantity of antimicrobial generated, and/or corresponding time stamps; (2) output to user and/or system controls including possible safety signal generation based upon: (i) operational parameters that do not make sense and thus that particular unit may be malfunctioning, (ii) recognition that a neighboring unit has experienced an error can initiate “alert status” among a local group of units, and a group or region of units could be powered off if airflow-dictated interactions between two local units cause interference, (iii) client and/or host operations control: the control system will watch for signals of parameters that do not make sense, across the entire installation of units.

[00186] System **100, 200** may include machine learning algorithms. For example, machine learning algorithms may use a multi-sensor suite to both measure and classify at least two fundamental characteristics of airborne microbial concentration in volume under treatment **124**.

[00187] System **100, 200** may include the capability to automatically measure the volume of any given volume under treatment **124**. Sensor array **108** may be utilized to automatically measure room volume so that generator **110** closed-loop performance can be translated from a concentration in the air to a value of required make up antimicrobial that will move the concentration from a measured value to the target concentration within volume under treatment **124**. System **100, 200** units may generate and emit a known test quantity of the antimicrobial upon initialization. The unit may initiate continuous antimicrobial sensor **108** readings while generator **110** is kept idle for a period of time between 1 min to 4 hours. On-unit computation capability measures peak concentration and uses machine learning aspect 1 (“ML1”) to measure room kinetics. Understanding that concentration = mass (derived from sensed dispensed antimicrobial volume, directly or indirectly sensed precursor utilization, mass flow measurement of antimicrobial gas, or any other value that can be traced back to quantity) of antimicrobial divided by volume of volume under treatment **124**. The volume of volume under treatment **124** is determined by using the measured quantity of antimicrobial generated and antimicrobial concentration reading at a time appropriate to the room kinetics measured with ML1. System **100, 200** may iterate with each antimicrobial gas emission to update ML1 room kinetics estimates,

while cataloging changes by time stamp. As machine learning aspect 2 (“ML2”) “learns” from the data lake or direct verification experiments, future algorithms may be designed to provide input data to the generator to predict the specific quantity of antimicrobial needed to achieve the desired concentration based upon environment conditions within volume under treatment **124**. Alternatively, or as a backup method, system **100, 200** may use a three-dimensional laser measuring system, or a tone emitter and microphone on units to ping the volume of volume under treatment **124** with a CHIRP acoustic signal. Measuring time of flight and collision of sound waves, system **100, 200** may build a characteristic volume estimate of volume under treatment **124**.

[00188] **FIGS. 3 and 4** illustrate schematics of example systems **300** and **400** for generating and monitoring an antimicrobial gas (including a disinfection gas and/or decontamination gas). The antimicrobial gas may be a ClO₂ gas. Systems **300** and **400** may include a microfluidic liquid dispensing and metering system. Systems **300** and **400** may be used to both generate antimicrobial gas (e.g., ClO₂ gas) and dispense the antimicrobial gas (e.g., ClO₂ gas) to the ambient environment, and to sample the ambient air to identify antimicrobial gas concentration therein and generate more or less antimicrobial gas as necessary to maintain a desired antimicrobial gas concentration. Systems **300** and **400** may be used to test air in a particular environment (e.g., a three-dimensional enclosed space) to determine the concentration of antimicrobial gas (e.g., ClO₂ gas) in parts per billion (“ppb”) of air. Systems **300** and **400** may be used to maintain a desired antimicrobial gas concentration in ambient air surrounding devices housing systems **300** and **400** by regularly sampling the ambient air, determining the concentration of antimicrobial gas in the ambient air, and via closed-loop control of the device, generating more or less antimicrobial gas to maintain the desired antimicrobial gas concentration in the ambient air.

[00189] Systems **300** and **400** may include wired connections to a computer network, cloud storage, or the like. Systems **300** and **400** may include wireless connections to a computer network, cloud storage, or the like. Systems **300** and **400** may document time-based tracking of system use, product maintenance, target concentration performance, and environmental parameters of interest. This documentation may be in the form of files, logs, or other records stored locally within a device housing system **300** and/or **400** or transmitted via wired connection or wirelessly to a computer network, cloud storage, or the like. Systems **300** and **400** may have cloud and/or IoT connectivity to enable user personas to effectively set up, train, manage, and maintain devices housing systems **300** and/or **400** in the three-dimensional enclosed spaces under treatment, view real-time and stored performance and environment data, and/or export data to compare validation tests such as animal and human exposure trials.

[00190] Systems **300** and **400** may be used to decontaminate (that is, to inactivate or destroy pathogens) a three-dimensional enclosed space (e.g., a hospital room) through high concentrations of antimicrobial gas (e.g., ClO₂ gas) (when unoccupied by humans), or through low concentrations of antimicrobial gas (e.g., ClO₂ gas) (when occupied by humans). In one aspect, systems **300** and **400** generate antimicrobial gas in a concentration of 1,000 ppb to 5,000 ppb or 50,000 to 300,000 ppb to decontaminate an unoccupied three-dimensional enclosed space. Systems **300** and **400** may destroy the COVID-19 within a three-dimensional enclosed space.

[00191] Systems **300** and **400** may be used to prevent the spread and/or survival of a virus in a three-dimensional enclosed space (e.g., a hospital room) through low concentrations of antimicrobial gas (e.g., ClO₂ gas) (whether occupied by humans or not). In one aspect, systems **300** and **400** generate antimicrobial gas in a concentration of less than 100ppb, for example 50 ppb, to prevent the spread and/or survival of a virus in an occupied three-dimensional enclosed space. Systems **300** and **400** may reduce aerosolized virus transmission and infection of viruses including COVID-19. Systems **300** and **400** may inactivate and/or kill airborne pathogens, and even protect against airborne contagions.

[00192] System **300** and/or **400** may be contained within a device housing **304**. Ambient air **302** may enter one or more inlet in device housing **304**. Ambient air **302** may pass through a particulate filter within device housing **304**. The particulate filter may not exclude any atmospheric molecules.

[00193] Ambient air **302** passes from device housing **304** into one or all of air pumps **308A**, **308B**, and **308C** via one or more air ducts. System **300** includes air pumps **308A**, **308B**, and **308C**, while system **400** only includes air pumps **308A** and **308C**, as will be further explained below.

[00194] A microcontroller **306** may control all on-board functions of system **300** and **400**. Microcontroller **306** includes software that can be written to change system **300** and **400**'s functions where necessary. Microcontroller **306** is operatively connected to various elements (described further below) of systems **300** and **400** via wired or wireless connection.

[00195] Microcontroller **306** is connected to air pumps **308A**, **308B**, and **308C** as illustrated, and controls the function of **308A**, **308B**, and **308C**, including one or more of start, stop, velocity, flow rate, pressure, and the like. Air pumps **308A**, **308B**, and **308C** may be disc pumps. In one aspect, air pumps **308A**, **308B**, and **308C** may be capable of producing pressure in excess of 270 mbar, flow rates in excess of 0.55 L/min, and vacuum in excess of 220 mbar. Air pumps **308A**, **308B**, and **308C** may include separate motor control units. Air pumps **308A**, **308B**,

and **308C** may include integrated motor control units. It is understood that system **400** does not include air pump **308B**.

[00196] Air pumps **308A** and **308B** in system **300** are connected to pressure relief valves **310A** and **310B**, such that excess or unnecessary pressure produced by air pumps **308A** and **308B** may be routed out of system **300**. System **400** likewise includes a pressure relief valve **310A** having the same function but does not include a pressure relief valve **310B**. Alternatively, as illustrated in **FIGS. 6** and **7**, systems **600** and **700** eliminate at least air pumps **308A** and **308B** as reagent containers **312A** and **312B** may be pressurized prior to assembly of systems **600** and **700**, and thus air pumps **308A** and **308B** are unnecessary.

[00197] System **300** includes reagent containers **312A** and **312B**, each containing a different liquid reagent **314A** and **314B**. Reagents **314A** and **314B** may be combined within a microfluidic mixer **320** to generate ClO_2 gas. One of reagents **314A** and **314B** may be a liquid precursor such as NaClO_2 (sodium chlorite). The other of reagents **314A** and **314B** may be a liquid activator such as an acid/ H^+ activator.

[00198] With respect to system **300**, air pump **308A** pressurizes reagent container **312A**, thus causing reagent **314A** to travel from reagent container **312A**, through a passage into an electronically operated normally closed valve **316A** (which is connected to and controlled by microcontroller **306**). From valve **316A** reagent **314A** travels through a microfluidic flow sensor **318A** (which is used for closed-loop control signals and is connected to and provides data to microcontroller **306**), and into microfluidic mixer **320**. It is contemplated that any pressure generator may be used in lieu of air pump **308A** to pressurize reagent container **312A**. In one aspect, reagent container **312A** may be pressurized by an external source during assembly of system **300**, and a valve connected to reagent container **312A** (e.g., valve **316A**) may open to permit the passage of a quantity of pressurized reagent to exit reagent container **312A** and proceed into microfluidic mixer **320** as described above. Such a system is illustrated in **FIG. 6**.

[00199] With respect to system **300**, air pump **308B** pressurizes reagent container **312B**, thus causing reagent **314B** to travel from reagent container **312B**, through a passage into an electronically operated normally closed valve **316B** (which is connected to and controlled by microcontroller **306**). From valve **316B** reagent **314B** travels through a microfluidic flow sensor **318B** (which is used for closed-loop control signals and is connected to and provides data to microcontroller **306**), and into microfluidic mixer **320**. It is contemplated that any pressure generator may be used in lieu of air pump **308B** to pressurize reagent container **312B**. In one aspect, reagent container **312B** may be pressurized by an external source during assembly of system **300**, and a valve connected to reagent container **312B** (e.g., valve **316B**) may open to

permit the passage of a quantity of pressurized reagent to exist reagent container **312B** and proceed into microfluidic mixer **320** as described above. Such a system is illustrated in **FIG. 6**.

[00200] Microfluidic mixer **320** may be a planar shape designed for low dead space volume and effective mixing to increase reaction kinetics of precursors.

[00201] The mixture of reagents **314A** and **314B** in microfluidic mixer **320** creates an antimicrobial gas, including for example, ClO_2 gas. Antimicrobial gas may pass via a passage into an off-gas and waste chamber **322**. Chamber **322** may include an absorber material, an evaporator, or the like. Within chamber **322**, any waste from the creation of antimicrobial gas may be absorbed in an absorber material. Chamber **322** may include a membrane. Antimicrobial gas may exit chamber **322** into the ambient atmosphere. In one aspect, antimicrobial gas exits chamber **322** through the membrane. System **300** and **400** may include a device for separation of antimicrobial gas (e.g., ClO_2 gas) and post-generator waste in communication with one or more air pumps and air ducts to one or more outlets, and on-device or in-device waste storage prior to disposal. Chamber **322** may act as the device for separation of antimicrobial gas and post-generator waste. Chamber **322** may act as the device for on-device or in-device waste storage prior to disposal. Chamber **322** may act as both the device for separation of antimicrobial gas and post-generator waste and the device for on-device or in-device waste storage prior to disposal.

[00202] With respect to system **400**, system **400** does not include an air pump **308B**, pressure relief valve **310B**, reagent container **312B**, reagent **314B**, valve **316B**, or a microfluidic flow sensor **318B**. Further, system **400** substitutes microfluidic mixer **320** with a microfluidic electrochemical generator **434**. In system **400**, air pump **308A** pressurizes reagent container **312A**, thus causing reagent **314A** to travel from reagent container **312A**, through a passage into an electronically operated normally closed valve **316A** (which is connected to and controlled by microcontroller **306**). From valve **316A** reagent **314A** travels through a microfluidic flow sensor **318A** (which is used for closed-loop control signals and is connected to and provides data to microcontroller **306**), and into microfluidic electrochemical generator **434**. An electrical current, provided by and controlled by microcontroller **306** within microfluidic electrochemical generator **434** causes a reaction with reagent **314A** within microfluidic electrochemical generator **434** that produces an antimicrobial gas, such as ClO_2 gas. Antimicrobial gas passes from microfluidic electrochemical generator **434** into chamber **322** and ultimately into the ambient environment as described with respect to system **300**.

[00203] It is contemplated that any pressure generator may be used in lieu of air pump **308A** to pressurize reagent container **312A**. In one aspect, reagent container **312A** may be pressurized by an external source during assembly of system **300**, and a valve connected to reagent container

312A (e.g., valve **316A**) may open to permit the passage of a quantity of pressurized reagent to exist reagent container **312A** and proceed into microfluidic mixer **320** as described above. Such a system is illustrated in **FIG. 7**.

[00204] Electronically operated normally closed valve **316A**, **316B** may be controlled by microcontroller **306**, and may be oriented such that when no power is provided, valve **316A**, **316B** is closed. Likewise, when power is provided, valve **316A**, **316B** is open.

[00205] Microfluidic flow sensor **318A**, **318B** may sense the flow of reagent **314A**, **314B**, respectively, and may provide data regarding that flow to microcontroller **306**. Such data may include flow rate, flow volume, flow time, mass, and the like.

[00206] Systems **300** and **400** may include a barometric sensor **328**. Barometric sensor **328** may sense the pressure within the three-dimensional enclosed space that systems **300** and **400** operate. Upon sensing a negative pressure (indicating that a HVAC return system is pulling air out of the room, a door or window is open, or the like), barometric sensor **328** may communicate the negative pressure via its connection with microcontroller **306**, upon which microcontroller **306** may pause antimicrobial gas (e.g., ClO₂ gas) generation until a neutral and/or positive pressure is sensed by barometric sensor **328**. Upon sensing a neutral or positive pressure, barometric sensor **328** may communicate the neutral or positive pressure to microcontroller **306**, at which point microcontroller **306** may once again initiate gas generation (e.g., ClO₂ gas).

[00207] Systems **300** and **400** may include an air quality sensor **330**. Air quality sensor **330** may sense any of a variety of ambient air **302**'s characteristics, including for example, humidity, temperature, and the like. Data regarding air quality may be recorded for evaluating the effectiveness of systems **300** and **400**. Alternatively, as antimicrobial gas (e.g., ClO₂ gas) may be more effective at destroying pathogens in more humid environments, humidity data, for example, may be communicated via air quality sensor **330**'s connection with microcontroller **306**, upon which microcontroller **306** may adjust the target concentration of antimicrobial gas in ambient air **302** based upon humidity readings.

[00208] The above-described aspects, methods, and processes of systems **300** and **400** demonstrate the generation of antimicrobial gas by each of systems **300** and **400**. Below is described the aspects of systems **300** and **400** that sample ambient air **302** to determine the concentration of antimicrobial gas (e.g., ClO₂ gas) within ambient air **302**.

[00209] In both systems **300** and **400**, ambient air **302** may be ducted to air pump **308C**, which causes a sample of ambient air **302** to enter a concentrator **324**. Concentrator **324** may separate antimicrobial gas (e.g., ClO₂ gas) from the mostly diamagnetic other components of ambient air **302**. One aspect of a concentrator is illustrated in **FIGS. 8A** and **8B**. Concentrator

324 may separate and concentrate a very low concentration of antimicrobial gas (e.g., ClO₂ gas) so that a more accurate measurement of its concentration may be obtained. Concentrator **324** may utilize magnets to separate diamagnetic gases from antimicrobial gas, thus permitting the testing of a concentrated and amplified level of antimicrobial gas. Diamagnetic gases may be passed back into the ambient environment after separation. In one aspect, antimicrobial gas may be amplified at least 100 times prior to further concentration testing.

[00210] Systems **300** and **400** may include a sensing system **326**. Sensing system **326** may sense the concentration of antimicrobial gas (e.g., ClO₂ gas) (which may be amplified 100 times or more following processing in concentrator **324**). Sensing system **326** may measure a time weighted average of the concentration of antimicrobial gas (e.g., ClO₂) in ambient air **302**. Data regarding the concentration is passed to microcontroller **306**, and if necessary, microcontroller **306** causes system **300** or **400** to generate more or less antimicrobial gas based upon the concentration measured in sensing system **326**.

[00211] After sensing in sensing system **326**, the sampled gas passes via a passage to off-gas and waste chamber **322** and is ultimately passed into the ambient atmosphere with the generated antimicrobial gas.

[00212] Thus, systems **300** and **400** may measure the concentration of antimicrobial gas (e.g., ClO₂ gas) in ambient air **302**, and if the concentration is below the target concentration, microcontroller **306** can cause system **300** or **400** to generate more antimicrobial gas to raise the concentration of antimicrobial gas (e.g., ClO₂ gas) in ambient air **302** until the sampled ambient air **302** meets the target concentration threshold.

[00213] All microcontrollers referenced herein (including microcontroller **306**), may have the computational ability and local data storage ability to enable closed-loop control of the antimicrobial gas generation system (including systems **300**, **400**, **600**, and **700**), including but not limited to: (1) local storage and microcontroller operations on data from sensor systems for antimicrobial gas (e.g., ClO₂) levels to the space environment variables such as barometric pressure, humidity, temperature, occupancy, or sounds that may be used to alter generation system (including systems **300**, **400**, **600**, and **700**) performance automatically or via user intervention; (2) measurement, local storage, and microcontroller operations on data from microfluidic sub-systems such as mass/volume sensors of reagents, pressure generator performance, microfluidic chip-borne sensors, valve status and/or any other electronic sub-system to provide control as well as storage of system performance data for maintenance, alert, troubleshooting, inactive modes of operation, active modes of operation, and local setup.

[00214] In another aspect, the system (including systems **300**, **400**, **600**, and **700**) has a communication device connected to the microcontroller and/or electronic components such that data from any electronic component within, on, or connected to the systems (including systems **300**, **400**, **600**, and **700**) or housing **304** can be gathered, locally stored, operated on by the microcontroller, and transmitted to external data gathering systems on mobile and/or fixed devices.

[00215] In another aspect, machine learning and/or artificial intelligence algorithms can be incorporated into the system (including systems **300**, **400**, **600**, and **700**) microcontroller (including microcontroller **306**) to alter system performance automatically or by user interactions. An example of local control includes alteration of system performance for detection of a virus or bacteria in the ambient air, altitude, temperature, air changes in the local space measured by changes in antimicrobial gas (e.g., ClO_2) concentration in the air of spaces containing antimicrobial gas (e.g., ClO_2), changes in occupancy by living beings, alterations for user preference, prediction of cycles of occupancy/vacancy, alerts as to normal or abnormal performance of the system, and the like. In one aspect, microcontroller **306** is controlled by machine learning algorithms to alter system performance. In another aspect, microcontroller **306** is controlled by artificial intelligence algorithms to alter system performance. Microcontroller **306** may alter system performance automatically. Microcontroller **306** may alter system performance by control by a user. Microcontroller **306** may alter the system performance based upon at least one of: a detection of a virus or bacteria in the ambient air; an altitude of the system; a temperature of the system; changes in the ambient air measured by changes in a concentration of antimicrobial gas (e.g., ClO_2) in ambient air; changes in occupancy by living beings of an area containing the system; alterations for a user's preferences; prediction of cycles of occupancy and vacancy by living beings of the area containing the system; and a diagnosis of normal or abnormal performance of the system.

[00216] In another aspect, the system (including systems **300**, **400**, **600**, and **700**) for distribution and monitoring of antimicrobial gas (e.g., ClO_2 gas) in a three-dimensional space will be designed for a plurality of operating modes. A first operating mode may be designed for occupied spaces, while a second operating mode may be designed for un-occupied spaces. Future user or engineered operating modes may be added. These operating modes may be changed by authorized users on the system (including systems **300**, **400**, **600**, and **700**) network (e.g., network **300**) connected to a plurality of system (including systems **300**, **400**, **600**, and **700**).

[00217] **FIG. 5** illustrates an example blueprint of a network **500** of disinfecting gas (e.g., ClO_2 gas) generator systems **300** and sensors **536** distributed in rooms and spaces in a floor of a

building. Network **500** illustrates a floor of a building bounded by exterior walls **538** and divided by interior walls **540**. Gas generator systems **300** may operate with the configuration and method of systems **300** or **400** described above, or **600** or **700** described below, and thus may include disinfecting gas (e.g., ClO₂ gas) concentration sensors. As illustrated, gas generator systems **300** may be oriented in each individual room of the floor, as well as in open spaces between the individual rooms. Standalone sensors **536** (configured simply to sense the concentration of disinfecting gas, such as ClO₂ gas, in the ambient air) supplement network **500** to ensure that the target concentration is achieved throughout network **500**.

[00218] The various gas generator systems **300** may operate to generate disinfecting gas (e.g., ClO₂ gas) independent of one another, and at different concentration target values depending upon the desired function of a particular gas generator systems **300**.

[00219] For example, where a room is occupied by a patient (e.g., in a hospital or nursing facility), employee (e.g., in an office), a guest (e.g., in a hotel), or the like, the gas generator system **300** in that particular room may have a target disinfecting gas (e.g., ClO₂ gas) concentration of about 50 ppb. After the room is no longer occupied (e.g., patient is moved from the room for a set period of time, employee is gone for the night, guest checks out, etc.), the gas generator system **300** in that room may increase its target disinfecting gas (e.g., ClO₂ gas) concentration to about 1,000 ppb to about 5,000 ppb for a set period of time. In this manner, the room can be decontaminated (1,000 ppb to 5,000 ppb concentration level, or 50,000 ppb to 300,000 ppb concentration level for extreme pathogens) between its use by particular individuals, or on a regular time schedule, and maintain a lower safe (to humans) concentration of 50 ppb for prevention or mitigation of virus spreading while occupied.

[00220] In another aspect, a plurality of systems **300** within a plurality of spaces which are arranged into network **500** can be connected via communication devices (as described above) to each other for distributed control via coordination of each system's microcontroller (e.g., microcontroller **306**), centralized unit control, and/or a combination of both local and distributed control.

[00221] In another aspect, machine learning and/or artificial intelligence algorithms can be incorporated into the distributed network **500** of systems **300** by the aspects described above. Examples of distributed control include adjusting individual systems **300** to achieve uniform and/or deliberately non-uniform distribution of disinfecting gas (e.g., ClO₂) in each individual generator system **300**'s location across an entire building floor to the entire building due to changes in disinfecting gas (e.g., ClO₂) concentration from HVAC, consumption or self-dissipation of disinfecting gas, control of day/night generation cycles, sensing patterns across

time, three-dimensional volumes, seasonal variations, and/or previously unknown factors that can be sensed either directly by the sensor systems **300** in/on the network **500**, inferred or traced to the signal measured, or directly traceable to the variations observed in disinfecting gas (e.g., ClO₂) concentrations across a collection of systems **300** installed across distinctly separate and/or varying interconnection of real world spaces in which control of infectious species is desired.

[00222] FIGS. **6** and **7** illustrate schematics of example systems **600** and **700** for generating and monitoring antimicrobial gas (e.g., ClO₂ gas). Systems **600** and **700** are substantially similar to systems **300** and **400**, respectively, except that air pumps **308A** and **308B** and pressure relief valves **310A** and **310B** are replaced with check valves **609A** and **609B**. These check valves are one-way, directional flow valves that permit the passage of fluid through check valves **609A**, **609B** toward reagent containers **312A**, **312B**, but prevent the passage of fluid away from reagent containers **312A**, **312B** through check valves **609A**, **609B**.

[00223] Such an arrangement may be used where reagent containers **312A**, **312B** are pressurized by an external source before or during assembly of systems **600**, **700**. Thus, reagent containers **312A**, **312B** may be pressurized containers housing reagents **314A**, **314B**, and as such do not need air pumps **308A**, **308B** to cause reagent **314A**, **314B** to flow to microfluidic mixer **320**. The flow of pressurized reagent **314A**, **314B** may be controlled by a valve, such as valves **316A**, **316B**. When valves **316A**, **316B** are opened, pressurized reagent **314A**, **314B** may flow from pressurized reagent containers **312A**, **312B**, through microfluidic flow sensors **318A**, **318B**, and into microfluid mixer **320**.

[00224] In one aspect, a closed-loop system to maintain target concentrations of an antimicrobial gas in the air, between lower bounds and upper bounds. The system may include an automated estimation of room volume (or a related characteristic) based on calculated concentration decay of a precise dosage of a gas. The system may be oriented within spaces where there is a desired and/or target gas concentration in a volume. The system includes one or more of: (a) the capability to generate and release an antimicrobial gas, (b) the capability to measure the concentration of the gas, (c) the capability to control the generation and release of the gas according to control parameters either programmed in software or controlled by digital or analog means, and/or (d) the capability to adapt to changing conditions and still maintain the target concentration.

[00225] The system may include capabilities for use in any application where a volume is unknown, where the user desires to apply, create, and/or generate a gas (or similar) in that volume, and where the gas (or similar) has a known decay characteristic such as percent decay per minute.

[00226] The system provides an advantage in that the physical volume (e.g., cubic feet or cubic meters) of the volume under treatment (e.g., a room) does not need to be previously known or previously calculated, and input into the system for the system to maintain a target concentration of an antimicrobial gas in the air. Where a system requires manual input of a predetermined volume (e.g., cubic feet or cubic meters), risk of overproduction (too high of a concentration to be safe) or underproduction (too low of a concentration to effectively manage microbials) is possible due to user volume miscalculation, user volume entry errors, and the like.

[00227] Additionally, removing a requirement for manual space volume input by a user improves safety, cost efficiency, and streamlines the adaption of the system to changing conditions (e.g., a higher antimicrobial concentration for decontamination versus a lower antimicrobial concentration for maintenance, moving the system to a different volume under treatment (having a different physical volume)).

[00228] The system's automated physical volume estimation and calibration may provide a consistent, data-driven method for estimating a physical volume and the benefit of ensuring safe and efficient dosage and dispensing of an antimicrobial gas even if multiple same-size volumes exhibit different gas decay characteristics. The system permits recursive refinement of (a) the gas decay response (how the volume under treatment (e.g., a room) reacts to the dosage), and (b) the optimization of the gas generation and release cycle to improve target concentration accuracy and consistency (reduce overshoot or under-tolerance) which improves safety, cost efficiency, concentration consistency (so that other factors do not have to be tightly controlled), and the like.

[00229] The data logging of the system's sensor and other operating data generated may provide for stable, complete, regulatorily-required, and standards-based reporting of long term conditions of the volume under treatment and activities of the system suitable for submission to required and desirable government and facility management programs.

[00230] The system may permit closed-loop intelligent, digital control of very small quantities of precursors in specific ratios (e.g., from 1:1 to 1:n) and in varying dosages that are tailored for a volume under treatment, monitored for status, traceability, and quality assurance, and which can be fine-tuned to respond to changing volume under treatment conditions and/or adjusted to serve multiple treatment scenarios. The system does not rely on manual intervention for treatment, monitoring, or record keeping. The system adapts to changing conditions of the volume under treatment (e.g., light, HVAC, entry/exit of living beings, occupancy levels, and the like). The system may include built-in recording, logging, and communications to cloud services for accurate record keeping.

[00231] The system may utilize automated physical volume estimation. Automated physical volume estimation eliminates costly and error-prone measurements that would typically be used to define the treatment parameters. When used recursively, the same or similar algorithm can periodically be used to refine the treatment parameters in order to optimize for one or more performance characteristics (e.g., concentration consistency, lower operational cycle frequency, and the like). The automated physical volume estimation provides input for treatment parameters that are specific to the physical volume, and eliminates guesswork for setup parameters related to antimicrobial dosage.

[00232] In one example, a volume under treatment has an unknown physical volume. The system may generate enough gas to fill a 10 m³ room to a concentration of 100 ppb. The system may wait for a specific duration and then measure the concentration of the antimicrobial gas in the volume under treatment using the device's sensor array. Knowing the expected decay rate of the antimicrobial gas in a room, the system may compare the measured antimicrobial gas concentration to the expected antimicrobial gas concentration, and calculate a ratio. The system may then apply the ratio to the 10 m³ room to obtain the estimated physical volume of the room. Finally, using either an algorithm or a scaled lookup table, the system may determine the desired generation "dose" based upon the estimated physical volume of the room.

[00233] The device and system may include various modes of operation, including a normal mode of operation wherein the device at least one of: (a) establishes and maintains target concentration of an antimicrobial gas without external inputs, (b) records the performance of the device and stores the data, (c) communicates data and status when possible, (d) receives inputs from secure, authorized sources, and (e) shuts down when outside of normal operating parameters or upon experiencing an error. When the device is powered on, the device may assess the current conditions, periodically generate an antimicrobial gas (e.g., ClO₂) and sense the resulting concentration of the antimicrobial gas in the ambient atmosphere, ramping up to and maintaining a target concentration using closed-loop control. The device will thus generate, sense, and communicate its sensed concentrations. The device's default mode may be autonomous operation.

[00234] FIG. 56 illustrates a diagram of an example system 5600 for various operational modes of the device, including one or more of: (a) an unpowered mode (no power is available to the device), (b) an off mode (power is available but the device is not generating or sensing), (c) a self-check mode (a standard power-on self-test ("POST") for the device CPU, checking function of control, generator, sensing, and communication sub-systems), (d) a setup mode (optional mode when device configuration needs to be updated), (e) a standby mode (the device is not operational (no generation and no sensing) but the device is configured and has power and communication

functions), (f) an operational mode (the device is executing its prime directive of sensing, generating, recording, and reporting), and (g) a sense-only mode (the device is executing a portion of the prime directive, including sensing, recording and reporting, but not generating).

[00235] Cloud communication or application-based communication (e.g., from a mobile device such as a smart phone) may suggest a mode for the device, plus a duration of operation for that mode. The device may accept or decline the suggestion. For safety, the mode setting may automatically expire after some predetermined amount of time.

[00236] Standby mode (e) may include a binary toggle for the device to be powered on and communicating, but not operating (no generation, no sensing). Standby mode may provide a power-on and communication-on mode used for reporting and/or audit access. Standby mode may also be useful for a device capability wherein the device is externally switched to the operational mode (e.g., an onboard schedule or connected application tells the device to operate in operational mode (f)).

[00237] Sense-only mode (g) may include a binary toggle that disengages the gas generate function. Sense-only mode may retain communication and sensing functions. Sense-only mode (g) may be used when consumables required for antimicrobial gas (e.g., reagents) are empty. Sense-only mode may be activated from an application and/or the system may include sense-only as an automatic default option when consumables are empty.

[00238] The system and device may be set to designate operational times during a 7-day week. A default mode may be constant (e.g., 24 hours a day and 7 days a week) autonomous generation required for the device to maintain a target concentration in an operational mode. That is, the device is constantly sensing, generating, recording, and reporting. A user may activate a preset timer to activate sense-only mode (g) for a desired amount of time (e.g., x hours), wherein the device thereafter returns to operational mode (f). Other possible schedules include a preset for a particular work shift (e.g., first shift) wherein the device operates for set hours and days corresponding to that shift, which may be for example 8AM – 5PM each day from Monday through Friday. Another possible schedule may include an occasional daily “keep fresh” schedule as desired by a user of x generation cycles per day while ignoring the target concentration, with the goal of keeping a vacant room fresh and/or reduce mold and mildew growth. Finally, a user may be able to make a custom schedule through the associated application.

[00239] Other possible device and system modes include a drone mode (h) wherein the device and system operate on command from a controller (e.g., an edge device) and reports local measures while acting to ensure its own safety parameters are not exceeded. That is, the device and system may be activated as a result of data provided by neighboring devices so as to buttress

those neighboring devices. Other possible device and system modes include a team or flocking mode (i) wherein the device and system reports local measures (from its sensors) to an edge device (e.g., neighboring device). Team or flocking mode (i) may act in concert with a nearby network of peer devices to monitor and maintain an antimicrobial gas concentration in a space larger than suitable for a single device. The devices in a flocked/team mode (i) may not know they are part of a team; the cloud may gather the devices as a group based upon some relationship (e.g., proximity to one another). The cloud may evaluate data from each device and activate pre-defined onboard modes to toggle the performance of a device while maintaining the target concentrations.

[00240] The system integrates four primary sub-systems, which are supported by power and physical housing, including: (a) command and control sub-system, (b) communications sub-system, (c) sensing sub-system, and (d) generation sub-system.

[00241] (a) The control sub-system is illustrated as sub-system **5700** in **FIG. 57**. The control sub-system **5700** manages the other sub-systems and ensures that the device performs as expected. Control sub-system **5700** may manage device initialization (new install) to prompt for and allow configuration of parameters that support normal operation, including one or more of: (i) configure and store device identification and location information, (ii) configure and store networking communications settings, and (iii) configure and store any other user preferences or performance parameters.

[00242] Control sub-system **5700** may manage device startup (power on), which may include checking communications sub-system, generation sub-system, and sensing sub-systems for any errors or conditions that would indicate against operation, including one or more of: (i) critical system errors, (ii) ambient conditions outside of operating parameters, (iii) gas sensing conditions outside of operating parameters, and (iv) generator errors or insufficient consumables.

[00243] Control sub-system **5700** may determine a desired operating mode and subsequently may run according to the operating mode, which may include one or more of: (i) run sensor and read levels, (ii) check levels against exposure limits, (iii) run generator if needed (iv) report on status, (v) wait for next cycle, and (vi) change mode and/or shut down the system if warranted.

[00244] Control sub-system **5700** may listen for any interrupts or commands, log information locally, and communicate information externally.

[00245] A power system may support the device and system by taking input power (standard AC) and delivering output power to the components of the device and system. Alternatively, the power system draws from onboard storage (e.g., batteries) to ensure device

viability during periods of absence of facility power sources, and providing for the graceful shutdown with assured storage of important data during extended facility power outages.

[00246] A housing may support the device and system by providing packaging, protection, and location support. The housing may: (a) hold and position all of the components, (b) provide features for mounting to a wall or placement on a surface, (c) protect the device from external hazards, including liquids, particles, and physical impacts, (d) provide aesthetic features increasing the acceptability of the presence of the device in occupied spaces, (e) provide additional security of the consumable components should their supply containment fail, (f) provide standards based locations for product labeling and regulatory required information, (g) provide visually detectable device identification and authentication features ensuring the manufacturers identity, (h) provide ports for connections between internal components (e.g., onboard power system or networking system) and facility services (standard AC power, internet, and the like), (i) provide feedback device viewports (e.g., a display device or LED status lights), and/or (j) provide venting for thermal control of exhaust of heat and intake of room air for measurements. The housing may additionally include electromagnetic interference (“EMI”) shielding to protect device components from EMI exposure and/or limit radiation of EMI from the device into the surrounding environment.

[00247] (b) The communication sub-system connects either via standard wired (e.g., USB, serial wires, ethernet, and the like) and/or wirelessly (e.g., wireless ethernet, Bluetooth, near field communications, and the like) to a network and exchanges data with a cloud service on an external network. Via the communication sub-system, the device and system may use networking to connect securely through a local intranet and to a cloud service on an external network. The communications protocols may be secured using standard-based industry practices including the exchange of security certificates held in secure persistent microelectronics resident on the device. Via the communication sub-system, the device may send performance, status, and history data to a cloud service for secure off-site storage as well as further analysis.

[00248] (c) The sensing sub-system utilizes a set of sensors, controls, air pumps, and air flow chambers to evaluate ambient air and measure and/or report multiple parameters. A blower may move (pull) ambient air from the volume under treatment, through a filter, into a plenum that houses multiple sensors which are connected to control sub-system **5700**. Clean ambient air may be filtered to remove dust and other particles that could adversely affect the sensors; filters may be selected such that the filters do not interact with measured gas(es) or change the temperature, relative humidity, or other parameters material to the functioning of one or more of the sensor components. Air may be routed through the plenum (a specifically designed set of ducts that route

air across multiple digital and/or analog sensors mounted to a sensor circuit board). Air flow rates may be managed across a set of sensors through control of the blower.

[00249] The sensors may measure and report values to control sub-system **5700**, which is connected to the sensors via wires. The sensors may report temperature, humidity, the presence and activity of reducing and/or oxidizing gases including many commonly found volatile organic compounds (“VOCs”), and the specific gas of interest (e.g., antimicrobial gas) to the system. VOCs may be characterized by the interpolation of characteristic patterns of sensor readings at, for instance, different temperature settings of components of the digital sensing device. At least one additional, identical VOC sensor may provide redundant measurements related to VOCs. The additional VOC sensor may be left inactive in order to act as a replacement should another sensor fail, thereby increasing the reliability and lifespan of the device and system. The additional VOC sensor may also be shielded from exposure to environmental gases and used as a baseline control to support differential signal analysis. A control algorithm may adjudicate the functionality of one or more of the sensor devices such that data from malfunctioning sensors may be excluded from further processing to avoid corrupting the data.

[00250] (d) The generation sub-system utilizes differential pressure or pumps to convey precursors in a specified ratio to a reactor, such as reactor **5800** illustrated in **FIG. 58**. Reactor **5800** may include at least one peristaltic, or other high accuracy, pump(s) provide fluid handling. The pumps may be digitally controlled and monitored to ensure accurate dosage and recordable history. Peristaltic pumps provide accurate dose measurement and may eliminate need for optional check valves or other backflow prevention, are capable of self-priming, and are tolerant of bubbles in the hoses. Peristaltic pumps may use replaceable tube sets with one or more choices for tubing inner diameter to provide a wide range of precision and volume options. Peristaltic pumps can be independent, or the pump heads can be combined to drive multiple parallel tube sets using the same motor drive, reducing motor cost and complexity.

[00251] The pump mechanism can be contained in a removable and/or replaceable consumables cartridge to limit fluid connections or interfaces, and ensure quality pumping for the life of the consumables because the tube sets and other mechanical components of the pump head will wear with usage. The pump mechanism can be custom designed for high volume production, compact packaging, and predictable and reliable function. The pump mechanisms can be designed for very low power consumption, increasing the lifetime of the unit and extending the time between maintenance and/or changes to, for instance, battery power systems.

[00252] Reactor **5800** includes a mixing chamber **5802** where two liquid reagents meet from two input tubes **5804**, **5806**, and two air chambers **5808**, **5810** that help direct the output

antimicrobial gas to exit reactor **5800**. The liquid reagents react and generate the desired antimicrobial gas. Two air chambers **5808**, **5810** surround mixing chamber **5802**, and each air chamber **5808**, **5810** contains a hydrophobic membrane to keep the liquids inside the fluid mixing chamber **5802**. The two hydrophobic membranes may be mechanically secured between the components of the reactor to prevent leaks and ensure liquid containment. Reactor **5800**'s design may be parametric to easily scale reactor **5800** for different doses. Reactor **5800** may utilize a wide range of air pressures and flow rates to leverage existing air flow devices and reduce need for duplicate components. In one aspect, the same blower used to pull air into the sensing sub-system may be used to push air into reactor **5800**.

[00253] The blower may move (push) air into reactor **5800** in low volumes and low pressures consistent with standards required for various volumes under treatment, such as HVAC standards for hospital rooms. This air moved into reactor **5800** may help facilitate liquid mixing, encourage thorough antimicrobial gas generation, and usher the antimicrobial gas out of the device. The blower may be designed and deployed in the airflow pathway such that incoming air is drawn through and over the sensor plenum before passing through the blower to remove the possibility of blower materials affecting the various measurements acquired by the sensors.

[00254] FIG. 59 illustrates a graph of concentration in ppb of antimicrobial gas versus time in minutes for a simulated operation of the system and device for a cubicle. The cubicle has a volume of 14 m³. The system and device generate antimicrobial gas in the amount of 8 µL/generation cycle. The antimicrobial gas is generated using 0.13 mL of precursor. The simulation and graph cover 120 minutes of operation. The upper line is the room concentration of antimicrobial gas in ppb, while the lower line is the concentration of antimicrobial gas generated in each generation cycle, in ppb.

[00255] FIG. 60 illustrates a schematic of a closed-loop system **6000** to maintain target concentrations of an antimicrobial gas in the air, between lower bounds and upper bounds. System **6000** includes a power supply electrically connected to a control sub-system **6002** and a combined generation and sensing sub-system **6004**. Specifically, the power supply may be electrically connected to a controller unit of the control sub-system **6002** and one or more pumps in the generation and sensing sub-system **6004**.

[00256] The controller unit may include communication elements (part of a communications sub-system) such as near-field communication (NFC), Bluetooth (BT), and Wi-Fi capabilities. The controller unit may include input/output ports such as universal serial bus (USB) and secure digital (SD) ports, which may also function as part of a communications sub-system. The controller may include status lights (status LED) indicating power status, Wi-Fi

status, Bluetooth status, and system online status. The controller unit may include analog and digital inputs and outputs. The controller may include power control operatively connected to an air pump driver and an air pump (e.g., a micro blower) of the generation and sensing sub-system **6004**, and a pump control operatively connected to the one or more pump of the generation and sensing sub-system **6004**.

[00257] System **6000** uses the air pump of generation and sensing sub-system **6004** to pull room air into a plenum that houses multiple pre-sensors. Alternatively, system **6000** may include multiple pre-sensors and/or sensors outside of the plenum. The air pump then moves that same room air into a reactor in generation and sensing sub-system **6004** (the reactor may be similar to reactor **5800** for example, or any of the variety of other reactors described herein). The reactor may receive two or more reagents from tanks (e.g., tanks 1 and 2), pumped by pumps (e.g., pumps 1 and 2), into a mixing chamber. Waste from the mixing chamber may be directed out of the reactor, while a resultant antimicrobial gas may be directed into a plenum that houses multiple post-sensors. The resultant antimicrobial gas may be introduced to the ambient, room air for treatment of the room air.

[00258] Measurements and data from the pre-sensors and/or post-sensors may be communicated to the controller for reporting, storage, and/or analysis.

Antimicrobial Target Control

[00259] In one aspect, the target concentration of antimicrobial in the volume under treatment may be controlled via a proportional, integral, and derivative (“PID”) control using mathematical calculations to take the kinetics of a complex system into account without knowing the underlying causes of some of the complex occurrences within that complex system.

[00260] PID does not need to understand what is causing the observed changes in system dynamics. PID focuses upon the target concentration and the immediate and past history of trying to achieve the target concentration mathematically drives electronic to computation controls based upon mathematical operations on the target signal, rather than the complex and changing extrinsic (and often unmeasurable) real world causes of deflection from the target concentration.

[00261] System level performance changes may have real world impact in PID control schemes. For example, control constants may be adjusted to make the system more responsive, acting to achieve the target concentration more rapidly. If the target concentration in the volume under treatment is within allowable limits using this scheme, then this strategy can be employed to ensure that the system is maximized for quick changes in response to volume under treatment changes, such as the number of people in the volume, the opening or closing of doors and

windows, adjustment of the HVAC system, and other events common in real world volumes under treatment.

[00262] Alternatively, the PID may be set by varying only the three PID constants to make the system much slower in response, and designed to never exceed a fixed hard maximum target (e.g., the maximum safe concentration for a particular volume under treatment).

[00263] In another aspect, the target concentration of antimicrobial in the volume under treatment may be controlled via a linear target control including the following steps: (1) input or use automated volume estimation to quantify the three-dimensional spatial volume of a volume under treatment; (2) measure the current antimicrobial concentration in the volume under treatment via antimicrobial concentration sensing; (3a) if the concentration of the antimicrobial is zero or functionally equivalent to zero (considering that concentration = mass/volume and the volume is known or estimated in step 1), instruct the antimicrobial generator to express a mass of antimicrobial estimated to be sufficient to attain the desired target antimicrobial concentration in the known volume of the volume under treatment; and/or (3b) if the concentration of the antimicrobial is non-zero, if the volume under treatment concentration is greater than the target antimicrobial concentration then the antimicrobial generator is held until the concentration is not greater than the target; and if the volume under treatment concentration is less than the target antimicrobial concentration then the antimicrobial generator is instructed to generate a mass proportional to the target antimicrobial minus the volume under treatment concentration, multiplied by the volume of the volume under treatment to bring the concentration of the antimicrobial in the volume under treatment to or above the target concentration.

Safety Assurance

[00264] In a given volume under treatment, various factors may cause decreases in antimicrobial concentration. The kinetics of decreases in antimicrobial concentration due to intrinsic characteristics associated with the volume under treatment may yield expected antimicrobial concentration losses of between 0.1% and 25.0% per minute, with real world expectations and experimental proof demonstrating a range of between 1.0% and 6.0% for indoor rooms, and up to 25.0% for airplanes and small vehicles (e.g., automobile) volumes under treatment.

[00265] In one aspect, with the aforementioned loss rates in mind, the antimicrobial generators may be capable of dosing an antimicrobial to fill or make-up concentration in cycles that have a generation duration of at least 0.25 seconds.

[00266] The systems herein may include a circuit, algorithm, or secondary component that can act as a programmable governor on the frequency generation (and the inverse delay durations)

cycles of the antimicrobial generator. As opposed to simple delay circuits, in the context of a digital disinfection strategy, the systems described herein may vary this programmable governor based upon simple factors, including for example: (1) the dispersion time variable; (2) the antimicrobial decay variable; (3) the user input or estimated volume of the volume under treatment; and (4) user input features of a volume under treatment, including for example, windows, doors, known HVAC design parameters, the presence of absorptive materials in the volume under treatment (e.g., furniture, carpet, curtains, bedding), and the like.

[00267] In another aspect, the systems described herein may be closed-loop system with the means to measure, record, store, and act on, within the target antimicrobial concentrations, a sensor signal proportional to or indicative of the concentration of an antimicrobial in the volume under treatment. The closed-loop systems can use the antimicrobial concentration sensing system to: (1) confirm that a cycle of emission from the antimicrobial generator has the expected concentration effect in the volume under treatment; and/or (2) monitor the power consumption, activation voltages, amperages, or digital signals to components that are utilized in the options of the antimicrobial generators described herein.

[00268] With respect to (1) described immediately above, if one or more cycles of generation have occurred and no volume under treatment concentration is sensed by the antimicrobial concentration sensing device, the closed-loop system will pause/stop/disable the generation unit and ensure that visual, auditory, tactile, and/or data-driven alerts/alarms/warnings are issued to avoid providing a dangerous concentration of antimicrobial to the volume under treatment. Where the concentration in a volume under treatment exceeds an accepted target antimicrobial concentration, an alert may be issued for a non-threatening overconcentration, while an alarm and a stop to all generation activities is issued for a threatening overconcentration. Where the concentration in a volume under treatment does not reach the target antimicrobial concentration when the closed-loop system expects it to reach that concentration (as sensed by the antimicrobial concentration sensing system), then generation activities may be stopped and service personnel may be alerted to examine the unit to ascertain why the target function of the closed-loop system is not being achieved.

[00269] With respect to (2) described immediately above, where the antimicrobial generator is an electrochemical generation with cationic membrane or electrochemical generation with evaporative extraction, measurement of the duration of the applied voltage, amperage, and/or power consumption may result in the closed-loop system shutting down generation where those voltages, amperages, or power consumption values exceed threshold values. This generation shut down may occur regardless of whether the antimicrobial concentration sensing system has

detected an error. The generation shut down may trigger an alert or alarm depending upon how much the threshold values were exceeded.

[00270] Where the antimicrobial generator includes UV with evaporative extraction, the duration that the UV emitter is on, total power consumed, and the like, can be disabled once a particular threshold is achieved, independent of the other channels of data.

[00271] Where the antimicrobial generator includes two chemicals with evaporative extraction, including the use of liquid precursors, an independent encoder on a pump driver's shaft, or a time of driver voltage, amperage, pulse width modulation, and/or other signals can be totaled and compared to safe threshold values.

Antimicrobial Generation Systems and Devices

[00272] FIG. 17 illustrates a system 1700 that is substantially similar to system 900 illustrated in FIG. 9 and described above, where like reference numbers indicate like elements. System 1700 additionally includes pressurized aerosol containers 1786A and 1786B. Aerosol container 1786A may contain liquid precursor 902, while aerosol container 1786B may contain liquid activator 904. Liquid precursor 902 and liquid activator 904 may be delivered to a reaction chamber 906 using the pressure within containers 1786A and 1786B to cause the delivery. Such an embodiment may eliminate the need for electrically powered components for antimicrobial generation and dispersal.

[00273] FIGS. 18A-18D illustrate a reactor 1800 for generating an antimicrobial gas (e.g., ClO₂ gas). Reactor 1800 may be a prepackaged device loaded with a liquid precursor 902 and a liquid activator 904 within containers inside reactor 1800. Liquid precursor 902 may be sealed within its container and may require pressurized air to flow into reaction chamber 906. Liquid activator 904 may be sealed within its container and may require pressurized air to flow into reaction chamber 906.

[00274] Reactor 1800 may include a housing 1840 containing liquid precursor 902, activator 904, a reaction chamber 906, and a waste liquid container 916, wherein device elements are machined or otherwise formed out of a housing material, as in common in the production of microfluidic devices. Reactor 1800 may be a microfluidic device.

[00275] Reactor 1800 may include a pressure input 1841 capable of applying an air pressure to liquid precursor 902 and activator 904 to break seals within their respective containers and/or cause them to travel to reaction chamber 906. Pressure input 1841 may receive pressure from a pump, a syringe, or the like.

[00276] Reaction chamber 906 may include a capillary filter 1842 that permits waste liquid to travel into waste liquid container 916 via capillary action. Waste liquid container 916 may

include an inactivator, neutralizing agent, or the like capable of rendering waste liquid from reaction chamber **906** into a safe state.

[00277] Reaction chamber **906** may include a gas permeable membrane **1844**, which allows an antimicrobial gas (e.g., ClO_2 gas) created in reaction chamber **906** to pass through membrane **1844** at a controlled rate but prevents a waste liquid from reaction chamber **906** from passing through membrane **1844**. Antimicrobial gas (e.g., ClO_2 gas) may exit reactor **1800** via a gas outlet **1843**. Gas outlet **1843** may permit antimicrobial gas (e.g., ClO_2 gas) to exit reactor **1800** and enter the surrounding area, including for example an enclosed space (e.g., a room within a building).

[00278] As illustrated in **FIG. 18D**, reactor **1800** may include a cover **1846** that seals the above-referenced contents (e.g., liquid precursor **902**, activator **904**, reaction chamber **906**, and waste liquid container **916**) within housing **1840**.

[00279] **FIGS. 19A–19I** illustrate a reactor **1900** for generating a disinfecting gas (e.g., ClO_2 gas). Reactor **1900** may include a housing **1950** having an upper surface **1952**. Housing **1950** may include a container **1970** and a reaction chamber **1972** connected to one another by a chamber duct **1976**, wherein device elements are machined or otherwise formed out of a housing material, as in common in the production of microfluidic devices. Reactor **1900** may be a microfluidic device.

[00280] Container **1970** may include a solid container cover **1954** oriented on or near upper surface **1952**. Reaction chamber **1972** may include a reaction chamber cover **1956** oriented on or near upper surface **1952**. Reaction chamber cover **1956** may include an outlet **1960** having an aperture **1958** in fluid communication with the interior of reaction chamber **1972**. Aperture **1958** may include a gas permeable membrane that allows a gas (e.g., ClO_2) to pass through, but prevents a liquid (e.g., waste liquid) from passing through.

[00281] Chamber duct **1976** may include a valve **1980**. Valve **1980** may be a check valve, backflow valve, seal, or the like that prevents the contents of container **1970** and the contents of reaction chamber **1972** from coming into contact with one another until a user selectively causes the contents of container **1970** to be transferred to reaction chamber **1972**.

[00282] Container **1970** may contain a liquid activator as described above, while reaction chamber **1972** may contain a liquid or solid precursor (e.g., liquid NaClO_2 or solid NaClO_2). Alternatively, container **1970** may contain a liquid precursor (e.g., NaClO_2) as described above, while reaction chamber **1972** contains a solid activator or liquid activator.

[00283] Housing **1950** may include an end **1964** including a pressurization device **1962**. Pressurization device may include any device capable of pressurizing the contents of container **1970**, thereby causing the contents of container **1970** to overcome and pass valve **1980** and enter

reaction chamber 1972. Pressurization device 1962 may include a plunger device including a hollow body 1966 extending from end 1964 and in fluid communication with container 1970 via a pressurization duct 1974, and a plunger 1968 extending into hollow body 1966. As illustrated in FIGS. 19H and 19I, plunger 1968 may be actuated by a user and pressed into hollow body 1966, thus causing pressurization of the contents of container 1970, which overcome and pass valve 1980 and flow into reaction chamber 1972. Antimicrobial gas (e.g., ClO₂ gas) is allowed to escape aperture 1958 via an optional gas permeable membrane, while waste liquid is contained within reaction chamber 1972 until reactor 1900 is cleaned and recharged (fresh precursor and activator is added).

[00284] Pressurization device 1962 may be removable. Alternatively, pressurization device 1962 may be entirely separate from housing 1950 and may be applied to housing 1950 by a user only when the user desires to activate reactor 1900. Pressurization duct 1974 may likewise include a valve 1980, which may be a check valve, backflow valve, seal, or the like.

[00285] FIGS. 20A-20D illustrate a reactor 2000 for generating an antimicrobial gas (e.g., ClO₂ gas). Reactor 2000 may be a prepackaged device loaded with a liquid precursor 902, and a solid activator 1330 within containers inside reactor 2000. Liquid precursor 902 may be sealed within its container and may require pressurized air to flow into reaction chamber 906. Solid activator 1330 may be sealed within the reaction chamber 906.

[00286] Reactor 2000 may include a housing 2040 containing liquid precursor 902, activator 1330, a reaction chamber 906, and a waste liquid container 916, wherein device elements are machined or otherwise formed out of a housing material, as in common in the production of microfluidic devices. Reactor 2000 may be a microfluidic device.

[00287] Reactor 2000 may include a pressure input 2041 capable of applying an air pressure to liquid precursor 902 to break a seal within its container and/or cause liquid precursor 902 to travel to reaction chamber 906. Pressure input 2041 may receive pressure from a pump, a syringe, or the like.

[00288] Reaction chamber 906 may include a capillary element 2042 that permits waste liquid to travel into waste liquid container 916 via capillary action. Waste liquid container 916 may include an inactivator, neutralizing agent, or the like capable of rendering waste liquid from reaction chamber 906 into a safe state.

[00289] Reaction chamber 906 may include a gas permeable membrane 2044, which allows antimicrobial gas (e.g., ClO₂ gas) created in reaction chamber 906 to pass through membrane 2044 at a controlled rate but prevents a waste liquid from reaction chamber 906 from passing through membrane 2044. Antimicrobial gas (e.g., ClO₂ gas) may exit reactor 2000 via a gas outlet 2043.

Gas outlet **2043** may permit antimicrobial gas (e.g., ClO₂ gas) to exit reactor **2000** and enter the surrounding area, including for example an enclosed space (e.g., a room within a building).

[00290] As illustrated in **FIG. 20D**, reactor **2000** may include a cover **2046** that seals the above-referenced contents (e.g., liquid precursor **902**, reaction chamber **906**, and waste liquid container **916**) within housing **2040**.

[00291] **FIGS. 23A-23G**, and **FIG. 24** illustrate an example antimicrobial gas (e.g., ClO₂ gas) generator **2300**, **2400**, respectively. Generator **2400** is substantially similar to generator **2300**, but includes a second reagent container **2356**, a second pressure generator **2366**, and all associated ducts and passages to permit the second reagent to flow to a generation chamber **2374**.

[00292] Antimicrobial gas (e.g., ClO₂ gas) generator **2300**, **2400** may include a base **2354**, at least one reagent container **2356** holding a liquid reagent **2358**, and a reagent container lid **2360** with air permeable seal configured to prevent escape of liquid reagent **2358**.

[00293] Within base **2354**, at least one pressure chamber **2362** is oriented below at least one reagent container **2356**, with at least one chamber passage **2364** in communication with pressure chamber **2362** and reagent container **2356**. At least one pressure generator **2366** is oriented in communication with both pressure chamber **2362** and passage **2364**, such that pressure generator **2366** can selectively block or unblock the entrance of chamber passage **2364** into pressure chamber **2362**. Pressure generator **2366** is biased into a position by at least one biasing device **2368**. Biasing device **2368** may be a common biasing device such as a spring. Biasing device **2368** may bias pressure generator **2366** into an open position. Biasing device **2368** may bias pressure generator **2366** into a closed position.

[00294] At least one fluid duct **2370** extends through base **2354** from pressure chamber **2362** to a microfluidic chip **2372**. Microfluidic chip **2372** may include a generation chamber **2374**. A generation duct **2376** may extend partly through base **2354** and partly through the wall of an off-gas and waste chamber **2378**. Chamber **2378** may include an absorber material, an evaporator, or the like. Chamber **2378** may include an absorber material for absorbing spent reagent waste. Chamber **2378** may include an inactivator for waste. Chamber **2378** may include a gas permeable lid **2380** configured to allow the passage of antimicrobial gas (e.g., ClO₂ gas) out of chamber **2378**. Lid **2380** may be a gas permeable membrane.

[00295] Each of the reagent container **2356**, microfluidic chip **2372**, and off-gas and waste chamber **2378** may be attached to and supported upon base **2354**.

[00296] In operation, pressure generator **2366** begins in its closed position, as illustrated in **FIGS. 23A** and **23B**. In this position, pressure generator **2366** seals chamber passage **2364**, such that no liquid reagent **2358** may enter chamber **2362**. Upon an instruction to generate

antimicrobial gas (such as ClO₂ gas) (e.g., from a microcontroller such as microcontroller **306**), pressure generator **2366** moves to its open position, as illustrated in **FIGS. 23C** and **23D**. Liquid reagent **2358** passes out of reagent container **2356** and into pressure chamber **2362**. Pressure chamber **2362** may be sized and shaped to permit a specific desired volume of liquid reagent **2358** to fill pressure chamber **2362** for transfer to microfluidic chip **2372**. Finally, pressure generator **2366** moves back to its closed position, as illustrated in **FIGS. 23E-23G**, at once sealing chamber passage **2364** to prevent further introduction of liquid reagent **2358** from reagent container **2356**, and pressurizing the liquid reagent within chamber **2362**, so as to force the liquid reagent through the remainder of the system. Specifically, the liquid reagent is forced through fluid duct **2370**, through generation chamber **2374**, through generation duct **2376**, and into off-gas and waste chamber **2378**. Here, liquid waste **2382** is captured within chamber **2378**, while antimicrobial gas (e.g., ClO₂ gas) **2384** passes through gas permeable lid **2380** and into the ambient environment.

[00297] It is understood that more than one cycle of pressure generator **2366** from its closed position, to its open position, and back to its closed position, may be required to push reagent **2358** completely through the system. Particularly, when antimicrobial gas (e.g., ClO₂ gas) generator **2300** is new, a few cycles of pressure generator **2366** may be required to begin generating antimicrobial gas (e.g., ClO₂ gas).

[00298] As illustrated in **FIGS. 23A-23G**, generator **2300** may include a single liquid reagent **2358** that enters generation chamber **2374** to generate an antimicrobial gas (e.g., ClO₂ gas). Thus, microfluidic chip **2372** may utilize a microfluidic electrochemical generator as described above.

[00299] Alternatively, as illustrated in **FIGS. 23A-23G**, generator **2300** may include a single liquid reagent **2358** comprising NaClO₂ that enters generation chamber **2374** where a solid activator is contained, thus generating an antimicrobial gas, such as ClO₂ gas.

[00300] Alternatively, as illustrated in **FIG. 24**, generator **2400** may include two separate reagent containers **2356**, with two separate pressure chambers **2362**, two separate pressure generators **2366**, and two separate fluid ducts **2370**, such that the two separate liquid reagents enter generation chamber **2374** separately where they combine and mix to generate antimicrobial gas (e.g., ClO₂ gas).

[00301] Pressure generator **2366** may be actuated via a connection to an actuator (not shown), including for example an electric motor, including an electric step motor, or the like. Pressure generator **2366** may be a plunger and may generate pressure via translation fore and aft (longitudinally).

[00302] Pressure generator **2366** may be, and translate in a direction, coaxial with chamber **2362** and fluid duct **2370**. Pressure generator **2366** may be oriented at, and translate in a direction at, an angle to chamber passage **2364**. In one aspect, pressure generator **2366** translates along an axis that is at a right angle (90 degrees) from the axis of chamber passage **2364**.

[00303] Generator **2300**, **2400** may include one or more control valves (not shown) in communication with pressure generator(s) **2366** and/or reagent container(s) **2356**. Likewise, one or more control valve (not shown) may be in communication with chamber passage(s) **2364** and microfluidic chip **2372**. These valves may selectively permit, prevent, or otherwise control the flow of reagents into generation chamber **2374**. Generator **2300**, **2400** may include a sensor system for determining the quantity, mass, volume, or the like of reagents transiting chamber passage(s) **2364**.

[00304] As such, while these alternative embodiments are not illustrated, they are contemplated and as such, the figures are not intended to be limiting.

Antimicrobial Distribution Systems and Devices

[00305] **FIG. 37** illustrates a system **3700** generating antimicrobial gas or vapor external to a sealed environment for disinfecting items therein. **FIGS. 38A** and **38B** illustrate a system **3800** generating antimicrobial gas or vapor within a sealed environment for disinfecting items in the sealed environment. **FIG. 40** illustrates methods of generating antimicrobial gas or vapor within a sealed environment or external to the sealed environment to disinfect items within the sealed environment. **FIGS. 41A** and **41B** illustrate ClO₂ efficacy test data on controlled samples.

[00306] As used herein, the term “items” may include both personal protective equipment (“PPE”) and non-PPE items, such as personal items, garments, medical equipment, apparel, garments, shoes, personal electronic devices, furniture, office supplies, built-in structures, drapes, fabrics, utensils, fixtures, decorative items, food, and plants. In addition, the term “sealed environment” may include any of: a sealable bag, a tent, a storage container, a drum, a tumbler drum, a chamber, a room, an office, a store, a warehouse, a home, a hospital, a floor of a multi-level building, a cabin, an aircraft cabin, a vehicle cabin, a shipping container, a surface vessel cabin, an underwater vessel cabin, public transportation vehicles.

[00307] Apparatuses/systems **3700** and **3800** utilize an antimicrobial gas, such as chlorine dioxide (ClO₂) gas, for disinfecting PPE including, without limitation, N95 respirators, surgical masks, protective suits, goggles, and helmets, making them safe for reuse by healthcare professionals and patients, as well as personal items and facilities in office and home settings. In addition, the disclosed methods and apparatuses may be applicable to general decontamination of contained spaces and items.

[00308] The technology has been shown effective against an Ebola surrogate on common hard surface and porous household materials and as a broad-spectrum chemical and biological decontaminant for sensitive equipment. The feasibility of disinfecting and reusing N95 masks has previously been demonstrated using hydrogen peroxide gas or vapor, but the need for specialized (and expensive) equipment requires moving used/contaminated N95 masks to a single location for treatment.

[00309] With the proposed approach, used N95s may be placed in a sealable chamber and exposed to the headspace of an antimicrobial gas (e.g., ClO₂ solution, generated on-site and at the time of use). After a short antimicrobial gas generation period, dissolved antimicrobial gas is off-gassed within the chamber, allowing the antimicrobial gas to penetrate and disinfect the respirators. After a sufficient disinfection period, the liquid and gas disinfection solution (e.g., ClO₂) are neutralized before opening the chamber to retrieve the disinfected N95s. Neutralization may be performed by adding a small quantity of neutralizing agent, such as a non-hazardous dry chemical packaged with the kit. The spent disinfection solution and any packaging materials are then disposed as non-hazardous waste. The system design is very scalable, from a single item construct for small batches (approx. 1 - 20 respirators) to a room-size chambers or dedicated rooms for large batches (hundreds or thousands of N95s) for use at treatment facilities, forward operating bases, or hospitals to treat large numbers of N95 masks and other equipment. The method requires no electricity, and the decontamination kit (including the reactive ingredients and a container, such as a plastic bag) can be easily transported with other field equipment. Optionally, gas dispersion units ("GDU") within large room-size chambers for dedicated rooms for large batches may include fans or blowers to accelerate the liberation of ClO₂ while forcing ClO₂ out into the enclosure for faster and more uniform distribution. The GDU may require very little power (e.g., may be operated with a battery).

[00310] Preliminary efficacy testing (**FIGS. 41A** and **41B**) has been conducted by contaminating nine coupons cut from an N95 with 7.7-logs of Phi6 bacteriophage (surrogate for Coronavirus and Ebola) prepared in an organic test soil. Coupons were exposed to ClO₂ gas generated from 6 liters of a 180 ppm ClO₂ solution in an 82-L container. A small fan was directed across the surface of the ClO₂ solution to aid in off-gassing and mixing. Coupons were removed after 1.50, 2.25, and 3.00 hours; the exposure times correspond to three treatment levels: 1500, 2200, and 2800 ppm-hours, respectively. Control coupons were held under ambient conditions for the duration of the experiment (3 hours). After treatment, the coupons were assayed; for all three treatment levels, no virions were recovered from the coupons treated with ClO₂ gas. For all

three treatment levels, a 6-log reduction of virions was observed. **FIGS. 41A** and **41B** show the recovered virions and log reduction observed for each treatment level. The limit of detection (LOD) for this assay was 1.7-logs. Based on this initial test, ClO₂ gas was effective against the Phi6 surrogate and 6-log reduction was achieved in less than 90 minutes.

[00311] **FIG. 37** is another schematic diagram of a system **3700** including an apparatus **3710** generating antimicrobial gas or vapor external to a sealed environment **3750** for disinfecting items therein. System **3700** may include a gas or vapor generator apparatus **3710** coupled to a heating ventilation and air conditioning (“HVAC”) system or a humidifier system to pass humidified disinfecting gas or vapor (e.g., ClO₂ gas or vapor) from a concentrated chlorine dioxide solution **3702**, and the humidified disinfecting gas or vapor **3730** (e.g., ClO₂ gas or vapor) may be further evaporated through a heater **3720** that may be recirculated within the sealed environment for disinfecting items therein.

[00312] System **3700** may additionally include a pump **3704** for pumping ClO₂ solution **3702** to generator apparatus **3710**. A water line **3706** may provide water to generator apparatus **3710**. A generator controller **3708** may act to control, permit user input into, or both, generator apparatus **3710**. A ClO₂ sensor **3734** may be oriented within sealed environment **3750** and may be in communication with (wired or wireless) a process controller **3736**. Process controller **3736** may ultimately control all antimicrobial gas or vapor generation of system **3700**, including receiving data from sensor **3734** regarding the concentration of disinfecting gas or vapor within sealed environment **3750**. Process controller **3736** may cause the generation of more or less disinfecting gas or vapor **3730** to achieve a desired antimicrobial gas or vapor concentration, based upon data received from sensor **3734**.

[00313] The items for disinfection may include one or more of: healthcare personal protective equipment (“PPE”), medical equipment, apparel, garments, shoes, personal electronic devices, furniture, office supplies, built-in structures, drapes, fabrics, utensils, fixtures, decorative items, plants, and packaged or unpackaged food.

[00314] Sealed environment **3750** may be any of: a sealable bag, a tent, a container, a drum, a tumbler drum, a chamber, a room, an office, a store, a warehouse, a home, a floor of a multi-level building, a cabin, an aircraft cabin, a vehicle cabin, a surface vessel cabin, an underwater vessel cabin. Disinfecting the items contained in sealed environment **3750** may achieve destruction of one or more of: microbial organisms, bacteria, viruses, fungi, pests, toxins, germs, mites, bed bugs, and the like.

[00315] FIGS. 38A and 38B illustrate a system 3800 for generating antimicrobial gas or vapor within a sealed environment for disinfecting items in the sealed environment. System 3800 may include apparatuses 3810 and 3860 for generating antimicrobial vapor within a sealed environment for disinfecting items in the sealed environment (3820, 3830, 3840, 3850).

[00316] In FIG. 38A, system 3800 includes an apparatus 3810 (e.g., shop vacuum) used to evacuate 3812 (via a suction side 3813) a sealed environment 3820 (e.g., large bag) through a single passage 3822. After the evacuation, sealed environment 3820 may be back filled 3814 (via an exhaust side 3815) with antimicrobial gas or vapor through single passage 3822 for disinfecting items 3824 therein.

[00317] In FIG. 38B, apparatus 3860 may be used to evacuate (via a suction side 3813) and a plurality of sealed environments 3830, 3840, 3850, and backfill (via an exhaust side 3815) the plurality of sealed environments 3830, 3840, 3850 with antimicrobial gas or vapor through respective passages 3832, 3842, 3852 for disinfecting items therein. Alternatively, as illustrated in FIG. 38B, apparatus 3860 may be used as a gas or vapor generator within a sealed environment 3870. Sealed environment 3870 may be anyone of: a sealable bag, a tent, a container, a drum, a tumbler drum, a chamber, a room, an office, a store, a warehouse, a home, a floor of a multi-level building, a cabin, an aircraft cabin, a vehicle cabin, a surface vessel cabin, an underwater vessel cabin.

[00318] FIG. 40 illustrates a method 4000 for generating antimicrobial gas or vapor within a sealed environment or external to the sealed environment to disinfect items within the sealed environment. Method 4000 includes: providing an antimicrobial vapor to an enclosed environment (step 4002); generating the antimicrobial vapor within the enclosed environment through one of: (step 4004) (a) pumping a controlled concentration level of liquid chlorine dioxide solution into a humidifier system to produce a stream of chlorine dioxide antimicrobial vapor, (b) directly pumping a controlled concentration level of chlorine dioxide antimicrobial vapor to an ambient of the enclosed environment, (c) generating ambient chlorine dioxide antimicrobial vapor by dissolving solid chlorine dioxide reagent into a container filled with water; and placing the container that releases the ambient chlorine dioxide antimicrobial vapor into the enclosed environment, (step 4006); generating the antimicrobial vapor external to the enclosed environment through one of: (step 4008) (a) pumping a controlled concentration level of liquid chlorine dioxide solution into a humidifier system to produce a stream of chlorine dioxide antimicrobial vapor, (b) directly pumping a controlled concentration level of liquid chlorine dioxide antimicrobial vapor to ingress the enclosed environment through a single passage of the enclosed environment, and

(c) directly pumping a controlled concentration level of chlorine dioxide antimicrobial vapor to ingress the enclosed environment through a first passage of the enclosed environment (step **4010**).

[00319] As illustrated, method **4000** optionally performs step **4002** followed by steps **4004** and **4006**, or performs step **4002** followed by steps **4008** and **4010**.

[00320] **FIG. 42** illustrates an apparatus **4200** that generates antimicrobial gas or vapor for disinfecting items in three-dimensional space. **FIG. 43** illustrates an apparatus **4300** that generates antimicrobial gas or vapor for disinfecting items in three-dimensional space. **FIG. 44** illustrates a procedure **4400** for the use of apparatus **4300** in **FIG. 43** to generate antimicrobial gas. **FIG. 45** illustrates a table showing temperature effects to solubility of ClO₂ gas in water and in air and required amount of ClO₂ gas for a defined room size. **FIG. 46** illustrates a uniformity of ClO₂ gas concentration distributed within a room. **FIG. 47** illustrates gas concentration profiles in room setting with furniture. **FIG. 48** illustrates relative humidity and generated ClO₂ gas concentration from a ClO₂ solution. **FIG. 49** illustrates a correlation of increase in disinfection efficacy with elevated humidity. **FIG. 50** illustrates a method **5000** for generating an antimicrobial gas and dispersing the gas via an apparatus.

[00321] **FIGS. 42** and **50** illustrate an example of a mobile apparatus **4200** performing a computer implemented method **5000** to generate and disperse an antimicrobial gas **4220** to a defined volume of space. Method **5000** includes performing the following steps: measuring a volume of space to be disinfected (step **5002**); setting by a controller **4231**, disinfection parameters based on the measured volume of space **4250** to be disinfected (step **5004**), wherein the disinfection parameters comprising at least the following: (a) determining an optimal location of the apparatus **4200** in the volume of space for uniform dispersion of the antimicrobial gas **4220**, (b) a time duration of disinfection cycle, (c) a minimum amount of antimicrobial gas required to be generated, (d) a flow rate of antimicrobial gas generation, a volume of antimicrobial solution, and a concentration of antimicrobial solution **4205** to meet the required flow rate of antimicrobial gas **4220**, (e) a range of antimicrobial gas relative humidity to be used during a disinfection cycle (step **5006**). Afterwards, activating the apparatus **4200** to run the disinfection cycle until completion; discharging through a plurality of nozzles **4210** which are mounted on an oscillating head **4212**, the antimicrobial gas **4220** to volume of space **4250**.

[00322] Method **5000** may further include: monitoring periodically, a reading of antimicrobial gas concentration at a plurality of remote locations (by a plurality of remote sensors **4242-4248**) within volume of space **4250** during the disinfection cycle and adjusting one or more

of: the antimicrobial gas flow rate and the antimicrobial gas concentration for uniform antimicrobial gas dispersion in volume of space **4250** (step **5010**).

[00323] Measuring of the volume of space may be performed by an integrated on-board laser beam scanner **4214**. The method may include oscillating along an axis, the plurality of nozzles **4210** mounted on the oscillating head **4212** in a full circle or less than a half circle. The method may include: in response to the monitored reading of the antimicrobial gas concentration at each of the plurality of locations **4242-4248**, configuring one or more respective nozzles **4210** mounted on the oscillating head **4212** to perform one or a combination of the following to offset concentration differences of the antimicrobial gas at the plurality of locations: adjusting a vertical angle of the nozzle, adjusting a discharge flow rate of the antimicrobial gas, and adjusting a discharge pressure of the antimicrobial.

[00324] In response to the monitored reading of the antimicrobial gas concentration at each of the plurality of locations **4242-4248**, the method may include varying a fan speed of a first blower **4206** which sucks the antimicrobial gas **4208** released from an antimicrobial solution contained in a reactor **4204**. The antimicrobial gas may be released from the antimicrobial solution in vapor phase at the range of relative humidity (RH) according the setting of the controller **4231**, wherein the range of relative humidity of the vapor phase is correlated to a temperature of the antimicrobial solution **4205**.

[00325] The antimicrobial gas or vapor **4220** may be one of: chlorine dioxide (ClO_2) gas or vapor and hydrogen peroxide (H_2O_2) gas or vapor. The ClO_2 gas or vapor may be generated by chemically reacting a chlorite containing compound with an activator and the H_2O_2 gas or vapor is generated by chemically reacting a urea hydrogen peroxide, borax, perborate, or percarbonate compound with the activator, wherein the activator includes an acid or a proton donating solvent. The chlorite or peroxide containing compound and the activator are separately packaged as anhydrous powder or separately packaged as concentrated solution packages which are to be mixed together in the reactor **4206** to form the antimicrobial solution **4205**.

[00326] Upon completion of the disinfection cycle, an aeration cycle may be started for a defined duration of time to adsorb ambient antimicrobial gas in the volume of space. Alternately, the aeration may also take place during the antimicrobial dispersing cycle to facilitate homogeneity of the antimicrobial gas **4220** in ambient. More specifically, the aeration cycle may be performed by drawing and recirculating by a second blower **4207**, ambient air through a carbon/HEPA filter **4224** disposed at an inlet **4209** of the apparatus, and venting filtered air at an outlet **4211** of the apparatus, wherein the second blower **4207** is physically disposed below and

away from the first blower, such that the antimicrobial gas or vapor in the ambient is adsorbed by the carbon/HEPA filter **4224**.

[00327] The mobile apparatus **4200** may be mounted on wheels **4228** to provide mobility. The method may include sending a warning signal from the mobile apparatus in a situation including one or a combination of: (1) when the antimicrobial gas or vapor **4250** in the ambient air exceeds a defined unsafe level, (2) malfunctioning of either the first blower **4206** or the second blower **4207**, or (3) depletion of antimicrobial solution **4205** in the reactor **4206**. The warning signal may be visual, audible, transmitted wirelessly to a remote device (e.g., phone), or any combination thereof.

[00328] FIGS. **43** and **44** illustrate an example of a mobile apparatus **4300** performing a computer implemented method **4400** to generate and disperse an antimicrobial gas or vapor **4310** for disinfecting items in three-dimensional space. Apparatus **4300** may include a humidifier unit **4302**, a main unit **4304**, a support element **4306**, a filtered air outlet **4308**, a carbon filter intake **4312**, main unit fans **4314**, a gas sensor **4316**, a removable remote and data readout tablet **4318**, an oscillating tower fan **4322** with fan outlet **4320**, under cart storage and portable battery placement area **4324**, and a cycle indicator light **4326**. Apparatus **4300** may be mobile and placed upon wheels for easy transport into and from a three-dimensional space to be disinfected.

[00329] Method **4400** may include turning a cap **4436** of a concentrated solution bottle **4432**, **4434** to “prime” and let sit for at 2 hours; place bottles **4432**, **4434** into container unit **4402** (of humidifier unit **4302**); turn caps **4436** of bottles **4432**, **4434** to “in use” and close lid down to lock bottles **4432**, **4434** into the system’s pump; place container unit **4402** into mobile apparatus **4300** adjacent to main unit **4404**; remove remote **4318** from apparatus **4300** and leave the room to be treated, and when yellow light **4441** illuminates, apparatus **4300** will begin pumping fluid into main unit **4404**; when green light **4442** illuminates, apparatus **4300** is ready to begin disinfection; when blue light **4443** illuminates, apparatus **4300** has begun its cycle and humidifier **4302** and fans **4314**, **4322** are activated; when the disinfection cycle is complete, a deactivation command will appear, and UV lights **4446** and chemical release will cause the system to deactivate; when red light **4444** illuminates, apparatus **4300**’s cycle is complete, it is safe for the user to return to the disinfected room, and the fluid has been pumped out of main unit **4304**, **4404** and into the original bottles **4432**, **4434**; container unit **4402** will unlock upon replacement of remote **4318** back upon apparatus **4300**, bottles **4432**, **4434** may be inspected and caps **4436** may be set to “dispose” and discarded.

[00330] In another aspect, the process of generating antimicrobial gas may include the following steps:

- [00331] 1. Steps in Process
- [00332] a. User inputs room identifying information (or automated via RFID tag) and selects disinfection routine via touch screen, Bluetooth or WIFI communication.
- [00333] i. Disinfection cycle may vary based on need, e.g., short-cycle sanitization, between patient turnover, known contagion in room, deodorizing, and the like.
- [00334] ii. Laser scanner to calculate room dimensions/volume, or user-selected options to determine size of a room which may include a combination of user input, laser scanning, and in response to gas concentration levels measured by the system sensors.
- [00335] iii. Disinfection cycle parameters (e.g., RH, ramp up, concentration, time, aeration) based on data models for targeted level of disinfection and room size.
- [00336] 1. Actual data will be recorded for each cycle for each room and used to refine models, in general and for specific rooms/spaces.
- [00337] iv. User provided feedback giving estimated time to run disinfection cycle.
- [00338] v. Warning light activated indicating cycle about to start (occupants should leave the room).
- [00339] b. Device executes user selected disinfection routine based on data model.
- [00340] i. Warning light changes color indicating cycle has started; user is notified via remote monitoring app.
- [00341] ii. Conditions the room to target RH value (based on remote sensor feedback).
- [00342] iii. Calculates rate of antimicrobial gas generation needed to reach target concentration (ppm) during pre-determined time window for initial ramp up.
- [00343] iv. Generates and dispenses antimicrobial gas at calculated rate.
- [00344] v. Uses forced air flow and directional and/or rotating nozzles to dispense gas into room volume.
- [00345] vi. CFM is in excess of gas generation uptake rate and enough to uniformly mix gas in room volume.
- [00346] vii. Intake air for gas antimicrobial mixing is HEPA filtered.
- [00347] viii. Adjusts rate of antimicrobial gas generation to hit targeted rate during ramp up based on feedback from remote chemical sensors to adjust gas generation.
- [00348] 1. Required rate of antimicrobial gas generation is impacted by amount of equipment, furniture, etc. in the room (taking up calculated volume space), the uptake of antimicrobial gas by porous items in the room, and the natural decay of antimicrobial gas concentration.

- [00349] ix. Automatically adjusts rate of antimicrobial gas generation based on feedback from remote chemical sensors to maintain target concentration for duration of disinfection cycle.
- [00350] x. Updates user on time to end of cycle once steady-state conditions are met.
- [00351] xi. Continuously monitors and records sensor data, creating a record that disinfection process parameters were maintained throughout cycle.
- [00352] xii. Terminates gas generation at end of program cycle.
- [00353] xiii. Aeration cycle is initiated.
- [00354] 1. Lower blower system turns over room in air until chemical antimicrobial is no longer detectable (plus factor of safety).
- [00355] 2. Intake air is filtered through carbon filter and HEPA filter to remove antimicrobial and contaminants from air.
- [00356] xiv. Warning light changes color indicating cycle has ended; user is notified via remote monitoring app that it is safe to enter the room.
- [00357] c. Reporting and data analytics.
- [00358] i. Report file generated and uploaded to central data collection system for documentation purposes.
- [00359] ii. Process data added to model training data set to continuously refine disinfection models, both generally and for that specific room.
- [00360] 2. Chlorine Dioxide Gas
- [00361] a. Pure chlorine dioxide gas can be generated from any number of source materials; preferably, generation materials produce a high level of chlorine dioxide.
- [00362] b. Method of generating ClO₂ needs to be capable of enough ClO₂ for at least one antimicrobial cycle.
- [00363] c. Method of generating ClO₂ needs to be capable of producing ClO₂ fast enough to reach target room concentration levels within about 15 minutes.
- [00364] d. Method of ClO₂ generation may be batch process generation or just-in-time production.
- [00365] e. Generation materials are preferably provided in a form that does not require human contact, here introduction/integration process with equipment support chemical feed, and feed rate can be controlled to control the rate of ClO₂ production.
- [00366] f. Pure ClO₂ gas can be separated from liquid using any method, e.g., stirring/mixing; aeration; surface fans/blower; water tower with countercurrent air; airflow over/through water flow or spray; thin film evaporation; vacuum; piezoelectric; heating; and the like.

[00367] g. Liquid byproducts from ClO₂ generation process may be neutralized by any number of chemical reaction processes to destroy residual ClO₂. Alternatively, generation liquids can be recirculated through the system during the aeration cycle to remove residual ClO₂.

[00368] 3. Configuration

[00369] a. The ClO₂ gas disinfection system can be configured as a fully automated unit, with full process control and documentation features, as described.

[00370] b. Manual configurations without process automation and control may be configured for use by properly trained personnel.

Example 1:

[00371] FIG. 51A illustrates the time (minutes) to equilibrium for a target concentration of 0.1 ppm of ClO₂ to air. As illustrated, equilibrium was reached in a matter of minutes using this very small setup.

[00372] After the ambient air inside the ISO shipping container reached an equilibrium of 0.08 ppm, the syringe pumps were turned on to a rate of 1 µL/min. and the ClO₂ concentration was measured at five different ports in the ISO shipping container walls, the ports being spread at different locations around the ISO shipping container. FIG. 51B illustrates the concentration (ppm of ClO₂ to air) measured at each of the five ports over time (minutes). The concentration measured at each port was substantially similar over the test time, as illustrated in FIG. 51B.

Example 2:

[00373] In Example 2, a dose of 125 mL of 0.75 g/mL NaClO₂ and 632 mL of 0.50 g/mL Na₂S₂O₈ were dispensed into a unit with fans blowing down onto the ClO₂ solution. The unit was located in the center of an ISO shipping container (e.g., sealed environment). The fans blew the air within the enclosed, and sealed, ISO shipping container, which had an internal volume of 1,300 cubic feet/36.8 cubic meters. FIG. 52A illustrates the time (minutes) to equilibrium for a target concentration of 350 ppm of ClO₂ to air. As illustrated, equilibrium was reached in about 60 minutes.

[00374] After the ambient air inside the ISO shipping container reached a concentration of about 350 ppm, ClO₂ production was ceased, and a PortaSens device was used to read the concentration at 12 different ports in the ISO shipping container walls, the ports being spread at different locations around the ISO shipping container. FIG. 52B illustrates the concentration (ppm of ClO₂ to air) measured at each of the 12 ports over time (minutes). The concentration measured at each port was substantially similar over the test time, as illustrated in FIG. 52B.

Example 3:

[00375] FIGS. 53A and 53B illustrate diagrams of an example system 5300 for generating ClO₂ vapor from small volumes of high concentration liquid precursors. System 5300 includes a sodium chlorite concentrate 5302 and an activator concentrate 5304. Sodium chlorite concentrate 5302 is fluidically connected to a pump 5306, while activator concentrate 5304 is fluidically connected to a pump 5308. A controller 5310 is operatively connected to both of pumps 5306 and 5308. Controller 5310 controls the operation of pumps 5306 and 5308, including at least volume of fluid pumped, flow rate, timing of pump activation, and the like.

[00376] As illustrated in FIG. 53A, each of pumps 5306 and 5308 are fluidically connected to a t-mixing chamber 5312, where sodium chlorite concentrate 5302 and activator concentrate 5304 are combined to generate ClO₂ vapor. As illustrated in FIG. 53B, each of pumps 5306 and 5308 are fluidically connected to a microfluidic mixing chip 5318, where sodium chlorite concentrate 5302 and activator concentrate 5304 are combined to generate ClO₂ vapor.

[00377] ClO₂ vapor is diffused into the ambient air at diffuser 5314. A ClO₂ sensor 5316 senses the concentration of ClO₂ in the ambient air and is operatively connected to controller 5310. If the concentration of ClO₂ in the ambient air is lower than desired, controller 5310 causes pumps 5306 and 5308 to generate more ClO₂, or to generate ClO₂ at a greater rate, as necessary to achieve the desired concentration of ClO₂. If the concentration of ClO₂ in the ambient air is greater than desired, controller 5310 causes pumps 5306 and 5308 to generate less ClO₂, or to generate ClO₂ at a lesser rate, or to cease the generation of ClO₂ for a desired time to allow the concentration of ClO₂ to fall to a desired level, as necessary to achieve the desired concentration of ClO₂.

[00378] Pumps, such as pumps 5306, 5308, 308A, 308B, and 308C, may be positive displacement pumps. Positive displacement pumps may provide a benefit in that for each rotation/reciprocation of the pump, the volume of fluid pumped is known. In this arrangement, a mass flow controller or flow sensor (such as flow sensors 318A and 318B) may be eliminated from the system. Positive displacement pumps may allow a closed-loop independent sensor (e.g., an encoder) on the pump's rotation/reciprocation means, which further allows the system to yield an independent measure of the pump's movement and/or the volume of fluid pumped. When not reciprocating or rotating, the pumping action may maintain a normally-closed configuration to eliminate leakage flow, which is critical to the control of microvolumes (e.g., microliters), and may eliminate one or more secondary valves, including for example one or more of a leak control valve and a check valve.

[00379] In one aspect, the matter transport system of antimicrobial generators must be designed to minimize post-pump to generator-release "dead volume," which pertains to how much material is left between a pump and downstream active/passive fluidic and/or generator elements.

In one aspect, a target may be less than 1X, or less than 0.5X of minimum generator cycle volume of precursors consumed as same dead space.

[00380] **FIGS. 54A-C** illustrate results of ClO₂ generation using system **5300** or similar systems. The results illustrated in **FIGS. 54A-C** correspond to generation of 0.1 ppm of ClO₂ vapor from small volumes of high concentration precursors. **FIG. 54A** illustrates results obtained from a two-component concentrated liquid generation of ClO₂. **FIG. 54B** illustrates results obtained from an electrochemical generation of ClO₂ from concentrated liquid NaClO₂. **FIG. 54C** illustrates projections for chemical use necessary for a 1,000 cubic foot (28.3 cubic meter) room including various activators, both for initial treatment and after 30 days of continuous operation.

Example 4:

[00381] The efficacy of ClO₂ at ranges of approximately 0.1 ppmv and 5 ppmv was assessed against clinically-relevant infectious bacteria including *Klebsiella pneumonia* (Kp), *Pseudomonas aeruginosa* (PA), *Staphylococcus aureus* (Sa), and *Salmonella enterica* (Se), as well as bacteriophage Phi6 and MS2 (representing enveloped and non-enveloped virus, respectively). The microorganisms were prepared in phosphate buffered saline (PBS), dispensed onto replicate glass coupons (five 10 µL droplets; equivalent to 5-6 log cells or virions per coupon), placed into a room-scale test chamber conditioned with ClO₂ and 50-60% relative humidity (RH) and operated at ambient temperatures ranging from 18 to 21 °C.

[00382] To assess efficacy, the concentration viable bacteria or infective virions recovered from ClO₂ treated coupons versus untreated control coupons versus time were measured. Per test, replicate coupons (duplicates or triplicates) were removed from the test chamber at various time intervals and assayed (extracted and enumerated) to determine the total quantity of organisms recovered. The results were plotted as kill curves (expressed as log organisms recovered versus time). The kill curves were then used to calculate the D-values of gas treatment, representing the time required to achieve a 90% reduction (or 1 log reduction) of viable/infective organisms at a given test condition. The area of the kill curve in which linear decay was observed was used to determine the D-value (calculated as the negative inverse of the linear decay slope).

[00383] **FIGS. 55A** and **55B** illustrate the mean D-values (hours) from replicate tests per organism performed at the range of 0.11 ± 0.04 ppmv (**FIG. 55A**) and 5.3 ± 2.4 ppmv (**FIG. 55B**).

[00384] The results demonstrate that at 0.1 ppmv (**FIG. 55A**) a reduction of 90% of all organisms was rapid and comparable ranging from 0.5 to 1.2 hours (or 31 to 70 minutes).

[00385] As would be expected, the efficacy increased with treatment at 5 ppmv (**FIG. 55B**) with D-values ranging from 0.2 to 0.3 hours (or 13 to 19 minutes).

[00386] Based on this data, the time to achieve a 99.9 % or 3-log reduction at 0.1 ppmv and 5 ppmv correlates to 1.5 to 3.6 hours and 0.6 to 0.9 hours, respectively.

Antimicrobial Generation and Monitoring Systems and Devices

[00387] A system for generating and monitoring an antimicrobial, is provided, the system comprising: a computational system; an antimicrobial sensor; and an antimicrobial generator, wherein the computational system, the antimicrobial generator, and the antimicrobial sensor are operatively connected. The computational system may be at least one of a microprocessor and a microcontroller. The system may further include an external communication device. The system may include a separate sensor sub-system comprising: at least one of a sensor sub-system microprocessor and a sensor sub-system microcontroller; a sensor sub-system external communications device; at least one of a sensor sub-system antimicrobial sensor and a sensor sub-system environmental sensor; and a sensor sub-system computational system. The system may include a separate generation sub-system comprising: at least one of a generation sub-system microprocessor and a generation sub-system microcontroller; a generation sub-system external communications device; and a generation sub-system antimicrobial generator. The external communications device, the computational system, the antimicrobial generator, and the at least one of an antimicrobial sensor and an environmental sensor may be oriented within an enclosed volume under treatment. At least one sensor sub-system and/or generation sub-system may be oriented within an enclosed volume under treatment.

[00388] A system for generating and monitoring an antimicrobial is provided, the system comprising: a sensor sub-system comprising: at least one of a sensor sub-system microprocessor and a sensor sub-system microcontroller, a sensor sub-system external communications device, at least one of a sensor sub-system antimicrobial sensor and a sensor sub-system environmental sensor, and a sensor sub-system computational system; a generation sub-system comprising: at least one of a generation sub-system microprocessor and a generation sub-system microcontroller, a generation sub-system external communications device, and a generation sub-system antimicrobial generator; and an enclosed space forming a volume under treatment. The sensor sub-system and the generation sub-system may be oriented within the enclosed volume under treatment. The sensor sub-system may be oriented within the enclosed volume under treatment and the generation sub-system may be oriented outside of the enclosed volume under treatment. The generation sub-system may be oriented within the enclosed volume under treatment and the sensor sub-system may be oriented outside of the enclosed volume under treatment. The system may include an HVAC air supply fluidically connected to the interior of the enclosed volume under treatment, the sensor sub-system may be oriented within the enclosed volume under

treatment, the generation sub-system may be oriented outside of the enclosed volume under treatment, and the generation sub-system may be fluidically connected to the HVAC air supply. The system may include an HVAC air return fluidically connected to the interior of the enclosed volume under treatment, the generation sub-system may be oriented within the enclosed volume under treatment, the sensor sub-system may be oriented outside of the enclosed volume under treatment, and the sensor sub-system may be fluidically connected to the HVAC air return.

[00389] A system for generating and monitoring ClO₂ is provided, the system comprising: a device housing including an inlet; a microcontroller or microprocessor; a reagent container containing a reagent; a device for generating a ClO₂ from the reagent; and a sensing system. The system may include two reagent containers, and each reagent container may contain a different reagent. The device for generating the ClO₂ may be a microfluidic mixer, and the two reagents may mix in the microfluidic mixer to generate the ClO₂. The device for generating the ClO₂ may be an electrochemical generator. The sensing system may measure a concentration of ClO₂ in ambient air introduced via the inlet. The measurement of concentration of ClO₂ in the ambient air may be communicated to the microcontroller or microprocessor, and the microcontroller or microprocessor may cause the system to generate the ClO₂ if the ClO₂ concentration is below a target value. The system may include one reagent container and one reagent, the device for generating the ClO₂ may be an electrochemical generator, and the electrochemical generator may use an electrical potential to cause a reaction with the reagent that generates the ClO₂. The electrochemical generator may be a microfluidic device. The system may include a barometric sensor to sense a pressure of ambient air introduced via the inlet, the pressure may be communicated to the microcontroller or microprocessor, and a negative pressure may cause the microcontroller or microprocessor to pause ClO₂ generation until a neutral and/or positive pressure is sensed by the barometric sensor. The system may include an off-gas and waste chamber having a membrane, waste from the generation of the ClO₂ may be absorbed in an absorber material, and ClO₂ may exit the off-gas and waste chamber through the membrane and into an ambient atmosphere. The system may include an air pump electrically connected to the microcontroller or microprocessor and fluidically connected to the inlet via an air duct. The microcontroller or microprocessor is controlled by machine learning algorithms to alter system performance. The microcontroller or microprocessor may be controlled by artificial intelligence algorithms to alter system performance. The microcontroller or microprocessor may alter system performance automatically. The microcontroller or microprocessor may alter system performance by control by a user. The microcontroller or microprocessor may alter the system performance based upon at least one of: a detection of a virus in ambient air containing the system; a detection

of bacteria in ambient air containing the system; an altitude of the system; a temperature of the system; changes in ambient air measured by changes in a concentration of ClO₂ in ambient air; changes in occupancy by living beings of an area containing the system; alterations for a user's preferences; prediction of cycles of occupancy and vacancy by living beings of the area containing the system; and a diagnosis of normal or abnormal performance of the system.

[00390] A network of systems for generating and monitoring ClO₂ is provided, the network of systems comprising: a plurality of systems for generating and monitoring ClO₂, including: a device housing including an inlet; a microcontroller; a reagent container containing a reagent; a microfluidic device for generating a ClO₂ from the reagent; and a sensing system; wherein the microcontroller includes a communication device capable of communication between the plurality of systems, wherein the communication device establishes distributed control of each system's microcontroller, and wherein the microcontroller is controlled by machine learning algorithms to alter system performance. The distributed control may include at least one of: adjusting individual systems to achieve a uniform or deliberately non-uniform distribution of ClO₂ in each individual sensor's location within a specified space; consumption of ClO₂; control of day and/or night generation cycles; using the sensing system to sense patterns across time, three-dimensional volumes, seasonal variations; sending patterns that are inferred or traced to a signal measured; and sensing patterns that are directly traceable to variations observed in ClO₂ concentrations across the network of systems installed across distinct spaces.

[00391] A network of systems for generating and monitoring ClO₂ concentration is provided, the network of systems comprising: a plurality of systems for generating and monitoring ClO₂, including: a device housing including an inlet; a microcontroller; a reagent container containing a reagent; a microfluidic device for generating a ClO₂ from the reagent; and a sensing system; wherein the microcontroller includes a communication device capable of communication between the plurality of systems, wherein the communication device establishes distributed control of each system's microcontroller, and wherein the microcontroller is controlled by artificial intelligence algorithms to alter system performance. The distributed control may include at least one of: adjusting individual systems to achieve a uniform or deliberately non-uniform distribution of ClO₂ in each individual sensor's location within a specified space; consumption of ClO₂; control of day and/or night generation cycles; using the sensing system to sense patterns across time, three-dimensional volumes, seasonal variations; sending patterns that are inferred or traced to a signal measured; and sensing patterns that are directly traceable to variations observed in ClO₂ concentrations across the network of systems installed across distinct spaces.

[00392] FIGS. 61A and 61B illustrates an example antimicrobial gas generator 6100. Generator 6100 includes a reaction chamber 6102 having an air/precursor inlet 6104, and optionally a UV light inlet 6106. UV light inlet 6106 may be operatively connected to a hollow tube 6108, thus permitting the UV light to travel into reaction chamber 6102. Hollow tube 6108 includes a curved portion 6110 in the shape of an inverted “U,” which extends into the top of an evaporative waste trap 6112. Evaporative waste trap 6112 includes an antimicrobial outlet 6114 including a hydrophilic membrane 6116 (PTFE or the like).

[00393] In one aspect, generator 6100 may be a photonic activation antimicrobial generator. Generator 6100 may use UV light to activate one, two, or more precursors (e.g., liquid precursors) within reaction chamber 6102. The light may be UV-C wavelengths centered around 255 nm are known to cleave the sodium atom of chlorite (NaClO_2) to release ClO_2 through hollow tube 6108, into evaporative waste trap 6112, through membrane 6116, and into the volume under treatment through antimicrobial outlet 6114.

[00394] The described wavelength of the UV-C light is also known to reduce ClO_2 gas to intermediate species on the way to reduction to chlorine gas. Thus, the time of exposure of the NaClO_2 to the UV-C light is limited.

[00395] NaClO_2 is introduced to reaction chamber 6102 in liquid form. UV-C penetration depth is very small in water. Thus, generator 6100 causes the evaporation of the water containing sodium chlorite in reaction chamber 6102 in a manner such that “fresh surfaces” are exposed throughout the evaporation process achieving the goal of exposing all the sodium chlorite in that volume of water assuming that a dried salt does not block the UV light. Considering that a user expects generator 6100 to generate only small doses of ClO_2 , it is noted that attempting to control a bulk solution of precursor removes the ability to control dose and/or deal with residues that interfere with reactions of sodium chlorite while it is solution without complicated membranes or machines. As such, generator 6100 causes fresh sodium chlorite to be exposed at an ever shrinking boundary layer between the atmosphere and a droplet containing an aqueous solution of sodium chlorite, by using vibrational atomization or nebulization to generate a highly uniform and size-limited pattern of droplets from incredibly small volumes of liquid when expelled into a gas flow stream past a UV source of the desired frequency. Providing the sodium chlorite in a volume of liquid defined as an evaporating droplet can ensure that all the sodium chlorite in solution is exposed to UV/UV-C, while still in an aqueous solution, and thus converted from NaClO_2 to ClO_2 .

[00396] Generator 6100 may also enable the control of total dose kinetics of UV or any other wavelength of light to a precursor liquid that can be nebulized or atomized into droplets.

Flowing gas (entering inlet **6104** and exiting outlet **6114**) in the hollow tube **6108** directs the flow of atomized antimicrobial out of outlet **6114**. This flowing “sheath gas” is the atmosphere of the room, pumped into a port (which may be the same as or different from inlet **6104**) in reaction chamber **6102**, at a known quantity from which it is easy to calculate the flow velocity in the much larger diameter UV exposure portion of hollow tube **6108** (e.g., that portion between UV light inlet **6106** and reaction chamber **6102**). Hollow tube **6108** may be much larger in diameter where the atomized droplets meet the sheath gas, which may result in the velocity of the combined streams of flowing gas and droplets of aqueous sodium chlorite able to be controlled simply by increasing or decreasing the gas sheath air pump velocity. Controlling this velocity of the combined streams controls the length of exposure to the highly focused UV-C light provided from UV light inlet **6106** (e.g., via an LED bulb) to the simultaneously moving and evaporating droplets for between 0.1 and 5.0 seconds. Changes to the quantity of gas pumped in as the sheath gas, diameter of the geometry of the unit, and/or a combination of these types of variables can provide a much larger range of time-of-flight exposure of an evolving UV-C and aqueous solution interface boundary being constantly refreshed with precursor material by the physics of evaporation of small droplets.

[00397] In another aspect, gas generator **6100** is an electrochemical generator. In this embodiment, UV light inlet **6106** is eliminated, and an electrochemical generator cell is oriented inside reaction chamber **6102**. The electrochemical generator cell includes an electrode array adjacent to the inlet side of reaction chamber **6102**, wherein reaction chamber **6102** further includes a mesh atomizer.

[00398] In each aspect, generator **6100** produces atomized antimicrobial droplets and separates the antimicrobial from the waste. That is, the atomized antimicrobial exits evaporative waste trap **6112** via membrane **6116** and outlet **6114**, while waste is unable to pass through membrane **6116** and falls instead to the bottom of evaporative waste trap **6112**.

[00399] Generator **6100** additionally uses the evaporation of the droplets to minimize waste volume. Evaporation of the liquid droplets in the time of flight, combined with a separation mechanism such as a hydrophobic small pore membrane (membrane **6116**) that is highly permeable to small gaseous molecules, enables the separation of the solid waste (and/or liquid waste should some percentage of droplets not fully evaporate due to size, coalescence of droplets, or other causes).

[00400] To the extent that the term “includes” or “including” is used in the specification or the claims, it is intended to be inclusive in a manner similar to the term “comprising” as that term is interpreted when employed as a transitional word in a claim. Furthermore, to the extent that the

term “or” is employed (e.g., A or B) it is intended to mean “A or B or both.” When the applicants use the term “and” in a list, such as “one or more of A, B, and C,” Applicant intends the term “and” to be interpreted as “and/or.” When the applicants intend to indicate “only A or B but not both” then the term “only A or B but not both” will be employed. Thus, use of the term “or” herein is the inclusive, and not the exclusive use. See Bryan A. Garner, *A Dictionary of Modern Legal Usage* 624 (2d. Ed. 1995). Also, to the extent that the terms “in” or “into” are used in the specification or the claims, it is intended to additionally mean “on” or “onto.” To the extent that the term “substantially” is used in the specification or the claims, it is intended to take into consideration the degree of precision available in manufacturing. To the extent that the term “selectively” is used in the specification or the claims, it is intended to refer to a condition of a component wherein a user of the apparatus may activate or deactivate the feature or function of the component as is necessary or desired in use of the apparatus. To the extent that the term “operatively connected” is used in the specification or the claims, it is intended to mean that the identified components are connected in a way to perform a designated function. As used in the specification and the claims, the singular forms “a,” “an,” and “the” include the plural. Finally, where the term “about” is used in conjunction with a number, it is intended to include $\pm 10\%$ of the number. In other words, “about 10” may mean from 9 to 11.

[00401] As stated above, while the present application has been illustrated by the description of aspects thereof, and while the aspects have been described in considerable detail, it is not the intention of the applicants to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications will readily appear to those skilled in the art, having the benefit of the present application. Therefore, the application, in its broader aspects, is not limited to the specific details, illustrative examples shown, or any apparatus referred to. Departures may be made from such details, examples, and apparatuses without departing from the spirit or scope of the general inventive concept.

CLAIMS

What is claimed is:

1. A closed-loop system for generating and monitoring an antimicrobial, comprising:
 - a control sub-system comprising:
 - a controller unit;
 - a communications sub-system comprising:
 - one or more of a wired communication mechanism and a wireless communication mechanism for connecting to an external network;
 - a sensing sub-system comprising:
 - one or more sensor,
 - wherein the one or more sensor is operatively connected to the control sub-system;
 - a generation sub-system;
 - wherein the antimicrobial is applied to a volume under treatment;
 - wherein the sensing sub-system samples air from the volume under treatment continuously or on a predetermined schedule and measures the concentration of the antimicrobial present in the air from the volume under treatment; and
 - wherein the generation sub-system generates the antimicrobial in response to a difference between a target value and the sensing sub-system measurement.
2. The closed-loop system of claim 1, further comprising an air pump located upstream or downstream of the one or more sensor, wherein the air pump draws the air from the volume under treatment into contact with the one or more sensor.
3. The closed-loop system of claim 1, wherein the one or more sensor is oriented in one or more plenum, wherein the one or more sensor and the one or more plenum comprise one or more pre-sensor located in a plenum upstream of the reactor, and one or more post-sensor located in a plenum downstream from the reactor.
4. The closed-loop system of claim 3, further comprising an air pump located downstream of the one or more pre-sensor and upstream of the one or more post-sensor.
5. The closed-loop system of claim 1, wherein the antimicrobial is an antimicrobial gas or vapor.
6. The closed-loop system of claim 5, wherein the antimicrobial gas is ClO_2 .
7. The closed-loop system of claim 1, wherein the antimicrobial is an airborne antimicrobial.

8. The closed-loop system of claim 1, wherein the generation sub-system comprises a reactor including a mixing chamber, wherein two or more reagents are combined in the mixing chamber to create an antimicrobial, and wherein the generation sub-system further comprises a plurality of liquid reagent tanks, wherein the reagent tanks and the reagent pumps are fluidically connected to the reactor mixing chamber.
9. The closed-loop system of claim 1, wherein the generation sub-system discontinues generation of the antimicrobial in response to a difference between a target value and the sensing sub-system measurement.
10. A closed-loop system for generating and monitoring an antimicrobial, comprising:
 - a sensor sub-system comprising:
 - at least one of a sensor sub-system microprocessor and a sensor sub-system microcontroller,
 - at least one of a sensor sub-system antimicrobial sensor, and
 - a sensor sub-system computational system;
 - a generation sub-system comprising:
 - at least one of a generation sub-system microprocessor and a generation sub-system microcontroller, and
 - a generation sub-system antimicrobial generator; and
 - an enclosed space forming a volume under treatment.
11. The system of claim 10, wherein the sensor sub-system and the generation sub-system are oriented within the enclosed volume under treatment.
12. The system of claim 10, wherein the sensor sub-system is oriented within the enclosed volume under treatment and wherein the generation sub-system is oriented outside of the enclosed volume under treatment.
13. The system of claim 10, wherein the generation sub-system is oriented within the enclosed volume under treatment and wherein the sensor sub-system is oriented outside of the enclosed volume under treatment.
14. The system of claim 10, further comprising an HVAC air supply fluidically connected to the interior of the enclosed volume under treatment, wherein the sensor sub-system is oriented within the enclosed volume under treatment, wherein the generation sub-system is oriented outside of the enclosed volume under treatment, and wherein the generation sub-system is fluidically connected to the HVAC air supply.
15. The system of claim 10, further comprising an HVAC air return fluidically connected to the interior of the enclosed volume under treatment, wherein the generation sub-

system is oriented within the enclosed volume under treatment, wherein the sensor sub-system is oriented outside of the enclosed volume under treatment, and wherein the sensor sub-system is fluidically connected to the HVAC air return.

16. The system of claim 10, further comprising an HVAC air return fluidically connected to the interior of the enclosed volume under treatment, wherein the generation sub-system is oriented within the enclosed volume under treatment, wherein the sensor sub-system is oriented within the enclosed volume under treatment, and wherein the sensor sub-system is fluidically connected to the HVAC air return.

17. The system of claim 10, further comprising an HVAC air return fluidically connected to the interior of the enclosed volume under treatment, wherein the generation sub-system is oriented within the enclosed volume under treatment, wherein the sensor sub-system is oriented within the enclosed volume under treatment, and wherein each of the generation sub-system and the sensor sub-system is fluidically connected to the HVAC return.

18. The system of claim 10, further comprising an HVAC air supply fluidically connected to the interior of the enclosed volume under treatment, wherein the generation sub-system is oriented within the enclosed volume under treatment, wherein the sensor sub-system is oriented within the enclosed volume under treatment, and wherein each of the generation sub-system and the sensor sub-system is fluidically connected to the HVAC air supply.

19. A network of systems for generating and monitoring an antimicrobial, comprising:

a plurality of systems for generating and monitoring an antimicrobial, including:

a microcontroller;

a sensing system;

wherein the microcontroller includes a communication device capable of communication between the plurality of systems, and

wherein the communication device establishes distributed control of each system's microcontroller.

20. The network of systems of claim 19, wherein the microcontroller is controlled by one or more of machine learning algorithms and artificial intelligence to alter system performance.

21. The network of systems of claim 19, wherein the antimicrobial is ClO₂.

22. The network of systems of claim 19, wherein the distributed control includes at least one of:

adjusting individual systems to achieve a uniform or deliberately non-uniform distribution of the antimicrobial in each individual sensor's location within a specified space;

consumption of the antimicrobial;

control of day and/or night generation cycles;

compensation for an HVAC system air exchange or other dilution of an air in which the antimicrobial is distributed;

using the sensing system to sense patterns across time, three-dimensional spaces, and seasonal variations;

sending patterns that are inferred or traced to a signal measured; and

sensing patterns that are directly traceable to variations observed in the antimicrobial concentrations across the network of systems installed across distinct spaces.

23. A system for generating and monitoring an antimicrobial, comprising:

a computational system;

an antimicrobial sensor; and

an antimicrobial generator,

wherein the computational system, the antimicrobial generator, and the antimicrobial sensor are operatively connected.

24. The system of claim 23, wherein the antimicrobial is ClO₂.

25. The system of claim 23, further comprising an external communication device.

26. The system of claim 23, further comprising one or more separate sensor sub-systems comprising:

at least one of a sensor sub-system microprocessor and a sensor sub-system microcontroller;

a sensor sub-system external communications device;

at least one of a sensor sub-system antimicrobial sensor and a sensor sub-system environmental sensor; and

a sensor sub-system computational system.

27. The system of claim 23, further comprising a separate generation sub-system comprising:

at least one of a generation sub-system microprocessor and a generation sub-system microcontroller;

a generation sub-system external communications device; and

a generation sub-system antimicrobial generator.

28. The system of claim 25, wherein the external communications device, the computational system, the antimicrobial generator, and the at least one of an antimicrobial sensor and an environmental sensor is oriented within an enclosed volume under treatment.

29. The system of claim 26, wherein at least one sensor sub-system is oriented within an enclosed volume under treatment.

30. The system of claim 27, wherein at least one generation sub-system is oriented within an enclosed volume under treatment.