

Conversion of Solid Waste into syngas and hydrogen

Subject matter of the present invention is the conversion of solid waste, like municipal solid waste and/or biomass in the form of solid recovered fuel (SRF) pellets to a product stream rich in hydrogen, preferably into pure hydrogen.

Municipal Solid Waste (MSW) is generated worldwide and has to be dealt with. In the western hemisphere municipal solid waste is either landfilled or incinerated. Incineration is focused on maximizing the use of the energy content of the municipal solid waste in contrast to recycling or reusing the contents of the municipal solid waste on a molecular scale as e.g. in chemical recycling. Incineration generates issues regarding the emission of pollutants into the atmosphere which results – depending on national or even local legislation – in significant technological efforts necessary to meet the limitations provided by national/local legislation. Further, the products generated by the incineration, e.g. fly ash, bottom ash, gypsum and heavy metal and/or dioxin laden active coal, create further challenges regarding their further use and/or processing. Furthermore, the waste to power efficiency, i.e. the amount of caloric value transferred to heat energy is low and is typically in a range of only 20 to 25%.

Based on this the object of the present invention is to overcome the drawbacks known from prior art.

This object is solved by the features of the independent claims. The respective dependent claims are directed to further embodiments of the invention. Further embodiments can be deducted from the specification including the figures and the respective description of the figures.

The method for processing solid recovered fuel pellets according to the present invention, comprises the following steps:

a) torrefaction of the pellets at a torrefaction temperature of 250°C to 300°C generating charred pellets and torrefaction gas, step a) preferably performed in a torrefaction unit as described below;

b) milling the charred pellets in a first milling step to coarsely milled charred pellets, step b) preferably performed in a second mill as described below;

c) removing metal residues from the coarsely milled charred pellets, step c) preferably performed using a third metal removal unit as described below;

5 d) milling the coarsely charred pellets to finely milled charred pellets, step d) preferably performed in a third mill as described below;

e) gasifying the finely milled charred pellets to raw syngas in an entrained flow gasifying process, step e) preferably performed in a gasification unit as described below;

10 f) performing CO shift reactions to the raw syngas creating shifted syngas, step f) preferably performed in a CO shift unit as described below;

g) removing carbon dioxide and hydrogen sulfide from the shifted syngas creating a syngas; and

h) generating a product gas stream rich in hydrogen by purifying the syngas, step g) and h) preferably performed in a gas cleaning unit as described below.

The steps a) to h) are performed according to the invention in the order mentioned, i.e. first step a), then step b), then step c), then step d), and so forth. The term torrefaction in step a) is understood as a thermochemical treatment of the solid recovered fuel pellets at temperatures of 250°C to 320°C. It is carried out under atmospheric pressure and without adding further oxygen, e.g. without providing air. During the torrefaction process water contained in the solid recovered fuel pellets evaporates as do volatiles included in the solid recovered fuel pellets. Biopolymers included in the solid recovered fuel pellets partly decompose under release of volatiles. The product of the torrefaction process are charred pellets and torrefaction gas.

25 The term hydrogen rich gas stream or a gas stream rich in hydrogen is understood as a gas that comprises at least 90 vol.-% hydrogen, preferably at least 95 vol.-% hydrogen, in particular at least 99.5 vol.-% hydrogen. The remaining amount comprises argon (Ar), nitrogen (N₂), carbon monoxide (CO) and carbon dioxide (CO₂). Preferably, in step g) and h) first, via adsorption, carbon dioxide and hydrogen sulfide are removed, thereafter, second, via a pressure swing adsorption (PSA) process, hydrogen is sepa-

rated from the remaining as to form the product gas stream rich in hydrogen with a hydrogen content of, preferably, at least 99.5% vol.-%.

Preferably, the solid recovered fuel pellets are produced from municipal solid waste, possibly with added biomass, preferably as disclosed below in connection with the pelletizing facility, in particular referring to figs. 1 and 3. In the process as described most metal residues are removed from the waste before producing the solid recovered fuel pellets. Nevertheless, it is possible that this does not remove metal residues in its entirety. Therefore, after step b) in step c) the amount of metal residues in the charred pellet is further reduced. As an eddy current technology is applied, both iron and non-iron metal residues can be removed from the coarsely milled charred pellets.

In step b) the milling process is performed to generate a first particle distribution having a first maximum particle size of preferably 10 mm [millimeters] and less. In step d) the milling process is performed to generate a second particle distribution having a second maximum particle size being significantly smaller than the first maximum particle size. Preferably, the second maximum particle size is 350 μm [micrometers]. The second maximum particle size is preferably chosen to allow an efficient entrained flow gasification in step e). This allows both an efficient removal of metal residues in step c) and an efficient entrained flow gasification in step e).

The entrained flow gasification in step e) is, preferably, performed using a full water quench on the syngas generated during the entrained flow gasification. The quench results in any solids even in the molten state included in the syngas are solidified and are collected as slag in the process. The quench water is used cyclical, i.e. preferably no water is discharged from the system. The waste water of the process is treated and evaporated eventually producing sodium chloride (NaCl) as a by-product. The condensate is reused in the process as process make-up water.

The method according to the present invention allows a chemical recycling of municipal solid waste generating hydrogen which can be used as feedstock in chemical processes and/or for storing energy.

According to an embodiment the torrefaction gas generated in step a) is thermally cracked for the generation of a torrefaction syngas, said torrefaction syngas being mixed with the raw syngas generated in step e) before step f).

5 The thermal cracking of the torrefaction gas is performed in a torrefaction gas processing unit which is described in detail below, in particular referring to fig. 4. Thermal cracking is preferably performed using a substoichiometric oxidization process for cracking long hydrocarbons possibly present in the torrefaction gas and/or the fuel gas used for the thermal cracking. Preferably, an oxygen rich gas stream with 95 vol.-% oxygen, preferably pure oxygen, is used in the thermal cracking process. With the
10 thermal cracking of the torrefaction gas the torrefaction syngas can be used for chemical recycling as well, instead of burning the same.

According to an embodiment in step b) the charred pellets are milled to a particle size of 10 mm and less. This allows an efficient removal of the metal residues in step c). Step b) is preferably performed in a second mill as described below.

15 According to an embodiment in step c) the metal residues are removed using an eddy current technology. The eddy current is applied in such a manner, that both iron and non-iron metal residues are removed. Step c) is preferably performed using a third metal removal unit as described below.

20 According to an embodiment in step d) the coarsely milled charred pellets are milled to a particle size of 500 μm [micrometer] and less. This allows an efficient entrained flow gasification of the finely milled charred pellets. It is possible to add milled biomass to the finely milled charred pellets before performing the entrained flow gasification as is described below. Step d) is preferably performed in a third mill as described below.

25 According to an embodiment in step g) carbon dioxide (CO_2) and hydrogen sulfide (H_2S) are removed from the syngas by adsorption. The respective carbon dioxide is purged from the respective at least one adsorber and is used as feedstock for chemical processes or is purged to the ambient. Hydrogen sulfide is converted into elemen-

tary Sulphur using a Claus process. The respective Claus unit offgases are hydrotreated and recycled to the respective adsorber.

According to an embodiment in step g) hydrogen is separated from the syngas using pressure swing adsorption (PSA) creating the product gas stream rich in hydrogen
5 and a purge gas.

According to an embodiment at least a part of the purge gas is provided to the CO shift reaction in step e). This allows an increase in the conversion efficiency in the CO shift unit and increases the total hydrogen yield.

According to an embodiment, a part of the purge gas is used as fuel gas.

10 The purge gas comprises at least one of carbon monoxide (CO), carbon dioxide (CO₂), nitrogen (N₂), hydrogen (H₂) and argon (Ar).

According to another aspect of the invention a plant for the processing of solid recovered fuel pellets to a product gas stream rich in hydrogen is proposed, comprising

- a torrefaction unit for torrefying the solid recovered fuel pellets to charred pellets;
- 15 - a second mill for milling the charred pellets to coarsely milled charred pellets;
- a third metal removal unit comprising an eddy current for removing metal residues from the coarsely milled charred pellets;
- a third mill for milling the coarsely milled charred pellets to finely milled charred pellets;
- 20 - a gasification unit comprising an entrained flow gasifier for gasifying the finely milled charred pellets to raw syngas;
- a CO shift unit for performing CO shift reactions to the raw syngas creating shifted syngas;
- a gas cleaning unit comprising adsorbing means for removing carbon dioxide
25 and hydrogen sulfide from the shifted syngas and a hydrogen separator for separating hydrogen from a purge gas generating a product gas stream rich in hydrogen.

According to an embodiment the plant further comprises a torrefaction gas processing unit for thermally cracking torrefaction gas generatable in the torrefaction unit.

According to an embodiment the hydrogen separator comprises a pressure swing adsorption system.

It should be noted that the individual features specified in the claims may be combined with one another in any desired technologically reasonable manner and form further embodiments of the invention. The specification, in particular taken together with the figures, explains the invention further and specifies particularly preferred embodiments of the invention. Particularly preferred variants of the invention and the technical field will now be explained in more detail with reference to the enclosed figures. It should be noted that the exemplary embodiment shown in the figures is not intended to restrict the invention. The figures are schematic and may not be to scale. The figures display:

Fig. 1 an example of a plant for conversing solid waste into a product gas stream comprising hydrogen;

Fig. 2 a visualization of a pelletizing facility;

Fig. 3 an example of a dryer used in the pelletizing facility;

Fig. 4 a torrefaction unit and a gasification unit;


Fig. 5 a torrefaction gas processing unit;

Fig. 6 a carbon monoxide (CO) shift unit; and

Fig. 7 a gas cleaning unit.

Fig. 1 displays schematically a pelletizing facility 100 in which solid recovered fuel pellets 117 manufactured in the pelletizing facility 100 are provided to a plant 1 for conversing solid waste into a gas comprising hydrogen, in particular into syngas comprising hydrogen and hydrogen. After preparing pellets from solid waste like municipal solid waste 103 and/or biomass in the pelletizing facility 100 the respective pellets 117 are transported to the plant 1 and are provided to a torrefaction unit 200 in which the pellets are oxidized substoichiometrically at temperatures of 250°C to 300°C. The torrefaction of the pellets results in charred pellets 201, which are gasified in a gasification unit 300. Another product of the torrefaction is torrefaction gas 202 which is provided

to a torrefaction gas processing unit 400 which is discussed in detail with reference to Fig. 5 below. The product of the torrefaction gas processing unit 400 is a torrefaction syngas 401 and of the gasification unit 300 is a raw syngas 301. The torrefaction syngas 401 and the raw syngas 301 comprise water steam, carbon monoxide and hydrogen. Both raw syngas 301 and torrefaction syngas 401 are introduced into a CO shift unit 500 in which carbon monoxide (CO) is reacting with water steam (H₂O) to carbon dioxide (CO₂) and hydrogen (H₂):



Shifted syngas 501 with increased hydrogen content compared to the syngases 301, 401 which is generated in the CO shift unit 500 and is transferred to a gas cleaning unit 600 which separates hydrogen from a purge gas 602 creating a product gas stream rich in hydrogen 601. The hydrogen content of the product gas stream rich in hydrogen 601 is at least 99.5 vol.-%. In the gas cleaning unit 600 carbon dioxide and hydrogen sulfide are separated from the remaining gas stream, creating a raw hydrogen stream which is fed to a pressure swing adsorption system which allows hydrogen to pass and absorbs all other molecules. By cyclic depressurizing while using multiple absorbers and purging with hydrogen. Purge gas is generated. Simultaneously, the product stream rich in hydrogen is produced with a hydrogen content of 99.5 vol.-% and more. The pelletizing facility 100 is preferably off-site, i.e. situated not in the same location than the plant 1 for conversing solid waste into a gas comprising hydrogen. The pelletizing facility 100 being off-site is advantageous, as it reduces the mass of the municipal solid waste, as usually about 30 to 35 wt.-% of water content of the municipal waste are evaporated. This reduces the mass to be transported significantly. Furthermore, the footprint of the chemical plants such as the plant 1 can be reduced as the pelletizing facility 100 allows a central production of solid recovered fuel pellets and the subsequent transport of these pellets to the chemical plant where needed.

According to Fig. 2 a pelletizing facility 100 includes a shredder 102. Solid waste 103, e.g. municipal solid waste (MSW) with a possible addendum of biomass, are provided to the shredder 102, generating shredded solid waste 104 which is conveyed by

a first metal removal unit 105 including a magnet to remove the iron residues 106 from the shredded solid waste 104. Thereafter, the shredded solid waste 104 is provided to a dryer 107 in which water 108 is removed from the shredded solid waste 104. The shredded solid waste 104 is then conveyed to a second metal removal unit 109 for
5 removing metal residues 110 from the shredded solid waste 104, the second metal removal unit 109 comprising a second magnet 139 for further removing iron metals and an eddy current to remove non-iron metals.

Thereafter, minerals as well as stainless steel are removed as further residues 111 in a density classifier 112. In the density classifier 112 high density residues like stain-
10 less steel particles, that can neither be removed with a magnet nor an eddy current, are removed based on the density differences between the further residues 111 and the remainder of the shredded solid waste 104. Same holds for minerals like glass or stone that are removed from the remainder of the shredded solid waste 104 by virtue of its density difference. Preferred examples for density classifiers 112 are e.g. air classifiers.

15 After removal of the further residues 111 the shredded solid waste 104 has been stripped from the iron metals (such as iron residues 106 and metal residues 110), the non-iron metals, stainless steel and minerals as further residues 111 like as well as moisture in the form of water 108. The remainder of the shredded solid waste 104 is basically identical to the solid waste 103 that has been input to the pelletizing facility
20 100. In particular, in the present pelletizing facility 100 it is not necessary to sort out e.g. fine fractions of the solid waste 103 or chlorine containing materials like e.g. Poly-vinyl chloride (PVC) or the like. This means the ratio of mass of the pre-cleaned material stream 113 which is present downstream of the first metal removal unit 105, the second metal removal unit 109, and the density classifier 112 to the mass of the solid
25 waste 103 input into the pelletizing facility 1 is larger than for known approaches.

The pre-cleaned material stream 113 is thereafter milled in a first mill 114, in particular to mean particle sizes of less than 25 mm to generate a milled material stream 115. Subsequently, the milled material stream 115 is introduced to a pellet press 116 to generate solid recovered fuel pellets 117.

Figure 3 displays an example of a dryer 107 used in a pelletizing facility 100 as in figure 1. The dryer 107 for drying shredded solid waste 104 comprises a kiln 118 for accommodating the shredded solid waste 104, a washing column 119 which also can be named a scrubber, a heat pump 120 and a radiator 121. Air is sucked into the dryer
5 107 through a dryer air inlet 122 which is usually fluidly connected with the atmosphere. The sucked in air can be conveyed to the radiator 121 via a vent which is not shown in figure 3. The dryer air inlet 122 is fluidly connected with a radiator air inlet 123 of the radiator 121 via a duct. The air conveyed into the radiator 121 is heated in the radiator 121 and exits the radiator 121 via a radiator air outlet 124. The heated air is
10 conveyed towards the kiln 118, wherein a kiln air inlet 125 is fluidly connected with the radiator air outlet 124 via a duct. The shredded solid waste 104 is arranged inside the kiln 118 and the air conveyed into the kiln 118 flows through the shredded solid waste 104 and exits the kiln 118 via a kiln air outlet 126. The temperature of the air entering the kiln 118 in a drying process is approximately 80°C, wherein the air exiting the kiln
15 118 exhibits a temperature of about 45°C. The relative humidity of the air exiting the kiln 118 is approximately 100 %.

The kiln 118 is in fluid communication with the washing column 119, wherein the kiln air outlet 126 is fluidly connected with a washing column air inlet 127. Inside the washing column 119 the air is brought into close contact with cold water. Thereby, the
20 moist and warm air is cooled down so that the humidity of the air is condensed out and latent heat is transferred into sensible heat of the water. This results into a heating of the water from approximately 18°C to approximately 25°C to 28°C and a cooling of the air from about 28°C to 32°C to approximately 22°C to 24°C. The cooled air exits the washing column 119 via a washing column air outlet 128 which is in fluid communication with a dryer air outlet 129.
25

The air exiting the washing column 119 also can be conveyed to the dryer air inlet 122 via a recirculation line 130, so that the washing column air outlet 128 is fluidly connected with the dryer air inlet 122. A corresponding arrangement results in a lower energy consumption of the device 100. The recirculation line 130 is not necessarily
30 included in the device 100 and can be left out.

With regard to the airflow the radiator 121 is positioned downstream of the dryer air inlet 122, the kiln 118 is positioned downstream of the radiator 121, the washing column 119 is positioned downstream of the kiln 118 and the dryer air outlet 129 is positioned downstream of the washing column 119.

5 The washing column 119 also comprises a washing column water outlet 131 which is fluidly connected with a first heat pump water inlet 132. A first heat pump water outlet 133 is fluidly connected with a washing column water inlet 134. Therefore, water is circulated between the washing column 119 and the heat pump 120. The water can be conveyed via a pump which is not shown in figure 3.

10 The water is heated in the washing column 119 via the air entering the washing column 119 via the washing column air inlet 127 and the heated water exits the washing column 119 via the washing column water outlet 131 and enters the heat pump 120 via the first heat pump inlet 132. The heat energy of the water entering the heat pump 120 then is transferred to another heat cycle which is realized between the heat
15 pump 120 and the radiator 121. The water entering the heat pump 120 exhibits a temperature of about 26°C to 28°C and the water exiting the heat pump 120 via the first heat pump outlet 133 exhibits a temperature of approximately 18°C.

20 The first heat pump outlet 133 is fluidly connected with a washing column water inlet 134. Therefore, the water cooled inside the heat pump 120 enters the washing column 119 via the washing column water inlet 134. Therefore, a heat cycle between the washing column 119 and the heat pump 120 is realized, wherein thermal energy of the water exiting the washing column 119 is transferred via the heat pump 120 to a second heat cycle between the heat pump 120 and the radiator 121.

25 A second heat pump outlet 135 is fluidly and therefore thermally connected with a radiator water inlet 136 and a radiator water outlet 137 is fluidly and therefore thermally connected with a second heat pump inlet 138. The water is thereby conveyed via pumps which are not shown in figure 3 between the heat pump 120 and the radiator 121. Consequently, a second heat cycle is realized between the heat pump 120 and the radiator 121.

Thermal energy from water exiting the washing column 119 is transferred via the heat pump 120 to the radiator 121 and to air flowing through the radiator 121 from the radiator air inlet 123 to the radiator air outlet 124.

The pelletizing facility 100 according to the present invention allows the manufacture of solid recovered fuel pellets from municipal solid waste without separating parts of the municipal solid waste before starting the pelletizing process. Thus, a higher amount of the municipal solid waste can actually be used to manufacture solid recovered fuel pellets. The pelletizing facility 100 as well as the method according to the invention can be used in particular to manufacture solid recovered fuel pellets that can be used in the production of hydrogen and/or carbon dioxide enriched syngas by a torrefaction of the solid recovered fuel pellets with a subsequent gas treatment.

Fig. 4 displays an example of a torrefaction unit 200 and a gasification unit 300. In the torrefaction unit 200 solid recovered fuel pellets 117 are provided to a furnace 203 which is in this embodiment a multiple hearth furnace. In this furnace 203 the torrefaction of the solid recovered fuel pellets 117 take place. The term torrefaction is understood as a thermochemical treatment of the solid recovered fuel pellets 117 at temperatures of 250°C to 320°C. It is carried out under atmospheric pressure and without adding further oxygen, e.g. without providing air. During the torrefaction process water contained in the solid recovered fuel pellets evaporates as do volatiles included in the solid recovered fuel pellets 117. Biopolymers included in the solid recovered fuel pellets 117 partly decompose under release of volatiles. The product of the torrefaction process are charred pellets 201 and torrefaction gas 202.

The torrefaction gas 202 is provided to the torrefaction gas processing unit 400 which is described below with reference to Fig. 5 The charred pellets 201 comprise charred plastic or organic parts and, possibly, metal inclusions as the metal parts of the solid recovered fuel pellets 117 are not charred in the torrefaction process. The charred pellets 201 are provided to a second mill 204 for coarse milling with particles sizes of 10 mm and less. Thereafter, in a third metal removal unit 205 which is based on an eddy current removal process metal residues 206 that have not been removed during the production of the solid recovered fuel pellets 117 are removed. Both iron and

non-iron residues are removed by the third metal removal unit 205. The remaining coarsely milled charred pellets 207 are moved to a third mill 208 in which a fine milling process of the coarsely milled charred pellets 207 to finely milled charred pellets 209 with a particle size of 500 μm [micrometers] and less is taking place

5 The finely milled charred pellets 209 are provided as feedstock 303 to the gasification unit 300 which comprises an entrained flow gasifier 302. Biomass 304, such as dried sludge, can be added to the finely milled charred pellets 209 after having been finely milled to a particle size in the same order of magnitude as the particle size of the finely milled charred pellets 209. The biomass 304 is milled in a respective fourth mill
10 305. The finely milled biomass 306 is then added to the feedstock 303 upstream of the entrained flow gasifier 302. Alternatively, but not shown in Fig. 4, the biomass 304 is milled together with charred pellets 201 and is, thus, introduced together with the charred pellets 201 into the second mill 204.

15 The feedstock 303 is provided to the entrained flow gasifier 302 together with an oxygen rich gas 307 having an oxygen content of at least 95 vol.-%, preferably at least 98 vol.-%, in particular 99.5 vol.-% and more. The gasification reactions take place in a dense cloud of very fine particles in co-current flow. The gasification takes place at temperatures of 2000°C and pressures of 40 bar.

20 The resulting intermediary product gas 308 is provided into a quench zone 309 in which the resulting intermediary product gas 308 is quenched with quench water 310 of a temperature of preferably 180°C to 220° C. Solids or melted solids solidify due to the quenching process and form slag 311 which can be removed to be used for civil construction. The generated raw syngas stream 312 is provided to a water washing cooling column 313 in which moisture included in the raw syngas 312 is condensing
25 due to the contact with water 314 having a lower temperature of 180°C to 200°C than the raw syngas 312 having a temperature of around 214°C. The cooled and washed raw syngas 301 is provided to the CO shift unit 500. The excess bleed water 315 is provided to a slurry stripper (not shown) for removing gases from the excess bleed water 315. Make up water 316 is provided from the low temperature heat recovery unit
30 524 of the CO shift unit 500 described below.

Fig. 5 displays the torrefaction gas processing unit 400. Torrefaction gas 202 produced in the torrefaction unit 200 is introduced into a burning chamber 402. Furthermore, a fuel gas 403 and an oxygen rich gas stream 404 are introduced into the burning chamber 402. As the fuel gas 403 a natural gas and/or site fuel gas is used. A fuel gas comprises at least one of methane, ethane, nitrogen, and hydrogen. So called on-site fuel gas is e.g. generated in steam crackers. The oxygen rich gas stream 404 comprises at least 95 vol.-% [Volume-%] oxygen, preferably at least 98 vol.-%, in particular 99.5 vol.-% and more. In particular, if the gasification unit 300 is using a parallel entrained flow gasification pure oxygen is readily available, i.e. the oxygen rich gas stream 307 used in the gasification unit 300 can be provided from the same source as the oxygen rich gas stream 404. The burning chamber 402 has a first inlet 436 for introducing the oxygen rich gas stream 404, a second inlet 437 for introducing the fuel gas, and a third inlet 438 for introducing the torrefaction gas 202. The resulting raw syngas 301 is provided to the CO shift unit 500.

In the burning chamber 402 a substoichiometric oxidization takes place by which larger hydrocarbon molecules which originate from the torrefaction gases 202 and/or the fuel gas 403 are thermally cracked and transformed into a syngas 407 comprising carbon monoxide (CO), carbon dioxide (CO₂), hydrogen (H₂), and water (H₂O). Due to the high moisture content of typically at least 50 vol.-% of the torrefaction gases 202 the generation of elementary carbon and, thus, soot is suppressed.

The temperature in the burning chamber 402 is in the range of 1000°C to 1200°C. After passing a burning chamber exit 405 the syngas 407 is quenched with recycled syngas 406 acting as quench gas to a temperature of 730°C to 770°C, preferably to a temperature of 740°C to 760°C, in particular of about 750°C. The syngas 407 is introduced into a mixing chamber 408 in which the quenching process and the accompanying mixing with the recycled syngas 406 is taking place resulting in a quenched syngas 409 which is cooling down in the mixing chamber 408. The quenching is performed in a quench zone 439 having inlets 440 for the recycled syngas 406. The effect of the quenching process, i.e. of the abrupt reduction of temperature due to the introduction of the cooler recycled syngas 406 is that any solids or melted solids being

present in the syngas 407 are solidified. These solids can be introduced together with the torrefaction gas 202. Both the burning chamber 202 and the mixing chamber 408 are internally insulated and uncooled.

Downstream of the mixing chamber 408 the quenched syngas 409 is introduced
5 into a heat recovery system 410 in which thermal energy or heat energy of the quenched syngas 409 is transferred to a thermal carrier 411, preferably a thermal oil, in a first heat exchanger 441. Downstream of the energy transfer to the thermal carrier 411 further thermal energy is transferred to boiler feed water 412 in a second heat exchanger 442 producing high-pressure steam 413 at least a part of which is transferred
10 via a fourth heat exchanger 414 to heat the recycled syngas 406, preferably to a temperature of more than 200°C, in particular to about 225°C. In the heat recovery system 410 in a superheater 443 downstream the second heat exchange exchanger 441 with the boiler feed water 412 further thermal energy from the quenched syngas 409 is transferred to a low-pressure steam 415 to superheat the same generating superheat-
15 ed low-pressure steam 416. The thermal carrier is heated e.g. from a temperature of 300°C to a temperature of 400°C and can be used, e.g. for an indirect heating of the torrefaction unit 200. The high-pressure steam 413 has e.g. a pressure of 140 bar and a temperature of 350°C when leaving the heat recovery system 410. The superheated low-pressure steam has a temperature of about 275°C when leaving the heat recovery
20 system 410 and is preferably used in the torrefaction process in the torrefaction unit 200. The quenched syngas 409 leaves the heat recovery system 410 with a temperature of about 170°C and more to avoid the formation of ammonium chloride (NH_4Cl) which causes corrosion and/or fouling. To ensure that the temperature of about 170°C is not undershot the boiler feed water 412 is introduced into the heat recovery system
25 410 of 140°C and more.

Downstream of the heat recovery system 410 the quenched syngas 409 is introduced into a wet scrubbing system 417 to remove solids and halogens (mainly chlorides). The wet scrubbing system 417 is a common wet scrubbing column. Used washing water 418 is bled from a sump 419 of the wet scrubbing system 417. The used
30 washing water 418 is transferred to a wastewater treatment facility (not shown) to be


recycled. A cleaned syngas 420 is exiting the wet scrubbing system 417 a head 421 of the wet scrubbing system 417. A first part of the cleaned syngas 420 is used as the recycled syngas 406 and is as described above reheated and used in the quenching of the syngas 407. The use of the cleaned syngas 420 as the recycled syngas 406 reduces the concentrations of pollutants (like, e.g. solids, halogens, in particular chlorides,) in the quenched syngas 409 and avoids damages, in particular corrosion, of the heat exchange surfaces in the heat recovery system, in particular a corrosion of the surfaces used to superheat the low-pressure steam 415 to the superheated low-pressure steam 416 is avoided. Simultaneously the high moisture content of 60vol.-% and more increases the heat capacity of the recycled syngas 406 and, consequently, the cooling efficiency during the quenching process. The recycled syngas 406 is compressed by a compressor 423.

A second – i.e. the remaining – part 424 of the cleaned syngas 420 is introduced into a two stage water washing cooling column 422. Due to the close contact with the colder water in the column 422 the moisture in the syngas 424 is condensing. The respective condensing heat warms the washing water in the column 422. Washing water 426 from a sump 425 is provided to a heat pump 427 for cooling e.g. from a temperature of about 85°C down to a temperature of 75°C. In the heat pump 427 low pressure steam is produced which is preferably used in the torrefaction unit 200 for process control. Most of the washing water 426 is introduced centrally in the column 422 being distributed both in a first stage 428 and a second stage 429 of the column 422. A smaller part of the washing water 426 is further cooled by an air cooler 430, preferably to temperatures of about 25°C resulting in a temperature of the syngas 424 to a temperature of about 30°C when leaving the column 422. The cooling of the syngas 422 removes about 60% of the mass as water. The excess washing water 431 is partly used as make up water 432 for the wet scrubbing system 417. Excess washing water 431 can be guided as bleed water 433 to a stripper system (not shown) in which gases are stripped from the bleed water 433, in particular ammonia (NH₃), carbon dioxide (CO₂) and hydrogen sulfide (H₂S) are stripped from the bleed water 433.

A syngas conveying means 434, preferably a fan or a blower, is used to convey torrefaction syngas 401 exiting the column 422 to the CO shift unit 500 (see Fig. 1) and/or to a flare 435. The syngas conveying means 434 creates an underpressure which pulls the quenched syngas 406 through the heat recovery system 410.

- 5 The torrefaction gas processing unit 400 allows the chemical recycling of torrefaction gas 202 produced by the torrefaction e.g. from solid recovered fuel (solid recovered fuel) pellets 117 without the need to burn the torrefaction gas 202.

Fig. 6 displays schematically a carbon monoxide (CO) shift unit 500 included in the plant 1. In a CO shift unit 500, a carbon monoxide (CO) shift reaction takes place in
10 which carbon monoxide (CO) reacts with water (H₂O) to form carbon dioxide (CO₂) and hydrogen (H₂):



- The reaction is in chemical equilibrium which can be influenced either in direction of the educts or the products in a usual way e.g. by use of the respective temperature
15 and the use and concentration of a specific catalyst. As the reaction is endothermic the water is usually provided as water steam. To shift the chemical equilibrium to the product side to increase the production of hydrogen a molar steam to carbon monoxide ratio of about 2.3 to 2.7, in particular about 2.5, has been found to be advantageous. The steam is provided preferably at a pressure which is above the pressure at
20 which the shift reaction is taking place which is preferably about 40 bar. If the molar steam to carbon monoxide ratio of 2.5 is used a surplus of 1.5 moles steam for every mole carbon dioxide remains in the reactor. This results in large amounts of water in the product gas of the CO shift reaction. When this product gas is cooled this leads to a considerable amount of condensing and, thus, so large amounts of low level heat in
25 the cooling train, while the product gas is cooled to ambient temperature. The majority of this energy is usually discarded which results in a low energy efficiency.

The raw syngas 301 generated by the gasification unit 300 is introduced into a high-pressure scrubbing unit 502. The high-pressure scrubbing unit 502 is a conventional wet scrubber unit in which e.g. higher hydrocarbons are removed from the raw

syngas 301. The high-pressure scrubbing unit 502 is fed with feed water 503 which is the condensed water 508 from a low temperature heat recovery which will be described later on. Water 505 which is collected in a sump 504 of the high-pressure scrubbing unit 502 is conveyed by conveying means 506 to a bleed water conduit 507. Excess condensed water 508 which is not needed as feed water 503 is conveyed to the bleed water conduit 507 as well. Cleaned syngas 509 generated in the high-pressure scrubbing unit 502 is provided downstream of the high-pressure scrubbing unit 502 to a first heat exchanger 518. The term conveying means within this document is understood as a pump and/or a compressor. Simultaneously to the cleaning of the raw syngas 301 in the high-pressure scrubbing unit 502 the moisture of the cleaned syngas 509 can be controlled.

The torrefaction syngas 401 being generated in the torrefaction gas processing unit 400 is conveyed to a saturation column 510 via a conveying means 511. By the conveying means 511 the torrefaction syngas 401 is compressed, preferably to a pressure of 40 bar. The conveying means 511 can comprise several compressors with intercoolers which provide for a multistage intercooled compression of the torrefaction syngas 401. Likewise, the purge gas 602 from the gas cleaning unit 600 is conveyed via a conveying means 512 to the saturation column 510 as well. By the conveying means 512 the purge gas 602 is compressed, preferably to a pressure of 40 bar. The conveying means 512 can comprise several compressors with intercoolers which provide for a multistage intercooled compression of the purge gas 602. The saturation column 510 is a conventional wet scrubber which is provided with process water 513 from a low temperature heat recovery unit 524 being described later on via conveying means 514. The water 515 collected in a sump 516 of the saturation column 510 is used as process water in a low temperature heat recovery unit 524 described below. By the saturation column 510 the torrefaction syngas 401 and the purge gas 602 are mixed and, simultaneously, moisture is added to the resulting saturation column product gas 517. Depending on the parameters of the operation of the saturation column, i.e. in particular the water flow and the temperature of the water, the moisture of the saturation column product gas 517 can be controlled.

The saturation column product gas 517 is provided together with the cleaned syngas 509 to a first heat exchanger 518. In the first heat exchanger 518 energy is transferred from a high temperature CO shift reactor offgas 519 to the cleaned syngas 509 and the saturation column product gas 517 which are combined downstream of the first heat exchanger 519 to a combined syngas stream 520. By the heat exchange in the first heat exchanger 518 the respective high temperature CO shift reactor offgas 519 is cooled while the cleaned syngas 509 and the purified gas stream 517 are heated. Preferably, the saturation column 510 is driven in such a way that the combined syngas stream 520 has a molar ratio of water steam to carbon monoxide of between 2.0 and 3.0, preferably between 2.4 and 2.6, in particular of about 2.5.

The combined syngas stream 520 is provided downstream of the first heat exchanger 518 to a high temperature CO shift reactor 521 in which the above-described shift reaction is taking place. The high temperature CO shift reactor offgas 519 has a reduced water/steam and carbon monoxide content and an increased hydrogen (H₂) content compared to the combined syngas stream 520. The high temperature CO shift reactor offgas 519 is - as will be described in the following - guided through several heat exchangers to reduce its temperature including the first heat exchanger 518 to a low temperature CO shift reactor 522 in which the CO shift reaction as described above is taking place. A low temperature CO shift reactor offgas 523 is increased in its hydrogen (H₂) content compared to the high temperature CO shift reactor offgas 519 that is entering the low temperature CO shift reactor 522.

The low temperature CO shift reactor offgas 523 is guided downstream of the low temperature CO shift reactor 522 through a low temperature heat recovery unit 524. In this low temperature heat recovery unit 524 the heat content of the low temperature CO shift reactor offgas 523 is used to increase the temperature of several water streams. After entering the low temperature heat recovery unit 524 the low temperature CO shift reactor offgas 523 is subsequently guided through a second heat exchanger 525, a third heat exchanger 526, a fourth heat exchanger 527, a fifth heat exchanger 528 and a sixth heat exchanger 529. While passing these heat exchangers 524, 525, 526, 527, 528, 529 the temperature of the low temperature CO shift reactor

offgas 523 is reduced steadily before leaving the low temperature heat recovery unit 524 as a syngas stream 530 and is passed, optionally and if necessary, through an air cooler 531. Thereafter, the syngas stream 530 is provided to the gas cleaning unit 600 as discussed above.

- 5 First, in the second heat exchanger 525 the heat content of the syngas stream 530 is used to heat feed water 508 to be used in the gasification unit 300. E.g. it is thus possible to heat this water 508 from 158°C to 205°C. Second, in the third heat exchanger 526 water is heated that can e.g. be used to generate high pressure steam. The water is e.g. heated from typically 155 to 200°C. Third, in the fourth heat exchanger 527 process water 513 is heated, typically from 135 to 158°C, which is used in the saturation column 510. Further use of this water as feed water 508 is possible, in particular after passing the second heat exchanger 525. In the fourth heat exchanger 527 the low temperature CO shift reactor offgas 523 is cooled below its dew point, thus, large amounts of condensing heat are released and used for the respective heat transfer.
- 10
15 Fourth, in the fifth heat exchanger 528 boiler feed water 536 is heated, typically from 35°C to 155°C, which is preferably used to prepare high pressure steam. Fifth, in the sixth heat exchanger 529 water is heated from typically 25°C to 135°C for use in the gasification of the charred pellets 201 in the gasification unit 300.

- The feed water 508 for the gasification unit 300 is at least a part of the water 515 collected in the sump 519 of the saturation column 510 as described above. The water 515 collected in the sump 516 of the saturation column 510 is entering the fourth heat exchanger 527. Water 521 from a waste water treatment unit (not shown) can be mixed with the water 515 after having passed the sixth heat exchanger 529. Downstream of the second heat exchanger 527 the heated fourth heat exchanger water offstream 533 is in part used as process water from low temperature heat recovery 513 in the saturation column 510 and in part it is guided through the second heat exchanger 525 to be used downstream of the second heat exchanger 525 partly as condensed water 508 to be used partly as feed water 503 in the high-pressure scrubbing unit 502 and partly as process water in the torrefaction unit 200. A further part of water downstream of the sixth heat exchanger 529 is used as condensate 534 provided e.g. to a water stripper.
- 20
25
30

Other water like e.g. external high pressure boiler feed water 535 generated for applications outside the plant 1 is guided through the fifth heat exchanger 528 to be partly used as boiler feed water 536 e.g. in the gasification unit 300 and/or for the generation of low pressure steam and/or in the torrefaction unit 200. Another part of the boiler
5 feed water 535 is guided downstream the fifth heat exchanger 528 through the second heat exchanger 526. Thereafter, it is passed through a seventh heat exchanger 537.

The CO shift unit 500 as part of the plant 1 for conversing solid waste into a product gas stream comprising hydrogen allows an energy efficient use of the low temperature heat energy in the low temperature heat recovery unit 524 to heat process water
10 streams used in the plant 1.

Fig. 7 displays the gas cleaning unit 600 in greater detail. The shifted syngas 501, which is the output of the CO shift unit 500, is introduced into the gas cleaning unit 600 and passes, subsequently, hydrogen sulfide absorption means 603 and carbon
15 dioxide absorption means 604. Thereafter, it passes the pressure swing adsorption means 605 wherein, by pressure swing adsorption, the product gas stream 601 rich in hydrogen, preferably pure hydrogen, with a hydrogen content of at least 99.5 vol.-% is generated. Frequently, the single adsorbers of the pressure swing adsorption means 605 are purged with hydrogen, generating the purge gas 602

20 The hydrogen sulfide collected in the hydrogen sulfide adsorption means 603 is used to generate sulphur 606 by a Claus process. The carbon dioxide 607 which is absorbed in the carbon dioxide absorption means 603 can be extracted therefrom and used in other processes .

The method and plant 1 for conversing solid recovered fuel pellets 117 made from
25 municipal solid waste 103 allow the transformation of the municipal solid waste 103 into hydrogen with a high yield instead of landfilling or incinerating the municipal solid waste 103. The hydrogen rich product gas stream 601 can be used as feedstock for chemical reactions or for storing energy in a releasable manner.

Reference numerals

1	plant for conversing solid waste into a gas comprising hydrogen
100	pelletizing facility
102	shredder
5 103	solid waste
104	shredded solid waste
105	first metal removal unit
106	iron residues
107	dryer
10 108	water
109	second metal removal unit
110	metal residues
111	further residues
112	density classifier
15 113	pre-cleaned material stream
114	first mill
115	milled material stream
116	pellet press
117	solid recovered fuel pellet
20 118	kiln
119	washing column
120	heat pump
121	radiator
122	dryer air inlet
25 123	radiator air inlet
124	radiator air outlet
125	kiln air inlet
126	kiln air outlet
127	washing column air inlet
30 128	washing column air outlet
129	dryer air outlet

	130	recirculation line
	131	washing column water outlet
	132	first heat pump inlet
	133	first heat pump outlet
5	134	washing column water inlet
	135	second heat pump outlet
	136	radiator water inlet
	137	radiator water outlet
	138	second heat pump inlet
10	139	second magnet
	200	torrefaction unit
	201	charred pellets
	202	torrefaction gas
	203	furnace
15	204	second mill
	205	third metal removal unit
	206	metal residues
	207	coarsely milled charred pellets
	208	third mill
20	209	finely milled charred pellets
	300	gasification unit
	301	raw syngas
	302	entrained flow gasifier
	303	feedstock
25	304	biomass
	305	fourth mill
	306	finely milled biomass
	307	oxygen rich gas stream
	308	intermediary product gas
30	309	quench zone
	310	quench water

	311	slag
	312	raw syngas
	313	water washing cooling column
	314	water
5	315	excess bleed water
	316	make up water
	400	torrefaction gas processing unit
	401	syngas
	402	burning chamber
10	403	fuel gas
	404	oxygen rich gas stream
	405	burning chamber exit
	406	recycled syngas
	407	syngas
15	408	mixing chamber
	409	quenched syngas
	410	heat recovery system
	411	thermal carrier
	412	boiler feed water
20	413	high-pressure steam
	414	fourth heat exchanger
	415	low-pressure steam
	416	superheated low-pressure steam
	417	wet scrubbing system
25	418	used washing water
	419	sump
	420	cleaned syngas
	421	head
	422	two stage water washing cooling column
30	423	compressor
	424	remaining part of the cleaned syngas

	425	sump
	426	washing water
	427	heat pump
	428	first stage
5	429	second stage
	430	air cooler
	431	excess washing water
	432	make up water
	433	bleed water
10	434	syngas conveying means
	435	flare
	436	first inlet
	437	second inlet
	438	third inlet
15	439	quench zone
	440	quench zone inlet
	441	first heat exchanger
	442	second heat exchanger
	443	superheater
20	500	CO shift unit
	501	shifted syngas
	502	high- pressure scrubbing unit
	503	feed water
	504	sump
25	505	water
	506	conveying means
	507	bleed water conduit
	508	condensed water
	509	cleaned syngas
30	510	saturation column
	511	conveying means

- 512 conveying means
- 513 process water from low temperature heat recovery
- 514 conveying means
- 515 water
- 5 516 sump
- 517 saturation column product gas
- 518 first heat exchanger
- 519 high temperature CO shift reactor offgas
- 520 combined high temperature syngas stream
- 10 521 high temperature CO shift reactor
- 522 low temperature CO shift reactor
- 523 low temperature CO shift reactor offgas
- 524 low temperature heat recovery unit
- 525 second heat exchanger
- 15 526 third heat exchanger
- 527 fourth heat exchanger
- 528 fifth heat exchanger
- 529 sixth heat exchanger
- 530 syngas stream
- 20 531 air cooler
- 532 waste water treatment unit
- 533 fourth heat exchanger water offstream
- 534 condensate
- 535 high pressure boiler feed water
- 25 536 boiler feed water
- 537 seventh heat exchanger
- 538 saturation column product gas
- 600 gas cleaning unit
- 601 product gas rich in hydrogen
- 30 602 purge gas
- 603 hydrogen sulfide absorption means

604 carbon dioxide absorption means
605 pressure swing adsorption means
606 sulphur
607 carbon dioxide

5

Claims

1. Method for processing solid recovered fuel pellets (117), comprising the following steps:
 - a) torrefaction of the pellets (117) at a torrefaction temperature of 250 to 300°C
5 generating charred pellets (201) and torrefaction gas (202);
 - b) milling the charred pellets (201) in a first milling step to coarsely milled charred pellets (207);
 - c) removing metal residues (206) from the coarsely milled charred pellets (207);
 - d) milling the coarsely charred pellets (207) to finely milled charred pellets (209);
10 e) gasifying the finely milled charred pellets (209) to raw syngas (301) in an entrained flow gasifying process;
 - f) performing CO shift reactions to the raw syngas (301) creating shifted syngas (501);
 - g) removing carbon dioxide and hydrogen sulfide from the shifted syngas (501)
15 creating a syngas; and
 - h) generating a product gas stream (601) rich in hydrogen by purifying the syngas.
2. Method according to claim 1, wherein the torrefaction gas (202) generated in step a) is thermally cracked for the generation of a torrefaction syngas (401), said torrefaction syngas (401) being mixed with the raw syngas (301) generated in step e) before step f).
3. Method according to one of the preceding claims, wherein in step b) the charred pellets (201) are milled to a particle size of 10 mm and less.
4. Method according to one of the preceding claims, wherein in step c) the metal
25 residues (206) are removed using an eddy current technology.
5. Method according to one of the preceding claims, wherein in step d) the coarsely milled charred pellets (207) are milled to a particle size of 500 μm [micrometer] and less.

6. Method according to one of the preceding claims, wherein in step h) carbon dioxide (CO₂) and hydrogen sulfide (H₂S) are removed from the syngas by adsorption.

7. Method according to one of the preceding claims, wherein in step g) hydrogen is separated from the syngas using a pressure swing adsorption system creating
5 the product gas stream rich in hydrogen (601) and a purge gas (602).

8. Method according to claim 7, wherein at least a part of the purge gas (602) is provided to the CO shift reaction in step e).

9. Method according to claim 7 or 8, wherein a part of the purge gas (602) is used as fuel gas.

10. A plant (1) for the processing of solid recovered fuel pellets (117) to a product
10 gas stream (601) rich in hydrogen, comprising

- a torrefaction unit (200) for torrefying the solid recovered fuel pellets (117) to charred pellets (201);
- a second mill (204) for milling the charred pellets (201) to coarsely milled charred
15 pellets (207);
- a third metal removal unit (205) comprising an eddy current for removing metal residues (206) from the coarsely milled charred pellets (207);
- a third mill (208) for milling the coarsely milled charred pellets (207) to finely milled charred pellets (209);
- 20 - a gasification unit (300) comprising an entrained flow gasifier (302) for gasifying the finely milled charred pellets (209) to raw syngas (301);
- a CO shift unit (500) for performing CO shift reactions to the raw syngas (301) creating shifted syngas (501);
- a gas cleaning unit (600) comprising adsorbing means (603, 604) for removing
25 carbon dioxide and hydrogen sulfide from the shifted syngas (501) and a hydrogen separator for separating hydrogen from a purge gas (602) generating a product gas stream (601) rich in hydrogen.

11. Plant according to claim 10, further comprising a torrefaction gas processing unit (400) for thermally cracking torrefaction gas (202) generatable in the torrefaction unit (200).

12. Plant according to claim 10 or 11, wherein the hydrogen separator comprises
5 pressure swing adsorption means (605).