

REPLACED SHEETS	SG
☒ Description : paged ...1... to paged ...21...	
☒ Claim(s) : paged ...22... to paged ...7...	
☒ Drawing(s) : paged ...46... to paged ...47...	
☒ Abstract : paged ...23... to paged ...3...	
DATE OF RECEIPT	

- 1 -

TAPE CASSETTE

The present invention relates to a tape cassette such
5 as a magnetic tape cassette, a cleaning tape cassette or
a video tape cassette.

In a conventional tape cassette, a magnetic tape is
guided in a tape traveling path between the head house
and the hubs in the cassette casing so that the magnetic
10 tape is wound around or rewound from the hubs. The hubs
are supported for rotation by circular peripheral wall
portions for fitting the hubs, which are formed around
axial holes formed in the casing in order to receive the
shaft portions of the hub. Various auxiliary elements
15 are installed in the head house, and therefore,
reinforcing ribs or partition walls are formed in the
head house, or the wall thickness of the casing is
increased, or material having service durability is used
for the casing so that it has a sufficient strength and
20 durability.

This Sheet Has Been Replaced



In the conventional tape cassette, the thickness of the outer peripheral wall of the casing is made thicker than the thickness of the flat surface wall portion of the casing in order to increase the impact resistance.

5 However, the conventional tape cassette has disadvantages as follows. There is a large scatter in the wall thickness at many portions; molding properties are not good and there are strains and deformation in the molded casing. Further, since the head house area at the front

10 portion of the casing has many ribs and partition walls, there is concentration of resin when the resin is injected to form the casing, and they are often caused recesses in the molded product. When there is a change in the wall thickness of the casing, a stream of molten

15 resin is changed whereby strains remain at the portion of the resin stream change and a thermal deformation is apt to occur. In particular, when a casing having a thin wall thickness is required, such undesirable tendency is increased, and there are conspicuous recesses on the

20 surface of the casing whereby the appearance of the casing is poor.

It is an object of the present invention to provide a tape cassette providing good molding properties and minimizing a strain or deformation.

25 It is an object of the present invention to provide a tape cassette which improves reliability on traveling of a tape and easy assembling by providing suitable tape



guide members; minimizes occurrences of recesses even when the wall thickness of the casing is small while the strength of the casing can be increased, and easy processing and accurate dimensions can be obtained, and
5 which can be used commonly for a fixed guide pole type and a guide roller type.

It is an object of the present invention to provide a tape cassette having a good appearance, a light weight and manufactured at a low cost, which minimizes a scatter
10 in a torque for the hubs and reduces remarkably the torque by reducing the contacting area of the hubs to the casing by suitably arranging the hubs; which improves reliability on magnetic tape traveling and easy assembling, and which minimizes occurrences of recesses
15 while increasing the strength even when the wall thickness of the cassette casing is small.

It is an object of the present invention to provide a tape cassette having a good appearance and providing good processability, which improves reliability on magnetic
20 tape traveling and easy assembling by providing a suitable connecting construction for the upper and lower half casings, and which determines accurate position for tape cassette elements and increases the strength of the connection of the upper and lower half casings even when
25 the wall thickness of the tape cassette is small.

According to the first invention, there is provided a tape cassette comprising a cassette casing composed of an



upper half casing and a lower half casing, a pair of hubs around which a tape is wound and which are rotatably fitted into circular peripheral wall portions formed in the cassette casing, and tape guide members formed in the cassette casing at positions through which the tape wound around the hubs is traveled, said tape cassette being characterized in that the thickness of the flat surface wall portion and the thickness of the outer peripheral wall portion of the upper and lower half casings are respectively uniform.

According to the second invention, there is provided a tape cassette comprising a cassette casing composed of an upper half casing and a lower half casing, a pair of hubs around which a tape is wound and which are rotatably held in the cassette casing, and tape guide members formed in the cassette casing at positions through which the tape wound around the hubs is traveled, the tape cassette being characterized in that the tape guide members are tape guide poles having a substantially U-shape in cross section which are formed integrally with either of the upper and lower casings wherein the circular arc surface of the U-shaped tape guide poles is a tape contacting surface.

According to the third invention, there is provided a tape cassette comprising a cassette casing composed of an upper half casing and a lower half casing, a pair of hubs around which a tape is wound and which are rotatably



fitted into circular peripheral wall portions ~~formed in~~
cassette casing, and tape guide members formed in ~~the~~
cassette casing at positions through which the ~~tape~~ ~~wound~~
around the hubs is traveled, said tape cassette ~~being~~
5 characterized in that the circular peripheral wall
portions for fitting the hubs are projected around ~~axial~~
holes of the hubs, and a plurality of parallel ~~linear~~
ribs are formed in the vicinity of the circular
peripheral wall portions for fitting the hubs in a
10 surface area including the outer peripheral wall ~~portions~~
in the upper and lower half casings.

According to the fourth invention, there is ~~provided~~
a tape cassette comprising a cassette casing composed of
an upper half casing and a lower half casing, a ~~pair of~~
15 hubs around which a tape is wound and which are rotatably
held in the cassette casing, tape guide members formed
in the cassette casing at positions through which the
tape wound around the hubs is traveled, and connecting
cylindrical bodies, said tape cassette being
20 characterized in that a rib for melt-bonding is formed in
the abutting surface of each of the connecting
cylindrical bodies of either the upper half casing or the
lower half, and a position-determining boss is formed in
the abutting surface of each of the connecting
25 cylindrical bodies of the other.

In drawings:

Figure 1 is a plane view showing an embodiment of the



tape cassette of the present invention wherein the upper and lower half casings are shown in a separated state to show the inside of them;

Figure 2 is an enlarged perspective view partly omitted of the lower half casing shown in Figure 1;

Figure 3 is a perspective view in a state of use of the embodiment shown in Figure 1;

Figure 4 is an enlarged longitudinal cross-sectional view of a corner portion of the lower half casing shown in Figure 1;

Figure 5 is an enlarged perspective view of an embodiment of a corner portion of the lower casing according to the present invention;

Figure 6 is a plane view of another embodiment of the present invention wherein the upper and lower half casings are shown in a separate state to show the inside of them;

Figure 7 is a perspective view in an exploded state of the tape cassette shown in Figure 6;

Figure 8 is an enlarged cross-sectional view taken along a line I-I in Figure 6;

Figure 9 is an enlarged perspective view of an embodiment of the lower half casing of the present invention;

Figure 10 is a plane view showing another embodiment of the tape cassette of the present invention wherein the upper and lower half casings are shown in a separate



state to show the inside of them;

Figure 11 is a plane view showing another embodiment of the tape cassette of the present invention wherein the upper and lower half casings are shown in a separated
5 state to show the inside of them;

Figure 12 is an enlarged longitudinal cross-sectional view taken along a line I-I in Figure 11;

Figure 13 is an enlarged longitudinal cross-sectional view partly omitted of a corner portion of the upper and
10 lower half casings shown in Figure 11;

Figure 14 is a plane view showing another embodiment of the tape cassette of the present invention wherein the upper and lower half casings are shown in a separated state to show the inside of them;

15 Figure 15 is an enlarged perspective view in a separated state of a corner portion of the upper and lower half casings shown in Figure 14;

Figure 16 is an enlarged longitudinal cross-sectional view taken along a line I-I in Figure 15;

20 Figure 17 is an enlarged longitudinal cross-sectional view of the upper and lower half casings in a state of connection shown in Figure 16;

Figure 18 is a plane view of an embodiment of the lower half casing of the present invention; and

25 Figure 19 is a perspective view of the lower half casing in use shown in Figure 18.

Preferred embodiments of the tape cassette according



to the present invention will be described with reference to the drawings.

Figure 1 through 4 shows a first embodiment of the tape cassette of the present invention. A cassette casing comprises an upper half casing 1 and a lower half casing 2. Inside the cassette casing, a pair of hubs 3 around which a tape 4 such as a magnetic tape is wound are rotatably supported by circular peripheral wall portions 8 for fitting the hubs 3, which are formed integrally with the upper and lower half casings 1, 2. As tape guide members located in the tape traveling path between the hubs 3, 3, provided are tape guide poles 5 having a substantially U-shape in cross section. The tape guide poles 5 are formed integrally with the upper half casing 1 or the lower half casing 2 so that the circular arc surface of the substantially U-shape comes in contact with the tape traveling. The circular peripheral wall portions 8 for supporting the hubs 3 are projected from the inner surface of the upper and lower half casings 1, 2 at positions around axial holes 10 for receiving the shaft portion of the hubs. A plurality of linear ribs 9, 9₁ are formed in a parallel relation so as to extend in an area including the circular peripheral wall portions 8, 8 and in the vicinity of them. In this embodiment, the thickness of the flat surface wall portion 1₁, 2₁ of the upper and lower half casings 1, 2 is determined in a range of $t_1 = 0.8-1.2$ mm, and the



thickness of the outer peripheral wall portions $1_2, 2_2$ is determined in a range of $t_2 = 0.8-1.2$ mm. The wall thickness of each of the upper and lower half casings $1, 2$ and the outer peripheral walls $1_2, 2_2$ is substantially uniform. A scatter in the wall thickness of each of the flat surface walls $1_1, 2_1$ and the outer peripheral walls $1_2, 2_2$ should be 20% or lower.

Reinforcing ribs formed projecting from the inner surface of the upper and lower half casings have a height sufficient to mount thereon the hubs 3, and include a center rib 9 connected to the circular peripheral walls 8 for fitting the hubs and arranged on a linear line connecting the center of each of the axial holes 10, 10 for receiving the shaft portion of the hubs, and side ribs $9_1, 9_1$ arranged with a distance at both sides of the center rib 9. The circular peripheral walls 8 are so constructed to reduce the surface area of contact of the hubs 3 to the cassette casing to thereby reduce a torque.

In addition to the reinforcing ribs 9, 9_1 , the provision of reinforcing ribs 9_2 at positions near a head house 14 and the opposite side of it are effective to reduce the wall thickness of the cassette casing. When the width of each of the ribs 9, $9_1, 9_2$ is made thinner than the wall thickness of the upper and lower half casings, a preferred stream of resin is obtained at the time of molding, and accordingly, a tape cassette having a less residual strain, accurate dimensions and excellent



heat resistance can be obtained.

It is preferable to locate the tape guide members 5b near each support pin 6 for supporting a roller for guiding the tape, which is formed in either the upper or the lower half casing. Preferably, some of the tape guide members 5 are provided to be removable. It is further preferable that the tape guide members 5 are located at both corner portions 7, 7 in either half casings so that a plurality of the tape guide members 5 are used and they are disposed at both sides of a plurality of supporting pins 6.

It is preferable that the wall thickness of the upper and lower half casings is thin as possible while a sufficient strength should be maintained. For this purpose, a partition walls 9₃ is preferably formed together with connecting bosses 11, 17 in addition to the reinforcing ribs 9, 9₁, 9₂ formed around the circular peripheral walls 8, 8 for fitting the hubs 3, at each of the corner portions 7.

Each of the upper and lower half casings 1, 2 is provided with windows 12, 12 between the circular peripheral walls 8, 8 for fitting the hubs and between the linear ribs 9, 9₁ and along these ribs, whereby an amount of the tape around the hubs is visible. In this case, the cassette casing body may not be transparent and a transparent window may not be provided. Further, a tape cassette having a unique design is provided.

This Sheet Has Been Replaced



Finger touch portions 13 are provided at both side surfaces of the upper and lower half casings 1, 2 at positions near the head house 14.

The head house 14 is a section for recording and reproducing a tape and comprises an insertion hole, supporting walls and an opening. In Figure 1, reference numerals 15 designate pin bearing portions.

In the above-mentioned first embodiment of the tape cassette having the construction described above, the thickness of the flat surface wall portions and the outer peripheral wall portions of the upper and lower half casings are respectively formed to be substantially uniform, whereby a scatter in the wall thickness of each of the wall portions can be small, molding property is remarkably improved to reduce occurrence of strains or deformation, accuracy in dimensions, and reliability on heat resistance can be increased. Further, a tape cassette having thin upper and lower half casings, a low manufacturing cost and suitable for a large-scale production can be provided.

Figures 4 and 5 show in detail a positional relation of the tape guide poles 5 to the guide roller supporting pin 6 provided in, for instance, the lower half casing 2.

Figures 6 and 7 shows another embodiment of the tape cassette according to the present invention, in which tape guide rollers 16 are assembled to form a cassette type.



In this embodiment, the tape guide poles 5 which has been located near and both sides of the head house 14 are removable, and the tape guide rollers 16 are respectively put around the roller supporting pins 6 to thereby form a traveling path for the tape 3.

In the embodiment shown in Figures 6 and 7, the tape guide poles having a U-shape in cross section whose circular arc surface provides a tape contacting surface are formed integrally with the upper and lower half casings in the same manner as the first embodiment shown in Figures 1 through 5. Accordingly, precise location of the tape guide poles is obtainable to thereby improve reliability on the tape traveling and easy assembling for the tape cassette. Further, the tape cassette of the embodiment shown in Figures 6 and 7 can be used commonly for a fixed guide pole type and a guide roller type. The other advantages of the embodiment are the same as those of the first embodiment.

Figures 8 and 9 show in details a relation of linear ribs to circular peripheral wall portions for fitting the hubs in the lower half casing 2.

The same reference numerals as in Figures 1 through 7 designate the same or corresponding parts.

The linear ribs comprise the center rib 9 which has a thickness thinner than the wall thickness of the lower half casing (or the upper half casing), a height sufficient to mount thereon the hubs 3 and arranged in a

linear line to connect the center of the axial holes 10 for receiving the hubs and contiguous to the circular peripheral walls 8 for fitting the hubs, and the side ribs 9₁, 9₁ arranged at both sides of the center rib 9 with a certain distance. The center rib 9 and the side ribs 9₁, 9₁ are formed integrally with the inner surface of the lower half casing 2. It is desirable to form reinforcing ribs 9₂ at both sides and near the head house 14 of the lower half casing 2.

10 Since the thickness of the linear rib and reinforcing ribs are made thinner than the wall thickness of the lower half casing 2 (or the upper half casing), a smooth flow of resin at the time of molding the casing is obtained and the casing having a less residual strain and accurate dimensions and good thermal resistance is obtainable.

Shoulder portions 19 are provided at both end portions of at least one of the linear ribs 9, 9₁ to support a tape movement controlling sheet 18 in the casing, whereby excellent assembling property is obtainable.

In the embodiment shown in Figures 8 and 9 wherein circular peripheral wall portions for fitting the hubs are formed around axial holes for receiving the shaft portion of the hubs, and linear ribs are formed in parallel with each other in the casing in an area including the circular peripheral wall portions and in



the vicinity of them, the hubs around which a tape is wound can be correctly positioned in the cassette casing and a contacting surface area of the casing to the hubs is made small to thereby reduce a resistance of friction and to reduce a torque of hub, whereby reliability on traveling of the tape, stabilization of torque and easy assembling of the cassette casing can be remarkably improved. Further, a tape cassette which eliminates occurrence of recesses and increases the strength even though the wall thickness of the cassette casing is thin can be provided. Further, such tape cassette having good appearance, light weight, a low manufacturing cost and suitable for a large scale production can be provided.

Figure 10 is a plane view showing a modification of the head house 14 shown in Figure 1.

The head house 14 of each of the upper and lower half casings 1, 2, is constituted solely by tape guide pins 20, a center boss 21, shield plate surrounding walls 27 and pad supporting plates 20 which form a head insertion recess in which a shield plate and a pad are received, and partition walls 25, 26 for surrounding in part cassette position determining openings 23 and capstan insertion holes 24 respectively.

The circular peripheral walls 8 for fitting the hubs are formed around the axial holes 10 for receiving the hubs. A plurality of thin linear ribs 9, 9₁ are formed



in a parallel relation in an area including the circular peripheral walls 8, 8 and near them.

The head house 14 has a shouldered recess portion formed in the casing. A magnetism shielding wall 9₂ is formed along the inner edge of the shouldered recess portion to thereby define that portion from an area where the circular peripheral walls 8 for fitting the hubs are formed.

The thin linear ribs comprise a center rib 9 which has a thickness thinner than the wall thickness of the upper and lower half casings and a height suitable for mounting thereon the hubs 3 and which is arranged on the linear line connecting each center of the axial holes 10, 10 for receiving the hubs so as to be connected to the circular peripheral walls 8, and side ribs 9₁, 9₁ formed at both sides of the center rib 9 with a certain distance. The center rib 9 and the side ribs 9 are formed integrally with the inner surface of the upper and lower half casings.

Reinforcing ribs may be formed at positions near the head house 14 and the opposite side in consideration of a balance in wall thickness. In the embodiment shown in Figure 10 which has the construction as described above, a smooth flow of molten resin can be obtained in molding operations to thereby avoid occurrence of recesses or strains as well as providing good releasability. Further, the preparation of accurate metal modls for



molding the upper and lower half casings are easy be-
pins are independently provided and the partition wa-
are separately prepared. In the tape cassette of the
embodiment, occurrence of recesses can be prevented even
5 though the wall thickness of the cassette casing is thin
and it has excellent appearance. Further, it can be
manufactured at a low cost and is suitable for a large
scale production.

Figures 11 through 13 show another embodiment of the
10 present invention.

The upper and lower half casings 1, 2 constitute a
cassette casing in which a pair of the hubs 3 around
which a tape 4 is wound are rotatably supported by the
circular peripheral walls 8 for fitting the hubs. Tape
15 guide poles 5 having a substantially U-shape in cross
section are located in a tape traveling path between the
hubs 3, 3. The tape guide poles are formed integrally
with either the upper half casing 1 or the lower half
casing, 2 so that the circular arc surface functions as a
20 tape contacting surface. Connecting cylindrical bodies
11a are formed at four corners of the upper and lower
half casings 1, 2. The connecting cylindrical bodies 11a
respectively have an abutting surface 38 at their top. A
rib for melt-bonding 39 is formed at the abutting surface
25 of each of the connecting cylindrical bodies 11a of
either of the upper and lower half casings 1, 2 and a
position-determining boss 36 is formed at the abutting



surface 38 of each of the connecting cylindrical bodies of the other.

The connecting cylindrical bodies 11a are respectively cylindrical bodies each having a cylindrical hole 37 at their axial center. The position-determining boss 36 is projected from the abutting surface 38 as a melt-bonding surface so that the boss is fitted to the hole 37 of the opposing connecting cylindrical body 11a. The hole 37 formed in the connecting cylindrical body 11a may not be a circular shape but it may be a polygonal shape such as a regular triangle shape, a square shape, a regular hexagonal shape or a regular octagonal shape as far as it can easily receive the position-determining boss 36 projecting from the opposing connecting cylindrical body. The position-determining boss 36 may be a shape of cross or star having radially extended blade portions wherein the top edge of the boss is slender. The root portion of the position-determining boss is press-fitted to the inner circumferential wall of the connecting cylindrical body 11a, or the boss may be formed integrally with the connecting cylindrical body 11a. Tape guides 5 are located near tape guide roller supporting pins 6 formed in the lower half casing 2. The tape guides 5 are preferably formed to be removable by breaking. It is more preferable that the tape guide poles 5 are in corner portions 7, 7 so that they are located with a distance between which a plurality of the



tape guide roller supporting pins 6 are arranged.

The wall thickness of the upper and lower half casings should be thin. For instance, the wall thickness of the flat surface of the casings is 1.0 mm or less and the difference in wall thickness of the flat surface wall of the casings from the outer peripheral wall of the casings is within 0.2 mm. In order to maintain the strength of the casings, circular peripheral walls 8, 8 for fitting the hubs 3 are formed and a plurality of reinforcing ribs are provided near the circular peripheral walls 8, 8. Further, partition walls may be formed at each of the corner portions 7. The thickness of the reinforcing ribs 9 are thinner than the wall thickness of the casings so that a smooth flow of resin at the molding can be obtained. As a result, a tape cassette having a less residual strain, accurate dimensions and thermal resistance is obtainable.

The tape cassette shown in Figure 11 can be applied not only to a tape cassette but also a disk cartridge.

A center boss 40 may be formed if necessary, and the position-determining boss 36 and the melt-bonding rib 39 may be provided for other bosses to further increase the connection and the strength of the casings.

In the embodiment shown in Figures 11 through 13, the connection of the upper and lower half casings which forms a cassette casing can be obtained with high precision without resulting an error of position in melt-



bonding. Accordingly, reliability and easy assembling of the tape cassette can be remarkably improved. Further, a tape cassette having good appearance, high precision and an increased strength while the thickness of the cassette casing is thin can be provided.

Figure 14 through 19 show another embodiment of the tape cassette having an improved connecting bosses for connecting the upper and lower half casings.

In Figure 14, the upper and lower half casings 1, 2 respectively have bosses 56, 57 to be used for assembling the upper and lower half casings by using ultrasonic waves. A melt-bonding rib 59 is formed in the contacting surface 66 of each of the melt-bonding bosses 56. On the other hand, a cut portion 60 is formed at the outer side of the contacting surface 67 of each of the melt-bonding bosses 57 which oppose the melt-bonding bosses 56. The cut portion 60 is to receive a part of molten portion of the melt-bonding rib 59.

As shown clearly in Figures 15 through 17, the melt-bonding boss 56 is provided with a conical or an annular melt-bonding rib 59 at the central portion of the contacting surface 66. The cut portion 60 to be formed in the opposing melt-bonding boss 57 should be formed at a position which does not directly contact with the melt-bonding rib 59. However, the cut portion 60 may be formed at the both melt-bonding bosses 56, 57. The melt-bonding rib 59 may be formed at a suitable position in



the contacting surface as far as a molten material is prevented from flowing outside the contacting surface 66, 67, and there is free from an error in position of the upper and lower half casings.

5 The cut portion 60 may be provided in a form of radially extending grooves in the contacting surface other than a shape formed by cutting away a part of the outer circumference of the melt-bonding boss as shown in Figures 14 through 17. Or, the cut portion 60 may be
10 parallel linear grooves or a lattice-like form within which the center rib 59 is formed at the central portion.

The melt-bonding boss may not be in a cylindrical form but also may be a polygonal boss such as a regular triangle boss, a square boss, a regular hexagonal boss,
15 or a regular octagonal boss. The melt-bonding boss is formed integrally with the upper and lower half casings.

The embodiment shown in Figure 14 is used for a tape cassette. However, it can be used as a disk cartridge.

A center boss may be formed if required. The melt-
20 bonding rib and the cut portion may be formed in another boss to further increase the strength of connection and resistance to distortion.

Figures 18 and 19 shows a digital compact cassette (DCC) type tape cassette. In Figures 18 and 19, a
25 shutter 80 having a channel form in cross section which has windows 78, 79 for opening and closing a driving shaft insertion opening 10, a case position determining



opening 75, a capstan insertion opening 76 and a front opening 77, is slidably placed in a slide area 81. In the upper and lower half casings, melt-bonding bosses 86, 86 are provided in an opposing state so that the upper and lower half casings 1, 2 are assembled by ultrasonic melt-bonding. A melt-bonding rib 89 is formed in melt-bonding bosses formed either the upper half casing or the lower half casing, and a cut portion to receive molten material of the melt-bonding rib is formed in the melt-bonding bosses of the other casing. In Figures 14 through 19, a cut portion to receive a molten part of the melt-bonding rib is formed at an outer portion of the melt-bonding bosses of either of the casings, whereby the flooding of the molten material is prevented. Further, an error in position of the assembled casings can be eliminated. Since the molten material can be received in the cut portion, a cassette casing having good appearance is obtainable. Further, a large strength of connection between the opposing melt-bonding bosses is obtained, whereby the upper and lower half casings forming a cassette casing can be strongly and precisely connected.

This Sheet Has Been Replaced



CLAIMS:

1. A tape cassette comprising a cassette casing composed
5 of an upper half casing and a lower half casing, a pair of
hubs around which a tape is wound and which are rotatably
held in the cassette casing, and tape guide members formed
in the cassette casing at positions through which the tape
wound around the hubs is travelled, the tape cassette being
10 characterised in that the tape guide members are tape guide
poles having substantially U-shaped in cross sections and
which are formed integrally with either of the upper and
lower casings wherein the circular arc surface of the U-
shaped tape guide poles is a tape contacting surface.
- 15
2. The tape cassette according to claim 1, wherein the
tape guide poles are arranged in the vicinity of tape guide
roller supporting pins formed in the casing so as to be
removable.
- 20
3. The tape cassette according to claim 1 or claim 2,
wherein the tape guide poles are formed with certain
distance at each corner of both side portions of the casing.
- 25
4. The tape cassette according to claim 1 substantially
as described herein with reference to the accompanying
drawings.

This Sheet Has Been Replaced




TAPE CASSETTE
ABSTRACT

A tape cassette comprising a cassette casing composed of an upper half casing and a lower half casing, a pair of hubs around which a magnetic tape is wound and which
5 are rotatably fitted into circular peripheral walls formed in the cassette casing, and tape guide members formed in the cassette casing at positions through which the magnetic tape wound around the hubs is traveled, wherein the thickness of the flat surface walls and the
10 thickness of the outer peripheral walls of the upper and lower half casings are respectively uniform.

This Sheet Has Been Replaced



FIGURE 1



This Sheet Has Been Replaced



FIGURE 2





FIGURE 3



This Sheet Has Been Replaced



FIGURE 4






FIGURE 5



This Sheet Has Been Replaced




FIGURE 6



This Sheet Has Been Replaced




FIGURE 7



This Sheet Has Been Replaced



FIGURE 11



This Sheet Has Been Replaced



FIGURE 12






FIGURE 13



This Sheet Has Been Replaced



FIGURE 14




This Sheet Has Been Replaced



FIGURE

15



FIGURE

16





FIGURE 17



This Sheet Has Been Replaced



FIGURE 18






FIGURE 19



This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

REPLACEMENT SHEETS		SG
☐ Description :	paged	to paged
☐ Claim(s) :	paged	to paged
☒ Drawing(s) :	paged <u>1/2</u>	to paged <u>2/2</u>
☐ Abstract :	paged	to paged
DATE OF RECEIPT <u>27/8/14</u>		

FIGURE 8





FIGURE 9




This is the replacement sheet

Date: 27 AUG 1996

THIS SHEET HAS BEEN
REPLACED

FIGURE 10



This is the replacement sheet

Date: 27 AUG 1996

This Sheet Has Been Replaced



- 23 -


TAPE CASSETTE

ABSTRACT

A tape cassette comprising a cassette casing composed of an upper half casing and a lower half casing, a pair of hubs around which a magnetic tape is wound and which are rotatably fitted into circular peripheral walls formed in the cassette casing, and tape guide members formed in the cassette casing at positions through which the magnetic tape wound around the hubs is traveled, wherein the thickness of the flat surface walls and the thickness of the outer peripheral walls of the upper and lower half casings are respectively uniform.

FIGURE 1

THIS SHEET HAS BEEN
REPLACED



2-8554022

REPLACEMENT SHEETS 50

- ☒ Description : paged 1. to paged 5.
☒ Claim(s) : paged 4. to paged 7.
☒ Drawing(s) : paged 1. to paged 4.
☐ Abstract : paged to paged

DATE OF RECEIPT...5/4/97.....

- 1 -

TAPE CASSETTE

The present invention relates to a tape cassette such as a magnetic tape cassette, a cleaning tape cassette or a video tape cassette. This invention has been divided from GB2262276.

In a conventional tape cassette having a head house and a pair of hubs, a magnetic tape is guided in a tape travelling path between the head house and the hubs in the cassette casing. In this way, the magnetic tape is wound onto or unwound from the hubs. The hubs are supported for rotation by circular wall portions. The Circular Wall Portions are formed around axial holes formed in the casing in order to receive the shaft portions of the hubs. Usually, various auxiliary elements are installed in the head house. Therefore, in order to ensure that the casing has a sufficient strength, reinforcing ribs or partition walls are formed in the head house. Alternatively, the wall thickness of the casing may be increased, or a highly durable material may be used.

In conventional tape cassettes, the outer wall of the casing is made thicker than the flat surface wall portion of the casing in order to increase the impact resistance of the casing.

However, the conventional tape cassette has numerous disadvantages. At many portions there is a large scatter in the wall thickness. Moulding properties are not good and there are strains and deformations in the moulded casing.

Further, the many ribs and partition walls in the head house area at the front portion of the casing cause a high concentration of resin when the resin is injected to form the casing. This often leads to the formation of recesses in the molded product. In addition, when there is a change in the thickness of the casing wall the rate of flow of the molten resin stream changes thereby causing strains in the resin. At these points, thermal deformation is apt to occur. When a casing having a thin wall thickness is required, such an undesirable tendency is increased, and there are often conspicuous recesses on the surface of the

This is the replacement sheet

- 5 DEC 1997

Date:

casing. These recesses seriously detract from the appearance of the casing. GB 2262276 claims the invention of the flat surface wall portion and the outer peripheral wall portion of a cassette casing have a thickness of 0.8 to 1.2mm and rib means are provided for strengthening the cassette casing.

It is an object of the present invention to provide a tape cassette which improves the reliability of the travel of a tape and increases the ease of assembly by providing suitable tape guide members. The tape cassette can be suitable for use commonly for a fixed guide pole type and a guide roller type cassette.

According to the invention, there is provided a tape cassette comprising a cassette casing composed of an upper half casing and a lower half casing, a pair of hubs around which a tape is wound and which are rotatably held in the cassette casing, and tape guide members formed in the cassette casing at positions through which the tape wound around the hubs is travelled, the tape cassette being characterized in that the tape guide members are tape guide poles having a substantially U-shape cross section and which are formed integrally with either of the upper and lower casings wherein the circular arc surface of the U-shaped tape guide poles is a tape contacting surface and wherein the casing has a wall thickness in a range of 0.8mm to 1.2mm.

Specific embodiments of the present invention are now described, by way of example only, with reference to the drawings in which:

Figure 1 is a plane view showing an embodiment of the

tape cassette of the present invention wherein the upper and lower half casings are shown in a separated state to show the inside of them;

Figure 2 is an enlarged perspective view partly omitted of the lower half casing shown in Figure 1;

Figure 3 is a perspective view in a state of use of the embodiment shown in Figure 1;

Figure 4 is an enlarged longitudinal cross-sectional view of a corner portion of the lower half casing shown in Figure 1;

Figure 5 is an enlarged perspective view of an embodiment of a corner portion of the lower casing according to the present invention;

Figure 6 is a plane view of another embodiment of the present invention wherein the upper and lower half casings are shown in a separate state to show the inside of them;

Figure 7 is a perspective view in an exploded state of the tape cassette shown in Figure 6;

Figure 8 is an enlarged cross-sectional view taken along a line I-I in Figure 6;

Figure 9 is an enlarged perspective view of an embodiment of the lower half casing of the present invention;

Figure 10 is a plane view showing another embodiment of the tape cassette of the present invention wherein the upper and lower half casings are shown in a separate

This is the replacement sheet

Date: - 5 DEC 1997

state to show the inside of them; and

Figure 11 is a plane view showing another embodiment of the tape cassette of the present invention wherein the upper and lower half casings are shown in a separated state to show the inside of them;

Preferred embodiments of the tape cassette according

This is the replacement sheet

Date: - 5 DEC 1997

to the present invention will be described with reference to the drawings.

Figure 1 through 4 shows a first embodiment of the tape cassette of the present invention. A cassette casing comprises an upper half casing 1 and a lower half casing 2. Inside the cassette casing, a pair of hubs 3 around which a tape 4 such as a magnetic tape is wound are rotatably supported by circular peripheral wall portions 8 for fitting the hubs 3, which are formed integrally with the upper and lower half casings 1, 2. As tape guide members located in the tape traveling path between the hubs 3, 3, provided are tape guide poles 5 having a substantially U-shape in cross section. The tape guide poles 5 are formed integrally with the upper half casing 1 or the lower half casing 2 so that the circular arc surface of the substantially U-shape comes in contact with the tape traveling. The circular peripheral wall portions 8 for supporting the hubs 3 are projected from the inner surface of the upper and lower half casings 1, 2 at positions around axial holes 10 for receiving the shaft portion of the hubs. A plurality of linear ribs 9, 9₁ are formed in a parallel relation so as to extend in an area including the circular peripheral wall portions 8, 8 and in the vicinity of them. In this embodiment, the thickness of the flat surface wall portion 1₁, 2₁ of the upper and lower half casings 1, 2 is determined in a range of $t_1 = 0.8-1.2$ mm, and the

This is the replacement sheet

Date: - 5 DEC 1977

thickness of the outer peripheral wall portions 1_2 , 2_2 is determined in a range of $t_2 = 0.8-1.2$ mm. The wall thickness of each of the upper and lower half casings 1 , 2 and the outer peripheral walls 1_2 , 2_2 is substantially uniform. A scatter in the wall thickness of each of the flat surface walls 1_1 , 2_1 and the outer peripheral walls 1_2 , 2_2 should be 20% or lower.

Reinforcing ribs formed projecting from the inner surface of the upper and lower half casings have a height sufficient to mount thereon the hubs 3 , and include a center rib 9 connected to the circular peripheral walls 8 for fitting the hubs and arranged on a linear line connecting the center of each of the axial holes 10 , 10 for receiving the shaft portion of the hubs, and side ribs 9_1 , 9_1 arranged with a distance at both sides of the center rib 9 . The circular peripheral walls 8 are so constructed to reduce the surface area of contact of the hubs 3 to the cassette casing to thereby reduce a torque.

In addition to the reinforcing ribs 9 , 9_1 , the provision of reinforcing ribs 9_2 at positions near a head house 14 and the opposite side of it are effective to reduce the wall thickness of the cassette casing. When the width of each of the ribs 9 , 9_1 , 9_2 is made thinner than the wall thickness of the upper and lower half casings, a preferred stream of resin is obtained at the time of molding, and accordingly, a tape cassette having a less residual strain, accurate dimensions and excellent

This is the replacement sheet

Date: - 5 DEC 1997

heat resistance can be obtained.

It is preferable to locate the tape guide members 5b near each support pin 6 for supporting a roller for guiding the tape, which is formed in either the upper or the lower half casing. Preferably, some of the tape guide members 5 are provided to be removable. It is further preferable that the tape guide members 5 are located at both corner portions 7, 7 in either half casings so that a plurality of the tape guide members 5 are used and they are disposed at both sides of a plurality of supporting pins 6..

It is preferable that the wall thickness of the upper and lower half casings is thin as possible while a sufficient strength should be maintained. For this purpose, a partition walls 9₃ is preferably formed together with connecting bosses 11, 17 in addition to the reinforcing ribs 9, 9₁, 9₂ formed around the circular peripheral walls 8, 8 for fitting the hubs 3, at each of the corner portions 7.

Each of the upper and lower half casings 1, 2 is provided with windows 12, 12 between the circular peripheral walls 8, 8 for fitting the hubs and between the linear ribs 9, 9₁ and along these ribs, whereby an amount of the tape around the hubs is visible. In this case, the cassette casing body may not be transparent and a transparent window may not be provided. Further, a tape cassette having a unique design is provided.

This is the replacement sheet

Date: - 5 DEC 1997

Finger touch portions 13 are provided at both side surfaces of the upper and lower half casings 1, 2 at positions near the head house 14.

The head house 14 is a section for recording and reproducing a tape and comprises an insertion hole, supporting walls and an opening. In Figure 1, reference numerals 15 designate pin bearing portions.

In the above-mentioned first embodiment of the tape cassette having the construction described above, the thickness of the flat surface wall portions and the outer peripheral wall portions of the upper and lower half casings are respectively formed to be substantially uniform, whereby a scatter in the wall thickness of each of the wall portions can be small, molding property is remarkably improved to reduce occurrence of strains or deformation, accuracy in dimensions, and reliability on heat resistance can be increased. Further, a tape cassette having thin upper and lower half casings, a low manufacturing cost and suitable for a large-scale production can be provided.

Figures 4 and 5 show in detail a positional relation of the tape guide poles 5 to the guide roller supporting pin 6 provided in, for instance, the lower half casing 2.

Figures 6 and 7 shows another embodiment of the tape cassette according to the present invention, in which tape guide rollers 16 are assembled to form a cassette type.

This is the replacement sheet

Date: ~ 5 DEC 1997

In this embodiment, the tape guide poles 5 which has been located near and both sides of the head house 14 are removable, and the tape guide rollers 16 are respectively put around the roller supporting pins 6 to thereby form a traveling path for the tape 3.

In the embodiment shown in Figures 6 and 7, the tape guide poles having a U-shape in cross section whose circular arc surface provides a tape contacting surface are formed integrally with the upper and lower half casings in the same manner as the first embodiment shown in Figures 1 through 5. Accordingly, precise location of the tape guide poles is obtainable to thereby improve reliability on the tape traveling and easy assembling for the tape cassette. Further, the tape cassette of the embodiment shown in Figures 6 and 7 can be used commonly for a fixed guide pole type and a guide roller type. The other advantages of the embodiment are the same as those of the first embodiment.

Figures 8 and 9 show in details a relation of linear ribs to circular peripheral wall portions for fitting the hubs in the lower half casing 2.

The same reference numerals as in Figures 1 through 7 designate the same or corresponding parts.

The linear ribs comprise the center rib 9 which has a thickness thinner than the wall thickness of the lower half casing (or the upper half casing), a height sufficient to mount thereon the hubs 3 and arranged in a

This is the replacement sheet

Date: - 5 DEC 1997

linear line to connect the center of the axial holes 10 for receiving the hubs and contiguous to the circular peripheral walls 8 for fitting the hubs, and the side ribs 9₁, 9₁ arranged at both sides of the center rib 9 with a certain distance. The center rib 9 and the side ribs 9₁, 9₁ are formed integrally with the inner surface of the lower half casing 2. It is desirable to form reinforcing ribs 9₂ at both sides and near the head house 14 of the lower half casing 2.

Since the thickness of the linear rib and reinforcing ribs are made thinner than the wall thickness of the lower half casing 2 (or the upper half casing), a smooth flow of resin at the time of molding the casing is obtained and the casing having a less residual strain and accurate dimensions and good thermal resistance is obtainable.

Shoulder portions 19 are provided at both end portions of at least one of the linear ribs 9, 9₁ to support a tape movement controlling sheet 18 in the casing, whereby excellent assembling property is obtainable.

In the embodiment shown in Figures 8 and 9 wherein circular peripheral wall portions for fitting the hubs are formed around axial holes for receiving the shaft portion of the hubs, and linear ribs are formed in parallel with each other in the casing in an area including the circular peripheral wall portions and in

This is the replacement sheet

Date: - 5 DEC 1997

the vicinity of them, the hubs around which a tape is wound can be correctly positioned in the cassette casing, and a contacting surface area of the casing to the hubs is made small to thereby reduce a resistance of friction and to reduce a torque of hub, whereby reliability on traveling of the tape, stabilization of torque and easy assembling of the cassette casing can be remarkably improved. Further, a tape cassette which eliminates occurrence of recesses and increases the strength even though the wall thickness of the cassette casing is thin can be provided. Further, such tape cassette having good appearance, light weight, a low manufacturing cost and suitable for a large scale production can be provided.

Figure 10 is a plane view showing a modification of the head house 14 shown in Figure 1.

The head house 14 of each of the upper and lower half casings 1, 2, is constituted solely by tape guide pins 20, a center boss 21, shield plate surrounding walls 27 and pad supporting plates 20 which form a head insertion recess in which a shield plate and a pad are received, and partition walls 25, 26 for surrounding in part cassette position determining openings 23 and capstan insertion holes 24 respectively.

The circular peripheral walls 8 for fitting the hubs are formed around the axial holes 10 for receiving the hubs. A plurality of thin linear ribs 9, 9₁ are formed

This is the replacement sheet

Date: - 5 DEC 1997

in a parallel relation in an area including the circular peripheral walls 8, 8 and near them.

The head house 14 has a shouldered recess portion formed in the casing. A magnetism shielding wall 9₂ is formed along the inner edge of the shouldered recess portion to thereby define that portion from an area where the circular peripheral walls 8 for fitting the hubs are formed.

The thin linear ribs comprise a center rib 9 which has a thickness thinner than the wall thickness of the upper and lower half casings and a height suitable for mounting thereon the hubs 3 and which is arranged on the linear line connecting each center of the axial holes 10, 10 for receiving the hubs so as to be connected to the circular peripheral walls 8, and side ribs 9₁, 9₁ formed at both sides of the center rib 9 with a certain distance. The center rib 9 and the side ribs 9 are formed integrally with the inner surface of the upper and lower half casings.

Reinforcing ribs may be formed at positions near the head house 14 and the opposite side in consideration of a balance in wall thickness. In the embodiment shown in Figure 10 which has the construction as described above, a smooth flow of molten resin can be obtained in molding operations to thereby avoid occurrence of recesses or strains as well as providing good releasability. Further, the preparation of accurate metal modls for

This is the replacement sheet

Date: - 5 DEC 1997

molding the upper and lower half casings are easy because pins are independently provided and the partition walls are separately prepared. In the tape cassette of the embodiment, occurrence of recesses can be prevented even though the wall thickness of the cassette casing is thin and it has excellent appearance. Further, it can be manufactured at a low cost and is suitable for a large scale production.

Figure 11 shows another embodiment of the present invention.

The upper and lower half casings 1, 2 constitute a cassette casing in which a pair of the hubs 3 around which a tape 4 is wound are rotatably supported by the circular peripheral walls 8 for fitting the hubs. Tape guide poles 5 having a substantially U-shaped in cross section are located in a tape traveling path between the hubs 3, 3. The tape guide poles are formed integrally with either the upper half casing 1 or the lower half casing, 2 so that the circular arc surface functions as a tape contacting surface. Connecting cylindrical bodies 11a are formed at four corners of the upper and lower half casings 1, 2. The connecting cylindrical bodies 11a respectively have an abutting surface 38 at their top. A rib for melt-bonding 39 is formed at the abutting surface of each of the connecting cylindrical bodies 11a of either of the upper and lower half casings 1, 2 and a position-determining boss 36 is formed at the abutting

surface 38 of each of the connecting cylindrical bodies of the other.

The connecting cylindrical bodies 11a are respectively cylindrical bodies each having a cylindrical hole 37 at their axial center. The position-determining boss 36 is projected from the abutting surface 38 as a melt-bonding surface so that the boss is fitted to the hole 37 of the opposing connecting cylindrical body 11a. The hole 37 formed in the connecting cylindrical body 11a may not be a circular shape but it may be a polygonal shape such as a regular triangle shape, a square shape, a regular hexagonal shape or a regular octagonal shape as far as it can easily receive the position-determining boss 36 projecting from the opposing connecting cylindrical body. The position-determining boss 36 may be a shape of cross or star having radially extended blade portions wherein the top edge of the boss is slender. The root portion of the position-determining boss is press-fitted to the inner circumferential wall of the connecting cylindrical body 11a, or the boss may be formed integrally with the connecting cylindrical body 11a. Tape guides 5 are located near tape guide roller supporting pins 6 formed in the lower half casing 2. The tape guides 5 are preferably formed to be removable by breaking. It is more preferable that the tape guide poles 5 are in corner portions 7, 7 so that they are located with a distance between which a plurality of the

This is the replacement sheet

Date: - 5 DEC 1997

tape guide roller supporting pins 6 are arranged.

The wall thickness of the upper and lower half casings should be thin. For instance, the wall thickness of the flat surface of the casings is 1.0 mm or less and the difference in wall thickness of the flat surface wall of the casings from the outer peripheral wall of the casings is within 0.2 mm. In order to maintain the strength of the casings, circular peripheral walls 8, 8 for fitting the hubs 3 are formed and a plurality of reinforcing ribs are provided near the circular peripheral walls 8, 8. Further, partition walls may be formed at each of the corner portions 7. The thickness of the reinforcing ribs 9 are thinner than the wall thickness of the casings so that a smooth flow of resin at the molding can be obtained. As a result, a tape cassette having a less residual strain, accurate dimensions and thermal resistance is obtainable.

This is the replacement sheet

Date: - 5 DEC 1997



THIS SHEET HAS BEEN
REPLACED

CLAIMS:

1. A tape cassette comprising a cassette casing composed of an upper half casing and a lower half casing, a pair of hubs around which a tape is wound and which are rotatably held in the cassette casing, and tape guide members formed in the cassette casing at positions through which the tape wound around the hubs travels, the tape cassette being characterised in that the tape guide members are tape guide poles having substantially U-shaped cross sections and which are formed integrally with either of the upper and lower casings wherein the circular arc surface of the U-shaped tape guide poles is a tape contacting surface, and wherein the casing has a wall thickness in a range of 0.8 to 1.2mm.
2. The tape cassette according to claim 1, wherein pairs of two tape guide poles are respectively formed on each side of either the upper or lower casing.
3. The tape cassette according to claim 2, wherein the pairs of two tape guide poles are each adjacent tape guide roller supporting pins which are respectively provided on each side of the casing.
4. The tape cassette according to claim 3, wherein one of each of the pairs of two U-shaped tape guide poles, which are formed integrally with either of the upper or lower casings, is removable and each of the tape guide roller supporting pins is provided with a roller.
6. The tape cassette according to claim 1 substantially as described herein with reference to the accompanying drawings.




* C L M S *

This is the replacement sheet

Date: - 5 DEC 1997

FIGURE 1



This is the replacement sheet

Date: - 5 DEC 1997

FIGURE 2





FIGURE 3



This is the replacement sheet

Date: - 5 DEC 1997

FIGURE 4






FIGURE 5



This is the replacement sheet

Date: 5 DEC 1997


FIGURE 6



This is the replacement sheet

Date: - 5 DEC 1997

FIGURE 7



This is the replacement sheet

Date: - 5 DEC 1997

FIGURE 8






FIGURE 9



This is the replacement sheet

Date: - 5 DEC 1997


FIGURE 10



This is the replacement sheet

Date: ~ 5 DEC 1997

FIGURE 11



This is the replacement sheet

Date: - 5 DEC 1997

16

REPLACEMENT SHEETS		80
☐ Description :	paged to paged	
☒ Claim(s) :	paged ..4. to paged ..7.	
☐ Drawing(s) :	paged to paged	
☒ Abstract :	paged ..7. to paged ..7.	
DATE OF RECEIPT		22/9/98

CLAIMS:

1. A tape cassette comprising a cassette casing composed of an upper half casing and a lower half casing, a pair of hubs around which a tape is wound and which are rotatably held in the cassette casing, and tape guide members formed in the cassette casing at positions through which the tape wound around the hubs travels, the tape cassette being characterised in that the tape guide members are tape guide poles having substantially U-shaped cross sections and which are formed integrally with either of the upper and lower casings wherein the circular arc surface of the U-shaped tape guide poles is a tape contacting surface, and wherein the casing has a wall thickness in a range of 0.8 to 1.2mm.
2. The tape cassette according to claim 1, wherein pairs of two tape guide poles are respectively formed on each side of either the upper or lower casing.
3. The tape cassette according to claim 2, wherein the pairs of two tape guide poles are each adjacent tape guide roller supporting pins which are respectively provided on each side of the casing.
4. The tape cassette according to claim 3, wherein one of each of the pairs of two U-shaped tape guide poles, which are formed integrally with either of the upper or lower casings, is removable and each of the tape guide roller supporting pins is provided with a roller.
5. The tape cassette according to claim 1 substantially as described herein with reference to the accompanying drawings.



This is the replacement sheet

Date: 22 SEP 1998

TAPE CASSETTE

ABSTRACT

A tape cassette comprising a cassette casing composed of an upper half casing and a lower half casing, a pair of hubs around which a magnetic tape is wound and which are rotatably fitted into circular peripheral walls formed in the cassette casing, and tape guide members formed in the cassette casing at positions through which the magnetic tape wound around the hubs is traveled, wherein the thickness of the flat surface walls and the thickness of the outer peripheral walls of the upper and lower half casings are respectively uniform.

FIGURE 1

This is the replacement sheet

Date: 22 SEP 1998