


A1

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 June 2002 (20.06.2002)


PCT

(10) International Publication Number
WO 02/48851 A2

- (51) International Patent Classification⁷: G06F 3/00 (72) Inventor: SMITH, Dipak, J., 7993 Lismore Circle, Eden Prairie, MN 55434 (US).
- (21) International Application Number: PCT/US01/50672 (74) Agents: CRISS, Roger, H. et al, Honeywell International Inc., 101 Columbia Avenue, P.O. Box 2245, Morristown, NJ 07960 (US)
- (22) International Filing Date:
1 November 2001 (01 11 2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/706,077 3 November 2000 (03.11.2000) US
- (71) Applicant: HONEYWELL INTERNATIONAL INC.
[US/US], 101 Columbia Avenue, P.O. Box 2245, Morristown, NJ 07960 (US)
- (81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: MULTIPLE LANGUAGE USER INTERFACE FOR THERMAL COMFORT CONTROLLER



(57) Abstract: A multiple language user interface system for a thermal comfort controller. The user interface system has a central processing unit coupled to a memory, a language selector and a touch sensitive display unit. The memory can store at least one user interface object and at least one control algorithm. In some embodiments, the user interface system also has a network interface for connecting to the Internet or other network. In some embodiments, the first time the user interface system is powered-up after installation, a first set of user interface objects are displayed on the display unit and the user selects a preferred language. Once a preferred language is chosen, user interface objects can be loaded into the memory and the display unit will display the user interface objects in the preferred language. In some embodiments, control algorithms are loaded into memory.

WO 02/48851 A2

162162

A2

WO 02/48851 A2



IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette

Published:

— *without international search report and to be republished upon receipt of that report*