

Description

The invention relates to an inductive device, comprising a soft magnetic core which consists of two E-shaped core halves, each of which comprises three limbs which are interconnected by a yoke, which core halves are arranged one against the other by way of the free ends of the limbs, the central limbs extending within a coil former on which a winding is provided, the coil former having connection strips thereon, the outer limbs extending between an upper boundary plane and a lower boundary plane, the lower boundary plane being above the lower boundary of the body of the device, and the upper and lower boundary planes extending parallel to the longitudinal directions of the outer limbs and the yokes, the distance between the boundary planes being equal to the height of the outer limbs in a direction perpendicular to the boundary planes, which height is greater than the height of the central limbs, the central limbs having a symmetry plane extending parallel to the boundary planes.

The inductive device can be, for example a transformer or a choke coil. A transformer of this kind is known from US-A 4,760,366. Transformers of this kind are intended particularly for mounting on a printed circuit board, the boundary planes then extending parallel to the plane of the board. The lower boundary plane is then formed by the boundary plane nearest to the board. The coil former may be provided with a connection strip with connection pins which are connected to lead-outs of the winding and which project below the lower boundary plane in a direction perpendicular to the boundary planes. The lower boundary of the coil former then rests against the surface of the board. The reason why the height of the central limb is smaller than the height of the outer limbs is that the structural height of the core may then be smaller than in conventional E-cores. This is important because printed circuit boards are often mounted one over the other and the distance between neighbouring boards must then be as small as possible, for example 25.4 mm. Because the transformer is often the largest (highest) component on such a board, its height must be as small as possible.

GB-A-2211669 discloses a compact transformer core having two identical E-shaped core halves whose central limbs having a trapezoidal cross-section are positioned with regard to the outer limbs such that the structural height of the transformer is relatively small.

It is an object of the invention to provide an inductive device of the kind set forth whose structural height may even be smaller than that of the known transformer, for example 12.5 mm or less.

To achieve this, the inductive device in accordance with the invention is characterized in that the central limbs are substantially rectangular in cross-

section, in that the lower surface of the connection strips define the lower boundary of the device and in that the lower surfaces of the central limbs are in a plane which is at such a distance from the lower boundary plane that the symmetry plane of the central limbs is situated halfway between the upper boundary plane and a plane which extends parallel to the boundary planes and is situated from 0.1 to 1 mm above the lower boundary of the device.

The invention is based on the recognition of the fact that a further reduction of the structural height of the known transformer can be achieved only by reducing the height of the soft magnetic yoke and/or the coil former. A reduction of the height of the yoke or the coil former reduces the winding space available above or below the central limb, respectively, so that a part of the overall winding space available is not used. The winding space thus lost increases the structural height of the transformer. In the inductive device in accordance with the invention, the central limb is shifted in the vertical direction with respect to the yoke (and with respect to the coil former), so that substantially the same winding space is available still in all directions and this space can be completely filled. The magnitude of the winding space is determined by the distance between the upper boundary plane of the core and the upper boundary of the central limb. This distance can be comparatively arbitrarily chosen by the designer, after which the dimensions of the coil former can be adapted in order to comply with the features proposed by the invention. The distance between the lower boundary of the central limb and the lower boundary plane preferably amounts to at least 0.2 mm.

The lateral dimensions of the winding space are determined by the distance between the facing side faces of the central limbs and the outer limbs. It is desirable to minimize this distance in order to minimize the quantity of core material used and to minimize the surface area occupied by the inductive device on the board. On the other hand, this distance should be so large that a coil former provided with a winding can be readily slid onto the central limb. To achieve this, a preferred embodiment of the inductive device in accordance with the invention is characterized in that the distance between facing side faces of the central limbs and the outer limbs is from 0.1 to 0.2 mm greater than the distance between the upper side of the central limb and the upper boundary plane. The clearance of from 0.1 to 0.2 mm suffices for easy sliding of the coil former with the winding onto the central limb, the increase of the width of the inductive device due to the introduction of this clearance being negligibly small.

These and other aspects of the invention will be described in detail hereinafter with reference to the drawing.

Figure 1 is an exploded view of a core comprising

two core halves and a coil former for a first embodiment of an inductive device in accordance with the invention,

Figure 2 is a cross-sectional view of one of the core halves shown in Figure 1,

Figure 3 is a plan view of the core half shown in Figure 2,

Figure 4 is a diagrammatic cross-sectional view of the complete first embodiment,

Figure 5 is a view, corresponding to Figure 1, of components for a second embodiment of an inductive device in accordance with the invention,

Figure 6 is a cross-sectional view, corresponding to Figure 2, of a core half for the second embodiment, and

Figure 7 is a cross-sectional view, corresponding to Figure 4, of the second embodiment.

Figure 1 is an exploded view of two identical core halves 1 and a coil former 3. The core halves 1 are made of soft magnetic material, for example ferrite. They are shaped approximately as a E with two outer limbs 5 and a central limb 7. The three limbs 5, 7 are interconnected by way of a yoke 9. The coil former 3 comprises a tubular central portion 11 with a through-cavity 13, the cross-sectional shape of which corresponds to the cross-section of the central limbs 7. At the two ends of the central portion 11 there are provided two flanges 15 which extend perpendicularly to the longitudinal axis of the through-cavity 13 and which support connection strips 17 at their lower side. The coil former is formed as an integral unit of a suitable, electrically insulating plastics, for example by injection moulding. The connection strips 17 are provided with metal connection pins 19. During the manufacture of for example a transformer a transformer winding consisting of a number of coils (not shown in Figure 1) is provided on the central portion 11 between the flanges 15. For the manufacture of, for example a choke coil it suffices to use a winding consisting of a single coil. Subsequently, the central limbs 7 of the two core halves 1 are slid into the cavity 13 in the direction of the arrows 21, 23 until the free ends of the corresponding limbs of the two core halves contact one another. The core halves 1 are fixed in this position, for example by means of glue or resilient means (not shown).

Figures 2 and 3 show one of the core halves 1 in a cross-sectional view and a plan view, respectively. The outer limbs 5 of each core half 1 extend between an upper boundary plane 25 and a lower boundary plane 27. These boundary planes are denoted by strokes/dot lines in Figure 2. The upper boundary plane 25 extends parallel to the longitudinal direction of the limbs 5, 7 and the yoke 9 and its position is determined by the upper side of the outer limbs 5. The lower boundary plane 27 extends parallel to the upper boundary plane 25 and its position is determined by the lower side of the outer limbs 5. The distance d be-

tween the two boundary planes 25, 27 is, therefore, determined by the height x of the two outer limbs 5, that is to say by their dimension perpendicular to the boundary planes. Because the two core halves 1 are identical, the upper boundary planes 25 coincide after assembly of the inductive device, like the two lower boundary planes 27. It is to be noted that only a relative meaning is to be attached to terms such as "upper", "lower" and "height" in the present context. The lower side of the inductive device is assumed to be the side which is intended to face the board when such an inductive device is mounted on, for example a printed circuit board. In the present embodiment this is the side where the contact strips 17 are situated. Therefore, the "lower side of the inductive device" remains the same when the inductive device is mounted in a position other than the position shown, for example in a vertical position.

Figure 3 shows that the three limbs 5, 7 extend over equal distances (hereafter termed as: "the length" of the limbs) from the yoke 9, so that the free ends of the limbs of the two core halves simultaneously contact one another when the core halves are slid into the cavity 13 by way of the central limbs 7. If the core is to comprise an air gap, the length of the central limbs 7 can be chosen to be slightly smaller than the length of the outer limbs 5. Figure 2 shows that the height y of the central limb 7 is smaller than the height x of the outer limbs 5 and that the height y of the central limb is smaller than the width z of the central limb.

Figure 4 is a cross-sectional view, corresponding to Figure 2, of the complete inductive device with a winding 29 arranged around the central portion 11 of the coil former 3. The central limb 7 has a symmetry plane 31 which extends parallel to the boundary planes 25, 27 and which is situated halfway between the upper boundary plane 25 and a plane 33 which extends parallel to the boundary planes and which is situated from 0.1 to 1 mm above the lower boundary 34 of the coil former 3. In the embodiment shown the lower boundary 34 of the coil former 3 coincides with the lower side of the contact strip 17. It is also possible to provide the lower side of the contact strips 17 with projections whose lower side define the lower boundary 34 (not shown). Preferably, the distance between the plane 33 and the lower boundary 34 of the coil former 3 amounts to 0.5 mm. The planes 31 and 33 are denoted by stroke/dot lines in Figure 4. The lower boundary of the central limb 7 is situated above the lower boundary plane 27 as shown in Figure 2. The distance preferably amounts to at least 0.2 mm and can be chosen to be larger (up to approximately 2 mm), depending on the dimensions of the core and the winding space required. Thanks to the described construction, the winding 29 extends between the planes 25 and 33 and substantially completely fills the space available at the upper and the

lower side. Thus, substantially no space which would increase the overall height of the inductive device remains above and below the winding 29. The distance of from 0.1 to 1 mm existing between the plane 33 and the lower side 34 of the coil former 3 is necessary to maintain, after the mounting of the inductive device on a printed circuit board, some clearance between this board and the winding 29 in order to allow air to flow around the winding for cooling purposes. This is because the lower side 34 of the coil former is generally mounted against the board.

The distance between the side faces 35 of the outer limbs 5 and the side faces 37 of the central limb 7 facing the former side faces is from 0.1 to 0.2 mm larger than the distance between the upper side of the central limb and the upper boundary plane 25. Consequently, between the central limb 7 and the outer limbs 5 exactly enough clearance exists to enable easy sliding of the coil former 3 with the winding 29 onto the central limb. If this clearance were greater, the space would no longer be completely filled by the winding 29, so that the inductive device would be unnecessarily wide. As a result, more material would be required for the formation of the core and the inductive device would occupy a larger surface area on a printed circuit board.

Because the winding 29 fills the space available substantially completely, hardly any room exists above and below this winding for guiding lead out wires from the winding to the connection pins 19. Therefore, approximately halfway the yoke 9 a recess 39 is provided at the upper side wherethrough the lead out wires (not shown) can be guided. Corresponding recesses 41 are provided at the upper side of the flanges 15.

The Figures 5 to 7 show a second embodiment of an inductive device in accordance with the invention. Elements in these Figures which correspond to elements of the first embodiment are denoted by the same reference numerals as used in the Figures 1, 2 and 4, be it that they are provided with an accent.

The major difference with respect to the first embodiment consists in that the lower boundary of the central limb 7' is situated below the lower boundary plane 27' instead of above this plane (see Figure 6). In this case the distance may again amount to from 0.2 to 2 mm. The height x' of the outer limbs 5' is smaller than the height x in the first embodiment. The height of the connection strips 17' is greater accordingly, so that in the second embodiment the symmetry plane 31' is also situated halfway between the upper boundary plane 25' and the plane 33' which extends parallel to the boundary planes 25', 27' and which is situated from 0.1 to 1 mm above the lower boundary 34' of the coil former 3'. As is clearly shown in Figure 7, the winding 29' substantially completely fills the space available between the planes 25' and 33' also in the second embodiment.

Figure 5 shows a portion 43 of the yoke 9' which is situated below the outer limbs 5'. At the top centre the connection strips 17' are provided with a recess 45 in order to prevent the cavity 13' from being partly closed due to their large height.

The two embodiments described demonstrate that the designer of an inductive device in accordance with the invention has a high degree of freedom as regards the choice of the shape of the core halves. As a result, the inductive device can be comparatively readily adapted to the requirements imposed by different applications.

Claims

1. An inductive device comprising a soft magnetic core which consists of two E-shaped core halves (1), each of which comprises three limbs (5,7) which are interconnected by a yoke (9), which core halves are arranged one against the other by way of the free ends of the limbs, the central limbs (7) extending within a coil former (3) on which a winding (29) is provided, the coil former (3) having connection strips (17) thereon, the outer limbs (5) extending between an upper boundary plane (25) and a lower boundary plane (27), the lower boundary plane (27) being above the lower boundary (34) of the device, and the upper and lower boundary planes extending parallel to the longitudinal directions of the outer limbs and the yokes, the distance (d) between the boundary planes being equal to the height (x) of the outer limbs in a direction perpendicular to the boundary planes, which height (x) is greater than the height (y) of the central limbs, the central limbs (7) having a symmetry plane (31) extending parallel to the boundary planes, characterized in that the central limbs (7) are substantially rectangular in cross-section in that the lower surfaces of the connection strips (17) define the lower boundary (34) of the body of the device, and in that the lower surface of the central limbs (7) are in a plane which is at such a distance from the lower boundary plane (27) that the symmetry plane (31) of the central limbs (7) is situated halfway between the upper boundary plane (25) and a plane (33) which extends parallel to the boundary planes (25,27) and is situated from 0.1 to 1 mm above the lower boundary (34) of the device.
2. A device as claimed in claim 1, characterized in that the distance between the lower boundary of the central limbs (7) and the lower boundary plane (27) amounts to at least 0.2 mm.
3. A device as claimed in claim 1 or 2, characterized in that the distance between the facing side faces



lower side. Thus, substantially no space which would increase the overall height of the inductive device remains above and below the winding 29. The distance of from 0.1 to 1 mm existing between the plane 33 and the lower side 34 of the coil former 3 is necessary to maintain, after the mounting of the inductive device on a printed circuit board, some clearance between this board and the winding 29 in order to allow air to flow around the winding for cooling purposes. This is because the lower side 34 of the coil former is generally mounted against the board.

The distance between the side faces 35 of the outer limbs 5 and the side faces 37 of the central limb 7 facing the former side faces is from 0.1 to 0.2 mm larger than the distance between the upper side of the central limb and the upper boundary plane 25. Consequently, between the central limb 7 and the outer limbs 5 exactly enough clearance exists to enable easy sliding of the coil former 3 with the winding 29 onto the central limb. If this clearance were greater, the space would no longer be completely filled by the winding 29, so that the inductive device would be unnecessarily wide. As a result, more material would be required for the formation of the core and the inductive device would occupy a larger surface area on a printed circuit board.

Because the winding 29 fills the space available substantially completely, hardly any room exists above and below this winding for guiding lead out wires from the winding to the connection pins 19. Therefore, approximately halfway the yoke 9 a recess 39 is provided at the upper side wherethrough the lead out wires (not shown) can be guided. Corresponding recesses 41 are provided at the upper side of the flanges 15.

The Figures 5 to 7 show a second embodiment of an inductive device in accordance with the invention. Elements in these Figures which correspond to elements of the first embodiment are denoted by the same reference numerals as used in the Figures 1, 2 and 4, be it that they are provided with an accent.

The major difference with respect to the first embodiment consists in that the lower boundary of the central limb 7' is situated below the lower boundary plane 27' instead of above this plane (see Figure 6). In this case the distance may again amount to from 0.2 to 2 mm. The height x' of the outer limbs 5' is smaller than the height x in the first embodiment. The height of the connection strips 17' is greater accordingly, so that in the second embodiment the symmetry plane 31' is also situated halfway between the upper boundary plane 25' and the plane 33' which extends parallel to the boundary planes 25', 27' and which is situated from 0.1 to 1 mm above the lower boundary 34' of the coil former 3'. As is clearly shown in Figure 7, the winding 29' substantially completely fills the space available between the planes 25' and 33' also in the second embodiment.

Figure 5 shows a portion 43 of the yoke 9' which is situated below the outer limbs 5'. At the top centre the connection strips 17' are provided with a recess 45 in order to prevent the cavity 13' from being partly closed due to their large height.

The two embodiments described demonstrate that the designer of an inductive device in accordance with the invention has a high degree of freedom as regards the choice of the shape of the core halves. As a result, the inductive device can be comparatively readily adapted to the requirements imposed by different applications.

Claims

1. An inductive device comprising a soft magnetic core which consists of two E-shaped core halves (1), each of which comprises three limbs (5,7) which are interconnected by a yoke (9), which core halves are arranged one against the other by way of the free ends of the limbs, the central limbs (7) extending within a coil former (3) on which a winding (29) is provided, the coil former (3) having connection strips (17) thereon, the outer limbs (5) extending between an upper boundary plane (25) and a lower boundary plane (27), the lower boundary plane (27) being above the lower boundary (34) of the device, and the upper and lower boundary planes extending parallel to the longitudinal directions of the outer limbs and the yokes, the distance (d) between the boundary planes being equal to the height (x) of the outer limbs in a direction perpendicular to the boundary planes, which height (x) is greater than the height (y) of the central limbs, the central limbs (7) having a symmetry plane (31) extending parallel to the boundary planes, characterized in that the central limbs (7) are substantially rectangular in cross-section in that the lower surfaces of the connection strips (17) define the lower boundary (34) of the body of the device, and in that the lower surface of the central limbs (7) are in a plane which is at such a distance from the lower boundary plane (27) that the symmetry plane (31) of the central limbs (7) is situated halfway between the upper boundary plane (25) and a plane (33) which extends parallel to the boundary planes (25,27) and is situated from 0.1 to 1 mm above the lower boundary (34) of the device.
2. A device as claimed in claim 1, characterized in that the distance between the lower boundary of the central limbs (7) and the lower boundary plane (27) amounts to at least 0.2 mm.
3. A device as claimed in claim 1 or 2, characterized in that the distance between the facing side faces



(35,37) of the central limbs (7) and the outer limbs (5) is from 0.1 to 0.2 mm greater than the distance between the upper side of the central limb and the upper boundary plane (25).

4. A device as claimed in any one of the preceding claims, characterized in that said winding (29) substantially entirely occupies the space between the upper boundary plane (25) and said plane (33) extending parallel to the boundary planes (25,27), thereby minimizing the height of said device for a given size of said winding (29).

Patentansprüche

1. Induktive Vorrichtung mit einem weichmagnetischen Kern, der aus zwei E-förmigen Kernhälften (1) mit je drei Schenkeln (5, 7) besteht, die durch ein Joch (9) miteinander verbunden sind, wobei die Kernhälften mit den freien Enden der Schenkel aneinander gestellt sind, wobei die Mittelschenkel (7) sich in einem Spulenkörper (3) erstrecken, auf dem eine Wicklung (29) angebracht ist, und wobei der Spulenkörper (3) Verbindungsstreifen (17) darauf enthält, die Außenschenkel (5) sich zwischen einer oberen Grenzebene (25) und einer unteren Grenzebene (27) erstrecken, die untere Grenzebene (27) über der unteren Grenzfläche (34) der Vorrichtung liegt, und die oberen und unteren Grenzebenen parallel zu den Längsrichtungen der Außenschenkel und der Joche verlaufen, der Abstand (d) zwischen den Grenzebenen gleich der Höhe (x) der Außenschenkel in der Richtung senkrecht zu den Grenzebenen ist, die Höhe (x) größer ist als die Höhe (y) der Mittelschenkel (7), die eine zu den Grenzebenen parallel verlaufende Symmetrieebene (31) besitzen, dadurch gekennzeichnet, daß die Mittelschenkel (7) im wesentlichen einen Rechteckquerschnitt haben, daß die unteren Flächen der Verbindungsstreifen (17) die untere Grenzfläche (34) des Körpers der Vorrichtung definieren, und daß die unteren Flächen der Mittelschenkel (7) so weit über oder unter der unteren Grenzebene (27) liegen, daß die Symmetrieebene (31) der Mittelschenkel (7) halbwegs zwischen der oberen Grenzebene (25) und einer zu den Grenzebenen (25, 27) parallel verlaufenden Ebene (33) liegt, und um 0,1 bis 1 mm über der unteren Begrenzung (34) der Vorrichtung liegt.
2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß der Abstand zwischen der unteren Begrenzung des Mittelschenkels (7) und der unteren Grenzebene (27) wenigstens 0,2 mm beträgt.

3. Vorrichtung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß der Abstand zwischen einander zugewandten Seitenflächen (35, 37) der Mittelschenkel (7) und der Außenschenkel (5) um 0,1 bis 0,2 mm größer ist als der Abstand zwischen der Oberseite des Mittelschenkels und der oberen Grenzebene (25).

4. Vorrichtung nach einer oder mehreren der vorangehenden Ansprüche, dadurch gekennzeichnet, daß die Wicklung (29) im wesentlichen den Raum zwischen der oberen Grenzebene (25) und der sich parallel zu den Grenzebenen (25, 27) erstreckenden Ebene (33) einnimmt, wobei die Höhe der Vorrichtung für eine vorgegebene Abmessung der Wicklung (29) minimiert wird.

Revendications

1. Dispositif inductif comportant un noyau magnétique doux constitué de deux moitiés de noyau en E (1) présentant chacune trois ailes (5, 7) reliées entre elles par une culasse (9), moitiés de noyau qui sont accolées par les extrémités libres des ailes, les ailes centrales (7) s'étendant dans une carcasse de bobine (3) sur laquelle est prévu un enroulement (29), la carcasse de bobine (3) portant des barrettes de connexion (17), les ailes extérieures (5) s'étendant entre des plans limites supérieur (25) et inférieur (27), le plan limite inférieur (27) étant situé au-dessus de la limite inférieure (34) du corps du dispositif et les plans limites supérieur et inférieur s'étendant parallèlement aux sens longitudinaux des ailes extérieures et des culasses, la distance (d) entre les plans limites, mesurée dans une direction perpendiculaire aux plans limites, étant égale à la hauteur (x) des ailes extérieures, hauteur (x) qui est supérieure à la hauteur (y) des ailes centrales, les ailes centrales (7) ayant un plan de symétrie (31) s'étendant parallèlement aux plans limites, caractérisé en ce que les ailes centrales (7) sont sensiblement rectangulaires en section transversale, en ce que les surfaces inférieures des barrettes de connexion (17) définissent la limite inférieure (34) du corps du dispositif, et en ce que les surfaces inférieures des ailes centrales (7) sont situées dans un plan séparé du plan limite inférieur (27) par une distance telle que le plan de symétrie (31) des ailes centrales (7) est situé à mi-distance entre le plan limite supérieur (25) et un plan (33) s'étendant parallèlement aux plans limites (25, 27) et qu'il est situé à une distance comprise entre 0,1 et 1 mm au-dessus de la limite inférieure (34) du dispositif.
2. Dispositif selon la revendication 1, caractérisé en



ce que la distance comprise entre la limite inférieure des ailes centrales (7) et le plan limite inférieure (27) est au moins égale à 0,2 mm.

3. Dispositif selon la revendication 1 ou 2, caractérisé en ce que la distance comprise entre les faces latérales opposées (35, 37) des ailes centrales (7) et des ailes extérieures (5) est supérieure de 0,1 à 0,2 mm à la distance comprise entre la face supérieure de l'aile centrale et le plan limite supérieur (25).
4. Dispositif selon l'une quelconque des revendications précédentes, caractérisé en ce que ledit enroulement (29) occupe à peu près entièrement l'espace compris entre le plan limite supérieur (25) et ledit plan (33), s'étendant parallèlement aux plans limites (25, 27), de façon à réduire à un minimum la hauteur dudit dispositif pour une taille donnée dudit enroulement (29).

5

10

15

20

25

30

35

40

45

50

55

6