

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 November 2003 (06.11.2003)

PCT

(10) International Publication Number
WO 03/092249 A2

(51) International Patent Classification⁷: **H04M**
(21) International Application Number: PCT/US03/09622
(22) International Filing Date: 27 March 2003 (27.03.2003)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
10/131,750 24 April 2002 (24.04.2002) US
(71) Applicant: **INTEL CORPORATION (a Delaware Corporation)** [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors: **KOROL, Victor**; 2/12 Gedera Street, #12, Petac-Tikva 49724 (IL). **BARAK, Ilan**; 20 Haggai Street, 44335 Kfar-Saba (IL).

(74) Agents: **TROP, Timothy, N.** et al.; Trop, Pruner & Hu, P.C., Suite 100, 8554 Katy Freeway, Houston, TX 77024 (US).

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONTROLLING OUTPUT POWER IN CELLULAR TELEPHONES

(57) Abstract: A cellular telephone utilizing a variable power voltage control oscillator (34) that may achieve a high dynamic range in output power. In some embodiments, a microprocessor (16) may be provided to adjust the amplitude of the variable power voltage control oscillator (34) in response to transmitted commands that may be received.



WO 03/092249 A2