

ALKOXYLATED SECONDARY ALCOHOL

[0001] The present invention relates to the general field of alkoxyated secondary alcohols.

[0002] Secondary alcohol alkoxyates are a family of compounds which offer a wide range of properties. Indeed, the applications are manifold. They may notably be used as solvent, hydrotrope or nonionic surfactant. They may also act as starting material to other compounds, such as etheramines or anionic surfactants obtained by phosphatation or sulfatation. Thus, secondary alcohol alkoxyates constitute a class of compounds that are of major industrial interest for many players.

[0003] Secondary alcohol alkoxyates are conventionally synthesized by means of basic catalysis, for example using potassium hydroxide. Another type of catalyst may also be used: the catalyst of dimetallic cyanide type, known as a DMC catalyst.

[0004] Various documents mention the alkoxylation of various compounds, including alcohols, by basic catalysis and/or by DMC catalysis.

[0005] For example, WO 2012/071149 describes the ethoxylation of poly-branched secondary alcohols by basic catalysis and/or DMC catalysis. In said document, the secondary alcohols comprise a large number of carbon atoms and numerous branches on the main chain.

[0006] Moreover, WO 2009/000852 describes a process for the alkoxylation of various compounds via DMC catalysis. Propylene oxide and/or butylene oxide react first with said compounds, in the presence of a DMC catalyst, and ethylene oxide is then grafted to the synthesized alkoxyate using the DMC catalyst initially present.

[0007] WO 2012/005897 notably discloses alcohols that are alkoxyated by means of a propoxyl block, followed by an ethoxyl block, in the presence of a DMC catalyst.

[0008] It is moreover known that alcohols of low molecular mass are poisons for the DMC catalyst.

[0009] This is one of the reasons for which industrial players favor the alkoxylation of long-chain or very highly branched alcohols to avoid the formation of stable chelates, in the presence of the DMC catalyst.

[0010] It should also be noted that industrial players favor a first step of alkoxylation with a propylene oxide and/or butylene oxide block, followed by a second step of alkoxylation using ethylene oxide.

[0011] The alkoxylation processes described in the two documents WO 2009/000852 and WO 2012/005897 as mentioned above are moreover performed according to this method.


[0012] It is also acknowledged that secondary alcohols have low reactivity when compared with primary alcohols. As a result, the industrialization of products obtained by alkoxyating secondary alcohols has never been reasonably envisaged.

[0013] In addition, at a time when the environmental challenges are truly high, it is interesting to envisage using a biobased or biodegradable reagent having a good ecotoxicological profile.

[0014] Thus, an alkoxyated, short-chain secondary alcohol is sought, the alkoxylation of which is performed via a simple process that allows low-cost industrial and commercial development. It would also be advantageous to develop alkoxyated secondary alcohols, the starting compound of which is a biobased and biodegradable reagent.

[0015] One object of the present invention is to propose a solution for resolving the problems mentioned above.

[0016] The subject of the present invention is a compound of formula (I) below:



in which:

- the groups R_1 and R_2 , which may be identical or different, represent, independently of each other, a linear, branched or cyclic, saturated or unsaturated hydrocarbon-based group, comprising from 1 to 6 carbon atoms, it being understood that the sum of the carbon atoms of the groups R_1 and R_2 ranges from 2 to 7, the groups R_1 and R_2 may also form, together with the carbon atom that bears them, a 6-, 7- or 8-membered ring,
- n is an integer between, limits inclusive, 1 and 100, preferably between 2 and 100, more preferably between 3 and 100, particularly between 4 and 100, more particularly between 5 and 100, preferably between 6 and 100, more preferably between 7 and 100, preferably between 8 and 100, more preferably between 9 and 100 and very preferably between 10 and 100.
- A represents a sequence of one or more units chosen from ethylene oxide, propylene oxide and butylene oxide units, and mixtures thereof,
- the group formed by R_1 , R_2 and the carbon atom to which R_1 and R_2 are attached has a degree of branching equal to 0, 1 or 2.

[0017] A subject of the present invention is also a process for preparing the compound of formula (I) according to the invention.

[0018] Another subject of the invention is the use of a catalyst of dimetallic cyanide (DMC) type for performing the alkoxylation of 2-octanol.

[0019] A subject of the invention is also the use of the compound of formula (I) according to the invention, as nonionic surfactant, low-foaming surfactant, wetting agent, foaming agent, hydrotrope, detergent, solvent, reactive solvent, coalescer, compatibilizer, emulsifying agent, dispersant, chemical intermediary, corrosion inhibitor, demulcent, plasticizer, sequestrants, mineral deposition inhibitor, ionic liquid, stabilizer, lubricant, bitumen additive, deinking additive, oil gellant, ore flotation collector, processing aid in the manufacture of plastics, antistatic agent, fertilizer coating additive, for plant protection, for treating textiles and for enhanced oil recovery, for the production of electrodes and electrolytes for batteries.

[0020] Other advantages and characteristics of the invention will become more clearly apparent on examining the detailed description.

[0021] It is specified that the expression "from ... to ..." used in the present description should be understood as including each of the limits mentioned.

[0022] For the purposes of the present invention, the term "ethylene oxide unit" refers to a unit derived from ethylene oxide after opening of the oxirane ring. For the purposes of the present invention, the term "propylene oxide unit" refers to a unit derived from propylene oxide after opening of the oxirane ring. For the purposes of the present invention, the term "butylene oxide unit" refers to a unit derived from butylene oxide after opening of the oxirane ring.

[0023] The compound according to the invention is of formula (I) as mentioned above.

[0024] In other words, the groups R_1 and R_2 , and the carbon atom to which they are attached, denote a C3-C8, preferably C4-C8, more particularly C5-C8, preferably C6-C8, secondary radical.

[0025] Preferably, the groups R_1 and R_2 , which may be identical or different, represent, independently of each other, methyl, ethyl, n-propyl, isopropyl, n-butyl, sec-butyl, pentyl or hexyl.

[0026] Preferably, the group formed by R_1 , R_2 and the carbon atom to which R_1 and R_2 are attached is chosen from the 2-octyl radical and the 4-methyl-2-pentyl radical. More particularly, the group formed by R_1 , R_2 and the carbon atom to which R_1 and R_2 are attached is the 2-octyl radical.

[0027] Advantageously, n is between, limits inclusive, 1 and 75, preferably between 2 and 75, more preferably between 3 and 75, particularly between 4 and 75, more

particularly between 5 and 75, preferably between 6 and 75, more preferably between 7 and 75, preferably between 8 and 75, more preferably between 9 and 75 and very preferably between 10 and 75.

[0028] Advantageously, n is between, limits inclusive, 1 and 50, preferably between 2 and 50, more preferably between 3 and 50, particularly between 4 and 50, more particularly between 5 and 50, preferably between 6 and 50, more preferably between 7 and 50, preferably between 8 and 50, more preferably between 9 and 50 and very preferably between 10 and 50.

[0029] Advantageously, n is between, limits inclusive, 1 and 30, preferably between 2 and 30, more preferably between 3 and 30, particularly between 4 and 30, more particularly between 5 and 30, preferably between 6 and 30, more preferably between 7 and 30, preferably between 8 and 30, more preferably between 9 and 30 and very preferably between 10 and 30. Preferably, n ranges from 2 to 30.

[0030] For the purposes of the present invention, the degree of branching denotes the total number of terminal methyl groups ($-\text{CH}_3$) present on the groups R_1 and R_2 minus 1. In other words, the degree of branching, denoted as D , is an integer equal to the difference between the sum of the terminal methyl groups ($-\text{CH}_3$) present on the groups R_1 and R_2 and 1. This equation may be expressed as follows:

$$D = \Sigma(\text{Me in } \text{R}_1 \text{ and } \text{R}_2) - 1$$

[0031] Thus, if the groups R_1 and R_2 comprise 2 methyl groups, the degree of branching is then 1.

$$D = \Sigma(\text{Me in } \text{R}_1 \text{ et } \text{R}_2) - 1 = 2 - 1 = 1$$

[0032] Preferably, the degree of branching is 1 or 2.

[0033] For example, the degree of branching of the 2-octyl radical is 1 and the degree of branching of the 4-methyl-2-pentyl radical is 2.

[0034] The compound of formula (I) comprises n ethylene oxide units, and a sequence including one or more units chosen from ethylene oxide, propylene oxide and butylene oxide units, and mixtures thereof.

[0035] According to a particular embodiment, when the compound of formula (I) includes a mixture of said different units, they may be distributed randomly, alternately or in blocks.

[0036] In a preferred embodiment of the invention, the compound of formula (I) comprises n ethylene oxide units and a sequence including one or more units chosen from ethylene oxide, propylene oxide and butylene oxide units, and mixtures thereof, said units possibly being distributed randomly, alternately or in blocks, at least one propylene oxide or butylene oxide unit being present in said sequence.

[0037] According to another preferred embodiment, A represents a sequence comprising at least one ethylene oxide unit and of at least one propylene oxide unit, distributed alternately, randomly or in blocks.

[0038] According to yet another preferred embodiment, A represents a sequence comprising at least one ethylene oxide unit and of at least one butylene oxide unit, distributed alternately, randomly or in blocks.

[0039] According to yet another preferred embodiment, A represents a sequence comprising at least one propylene oxide unit and of at least one butylene oxide unit, distributed alternately, randomly or in blocks.

[0040] A subject of the invention is also a process for preparing a compound of formula (I) as defined previously, comprising the following successive steps:

(a) reacting a secondary alcohol of formula (II) below: $R_1CH(OH)R_2$ (II), in which R_1 and R_2 are as defined previously, with n ethylene oxide(s), where n is as defined previously, in the presence of at least one catalyst of dimetallic cyanide type;

(b) reacting the product obtained from step (a) with one or more oxides chosen from ethylene oxide, propylene oxide and butylene oxide, and mixtures thereof, in the presence of at least one catalyst of dimetallic cyanide type.

[0041] Optionally, the product obtained from step (a) may be isolated. The process according to the invention has the advantage of synthesizing the compound of formula (I) under good safety conditions, which means that it can be performed on an industrial scale. Specifically, the operating conditions in terms of temperature and pressure are controlled by means of the process according to the invention. The exothermicity of the reaction is notably controlled.

[0042] The secondary alcohol of formula (II) has a degree of branching of 0, 1 or 2. Advantageously, the secondary alcohol of formula (II) has a weight-average molar mass ranging from 70 to 200 g/mol, preferably from 80 to 180 g/mol. The secondary alcohol of formula (II) is a C3-C8 and preferably C6-C8 alcohol.

[0043] The secondary alcohol of formula (II) may be chosen from 2-octanol and methylisobutylcarbinol, preferably 2-octanol. This alcohol is of particular interest in several respects. Specifically, it is a biobased, biodegradable product and has a good ecotoxicological profile. In addition, the boiling point of 2-octanol is high and its cost price is entirely reasonable.

[0044] According to a preferred embodiment, the secondary alcohol of formula (II) is used after drying, such that the water content in said alcohol is less than or equal to 200 ppm, preferably less than or equal to 100 ppm.

[0045] Preferably, the catalyst of dimetallic cyanide type may be of any nature known to a person skilled in the art. These catalysts are described in patents US 6 429 342, US 6 977 236 and PL 398 518. More particularly, the catalyst used is zinc hexacyanocobaltate, which is sold, for example, by the company Bayer under the name Arcol[®] or by the company Mexeo under the name MEO-DMC[®].

[0046] Advantageously, the content of catalyst of dimetallic cyanide type ranges from 1 to 1000 ppm relative to the content of secondary alcohol of formula (II), preferably from 1 to 500 ppm, preferably from 2 to 300 ppm, more preferentially from 5 to 200 ppm.

[0047] According to a preferred embodiment, the ethylene oxide/secondary alcohol of formula (II) mole ratio ranges from 1 to 100, preferably from 2 to 100, preferably from 3 to 100, preferably from 4 to 100, particularly from 5 to 100, more particularly from 6 to 100, preferably from 7 to 100, even more preferably from 8 to 100, preferentially from 9 to 100 and preferably from 10 to 100.

[0048] Preferably, the reaction temperature during step (a) ranges from 80 to 200°C, preferably from 100 to 180°C. The reaction pressure during step (a) may range from 0.01 MPa to 3 MPa, preferably from 0.02 MPa to 2 MPa.

[0049] Preferably, the reaction temperature during step (b) ranges from 80 to 200°C, preferably from 100 to 180°C. The reaction pressure during step (b) may range from 0.01 MPa to 3 MPa, preferably from 0.02 MPa to 2 MPa.

[0050] The duration of each of the steps (a) and (b) may range from a few minutes to a few hours, typically 5 minutes to 24 hours.

[0051] Preferably, the process according to the invention comprises a step of removing the residual oxides chosen from ethylene oxide, propylene oxide and butylene oxide, and mixtures thereof, used during the process according to the invention. Thus, this step may proceed between step (a) and step (b) and also after step (b).

[0052] For the purposes of the present invention, the term "residual oxide" means an oxide which has not reacted. Preferably, said step of removing the residual oxide is performed by cooking, i.e. by maintaining a temperature ranging from 70°C to 170°C, preferentially from 100°C to 160°C, in order to consume the residual oxide, and/or by means of a stripping step under an inert gas stream. Alternatively, said stripping step may be performed under vacuum.

[0053] Preferably, after said removal step, the mass content of residual oxide is less than or equal to 0.1% relative to the weight of compound of formula (I) obtained, preferentially less than or equal to 0.01%, more preferentially less than or equal to 0.001%.

[0054] Preferably, the process according to the invention comprises the following successive steps:

- (a1) mixing in a reactor at least one secondary alcohol of formula (II), preferably dried beforehand as described previously, and at least one catalyst of dimetallic cyanide type;
- (a2) gradually adding to the mixture n ethylene oxide(s), to obtain the ethoxylated secondary alcohol of formula (I);
- (a3) maintaining the reaction temperature until the pressure has stabilized;
- (a4) adding to the mixture one or more oxides chosen from ethylene oxide, propylene oxide and butylene oxide, and mixtures thereof;
- (a5) maintaining the reaction temperature until the pressure has stabilized;
- (a6) recovering the expected product after optional (but preferred) stripping.

[0055] Preferably, the process according to the invention comprises the following successive steps:

- (a1) mixing in a reactor at least one secondary alcohol of formula (II), preferably dried beforehand as described previously, and at least one catalyst of dimetallic cyanide type;
- (a2) gradually adding to the mixture n ethylene oxide(s), to obtain the ethoxylated secondary alcohol of formula (I);
- (a3) maintaining the reaction temperature until the pressure has stabilized;
- (a4) adding to the mixture one or more oxides chosen from propylene oxide and butylene oxide, and mixtures thereof;
- (a5) maintaining the reaction temperature until the pressure has stabilized;
- (a6) adding to the mixture one or more oxides chosen from ethylene oxide, propylene oxide and butylene oxide, and mixtures thereof;
- (a7) maintaining the reaction temperature until the pressure has stabilized;
- (a8) recovering the expected product after optional (but preferred) stripping.

[0056] Moreover, the process may be performed batchwise, semi-continuously or continuously. A person skilled in the art will know how to adapt the process for manufacturing the compound of formula (I) according to the invention according to the random, alternating or block distribution of the sequence A.

[0057] A subject of the invention is also the use of a catalyst of dimetallic cyanide type for performing the alkoxylation of 2-octanol.

[0058] A subject of the invention is also the use of the compound of formula (I) as defined previously, as nonionic surfactant, low-foaming surfactant, wetting agent, foaming agent, hydrotrope, detergent, solvent, reactive solvent, coalescer, compatibilizer, emulsifying agent, dispersant, chemical intermediary, corrosion inhibitor, demulcent, plasticizer, sequestrant, mineral deposition inhibitor, ionic liquid, stabilizer, lubricant,

bitumen additive, deinking additive, oil gellant, ore flotation collector, processing aid in the manufacture of plastics, antistatic agent, fertilizer coating additive, for plant protection, for treating textiles and for enhanced oil recovery, for the production of electrodes and electrolytes for batteries.

[0059] A subject of the present invention is also a composition comprising at least one compound of formula (I) as defined previously, and one or more aqueous, organic or aqueous-organic solvents, for instance water, alcohols, glycols, polyols, mineral oils, plant oils, and the like, alone or as mixtures of two or more thereof, in all proportions.

[0060] The composition according to the invention may also contain one or more additives and fillers that are well known to those skilled in the art, for instance, in a nonlimiting manner, anionic, cationic, amphoteric or nonionic surfactants, rheology modifiers, demulcents, deposition-inhibiting agents, antifoams, dispersants, pH control agents, colorants, antioxidants, preserving agents, corrosion inhibitors, biocides, and other additives, for instance sulfur, boron, nitrogen or phosphate products, and the like. The nature and amount of the additives and fillers may vary within wide proportions depending on the nature of the intended application and may readily be adapted by a person skilled in the art.

[0061] The invention is illustrated by the following examples, which are not in any way limiting.

EXAMPLES

[0062] The 2-octanol (CAS RN 123-96-6) used is the “refined” grade 2-octanol Oleris[®] (purity > 99%), sold by Arkema France.

Example 1: Ethoxylation of 2-octanol

[0063] 619 g (4.76 M) of 2-octanol dried to less than 200 ppm of water and 0.06 g (100 ppm) of catalyst DMC Arcol[®] are placed in a clean, dry 4 L autoclave. The reactor is closed and purged with nitrogen and the leaktightness under pressure is checked. The reactor is pressurized with nitrogen to 0.269 MPa at 20°C.

[0064] The reaction medium is brought to 120°C with stirring. At this temperature of 120°C, 40 g of ethylene oxide are introduced. When initiation of the reaction is observed, the rest of the ethylene oxide is introduced, i.e. 628 g (14.27 M) in total over 60 minutes at a temperature of 140°C-150°C. At the end of the addition, the temperature is maintained for 30 minutes and the residual ethylene oxide is then stripped out with nitrogen. The reactor is cooled to 60°C and 1240 g of alkoxyated 2-octanol comprising 3 ethylene oxide

units are recovered. The hydroxyl number (OHN) is 210 mg of KOH/g and the coloration is 26 Hz.

Example 2: Ethoxylation of methylisobutylcarbinol (MIBC)

[0065] 441 g (4.32 M) of MIBC dried to less than 200 ppm of water and 0.044 g (100 ppm) of catalyst DMC Arcol[®] are placed in a clean, dry 4 L autoclave. The reactor is closed and purged with nitrogen and the leaktightness under pressure is checked. The reactor is pressurized with nitrogen to 0.246 MPa at 28°C.

[0066] The reaction medium is brought to 120°C with stirring. At this temperature of 120°C, 40 g of ethylene oxide are introduced. When initiation of the reaction is observed at 141°C, the rest of the ethylene oxide is introduced, i.e. 380 g (8.64 M) in total over 40 minutes at a temperature of 140°C-150°C. At the end of the addition, the temperature is maintained for 60 minutes and the residual ethylene oxide is then stripped out with nitrogen. The reactor is cooled to 60°C and 815 g of alkoxyated methylisobutylcarbinol comprising 2 ethylene oxide units are recovered. (OHN): 290 mg of KOH/g and coloration: 3 Hz).

Example 3: Ethoxylation-propoxylation of 2-octanol


[0067] 1034 g (7.95 M) of 2-octanol dried to less than 200 ppm of water and 0.15 g (145 ppm) of catalyst DMC Arcol[®] are placed in a clean, dry 10 L autoclave. The reactor is closed and purged with nitrogen and the leaktightness under pressure is checked. The reactor is pressurized with nitrogen to 0.12 MPa at 27°C.

[0068] The reaction medium is brought to 120°C with stirring. At this temperature of 120°C, 35 g of ethylene oxide are introduced. When initiation of the reaction is observed, the rest of the ethylene oxide is introduced, i.e. 2098 g (47.68 M) in total over 4 hours at a temperature of 140°C-150°C. At the end of the addition, the temperature is maintained for 30 minutes to consume the residual ethylene oxide. A sample of the intermediate product withdrawn for analysis indicates the following features: OHN = 136 mg of KOH/g and coloration of 39 Hz.

[0069] The reaction is continued by introducing propylene oxide, i.e. 1844 g (31.18 M) in total over 3 hours. At the end of the reaction, the temperature is maintained at 140°C for 30 minutes to consume the residual propylene oxide, the system is then purged and degassed, and 4910 g of 2-octanol-6OE-4PO are recovered. OHN = 86 mg of KOH/g and coloration of 44 Hz.

CLAIMS

1. A compound of formula (I) below:



in which:

- the groups R_1 and R_2 , which may be identical or different, represent, independently of each other, a linear, branched or cyclic, saturated or unsaturated hydrocarbon-based group, comprising from 1 to 6 carbon atoms, it being understood that the sum of the carbon atoms of the groups R_1 and R_2 ranges from 2 to 7, the groups R_1 and R_2 may also form, together with the carbon atom that bears them, a 6-, 7- or 8-membered ring,
- n is an integer between, limits inclusive, 1 and 100, preferably between 2 and 100, more preferably between 3 and 100, particularly between 4 and 100, more particularly between 5 and 100, preferably between 6 and 100, more preferably between 7 and 100, preferably between 8 and 100, more preferably between 9 and 100 and very preferably between 10 and 100.
- A represents a sequence of one or more units chosen from ethylene oxide, propylene oxide and butylene oxide units, and mixtures thereof,
- the group formed by R_1 , R_2 and the carbon atom to which R_1 and R_2 are attached has a degree of branching equal to 0, 1 or 2.

2. The compound as claimed in claim 1, characterized in that the group formed by R_1 , R_2 and the carbon atom to which R_1 and R_2 are attached has a degree of branching of 1 or 2.

3. The compound as claimed in either of the preceding claims, characterized in that the group formed by R_1 , R_2 and the carbon atom to which R_1 and R_2 are attached is chosen from the 2-octyl radical and the 4-methyl-2-pentyl radical, more particularly the 2-octyl radical.

4. A process for preparing a compound of formula (I) as defined in any one of claims 1 to 3, comprising the following successive steps:

(a) reacting a secondary alcohol of formula (II) below: $R_1CH(OH)R_2$ (II), in which R_1 and R_2 are as defined in claim 1, with n ethylene oxide(s), where n is as defined in claim 1, in the presence of at least one catalyst of dimetallic cyanide type;

(b) reacting the product obtained from step (a) with one or more oxides chosen from ethylene oxide, propylene oxide and butylene oxide, and mixtures thereof, in the presence of at least one catalyst of dimetallic cyanide type.

5. The process as claimed in claim 4, characterized in that the secondary alcohol of formula (II) has a weight-average molar mass ranging from 70 to 200 g/mol, preferably from 80 to 180 g/mol.

6. The process as claimed in claim 4 or 5, characterized in that the secondary alcohol of formula (II) is chosen from 2-octanol and methylisobutylcarbinol, preferably 2-octanol.

7. The process as claimed in any one of claims 4 to 6, characterized in that the catalyst of dimetallic cyanide type is zinc hexacyanocobaltate.

8. The process as claimed in any one of claims 4 to 7, characterized in that the content of catalyst of dimetallic cyanide type ranges from 1 to 1000 ppm relative to the content of secondary alcohol of formula (II), preferably from 2 to 300 ppm, more preferentially from 5 to 200 ppm.

9. The process as claimed in any one of claims 4 to 8, characterized in that the ethylene oxide/secondary alcohol of formula (II) mole ratio ranges from 2 to 100, preferably from 3 to 100, more preferably from 4 to 100, particularly from 5 to 100, more particularly from 6 to 100, preferably from 7 to 100, even more preferably from 8 to 100, preferentially from 9 to 100 and preferably from 10 to 100.

10. The use of a catalyst of dimetallic cyanide type for performing the alkoxylation of 2-octanol.

11. The use of the compound of formula (I) as defined in any one of claims 1 to 3, as nonionic surfactant, low-foaming surfactant, wetting agent, foaming agent, hydrotrope, detergent, solvent, reactive solvent, coalescer, compatibilizer, emulsifying agent,

dispersant, chemical intermediary, corrosion inhibitor, demulcent, plasticizer, sequestrants, mineral deposition inhibitor, ionic liquid, stabilizer, lubricant, bitumen additive, deinking additive, oil gellant, ore flotation collector, processing aid in the manufacture of plastics, antistatic agent, fertilizer coating additive, for plant protection, for treating textiles and for enhanced oil recovery, for the production of electrodes and electrolytes for batteries.

12. A composition comprising at least one compound of formula (I) as defined in any one of claims 1 to 3, and one or more aqueous, organic or aqueous-organic solvents, optionally with one or more additives and fillers.