

EQUALIZING ELECTRODE PLATE WITH INSULATED SPLIT-FLOW CONDUCTIVE STRUCTURE

BACKGROUND OF THE INVENTION

5 (a) Field of the Invention

The present invention is an innovation for capacitors for electrostatic storage/discharge, or for rechargeable device with the function to transfer electric energy to chemical energy and/or transfer chemical energy to electric energy, or for electrode plate conductive structure used for fuel
10 cell; the electrode plate of the invention is used to constitute power supply and/or rechargeable device, and the feature of the invention relates to a specifically installed insulated split-flow conductive structure with internal conductive body coated with insulator, wherein one end of the insulated split-flow conductive structure connects to the electric energy
15 input/output terminal of the electrode plate, and another end connects to the electrode plate area where the current path more far away from the electric energy input/output terminal and/or the current passing with larger impedance, such as the surrounding part and/or the middle part and/or the bottom of the electrode plate, by way of the dedicated insulated split-flow
20 conductive structure connecting with the electric energy input/output terminal, the electric energy, between the electrode plate area where the current path more far away from the electric energy output terminal and/or the current passing with larger impedance and the electric energy input/output terminal, specifically transmits therebetween, and the
25 conductive body and the contacting electrochemical active substance in every area of the electrode plate can operate in more uniform current density when outputting and/or inputting electric energy.

(b) Description of the Prior Art

The conventional electrode plate is usually installed with one or
30 more electric energy input/output terminals at single side for outputting

electrical energy or charging, wherein the impedance between the electrode plate area at another side more far away from the electric energy input/output terminal and the electric energy input/output terminal, and the impedance between the electrode plate area more near the electric energy input/output terminal and the electric energy input/output terminal, the two impedances are different, thus there is a shortcoming that the current between the above both areas is uneven when outputting and/or inputting electric energy.

10 SUMMARY OF THE INVENTION

The present invention relates to an equalizing electrode plate with insulated split-flow conductive structure, which is a specifically installed insulated split-flow conductive structure with internal conductive body coated with insulator, wherein one end of the insulated split-flow conductive structure connects to the electric energy input/output terminal of the electrode plate, and another end connects to the electrode plate area in the electrode plate where the current path more far away from the electric energy input/output terminal and/or the current passing with larger impedance when outputting and/or inputting electric energy, by way of the dedicated insulated split-flow conductive structure connecting with the electric energy input/output terminal, the electric energy, between the electrode plate area where the current path more far away from the electric energy output terminal and/or the electrode plate area with larger impedance and the electric energy input/output terminal, specifically transmits therebetween, and the conductive body and the contacting electrochemical active substance in every area of the electrode plate can operate in more uniform current density when outputting and/or inputting electric energy; the present invention can be applied for plate type or laminate or winding type electrode plate, or for the electrode plate constituting primary battery, rechargeable secondary battery, capacitor, or

ultra-capacitor, or fuel cell for transferring chemical energy to electric energy.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 shows the first embodiment of the present invention;
Fig. 2 shows the second embodiment of the present invention;
Fig. 3 shows the third embodiment of the present invention;
Fig. 4 shows the fourth embodiment of the present invention;
Fig. 5 shows the fifth embodiment of the present invention;
10 Fig. 6 shows the sixth embodiment of the present invention;
Fig. 7 shows the seventh embodiment of the present invention;
Fig. 8 shows the eighth embodiment of the present invention;
Fig. 9 shows the ninth embodiment of the present invention;
Fig. 10 shows the tenth embodiment of the present invention;
15 Fig. 11 shows the eleventh embodiment of the present invention;
Fig. 12 shows the 12th embodiment of the present invention;
Fig. 13 shows the 13th embodiment of the present invention;
Fig. 14 shows the 14th embodiment of the present invention;
Fig. 15 shows the 15th embodiment of the present invention;
20 Fig. 16 shows the 16th embodiment of the present invention;
Fig. 17 shows the 17th embodiment of the present invention;
Fig. 18 shows the 18th embodiment of the present invention;
Fig. 19 shows the 19th embodiment of the present invention;
Fig. 20 shows the 20th embodiment of the present invention;
25 Fig. 21 shows the 21th embodiment of the present invention;
Fig. 22 shows the 22th embodiment of the present invention;
Fig. 23 shows the 23th embodiment of the present invention;
Fig. 24 shows the 24th embodiment of the present invention;
Fig. 25 shows the 25th embodiment of the present invention;
30 Fig. 26 shows the second embodiment of Fig. 25;

Fig. 27 shows the 27th embodiment of the present invention;
Fig. 28 shows the 28th embodiment of the present invention;
Fig. 29 shows the 29th embodiment of the present invention;
Fig. 30 shows the 30th embodiment of the present invention;
5 Fig. 31 shows the 31th embodiment of the present invention;
Fig. 32 shows the 32th embodiment of the present invention;
Fig. 33 shows the 33th embodiment of the present invention;
Fig. 34 shows the 34th embodiment of the present invention;
Fig. 35 shows the 35th embodiment of the present invention;
10 Fig. 36 shows the 36th embodiment of the present invention;
Fig. 37 shows the 37th embodiment of the present invention;
Fig. 38 shows the 38th embodiment of the present invention;
Fig. 39 shows the 39th embodiment of the present invention;
Fig. 40 shows the 40th embodiment of the present invention;
15 Fig. 41 shows the 41th embodiment of the present invention;
Fig. 42 shows the 42th embodiment of the present invention;
Fig. 43 shows the 43th embodiment of the present invention;
Fig. 44 shows the 44th embodiment of the present invention;
Fig. 45 shows the 45th embodiment of the present invention;
20 Fig. 46 shows the 46th embodiment of the present invention;
Fig. 47 shows the 47th embodiment of the present invention;
Fig. 48 shows the 48th embodiment of the present invention;
Fig. 49 shows the 49th embodiment of the present invention;
Fig. 50 shows the 50th embodiment of the present invention;
25 Fig. 51 shows the 51th embodiment of the present invention;
Fig. 52 shows the 52th embodiment of the present invention;
Fig. 53 shows the 53th embodiment of the present invention;
Fig. 54 shows the 54th embodiment of the present invention;
Fig. 55 shows the 55th embodiment of the present invention;
30 Fig. 56 shows the 56th embodiment of the present invention;

Fig. 57 shows the 57th embodiment of the present invention;
Fig. 58 shows the 58th embodiment of the present invention;
Fig. 59 shows the 59th embodiment of the present invention;
Fig. 60 shows the 60th embodiment of the present invention;
5 Fig. 61 shows the 61th embodiment of the present invention;
Fig. 62 shows the 62th embodiment of the present invention;
Fig. 63 shows the 63th embodiment of the present invention;
Fig. 64 shows the 64th embodiment of the present invention;
Fig. 65 shows the 65th embodiment of the present invention;
10 Fig. 66 shows the 66th embodiment of the present invention;
Fig. 67 shows the 67th embodiment of the present invention;
Fig. 68 shows the 68th embodiment of the present invention;
Fig. 69 shows the 69th embodiment of the present invention;
Fig. 70 shows the 70th embodiment of the present invention;
15 Fig. 71 shows the 71th embodiment of the present invention;
Fig. 72 shows the 72th embodiment of the present invention;
Fig. 73 shows the 73th embodiment of the present invention;
Fig. 74 shows the 74th embodiment of the present invention;
Fig. 75 shows the 75th embodiment of the present invention;
20 Fig. 76 shows the 76th embodiment of the present invention;
Fig. 77 shows the 77th embodiment of the present invention;
Fig. 78 shows the 78th embodiment of the present invention;
Fig. 79 shows the 79th embodiment of the present invention;
Fig. 80 shows the 80th embodiment of the present invention;
25 Fig. 81 shows the 81th embodiment of the present invention;
Fig. 82 shows the 82th embodiment of the present invention;
Fig. 83 shows the 83th embodiment of the present invention;
Fig. 84 shows the 84th embodiment of the present invention;
Fig. 85 shows the 85th embodiment of the present invention;
30 Fig. 86 shows the 86th embodiment of the present invention;

Fig. 87 shows the 87th embodiment of the present invention;
Fig. 88 shows the 88th embodiment of the present invention;
Fig. 89 shows the 89th embodiment of the present invention;
Fig. 90 shows the 90th embodiment of the present invention;
5 Fig. 91 shows the 91th embodiment of the present invention;
Fig. 92 shows the 92th embodiment of the present invention;
Fig. 93 shows the 93th embodiment of the present invention;
Fig. 94 shows the 94th embodiment of the present invention;
Fig. 95 is the A-A cross-section view of insulated split-flow
10 conductive structure 104, according to the present invention;
Fig. 96 is the B-B cross-section view of the conductive grid of the
electrode plate, according to the present invention;
Fig. 97 is the C-C cross-section view of the insulated split-flow
conductive structure 104, according to the present invention;
15 Fig. 98 is the D-D cross-section view of the insulated split-flow
conductive structure 104, according to the present invention;
Fig. 99 is the E-E cross-section view of the parallel insulated
split-flow conductive structures 104, according to the present invention;
Fig. 100 is the F-F cross-section view of two parallel insulated
20 split-flow conductive structures 1041 and 1042, in which at least one side
of conductive body 1045 of one insulated split-flow conductive structure
104 without insulator 1046 installed, according to the present invention;
Fig. 101 is the G-G cross-section view of two parallel laminated
insulated split-flow conductive structures 1041 and 1042, according to the
25 present invention;
Fig. 102 is a cross-section view of the insulated split-flow conductive
structure 1041 and/or the insulated split-flow conductive structure 1042
shown in Fig. 101, in which at least one side without insulator installed;
Fig. 103 is the H-H cross-section view of the insulated split-flow
30 conductive structure 104 pasted at the electrode plate at single side,

according to the present invention; and

Fig. 104 is a cross-section view of the insulated split-flow conductive structure 104 shown in Fig. 103, in which at least one side without insulator installed.

5

DESCRIPTION OF MAIN COMPONENT SYMBOLS

101: Electrode plate

102: Electric energy input/output terminal

103: Electrochemical active substance

10 104, 1041, 1042: Insulated split-flow conductive structure

1023: Electric energy input/output terminal for independently inputting/outputting electric energy

1045: Conductive body

1046: Insulator

15

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention relates to an equalizing electrode plate with insulated split-flow conductive structure, which is specifically installed insulated split-flow conductive structure with one or more internal
20 conductive bodies coated with insulators, wherein one end of the insulated split-flow conductive structure connects to the electric energy input/output terminal of the electrode plate, and another end connects to the surrounding part and/or the middle part and/or the bottom of the electrode plate, the electrode plate area where the current path more far away from
25 the electric energy input/output terminal and/or the current passing with larger impedance when outputting and/or inputting electric energy, by way of the dedicated insulated split-flow conductive structure connecting with the electric energy input/output terminal, the electric energy, between the electrode plate area where the current path more far away from the
30 electric energy output terminal and/or the electrode plate area with larger

impedance and the electric energy input/output terminal, specifically transmits therebetween, and the conductive body and the contacting electrochemical active substance in every area of the electrode plate can operate in more uniform current density when outputting and/or inputting electric energy.

Figs. 1 to 70 show the principles and foundations of the equalizing electrode plate with insulated split-flow conductive structure, according to the present invention; the following embodiments are provided to facilitate the description, and the main components include:

---Electrode plate 101: related to positive and/or negative electrode plate constituted by grid sheet, radiative grid sheet, laminate, or winding type electrode plate, wherein the positive pole and the negative pole of the electrode plate is constituted by same or different conductive material;

---Electric energy input/output terminal 102: made of the electrode plate extended or being additionally installed, to connect the electrode plate 101 at one or more sides, wherein every side is installed with one or more electric energy input/output terminals to be the interface for the electrode plate outputting and/or inputting electric energy, and the conductive material of the electric energy input/output terminal and that of the electrode plate are same or different;

---Electrochemical active substance 103: related to electrochemical material in gaseous state, liquid state, colloidal state, or solid state; and

---Insulated split-flow conductive structure 104: constituted by a conductive body 1045, whose material is same as or different from that of the electrode plate, around covered or draped with an insulator 1046, wherein one or more insulated split-flow conductive structures 104 are installed along the side of the electrode plate and/or into the central area of the electrode plate, one end of the insulated split-flow conductive structure 104 connects in a manner of conductive features to the electric energy input/output terminal 102 of the electrode plate 101 or the

conductive body of the electrode plate, including welding, heat sealing, spot welding, mechanical riveting, locking, clamping, and blocking, and another end connects in a manner of conductive features to the electrode plate area of the electrode plate where the current path more far away from the electric energy input/output terminal 102 and/or the current passing with larger impedance when outputting and/or inputting electric energy, including welding, heat sealing, spot welding, mechanical riveting, locking, clamping and blocking, for specifically transmitting the electric energy therebetween.

10 For the equalizing electrode plate with insulated split-flow conductive structure, which is applied for a positive and negative electrode plate, including grid sheet, radiative grid sheet, laminate, or winding type electrode plate constituting primary battery, rechargeable secondary battery, capacitor, or ultra-capacitor, or rechargeable device or
15 fuel cell for transferring electric energy to chemical energy or chemical energy to electric energy.

For the equalizing electrode plate with insulated split-flow conductive structure, the conductive body 1045 of the insulated split-flow conductive structure 104 is made of the following one or more ways,
20 including:

- (1) made of the same material as that of the electrode plate;
- (2) made of the different material, which is well conductive material with the specific resistance lower than that of the electrode plate;
- (3) made of the electrode plate material coated with the conductive
25 body with the specific resistance lower than that of the electrode plate material; and
- (4) made of two or more different materials from that of the electrode plate, wherein the materials are ring coating with each other for two or more layers.

30 The combination of the insulated split-flow conductive structure 104

and the electrode plate 101 is constituted by the following one or more ways, including:

(1) the insulated split-flow conductive structure 104 and the electrode plate 101 are integrated, wherein the conductive body 1045 of the insulated split-flow conductive structure 104 is around covered or coated with the insulator 1046, or draped with the insulator 1046, such as epoxy resin, insulating glue, varnish, insulating paint, or PVF, etc.; one end of the insulated split-flow conductive structure 104 and the electrode plate area set in the electrode plate 101 for directly transmitting current to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101 are integrated, another end and the electric energy input/output terminal 102 or the conductive body of the electrode plate 101 are integrated, and the current is directly transmitted in lower impedance therebetween; the insulated split-flow conductive structure 104 in flat or curved shape matches with the electrode plate 101 to form a part of the electrode plate for being co-located in the groove structural body or case of the applying device for electrochemical action;

(2) one end of the insulated split-flow conductive structure 104 and the electrode plate area set in the electrode plate 101 for directly transmitting current to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101 are integrated, wherein the conductive body 1045 of the insulated split-flow conductive structure 104 is around covered or coated with the insulator 1046, or draped with the insulator 1046, such as epoxy resin, insulating glue, insulating paint, varnish, or PVF, another end is welded, riveted, clamped, or locked at the electric energy input/output terminal 102 or the conductive body of the electrode plate 101, and the current is directly transmitted in lower impedance therebetween; the insulated split-flow conductive structure 104 in flat or curved shape matches with the electrode plate 101 to form a part of the electrode plate for being co-located in the groove structural body or

case of the applying device for electrochemical action;

(3) the insulated split-flow conductive structure 104 in the type of independent conductive line or conductive strip constitutes the conductive body 1045, the conductive body 1045 is around covered or coated with the insulator 1046, or draped with the insulator 1046, such as epoxy resin, insulating glue, insulating paint, varnish, or PVF, and the two ends of the conductive body 1045 of the insulated split-flow conductive structure 104 respectively connect in a manner of conductive features, including welding, heat sealing, spot welding, mechanical riveting, locking, clamping, and blocking, wherein one end connects to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate, and another end connects to the electrode plate area set in the electrode plate 101 for directly transmitting current to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101 and parallels the electrode plate 101; when outputting and/or inputting electric energy, the current is directly transmitted in lower impedance between the electrode plate area set in the electrode plate 101 for directly transmitting current to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101 and the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101; and the insulated split-flow conductive structure 104 in flat or curved shape matches with the electrode plate 101 to form a part of the electrode plate for being co-located in the groove structural body or case of the applying device for electrochemical action;

(4) the insulated split-flow conductive structure 104 in the type of independent conductive line or conductive strip constitutes the conductive body 1045, the conductive body 1045 is around covered or coated with the insulator 1046, or draped with the insulator 1046, such as epoxy resin, insulating glue, insulating paint, varnish, or PVF, and the two ends of the conductive body 1045 of the insulated split-flow conductive structure 104

respectively connect in a manner of conductive features, including welding, heat sealing, spot welding, mechanical riveting, locking, clamping, and blocking, wherein one end connects to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate, and another end connects to the electrode plate area set in the electrode plate 101 for directly transmitting current to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101; the insulated split-flow conductive structure 104 is installed and superimposed on one or two sides of the electrode plate 101; when outputting and/or inputting electric energy, the current in the current path is directly transmitted in lower impedance between the electrode plate area set in the electrode plate 101 for directly transmitting current to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101 and the electric energy input/output terminal 102 or the conductive body of the electrode plate 101; and the insulated split-flow conductive structure 104 in flat or curved shape matches with the electrode plate 101 to form a part of the electrode plate for being co-located in the groove structural body or case of the applying device for electrochemical action; and

(5) the independent insulated split-flow conductive structure 104 is installed at the external part of the groove structural body or case of the electrode plate, wherein the independent insulated split-flow conductive structure 104 includes the conductive body 1045 of the insulated split-flow conductive structure 104 covered or coated with the insulator 1046, or draped with the insulator 1046, such as epoxy resin, insulating glue, insulating paint, varnish, or PVF, and the electrode plate area set in the electrode plate 101 for directly transmitting current to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101; in the current path when outputting and/or inputting electric energy, between the electrode plate area set in the electrode plate

101 for directly transmitting current to the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101 and the electric energy input/output terminal 102 and/or the conductive body of the electrode plate 101, the electric energy is directly transmitted in lower impedance therebetween, or the above both separate and respectively operate for outputting and/or inputting electric energy.

For the equalizing electrode plate with insulated split-flow conductive structure, based on the above principles, which is applied for various structural arrangements, and the following embodiments are provided only for descriptions but not limited to the applications.

For the equalizing electrode plate with insulated split-flow conductive structure, as shown in Figs. 1 to 10, which is constituted by a grid sheet, radiative grid sheet, laminate, or winding type electrode plate, wherein the single side of the electrode plate 101 is installed with one or more electric energy input/output terminals 102, and the electric energy input/output terminal 102 downward extends to one or two sides of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, including extending to the intermediate part of the side of the electrode plate 101; and/or extending to the bottom of the side of the electrode plate 101; and/or extending to the bottom of electrode plate 101 and further extending to the bottom edge of electrode plate 101.

Fig. 1 shows the first embodiment of the present invention; as shown in Fig. 1, the electric energy input/output terminal 102 is installed at the left upper of the electrode plate 101, extends along the upside of the electrode plate 101 to the right side more far away from the electric energy input/output terminal 102, and further downward extends from the right side of the electrode plate 101 to the bottom or near the bottom for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the right side bottom of the electrode plate 101 and the electric energy input/output terminal 102.

Fig. 2 shows the second embodiment of the present invention; as shown in Fig. 2, the electric energy input/output terminal 102 is installed at the left upper of the electrode plate 101, and extends along the left upside of the electrode plate 101 and along the left side of the electrode plate 101 to the bottom of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the bottom of the electrode plate 101 and the electric energy input/output terminal 102.

Fig. 3 shows the third embodiment of the present invention; as shown in Fig. 3, the electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, and extends along the upside of the electrode plate 101 to the right side and the right side near the intermediate part for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the intermediate parts of the two sides of the electrode plate 101 and the electric energy input/output terminal 102; and the electric energy input/output terminal 102 extends along the upside of the electrode plate 101 to the left side and the left side bottom of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the bottom of the electrode plate 101 and the electric energy input/output terminal 102.

Fig. 4 shows the fourth embodiment of the present invention; as shown in Fig. 4, the electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, extends along the upside of the electrode plate 101 to the left and right sides, and further extends to the bottom for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the bottoms of two sides of the electrode plate 101 and the electric energy input/output terminal 102.

Fig. 5 shows the fifth embodiment of the present invention; as shown

in Fig. 5, the electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, and extends along the upside of the electrode plate 101 to two sides for installing with the insulated split-flow conductive structure 104, in which the insulated split-flow conductive structure 104 is installed at the left side of the electrode plate 101 more near the electric energy input/output terminal 102 extends to the bottom near the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted between the intermediate part of the bottom of the electrode plate 101 and the electric energy input/output terminal 102; and the insulated split-flow conductive structure 104 is installed at the right side of the electrode plate 101 more far away from the electric energy input/output terminal 102 extends to the intermediate part of the right side near the bottom of the electrode plate 101, thus the input/output current is direct transmitted between the intermediate part of the right side near the bottom of the electrode plate 101 and the electric energy input/output terminal 102.

Fig. 6 shows the sixth embodiment of the present invention; as shown in Fig. 6, two electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, in which the electric energy input/output terminal 102 installed at the upside near the left side is more near the left side of the electrode plate 101, the electric energy input/output terminal 102 installed at the upside near the right side is more near the right side of the electrode plate 101, and the electric energy input/output terminal 102 installed at the upside near the right side extends along the intermediate part of the right side of the electrode plate 101 to the position near the bottom for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the intermediate part of the right side near the bottom of the electrode plate 101 and the electric energy input/output terminal 102 installed at the

upside near the right side of the electrode plate 101.

Fig. 7 shows the seventh embodiment of the present invention; as shown in Fig. 7, two electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, in which the electric energy input/output terminal 102 installed at the upside near the left side is more near the left side of the electrode plate 101, the electric energy input/output terminal 102 installed at the upside near the right side is more near the right side of the electrode plate 101, and the electric energy input/output terminal 102 installed at the upside near the right side extends along the right side of the electrode plate 101 to the intermediate part of the bottom for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the intermediate part of the bottom of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside near the right side of the electrode plate 101.

Fig. 8 shows the eighth embodiment of the present invention; as shown in Fig. 8, two electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, in which the electric energy input/output terminal 102 installed at the upside near the left side is more near the left side of the electrode plate 101, the electric energy input/output terminal 102 installed at the upside near the right side is more near the right side of the electrode plate 101; the electric energy input/output terminal 102 installed at the upside near the left side downward extends along the left side of the electrode plate 101 to the position near the bottom for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the left side near the bottom of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside near the left side

of the electrode plate 101; and the electric energy input/output terminal 102 installed at the upside near the right side downward extends along the right side of the electrode plate 101 to the position near the bottom for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the right side near the bottom of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside near the right side of the electrode plate 101.

Fig. 9 shows the ninth embodiment of the present invention; as shown in Fig. 9, two electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, in which the electric energy input/output terminal 102 installed at the upside near the left side is more near the left side of the electrode plate 101, the electric energy input/output terminal 102 installed at the upside near the right side is more near the right side of the electrode plate 101; the electric energy input/output terminal 102 installed at the upside near the left side downward extends along the left side of the electrode plate 101 to the bottom edge near the position of the intermediate part for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the bottom edge near the position of the intermediate part of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside near the left side of the electrode plate 101; and the electric energy input/output terminal 102 installed at the upside near the right side downward extends along the right side of the electrode plate 101 to the bottom edge near the position of the intermediate part for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the bottom edge near the position of the intermediate part of the

electrode plate 101 and the electric energy input/output terminal 102 installed at the upside near the right side of the electrode plate 101; the bottom segment of the insulated split-flow conductive structure 104 connects or links with that of the above insulated split-flow conductive structure 104 downward extending from the left side of the electrode plate 101, and is conductive with the electrode plate 101.

Fig. 10 shows the tenth embodiment of the present invention; as shown in Fig. 10, the electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, and downward extends along the left side and the right side of the electrode plate 101 to the position near the bottom for installing with two insulated split-flow conductive structures 104, thus the input/output current is directly transmitted between two sides near the bottom of the electrode plate 101 and the electric energy input/output terminal 102; and the segments of the insulated split-flow conductive structures 104 installed at two sides near the intermediate part of the bottom are respectively installed with the insulated split-flow conductive structure 104 with shunt function extending inward the electrode plate 101, thus the input/output current is directly transmitted between the segments, near the bottom and the intermediate part of the electrode plate 101, with shunt function extending inward the electrode plate 101, and the electric energy input/output terminal 102.

For the equalizing electrode plate with insulated split-flow conductive structure, as shown in Figs. 11 to 14, which is constituted by a grid sheet, radiative grid sheet, laminate, or winding type electrode plate, wherein the single side of the electrode plate 101 is installed with one or more electric energy input/output terminals 102, and the electric energy input/output terminal 102 downward extends to one or two sides of the electrode plate 101 for installing with two or more parallel insulated split-flow conductive structures 104, each insulated split-flow conductive

structure 104 downward extends to the intermediate part of the side of the electrode plate 101, and/or to the bottom of the side of the electrode plate 101, and/or through the bottom of the side of the electrode plate 101 and further to the bottom edge of electrode plate 101.

5 Fig. 11 shows the eleventh embodiment of the present invention; as shown in Fig. 11, the electric energy input/output terminal 102 is installed at the upside near the left side of the electrode plate 101, and extends along the upside to the right side of the electrode plate 101 to be parallel, or as shown in Fig. 99, two insulated split-flow conductive structures
10 1041 and 1042 are laminated and installed, in which the insulated split-flow conductive structure 1041 extends along the upside of the electrode plate 101 to the right side near the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted between the intermediate part of the right side of the electrode plate 101
15 and the electric energy input/output terminal 102; and the insulated split-flow conductive structure 1042 extends along the upside of the electrode plate 101 to the right side near the bottom of the electrode plate 101, thus the input/output current is direct transmitted between the right side bottom of the electrode plate 101 and the electric energy input/output
20 terminal 102.

 Fig. 12 shows the 12th embodiment of the present invention; as shown in Fig. 12, the electric energy input/output terminal 102 is installed at the upside near the left side of the electrode plate 101, and extends along the upside to the right side of the electrode plate 101 to be parallel,
25 or as shown in Fig. 99, two insulated split-flow conductive structures 1041 and 1042 are laminated and installed, in which the insulated split-flow conductive structure 1041 extends along the upside of the electrode plate 101 to the right side near the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted
30 between the intermediate part of the right side of the electrode plate 101

and the electric energy input/output terminal 102; and the insulated split-flow conductive structure 1042 extends along the upside of the electrode plate 101 to the right side near the bottom of the electrode plate 101, thus the input/output current is direct transmitted between the right side bottom of the electrode plate 101 and the electric energy input/output terminal 102; and the electric energy input/output terminal 102 extends along the upside to the left side of the electrode plate 101, and further downward extends to the left side bottom of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the left side bottom of the electrode plate 101 and the electric energy input/output terminal 102.

Fig. 13 shows the 13th embodiment of the present invention; as shown in Fig. 13, the electric energy input/output terminal 102 is installed at the upside near the left side of the electrode plate 101, and extends along the upside to the right side of the electrode plate 101 to be parallel, or as shown in Fig. 99, two insulated split-flow conductive structures 1041 and 1042 are laminated and installed, in which the insulated split-flow conductive structure 1041 extends along the upside of the electrode plate 101 to the right side near the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted between the intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102; and the insulated split-flow conductive structure 1042 extends along the upside of the electrode plate 101 to the right side near the bottom of the electrode plate 101, thus the input/output current is direct transmitted between the right side bottom of the electrode plate 101 and the electric energy input/output terminal 102; and

the electric energy input/output terminal 102 extends along the upside to the left side of the electrode plate 101 for installing with two insulated split-flow conductive structures 1041 and 1042, in which the

insulated split-flow conductive structure 1041 extends along the upside of the electrode plate 101 to the left side near the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted between the intermediate part of the left side of the electrode plate 101 and the electric energy input/output terminal 102; and the insulated split-flow conductive structure 1042 extends along the upside of the electrode plate 101 to the left side near the bottom of the electrode plate 101, thus the input/output current is direct transmitted between the left side bottom of the electrode plate 101 and the electric energy input/output terminal 102.

Fig. 14 shows the 14th embodiment of the present invention; as shown in Fig. 14, the electric energy input/output terminal 102 is installed at the upside near the right side of the electrode plate 101, and extends along the upside to the right side of the electrode plate 101 to be parallel, or as shown in Fig. 99, two insulated split-flow conductive structures 1041 and 1042 are laminated and installed, in which the insulated split-flow conductive structure 1041 extends along the upside of the electrode plate 101 to the region where the right side near the intermediate part and bending inwards into the electrode plate 101, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the region where the intermediate part of the right side and bending inwards into the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside near the right side of the electrode plate 101; and the insulated split-flow conductive structure 1042 extends along the upside of the electrode plate 101 to the right side near the bottom of the electrode plate 101, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the right side bottom of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside near the right side of the electrode plate 101; and

the electric energy input/output terminal 102 extends along the upside near the left side to the left side of the electrode plate 101 for installing with two insulated split-flow conductive structures 1041 and 1042, in which the insulated split-flow conductive structure 1041 extends
5 along the upside of the electrode plate 101 to the region where the left side near the intermediate part and bending inwards into the electrode plate 101, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the region where the intermediate part of the left side and bending inwards into the electrode
10 plate 101 and the electric energy input/output terminal 102 installed at the upside near the left side of the electrode plate 101; and the insulated split-flow conductive structure 1042 extends along the upside of the electrode plate 101 to the left side near the bottom of the electrode plate 101, thus the input/output current is direct transmitted between the left
15 side bottom of the electrode plate 101 and the electric energy input/output terminal 102.

For the equalizing electrode plate with insulated split-flow conductive structure, as shown in Figs. 15 to 21, which is constituted by a grid sheet, radiative grid sheet, laminate, or winding type electrode plate,
20 wherein one or more electric energy input/output terminals 102 are installed at each of two or more sides of the electrode plate 101, and the electric energy input/output terminal 102 downward extends to one or two sides of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, including extending to the intermediate part of
25 the side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104; and/or extending to the bottom of the side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104; and/or extending to the bottom of the side of the electrode plate 101 and further to the bottom edge of electrode plate 101.

30 Fig. 15 shows the 15th embodiment of the present invention; as

shown in Fig. 15, the electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, and downward extends along the left side of the upside to the intermediate part of the left side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the the intermediate part of the left side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside of the electrode plate 101; and the electric energy input/output terminal 102 extends along the upside of the electrode plate 101 to the position near the right side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside of the electrode plate 101; and

the electric energy input/output terminal 102 is installed at the downside of the electrode plate 101, and upward extends from the right side of the electric energy input/output terminal 102 to the intermediate part of the right side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the the intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the downside of the electrode plate 101; the electric energy input/output terminal 102 leftward extends along the downside of the electrode plate 101 to the position near the left lower of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the left lower of the electrode plate 101 and the electric energy input/output terminal 102; and the electric energy input/output terminal 102 extends along the downside of the electrode plate 101 and from the downside to the intermediate part of the right side of the electrode plate 101 for installing

with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the downside of the electrode plate 101.

Fig. 16 shows the 16th embodiment of the present invention; as shown in Fig. 16, the electric energy input/output terminal 102 is installed at the left side of the upside of the electrode plate 101, and the electric energy input/output terminal 102 is installed at the right side of the downside of the upside of the electrode plate 101, and the insulated split-flow conductive structure 104 is installed between the left side of the electric energy input/output terminal 102 installed at the upside of the electrode plate 101 and the segment extends along the bottom edge to the electric energy input/output terminal 102 installed at the downside of the electrode plate 101, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the upside of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside of the electrode plate 101.

Fig. 17 shows the 17th embodiment of the present invention; as shown in Fig. 17, the electric energy input/output terminal 102 is installed at the left side of the upside of the electrode plate 101, and downward extends along the right side of the upside of the electric energy input/output terminal 102 installed at the upside of the electrode plate 101 to the position near the intermediate part of the right side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the position near the intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside of the electrode plate 101; and

the electric energy input/output terminal 102 is installed at the right

side of the downside of the electrode plate 101, and leftward and upward extends along the downside of the electrode plate 101 to the position near the intermediate part of the left side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the position near the intermediate part of the left side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the downside of the electrode plate 101.

Fig. 18 shows the 18th embodiment of the present invention; as shown in Fig. 18, the electric energy input/output terminal 102 is installed at the left side of the upside of the electrode plate 101, and downward extends along the right side of the electric energy input/output terminal 102 installed at the upside of the electrode plate 101 to the position near the intermediate part of the right side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the position near the intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside of the electrode plate 101; and the electric energy input/output terminal 102 installed at the upside of the electrode plate 101 leftward and downward extends along the upside of the electrode plate 101 to the position near the intermediate part of the left side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the position near the intermediate part of the left side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the upside of the electrode plate 101; and

the electric energy input/output terminal 102 is installed at the right side of the downside of the electrode plate 101, and leftward and upward extends along the downside of the electrode plate 101 to the position near

the intermediate part of the left side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the position near the intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the downside of the electrode plate 101; and the electric energy input/output terminal 102 installed at the downside of the electrode plate 101 rightward and upward extends along the downside of the electrode plate 101 to the position near the intermediate part of the right side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the position near the intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the downside of the electrode plate 101.

Fig. 19 shows the 19th embodiment of the present invention; as shown in Fig. 19, two electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, in which the electric energy input/output terminal 102 installed at position near the left side of the upside is more near the left side of the upside of the electrode plate 101, and the electric energy input/output terminal 102 installed at position near the right side of the upside is more near the right side of the upside of the electrode plate 101; and two electric energy input/output terminals 102 are installed at the downside of the electrode plate 101, in which the electric energy input/output terminal 102 installed at position near the right side of the downside is more near the right side of the downside of the electrode plate 101, and the electric energy input/output terminal 102 installed at position near the left side of the downside is more near the left side of the downside of the electrode plate 101; the electric energy input/output terminal 102 installed at the position near the left side of the upside downward extends along the upside of the electrode plate 101 to

the left side, and along the left side of the electrode plate 101 to the
downside of the electrode plate 101, and rightward extends from the
downside of the electrode plate 101 to connect the electric energy
input/output terminal 102 installed at the position near the left side of the
5 downside for installing with the insulated split-flow conductive structure
104, thus the input/output current is direct transmitted between the electric
energy input/output terminal 102 installed at the position near the left side
of the upside and the electric energy input/output terminal 102 installed at
the position near the left side of the downside.

10 Fig. 20 shows the 20th embodiment of the present invention; as
shown in Fig. 20, two electric energy input/output terminals 102 are
installed at the upside of the electrode plate 101, in which the electric
energy input/output terminal 102 installed at position near the left side of
the upside is more near the left side of the electrode plate 101, and the
15 electric energy input/output terminal 102 installed at position near the
right side of the upside is more near the right side of the electrode plate
101; and two electric energy input/output terminals 102 are installed at the
downside of the electrode plate 101, in which the electric energy
input/output terminal 102 installed at position near the right side of the
20 downside is more near the right side of the electrode plate 101, and the
electric energy input/output terminal 102 installed at position near the left
side of the downside is more near the left side of the electrode plate 101;
the electric energy input/output terminal 102 installed at the position near
the left side of the upside downward extends along the neighboring left
25 side to the electric energy input/output terminal 102 installed at the
position near the left side of the downside of the left side of the
neighboring bottom edge for installing with the insulated split-flow
conductive structure 104, thus the input/output current is direct
transmitted between the electric energy input/output terminal 102 installed
30 at the position near the left side of the upside and the electric energy

input/output terminal 102 installed at the position near the left side of the downside; and the electric energy input/output terminal 102 installed at the position near the right side of the upside downward extends along the neighboring right side to the electric energy input/output terminal 102
5 installed at the position near the right side of the downside of the right side of the neighboring bottom edge for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the position near the right side of the upside and the electric energy
10 input/output terminal 102 installed at the position near the right side of the downside.

Fig. 21 shows the 21th embodiment of the present invention; as shown in Fig. 21, two electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, in which the electric
15 energy input/output terminal 102 installed at position near the left side of the upside is more near the left side of the electrode plate 101, and the electric energy input/output terminal 102 installed at position near the right side of the upside is more near the right side of the electrode plate 101; the insulated split-flow conductive structure 104 is installed along
20 the left side of the electric energy input/output terminal 102 installed at the position near the left side of the upside to the position near the intermediate part of the left side, thus the input/output current is direct transmitted between the position near the intermediate part of the left side of the electrode plate 101 and the electric energy input/output terminal
25 102 installed at the position near the left side of the upside; and the insulated split-flow conductive structure 104 is installed along the right side of the electric energy input/output terminal 102 installed at the position near the right side of the upside to the position near the intermediate part of the right side, thus the input/output current is direct
30 transmitted between the position near the intermediate part of the right

side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the right side of the upside; and
two electric energy input/output terminals 102 are installed at the
downside of the electrode plate 101, in which the electric energy
input/output terminal 102 installed at position near the right side of the
downside is more near the right side of the downside of the electrode plate
101, and the electric energy input/output terminal 102 installed at position
near the left side of the downside is more near the left side of the electrode
plate 101; the insulated split-flow conductive structure 104 is installed
along the left side of the electric energy input/output terminal 102
installed at the position near the left side of the downside to the position
near the intermediate part of the left side of the electrode plate 101, thus
the input/output current is direct transmitted between the position near the
intermediate part of the left side of the electrode plate 101 and the electric
energy input/output terminal 102 installed at the position near the left side
of the downside; and the insulated split-flow conductive structure 104 is
installed along the right side of the electric energy input/output terminal
102 installed at the position near the right side of the downside to the
position near the intermediate part of the right side of the electrode plate
101, thus the input/output current is direct transmitted between the
position near the intermediate part of the right side of the electrode plate
101 and the electric energy input/output terminal 102 installed at the
position near the right side of the downside.

For the equalizing electrode plate with insulated split-flow
conductive structure, as shown in Figs. 22 to 28, which is constituted by a
grid sheet, radiative grid sheet, laminate, or winding type electrode plate,
wherein the electric energy input/output terminal 102 or the conductive
body of the electrode plate 101 between two electric energy input/output
terminals 102 in the non-side electrode plate region of the electrode plate
101 downward extend for installing with the insulated split-flow

conductive structure 104, including extending to the intermediate region of the electrode plate, or downward extending through the intermediate region of the electrode plate 101 to the bottom edge of the electrode plate 101, or downward extending through the intermediate region of the electrode plate 101 to the bottom edge of the electrode plate 101 and further extending to the insulated split-flow conductive structure 104; and/or the electric energy input/output terminal 102 downward extends to one or two sides of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, including extending to the intermediate part of the side of the electrode plate 101; and/or extending to the bottom of the side of the electrode plate 101; and/or extending to the bottom of the side of the electrode plate 101 and further extending to the bottom edge of the electrode plate 101.

As shown in Figs. 22 to 28, the insulated split-flow conductive structure 104 is installed between the electric energy input/output terminal 102 and the intermediate part and/or the bottom of the electrode plate 101 in the grid sheet electrode plate with the grid conductive body, according to the present invention, to make the current density when inputting/outputting current between the intermediate part or the bottom of the electrode plate 101 and the electric energy input/output terminal 102 to be more similar with that of other regions; the related embodiments are described as following:

Fig. 22 shows the 22th embodiment of the present invention; as shown in Fig. 22, two electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, in which the electric energy input/output terminal 102 installed at the position near the left side of the upside is more near the left side of the electrode plate 101, and the electric energy input/output terminal 102 installed at the position near the right side of the upside is more near the right side of the electrode plate 101; the electric energy input/output terminal 102 installed at the position near

the left side of the upside downward extends along the left side of the electrode plate 101 to the intermediate part of the bottom edge for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy
5 input/output terminal 102 installed at the intermediate part of the bottom edge of the left side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the left side of the upside; and

the electric energy input/output terminal 102 installed at the position
10 near the right side of the upside downward extends along the right side of the electrode plate 101 to the position near the bottom edge for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the position near the bottom edge of
15 the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the right side of the upside; and further

the insulated split-flow conductive structure 104 is installed at the position extended between the electric energy input/output terminal 102
20 installed at the position near the left side of the upside of the electrode plate 101 and the electric energy input/output terminal 102 installed at position near the right side of the upside, to the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted between the intermediate part of the electrode plate 101 and the position
25 between the electric energy input/output terminal 102 installed at the position near the left side of the upside and the electric energy input/output terminal 102 installed at position near the right side of the upside.

Fig. 23 shows the 23th embodiment of the present invention; as shown in Fig. 23, two electric energy input/output terminals 102 are
30 installed at the upside of the electrode plate 101, in which the electric

energy input/output terminal 102 installed at the position near the left side of the upside is more near the left side of the electrode plate 101, and the electric energy input/output terminal 102 installed at the position near the right side of the upside is more near the right side of the electrode plate 101; and two electric energy input/output terminals 102 are installed at the downside of the electrode plate 101, in which the electric energy input/output terminal 102 installed at the position near the left side of the downside is more near the left side of the electrode plate 101, and the electric energy input/output terminal 102 installed at the position near the right side of the downside is more near the right side of the electrode plate 101; and

the electric energy input/output terminal 102 installed at the position near the left side of the upside downward extends along the left side of the electrode plate 101 to the position near the intermediate part of the left side of the electrode plate 101 for installing the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the position near the intermediate part of the left side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the left side of the upside; and the electric energy input/output terminal 102 installed at the position near the right side of the upside downward extends along the right side of the electrode plate 101 to the position near the intermediate part of the right side of the electrode plate 101 for installing the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the position near the intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the right side of the upside; and

the electric energy input/output terminal 102 installed at the position

near the left side of the downside upward extends along the left side of the electrode plate 101 to the position near the intermediate part of the left side of the electrode plate 101 for installing the insulated split-flow conductive structure 104, thus the input/output current is direct
5 transmitted between the electric energy input/output terminal 102 installed at the position near the intermediate part of the left side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the left side of the downside; and the electric energy input/output terminal 102 installed at the position near the right side of the
10 downside upward extends along the right side of the electrode plate 101 to the position near the intermediate part of the right side of the electrode plate 101 for installing the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the position near the
15 intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the right side of the downside; and

the insulated split-flow conductive structure 104 is installed at the position extended between the electric energy input/output terminal 102
20 installed at the position near the right side of the upside of the electrode plate 101 and the electric energy input/output terminal 102 installed at position near the left side of the upside, to the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted between the intermediate part of the electrode plate 101 and the position
25 between the electric energy input/output terminal 102 installed at the position near the right side of the upside and the electric energy input/output terminal 102 installed at position near the left side of the upside; and

the insulated split-flow conductive structure 104 is installed at the
30 position extended between the electric energy input/output terminal 102

installed at the position near the right side of the downside of the electrode plate 101 and the electric energy input/output terminal 102 installed at position near the left side of the downside, to the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted
5 between the intermediate part of the electrode plate 101 and the position between the electric energy input/output terminal 102 installed at the position near the right side of the downside and the electric energy input/output terminal 102 installed at position near the left side of the downside.

10 Fig. 24 shows the 24th embodiment of the present invention; as shown in Fig. 24, two electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, in which the electric energy input/output terminal 102 installed at the position near the left side of the upside is more near the left side of the electrode plate 101, and the
15 electric energy input/output terminal 102 installed at the position near the right side of the upside is more near the right side of the electrode plate 101; and

the electric energy input/output terminal 102 installed at the position near the left side of the upside downward extends along the left side of the
20 electrode plate 101 to the bottom edge for installing the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the bottom edge of the left side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the
25 left side of the upside; and the electric energy input/output terminal 102 installed at the position near the right side of the upside downward extends along the right side of the electrode plate 101 to the bottom edge for installing the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the electric energy
30 input/output terminal 102 installed at the bottom edge of the right side of

the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the right side of the upside; and

the insulated split-flow conductive structure 104 is installed at the position downward extended between the electric energy input/output terminal 102 installed at the position near the left side of the upside of the electrode plate 101 and the electric energy input/output terminal 102 installed at position near the right side of the upside, to the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted between the intermediate part of the electrode plate 101 and the position between the electric energy input/output terminal 102 installed at the position near the left side of the upside and the electric energy input/output terminal 102 installed at position near the right side of the upside.

Fig. 25 shows the 25th embodiment of the present invention; as shown in Fig. 25, one or more electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, and it is characterized by the insulated split-flow conductive structure 104 installed at the position downward extended from the downside of one or more electric energy input/output terminals 102 installed at the electrode plate 101, and through the intermediate part of the electrode plate 101.

Fig. 26 shows the 26th embodiment of the present invention; and Fig. 26 is the second embodiment of the same structural features of the equalizing electrode plate with insulated split-flow conductive structure as shown in Fig. 25.

Fig. 27 shows the 27th embodiment of the present invention; as shown in Fig. 27, one or more electric energy input/output terminal 102 are installed at the upside of the electrode plate 101, one or more electric energy input/output terminal 102 are installed at the downside of the electrode plate 101, and the electric energy input/output terminals 102 installed at the upside of the electrode plate 101 and the electric energy

input/output terminals 102 installed at the downside of the electrode plate 101 are staggered; in which the insulated split-flow conductive structure 104 is installed at the position downward extended from the downside of the electric energy input/output terminal 102 installed at the upside of the electrode plate 101, and through the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the upside of the electrode plate 101 and the intermediate part of the electrode plate 101; and the insulated split-flow conductive structure 104 is installed at the position upward extended from the upside of the electric energy input/output terminal 102 installed at the downside of the electrode plate 101, and through the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted between the electric energy input/output terminal 102 installed at the downside of the electrode plate 101 and the intermediate part of the electrode plate 101.

Fig. 28 shows the 28th embodiment of the present invention; and Fig. 28 is the second embodiment of the same structural features of the equalizing electrode plate with insulated split-flow conductive structure as shown in Fig. 27.

For the equalizing electrode plate with insulated split-flow conductive structure, as shown in Figs. 29 to 31, which is constituted by a grid sheet, radiative grid sheet, laminate, or winding type electrode plate, wherein the independent insulated split-flow conductive structure 104 is additional installed at one or more sides of the electrode plate 101, and the independent insulated split-flow conductive structure 104 includes an electric energy input/output terminal 1023 for independently inputting/outputting electric energy, which downward extends along the side of the electrode plate 101 to the bottom of the side of the electrode plate 101, and/or extends to the bottom of the electrode plate 101 and further to the intermediate part of the bottom edge of the electrode plate

101, and/or extends to the bottom of the electrode plate 101 and further to the bottom edge of the whole electrode plate 101.

Fig. 29 shows the 29th embodiment of the present invention; as shown in Fig. 29, the electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, and it is characterized by the insulated split-flow conductive structure 104 independently installed from the position near the bottom edge of the electrode plate 101, extending to the direction of the electric energy input/output terminal 102, and to the electric energy input/output terminal 1023 for independently inputting/outputting electric energy.

Fig. 30 shows the 30th embodiment of the present invention; as shown in Fig. 30, the electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, and it is characterized by the insulated split-flow conductive structure 104 independently installed from the intermediate part of the bottom edge of the electrode plate 101, extending to the direction of the electric energy input/output terminal 102, and to the electric energy input/output terminal 1023 for independently inputting/outputting electric energy.

Fig. 31 shows the 31th embodiment of the present invention; as shown in Fig. 31, the electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, and it is characterized by the insulated split-flow conductive structure 104 independently installed from the bottom edge where the electrode plate 101 and the electric energy input/output terminal 102 are diagonal, extending to the direction of the electric energy input/output terminal 102, and to the electric energy input/output terminal 1023 for independently inputting/outputting electric energy.

For the equalizing electrode plate with insulated split-flow conductive structure, as shown in Figs. 1 to 31, wherein one or more electric energy input/output terminals 102 are installed at each of one or

more sides of the electrode plate with radiative grid conductive body, and one or more insulated split-flow conductive structures 104 are installed around and/or at the intermediate part and/or at the bottom of the electric energy input/output terminal 102 and the electrode plate 101.

5 As shown in Figs. 32 to 40, which are the drawings showing the embodiments of the insulated split-flow conductive structures 104 installed between the electric energy input/output terminal 102 of the electrode plate with radiative grid conductive body and the position around the electrode plate, according to the present invention, and the
10 descriptions are as following:

 Fig. 32 shows the 32th embodiment of the present invention; as showing in Fig. 32, the constitution is same as that of the embodiment shown in Fig. 1.

 Fig. 33 shows the 33th embodiment of the present invention; as
15 showing in Fig. 33, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 3.

 Fig. 34 shows the 34th embodiment of the present invention; as showing in Fig. 34, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 6.

20 Fig. 35 shows the 35th embodiment of the present invention; as showing in Fig. 35, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 8.

 Fig. 36 shows the 36th embodiment of the present invention; as showing in Fig. 36, the constitution of the insulated split-flow conductive
25 structure 104 is same as that of the embodiment shown in Fig. 15.

 Fig. 37 shows the 37th embodiment of the present invention; as showing in Fig. 37, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 16.

 Fig. 38 shows the 38th embodiment of the present invention; as
30 showing in Fig. 38, the constitution of the insulated split-flow conductive

structure 104 is same as that of the embodiment shown in Fig. 17.

Fig. 39 shows the 39th embodiment of the present invention; as shown in Fig. 39, two electric energy input/output terminals 102 are installed at the upside of the electrode plate 101, wherein the electric energy input/output terminal 102 installed at the position near the left side of the upside is more near the left side of the electrode plate 101, and the electric energy input/output terminal 102 installed at the position near the right side of the upside is more near the right side of the electrode plate 101; and two electric energy input/output terminals 102 are installed at the downside of the electrode plate 101, wherein the electric energy input/output terminal 102 installed at the position near the right side of the downside is more near the right side of the electrode plate 101, and the electric energy input/output terminal 102 installed at the position near the left side of the downside is more near the left side of the electrode plate 101; and

the electric energy input/output terminal 102 installed at the position near the right side of the upside downward extends along the right side to the position near the intermediate part of the right side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the position near the intermediate part of the right side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the right side of the upside; and

the electric energy input/output terminal 102 installed at the position near the left side of the downside upward extends along the left side to the position near the intermediate part of the left side of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the position near the intermediate part of the left side of the electrode plate 101 and the electric energy input/output terminal 102 installed at the position near the

left side of the downside.

Fig. 40 shows the 40th embodiment of the present invention; as showing in Fig. 40, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 21.

5 As shown in Figs. 41 to 42, which are the drawings showing the embodiments of the insulated split-flow conductive structures 104 installed at the electric energy input/output terminal 102 and the intermediate part and/or the bottom of the electrode plate 101 in the electrode plate with radiative grid conductive body, and the descriptions
10 are as following:

Fig. 41 shows the 41th embodiment of the present invention; as showing in Fig. 41, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 23.

Fig. 42 shows the 42th embodiment of the present invention; as
15 showing in Fig. 42, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 24.

For the equalizing electrode plate with insulated split-flow conductive structure, which is further constituted by the insulated split-flow conductive structure installed between the electric energy
20 input/output terminal 102 of the laminate electrode plate and the position around and/or at the intermediate part of and/or at the bottom of the laminate electrode plate 101.

As shown in Figs. 43 to 62, which are the drawings showing the embodiments of the electrode plate constituted by the insulated split-flow
25 conductive structures 104 installed between the electric energy input/output terminal 102 of the laminate electrode plate and the position around or at the bottom of the electrode plate 101, and the descriptions are as following:

Fig. 43 shows the 43th embodiment of the present invention; as
30 showing in Fig. 43, the constitution of the insulated split-flow conductive

structure 104 is same as that of the embodiment shown in Fig. 1.

Fig. 44 shows the 44th embodiment of the present invention; as showing in Fig. 44, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 2.

5 Fig. 45 shows the 45th embodiment of the present invention; as showing in Fig. 45, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 3.

Fig. 46 shows the 46th embodiment of the present invention; as showing in Fig. 46, the constitution of the insulated split-flow conductive
10 structure 104 is same as that of the embodiment shown in Fig. 4.

Fig. 47 shows the 47th embodiment of the present invention; as showing in Fig. 47, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 5.

Fig. 48 shows the 48th embodiment of the present invention; as
15 showing in Fig. 48, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 6.

Fig. 49 shows the 49th embodiment of the present invention; as showing in Fig. 49, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 7.

20 Fig. 50 shows the 50th embodiment of the present invention; as showing in Fig. 50, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 8.

Fig. 51 shows the 51th embodiment of the present invention; as showing in Fig. 51, the constitution of the insulated split-flow conductive
25 structure 104 is same as that of the embodiment shown in Fig. 10.

Fig. 52 shows the 52th embodiment of the present invention; as showing in Fig. 52, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 15.

Fig. 53 shows the 53th embodiment of the present invention; as
30 showing in Fig. 53, the constitution of the insulated split-flow conductive

structure 104 is same as that of the embodiment shown in Fig. 11.

Fig. 54 shows the 54th embodiment of the present invention; as showing in Fig. 54, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 12.

5 Fig. 55 shows the 55th embodiment of the present invention; as showing in Fig. 55, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 13.

Fig. 56 shows the 56th embodiment of the present invention; as showing in Fig. 56, the constitution of the insulated split-flow conductive
10 structure 104 is same as that of the embodiment shown in Fig. 14.

Fig. 57 shows the 57th embodiment of the present invention; as showing in Fig. 57, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 16.

Fig. 58 shows the 58th embodiment of the present invention; as
15 showing in Fig. 58, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 17.

Fig. 59 shows the 59th embodiment of the present invention; as showing in Fig. 59, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 18.

20 Fig. 60 shows the 60th embodiment of the present invention; as showing in Fig. 60, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 19.

Fig. 61 shows the 61th embodiment of the present invention; as showing in Fig. 61, the constitution of the insulated split-flow conductive
25 structure 104 is same as that of the embodiment shown in Fig. 20.

Fig. 62 shows the 62th embodiment of the present invention; as showing in Fig. 62, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 21.

As shown in Figs. 63 to 72, which are the drawings showing the
30 embodiments of the insulated split-flow conductive structures 104

installed between the electric energy input/output terminal 102 of the laminate electrode plate and the intermediate part and/or the bottom of the electrode plate, according to the present invention, and the descriptions are as following:

5 Fig. 63 shows the 63th embodiment of the present invention; as showing in Fig. 63, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 22.

 Fig. 64 shows the 64th embodiment of the present invention; as showing in Fig. 64, the constitution of the insulated split-flow conductive
10 structure 104 is same as that of the embodiment shown in Fig. 23.

 Fig. 65 shows the 65th embodiment of the present invention; as showing in Fig. 65, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 24.

 Fig. 66 shows the 66th embodiment of the present invention; as
15 showing in Fig. 66, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 25.

 Fig. 67 shows the 67th embodiment of the present invention; as showing in Fig. 67, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 26.

20 Fig. 68 shows the 68th embodiment of the present invention; as showing in Fig. 68, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 27.

 Fig. 69 shows the 69th embodiment of the present invention; as showing in Fig. 69, the constitution of the insulated split-flow conductive
25 structure 104 is same as that of the embodiment shown in Fig. 28.

 Fig. 70 shows the 70th embodiment of the present invention; as showing in Fig. 70, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 29.

 Fig. 71 shows the 71th embodiment of the present invention; as
30 showing in Fig. 71, the constitution of the insulated split-flow conductive

structure 104 is same as that of the embodiment shown in Fig. 30.

Fig. 72 shows the 72th embodiment of the present invention; as showing in Fig. 72, the constitution of the insulated split-flow conductive structure 104 is same as that of the embodiment shown in Fig. 31.

5 For the equalizing electrode plate with insulated split-flow conductive structure, which is applied to the electrode plate constituted by the grid sheet conductive material, or radiative grid sheet, laminate, or winding type electrode plate; and there is the electric energy input/output terminal 102 with same or near width as that of the electrode plate at one
10 or more sides of the electrode plate, in which the arrangement of the insulated split-flow conductive structure 104 is same as which, single electric energy input/output terminal installed at one or more sides of the electrode plate 101, in the above embodiments.

Fig. 73 shows the 73th embodiment of the present invention; as
15 shown in Fig. 73, the electrode plate 101 is grid sheet structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 2, and the further feature is that there is the electric energy input/output terminal with same or near width as that of the electrode plate at one side of the electrode plate.

20 Fig. 74 shows the 74th embodiment of the present invention; as shown in Fig. 74, the electrode plate 101 is laminate structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 44, and the further feature is that there is the electric energy input/output terminal with same or near width as that of the
25 electrode plate at one side of the electrode plate.

Fig. 75 shows the 75th embodiment of the present invention; as shown in Fig. 75, the electrode plate 101 is grid sheet structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 4, and the further feature is that there is the electric
30 energy input/output terminal with same or near width as that of the

electrode plate at one side of the electrode plate.

Fig. 76 shows the 76th embodiment of the present invention; as shown in Fig. 76, the electrode plate 101 is laminate structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 46, and the further feature is that there is the electric energy input/output terminal with same or near width as that of the electrode plate at one side of the electrode plate.

Fig. 77 shows the 77th embodiment of the present invention; as shown in Fig. 77, the electrode plate 101 is laminate structure, in which the electric energy input/output terminal 102 installed at the upside of the electrode plate 101 downward extends along the left side of the electrode plate 101 to the bottom edge near the position of the intermediate part for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the bottom edge near the position of the intermediate part of the electrode plate 101 and the electric energy input/output terminal 102; and the electric energy input/output terminal 102 downward extends along the right side of the electrode plate 101 to the bottom edge near the position of the intermediate part for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the bottom edge of the right side near the position of the intermediate part of the electrode plate 101 and the electric energy input/output terminal 102; the bottom segment of the insulated split-flow conductive structure 104 nears or links with that of the above insulated split-flow conductive structure 104 downward extending from the left side of the electrode plate 101, and is conductive with the electrode plate 101.

Fig. 78 shows the 78th embodiment of the present invention; as shown in Fig. 78, the electrode plate 101 is laminate structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 9.

Fig. 79 shows the 79th embodiment of the present invention; as shown in Fig. 79, the electrode plate 101 is grid sheet structure, in which the electric energy input/output terminal 102 installed at the upside of the electrode plate 101 downward extends along the left side of the electrode plate 101 to the bottom edge near the position of the intermediate part for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the bottom edge near the position of the intermediate part of the electrode plate 101 and the electric energy input/output terminal 102; and the electric energy input/output terminal 102 downward extends along the right side of the electrode plate 101 to the bottom edge near the position of the intermediate part for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the bottom edge of the right side near the position of the intermediate part of the electrode plate 101 and the electric energy input/output terminal 102; the bottom segment of the insulated split-flow conductive structure 104 nears or links with that of the above insulated split-flow conductive structure 104 downward extending from the left side of the electrode plate 101, and is conductive with the electrode plate 101; and the intermediate part of the electric energy input/output terminal 102 extends to the bottom of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the bottom edge of the electrode plate 101 and the intermediate part of the electric energy input/output terminal 102.

Fig. 80 shows the 80th embodiment of the present invention; as shown in Fig. 80, the electrode plate 101 is laminate structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 79.

Fig. 81 shows the 81th embodiment of the present invention; as shown in Fig. 81, the electrode plate 101 is laminate structure, in which

the electric energy input/output terminal 102 with same or near width as that of the electrode plate is installed at the upside of the electrode plate 101; and

the intermediate part of the electric energy input/output terminal 102
5 installed at the upside of the electrode plate 101 downward extends to the position near the intermediate part region of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted with lower impedance between the electrode plate region set in the electrode plate 101 for direct
10 transmitting current with the electric energy input/output terminal 102, and the electric energy input/output terminal 102 linking with another side of the connecting insulated split-flow conductive structure 104.

Fig. 82 shows the 82th embodiment of the present invention; as shown in Fig. 82, the electrode plate 101 is laminate structure, in which
15 the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 81.

Fig. 83 shows the 83th embodiment of the present invention; as shown in Fig. 83, the electrode plate 101 is grid sheet structure, in which the electric energy input/output terminal 102 with same or near width as
20 that of the electrode plate is installed at the upside of the electrode plate 101; and

two or more electric energy input/output terminals 102 (in the figure is represented by two) are installed at the upside of the electrode plate 101, and the intermediate part of the electric energy input/output terminals 102
25 downward extend to the position near the intermediate part region of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted with lower impedance between the electrode plate region set in the electrode plate 101 for direct transmitting current with the electric energy input/output
30 terminal 102, and the electric energy input/output terminal 102 linking

with another side of the connecting insulated split-flow conductive structure 104.

Fig. 84 shows the 84th embodiment of the present invention; as shown in Fig. 84, the electrode plate 101 is laminate structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 83.

Fig. 85 shows the 85th embodiment of the present invention; as shown in Fig. 85, the electrode plate 101 is grid sheet structure, in which the electric energy input/output terminal 102 with same or near width as that of the electrode plate is installed at each of the upside and the downside of the electrode plate 101; and

two or more intermediate part of the electric energy input/output terminals 102 (in the figure is represented by two) installed at the upside of the electrode plate 101, and the positions near two sides of the electric energy input/output terminals 102 downward extend to the position near the intermediate part region of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, and one or more electric energy input/output terminals 102 (in the figure is represented by one) installed at intermediate part of the insulated split-flow conductive structure 104 installed at the position where the electric energy input/output terminal 102 installed at the downside of the electrode plate 101 downward extending, upward extend to the position near the intermediate part region of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, which is the above insulated split-flow conductive structure 104 , thus the input/output current is direct transmitted with lower impedance between the electrode plate region near the intermediate part region set in the electrode plate 101 for direct transmitting current with the electric energy input/output terminals 102 installed at the upside and the downside, and the electric energy input/output terminal 102 linking with another side of the insulated

split-flow conductive structure 104 connecting with the upside and the downside.

Fig. 86 shows the 86th embodiment of the present invention; as shown in Fig. 86, the electrode plate 101 is laminate structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 85.

For the equalizing electrode plate with insulated split-flow conductive structure, which is further applied to winding type electrode plate, the embodiments are as follow:

Fig. 87 shows the 87th embodiment of the present invention; as shown in Fig. 87, the electrode plate 101 is grid sheet structure, in which at least one electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, and downward extends along the left side of the electrode plate 101 to the position near the intermediate part of the bottom edge for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the position near the intermediate part of the bottom edge of the electrode plate 101 and the electric energy input/output terminal 102; and the electric energy input/output terminal 102 installed at the most right side of the electrode plate downward extends along the right side (including the right side in the case of single electric energy input/output terminal) of the electrode plate 101 to the bottom edge for installing with the insulated split-flow conductive structure 104 along the bottom edge, thus the input/output current is direct transmitted between the bottom edge of the right side of the electrode plate 101 and the electric energy input/output terminal 102, and the bottom segment of the insulated split-flow conductive structure 104 links with that of the above insulated split-flow conductive structure 104 downward extending from the left side of the electrode plate 101, and is conductive with the electrode plate 101; if two or more electric energy input/output terminals 102 are installed, the

electric energy input/output terminal 102 installed at intermediate part extends to the bottom of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted between the bottom edge of the electrode plate 101 and the electric energy input/output terminal 102 installed at intermediate part of the electrode plate 101; and there is an isolated body installed between the electrode plate 101 and another electrode plate with different polarity for winding type structure.

Fig. 88 shows the 88th embodiment of the present invention; as shown in Fig. 88, the electrode plate 101 is laminate structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 87.

Fig. 89 shows the 89th embodiment of the present invention; as shown in Fig. 89, at least one electric energy input/output terminal 102 is installed at the upside of the electrode plate 101, and the intermediate part of the electric energy input/output terminal 102 installed at the upside of the electrode plate 101 downward extends to the position near the bottom edge of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted with lower impedance between the position near the bottom edge of the electrode plate 101 and the electric energy input/output terminal 102 linking with another side of the connecting insulated split-flow conductive structure 104; and there is an isolated body installed between the electrode plate 101 and another electrode plate with different polarity for winding type structure.

Fig. 90 shows the 90th embodiment of the present invention; as shown in Fig. 90, the electrode plate 101 is laminate structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 89.

Fig. 91 shows the 91th embodiment of the present invention; as

shown in Fig. 91, the electrode plate 101 is grid sheet structure, in which the electric energy input/output terminal 102 with same or near width as that of the electrode plate at the upside of the electrode plate; and

two or more electric energy input/output terminals 102 (in the figure is represented by two) are installed at the upside of the electrode plate 101, and the intermediate part of the electric energy input/output terminals 102 downward extend to the position beyond the intermediate part and near the bottom edge region of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, thus the input/output current is direct transmitted with lower impedance between the electrode plate region beyond the intermediate part and near the bottom edge set in the electrode plate 101 for direct transmitting current with the electric energy input/output terminal 102, and the electric energy input/output terminal 102 linking with another side of the connecting insulated split-flow conductive structure 104; and the insulated split-flow conductive structure 104 is installed at the region where the above electric energy input/output terminals 102 downward extend to the position near the intermediate part of the electrode plate 101, thus the input/output current is direct transmitted with lower impedance between the electrode plate region beyond the intermediate part and near the intermediate edge set in the electrode plate 101 for direct transmitting current with the electric energy input/output terminal 102, and the electric energy input/output terminal 102 linking with another side of the connecting insulated split-flow conductive structure 104; and there is an isolated body installed between the electrode plate 101 and another electrode plate with different polarity for winding type structure.

Fig. 92 shows the 92th embodiment of the present invention; as shown in Fig. 92, the electrode plate 101 is laminate structure, in which the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 91.

Fig. 93 shows the 94th embodiment of the present invention; as shown in Fig. 93, the electrode plate 101 is grid sheet structure, in which the electric energy input/output terminal 102 with same or near width as that of the electrode plate is installed at each of the upside and the
5 downside of the electrode plate 101; and

two or more intermediate part of the electric energy input/output terminals 102 (in the figure is represented by three) installed at the upside of the electrode plate 101, and the positions near two sides of the electric energy input/output terminals 102 downward extend to the position near
10 the intermediate part region of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, and one or more electric energy input/output terminals 102 (in the figure is represented by two) installed at intermediate part of the insulated split-flow conductive structure 104 installed at the position where the electric energy
15 input/output terminal 102 installed at the downside of the electrode plate 101 downward extending, upward extend to the position near the intermediate part region of the electrode plate 101 for installing with the insulated split-flow conductive structure 104, which is the above insulated split-flow conductive structure 104 , thus the input/output current is direct
20 transmitted with lower impedance between the electrode plate region near the intermediate part region set in the electrode plate 101 for direct transmitting current with the electric energy input/output terminals 102 installed at the upside and the downside, and the electric energy input/output terminal 102 linking with another side of the insulated
25 split-flow conductive structure 104 connecting with the upside and the downside ; and there is an isolated body installed between the electrode plate 101 and another electrode plate with different polarity for winding type structure.

Fig. 94 shows the 94th embodiment of the present invention; as shown in Fig. 94, the electrode plate 101 is laminate structure, in which
30

the constitution of the insulated split-flow conductive structure 104 is same as that in Fig. 93.

For the equalizing electrode plate with insulated split-flow conductive structure, the cross-section shapes of the insulated split-flow
5 conductive structures 104 in various embodiments are as following:

Fig. 95 is the A-A cross-section view of insulated split-flow conductive structure 104, according to the present invention; as shown in Fig. 95, the cross-section structure of the insulated split-flow conductive structure 104 is constituted by the conductive body 1045 coated with the
10 insulator 1046.

Fig. 96 is the B-B cross-section view of the conductive grid of the electrode plate, according to the present invention; as shown in Fig. 96, the cross-section structure of the conductive grid electrode is constituted by the strip conductive body 1045.

Fig. 97 is the C-C cross-section view of the insulated split-flow conductive structure 104, according to the present invention; as shown in Fig. 97, which is the cross-section structure of the conductive body 1045 of the insulated split-flow conductive structure 104, in which a side without the insulator 1046 installed.
15

Fig. 98 is the D-D cross-section view of the insulated split-flow conductive structure 104, according to the present invention; as shown in Fig. 98, which is the cross-section structure of the conductive body 1045 of the insulated split-flow conductive structure 104, in which two sides of the conductive body without the insulator 1046 installed.
20

Fig. 99 is the E-E cross-section view of the parallel insulated split-flow conductive structures 104, according to the present invention; as shown in Fig. 99, which is the cross-section structure of the two parallel insulated split-flow conductive structures 104.
25

Fig. 100 is the F-F cross-section view of two parallel insulated split-flow conductive structures 1041 and 1042, in which at least one side
30

of the conductive body 1045 of one insulated split-flow conductive structure 104 without the insulator 1046 installed, according to the present invention; as shown in Fig. 100, which is the cross-section structure of the two parallel insulated split-flow conductive structures 1041 and 1042, in which an insulator is additionally installed around one insulated split-flow conductive structure 104, and at least one side of the conductive body 1045 of another insulated split-flow conductive structure 104 is not installed with the insulator 1046.

Fig. 101 is the G-G cross-section view of two parallel laminated insulated split-flow conductive structures 1041 and 1042, according to the present invention; as shown in Fig. 101, which is the cross-section structure of two parallel laminated insulated split-flow conductive structures 104.

Fig. 102 is a cross-section view of the insulated split-flow conductive structure 1041 and/or the insulated split-flow conductive structure 1042 shown in Fig. 101, in which at least one side without insulator installed; as shown in Fig. 102, which is the cross-section structure of two parallel laminated insulated split-flow conductive structures, in which at least one or two sides of the conductive body 1045 without insulator installed.

Fig. 103 is the H-H cross-section view of the insulated split-flow conductive structure 104 pasted at the electrode plate at single side, according to the present invention; as shown in Fig. 103, which is the cross-section structure of a layer of the insulated split-flow conductive structure 104 pasted at the electrode plate 101 at single side.

Fig. 104 is a cross-section view of the insulated split-flow conductive structure 104 shown in Fig. 103, in which at least one side without insulator installed; as shown in Fig. 104, which is the cross-section structure of a layer of the insulated split-flow conductive structure 104 pasted at the electrode plate 101 at single side, in which at least one side of the conductive body 1045 without insulator installed.

For the above various equalizing electrode plate with insulated split-flow conductive structures, which are applied to positive and negative electrode plates constituting the electrode pair for the device with storage-discharge function, and further applied to a number of electrode
5 pairs, which are parallel or in series, for the expansion of rated voltage and constant value current.

CLAIMS:

1. An equalizing electrode plate with insulated split-flow conductive structure, which is specifically installed insulated split-flow conductive structure with one or more internal conductive bodies coated with insulators, wherein one end of the insulated split-flow conductive structure connects to the electric energy input/output terminal of the electrode plate, and another end connects to the surrounding part and/or the middle part and/or the bottom of the electrode plate, the electrode plate area where the current path more far away from the electric energy input/output terminal and/or the current passing with larger impedance when outputting and/or inputting electric energy, by way of the dedicated insulated split-flow conductive structure connecting with the electric energy input/output terminal, the electric energy, between the electrode plate area where the current path more far away from the electric energy output terminal and/or the electrode plate area with larger impedance and the electric energy input/output terminal, specifically transmits therebetween, and the conductive body and the contacting electrochemical active substance in every area of the electrode plate can operate in more uniform current density when outputting and/or inputting electric energy; the main components include:
 - Electrode plate (101): related to positive and/or negative electrode plate constituted by grid sheet, radiative grid sheet, laminate, or winding type electrode plate, wherein the positive pole and the negative pole of the electrode plate is constituted by same or different conductive material;
 - Electric energy input/output terminal (102): made of the electrode plate extended or being additionally installed, to connect the electrode plate (101) at one or more sides, wherein every side is installed with one or more electric energy input/output terminals to

be the interface for the electrode plate outputting and/or inputting electric energy, and the conductive material of the electric energy input/output terminal and that of the electrode plate are same or different;

5 ---Electrochemical active substance (103): related to electrochemical material in gaseous state, liquid state, colloidal state, or solid state; and

---Insulated split-flow conductive structure (104): constituted by a conductive body (1045), whose material is same as or different from that of the electrode plate, around covered or draped with an insulator (1046), wherein one or more insulated split-flow conductive structures (104) are installed along the side of the electrode plate and/or into the central area of the electrode plate, one end of the insulated split-flow conductive structure (104) connects in a manner of conductive features to the electric energy input/output terminal (102) of the electrode plate (101) or the conductive body of the electrode plate, including welding, heat sealing, spot welding, mechanical riveting, locking, clamping, and blocking, and another end connects in a manner of conductive features to the electrode plate area of the electrode plate where the current path more far away from the electric energy input/output terminal (102) and/or the current passing with larger impedance when outputting and/or inputting electric energy, including welding, heat sealing, spot welding, mechanical riveting, locking, clamping and blocking, for specifically transmitting the electric energy therebetween; and in which

for the equalizing electrode plate with insulated split-flow conductive structure, which is applied for a positive and negative electrode plate, including grid sheet, radiative grid sheet, laminate, or winding type electrode plate constituting primary battery, rechargeable secondary

battery, capacitor, or ultra-capacitor, or rechargeable device or fuel cell for transferring electric energy to chemical energy or chemical energy to electric energy; and

the equalizing electrode plate with insulated split-flow
5 conductive structure is further to use the positive and negative electrode plates constituting the electrode pair for the device with storage-discharge function, and further to use a number of electrode pairs, which are parallel or in series, for the expansion of rated voltage and constant value current.

- 10 2. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, wherein the conductive body (1045) of the insulated split-flow conductive structure (104) is made of the following one or more ways, including:

(1) made of the same material as that of the electrode plate;

- 15 (2) made of the different material, which is well conductive material with the specific resistance lower than that of the electrode plate;

(3) made of the electrode plate material coated with the conductive body with the specific resistance lower than that of the electrode plate material; and

- 20 (4) made of two or more different materials from that of the electrode plate, wherein the materials are ring coating with each other for two or more layers.

3. The equalizing electrode plate with insulated split-flow conductive
25 structure as claimed in Claim 1, wherein the combination of the insulated split-flow conductive structure (104) and the electrode plate (101) is constituted by the following one or more ways, including:

the insulated split-flow conductive structure (104) and the electrode plate (101) are integrated, wherein the conductive body (1045) of the insulated split-flow conductive structure (104) is around covered or
30 coated with the insulator (1046), or draped with the insulator (1046),

such as epoxy resin, insulating glue, varnish, insulating paint, or PVF, etc.; one end of the insulated split-flow conductive structure (104) and the electrode plate area set in the electrode plate (101) for directly transmitting current to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101) are integrated, another end and the electric energy input/output terminal (102) or the conductive body of the electrode plate (101) are integrated, and the current is directly transmitted in lower impedance therebetween; the insulated split-flow conductive structure (104) in flat or curved shape matches with the electrode plate (101) to form a part of the electrode plate for being co-located in the groove structural body or case of the applying device for electrochemical action.

4. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, wherein the combination of the insulated split-flow conductive structure (104) and the electrode plate (101) is constituted by the following one or more ways, including: one end of the insulated split-flow conductive structure (104) and the electrode plate area set in the electrode plate (101) for directly transmitting current to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101) are integrated, wherein the conductive body (1045) of the insulated split-flow conductive structure (104) is around covered or coated with the insulator (1046), or draped with the insulator (1046), such as epoxy resin, insulating glue, insulating paint, varnish, or PVF, another end is welded, riveted, clamped, or locked at the electric energy input/output terminal (102) or the conductive body of the electrode plate (101), and the current is directly transmitted in lower impedance therebetween; the insulated split-flow conductive structure (104) in flat or curved shape matches with the electrode

plate (101) to form a part of the electrode plate for being co-located in the groove structural body or case of the applying device for electrochemical action.

5. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, wherein the combination of the insulated split-flow conductive structure (104) and the electrode plate (101) is constituted by the following one or more ways, including:
- the insulated split-flow conductive structure (104) in the type of independent conductive line or conductive strip constitutes the conductive body (1045), the conductive body (1045) is around covered or coated with the insulator (1046), or draped with the insulator (1046), such as epoxy resin, insulating glue, insulating paint, varnish, or PVF, and the two ends of the conductive body (1045) of the insulated split-flow conductive structure (104) respectively connect in a manner of conductive features, including welding, heat sealing, spot welding, mechanical riveting, locking, clamping, and blocking, wherein one end connects to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate, and another end connects to the electrode plate area set in the electrode plate (101) for directly transmitting current to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101) and parallels the electrode plate (101); when outputting and/or inputting electric energy, the current is directly transmitted in lower impedance between the electrode plate area set in the electrode plate (101) for directly transmitting current to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101) and the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101); and the insulated split-flow conductive structure (104) in flat or curved shape matches with the electrode

plate (101) to form a part of the electrode plate for being co-located in the groove structural body or case of the applying device for electrochemical action.

6. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, wherein the combination of the insulated split-flow conductive structure (104) and the electrode plate (101) is constituted by the following one or more ways, including: the insulated split-flow conductive structure (104) in the type of independent conductive line or conductive strip constitutes the conductive body (1045), the conductive body (1045) is around covered or coated with the insulator (1046), or draped with the insulator (1046), such as epoxy resin, insulating glue, insulating paint, varnish, or PVF, and the two ends of the conductive body (1045) of the insulated split-flow conductive structure (104) respectively connect in a manner of conductive features, including welding, heat sealing, spot welding, mechanical riveting, locking, clamping, and blocking, wherein one end connects to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate, and another end connects to the electrode plate area set in the electrode plate (101) for directly transmitting current to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101); the insulated split-flow conductive structure (104) is installed and superimposed on one or two sides of the electrode plate (101); when outputting and/or inputting electric energy, the current in the current path is directly transmitted in lower impedance between the electrode plate area set in the electrode plate (101) for directly transmitting current to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101) and the electric energy input/output terminal (102) or the conductive body of the electrode plate (101); and the

insulated split-flow conductive structure (104) in flat or curved shape matches with the electrode plate (101) to form a part of the electrode plate for being co-located in the groove structural body or case of the applying device for electrochemical action.

- 5 7. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, wherein the combination of the insulated split-flow conductive structure (104) and the electrode plate (101) is constituted by the following one or more ways, including:
- 10 the independent insulated split-flow conductive structure (104) is installed at the external part of the groove structural body or case of the electrode plate, wherein the independent insulated split-flow conductive structure (104) includes the conductive body (1045) of the insulated split-flow conductive structure (104) covered or coated with the insulator (1046), or draped with the insulator (1046), such as
- 15 epoxy resin, insulating glue, insulating paint, varnish, or PVF, and the electrode plate area set in the electrode plate (101) for directly transmitting current to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101); in the current path when outputting and/or inputting electric energy,
- 20 between the electrode plate area set in the electrode plate (101) for directly transmitting current to the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101) and the electric energy input/output terminal (102) and/or the conductive body of the electrode plate (101), the electric energy is
- 25 directly transmitted in lower impedance therebetween, or the above both separate and respectively operate for outputting and/or inputting electric energy.
- 30 8. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, which is constituted by a grid sheet, radiative grid sheet, laminate, or winding type electrode plate,

wherein the one or more than one side of the electrode plate (101) is installed one or more electric energy input/output terminals (102), and the electric energy input/output terminal (102) downward extends to one or two sides of the electrode plate (101) for installing with one or more than one parallel installed insulated split-flow conductive structure (104), including extending to the intermediate part of the side of the electrode plate (101) to be installed with the insulated split-flow conductive structure (104); and/or extending to the bottom of the side of the electrode plate (101); and/or extending to the bottom of electrode plate (101) and further extending to the bottom edge of electrode plate (101).

9. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, which is further constituted by a grid sheet, radiative grid sheet, laminate, or winding type electrode plate, wherein the electric energy input/output terminal (102) or the conductive body of the electrode plate (101) between two electric energy input/output terminals (102) in the non-side electrode plate region of the electrode plate (101) downward extend for installing with the insulated split-flow conductive structure (104), including extending to the intermediate region of the electrode plate, or downward extending through the intermediate region of the electrode plate (101) to the bottom edge of the electrode plate (101), or downward extending through the intermediate region of the electrode plate (101) to the bottom edge of the electrode plate (101) and further extending to the insulated split-flow conductive structure (104); and/or the electric energy input/output terminal (102) downward extends to one or two sides of the electrode plate (101) for installing with the insulated split-flow conductive structure (104), including extending to the intermediate part of the side of the electrode plate (101); and/or extending to the bottom of the side of the electrode

plate (101); and/or extending to the bottom of the side of the electrode plate (101) and further extending to the bottom edge of the electrode plate (101).

10. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, which is constituted by a grid sheet, radiative grid sheet, laminate, or winding type electrode plate, wherein the independent insulated split-flow conductive structure (104) is additional installed at one or more sides of the electrode plate (101), and the independent insulated split-flow conductive structure (104) includes an electric energy input/output terminal (1023) for independently inputting/outputting electric energy, which downward extends along the side of the electrode plate (101) to the bottom of the side of the electrode plate (101), and/or extends to the bottom of the electrode plate (101) and further to the intermediate part of the bottom edge of the electrode plate (101), and/or extends to the bottom of the electrode plate (101) and further to the bottom edge of the whole electrode plate (101).
11. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, wherein two electric energy input/output terminals (102) are installed at the upside of the electrode plate (101), the electric energy input/output terminal (102) installed at position near the left side of the upside is more near the left side of the electrode plate (101), and the electric energy input/output terminal (102) installed at position near the right side of the upside is more near the right side of the electrode plate (101); and two electric energy input/output terminals (102) are installed at the downside of the electrode plate (101), the electric energy input/output terminal (102) installed at the position near the right side of the downside is more near the right side of the electrode plate (101), and the electric energy input/output terminal (102) installed at

the position near the left side of the downside is more near the left side of the electrode plate (101); and

the electric energy input/output terminal (102) installed at the position near the right side of the upside downward extends along the right side to the position near the intermediate part of the right side of the electrode plate (101) for installing with the insulated split-flow conductive structure (104), thus the input/output current is direct transmitted between the position near the intermediate part of the right side of the electrode plate (101) and the electric energy input/output terminal (102) installed at the position near the right side of the upside; and

the electric energy input/output terminal (102) installed at the position near the left side of the downside upward extends along the left side to the position near the intermediate part of the left side of the electrode plate (101) for installing with the insulated split-flow conductive structure (104), thus the input/output current is direct transmitted between the position near the intermediate part of the left side of the electrode plate (101) and the electric energy input/output terminal (102) installed at the position near the left side of the downside.

12. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, including the electrode plate constituted by the grid sheet conductive material, or radiative grid sheet, laminate, or winding type electrode plate; in which there is an electric energy input/output terminal with same or near width as that of the electrode plate at one or more sides of the electrode plate.

13. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, in which at least one electric energy input/output terminal (102) is installed at the upside of the electrode plate (101), and downward extends along the left side of the

electrode plate (101) to the position near the intermediate part of the bottom edge for installing with the insulated split-flow conductive structure (104), thus the input/output current is direct transmitted between the position near the intermediate part of the bottom edge of the electrode plate (101) and the electric energy input/output terminal (102); and the electric energy input/output terminal (102) installed at the most right side of the electrode plate downward extends along the right side (including the right side in the case of single electric energy input/output terminal) of the electrode plate (101) to the bottom edge for installing with the insulated split-flow conductive structure (104) along the bottom edge, thus the input/output current is direct transmitted between the bottom edge of the right side of the electrode plate (101) and the electric energy input/output terminal (102), and the bottom segment of the insulated split-flow conductive structure (104) links with that of the above insulated split-flow conductive structure (104) downward extending from the left side of the electrode plate (101), and is conductive with the electrode plate (101); if two or more electric energy input/output terminals (102) are installed, the electric energy input/output terminal (102) installed at intermediate part extends to the bottom of the electrode plate (101) for installing with the insulated split-flow conductive structure (104), thus the input/output current is direct transmitted between the bottom edge of the electrode plate (101) and the electric energy input/output terminal (102) installed at intermediate part of the electrode plate (101); and there is an isolated body installed between the electrode plate (101) and another electrode plate with different polarity for winding type structure.

14. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, in which at least one electric energy input/output terminal (102) is installed at the upside of the electrode

plate (101), and the intermediate part of the electric energy input/output terminal (102) installed at the upside of the electrode plate (101) downward extends to the position near the bottom edge of the electrode plate (101) for installing with the insulated split-flow conductive structure (104), thus the input/output current is direct transmitted with lower impedance between the position near the bottom edge of the electrode plate (101) and the electric energy input/output terminal (102) linking with another side of the connecting insulated split-flow conductive structure (104); and there is an isolated body installed between the electrode plate (101) and another electrode plate with different polarity for winding type structure.

15. The equalizing electrode plate with insulated split-flow conductive structure as claimed in Claim 1, in which the electric energy input/output terminal (102) with same or near width as that of the electrode plate at the upside of the electrode plate; and two or more electric energy input/output terminals (102) are installed at the upside of the electrode plate (101), and the intermediate part of the electric energy input/output terminals (102) downward extend to the position beyond the intermediate part and near the bottom edge region of the electrode plate (101) for installing with the insulated split-flow conductive structure (104), thus the input/output current is direct transmitted with lower impedance between the electrode plate region beyond the intermediate part and near the bottom edge set in the electrode plate (101) for direct transmitting current with the electric energy input/output terminal (102), and the electric energy input/output terminal (102) linking with another side of the connecting insulated split-flow conductive structure (104); and the insulated split-flow conductive structure (104) is installed at the region where the above electric energy input/output terminals (102)

downward extend to the position near the intermediate part of the electrode plate (101), thus the input/output current is direct transmitted with lower impedance between the electrode plate region beyond the intermediate part and near the intermediate edge set in the electrode plate (101) for direct transmitting current with the electric energy input/output terminal (102), and the electric energy input/output terminal (102) linking with another side of the connecting insulated split-flow conductive structure (104); and there is an isolated body installed between the electrode plate (101) and another electrode plate with different polarity for winding type structure.