

VALVE AND METHOD OF OPERATING A VALVE

This invention relates to a valve, typically a ball valve, and especially to a ball valve used in an oil or gas well, typically in an intervention or well control string.

5

In downhole wellbores the flow paths through the main bores of the well and other flow conduits are typically controlled by valves. The valves typically close and open against a seat which provides a sealing face to engage with a movable member in the valve and prevent fluid flow. Typically the seat is faced with a resilient material that conforms to the sealing face of the valve to create the seal.

10

Problems arise when the seat of the valve is damaged by the movement of the moveable member between its open and closed configurations. Typically, in a ball valve, the valve moves between its open and closed configurations by rotation of the ball, to rotate a bore in the ball in and out of alignment with the bore of the conduit in which the ball valve is located. As the bore of the ball rotates out of alignment with the bore of the tubular, the edge of the bore can sometimes tear or otherwise damage the seat against which the ball seals, possibly tearing the resilient material on the face of that seat.

15

20

This is particularly problematic when the ball valve needs to cut a wire or other elongate member that is passing through the bore as it moves between the open and closed configurations, because the inner edge of the bore through the ball typically becomes damaged by shearing of the wire, and the damaged edge then rakes across the more delicate seating surface on the seal, typically causing tears and other damage to the softer material used on that component. When the ball valve has closed and the bore of the valve is out of alignment with the bore of the tubular, the sealing surface of the ball frequently does not seal adequately against the damaged surface of the seat, and leaks then arise when the stroke has been completed.

25

30

In accordance with the invention there is provided a valve for use in an oil or gas well, the valve comprising a moveable member configured to move between open

and closed configurations of the valve to allow and resist flow of fluid through the valve in respective open and closed configurations, the moveable member having a cutting surface adapted to shear against an anvil member when the moveable member is moving between the open and closed configurations; the valve having a sealing member providing a seat for seating of the moveable member when the moveable member is in the closed configuration; wherein the valve has a sealing member displacement mechanism configured to vary the spacing between the sealing member and the movable member when the moveable member is moving between the open and the closed configurations.

The invention also provides a method of operating an oil or gas well valve, the valve comprising a moveable member configured to move between open and closed configurations of the valve to allow flow of fluid through the valve when the valve is in the open configuration, and to resist flow of fluid through the valve when the valve is in the closed configuration, the valve having a sealing member providing a seat for seating of the movable member when the movable member is in the closed configuration; the movable member having a cutting surface arranged to shear against an anvil member when the movable member is moving between the open and closed configurations; wherein the method includes varying the spacing between the sealing member and the movable member during the stroke of the moveable member between the open configuration and the closed configuration.

Typically the sealing member moves away from the moveable member during the stroke of the moveable member between the open and closed configurations, typically moving so that the sealing member is displaced away from the cutting surface (typically the inner surface of the bore) of the movable member when the cutting surface engages the anvil member. Typically the sealing member is moveable and the anvil member is located in a fixed position. However, in certain embodiments, the anvil member can be moveable relative to a fixed sealing member. Typically one of the sealing member and the anvil is moveable in an axial direction, parallel to the axis of the throughbore of the valve.

Typically the valve is a ball valve and the movement of the valve between the open and closed configurations is a rotational movement to rotate a bore through the ball valve between an aligned and an unaligned configuration with respect to the bore of the conduit in which the valve is located.

5

Typically the sealing member displacement mechanism comprises a cam device having a non-circular profile that pushes the seal away from the moveable member. Typically the cam member is arranged to push the sealing member to a maximum separation from the movable member at the point on the stroke of the moveable member when the cutting surface of the moveable member is moving past the anvil member.

10

Typically the cam member is located on a rotating part of the valve, typically on the ball of the ball valve. Typically the ball is spherical, and the cam member is non-circular. Typically the cam member is located on a part of the moveable member such that the cam member engages with the sealing member but does not engage with the anvil member.

15

Typically the anvil and sealing members are concentrically arranged, typically with the anvil member located radially inwards of the sealing member, and the sealing member surrounding the anvil member.

20

Typically more than one cam member can be provided. The cam member can optionally be formed separately and attached subsequently to the moveable member, or can comprise an integral part of the moveable member in the form of a non-circular projection from the outer surface of the moveable member.

25

Optionally, a pair of cam members can be provided on the ball. Typically the pair of cam members can be parallel to one another, and can typically have the same non-circular arrangement, so that movement of the moveable member moves each of the cam members against the seal member at the same time. The cam members are typically arranged as chords on the ball, on the outer surface of the ball and spaced

30

radially between the centre of the ball and its outer surface. Typically the chordal cam members can be disposed at any location between the centre of the ball and the outer circumference, and do not need to be located halfway between these points. Optionally the cam members can be formed as tangential formations on the ball, or
5 can approach a tangential position.

The cam members are typically provided with an outer bearing surface that slides against the sealing member, to push the sealing member axially away from the moveable member during the stroke of the moveable member between the open
10 and closed configurations. The bearing surface is typically smooth and typically has a relatively low co-efficient of friction, and so typically slides against the seat of the sealing member without substantially deforming the seat.

Typically the sealing member is biased against the moveable member by a resilient means, typically a spring such as a coil spring, although gas springs, and other
15 resilient devices can be employed to press the sealing member axially against the moveable member. Typically the cam member moves the sealing member in such a way as to energise the resilient devices that bias the sealing member against the movable member. Typically the cam members overcome the force of the springs
20 etc. to move the sealing members radially back axially with respect to the bore of the tubular in which the valve is located, moving the sealing faces on the seat of the sealing member away from the hard faced cutting surface as it passes across the anvil member.

Typically the sealing member is moved out of contact with the moveable member by the cam when the cutting surface engages the anvil member, and moves back into contact with the moveable member when the cutting surface has passed the sealing member and the sealing surface of the moveable member (e.g. the outer surface of the ball) is aligned with the sealing member.
25

The resilient devices biasing the sealing member against the moveable member then typically push the sealing member against the sealing face of the moveable member
30

to seal against passage of fluid through the valve when the cutting face has passed the anvil member and seal member.

Typically the anvil member has a close fit with the cutting surface of the moveable member and provides a shearing function to shear any wires or other longitudinal members passing through the bore of the valve. Typically the opposing faces of the anvil member and the cutting surface and the movable member can be faced with hard materials such as tungsten carbide, diamond, etc.

Spacing the cam members radially outside the anvil member but with a radial spacing that is less than the outer diameter of the sealing member means that the rotation of the ball to rotate the cam members can engage the cam members with the sealing member but can avoid reacting the cam members against the anvil member. Therefore, the seal member can be pushed axially away from the ball without engaging the anvil members and reducing the force available from the cam members as a result of the rotation of the ball.

Typically the cam members engage the sealing sleeve at a position radially outside a resilient seal on the sealing sleeve. Typically the cam members do not engage the resilient seal during the stroke of the movable member between the open and closed configurations.

Typically the sealing member remains axially spaced from the movable member until the cutting surface of the movable member has moved past the resilient seal on the sealing member, at which point the sealing member can be moved back into contact with the movable member to compress the resilient seal against the movable member once more.

The various aspects of the present invention can be practiced alone or in combination with one or more of the other aspects, as will be appreciated by those skilled in the relevant arts. The various aspects of the invention can optionally be provided in combination with one or more of the optional features of the other

aspects of the invention. Also, optional features described in relation to one embodiment can typically be combined alone or together with other features in different embodiments of the invention.

5 Various embodiments and aspects of the invention will now be described in detail with reference to the accompanying figures. Still other aspects, features, and advantages of the present invention are readily apparent from the entire description thereof, including the figures, which illustrates a number of exemplary
10 other and different embodiments and aspects, and its several details can be modified in various respects, all without departing from the spirit and scope of the present invention. Accordingly, the drawings and descriptions are to be regarded as illustrative in nature, and not as restrictive. Furthermore, the terminology and phraseology used herein is solely used for descriptive purposes and should not be
15 construed as limiting in scope. Language such as "including," "comprising," "having," "containing," or "involving," and variations thereof, is intended to be broad and encompass the subject matter listed thereafter, equivalents, and additional subject matter not recited, and is not intended to exclude other additives, components, integers or steps. Likewise, the term "comprising" is considered
20 synonymous with the terms "including" or "containing" for applicable legal purposes.

Any discussion of documents, acts, materials, devices, articles and the like is included in the specification solely for the purpose of providing a context for the
25 present invention. It is not suggested or represented that any or all of these matters formed part of the prior art base or were common general knowledge in the field relevant to the present invention.

In this disclosure, whenever a composition, an element or a group of elements is
30 preceded with the transitional phrase "comprising", it is understood that we also contemplate the same composition, element or group of elements with transitional phrases "consisting essentially of", "consisting", "selected from the group of

consisting of", "including", or "is" preceding the recitation of the composition, element or group of elements and vice versa.

All numerical values in this disclosure are understood as being modified by "about".

5 All singular forms of elements, or any other components described herein are understood to include plural forms thereof and vice versa.

An embodiment of the invention will now be described by way of example and with reference to the accompanying drawings in which:

10 Figs 1, 2 and 3 are plan, end and side views of a valve in an open configuration;
 Figs 4 and 5 are enlarged views of Figs 1 and 3 respectively;
 Figs 6 and 7 are plan and side views of the Fig 1 valve in a transitional configuration during movement of the valve between open and closed configurations;
 Figs 8 and 9 are enlarged views of Figs 6 and 7 respectively;
 15 Figs 10 and 11 are plan and side views of the Fig 1 valve in a closed configuration;
 Figs 12 and 13 are enlarged views of Figs 10 and 11 respectively;
 Figs 14 and 15 are perspective views of the ball of the valve of Fig 1 in different rotational positions of the ball; and
 Fig 16 is a plan view of a second valve.

20

Referring now to the drawings, and referring particularly to Figs 1 to 5, in an open configuration a valve V has a through bore T that is open and closed by first and second moveable members in the form of ball members B1 and B2 arranged in series in the valve V, and arranged to provide backup in the event of failure of one of
 25 the ball members. Each ball member B comprises a generally spherical ball 5 mounted on a transverse axle 2. The axles 2 are parallel to one another in the valve V and extend perpendicular to the axis of the through bore T, allowing rotation of the balls 5 around the axles 2. Each ball 5 has a through bore 6, which can be brought in an out of register with the through bore T. Rotation of the balls 5 around
 30 the axles 2 rotates the through bore 6 in and out of alignment with the through bore of the valve T, thereby moving the valve V from an open configuration, in which the through bore of 6 of each ball 5 is aligned with the through bore T of the valve, to a

closed position, in which the through bore 6 of each ball 5 is non-aligned with the through bore T of the valve (and is typically perpendicular thereto).

Each ball 5 seats against a sealing member in the form of a sealing sleeve 10. The
5 sealing sleeve 10 typically has an end surface with a seat in the form of a bevelled
inner surface closest to the ball 5 where it engages with the ball 5. The bevelled
inner surface of the end is configured to match the sealing face of the ball 5s to
create a seal denying fluid passage past the ball 5. Typically the bevelled inner face
carries a resilient seal, such as an o-ring seal retained in a seal groove. The seal is
10 compressed between the bevelled face of the sleeve 10 and the sealing face of the
ball when the valve is closed. The sealing sleeve 10 is axially movable in a direction
parallel to the axis of the through bore T and is biased against the sealing face 5s of
the ball 5 by a spring 11. This compresses the resilient seal on the inner bevelled
surface of the sleeve 10 between the sleeve 10 and the ball 5, to resist passage of
15 fluid. The end face of the sleeve 10 outside the bevelled inner face typically has a
flat face, which is typically perpendicular to the axis of the throughbore. Typically
the flat end face acts as a bearing surface, and can be provided with a friction
reducing coating. The end bearing surface is typically located outside the resilient
seal, spaced radially away from the seal.

20 The sealing sleeve 10 has a central bore which is coaxial with the through bore T.
Within the bore of the sealing sleeve 10 is provided an anvil member in the form of
an anvil sleeve 15, which typically also has a through bore that is coaxial with the
bore T of the valve, and is typically configured to allow the passage of fluids through
25 the valve V when the balls 5 are in the open orientation. The inner surface of the
neck of the anvil sleeve 15 nearest to the ball 5 has a cutting surface in the form of a
hard faced ring 15h formed of a hardened material such as ceramic material,
diamond or tungsten carbide etc. Typically the ring 15h is provided on the inner
surface of the anvil sleeve 15. Typically the anvil sleeve 15 is fixed within the
30 through bore T so that it is not axially moveable and is adapted to resist axial forces
tending to move it. It can be connected within the bore T by screw threads, or by

collets or dogs etc. Typically the anvil sleeve 15 remains fixed in position when the sealing sleeve 10 moves axially with respect to the through bore T.

The outer surface of the ball 5 typically has at least one cam member 20. The cam member typically extends circumferentially with respect to the ball 5, at a radial spacing from the centre of the ball that is in alignment with a portion of the flat bearing end surface of the sealing sleeve 10, but is radially spaced outward from the anvil sleeve 15, and out of alignment with it. Typically two cam members 20 are provided at chordal or tangential locations on the outer surface of the ball 5 at a spacing that engages the flat end surface of the sealing sleeve 10 at each side of the sealing sleeve 10, but so that the lateral spacing between each of the cam members 20 is larger than the outer diameter of the anvil sleeve 15, which passes between the cam members 20. The cam members 20 are typically arranged parallel to the through bore 6 of the bore through each ball 5, so that as the ball 5 rotates around the axle 2, the cam members 20 are rotated at the same time. The cam members 20 on each side of the ball 5 are typically symmetrical in their cam profile so that rotation of the ball presents a uniform side profile as the cam profile changes with the rotation. The cam members typically have non-circular side profiles as best seen in Figs 3, 5, 7, 9, 11, 13, 14 and 15. Typically the cam members engage the bearing surface on the flat end face of the sealing sleeve 10 outside the bevelled inner face with the resilient seal, and hence the cam surfaces typically do not contact the more delicate seat with the resilient seal inside the flat end face.

Rotation of the balls 5 by the axles 2 rotates each cam member 20 so that the cam profile of the part of the cam member 20 that engages the flat end bearing surface of the sealing sleeve 10 changes with the rotational position of the ball 5. When the valve V is in the open configuration shown in Figs 1 to 5 and 16, the side profile of the cam devices 20 is very close to the nominal outer circumference of the ball 5, and has little or (typically) no effect on the axial movement of the sealing sleeve 10, which remains pressed hard against the sealing surface 5s of the ball 5, compressing the resilient seal and sealing the throughbore. However, as the ball 5 starts to rotate from the open to the closed position, and the alignment of the cutting surface 6h of

the ball 5 starts to change relative to the sealing sleeve 10, the profile of the cam members 20 that is pressed against the flat end bearing surface of the sealing sleeve 10 also starts to change, and the cam profile of the cam members 20 starts to increase beyond the nominal outer diameter of the ball, thereby pushing the sealing sleeve 10 axially away from the ball in the direction of arrow A against the force of the spring 11 as the rotation progresses and the change in alignment continues. The axial displacement of the cam profile reaches a peak at the point shown in Fig 9. At this stage, a hard facing ring 6h on the inner surface of the through bore 6 through the ball 5 is about to shear against the hard facing 15h on the anvil sleeve 15, in order to cut any wire, cable or other elongate member that remains within the through bore T of the valve V. The hard facing ring 6h is axially spaced away from the delicate resilient seal on the bevelled inner surface of the sealing sleeve 10 because of the action of the cam members 20, and so it cannot rake across the seat or damage the resilient seal as it rotates in relation to the anvil sleeve 15.

At this stage, the cam members 20 are approaching or optionally have reached their maximum displacement away from the nominal outer surface of the ball, and they have pushed the sealing sleeve 10 axially back in the direction of arrow A against the force of the springs 11, thereby compressing the springs, and pushing the seat with the delicate resilient sealing face at the bevelled inner surface of the end of the sealing sleeve 10 axially away from the moving cutting surface 6h. The increased axial displacement of the cam members continues while the ball 5 rotates past the cutting point shown in Fig 9 until the hard faces 6h and 15h have passed one another and the hard face 6h on the inner surface of the bore 6 through the ball 5 has rotated past the outer diameter of the sealing sleeve 10 and can no longer rake the seat at the bevelled end sealing surface of the sealing sleeve 10. Thus the cams 20 keep the sealing sleeve 10 spaced away from the ball 5 for as long as the moving cutting surface 6h is aligned with the resilient seal on the bevelled end surface of the sleeve 10. Therefore, while the cutting surface 6h is inside the diameter of the sealing sleeve 10, the sealing sleeve 10 and cutting surface 6h are spaced apart, and the cutting surface cannot rake the resilient seal. Typically the cams 20 keep the sealing sleeve 10 spaced axially away from the movable member at least until the

cutting surface on the ball 5 has rotated past the sealing sleeve 10, but it is especially useful for the separation to be maintained until the whole of the rotating cutting surface 6h has moved past the outer diameter of the sleeve 10, so that the end surfaces of the sleeve 10 are kept axially away from the rotating cutting surface 6h on the ball. After the point of maximum displacement, the cam profile on the cam members 20 starts to diminish to reduce the axial displacement of the cam relative to the nominal outer diameter of the ball 5, which allows the spring 11 to push the sealing sleeve 10 back into engagement with the sealing surface 5s of the ball as the cams 20 reduce their displacement. At this point, since the ball has rotated past the point at which the cutting surface is aligned with the sealing sleeve 10, the delicate sealing surface on the sleeve can never contact the cutting surface of the ball 5, so even if the moving cutting surface 6h eventually becomes deformed or burred through the high forces required for the cutting process, the burrs or surface deformations on the cutting surface do not interfere with the delicate resilient seal on the sleeve 10 when the valve is opening and closing. The valve V is then in the configuration shown in Figs 11 to 16, in which the spring 11 is forcing the sealing sleeve 10 hard against the sealing surface 5s of the ball 5 in the direction of the arrow B, as the hard facing cutting edge 6h has been moved out alignment with the delicate sealing surface of the sealing sleeve 10.

Stroking of the valve V back to its open configuration automatically moves the cam members 20 in reverse urging the sealing sleeve 10 axially away from the ball 5, so that the delicate resilient sealing surface of the sealing sleeve 10 is not raked by the hard facing 6h on the ball 5 during the rotation.

The cam members 20 can be fully circumferential, extending around the entire circumference, or can extend around only a part of the circumference if desired. One cam member can suffice, but a more even force is applied by the more symmetrical arrangement of two cam members, and a more even movement of the sealing sleeve 10 is thereby achieved.

In certain valves the movable member e.g. the ball can be asymmetrically arranged on opposite sides of the axis through the valve. In certain embodiments the tolerance of the ball is different on one side, as compared with the other side of the axis. Typically the ball has a differential sealed area on different sides of the axis, which under pressure causes the ball to move from one side to the other, under the force of the pressure differential. Typically also, the ball has a stop member provided on one side of the axis, typically on the side of the axis to which the ball is urged by the asymmetric differential. Typically the stop member engages the ball with a very precise tolerance, which is more precise than the tolerance between the ball and other parts of the valve, for example between the ball and the socket housing the ball. This asymmetric arrangement between the two sides of the movable member typically means that during assembly, the ball can be held in the socket with the stop member engaging the ball in a position in the socket that is defined by the precise tolerance between the ball and the stop member, rather than by the less precise tolerance between the ball and the socket for example. Also, the asymmetric arrangement which typically causes the ball to move toward the stop member and engage it in that precise location in the socket enables higher confidence location of the ball in the socket during stroking of the moveable member under load, because under load, the ball moves preferentially to engage the stop member, with which it has a very precise tolerance. Therefore, under load, when the ball is engaged with the precise tolerance stop member, the ball is less prone to uncontrolled oscillations or imperceptible "rattling" of the ball in the socket due to machining tolerances between the two, so the location of the ball during stroking is more consistent and more predictable, as the ball is preferentially moved in the direction favoured by the asymmetry between the two sides, and is held in a precise location by the precise tolerance between the stop member and the ball. Generally the machining tolerances between the ball and the socket are very tight, as it is typically important that the contact point between the cutting surface and the anvil member remains as close to possible to pure shear, and free of bending and smearing effects. This is only achievable by ensuring tight fit, good concentricity etc. between the cutting surface on the ball and the shearing surface on the anvil member. It has been found that introducing the asymmetry in the ball

increases the predictability of the relative positions of the ball and the anvil, especially under fluid pressure in an axial direction tending to urge the ball in a particular axial direction. The difference need not be noticeable to the naked eye, and a very small asymmetric difference can be sufficient in certain embodiments to introduce the required bias, and improve the predictability of the movement of the ball under pressure. Fig 16 shows one such example. Referring to figure 16, a modified valve V' is generally similar to the valve V and similar features will be indicated in figure 18 with the same reference numbers, but increased by 100. The valve V' has at least one ball 105 which is rotatable in a through bore T', on axles 102 which are sealed at S1 and S2, in order to rotate a through bore 106 in the ball 105 in and out of register with the through bore T', to open and close the valve V' in the same manner as previously described for the earlier valve V. The valve V' has a sealing sleeve 110, urged by springs 111, and an anvil sleeve 115, all of which function essentially as described for the previous valve V. The difference between the figure 18 valve V' and the valve V disclosed in the previous figures is that in the valve V', the ball 105 is asymmetrically arranged within the through bore T'. In particular, the OD of the axles 105 is typically asymmetric in the valve V', creating a differential sealed area between o-ring or other seals at S1 and S2. In this example, the OD of the axle on the left side of the valve, at S2 is very slightly greater than the corresponding OD on the axle on the right side of the valve at S1. Therefore, the diameter of the sealed area at S2 on the left is larger than the diameter of the sealed area at S1 on the right. Also, on the left side, radially outwardly displaced from S2, the end face of the axle 102 is engaged with a stop member in the form of a bearing 101. The bearing 101 is typically a ball bearing, but other kinds of bearing can be used, e.g. a thrust bearing etc. The tolerance between the bearing 101 and the end face of the axle 102 has a very precise tolerance, so that when the end face of the axle 102 is engaged with the bearing 101, the displacement of the ball 105 in relation to the central axis of the throughbore T' is very precisely known, as a result of the precise tolerance between the bearing 101 and the end face of the axle 102. Because the orientation of the ball 105 relative to the axis of the through bore T' is dependent on the precise tolerance of the stop member 101 and axle 102, the tolerance of the overall system is significantly improved without necessarily

improving the tolerance of the other features of the ball 105 within the socket, which can typically be engineered to less precise tolerances, without compromising the performance of the valve V'. When the ball 105 rotates as previously described, the differential sealed areas between S1 and S2 moves the ball 105 preferentially
5 moves toward the left seal S2 in tighter engagement with the stop member 101. Since the stop member 101 and the end face of the axle 102 have the precise tolerance referred to previously, there is significantly more certainty as to the location of the ball 105 under load. The precise tolerance of the stop member 101 and the end face of the axle 102 can be manipulated relatively easily, and the rest of
10 the socket for housing the ball in the body of the valve V' can be made up to a less precise tolerance, without compromising the overall function of the valve.. In the present embodiment, the stop member is provided by the bearing 101, which is typically a ball bearing, but other spacers can be used, and other asymmetric characteristics can be adopted (with or without spacers) in alternative examples of
15 the invention.

Modifications and improvements can be incorporated without departing from the scope of the invention. For example, the sealing member can be moved by devices other than cam devices, for example a hydraulic cylinder.

Claims

- 1 A valve for use in an oil or gas well, the valve comprising a moveable
 member (5) configured to move between open and closed configurations of the
 5 valve to allow and resist flow of fluid through the valve in respective open and
 closed configurations, the valve having a sealing member (10) providing a seat for
 seating of the moveable member (5) when the moveable member (5) is in the closed
 configuration; the moveable member (5) having a cutting surface (6h) arranged to
 shear against an anvil member (15) when the moveable member (5) is moving
 10 between the open and closed configurations; wherein the valve has a sealing
 member displacement mechanism (20) configured to vary the spacing between the
 sealing member (10) and the movable member (5) when the moveable member (5)
 is moving between the open and the closed configurations.

- 15 2 A valve as claimed in claim 1, wherein the sealing member (10) moves away
 from the moveable member (5) during the stroke of the moveable member (5)
 between the open and closed configurations.

- 20 3 A valve as claimed in claim 1 or claim 2, wherein the sealing member (10)
 the sealing member (10) remains axially spaced from the movable member (5) until
 the cutting surface (6h) of the movable member (5) has moved past the seat of the
 sealing member (10), after which point the sealing member (10) is pressed against
 the movable member (5) to engage the movable member (5) on the seat of the
 sealing member (10).

- 25 4 A valve as claimed in any one of claims 1-3, wherein the valve has a bore
 with an axis, and wherein the sealing member (10) moves axially within the bore
 relative to the movable member (5).

- 30 5 A valve as claimed in any one of claims 1-4, wherein the valve is a ball valve
 having a ball (5) with a through bore and the movement of the valve between the
 open and closed configurations is a rotational movement to rotate a bore through

the ball (5) between an aligned and an unaligned configuration with respect to the through bore of the valve.

6 A valve as claimed in any one of claims 1-5, wherein the sealing member
5 displacement mechanism comprises one or more cam devices (20) having a cam
surface with a non-circular profile, and wherein the movement of the movable
member (5) from the open configuration to the closed configuration rotates the or
each cam device (20 and moves the non-circular cam surface over the sealing
member (10) thereby increasing the displacement between the sealing member
10 (10) and the moveable member (5) as the sealing member (10) moves along the
non-circular cam surface.

7 A valve as claimed in claim 6, wherein the cam device (20) is configured to
displace the sealing member (10) to a maximum separation from the movable
15 member (5) at the point on the stroke of the moveable member (5) when the cutting
surface (6h) is passing the anvil member (15).

8 A valve as claimed in any one of claims 6-7 wherein the or each cam surface
comprises a non circular projection extending from the outer surface of the
20 moveable member (5).

9 A valve as claimed in any one of claims 6-8, wherein the valve is a ball valve
having a ball (5), and wherein the cam device (20) is arranged as a chord on the ball
(5), on the outer surface of the ball (5) and spaced radially between the centre of the
25 ball (5) and its outer surface.

10 A valve as claimed in any one of claims 6-9, wherein the or each cam device
(20) is arranged on the movable member (5) out of alignment with the anvil
member (15) whereby the movement of the cam device (20) to engage the or each
30 cam device (20) with the sealing member (10) does not engage the or each cam
device (20) with the anvil member (15).

11 A valve as claimed in any one of claims 6-10, wherein the non-circular cam
surface of the or each cam device (20) comprises an outer bearing surface that
slides against the sealing member (10), to push the sealing member (10) axially
away from the moveable member (5) during the stroke of the moveable member (5)
5 between the open and closed configurations.

12 A valve as claimed in claim 11, wherein the outer bearing surface of the or
each cam device (20) is arranged on the movable member out of alignment with the
seat on the sealing member (10), whereby the or each cam device (20) does not
10 engage the seat of the sealing member (10) during the stroke of the movable
member between the open and closed configurations.

13 A valve as claimed in any one of claims 1-12, wherein the anvil member (15)
and the sealing member (10) are concentrically arranged, with the anvil member
15 (15) located radially inwards of the sealing member (10), and the sealing member
(10) surrounding the anvil member (15).

14 A valve as claimed in any one of claims 1-13, wherein the sealing member
(10) is biased axially toward the moveable member (5) by a resilient device (11),
20 and wherein the movement of the movable member (5) from the open to the closed
configuration energises the resilient device (11).

15. A method of operating an oil or gas well valve, the valve comprising a
moveable member (5) configured to move between open and closed configurations
25 of the valve to allow flow of fluid through the valve when the valve is in the open
configuration, and to resist flow of fluid through the valve when the valve is in the
closed configuration, the valve having a sealing member (10) providing a seat for
seating of the movable member (5) when the movable member (5) is in the closed
configuration; the movable member (5) having a cutting surface (6h) arranged to
30 shear against an anvil member (15) when the movable member (5) is moving
between the open and closed configurations;

wherein the method includes varying the spacing between the sealing member (10) and the movable member (15) during the stroke of the moveable member (5) between the open configuration and the closed configuration.

5 16. The method of claim 15, wherein the valve includes a sealing member displacement mechanism for moving the sealing member (10) comprising a cam device (20) having a cam surface with a non-circular profile provided on the outer surface of the movable member (5), and wherein the movement of the movable member (5) from the open configuration to the closed configuration moves the non-circular cam surface
10 with respect to the sealing member (10);

 -and wherein the method includes moving the non-circular cam surface relative to the sealing member (10) so that the sealing member (10) translates along the non-circular cam surface, thereby varying the displacement between the sealing member (10) and the moveable member (5) as the sealing member (10) moves along the non-
15 circular cam surface during the stroke of the moveable member (5) between the open configuration and the closed configuration.

 17. The method of claim 16, wherein the valve includes a resilient device that is arranged to urge the sealing member axially against the ball to seal against the passage
20 of fluid through the valve and wherein the method includes energising the resilient device by rotation of the ball during the stroke of the ball between the open and closed configurations.