

MULTIMEDIA QUALITY MONITORING METHOD, AND DEVICE

TECHNICAL FIELD

5 [0001] The present invention relates to the field of information technologies, and in particular, to a multimedia quality monitoring method, and a device.

BACKGROUND

[0002] With development of network technologies and the advent of a new era of multimedia, video on demand, web television, video telephone and the like have become main
10 services of a broadband network. For a multimedia service, an amount of data is large, a requirement for real-time performance is high, and user sensitivity is strong; therefore, multimedia quality monitoring has a very important significance for a manufacturer and an operator of multimedia communications equipment.

[0003] In the prior art, audio quality and video quality of multimedia are separately
15 acquired first, and then, multimedia quality is obtained by using the two types of quality. However, when cases such as packet loss and the like occurs in multimedia, it is difficult to reflect multimedia distortion caused by the packet loss by using an existing method, thereby making a multimedia quality monitoring result inaccurate.

SUMMARY

20 [0004] Embodiments of the present invention provide a multimedia quality monitoring method, and a device, so as to improve accuracy of a multimedia quality monitoring result.

[0005] According to a first aspect, an embodiment of the present invention provides a

multimedia quality monitoring method, including:

determining reference quality of multimedia according to reference video quality and reference audio quality of the multimedia;

5 acquiring multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs; and

determining quality of the multimedia according to the reference quality of the multimedia and the multimedia distortion quality.

[0006] In a possible implementation manner of the first aspect, the determining reference quality of multimedia according to reference video quality and reference audio quality of the multimedia includes: determining the reference quality of the multimedia according to
10 $AV_MOSC = av1 \cdot V_MOSC + av2 \cdot A_MOSC + av3 \cdot V_MOSC \cdot A_MOSC + av4$, where AV_MOSC is the reference quality of the multimedia, V_MOSC is the reference video quality, A_MOSC is the reference audio quality, and $av1$, $av2$, $av3$, and $av4$ are constants.

[0007] In another possible implementation manner of the first aspect, the multimedia distortion quality includes: multimedia distortion quality due to packet loss and/or multimedia distortion quality due to rebuffering; and the acquiring multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs includes: determining, according to the reference video quality and a video packet loss rate, video quality due to packet loss that is after a packet in a video of the multimedia is lost, and/or
20 determining, according to the reference audio quality and an audio packet loss rate, audio quality due to packet loss that is after a packet in an audio of the multimedia is lost; acquiring the multimedia distortion quality due to packet loss according to the video quality due to packet loss and/or the audio quality due to packet loss; and/or acquiring the multimedia distortion quality due to rebuffering according to a rebuffering parameter, during a
25 transmission process, of the multimedia.

[0008] In another possible implementation manner of the first aspect, the acquiring the multimedia distortion quality due to packet loss according to the video quality due to packet loss and/or the audio quality due to packet loss includes: determining video distortion quality due to packet loss according to the video quality due to packet loss and the reference video

quality, and determining audio packet loss distortion quality according to the audio quality due to packet loss and the reference audio quality; determining a video packet loss distortion factor according to the video distortion quality due to packet loss and the reference video quality, and determining an audio packet loss distortion factor according to the audio packet loss distortion quality and the reference audio quality; determining a multimedia packet loss distortion factor according to the video packet loss distortion factor and the audio packet loss distortion factor; and determining the multimedia distortion quality due to packet loss according to the multimedia packet loss distortion factor and the reference quality of the multimedia.

[0009] In yet another possible implementation manner of the first aspect, the determining video distortion quality due to packet loss according to the video quality due to packet loss and the reference video quality, and determining audio packet loss distortion quality according to the audio quality due to packet loss and the reference audio quality includes: determining the video distortion quality due to packet loss V_DP according to $V_DP = V_MOSC - Video_MOS$, where V_MOSC is the reference video quality, and $Video_MOS$ is the video quality due to packet loss; and determining the audio packet loss distortion quality A_DP according to $A_DP = A_MOSC - Audio_MOS$, where A_MOSC is the reference audio quality, and $Audio_MOS$ is the audio quality due to packet loss.

[0010] In yet another possible implementation manner of the first aspect, the determining a video packet loss distortion factor according to the video distortion quality due to packet loss and the reference video quality, and determining an audio packet loss distortion factor according to the audio packet loss distortion quality and the reference audio quality includes: determining the video packet loss distortion factor AV_DFV according to $AV_DFV = \frac{V_DP}{V_MOSC}$ or $AV_DFV = \frac{V_MOSC - Video_MOS}{V_MOSC}$, where V_MOSC is the reference video quality, and V_DP is the video distortion quality due to packet loss; and/or determining the audio packet loss distortion factor AV_DFA according to

$$AV_DFA = \frac{A_DP}{A_MOSC} \quad \text{or} \quad AV_DFA = \frac{A_MOSC - \text{Audio_MOS}}{A_MOSC}, \quad \text{where } A_MOSC \text{ is the}$$

reference audio quality, and A_DP is the audio packet loss distortion quality.

[0011] In another possible implementation manner of the first aspect, the determining a multimedia packet loss distortion factor according to the video packet loss distortion factor and the audio packet loss distortion factor includes:

determining the multimedia packet loss distortion factor AV_DF according to

$$\frac{av5 \cdot AV_DFV + av6 \cdot AV_DFA}{1 + av5 \cdot AV_DFV + av6 \cdot AV_DFA} \quad \text{or} \quad AV_DF = av5 + av6 \cdot AV_DFV + av7 \cdot AV_DFA,$$

where AV_DFA is the audio packet loss distortion factor, AV_DFV is the video packet loss distortion factor, and $av5$, $av6$ and $av7$ are constants.

[0012] In yet another possible implementation manner of the first aspect,

the determining the multimedia distortion quality due to packet loss according to the multimedia packet loss distortion factor and the reference quality of the multimedia includes: determining the multimedia distortion quality due to packet loss AV_DP according to $AV_DP = (AV_MOSC - MOS_MIN) \cdot AV_DF$, where AV_MOSC is the reference quality of the multimedia, MOS_MIN is lowest quality of the multimedia, and AV_DF is the multimedia packet loss distortion factor.

[0013] In another possible implementation manner of the first aspect, the rebuffering parameter includes one or any combination of the following: the number of rebufferings, rebuffering duration, an impact factor between multiple rebufferings, and multimedia initial quality.

[0014] In yet another possible implementation manner of the first aspect, the acquiring the multimedia distortion quality due to rebuffering according to a rebuffering parameter, during a transmission process, of the multimedia includes: acquiring the multimedia distortion quality due to rebuffering according to

$$AV_DR = (Audiovisual_Quality - MOS_MIN) \cdot \frac{\left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}}{1 + \left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}},$$

where *Audiovisual_Quality* is the multimedia initial quality, *NR* is the number of rebufferings, *ARL* is the rebuffering duration, *MRF* is the impact factor between multiple rebufferings, and *av7–av12* are constants.

[0015] In another possible implementation manner of the first aspect, the determining
5 quality of the multimedia according to the reference quality of the multimedia and the multimedia distortion quality includes: determining the multimedia quality due to packet loss according to the reference quality of the multimedia and the multimedia distortion quality due to packet loss; and determining the quality of the multimedia according to the reference quality of the multimedia or the multimedia quality due to packet loss, and the distortion
10 quality due to rebuffering.

[0016] In another possible implementation manner of the first aspect, the determining the multimedia quality due to packet loss according to the reference quality of the multimedia and the multimedia distortion quality due to packet loss includes: determining the multimedia quality due to packet loss *AV_MOSP* according to $AV_MOSP = AV_MOSC - AV_DP$,
15 where *AV_MOSC* is the reference quality of the multimedia, and *AV_DP* is the multimedia distortion quality due to packet loss.

[0017] In another possible implementation manner of the first aspect, the determining the quality of the multimedia according to the reference quality of the multimedia or the multimedia quality due to packet loss, and the distortion quality due to rebuffering includes:
20 determining the quality *AV_MOSR* of the multimedia according to $AV_MOSR = Audiovisual_Quality - AV_DR$, where *Audiovisual_Quality* is the reference quality of the multimedia or the multimedia quality due to packet loss, and *AV_DR* is the distortion quality due to rebuffering.

[0018] According to yet another aspect, an embodiment of the present invention provides
25 a multimedia quality monitoring apparatus, including:

a first determining module, configured to determine reference quality of multimedia according to reference video quality and reference audio quality of the multimedia;

a second determining module, configured to acquire multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs; and

a third determining module, configured to determine quality of the multimedia according to the reference quality of the multimedia and the multimedia distortion quality.

5 [0019] In a possible implementation manner of a second aspect, the first determining module is specifically configured to:

determine the reference quality of the multimedia according to

$AV_MOSC = av1 \cdot V_MOSC + av2 \cdot A_MOSC + av3 \cdot V_MOSC \cdot A_MOSC + av4$, where

AV_MOSC is the reference quality of the multimedia, V_MOSC is the reference video quality,

10 A_MOSC is the reference audio quality, and av1, av2, av3, and av4 are constants.

[0020] In a possible implementation manner of the second aspect, the multimedia distortion quality includes: multimedia distortion quality due to packet loss and/or multimedia distortion quality due to rebuffering; and the second determining module is specifically configured to: determine, according to the reference video quality and a video packet loss rate,

15 video quality due to packet loss that is after a packet in a video of the multimedia is lost, and/or determine, according to the reference audio quality and an audio packet loss rate, audio quality due to packet loss that is after a packet in an audio of the multimedia is lost; acquire the multimedia distortion quality due to packet loss according to the video quality due to packet loss and/or the audio quality due to packet loss, and/or acquire the multimedia distortion quality due to rebuffering according to a rebuffering parameter, during a transmission process, of the multimedia.

[0021] In a possible implementation manner of the second aspect, the second determining module is specifically configured to: determine video distortion quality due to packet loss according to the video quality due to packet loss and the reference video quality, and
25 determine audio packet loss distortion quality according to the audio quality due to packet loss and the reference audio quality; determine a video packet loss distortion factor according to the video distortion quality due to packet loss and the reference video quality, and determine an audio packet loss distortion factor according to the audio packet loss distortion quality and the reference audio quality; determine a multimedia packet loss distortion factor

according to the video packet loss distortion factor and the audio packet loss distortion factor;
and determine the multimedia distortion quality due to packet loss according to the
multimedia packet loss distortion factor and the reference quality of the multimedia.

[0022] In a possible implementation manner of the second aspect, the second determining
5 module is specifically configured to: determine the video distortion quality due to packet loss
V_DP according to $V_DP = V_MOSC - Video_MOS$, where V_MOSC is the reference
video quality, and Video_MOS is the video quality due to packet loss; and determine the
audio packet loss distortion quality A_DP according to $A_DP = A_MOSC - Audio_MOS$,
where A_MOSC is the reference audio quality, and Audio_MOS is the audio quality due to
10 packet loss.

[0023] In a possible implementation manner of the second aspect, the second determining
module is specifically configured to:

determine the video packet loss distortion factor AV_DFV according to
 $AV_DFV = \frac{V_DP}{V_MOSC}$ or $AV_DFV = \frac{V_MOSC - Video_MOS}{V_MOSC}$, where V_MOSC is the

15 reference video quality, and V_DP is the video distortion quality due to packet loss; and/or,
determine the audio packet loss distortion factor AV_DFA according to
 $AV_DFA = \frac{A_DP}{A_MOSC}$ or $AV_DFA = \frac{A_MOSC - Audio_MOS}{A_MOSC}$, where A_MOSC is the

reference audio quality, and A_DP is the audio packet loss distortion quality.

[0024] In a possible implementation manner of the second aspect, the second determining
20 module is specifically configured to: determine the multimedia packet loss distortion factor

AV_DF according to $\frac{av5 \cdot AV_DFV + av6 \cdot AV_DFA}{1 + av5 \cdot AV_DFV + av6 \cdot AV_DFA}$ or

$AV_DF = av5 + av6 \cdot AV_DFV + av7 \cdot AV_DFA$, where AV_DFA is the audio packet loss
distortion factor, AV_DFV is the video packet loss distortion factor, and av5, av6 and av7 are
constants.

[0025] In a possible implementation manner of the second aspect, the second determining

module is specifically configured to: determine the multimedia distortion quality due to packet loss AV_DP according to $AV_DP = (AV_MOSC - MOS_MIN) \cdot AV_DF$, where AV_MOSC is the reference quality of the multimedia, MOS_MIN is lowest quality of the multimedia, and AV_DF is the multimedia packet loss distortion factor.

5 [0026] In a possible implementation manner of the second aspect, the rebuffering parameter includes one or any combination of the following: the number of rebufferings, rebuffering duration, an impact factor between multiple rebufferings, and multimedia initial quality.

[0027] In a possible implementation manner of the second aspect, the second determining
10 module is specifically configured to: according to

$$AV_DR = (Audiovisual_Quality - MOS_MIN) \cdot \frac{\left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}}{1 + \left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}},$$

acquire the multimedia distortion quality due to rebuffering, where $Audiovisual_Quality$ is the multimedia initial quality, NR is the number of rebufferings, ARL is the rebuffering duration, MRF is the impact factor between multiple rebufferings, and $av7 - av12$ are
15 constants.

[0028] In a possible implementation manner of the second aspect, the third determining module is specifically configured to: determine the multimedia quality due to packet loss according to the reference quality of the multimedia and the multimedia distortion quality due to packet loss; and determine the quality of the multimedia according to the reference quality
20 of the multimedia or the multimedia quality due to packet loss, and the distortion quality due to rebuffering.

[0029] In a possible implementation manner of the second aspect, the third determining module is specifically configured to: determine the multimedia quality due to packet loss AV_MOSP according to $AV_MOSP = AV_MOSC - AV_DP$, where AV_MOSC is the
25 reference quality of the multimedia, and AV_DP is the multimedia distortion quality due to packet loss.

[0030] In a possible implementation manner of the second aspect, the third determining module is specifically configured to: determine the quality AV_MOSR of the multimedia according to $AV_MOSR = Audiovisual_Quality - AV_DR$, where *Audiovisual_Quality* is the reference quality of the multimedia or the multimedia quality due to packet loss, and
5 AV_DR is the distortion quality due to rebuffering.

[0031] According to another aspect, an embodiment of the present invention further provides a terminal, including a receiving module, configured to receive multimedia; and further including the multimedia quality monitoring apparatus provided in the embodiment of the present invention.

10 [0032] According to another aspect, an embodiment of the present invention further provides a terminal, including a receiver, configured to receive multimedia; and further including: a processor, configured to execute the multimedia quality monitoring method provided in the embodiment of the present invention.

[0033] According to another aspect, an embodiment of the present invention further
15 provides a network device, including a receiving module, configured to receive multimedia; and further including the multimedia quality monitoring apparatus provided in the embodiment of the present invention.

[0034] According to another aspect, an embodiment of the present invention further provides a network device, including a receiver, configured to receive multimedia; and further
20 including: a processor, configured to execute the multimedia quality monitoring method provided in the embodiment of the present invention.

[0035] According to the multimedia quality monitoring method, and the device that are provided in the embodiments of the present invention, reference quality of multimedia is obtained by using reference video quality and reference audio quality of the multimedia,
25 multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs is acquired, and quality of the multimedia is determined according to the reference quality of the multimedia and the multimedia distortion quality. Therefore, accuracy of a multimedia quality monitoring result is improved.

BRIEF DESCRIPTION OF DRAWINGS

[0036] To describe the technical solutions in the embodiments of the present invention or in the prior art more clearly, the following briefly introduces the accompanying drawings required for describing the embodiments or the prior art. Apparently, the accompanying drawings in the following description show some embodiments of the present invention, and a person of ordinary skill in the art may still derive other drawings from these accompanying drawings without creative efforts.

[0037] FIG. 1 is a schematic structural diagram of an embodiment of a multimedia quality monitoring method according to the present invention;

[0038] FIG. 2 is a schematic structural diagram of yet another embodiment of a multimedia quality monitoring method according to the present invention;

[0039] FIG. 3 is a schematic structural diagram of an embodiment of a multimedia quality monitoring apparatus according to the present invention;

[0040] FIG. 4 is a schematic structural diagram of an embodiment of a terminal according to the present invention;

[0041] FIG. 5 is a schematic structural diagram of yet another embodiment of a terminal according to the present invention;

[0042] FIG. 6 is a schematic structural diagram of an embodiment of a network device according to the present invention; and

[0043] FIG. 7 is a schematic structural diagram of yet another embodiment of a network device according to the present invention.

DESCRIPTION OF EMBODIMENTS

[0044] To make the objectives, technical solutions, and advantages of the embodiments of the present invention clearer, the following clearly and completely describes the technical solutions in the embodiments of the present invention with reference to the accompanying drawings in the embodiments of the present invention. Apparently, the described embodiments are a part rather than all of the embodiments of the present invention. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of

the present invention without creative efforts shall fall within the protection scope of the present invention.

[0045] Technologies described in this specification may be applied to various communications systems, for example, current 2G and 3G communications systems and
5 next-generation communications systems, for example, a Global System for Mobile Communications (GSM, Global System for Mobile communications), a Code Division Multiple Access (CDMA, Code Division Multiple Access) system, a Time Division Multiple Access (TDMA, Time Division Multiple Access) system, a Wideband Code Division Multiple Access (WCDMA, Wideband Code Division Multiple Access Wireless) system, a Frequency
10 Division Multiple Access (FDMA, Frequency Division Multiple Addressing) system, an Orthogonal Frequency-Division Multiple Access (OFDMA, Orthogonal Frequency-Division Multiple Access) system, a single-carrier FDMA (SC-FDMA) system, a General Packet Radio Service (GPRS, General Packet Radio Service) system, a Long Term Evolution (LTE, Long Term Evolution) system, and other similar communications systems.

[0046] A terminal involved in this application, that is, a user device, may be a wireless terminal or a wired terminal. The wireless terminal may refer to a device that provides a user with voice and/or data connectivity, a handheld device with a radio connection function, or another processing device connected to a radio modem. The wireless terminal may communicate with one or more core networks through a radio access network (such as RAN,
20 Radio Access Network). The wireless terminal may be a mobile terminal, such as a mobile phone (also referred to as a "cellular" phone) and a computer with a mobile terminal, for example, may be a portable, pocket-sized, handheld, computer built-in, or vehicle-mounted mobile apparatus, which exchanges voice and/or data with the radio access network. For example, it may be a device such as a personal communication service (PCS, Personal
25 Communication Service) phone, a cordless telephone set, a Session Initiation Protocol (SIP) phone, a wireless local loop (WLL, Wireless Local Loop) station, or a personal digital assistant (PDA, Personal Digital Assistant). The wireless terminal may also be called a system, a subscriber unit (Subscriber Unit), a subscriber station (Subscriber Station), a mobile station (Mobile Station), a mobile terminal (Mobile), a remote station (Remote Station), an access
30 point (Access Point), a remote terminal (Remote Terminal), an access terminal (Access

Terminal), a user terminal (User Terminal), a user agent (User Agent), a user device (User Device), or a user equipment (User Equipment).

[0047] Network devices involved in the application may be various network node devices, such as base stations, base station controllers, access points (Access Point, AP) on various networks, or network elements such as controllers or authenticators behind the access points and the base stations mentioned above.

[0048] In addition, the terms "system" and "network" may be used interchangeably in this specification. The term "and/or" in this specification describes only an association relationship for describing associated objects and represents that three relationships may exist. For example, A and/or B may represent the following three cases: Only A exists, both A and B exist, and only B exists. In addition, the character "/" in this specification generally represents an "or" relationship between the associated objects.

[0049] FIG. 1 is a schematic structural diagram of an embodiment of a multimedia quality monitoring method according to the present invention. As shown in FIG. 1, the method includes:

[0050] S101: Determine reference quality of multimedia according to reference video quality and reference audio quality of the multimedia.

[0051] S102: Acquire multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs.

[0052] S103: Determine quality of the multimedia according to the reference quality of the multimedia and the multimedia distortion quality.

[0053] Multimedia involved in this embodiment of the present invention refers to various multimedia files including video and audio, for example, multimedia data that is received when a terminal performs a service process, such as video on demand, web television, and video telephone.

[0054] The multimedia needs to be encoded before being transmitted, and video data and audio data in the multimedia generally need to be encoded separately. After the encoding, two transport streams, namely a video stream and an audio stream, may be transmitted; or interleaved packetization may be performed on the encoded video data and the encoded audio data, that is, one packet includes not only the video data but also the audio data, and the video

data and the audio data are transmitted in one transport stream.

[0055] Because encoding of the video data and the audio data may result in distortion to a certain extent, the reference video quality of the multimedia involved in this embodiment of the present invention may be video quality that is after video encoding is performed on the video data in the multimedia, and similarly, reference audio quality of the multimedia may be audio quality that is after audio encoding is performed on the audio data in the multimedia.

[0056] In this embodiment of the present invention, various existing methods may be used to determine the reference quality of the multimedia according to the reference video quality and the reference audio quality of the multimedia.

[0057] Optionally, the reference quality of the multimedia may be determined according to $Q_{av}' = a_1 \cdot Q_{v_coding} + a_2 \cdot Q_{a_coding} + a_3 \cdot Q_{v_coding} \cdot Q_{a_coding} + a_4$, where Q_{av}' is the reference quality of the multimedia, Q_{v_coding} is the reference video quality, Q_{a_coding} is the reference audio quality, and a_1 , a_2 , a_3 , and a_4 are constants.

[0058] Multimedia distortion quality may include: multimedia distortion quality due to packet loss and/or multimedia distortion quality due to rebuffering. That is, multimedia distortion may be caused by video packet loss and/or audio packet loss, and may also be caused by a rebuffering, during a transmission process, of multimedia. It can be understood that multimedia distortion may also be caused by other reasons, for example, quality of service of a transmission channel, which may include bandwidth, time delay, jitter and the like, and a status of adaptation between parameters for an audio/video encoder and a transmission channel, where the parameters may include an encoding manner, video resolution, a video frame rate and the like.

[0059] Therefore, video quality due to packet loss may be determined according to a packet loss status of video data, or video quality due to packet loss that is after a packet in a video of the multimedia is lost may also be determined according to the reference video quality and a video packet loss rate, and the video quality due to packet loss may also be determined according to various existing methods.

[0060] Similarly, audio quality due to packet loss may be determined according to a packet loss status of audio data, or audio quality due to packet loss that is after a packet in an

audio of the multimedia is lost may also be determined according to the reference audio quality and an audio packet loss rate, and the audio quality due to packet loss may also be determined according to various existing methods.

[0061] Further, multimedia distortion quality due to packet loss may be acquired according to the video quality due to packet loss and/or the audio quality due to packet loss.

[0062] Optionally, video distortion quality due to packet loss may be determined according to the video quality due to packet loss and the reference video quality, and audio packet loss distortion quality may be determined according to the audio quality due to packet loss and the reference audio quality. For example, the video distortion quality due to packet loss may be a difference between the reference video quality and the video quality due to packet loss, and similarly, the audio packet loss distortion quality may be a difference between the reference audio quality and the audio quality due to packet loss.

[0063] Further, a video packet loss distortion factor may be further determined according to the video distortion quality due to packet loss and the reference video quality, and an audio packet loss distortion factor may be determined according to the audio packet loss distortion quality and the reference audio quality. For example, the video packet loss distortion factor may be a ratio of the video distortion quality due to packet loss to the reference video quality, and similarly, the audio packet loss distortion factor may be a ratio of the audio packet loss distortion quality to the reference audio quality.

[0064] Further, a multimedia packet loss distortion factor may be determined according to the video packet loss distortion factor and the audio packet loss distortion factor. For example, the multimedia packet loss distortion factor may have a linear or non-linear relationship with the video packet loss distortion factor or the audio packet loss distortion factor, or may be a combination of linearity and non-linearity.

[0065] Finally, the multimedia distortion quality due to packet loss may be determined according to the multimedia packet loss distortion factor and the reference quality of the multimedia.

[0066] As another feasible implementation manner, a rebuffering parameter, such as the number of rebufferings, rebuffering duration, and an impact factor between multiple rebufferings, of multimedia during a transmission process may be acquired, and further, the

multimedia distortion quality due to rebuffering is acquired according to the rebuffering parameter. The rebuffering parameter or a combination of the rebuffering parameters may have a linear or non-linear relationship with the multimedia distortion quality due to rebuffering, or may be in a linearity or non-linearity combined relationship.

5 **[0067]** After the multimedia distortion quality is determined, the quality of the multimedia may be determined according to the reference quality of the multimedia and the multimedia distortion quality. The multimedia distortion quality may include a multimedia distortion vector due to packet loss, or include the multimedia distortion quality due to rebuffering, or include the multimedia distortion vector due to packet loss and the multimedia distortion
10 quality due to rebuffering.

[0068] Specifically, during a transmission process of multimedia, if no rebuffering occurs and only a case of video packet loss and/or audio packet loss occurs, the multimedia distortion quality may include only the multimedia distortion quality due to packet loss; during a transmission process of multimedia, if a rebuffering occurs but a case of video packet loss
15 and/or audio packet loss does not occur, the multimedia distortion quality may include only the multimedia distortion quality due to rebuffering; and during a transmission process of multimedia, if not only a rebuffering occurs, but also a case of video packet loss and/or audio packet loss occurs, the multimedia distortion quality not only includes the multimedia distortion quality due to rebuffering, but also includes the multimedia distortion quality due to
20 packet loss.

[0069] According to the multimedia quality monitoring method provided in this embodiment, reference quality of multimedia is obtained by using reference video quality and reference audio quality of the multimedia, multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs is acquired, and quality of
25 the multimedia is determined according to the reference quality of the multimedia and the multimedia distortion quality. Therefore, accuracy of a multimedia quality monitoring result is improved.

[0070] FIG. 2 is a schematic structural diagram of another embodiment of a multimedia quality monitoring method according to the present invention. As shown in FIG. 2, the method
30 includes:

[0071] S201: Acquire reference video quality V_MOSC and reference audio quality A_MOSC of multimedia.

[0072] S202: Determine, according to the reference video quality and a video packet loss rate, video quality due to packet loss that is after a packet in a video of the multimedia is lost, and determine, according to the reference audio quality and an audio packet loss rate, audio quality due to packet loss that is after a packet in an audio of the multimedia is lost.

[0073] S203: Determine video distortion quality due to packet loss according to the video quality due to packet loss and the reference video quality, and determine audio packet loss distortion quality according to the audio quality due to packet loss and the reference audio quality.

[0074] Optionally, the video distortion quality due to packet loss V_DP may be determined according to $V_DP = V_MOSC - Video_MOS$, where V_MOSC is the reference video quality, and $Video_MOS$ is the video quality due to packet loss. It should be noted that, if a case of video packet loss does not occur, $Video_MOS$ is equal to the reference video quality.

[0075] Similarly, the audio packet loss distortion quality A_DP may be determined according to $A_DP = A_MOSC - Audio_MOS$, where A_MOSC is the reference audio quality, and $Audio_MOS$ is the audio quality due to packet loss. It should be noted that, if a case audio packet loss does not occur, $Audio_MOS$ is equal to the reference audio quality.

[0076] Video quality $Video_MO$ that is after packet loss distortion or video distortion quality due to packet loss V_DP , and audio quality $Audio_MOS$ of multimedia that is after packet loss or audio packet loss distortion quality A_DP are acquired.

[0077] The foregoing video quality of the multimedia that is after packet loss may be reference video quality of the multimedia or video quality due to packet loss of the multimedia, that is, if packet loss does not occur in a video of the multimedia, the quality is reference quality, and if packet loss occurs, the quality is packet loss quality.

[0078] The foregoing audio quality of the multimedia that is after packet loss may be reference audio quality of the multimedia or audio quality due to packet loss of the

multimedia, that is, if packet loss does not occur in audio of the multimedia, the quality is reference quality, and if packet loss occurs, the quality is packet loss quality.

[0079] The video distortion quality due to packet loss may also be equal to the reference video quality minus the video quality due to packet loss.

5 [0080] Similarly, the audio packet loss distortion quality may be equal to the reference audio quality minus the audio quality due to packet loss.

[0081] S204: Determine reference quality (AV_MOSC) of the multimedia according to the reference video quality and the reference audio quality of the multimedia. The reference quality of the multimedia may be determined by using various existing methods.

10 [0082] Optionally, the reference quality of the multimedia may be determined according to $AV_MOSC = av1 \cdot V_MOSC + av2 \cdot A_MOSC + av3 \cdot V_MOSC \cdot A_MOSC + av4$.

[0083] AV_MOSC is the reference quality of the multimedia, V_MOSC is the reference video quality, A_MOSC is the reference audio quality, and av1, av2, av3, and av4 are constants.

15 [0084] S205: Determine a video packet loss distortion factor (AV_DFV) of the multimedia according to the video distortion quality due to packet loss (V_DP) and the reference video quality (V_MOSC) of the multimedia, and determine an audio packet loss distortion factor (AV_DFA) of the multimedia according to the audio packet loss distortion quality (A_DP) and the reference audio quality (A_MOSC) of the multimedia.

20 [0085] Optionally, the video packet loss distortion factor (AV_DFV) of the multimedia may be determined according to $AV_DFV = \frac{V_DP}{V_MOSC}$ or

$AV_DFV = \frac{V_MOSC - Video_MOS}{V_MOSC}$, where V_MOSC is the reference video quality, and

V_DP is the video distortion quality of the multimedia.

[0086] Similarly, the audio packet loss distortion factor (AV_DFA) of the multimedia may

25 be determined according to $AV_DFA = \frac{A_DP}{A_MOSC}$ or $AV_DFA = \frac{A_MOSC - Audio_MOS}{A_MOSC}$,

where A_MOSC is the reference audio quality, and A_DP is the audio distortion quality of the

multimedia.

[0087] S206: Determine a multimedia packet loss distortion factor (AV_DF) according to the video packet loss distortion factor (AV_DFV) of the multimedia and the audio packet loss distortion factor (AV_DFA) of the multimedia.

5 [0088] The multimedia packet loss distortion factor may increase when a value of the video packet loss distortion factor of the multimedia and/or a value of the audio packet loss distortion factor of the multimedia increases, the multimedia packet loss distortion factor may have a linear or non-linear relationship with the video packet loss distortion factor of the multimedia and/or the audio packet loss distortion factor of the multimedia, or may have a
10 relationship, combining linearity and non-linearity, with the video packet loss distortion factor of the multimedia and/or the audio packet loss distortion factor of the multimedia.

[0089] Optionally, the multimedia packet loss distortion factor (AV_DF) may be determined according to the following method:

$$AV_DF = \frac{av5 \cdot AV_DFV + av6 \cdot AV_DFA}{1 + av5 \cdot AV_DFV + av6 \cdot AV_DFA} \quad \text{or} \quad AV_DF = av5 + av6 \cdot AV_DFV + av7 \cdot AV_DFA$$

[0090] AV_DFA is the audio packet loss distortion factor of the multimedia, AV_DFV is
15 the video packet loss distortion factor of the multimedia, and av5, av6, and av7 are constants.

[0091] S207: Determine, according to the multimedia packet loss distortion factor and the reference quality of the multimedia, multimedia distortion quality due to packet loss that is after video packet loss distortion and/or audio packet loss distortion of the multimedia.

[0092] Optionally, the multimedia distortion quality due to packet loss AV_DP that is after
20 video packet loss distortion and/or audio packet loss distortion of the multimedia may be determined according to $AV_DP = (AV_MOSC - MOS_MIN) \cdot AV_DF$, where AV_MOSC is the reference quality of the multimedia, and MOS_MIN is lowest quality of the multimedia, for example, MOS_MIN may be set to 1, and AV_DF is the multimedia packet loss distortion factor.

25 [0093] S208: Determine multimedia quality due to packet loss according to the reference quality of the multimedia and the multimedia distortion quality due to packet loss that is after video packet loss distortion and/or audio packet loss distortion.

[0094] Optionally, the multimedia quality due to packet loss AV_MOSP may be determined according to $AV_MOSP = AV_MOSC - AV_DP$, where AV_MOSC is the reference quality of the multimedia, and AV_DP is the multimedia distortion quality due to packet loss that is after video packet loss distortion and/or audio packet loss distortion.

5 [0095] S209: Acquire multimedia distortion quality due to rebuffering according to a rebuffering parameter, during a transmission process, of the multimedia.

[0096] The rebuffering parameter includes one or any combination of the following: the number of rebufferings (NR), rebuffering duration (ARL), an impact factor between multiple rebufferings (MRF), and multimedia initial quality. Multimedia distortion quality due to rebuffering is calculated. The rebuffering duration may be average duration of multiple rebufferings, or may be total duration of multiple averages.

[0097] Optionally, the multimedia distortion quality due to rebuffering AV_DR may be determined according to

$$AV_DR = (Audiovisual_Quality - MOS_MIN) \cdot \frac{\left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}}{1 + \left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}}, \text{ where}$$

15 $av7 - av12$ are constants, and $Audiovisual_Quality$ is multimedia initial quality.

Specifically, the multimedia initial quality may be the reference quality of the multimedia or the multimedia quality due to packet loss, that is, if packet loss does not occur in the multimedia, the multimedia initial quality may be the reference quality, and if packet loss occurs, the multimedia initial quality may be the multimedia quality due to packet loss.

20 [0098] S210: Determine quality of the multimedia according to the reference quality of the multimedia or the multimedia quality due to packet loss, and the distortion quality due to rebuffering.

[0099] Optionally, multimedia rebuffering quality AV_MOSR may be determined according to $AV_MOSR = Audiovisual_Quality - AV_DR$. $Audiovisual_Quality$ is the

25 reference quality of the multimedia or the multimedia quality due to packet loss, AV_DR is

the distortion quality due to rebuffering. The multimedia initial quality may be the reference quality of the multimedia or the multimedia quality due to packet loss, that is, if packet loss does not occur in the multimedia, the multimedia initial quality may be the reference quality, and if packet loss occurs, the multimedia initial quality may be the multimedia quality due to packet loss.

[0100] According to the multimedia quality monitoring method provided in this embodiment, reference quality of multimedia is obtained by using reference video quality and reference audio quality of the multimedia, multimedia distortion quality due to packet loss is determined by using video quality of the multimedia that is after packet loss and audio quality of the multimedia that is after packet loss, multimedia distortion quality due to rebuffering is obtained by using a rebuffering parameter, and finally, ultimate quality of the multimedia is determined according to the reference quality of the multimedia, and/or the multimedia distortion quality due to packet loss and/or the multimedia distortion quality due to rebuffering. Therefore, accuracy of a multimedia quality monitoring result is improved.

[0101] FIG. 3 is a schematic structural diagram of an embodiment of a multimedia quality monitoring apparatus according to the present invention. As shown in FIG. 3, the multimedia quality monitoring apparatus includes: a first determining module 11, a second determining module 12, and a third determining module 13.

[0102] The first determining module 11 is configured to determine reference quality of multimedia according to reference video quality and reference audio quality of the multimedia.

[0103] The second determining module 12 is configured to acquire multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs.

[0104] The third determining module 13 is configured to determine quality of the multimedia according to the reference quality of the multimedia and the multimedia distortion quality.

[0105] Optionally, the first determining module 11 may be specifically configured to:

determine the reference quality of the multimedia according to

$AV_MOSC = av1 \cdot V_MOSC + av2 \cdot A_MOSC + av3 \cdot V_MOSC \cdot A_MOSC + av4$, where

AV_MOSC is the reference quality of the multimedia, V_MOSC is the reference video quality, A_MOSC is the reference audio quality, and *av1*, *av2*, *av3*, and *av4* are constants.

[0106] Optionally, the multimedia distortion quality may include: multimedia distortion quality due to packet loss and/or multimedia distortion quality due to rebuffering; and the second determining module 12 may be specifically configured to: determine, according to the reference video quality and a video packet loss rate, video quality due to packet loss that is after a packet in a video of the multimedia is lost, and determine, according to the reference audio quality and an audio packet loss rate, audio quality due to packet loss that is after a packet in an audio of the multimedia is lost; acquire the multimedia distortion quality due to packet loss according to the video quality due to packet loss and/or the audio quality due to packet loss, and/or

acquire the multimedia distortion quality due to rebuffering according to a rebuffering parameter, during a transmission process, of the multimedia.

[0107] Optionally, the second determining module 12 may be specifically configured to: determine video distortion quality due to packet loss according to the video quality due to packet loss and the reference video quality, and determine audio packet loss distortion quality according to the audio quality due to packet loss and the reference audio quality; determine a video packet loss distortion factor according to the video distortion quality due to packet loss and the reference video quality, and determine an audio packet loss distortion factor according to the audio packet loss distortion quality and the reference audio quality; determine a multimedia packet loss distortion factor according to the video packet loss distortion factor and the audio packet loss distortion factor; and determine the multimedia distortion quality due to packet loss according to the multimedia packet loss distortion factor and the reference quality of the multimedia.

[0108] Optionally, the second determining module 12 may be specifically configured to: determine the video distortion quality due to packet loss V_DP according to $V_DP = V_MOSC - Video_MOS$, where V_MOSC is the reference video quality, and $Video_MOS$ is the video quality due to packet loss; and

determine the audio packet loss distortion quality A_DP according to

$A_DP = A_MOSC - Audio_MOS$, where A_MOSC is the reference audio quality, and $Audio_MOS$ is the audio quality due to packet loss.

[0109] Optionally, the second determining module 12 may be specifically configured to:

determine the video packet loss distortion factor AV_DFV according to

$$5 \quad AV_DFV = \frac{V_DP}{V_MOSC} \quad \text{or} \quad AV_DFV = \frac{V_MOSC - Video_MOS}{V_MOSC}, \quad \text{where } V_MOSC \text{ is the}$$

reference video quality, and V_DP is the video distortion quality due to packet loss; and/or, determine the audio packet loss distortion factor AV_DFA according to

$$AV_DFA = \frac{A_DP}{A_MOSC} \quad \text{or} \quad AV_DFA = \frac{A_MOSC - Audio_MOS}{A_MOSC}, \quad \text{where } A_MOSC \text{ is the}$$

reference audio quality, and A_DP is the audio packet loss distortion quality.

10 [0110] Optionally, the second determining module 12 may be further specifically configured to: determine the multimedia packet loss distortion factor AV_DF according to

$$\frac{av5 \cdot AV_DFV + av6 \cdot AV_DFA}{1 + av5 \cdot AV_DFV + av6 \cdot AV_DFA} \quad \text{or} \quad AV_DF = av5 + av6 \cdot AV_DFV + av7 \cdot AV_DFA, \quad ,$$

where AV_DFA is the audio packet loss distortion factor, AV_DFV is the video packet loss distortion factor, and $av5$, $av6$ and $av7$ are constants.

15 [0111] Optionally, the second determining module 12 may be specifically configured to: determine the multimedia distortion quality due to packet loss AV_DP according to

$AV_DP = (AV_MOSC - MOS_MIN) \cdot AV_DF$, where AV_MOSC is the reference quality of the multimedia, MOS_MIN is lowest quality of the multimedia, and AV_DF is the multimedia packet loss distortion factor.

20 [0112] Optionally, the rebuffering parameter may include one or any combination of the following: the number of rebufferings, rebuffering duration, an impact factor between multiple rebufferings, and multimedia initial quality.

[0113] Optionally, the second determining module 12 may be specifically configured to acquire the multimedia distortion quality due to rebuffering according to

$$AV_DR = (Audiovisual_Quality - MOS_MIN) \cdot \frac{\left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}}{1 + \left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}}$$

, where *Audiovisual_Quality* is the multimedia initial quality, *NR* is the number of rebufferings, *ARL* is the rebuffering duration, *MRF* is the impact factor between multiple rebufferings, and *av7*–*av12* are constants.

5 [0114] Optionally, the third determining module 13 may be specifically configured to: determine multimedia quality due to packet loss according to the reference quality of the multimedia and the multimedia distortion quality due to packet loss; and determine quality of the multimedia according to the reference quality of the multimedia or the multimedia quality due to packet loss, and the distortion quality due to rebuffering.

10 [0115] Optionally, the third determining module 13 may be specifically configured to: determine the multimedia quality due to packet loss *AV_MOSP* according to $AV_MOSP = AV_MOSC - AV_DP$, where *AV_MOSC* is the reference quality of the multimedia, and *AV_DP* is the multimedia distortion quality due to packet loss.

[0116] Optionally, the third determining module 13 may be specifically configured to:
15 determine the quality *AV_MOSR* of the multimedia according to $AV_MOSR = Audiovisual_Quality - AV_DR$, where *Audiovisual_Quality* is the reference quality of the multimedia or the multimedia quality due to packet loss, and *AV_DR* is the distortion quality due to rebuffering.

[0117] The multimedia quality monitoring apparatus provided in the embodiment of the
20 present invention corresponds to the multimedia quality monitoring method provided in the embodiment of the present invention, and is a device for executing the multimedia quality monitoring method. For a process of executing, by the apparatus, the multimedia quality monitoring method, refer to method embodiments, and no details are repeatedly described herein.

25 [0118] According to the multimedia quality monitoring apparatus provided in this embodiment of the present invention, reference quality of multimedia is obtained by using

reference video quality and reference audio quality of the multimedia, multimedia distortion quality due to packet loss is determined by using video quality of the multimedia that is after packet loss and audio quality of the multimedia that is after packet loss, multimedia distortion quality due to rebuffering is obtained by using a rebuffering parameter, and finally, ultimate
5 quality of the multimedia is determined according to the reference quality of the multimedia, and/or the multimedia distortion quality due to packet loss and/or the multimedia distortion quality due to rebuffering. Therefore, accuracy of a multimedia quality monitoring result is improved.

[0119] FIG. 4 is a schematic structural diagram of an embodiment of a terminal according
10 to the present invention. As shown in FIG. 4, the terminal includes: a receiving module 21 and a multimedia quality monitoring apparatus 22.

[0120] The receiving module 21 is configured to receive multimedia.

[0121] For a structure of the multimedia quality monitoring apparatus 22 and functions of modules in the multimedia quality monitoring apparatus 22, refer to related description in the
15 embodiment shown in FIG. 3, and no details are repeatedly described herein.

[0122] FIG. 5 is a schematic structural diagram of yet another embodiment of a terminal according to the present invention. As shown in FIG. 5, the terminal includes: a receiver 31 and a processor 32.

[0123] The receiver 31 is configured to receive multimedia.

[0124] The processor 32 may execute the multimedia quality monitoring methods
20 provided in the embodiments, shown in FIG. 1 and FIG. 2, of the present invention. For specific processes of executing, by the processor 32, the multimedia quality monitoring methods, refer to related description in the embodiments shown in FIG. 1 and FIG. 2, and no details are repeatedly described herein.

[0125] According to the terminal provided in this embodiment of the present invention,
25 reference quality of multimedia is obtained by using reference video quality and reference audio quality of the multimedia, multimedia quality that is after multimedia distortion is determined by using video quality that is after video distortion of the multimedia and audio quality that is after audio distortion of the multimedia, and finally, quality of the multimedia is
30 determined according to the reference quality of the multimedia and the multimedia quality

that is after the distortion. Therefore, accuracy of a multimedia quality monitoring result is improved.

[0126] FIG. 6 is a schematic structural diagram of an embodiment of a network device according to the present invention. As shown in FIG. 6, the network device includes: a receiving module 41 and a multimedia quality monitoring apparatus 42.

[0127] The receiving module 41 is configured to receive multimedia.

[0128] For a structure of the multimedia quality monitoring apparatus 42 and functions of modules within the multimedia quality monitoring apparatus 42, refer to related description in the embodiment shown in FIG. 3, and no details are repeatedly described herein.

[0129] FIG. 7 is a schematic structural diagram of yet another embodiment of a network device according to the present invention. As shown in FIG. 7, the network device includes: a receiver 51 and a processor 52.

[0130] The receiver 51 is configured to receive multimedia.

[0131] The processor 52 may execute the multimedia quality monitoring methods provided in the embodiments, shown in FIG. 1 and FIG. 2, of the present invention. For specific processes of executing, by the processor 52, the multimedia quality monitoring methods, refer to related description in the embodiments shown in FIG. 1 and FIG. 2, and no details are repeatedly described herein.

[0132] According to the network device provided in this embodiment of the present invention, reference quality of multimedia is obtained by using reference video quality and reference audio quality of the multimedia, multimedia distortion quality due to packet loss is determined by using video quality of the multimedia that is after packet loss and audio quality of the multimedia that is after packet loss, multimedia distortion quality due to rebuffering is obtained by using a rebuffering parameter, and finally, ultimate quality of the multimedia is determined according to the reference quality of the multimedia, and/or the multimedia distortion quality due to packet loss and/or the multimedia distortion quality due to rebuffering. Therefore, accuracy of a multimedia quality monitoring result is improved.

[0133] It may be clearly understood by a person skilled in the art that, for the purpose of convenient and brief description, division of the foregoing functional modules is taken as an example for illustration. In an actual application, the foregoing functions may be allocated to

different functional modules and implemented according to needs, that is, an inner structure of an apparatus is divided into different functional modules to implement all or part of the functions described above. For a specific working process of the foregoing system, apparatus, and unit, refer to a corresponding process in the foregoing method embodiments, and details are not described herein again.

[0134] In the several embodiments provided in the present application, it should be understood that the disclosed system, apparatus, and method may be implemented in other manners. For example, the described apparatus embodiment is merely exemplary. For example, the module or unit division is merely logical function division and may be other division in actual implementation. For example, a plurality of units or components may be combined or integrated into another system, or some features may be ignored or not performed. In addition, the displayed or discussed mutual couplings or direct couplings or communication connections may be implemented through some interfaces. The indirect couplings or communication connections between the apparatuses or units may be implemented in electronic, mechanical, or other forms.

[0135] The units described as separate parts may or may not be physically separate, and parts displayed as units may or may not be physical units, may be located in one position, or may be distributed on a plurality of network units. A part or all of the units may be selected according to actual needs to achieve the objectives of the solutions of the embodiments.

[0136] In addition, functional units in the embodiments of the present application may be integrated into one processing unit, or each of the units may exist alone physically, or two or more units are integrated into one unit. The integrated unit may be implemented in a form of hardware, or may be implemented in a form of a software functional unit.

[0137] When the integrated unit is implemented in the form of a software functional unit and sold or used as an independent product, the integrated unit may be stored in a computer-readable storage medium. Based on such an understanding, the technical solutions of the present application essentially, or the part contributing to the prior art, or all or a part of the technical solutions may be implemented in the form of a software product. The software product is stored in a storage medium and includes several instructions for instructing a computer device (which may be a personal computer, a server, or a network device) or a

processor to perform all or a part of the steps of the methods described in the embodiments of the present application. The foregoing storage medium includes: any medium that may store program code, such as a USB flash drive, a removable hard disk, a read-only memory (ROM, Read-Only Memory), a random access memory (RAM, Random Access Memory), a magnetic disk, or an optical disc.

[0138] The foregoing embodiments are merely intended for describing the technical solutions of the present application, but not for limiting the present application. Although the present application is described in detail with reference to the foregoing embodiments, persons of ordinary skill in the art should understand that they may still make modifications to the technical solutions described in the foregoing embodiments or make equivalent replacements to some technical features thereof, without departing from the spirit and scope of the technical solutions of the embodiments of the present application.

CLAIMS

What is claimed is:

1. A multimedia quality monitoring method, comprising:

5 determining reference quality of multimedia according to reference video quality and reference audio quality of the multimedia;

acquiring multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs; and

determining quality of the multimedia according to the reference quality of the multimedia and the multimedia distortion quality.

10 2. The method according to claim 1, wherein the determining reference quality of multimedia according to reference video quality and reference audio quality of the multimedia comprises:

determining the reference quality of the multimedia according to $AV_MOSC = av1 \cdot V_MOSC + av2 \cdot A_MOSC + av3 \cdot V_MOSC \cdot A_MOSC + av4$, wherein

15 AV_MOSC is the reference quality of the multimedia, V_MOSC is the reference video quality, A_MOSC is the reference audio quality, and $av1$, $av2$, $av3$, and $av4$ are constants.

3. The method according to claim 1 or 2, wherein the multimedia distortion quality comprises: multimedia distortion quality due to packet loss and/or multimedia distortion quality due to rebuffering; and the acquiring multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs comprises:

20 determining, according to the reference video quality and a video packet loss rate, video quality due to packet loss that is after a packet in a video of the multimedia is lost, and/or determining, according to the reference audio quality and an audio packet loss rate, audio quality due to packet loss that is after a packet in an audio of the multimedia is lost; acquiring the multimedia distortion quality due to packet loss according to the video quality due to packet loss and/or the audio quality due to packet loss; and/or

acquiring the multimedia distortion quality due to rebuffering according to a rebuffering parameter, during a transmission process, of the multimedia.

4. The method according to claim 3, wherein the acquiring the multimedia distortion quality due to packet loss according to the video quality due to packet loss and/or the audio quality due to packet loss comprises:

determining video distortion quality due to packet loss according to the video quality due to packet loss and the reference video quality, and determining audio packet loss distortion quality according to the audio quality due to packet loss and the reference audio quality;

determining a video packet loss distortion factor according to the video distortion quality due to packet loss and the reference video quality, and determining an audio packet loss distortion factor according to the audio packet loss distortion quality and the reference audio quality;

determining a multimedia packet loss distortion factor according to the video packet loss distortion factor and the audio packet loss distortion factor; and

determining the multimedia distortion quality due to packet loss according to the multimedia packet loss distortion factor and the reference quality of the multimedia.

5. The method according to claim 4, wherein the determining video distortion quality due to packet loss according to the video quality due to packet loss and the reference video quality, and determining audio packet loss distortion quality according to the audio quality due to packet loss and the reference audio quality comprises:

determining the video distortion quality due to packet loss V_DP according to $V_DP = V_MOSC - Video_MOS$, wherein V_MOSC is the reference video quality, and $Video_MOS$ is the video quality due to packet loss; and

determining the audio packet loss distortion quality A_DP according to $A_DP = A_MOSC - Audio_MOS$, wherein A_MOSC is the reference audio quality, and $Audio_MOS$ is the audio quality due to packet loss.

6. The method according to claim 4 or 5, wherein the determining a video packet loss distortion factor according to the video distortion quality due to packet loss and the reference video quality, and determining an audio packet loss distortion factor according to the audio packet loss distortion quality and the reference audio quality comprises:

determining the video packet loss distortion factor AV_DFV according to
 $AV_DFV = \frac{V_DP}{V_MOSC}$ or $AV_DFV = \frac{V_MOSC - Video_MOS}{V_MOSC}$, wherein V_MOSC is the

reference video quality, and V_DP is the video distortion quality due to packet loss; and/or

determining the audio packet loss distortion factor AV_DFA according to
5 $AV_DFA = \frac{A_DP}{A_MOSC}$ or $AV_DFA = \frac{A_MOSC - Audio_MOS}{A_MOSC}$, wherein A_MOSC is the

reference audio quality, and A_DP is the audio packet loss distortion quality.

7. The method according to any one of claims 4 to 6, wherein the determining a multimedia packet loss distortion factor according to the video packet loss distortion factor and the audio packet loss distortion factor comprises:

10 determining the multimedia packet loss distortion factor AV_DF according to

$$\frac{av5 \cdot AV_DFV + av6 \cdot AV_DFA}{1 + av5 \cdot AV_DFV + av6 \cdot AV_DFA}$$
 or $AV_DF = av5 + av6 \cdot AV_DFV + av7 \cdot AV_DFA$,

wherein AV_DFA is the audio packet loss distortion factor, AV_DFV is the video packet loss distortion factor, and $av5$, $av6$ and $av7$ are constants.

8. The method according to any one of claims 4 to 7, wherein the determining the
15 multimedia distortion quality due to packet loss according to the multimedia packet loss distortion factor and the reference quality of the multimedia comprises:

determining the multimedia distortion quality due to packet loss AV_DP according to
 $AV_DP = (AV_MOSC - MOS_MIN) \cdot AV_DF$, wherein AV_MOSC is the reference quality of the multimedia, MOS_MIN is lowest quality of the multimedia, and AV_DF is the multimedia
20 packet loss distortion factor.

9. The method according to any one of claims 3 to 8, wherein the rebuffering parameter comprises one or any combination of the following: the number of rebufferings, rebuffering duration, an impact factor between multiple rebufferings, and multimedia initial quality.

10. The method according to claim 9, wherein the acquiring the multimedia distortion
25 quality due to rebuffering according to a rebuffering parameter, during a transmission process, of the multimedia comprises: acquiring the multimedia distortion quality due to rebuffering

AV_DR according to

$$AV_DR = (Audiovisual_Quality - MOS_MIN) \cdot \frac{\left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}}{1 + \left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}},$$

wherein $Audiovisual_Quality$ is the multimedia initial quality, NR is the number of rebufferings, ARL is the rebuffering duration, MRF is the impact factor between multiple rebufferings, and $av7-av12$ are constants.

11. The method according to claim 10, wherein the determining quality of the multimedia according to the reference quality of the multimedia and the multimedia distortion quality comprises:

determining the multimedia quality due to packet loss according to the reference quality of the multimedia and the multimedia distortion quality due to packet loss; and

determining the quality of the multimedia according to the reference quality of the multimedia or the multimedia quality due to packet loss, and the distortion quality due to rebuffering.

12. The method according to claim 11, wherein the determining the multimedia quality due to packet loss according to the reference quality of the multimedia and the multimedia distortion quality due to packet loss comprises:

determining the multimedia quality due to packet loss AV_MOSP according to $AV_MOSP = AV_MOSC - AV_DP$, wherein AV_MOSC is the reference quality of the multimedia, and AV_DP is the multimedia distortion quality due to packet loss.

13. The method according to claim 11 or 12, wherein the determining the quality of the multimedia according to the reference quality of the multimedia or the multimedia quality due to packet loss, and the distortion quality due to rebuffering comprises:

determining the quality AV_MOSR of the multimedia according to $AV_MOSR = Audiovisual_Quality - AV_DR$, wherein $Audiovisual_Quality$ is the reference quality of the multimedia or the multimedia quality due to packet loss, and AV_DR is the

distortion quality due to rebuffering.

14. A multimedia quality monitoring apparatus comprising:

a first determining module, configured to determine reference quality of multimedia according to reference video quality and reference audio quality of the multimedia;

5 a second determining module, configured to acquire multimedia distortion quality that is after video distortion and/or audio distortion of the multimedia occur/occurs; and

a third determining module, configured to determine quality of the multimedia according to the reference quality of the multimedia and the multimedia distortion quality.

10 15. The apparatus according to claim 14, wherein the first determining module is specifically configured to:

determine the reference quality of the multimedia according to $AV_MOSC = av1 \cdot V_MOSC + av2 \cdot A_MOSC + av3 \cdot V_MOSC \cdot A_MOSC + av4$, wherein

AV_MOSC is the reference quality of the multimedia, V_MOSC is the reference video quality, A_MOSC is the reference audio quality, and $av1$, $av2$, $av3$, and $av4$ are constants.

15 16. The apparatus according to claim 14 or 15, wherein the multimedia distortion quality comprises: multimedia distortion quality due to packet loss and/or multimedia distortion quality due to rebuffering; and the second determining module is specifically configured to: determine, according to the reference video quality and a video packet loss rate, video quality due to packet loss that is after a packet in a video of the multimedia is lost, and/or determine,
20 according to the reference audio quality and an audio packet loss rate, audio quality due to packet loss that is after a packet in an audio of the multimedia is lost; acquire the multimedia distortion quality due to packet loss according to the video quality due to packet loss and/or the audio quality due to packet loss; and/or

acquire the multimedia distortion quality due to rebuffering according to a rebuffering
25 parameter, during a transmission process, of the multimedia.

17. The apparatus according to claim 16, wherein the second determining module is specifically configured to: determine video distortion quality due to packet loss according to the video quality due to packet loss and the reference video quality, and determine audio packet loss distortion quality according to the audio quality due to packet loss and the

reference audio quality; determine a video packet loss distortion factor according to the video distortion quality due to packet loss and the reference video quality, and determine an audio packet loss distortion factor according to the audio packet loss distortion quality and the reference audio quality; determine a multimedia packet loss distortion factor according to the video packet loss distortion factor and the audio packet loss distortion factor; and determine the multimedia distortion quality due to packet loss according to the multimedia packet loss distortion factor and the reference quality of the multimedia.

18. The apparatus according to claim 17, wherein the second determining module is specifically configured to: determine the video distortion quality due to packet loss V_{DP} according to $V_{DP} = V_{MOSC} - Video_MOS$, wherein V_{MOSC} is the reference video quality, and $Video_MOS$ is the video quality due to packet loss; and

determine the audio packet loss distortion quality A_{DP} according to $A_{DP} = A_{MOSC} - Audio_MOS$, wherein A_{MOSC} is the reference audio quality, and $Audio_MOS$ is the audio quality due to packet loss.

19. The apparatus according to claim 17 or 18, wherein the second determining module is specifically configured to:

determine the video packet loss distortion factor AV_{DFV} according to $AV_{DFV} = \frac{V_{DP}}{V_{MOSC}}$ or $AV_{DFV} = \frac{V_{MOSC} - Video_MOS}{V_{MOSC}}$, wherein V_{MOSC} is the

reference video quality, and V_{DP} is the video distortion quality due to packet loss; and/or,

determine the audio packet loss distortion factor AV_{DFA} according to $AV_{DFA} = \frac{A_{DP}}{A_{MOSC}}$

or $AV_{DFA} = \frac{A_{MOSC} - Audio_MOS}{A_{MOSC}}$, wherein A_{MOSC} is the reference audio quality,

and A_{DP} is the audio packet loss distortion quality.

20. The apparatus according to any one of claims 17 to 19, wherein the second determining module is specifically configured to: determine the multimedia packet loss

distortion factor AV_DF according to $\frac{av5 \cdot AV_DFV + av6 \cdot AV_DFA}{1 + av5 \cdot AV_DFV + av6 \cdot AV_DFA}$ or

$AV_DF = av5 + av6 \cdot AV_DFV + av7 \cdot AV_DFA$, wherein AV_DFA is the audio packet loss distortion factor, AV_DFV is the video packet loss distortion factor, and $av5$, $av6$ and $av7$ are constants.

21. The apparatus according to any one of claims 17 to 20, wherein the second determining module is specifically configured to: determine the multimedia distortion quality due to packet loss AV_DP according to $AV_DP = (AV_MOSC - MOS_MIN) \cdot AV_DF$, wherein AV_MOSC is the reference quality of the multimedia, MOS_MIN is lowest quality of the multimedia, and AV_DF is the multimedia packet loss distortion factor.

22. The apparatus according to any one of claims 16 to 21, wherein the rebuffering parameter comprises one or any combination of the following: the number of rebufferings, rebuffering duration, an impact factor between multiple rebufferings, and multimedia initial quality.

23. The apparatus according to claim 22, wherein the second determining module is specifically configured to: according to

$$AV_DR = (Audiovisual_Quality - MOS_MIN) \cdot \frac{\left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}}{1 + \left(\frac{NR}{av7}\right)^{av8} \cdot \left(\frac{ARL}{av9}\right)^{av10} \cdot \left(\frac{MRF}{av11}\right)^{av12}},$$

acquire the multimedia distortion quality due to rebuffering AV_DR , wherein $Audiovisual_Quality$ is the multimedia initial quality, NR is the number of rebufferings, ARL is the rebuffering duration, MRF is the impact factor between multiple rebufferings, and $av7$ – $av12$ are constants.

24. The apparatus according to claim 23, wherein the third determining module is specifically configured to:

determine the multimedia quality due to packet loss according to the reference quality of the multimedia and the multimedia distortion quality due to packet loss; and

determine the quality of the multimedia according to the reference quality of the multimedia or the multimedia quality due to packet loss, and the distortion quality due to rebuffering.

25. The apparatus according to claim 24, wherein the third determining module is
5 specifically configured to: determine the multimedia quality due to packet loss AV_MOSP according to $AV_MOSP = AV_MOSC - AV_DP$, wherein AV_MOSC is the reference quality of the multimedia, and AV_DP is the multimedia distortion quality due to packet loss.

26. The apparatus according to claim 24 or 25, wherein the third determining module is
specifically configured to: determine the quality AV_MOSR of the multimedia according to
10 $AV_MOSR = Audiovisual_Quality - AV_DR$, wherein $Audiovisual_Quality$ is the reference quality of the multimedia or the multimedia quality due to packet loss, and AV_DR is the distortion quality due to rebuffering.

27. A terminal, comprising a receiving module, configured to receive multimedia; and
further comprising: the multimedia quality monitoring apparatus according to any one of
15 claims 14 to 26.

28. A terminal, comprising a receiver, configured to receive multimedia; and further
comprising: a processor, configured to execute the multimedia quality monitoring method
according to any one of claims 1 to 13.

29. A network device, comprising: a receiving module, configured to receive multimedia;
20 and further comprising: the multimedia quality monitoring apparatus according to any one of
claims 14 to 26.

30. A network device, comprising a receiver, configured to receive multimedia; and
further comprising: a processor, configured to execute the multimedia quality monitoring
method according to any one of claims 1 to 13.