

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
4 August 2011 (04.08.2011)



(10) International Publication Number
WO 2011/092450 A8

(51) International Patent Classification:
F17C 11/00 (2006.01)

(21) International Application Number:
PCT/GB2010/002315

(22) International Filing Date:
22 December 2010 (22.12.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1001525.3 29 January 2010 (29.01.2010) GB
1018353.1 29 October 2010 (29.10.2010) GB

(71) Applicant (for all designated States except US): **HAM-WORTHY COMBUSTION ENGINEERING LIMITED** [GB/GB]; Fleets Corner, Poole BH17 0LA (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **O'CONNOR, Simon, Mark** [GB/GB]; 28 Hunt Road, Poole BH15 3QD (GB).

(74) Agent: **HARKNESS, Kate**; Atkinson Wheller Limited, St Brandon's House, 27-29 Great George Street, Bristol BS1 5QT (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,

DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

Published:

— with international search report (Art. 21(3))


(48) Date of publication of this corrected version:

7 September 2012

(15) Information about Correction:
see Notice of 7 September 2012

(54) Title: HANDLING HYDROCARBON CARGOES

Fig 2



(57) Abstract: The loading of crude oil into a storage tank (12) at A causes vent gas comprising a mixture of VOC and inert gas to be vented from the tank (12) at C. The vent gas is compressed and delivered at D to a burner (32) of a boiler (34). The burner also receives, at F, a supply of oil (14) as a support fuel to provide stable combustion, the supply of oil (14) being adjusted automatically according to the Wobbe Index and flow rate of the vent gas. Steam generated in the boiler (34) from the burning of the fuels is used to heat the oil (14), to counter waxiness, or for other purposes.