



(6)

Description

The invention relates to terminals for connecting wires to circuit boards.

A known terminal for connecting a wire to a circuit board comprises a first wire connecting portion including first and second plates located adjacent one another in parallel face-to-face relation and integrally joined at one end by a bight, first and second aligned wire receiving slots extending along respective plates away from a common wire admitting mouth which extends through the bight to provide electrical connection to an insulated wire forced transversely of its axis through the bight into the slots, a first terminal post extending longitudinally away from the other end of the first plate for receipt in an aperture in a printed circuit board.

A disadvantage of the known terminals is that it may upstand for too great a distance from the printed circuit board and may be relatively unstable during connection. Furthermore, the forces produced during insertion of a wire into the slots may be transmitted to the terminal post, possibly damaging a soldered connection between the post and the printed circuit board.

An object of the invention is to provide a terminal of relatively low height, of stable configuration and in which the majority of the force produced during insertion will not be transmitted to the terminal post.

According to the invention, a second plate of a second wire connecting portion similar to the first wire connecting portion is integrally joined at its other end to the other end of the second plate of the first wire connection portion by a transverse web with the slots of both wire connecting portions aligned, a second terminal post extending longitudinally away from the other end of the first plate of the second wire connecting portion, both terminals posts extending towards each other under the web at their root ends, the terminals being comprised in a continuous strip of identical terminals which are formed integrally with one another and are arranged in juxtaposed relationship.

The wire insertion forces may be carried largely by the root ends of the posts which rest on the printed circuit board. The terminal according to the invention is very stable, of versatile function and may be made of thin stock and of very low profile.

Preferably, each second plate is of greater width than each first plate.

Although FR—A—2,270,692 discloses an electrical terminal having a pair of portions each comprising first and second plates located adjacent to one another and each plate having a wire receiving recess, a flexible tongue projecting away from one of the plates, these portions are adapted to act only as wire guides and do not serve to make electrical connection with a wire, and the tongue would not, in practice be

suitable for use as a terminal post for insertion in an aperture in a printed circuit board.

US—A—3,845,455 discloses an electrical terminal having a wire connecting portion comprising a pair of juxtaposed slotted plates each having a wire receiving slot, a pair of terminal posts projecting from the terminal in juxtaposed relationship. However, there is no second such wire connecting portion and the posts project from straps by which the slotted plates are connected.

An example of a terminal according to the invention will now be described with reference to the accompanying drawings in which:—

Figure 1 is a perspective view of several terminals mounted in a printed circuit board;

Figure 2 is a cross-sectional view through a terminal shown in Figure 1;

Figure 3 is a plan view of a terminal blank;

Figure 4 is a perspective view of a strip of terminals;

Figure 5 is a schematic perspective view of terminal mounting apparatus; and

Figure 6 is a schematic perspective view of wire terminating apparatus.

The terminal is stamped and formed from a single piece of sheet metal stock and comprises first and second wire connecting portions 11 and 12 each including first and second plates 13 and 14 or 15 and 16 located adjacent in parallel face-to-face relation and integrally joined at one end by a bight 17 or 18 extending through 180°. First and second aligned wire-receiving slots 21 or 22 and 23 or 24 extend along respective plates of each wire connecting portion away from a common wire admitting mouth 25 or 26 which extends through the bight 17 or 18, each second wire-receiving slot 23 or 24 being narrower than each first slot 21 or 22, respectively, to provide electrical connection and strain relief for an insulated wire forced transversely of its axis through the bight into the slots.

The second plates 23 and 24 are integrally joined together at their other ends by a transverse web 27 so that the narrower, wire core contacting slots 23 and 24, are aligned facing each other. First and second terminal posts 29 and 30 respectively, extend longitudinally away from the other ends of the first plates 13 and 14 of respective wire connecting portions and are integrally joined to respective first plates by root ends 31 and 32, respectively, which extend towards each other.

It should be noted that the plates 15 and 16 are of greater width than the plates 21 and 22 to define the profile of the terminal regardless of minor variations in forming. The free ends of the terminal post may abut during insertion into an aperture in a printed circuit board to provide a resilient wedging action, aiding retention.

When an insulated wire is forced transversely of its axis into the terminal, edges of the slots 23 and 24 penetrate the insulation to establish electrical connection to the wire core

while the slots 21 and 22 grip the insulation to provide strain relief.

The terminal is formed from the blank shown in figure 3 in which precursors of the terminal portions are indicated by primed reference numerals. The terminal is formed so that all burred edges left on the die side of the blank lie against each other on internal surfaces of the terminal and the rounded edges on the punch side lie on the exposed surfaces of the terminal. This is particularly important for the strain relief slots where a wire will be subject to shear stresses only at the rounded edges, while the burred edges may assist in gripping the wire.

The terminal is rugged and stable although of comparatively small size enabling printed circuit boards carrying the terminals to be closely spaced in overlying relation — an important advantage in designing compact electronic equipment. For example, a terminal for 22 gauge wire may be 0.10 inch wide by 0.19 inch high (2.5 mm x 4.8 mm) when mounted on a printed circuit board. The stock material may be brass or phosphor bronze 0.012 inch thick (0.3 mm).

Various wire terminations are possible to both stranded and solid wire including terminating a single wire intermediate its ends in both wire receiving portions and two wires in respective wire receiving portions. In both cases the strain relief will be provided on the correct side of the connection obviating a need for an operator to determine the correct side. In the former case, the termination of stranded wire may be particularly effective as torsional forces inherent in the strand lay may be maintained between the wire receiving portions, enhancing the contact force on the slot edges. If only one wire receiving portion were used lateral movement of the wire could tend to unwrap the lay of the strands resulting in loss of the torsional effect and less physical and electrical contact.

The terminals are manufactured in strip form, such as shown in Figure 4 and the apparatus shown in Figure 5 may be used to sever and insert the terminals successively into a printed circuit board.

In using the apparatus, a strip of terminals is fed along a track 40 until a leading terminal is located in a broad section 41 of a guide tube 42. In this position, the carrier strip will be aligned between a shear die (not shown) at the end of the track and a shear blade 43 on the rear of an insertion ram 44. Operation of the ram drives the leading terminal through a relatively narrow section 45 of the tube where the plates 13 and 14 are pivoted towards each other and into an aperture 46 in the printed circuit board. The resiliency of the terminal may tend to spread the posts 29 in the aperture assisting in retaining the terminal therein.

Wire termination is facilitated by the insertion apparatus shown in Figure 6. A wire is firstly inserted into the terminal slot mouths and a channel section shroud 48 having an insertion ram receiving through-aperture 49 is

placed over the terminal with the wire located in the channel 50. An inserter 51 having suitably located wire engaging rams 52, 53 and 54 is abutted against the upper end of the shroud with the rams received in the aperture 49 in contact with the wire. The inserter 51 is then pushed down to urge the shroud towards the printed circuit board. The wire is engaged by rams 52, 53 and 54 and the channels 50 pushing it into the slots. The shroud permits only sufficient expansion of the terminal during insertion to permit the resilient distention necessary to provide an effective connection to the wire. The clearance between the walls of the shroud aperture 49 and the plates is therefore important and is one reason why the terminal width is defined by the plates 13 and 14. The outer rams contact the surface of the printed circuit board before the wire reaches the blind end of the slots preventing bottoming out of the wire with the attendant risk of shearing and loss of resilient action in the terminal plates.

It should be noted that the slots of the first wire connecting portion may be slightly misaligned with the slots of the second wire connecting portion, for some applications.

Claims

1. A terminal for connecting a wire to a printed circuit board, comprising a first wire connecting portion (11) including first (13) and second (15) plates located adjacent to one another in parallel face-to-face relation and integrally joined at one end by a bight (17), first (21) and second (23) aligned wire receiving slots extending along respective plates (13, 15) away from a common wire admitting mouth (25) which extends through the bight, to provide electrical connection to an insulated wire forced transversely of its axis through the bight (17) into the slots (21, 23), a first terminal post (29), extending longitudinally away from the other end of the first plate for receipt in an aperture in a printed circuit board, characterised in that a second plate (16) of a second wire connecting portion (12) similar to the first wire connecting portion (11) is integrally joined at its other end to the other end of the second plate (15) of the first wire connecting portion (11) by a transverse web (27) with the slots (21, 23, 22, 24) of both wire connecting portions (11, 12) aligned, a second terminal post (30) extending longitudinally away from the other end of the first plate (13) of the second wire connecting portion (12) both terminal posts (29 and 30) extending towards each other under the web (27) at their root ends (31 and 32), the terminal being comprised in a continuous strip of identical terminals which are formed integrally with one another and are arranged in juxtaposed relationship.

2. A terminal according to Claim 1, characterised in that each second plate (15 or 16) is of greater width than each first plate (13 or 14).

while the slots 21 and 22 grip the insulation to provide strain relief.

The terminal is formed from the blank shown in figure 3 in which precursors of the terminal portions are indicated by primed reference numerals. The terminal is formed so that all burred edges left on the die side of the blank lie against each other on internal surfaces of the terminal and the rounded edges on the punch side lie on the exposed surfaces of the terminal. This is particularly important for the strain relief slots where a wire will be subject to shear stresses only at the rounded edges, while the burred edges may assist in gripping the wire.

The terminal is rugged and stable although of comparatively small size enabling printed circuit boards carrying the terminals to be closely spaced in overlying relation — an important advantage in designing compact electronic equipment. For example, a terminal for 22 gauge wire may be 0.10 inch wide by 0.19 inch high (2.5 mm x 4.8 mm) when mounted on a printed circuit board. The stock material may be brass or phosphor bronze 0.012 inch thick (0.3 mm).

Various wire terminations are possible to both stranded and solid wire including terminating a single wire intermediate its ends in both wire receiving portions and two wires in respective wire receiving portions. In both cases the strain relief will be provided on the correct side of the connection obviating a need for an operator to determine the correct side. In the former case, the termination of stranded wire may be particularly effective as torsional forces inherent in the strand lay may be maintained between the wire receiving portions, enhancing the contact force on the slot edges. If only one wire receiving portion were used lateral movement of the wire could tend to unwrap the lay of the strands resulting in loss of the torsional effect and less physical and electrical contact.

The terminals are manufactured in strip form, such as shown in Figure 4 and the apparatus shown in Figure 5 may be used to sever and insert the terminals successively into a printed circuit board.

In using the apparatus, a strip of terminals is fed along a track 40 until a leading terminal is located in a broad section 41 of a guide tube 42. In this position, the carrier strip will be aligned between a shear die (not shown) at the end of the track and a shear blade 43 on the rear of an insertion ram 44. Operation of the ram drives the leading terminal through a relatively narrow section 45 of the tube where the plates 13 and 14 are pivoted towards each other and into an aperture 46 in the printed circuit board. The resiliency of the terminal may tend to spread the posts 29 in the aperture assisting in retaining the terminal therein.

Wire termination is facilitated by the insertion apparatus shown in Figure 6. A wire is firstly inserted into the terminal slot mouths and a channel section shroud 48 having an insertion ram receiving through-aperture 49 is

placed over the terminal with the wire located in the channel 50. An inserter 51 having suitably located wire engaging rams 52, 53 and 54 is abutted against the upper end of the shroud with the rams received in the aperture 49 in contact with the wire. The inserter 51 is then pushed down to urge the shroud towards the printed circuit board. The wire is engaged by rams 52, 53 and 54 and the channels 50 pushing it into the slots. The shroud permits only sufficient expansion of the terminal during insertion to permit the resilient distention necessary to provide an effective connection to the wire. The clearance between the walls of the shroud aperture 49 and the plates is therefore important and is one reason why the terminal width is defined by the plates 13 and 14. The outer rams contact the surface of the printed circuit board before the wire reaches the blind end of the slots preventing bottoming out of the wire with the attendant risk of shearing and loss of resilient action in the terminal plates.

It should be noted that the slots of the first wire connecting portion may be slightly misaligned with the slots of the second wire connecting portion, for some applications.

Claims

1. A terminal for connecting a wire to a printed circuit board, comprising a first wire connecting portion (11) including first (13) and second (15) plates located adjacent to one another in parallel face-to-face relation and integrally joined at one end by a bight (17), first (21) and second (23) aligned wire receiving slots extending along respective plates (13, 15) away from a common wire admitting mouth (25) which extends through the bight, to provide electrical connection to an insulated wire forced transversely of its axis through the bight (17) into the slots (21, 23), a first terminal post (29), extending longitudinally away from the other end of the first plate for receipt in an aperture in a printed circuit board, characterised in that a second plate (16) of a second wire connecting portion (12) similar to the first wire connecting portion (11) is integrally joined at its other end to the other end of the second plate (15) of the first wire connecting portion (11) by a transverse web (27) with the slots (21, 23, 22, 24) of both wire connecting portions (11, 12) aligned, a second terminal post (30) extending longitudinally away from the other end of the first plate (13) of the second wire connecting portion (12) both terminal posts (29 and 30) extending towards each other under the web (27) at their root ends (31 and 32), the terminal being comprised in a continuous strip of identical terminals which are formed integrally with one another and are arranged in juxtaposed relationship.

2. A terminal according to Claim 1, characterised in that each second plate (15 or 16) is of greater width than each first plate (13 or 14).



(18)

3. A terminal according to Claim 1 or Claim characterised in that each second wire receiving slot (23 or 24) is narrower than each first wire receiving slot (21 or 22) so that the slots provide respectively electrical connection and strain relief for an insulated wire.

Revendications

1. Borne pour connecter un fil à une plaquette à circuit imprimé, comprenant une première partie (11) de connexion d'un fil comportant des première (13) et seconde (15) plaques disposées de façon à être adjacentes et parallèles entre elles, face à face et reliées, à une première extrémité, par un coude (17) avec lequel elles sont réalisées d'une seule pièce, des première (21) et seconde (23) encoches alignées de réception de fil s'étendant le long des plaques respectives (13, 15) à partir d'une embouchure commune (25) d'admission de fil qui s'étend à travers le coude, afin d'établir une connexion électrique avec un fil isolé introduit à force transversalement à son axe, à travers le coude (17), dans les encoches (21, 23), une première broche (29) de borne partant longitudinalement de l'autre extrémité de la première plaque afin de se loger dans une ouverture d'une plaquette à circuit imprimé, caractérisée en ce qu'une seconde plaque (16) d'une seconde partie (12) de connexion de fil, similaire à la première partie (11) de connexion de fil, est reliée, par son autre extrémité, à l'autre extrémité de la seconde plaque (15), avec laquelle elle est réalisée d'une seule pièce, de la première partie (11) de connexion de fil, par une âme transversale (27), les encoches (21, 23, 22, 24) des deux parties (11, 12) de connexion de fil étant alignées, une seconde broche (30) de la borne partant longitudinalement de l'autre extrémité de la première plaque (13) de la seconde partie (12) de connexion de fil, les deux broches (29 et 30) de la borne s'étendant l'une vers l'autre au-dessous de l'âme (27), à leurs extrémités de pied (31 et 32), la borne étant réalisée sous la forme d'une bande continue de bornes identiques qui sont réalisées d'une seule pièce les unes avec les autres et sont juxtaposées les unes aux autres.

2. Borne selon la revendication 1, caractérisée en ce que chaque seconde plaque (15 ou 16) est d'une largeur supérieure à chaque première plaque (13 ou 14).

3. Borne selon la revendication 1 ou la revendication 2, caractérisée en ce que chaque seconde encoche (23 ou 24) de réception de fil est plus étroite que chaque première encoche (21 ou 22) de réception de fil de manière que

les encoches établissent, respectivement, une connexion électrique et une soulagement de contrainte pour un fil isolé.

Patentansprüche

1. Anschluß zum Verbinden eines Drahtes mit einer gedruckten Schaltungsplatte mit einem ersten Drahtverbindungsteil (11), der erste (13) und zweite (15) Platten aufweist, die benachbar zueinander und parallel derart angeordnet sind, daß ihre Flächen nebeneinander liegen, und die an einem Ende durch eine Scheitelkrümmung (17) einstückig miteinander verbunden sind, wobei sich erste (21) und zweite (23) zueinander ausgerichtete Drahtaufnahmeschlitzte längs der jeweiligen Platten (13, 15) von einer gemeinsamen Drahteinlaßmündung (25) weg erstrecken, die sich durch die Scheitelkrümmung erstreckt, um eine elektrische Verbindung mit einem isolierten Draht zu schaffen, der quer zu seiner Achse durch die Scheitelkrümmung hindurch in die Schlitzte (21, 23) hineingedrückt wird, wobei sich ein erster Anschlußstift (29) in Längsrichtung von dem anderen Ende der ersten Platte weg zur Aufnahme in einer Öffnung in einer gedruckten Schaltungsplatte erstreckt, dadurch gekennzeichnet, daß eine zweite Platte (16) eines zweiten Drahtverbindungsteils (12) ähnlich dem ersten Drahtverbindungsteil (11) an ihrem anderen Ende mit dem anderen Ende der zweiten Platte (15) des ersten Drahtverbindungsteils (11) durch einen Quersteg (27) einstückig verbunden ist, wobei die Schlitzte (21, 23, 22, 24) beider Drahtverbindungsteile (11, 12) zueinander ausgerichtet sind, wobei sich ein zweiter Anschlußstift (30) in Längsrichtung von dem anderen Ende der ersten Platte (14) des zweiten Drahtverbindungsteils (12) weg erstreckt und beide Anschlußstifte (29 und 30) sich unter dem Steg (27) an ihren Fußenden (31 und 32) aufeinander zu erstrecken, wobei der Anschluß in einem kontinuierlichen Streifen identischer Anschlüsse enthalten ist, die einstückig miteinander ausgebildet und nebeneinander angeordnet sind.

2. Anschluß nach Anspruch 1, dadurch gekennzeichnet, daß jede zweite Platte (15 oder 16) größere Breite hat also jede erste Platte (13 oder 14).

3. Anschluß nach Anspruch 1 oder Anspruch 2, dadurch gekennzeichnet, daß jeder zweite Drahtaufnahmeschlitz (23 oder 24) schmaler ist also jeder erste Drahtaufnahmeschlitz (21 oder 22), so daß die Schlitzte einerseits elektrische Verbindung und andererseits Zugentlastung für einen isolierten Draht bieten.

This Sheet Has Been Replaced



65

4.



* C L M S *