

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H01F 17/00, 17/04, 41/04	A1	(11) International Publication Number: WO 97/20327 (43) International Publication Date: 5 June 1997 (05.06.97)												
(21) International Application Number: ✓ PCT/JP96/03462 (22) International Filing Date: ✓ 27 November 1996 (27.11.96) (30) Priority Data: <table border="0"> <tr> <td>✓ 7/307079</td> <td>✓ 27 November 1995 (27.11.95)</td> <td>✓ JP</td> </tr> <tr> <td>✓ 7/325435</td> <td>✓ 14 December 1995 (14.12.95)</td> <td>✓ JP</td> </tr> <tr> <td>✓ 8/65949</td> <td>✓ 22 March 1996 (22.03.96)</td> <td>✓ JP</td> </tr> <tr> <td>✓ 8/65952</td> <td>✓ 22 March 1996 (22.03.96)</td> <td>✓ JP</td> </tr> </table> (71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571 (JP). ✓ (72) Inventors; and (75) Inventors/Applicants (for US only): IBATA, Akihiko [JP/JP]; 5-3-5, Hagoromo, Takaishi-shi, Osaka 592 (JP). HARADA, Shinji [JP/JP]; 4-4-12, Myokenzaka, Katano-shi, Osaka 576 (JP). KAWAMATA, Tadashi [JP/JP]; 2-27-15, Shojaku Honmachi, Settsu-shi, Osaka 566 (JP). ✓ (74) Agents: AOYAMA, Tamotsu et al.; Aoyama & Partners, IMP Building, 3-7, Shiromi 1-chome, Chuo-ku, Osaka-shi, Osaka 540 (JP).		✓ 7/307079	✓ 27 November 1995 (27.11.95)	✓ JP	✓ 7/325435	✓ 14 December 1995 (14.12.95)	✓ JP	✓ 8/65949	✓ 22 March 1996 (22.03.96)	✓ JP	✓ 8/65952	✓ 22 March 1996 (22.03.96)	✓ JP	(81) Designated States: CN, KR, SG, US. Published With international search report. SG 9802879-8 (26/5/99) PCT + Annexes + PF23
✓ 7/307079	✓ 27 November 1995 (27.11.95)	✓ JP												
✓ 7/325435	✓ 14 December 1995 (14.12.95)	✓ JP												
✓ 8/65949	✓ 22 March 1996 (22.03.96)	✓ JP												
✓ 8/65952	✓ 22 March 1996 (22.03.96)	✓ JP												
(54) Title: COILED COMPONENT AND ITS PRODUCTION METHOD ✓ (57) Abstract A coiled component (K1) comprising: an insulating member (3); a conductive member (5) which is provided in the insulating member (3) and has a plurality of turns gradually different, in diameter, from each other from one end towards the other end of the conductive member (5) such that at least the turns of the conductive member (5) are disposed in different planes, respectively; and a magnetic layer (8, 9) which is provided on at least one of upper and lower faces of the insulating member (3).														