

## METHOD AND DEVICE FOR THE DETECTION OF MICROSLEEP EVENTS

### FIELD OF THE INVENTION

The present invention concerns a method and device for the detection of  
5    microsleep events.

### BACKGROUND OF THE INVENTION

Methods for quantifying driving performance errors associated with sleep onset  
are of key importance for reducing the number of sleep related crashes. In the  
US, driver sleepiness is a major cause of motor vehicle crashes and is  
10    responsible for approximately 40,000 injuries and 1500 deaths each year. In one  
study, 55% of 1000 drivers surveyed indicated that they had driven while drowsy  
and 23% had fallen asleep at the wheel. This confirms other studies that  
sleepiness or sleep onset may play a role in vehicle crashes that are erroneously  
attributed to other causes.

15    Microsleep events are a useful indicator of sleep onset. A microsleep event often  
occurs as a result of sleep deprivation, or mental fatigue, sleep apnea,  
narcolepsy, or hypersomnia.

There are standardized methods for monitoring microsleep, which include:  
monitoring the electroencephalogram (EEG) and electrooculogram (EOG), video,  
20    test of performance, and the like. Of all these methods, the EEG is considered  
the most reliable for measuring sleepiness. However, both EEG and EOG,  
require the use of electrodes, which are attached to the subject, thereby making  
these methods inappropriate to routinely monitor any operators conducting  
fatigue prone tasks, such as, for example, vehicle drivers. The other methods are  
25    impractical because they are both difficult to set-up and because they require  
intensive data analysis by humans thereby making data treatment difficult to  
automate.

There are various ways by which microsleep episodes can be identified. Some experts define microsleep according to behavioral criteria (eyelids closure), while others rely on electroencephalogram markers such as a 3-15 second episode (shorter durations would be difficult to visually detect and longer times would  
5 qualify as sleep onset.) during which 4-7 Hz (theta wave) activity replaced the waking 14-20 Hz (alpha wave) background rhythm.

Microsleep, subjectively related to the sensation of "nodding off", is associated with the interruption of the blinking artifacts characteristic of full wakefulness. During microsleep events, attention lapses can impair the ability to detect and  
10 respond to crucial stimuli and events. For example, microsleeps (or microsleep episodes) can become extremely dangerous when occurring during situations which require continual alertness, such as driving a motor vehicle or operating machinery. People who experience microsleeps usually remain unaware of them, instead believing themselves to have been awake the whole time, or feeling a  
15 sensation of 'spacing out'. The sleepy driver is at very high risk of having an accident during a microsleep episode. Many accidents have occurred because of microsleep episodes.

Clearly, the ability to detect microsleep events would be useful as a means of alerting and warning drowsy drivers of such events.

20 Several studies have used "quantitative" EEG methods to identify driver sleepiness. Theta power (EEG waves), and the frequency of theta bursts typically increase during prolonged driving, and are associated with poor driving performance. Disadvantageously, these techniques typically average EEG activity over several seconds (up to 1 minute), and therefore could not be used to  
25 detect brief microsleep events of between 3 seconds and 15 seconds.

A variety of physiological measures have been proposed to alert drivers to the onset of drowsiness.

One of the most investigated is PERCLOS (or PERcent CLOSure), which measures drowsiness as the percent of time a driver's eyes are closed over a

time period. When a sufficient number of open/closed patterns are obtained, PERCLOS will trigger an alarm. PERCLOS works at percentages greater than 80%, which typically means that within 1 minute, the eyes of the individual must be closed for 48 seconds before an alarm is triggered. Clearly, this delay in  
5 unacceptable in tasks such as driving a vehicle because by the time PERCLOS activates the alarm, the driver will already have either fallen asleep, or be on the verge of falling asleep. Therefore, disadvantageously PERCLOS is too slow a system to allow preventive actions to be taken before an individual, such as a driver, experiences the first signs of sleepiness.

10 EOG records, which are made to exclude potential artifacts during EEG records, also show that normal eye blinks often continue during microsleep events, indicating that the eyes are at least partially open.

Another physiological measure, which is based on measurements of eye closure and which supposedly alerts drivers to the onset of drowsiness, is the  
15 measurement of peak blink velocities, as described in United States Patent 7071831B2. The system described therein includes a pair of glasses or spectacle frames that must be worn by the individuals in order to monitor the occurrence of eye blinks. However, this kind of device must be carried or worn by operators (i.e. portable devices).

20 Thus, there is a need for a detection method and device for the detection of microsleep events in a subject as an indicator of sleep onset that is able to detect brief microsleep events, at early stages, not requiring the use of electrodes or other portable devices.

### **BRIEF SUMMARY**

25 We have unexpectedly discovered that microsleep events can be easily and readily detected by measuring the closing and opening patterns of the eyelids over time using a microsleep detection process, converting the raw data collected from the measurements into graphs and comparing the graphs to those of stored, standardized microsleep patterns.

Accordingly, in one embodiment there is provided a method of detecting a microsleep event in a subject, the method comprising: - determining a plurality of eye openness factors by measuring a plurality of distances between an upper eyelid and a lower eyelid of at least one eye over a time period; - generating graphical representations of the eye openness factors; and - correlating changes in the eye openness factors over the time period with a reference eye closure pattern indicative of the microsleep event.

The method, as described above, further comprising: illuminating the face of the subject; and recording a facial image. A digital camera having an infra-red source is used to illuminate the face and to record the facial image.

The method, as described above, further comprising: identifying the eye and the eyelids by using a facial feature recognition algorithm.

The method, as described above, further comprising: verifying the presence of microsleep characteristic eye openness factor levels by measuring the eye openness factors as a function of time for a blink cycle of the eye. The eye openness factors levels include at least one eye openness level. The eye openness factors include one or more eye openness levels and five or less eye openness levels. The eye openness factors include five eye openness levels. The eye openness levels are associated with an open eye, the closure of the eyelids, partial or closed eye, and opening of the eyelids.

The method, as described above, in which the eye openness factors include five successive eye openness levels, the sequential detection of the five levels being indicative of microsleep characteristics. The method further comprising: determining additional eye openness factors if less than five successive eye openness factor levels are detected.

The method, as described above, further comprising: computing eye opening and eye closure representative curves. The eye closure representative curves are computed using a negative slope and a second order polynomial regression applied to the eye openness factors of the first and second eye openness factor

levels. The eye opening factors are computed using a positive slope and a second order polynomial regression applied to the eye openness factors of the fourth and fifth eye openness factor levels. The method further comprising: verifying the presence of microsleep eye opening and closing representative  
5 curves by computing the Pearson coefficient of the eye closure representative curves with regard to the first and second eye openness factor levels and the eye opening representative curves with regard to the fourth and fifth eye factor levels. The subject is informed when the Pearson coefficients are greater than or equal to a predetermined threshold value.

- 10 The method, as described above, in which images of the face are sampled at a frequency of between 10 Hz and 60Hz.

The method, as described above, further comprising: a sub-process for detecting microsleep characteristic eye openness factor levels at an image sampling frequency of 20Hz. The sub-process comprises: verifying that a first level is  
15 detected by confirming the presence of a series six or more successive eye openness factors corresponding to an open eye.

The method, as described above, further comprising: verifying that a second level is detected by confirming the presence of a series four or more successive decreasing eye openness factors. The method, as described above, further  
20 comprising: verifying that a third level is detected by confirming the presence of a series of a minimum of five and a maximum of one-hundred and twenty successive eye openness factors.

The method, as described above, further comprising: verifying that a fourth level is detected by confirming the presence of a series of a minimum of four  
25 successive eye openness factors.

The method, as described above, further comprising: verifying that a fifth level is detected by confirming the presence of a series of a minimum of six successive eye openness factors corresponding to the open eye.

The method, as described above, further comprising: alerting the subject to the presence of the microsleep event.

According to one aspect, there is provided a microsleep event detection device, the device comprising:

- 5           - a facial image sampler for sampling facial images over time of a subject; the sampler having an infra red source for illuminating one or more eyes of the subject;
- a microprocessor having electronically stored therein an electronically executable microsleep detection process, the microprocessor being connected to the sampler for receiving the sampled facial images, the images being graphical
- 10       representations of eye openness factors, the microprocessor, when in operation, electronically executes a microsleep detection process; and
- a memory electronically connected to the microprocessor, the memory having stored therein a plurality of reference eye closure patterns which, in operation, permits electronic correlation of the eye openness factors with the reference eye closure
- 15       patterns.

The device, as described above further comprises an alert connected to the microprocessor for alerting the subject to the microsleep event.

- 20       Accordingly, in another aspect there is provided a method of alerting a vehicle operator to a microsleep event, the method comprising:

- determining a plurality of eye openness factors by measuring a plurality of distances between an upper eyelid and a lower eyelid of at least one eye over a time period;
- 25       - generating graphical representations of the eye openness factors;
- correlating changes in the eye openness factors over the time period with a reference eye closure pattern indicative of the microsleep event; and
- triggering an alarm so as to alert the operator to the microsleep event.

30

Accordingly, in yet another aspect, there is provided a method of correlating EEG and EOG microsleep patterns with eye closure patterns, the method comprising:

- measuring EEG and EOG microsleep patterns in a subject;
- determining a plurality of eye openness factors by measuring a plurality of distances between an upper eyelid and a lower eyelid of at least one eye over a time period;
- generating graphical representations of the eye openness factors; and
- correlating changes in the eye openness factors with the EEG and EOG microsleep patterns.

In yet another aspect, there is provided a computer-implemented method of detecting a microsleep event in a subject, the method comprising: receiving a signal from an infra red source at one or more eyes of the subject; determining a plurality of eye openness factors by measuring a plurality of distances between an upper eyelid and a lower eyelid of at least one eye over a time period; generating graphical representations of the eye openness factors; and correlating changes in the eye openness factors over the time period with a reference eye closure pattern indicative of the microsleep event.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Embodiments of the invention will be described by way of example only with reference to the accompany drawings, in which:

Figure 1 is a block diagram of a microsleep detection device according to an illustrative embodiment of the present invention, the device being used on a subject;

Figure 2 is a flow diagram of a microsleep event detection process that may be used by the device of Figure 1;

Figure 3A and 3B are schematic views of the fully open eye (Figure 3A) and the fully closed eye (Figure 3B) with their associated eye openness factor;

Figure 4 is a series of schematic views of an example of the variation of the eye openness factor as a function of time for a blink cycle;

Figure 5 is an illustrative example of the fully closed eye (period L4 and L5), at the moment of a microsleep; and

Figure 6 is a flow diagram of a microsleep characteristic eye openness factor levels detection sub-process that may be used with the microsleep event detection process of Figure 2 for an image sampling frequency of 20 Hz.

### **DETAILED DESCRIPTION**

- 5 Generally stated, the non-limitative illustrative embodiment of the present invention provides a method and device for the detection of microsleep events in a human subject based on the analysis of eye closure patterns of at least one eye, typically both eyes, which occur during microsleep events.

- During microsleep events, measured by EEG and EOG, we observed a  
10 progressive variation of the distance between an upper eyelid and a lower eyelid of a human subject over time. We now describe hereinbelow a method and device, which provides complementary evidence of impending sleep in drowsy operators, such as vehicle drivers, airplane pilots, air traffic controllers and the like, using eye closure patterns, which when detected, alerts sleepy operators to  
15 unsafe situations before eyelid closure occurs, thereby correlating EEG and EOG microsleep patterns with eye closure patterns.

Also described is a method for the analysis of eye closure patterns allowing the differentiation between a normal eyelid closure and one due to drowsiness.

- Referring to Figure 1, there is shown an example of a microsleep event detection  
20 device 100, which generally comprises facial image sampler such as a digital camera 102 with an associated infrared source 104, a microprocessor 106 with an associated memory 108 and either or both an alarm/display 110 and input/output interface 112.

- Thus, in one example, there is described a method using the device 100 for  
25 detecting a microsleep event in a human subject. The method comprises: determining a plurality of eye openness factors by measuring a plurality of distances between an upper eyelid and a lower eyelid of at least one eye, typically both eyes, over a time period; generating graphical representations of

the eye openness factors; and correlating changes in the eye openness factors over the time period with a reference eye closure pattern indicative of the microsleep event.

In operation, the digital camera 102 is aimed at the face of a subject 10 and  
5 illuminates his or her eyes 12 using the infrared source 104 in order to determine the eye openness factor, i.e. a value representative of the distance between the upper 14a and lower 14b eyelids. The images taken by the digital camera 102 are then processed by the processor 106 which executes a microsleep event detection process stored on its associated memory 108. Upon detection of a  
10 microsleep event, the microsleep event detection device 100 may inform the user of a microsleep event by triggering an integrated alarm and/or display 110 or provide the information to a further process or device via the input/output interface 112. It is to be understood that other components may be added to the microsleep event detection device 100 such as, for example, a user interface and  
15 a wireless communication device.

Referring now to Figure 2, there is shown a flow diagram of a microsleep event detection process 200 that may be electronically executed by the processor 106 of the microsleep event detection device 100 of Figure 1. The steps of the process 200 are indicated by blocks 202 to 212. The process 200 starts at block  
20 202 by sampling an image of the face of a subject 10 using the digital camera 102. The digital camera 102 may sample images at a frequency between about 10 and 60Hz (i.e. sampling frequency). At block 204, the process 200 identifies, in the sampled digital image, the eye 12 and eyelids 14a, 14b of the subject 10. This may be accomplished using a facial feature recognition algorithm executed  
25 by the processor 106. Then, the eye openness factor is computed.

Referring now to Figures 3A and 3B, the eye openness factor may be expressed as  $\delta$  having a value between 1, representing a fully open eye 12 (see Figure 3A), and 0, representing a fully closed eye 12 (see Figure 3B). The value of  $\delta$  may be computed, for example, by dividing the measured distance between the upper

14a and lower 14b eyelids positions in a Cartesian representation (X,Y) by a reference measure of the fully open eye D. Thus:

$$\delta = (\text{upper lid position } (x_u, y_u) - \text{lower lid position } (x_l, y_l)) / D_{\perp}$$

where D = upper lid position  $(x_u, y_u)$  – lower lid position  $(x_l, y_l)$  and  $(x_u, y_u)$  =

- 5 instant upper lid position,  $(x_l, y_l)$  = instant lower lid position,  $(x_u, y_u)$  = upper lid position at maximum eye opening and  $(x_l, y_l)$  = lower lid position at maximum eye opening.

Referring again to Figure 2 at block 206, the process verifies if the microsleep characteristic eye openness factor levels are present.

- 10 Referring to Figure 4, there is shown an illustrative example of the variation of the eye openness factor as a function of time for a blink cycle. The blink cycle starts at time  $t_1$  with a fully open eye 12 (eye openness factor  $\delta = 1.00$ ), at  $t_2$  the eye openness factor remains at  $\delta = 1.00$ , then decreases, going through  $\delta = 0.80$  and  $\delta = 0.50$  at times  $t_i$  and  $t_{i+1}$ , until it reaches  $\delta = 0.00$  at time  $t_j$  (fully closed eye 12),  
 15 and then increases, going through  $\delta = 0.50$  and  $\delta = 0.80$  at times  $t_k$  and  $t_{k+1}$ , until it reaches  $\delta = 1.00$  again at  $t_n$ . It is to be understood that the blink cycle illustrated in Figure 4 for illustrative purpose only and that an actual cycle would comprise a number of sample times depending the sample frequency.

- Referring now to Figure 5, these computed eye openness factors, as a function of  
 20 time, can be represented in a graph which may be generally characterized by five successive levels, L1 to L5. The first and last levels, L1 and L5, are associated with the open eye (i.e.  $\delta = 1.00$ ), the second level, L2, with the closure of the eyelids, 14a, 14b (i.e.  $0.00 > \delta > 0.00$ ,  $\delta$  decreasing), the third level L3, with the partial or closed eye (i.e.  $0.00 < \delta < 0.5$  for example) and fourth level, L4, with the  
 25 opening of the eyelids 14a, 14b (i.e.  $0.00 < \delta < 1.00$ ,  $\delta$  increasing).

Referring again to Figure 2, the process 200 detects all five levels, i.e. L1 to L5, it then proceeds to block 208. If not, it proceeds back to block 202 for the next

image sample. At block 208, the process computes the eye closure 21 or 26 and eye opening 25 or 27 representative curves. The eye closure representative curve 21 or 26 is computed using negative slope second order polynomial regression (parabolic curve), i.e.

$$Y = d_0 + d_1.X + d_2.X^2.$$

where Y is the predicted outcome value for the polynomial model with regression coefficients  $d_1$  to  $d_2$  for each degree and Y intercept  $d_0$ ;

which is applied to the eye openness factors composing the first and second eye openness factor levels, i.e. L1 and L2. As for the eye opening representative curve 25 or 27, it is computed using positive slope second order polynomial regression applied to the eye openness factors composing the fourth and fifth eye openness factor levels, i.e. L4 and L5. Then, at block 210, the process 220 verifies if the microsleep eye opening and closing representative curves are present. This is accomplished by computing the Pearson coefficient, r:

$$r = \frac{\sum XY - \frac{\sum X \sum Y}{N}}{\sqrt{(\sum X^2 - \frac{(\sum X)^2}{N})(\sum Y^2 - \frac{(\sum Y)^2}{N})}}$$

where X and Y are positions in a Cartesian representation;

of the eye closure representative curve 21 or 26 with regard to the eye openness factors composing eye openness factor levels L1 and L2, and of the eye opening representative curve 25 or 27 with regard to the eye openness factors composing the eye openness factor levels L4 and L5. If both Pearson coefficients are greater or equal to a given threshold such as, for example, 0.9, then the process 200 proceeds to block 212. If not, it proceeds back to block 202 for next image sample. Finally, at block 212, the microsleep event detection device 100 may inform the user 10 of the detection of a microsleep event state via the integrated alarm and/or display 110 or provide the information to a further process or device via the input/output interface 112 (see Figure 1) using, for instance, a wired or

wireless telecommunication link such as, for example, Bluetooth, WiFi and the like.

It is to be understood that the Pearson coefficient threshold is not meant to be restricted to 0.9 and may be adjusted to suit a desired confidence level. It may  
5 also vary depending on the resolution of the digital camera 102 (see Figure 1).

The eye closure pattern is based on these particular observations closing, duration of the eyelid complete or partial closure and re-opening. More precisely, the eye closure pattern indicates a progressive decreasing followed by a baseline period where the eyelids are fully closed and then a reopening. If all the above  
10 occur, then a microsleep is detected.

Example of microsleep characteristic eye openness factor levels at an image sampling frequency of 20GHz

Referring now to Figure 6, there is shown a flow diagram a microsleep  
15 characteristic eye openness factor levels detection sub-process 300 that may be executed at block 206 of process 200 in order to detect the presence of the five microsleep characteristic eye openness factor levels, i.e. L1 to L5 (see Figure 5) for an image sampling frequency of 20 Hz. The steps of the sub-process 300 are indicated by blocks 301 to 305.

20 At block 301, the sub-process 300 verifies if the first level L1 is detected. To that end, the sub-process 300 checks if a series of a minimum of six (6) successive eye openness factors having a value of  $\delta = 1.00$  is present. If so, the sub-process 300 proceeds to block 302, if not, it goes back to block 202 of process 200 (see Figure 2).

25 At block 302, the sub-process 300 verifies if the second level L2 is detected. To that end, the sub-process 300 checks if a series of a minimum of four (4) successive decreasing eye openness factors having values between of  $\delta = 0.99$

and  $\delta = 0.01$  is present. If so, the sub-process 300 proceeds to block 303, if not, it goes back to block 202 of process 200 (see Figure 2).

Then, at block 303, the sub-process 300 verifies if the third level L3 is detected. To that end, the sub-process 300 checks if a series of a minimum of five (5) and  
5 a maximum of 120 successive eye openness factors having a value of  $\delta = 0.00$  is present. If so, the sub-process 300 proceeds to block 304, if not, it goes back to block 202 of process 200 (see Figure 2).

At block 304, the sub-process 300 verifies if the fourth level L4 is detected. To that end, the sub-process 300 checks if a series of a minimum of four (4)  
10 successive increasing eye openness factors having values between of  $\delta = 0.01$  and  $\delta = 0.99$  is present. If so, the sub-process 300 proceeds to block 305, if not, it goes back to block 202 of process 200 (see Figure 2).

Finally, at block 305, the sub-process 300 verifies if the fifth level L5 is detected. To that end, the sub-process 300 checks if a series of a minimum of six (6)  
15 successive eye openness factors having a value of  $\delta = 1.00$  is present. If so, the sub-process 300 proceeds to block 208 of process 200 (see Figure 2), the presence of all five (5) microsleep characteristic eye openness factor levels. If not, the sub-process 300 goes back to block 202 of process 200 (see Figure 2). It is to be understood that the number of eye openness factors used to detect the  
20 presence of each microsleep characteristic eye openness factor level may vary, for example according to the image sampling frequency and are meant as illustrative examples only.

It is to be understood that the memory associated with the microprocessor as described above, contains a plurality of reference eye closure patterns stored  
25 therein. The graphs as illustrated in Figure 5 are compared to the reference eye closure patterns. Once a match is found, a microsleep event is verified and the alarm is activated

Although the present invention has been described by way of a particular embodiment and examples thereof, it should be noted that it will be apparent to

persons skilled in the art that modifications may be applied to the present particular embodiment without departing from the scope of the present invention.

## CLAIMS

1. A method of alerting a vehicle operator to a microsleep event, the method comprising:

determining a plurality of eye openness factors by measuring a plurality of distances between an upper eyelid and a lower eyelid of at least one eye over a time period;

generating graphical representations of the eye openness factors;

correlating changes in the eye openness factors over the time period with a reference eye closure pattern indicative of the microsleep event; and

triggering an alarm so as to alert the operator to the microsleep event.

2. The method, according to claim 1, further comprising: illuminating the face of the subject; and recording a facial image.

3. The method, according to claim 2, in which a digital camera having an infra-red source is used to illuminate the face and to record the facial image.

4. The method, according to claim 1, further comprising: identifying the eye and the eyelids using a facial feature recognition algorithm.

5. The method, according to claim 1, further comprising: verifying the presence of microsleep characteristic eye openness factor levels by measuring the eye openness factors as a function of time for a blink cycle of the eye.

6. The method, according to claim 5, in which the eye openness factors levels include at least one eye openness level.

7. The method, according to claim 5, in which the eye openness factors include one to five eye openness levels.

8. The method, according to claim 5, in which the eye openness factors include five eye openness levels.
9. The method, according to claim 5, in which the eye openness levels are associated with an open eye, the closure of the eyelids, partial or closed eye, and opening of the eyelids.
10. The method, according to claim 1, in which the eye openness factors include five successive eye openness levels, the sequential detection of the five levels being indicative of microsleep characteristics.
11. The method, according to claim 10, further comprising: determining additional eye openness factors if less than five successive eye openness levels are detected.
12. The method, according to claim 5, further comprising: computing eye opening and eye closure representative curves.
13. The method, according to claim 12, in which the eye closure representative curves are computed using a negative slope and a second order polynomial regression applied to the eye openness factors of the first and second eye openness factor levels.
14. The method, according to claim 12, in which the eye opening factors are computed using a positive slope and a second order polynomial regression applied to the eye openness factors of the fourth and fifth eye openness factor levels.
15. The method, according to claim 12, further comprising: verifying the presence of microsleep eye opening and closing representative curves by computing the Pearson coefficient of the eye closure representative curves with regard to the first and second eye openness factor levels and the eye opening representative curves with regard to the fourth and fifth eye openness factor levels.
16. The method, according to claim 15, in which the subject is informed when the Pearson coefficients are greater than or equal to a predetermined threshold value.

17. The method, according to claim 3, in which images of the face are sampled at a frequency of between 10 Hz and 60 Hz.

18. The method, according to claim 5, further comprising: a sub-process for detecting microsleep characteristic eye openness factor levels at an image sampling frequency of 20 Hz.

19. The method, according to claim 18, in which the sub-process comprises: verifying that a first level is detected by confirming the presence of a series six or more successive eye openness factors corresponding to an open eye.

20. The method, according to claim 19, further comprising: verifying that a second level is detected by confirming the presence of a series four or more successive decreasing eye openness factors.

21. The method, according to claim 20, further comprising: verifying that a third level is detected by confirming the presence of a series of a minimum of five and a maximum of one-hundred and twenty successive eye openness factors.

22. The method, according to claim 21, further comprising: verifying that a fourth level is detected by confirming the presence of a series of at least four successive eye openness factors.

23. The method, according to claim 22, further comprising: verifying that a fifth level is detected by confirming the presence of a series of a minimum of six successive eye openness factors corresponding to the open eye.

24. The method, according to claim 1, further comprising: alerting the subject to the presence of the microsleep event.

25. A microsleep event detection device, the device comprising:

a facial image sampler for sampling facial images over time of a subject, the sampler having an infra red source for illuminating one or more eyes of the subject;

a microprocessor connected to the sampler for receiving the sampled facial images, the images being graphical representations of eye openness factors, the microprocessor, when in operation, electronically executes a microsleep detection process; and

a memory electronically connected to the microprocessor, the memory having stored therein a plurality of reference eye closure patterns, which, in operation, permits electronic correlation of the eye openness factors with the reference eye closure patterns.

26. The device, according to claim 25, further comprising an alert connected to the microprocessor for alerting the subject to the microsleep event.

27. A method of correlating EEG and EOG microsleep patterns with eye closure patterns, the method comprising: measuring EEG and EOG microsleep patterns in a subject; determining a plurality of eye openness factors by measuring a plurality of distances between an upper eyelid and a lower eyelid of at least one eye over a time period; generating graphical representations of the eye openness factors; and correlating changes in the eye openness factors with the EEG and EOG microsleep patterns.

28. A computer-implemented method of detecting a microsleep event in a subject, the method comprising:

receiving a signal from an infra red source at one or more eyes of the subject;

determining a plurality of eye openness factors by measuring a plurality of distances between an upper eyelid and a lower eyelid of at least one eye over a time period; generating graphical representations of the eye openness factors; and

correlating changes in the eye openness factors over the time period with a reference eye closure pattern indicative of the microsleep event.