

Systems and Methods for Automatic Device Detection

RELATED APPLICATIONS

[0001] This application claims the benefit of the filing date of U.S. provisional patent application No. 62/315,834, filed on March 31, 2016, entitled “Systems and Methods for Automatic Device Detection,” the entire contents of which are incorporated by reference herein.

BACKGROUND

[0002] The invention relates to computer security, and in particular to systems and methods for automatic device discovery and remote device management.

[0003] Malicious software, also known as malware, affects a great number of computer systems worldwide. In its many forms such as computer viruses, exploits, and spyware, malware presents a serious risk to millions of computer users, making them vulnerable to loss of data and sensitive information, to identity theft, and to loss of productivity, among others.

[0004] A great variety of devices, informally referred to as the Internet of Things (IoT), are increasingly being connected to communication networks and the Internet. Such devices include, among others, smartphones, smartwatches, TVs and other multimedia devices, game consoles, home appliances, and various sensors/actuators such as thermostats and intelligent lighting systems. As more such devices go online, they become targets for malicious software and hacking. Therefore, there is an increasing need to secure such devices against malware, as well as to protect communications to and from such devices.

[0005] In addition, the proliferation of intelligent devices in environments such as homes and offices creates an increasing problem of device and network management. When each device uses a distinct configuration interface and requires separate connection settings, managing a large number of such devices may become a burden, especially for a typical home user who is not experienced in network administration. Therefore, there is an increasing interest in developing systems and methods for automatic device discovery and configuration, with particular emphasis on security.

SUMMARY

[0006] According to one aspect, a device detection appliance comprises a hardware processor and a memory. The hardware processor is configured to analyze data received from a client device connected to the device detection appliance by a local network, to determine a set of features of the client device, and in response, to select a category of devices according to the set of features. The hardware processor is further configured to determine a first score according to a first subset of the set of features, the first score indicative of a first degree to which the client device is representative of the category of devices. The hardware processor is further configured to determine a second score according to a second subset of the set of features, the second score indicative of a second degree to which the client device is representative of the category of devices. The hardware processor is further configured to combine the first and second scores to produce an aggregate score, and in response to producing the aggregate score, to determine whether to assign the client device to the category of devices according to the aggregate score.

[0007] According to another aspect, a method comprises employing at least one hardware processor of a device detection appliance to analyze data received from a client device connected to the device detection appliance by a local network, to determine a set of features of the client device, and in response, employing the at least one hardware processor to select a category of devices according to the set of features. The method further comprises employing the at least one hardware processor to determine a first score according to a first subset of the set of features, the first score indicative of a first degree to which the client device is representative of the category of devices. The method further comprises employing the at least one hardware processor to determine a second score according to a second subset of the set of features, the second score indicative of a second degree to which the client device is representative of the category of devices. The method further comprises employing the at least one hardware processor to combine the first and second scores to produce an aggregate score, and in response to producing the aggregate score, employing the at least one hardware processor to determine whether to assign the client device to the category of devices according to the aggregate score.

[0008] According to another aspect, a non-transitory computer-readable medium stores instructions which, when executed by at least a hardware processor of a device detection appliance, cause the device detection appliance to analyze data received from a client device connected to the device detection appliance by a local network, to determine a set of features of the client device, and in response, to select a category of devices according to the set of features. The instructions further cause the hardware processor to determine a first score according to a first subset of the set of features, the first score indicative of a first degree to which the client device is representative of the category of devices. The instructions further cause the hardware processor to determine a second score according to a second subset of the set of features, the second score indicative of a second degree to which the client device is representative of the category of devices. The instructions further cause the hardware processor to combine the first and second scores to produce an aggregate score, and in response to producing the aggregate score, to determine whether to assign the client device to the category of devices according to the aggregate score.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The foregoing aspects and advantages of the present invention will become better understood upon reading the following detailed description and upon reference to the drawings where:

[0010] Fig. 1-A shows an exemplary configuration of client systems interconnected by a local network, and a device detection appliance according to some embodiments of the present invention.

[0011] Fig. 1-B shows alternative configuration of client systems and device detection appliance according to some embodiments of the present invention.

[0012] Fig. 2 shows a set of remote servers collaborating with the device detection appliance according to some embodiments of the present invention.

[0013] Fig. 3 shows an exemplary hardware configuration of a client system according to some embodiments of the present invention.

[0014] Fig. 4 shows an exemplary hardware configuration of a device detection appliance according to some embodiments of the present invention.

5 [0015] Fig. 5 shows an exemplary hardware configuration of a configuration server according to some embodiments of the present invention.

[0016] Fig. 6 shows a set of exemplary software components executing on a client system according to some embodiments of the present invention.

10 [0017] Fig. 7 shows an exemplary set of software components executing on the device detection appliance according to some embodiments of the present invention.

[0018] Fig. 8 shows exemplary software executing on a configuration server according to some embodiments of the present invention.

[0019] Fig. 9 illustrates exemplary components of a categorization engine according to some embodiments of the present invention.

15 [0020] Fig. 10 illustrates an exemplary sequence of steps performed by the categorization engine according to some embodiments of the present invention.

[0021] Fig. 11 shows an exemplary data exchange between the device detection appliance and configuration server, performed during a device discovery/detection procedure according to some embodiments of the present invention.

20 [0022] Fig. 12 illustrates an exemplary sequence of steps performed by the device detection appliance during an agent provisioning procedure, according to some embodiments of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0023] In the following description, it is understood that all recited connections between structures can be direct operative connections or indirect operative connections through intermediary structures. A set of elements includes one or more elements. Any recitation of an element is understood to refer to at least one element. A plurality of elements includes at least two elements. Unless otherwise specified, any use of “OR” refers to a non-exclusive or. Unless otherwise required, any described method steps need not be necessarily performed in a particular illustrated order. A first element (e.g. data) derived from a second element encompasses a first element equal to the second element, as well as a first element generated by processing the second element and optionally other data. Making a determination or decision according to a parameter encompasses making the determination or decision according to the parameter and optionally according to other data. Unless otherwise specified, an indicator of some quantity/data may be the quantity/data itself, or an indicator different from the quantity/data itself. Computer security encompasses protecting users and equipment against unintended or unauthorized access to data and/or hardware, against unintended or unauthorized modification of data and/or hardware, and against destruction of data and/or hardware. A computer program is a sequence of processor instructions carrying out a task. Computer programs described in some embodiments of the present invention may be stand-alone software entities or sub-entities (e.g., subroutines, libraries) of other computer programs. Two devices are said to be connected to or to belong to the same local network when their network addresses belong to the same subnet and/or when both have the same broadcast address. A local network is a network that has its communication hardware locally managed. A tunnel is a virtual point-to-point connection between two entities connected to a communication network. Computer readable media encompass non-transitory media such as magnetic, optic, and semiconductor storage media (e.g. hard drives, optical disks, flash memory, DRAM), as well as communication links such as conductive cables and fiber optic links. According to some embodiments, the present invention provides, *inter alia*, computer systems comprising hardware (e.g. one or more microprocessors) programmed to perform the methods described herein, as well as computer-readable media encoding instructions to perform the methods described herein.

[0024] The following description illustrates embodiments of the invention by way of example and not necessarily by way of limitation.

[0025] Figs. **1-A-B** show exemplary network configurations **10a-b** according to some embodiments of the present invention, wherein a plurality of client systems **12a-f** are interconnected by a local network **14**, and further connected to an extended network **16**, such as the Internet. Client systems **12a-f** may represent any electronic device having a processor, a memory, and a communication interface. Exemplary client systems **12a-f** include personal computers, laptops, tablet computers, mobile telecommunication devices (e.g., smartphones), media players, TVs, game consoles, home appliances (e.g., refrigerators, thermostats, intelligent heating and/or lighting systems), and wearable devices (e.g., smartwatches, sports and fitness equipment), among others. Local network **14** may comprise a local area network (LAN). Exemplary local networks **14** may include a home network and a corporate network, among others.

[0026] Router **19** comprises an electronic device enabling communication between client systems **12a-f** and/or access of client systems **12a-f** to extended network **16**. In some embodiments, router **19** acts as a gateway between local network **14** and extended network **16**, and provides a set of network services to client systems **12a-f**. The term gateway is used herein to denote a device configured so that at least a part of the communication traffic between client systems **12a-f** and extended network **16** traverses the gateway device. Unless otherwise specified, the term network services is used herein to denote services enabling the inter-communication of client systems **12a-f**, as well as communication between client systems **12a-f** and other entities. Such services may include, for instance, distributing network configuration parameters (e.g., network addresses) to clients systems **12a-f**, and routing communication between participating endpoints. Exemplary network services may include a dynamic host configuration protocol (DHCP). DHCP services are typically used for delivering internet protocol (IP) configuration information to clients requesting access to local network **14** and/or extended network **16**.

[0027] Figs. 1-A-B further show a device detection appliance **18** connected to local network **14**. In some embodiments, device detection appliance **18** comprises an electronic device (e.g., computer system) configured to perform various services for client systems **12a-f**. Such services include, among others, computer security services (e.g., anti-malware, intrusion detection, anti-spyware, etc.), device management (e.g., remote configuration of client systems **12a-f**), parental control services, secure communication services (e.g., virtual private networking – VPN), and remote technical assistance (e.g., device and/or network troubleshooting).

[0028] In some embodiments, device detection appliance **18** is further configured to carry out automatic device discovery/detection operations. The terms ‘device discovery’ and ‘device detection’ are herein interchangeable. Device detection comprises determining a device type of a device connected to local network **14**, for instance, of any of client systems **12a-f**, router **19**. Stated differently, device detection comprises automatically assigning the respective device to a device category according to available information about the respective device. In some embodiments, a device category comprises a tuple of device characteristics $\{C_1, C_2, \dots, C_n\}$ which may include, for instance, a product category (e.g., personal computer, tablet computer, printer, smartwatch, home entertainment system, thermostat, etc.), a manufacturer (e.g., Samsung®, Nest®, Sonos® etc.), a hardware model (e.g., iPad® 2, MacBook® Air®, Galaxy® S6, etc.), and a version of software (e.g., Windows®, iOS® 8, Android® Marshmallow etc.). Some embodiments allow characteristic values of type ‘unknown’ and/or ‘not applicable’, as in $\{\text{‘tablet computer’}, \text{‘unknown’}, \text{‘Android’}\}$. Device detection activities may be carried out at appliance **18**, configuration server **52**, or may be divided between appliance **18** and configuration server **52**. Methods described herein may also be executed by one of client systems **12a-f**.

[0029] In a typical scenario according to some embodiments of the present invention, device detection appliance **18** is introduced to a local network already configured and managed by router **19**. Appliance **18** may then progressively discover devices connected to the local network, for instance client systems **12a-f** and/or router **19**. In some embodiments, appliance **18** further takes over network services such as DHCP from router **19** and reconfigures network **14** to place appliance **18** in a gateway position between local network **14** and extended network **16**, so that at

least a part of the traffic between client systems **12a-f** and extended network **16** traverses device detection appliance **18** (see e.g., Fig. **1-A**). Placing appliance **18** in a gateway position may be preferable for security reasons, since such a position facilitates interception and analysis of traffic between a client systems and a remote party.

5 **[0030]** In some embodiments such as the example in Fig. **1-B**, router **19** may continue to operate as a gateway to local network **14** after installation of appliance **18**, but in such cases device detection appliance **18** is preferably placed between client systems **12a-f** and the existing gateway (i.e., router **19**), so that appliance **18** belongs to the same local network as client systems **12a-f**. Such a position is preferred because it facilitates the delivery of device-specific
10 utility agents to some of client systems **12a-f**.

[0031] In some embodiments, client systems **12a-f** are monitored, managed, and/or configured remotely by a user/administrator, using software executing on an administration device **20** connected to extended network **16** (e.g., the Internet). Exemplary administration devices **20** include smartphones and personal computer systems, among others. Device **20** may expose a
15 graphical user interface (GUI) allowing a user to remotely configure and/or manage operation of client systems **12a-f**, for instance to set configuration options and/or to receive notifications about events occurring on the respective client systems.

[0032] In some embodiments, device detection appliance **18** collaborates with a set of remote computer systems in order to perform various services for client systems **12a-f**. Exemplary
20 remote computer systems include a security server **50** and a configuration server **52**, illustrated in Fig. **2**. Servers **50** and **52** may comprise individual machines, or clusters of multiple interconnected computer systems. In some embodiments, device detection appliance **18** is configured to redirect some or all of the traffic coming to and/or from client systems **12a-f** to security server **50**. In such configurations, security server **50** may perform threat detection
25 operations (e.g., malware detection, blocking access to malicious or fraudulent websites, intrusion prevention, etc.), to protect client systems **12a-f** against computer security threats. Security server **50** may be further connected to an event database **55** comprising a plurality of

security records. In one example, each such security record includes data indicative of a security event occurring on a protected client system, as well as an indicator of an association between the respective event and the respective client system.

[0033] In some embodiments, configuration server **52** collaborates with appliance **18** and/or administration device **20** to configure device management and/or security settings of appliance **18**, router **19**, and/or of a client system **12a-f**. Server **52** may be communicatively connected to a subscriber database **54** and to a device feature database **56**. Subscriber database **54** may store a plurality of subscription records, each subscription record indicative of a set of client systems under device management according to some embodiments of the present invention. In one embodiment, each subscription record is uniquely associated with a distinct device detection appliance **18**. In such embodiments, all client systems configured and/or otherwise serviced by the respective device detection appliance (e.g., client systems **12a-f** connected to local network **14** in Fig. **1-A**) are associated with the same subscription record. Each subscription record may include an indicator of a subscription period and/or a set of subscription parameters describing, for instance, a desired level of security or a selection of services subscribed for. Subscriptions may be managed according to a service-level agreement (SLA).

[0034] In some embodiments, device feature database **56** comprises a set of records indicating configurable features of each client system and/or current configuration settings for each client system. Database **56** may further comprise an extensive device feature knowledgebase comprising a plurality of records. In one exemplary embodiment, each record represents a device, and may comprise a plurality of fields indicating, among others, a product category of the device (e.g., router, smartphone, etc.), a hardware model, a manufacturer, an operating system (e.g., Windows®, Linux®). Other fields may correspond to various device features such as whether the respective device uses a particular network protocol to communicate (e.g., HTTP, Bonjour®), an indicator of a layout of a login interface exposed by the respective device type, user agents used by the respective device, etc.

[0035] Figs. 3-4-5 show exemplary hardware configurations of a client system **12**, device detection appliance **18**, and configuration server **52**, respectively. Client system **12** may represent, for instance, any of client systems **12a-f** of Fig. 1. Without loss of generality, the illustrated configurations correspond to computer systems. The hardware configuration of other client systems (e.g., tablet computers, smart watches) may differ from the one illustrated in Fig. 3. Each of processors **22**, **122**, and **222** comprises a physical device (e.g. microprocessor, multi-core integrated circuit formed on a semiconductor substrate) configured to execute computational and/or logical operations with a set of signals and/or data. Memory units **24**, **124**, and **224** comprise volatile computer-readable media (e.g. RAM) storing data/signals accessed or generated by processors **22**, **122**, and **222**, respectively, in the course of carrying out operations.

[0036] Input devices **26** may include computer keyboards, mice, and microphones, among others, including the respective hardware interfaces and/or adapters allowing a user to introduce data and/or instructions into the respective system. Output devices **28** may include display devices such as monitors and speakers among others, as well as hardware interfaces/adapters such as graphic cards, allowing the respective system to communicate data to a user. In some embodiments, input and output devices share a common piece of hardware (e.g., touch-screen). Storage devices **32**, **132**, and **232**, include computer-readable media enabling the non-volatile storage, reading, and writing of software instructions and/or data. Exemplary storage devices include magnetic and optical disks and flash memory devices, as well as removable media such as CD and/or DVD disks and drives.

[0037] Network adapters **34**, **134**, and **234** enable client system **12**, device detection appliance **18**, and configuration server **52**, respectively, to connect to an electronic communication network such as networks **14**, **16**, and/or to other devices/computer systems.

[0038] Controller hubs **30**, **130**, and **230**, generically represent the plurality of system, peripheral, and/or chipset buses, and/or all other circuitry enabling the communication between the processor of each respective system and the rest of the hardware components. In an exemplary client system **12** (Fig. 3), hub **30** may comprise a memory controller, an input/output

(I/O) controller, and an interrupt controller. Depending on hardware manufacturer, some such controllers may be incorporated into a single integrated circuit, and/or may be integrated with the processor.

[0039] Fig. 6 shows exemplary software components executing on client system **12** according to some embodiments of the present invention. Such software may include an operating system (OS) **40** providing an interface between the hardware of client system **12** and a set of software applications executing on the respective client system. Examples of operating systems include Microsoft® Windows®, MacOS®, iOS®, and Android, among others. Software applications may include word processing, graphics, games, browser, and communication applications, among others. In some embodiments, software applications executing on client system **12** include a utility agent **41** configured to provide various services to the respective client system, such as device management and/or security services (e.g., anti-malware). In one example, utility agent **41** is configured to access and/or modify a set of configuration options of client system **12** (e.g., network configuration parameters, power management parameters, security parameters, device-specific parameters such as a desired temperature in the case of a remotely controlled thermostat, or a selection of lights in the case of a remotely controlled home lighting manager, etc.). In some embodiments, the installation of agent **41** on client system **12** is initiated and/or facilitated by device detection appliance **18**.

[0040] Fig. 7 shows a set of software components executing on device detection appliance **18** according to some embodiments of the present invention. Such components may include, among others, a device detection module **42** and a DHCP module **43** providing DHCP services for local network **14**. Such services may include delivering IP configuration information to clients requesting access to local network **14** and/or to extended network **16**. Device detection module **42** may include a categorization engine **45**, and may be configured to collaborate with configuration server **52** to automatically determine a device type of client system **12**, as shown in detail below. In some embodiments, appliance **18** further executes a network disruption module **44** configured to perform a network service takeover from router **19**. In a particular example, in response to determining a device category of router **19**, appliance **18** may use

disruption module **44** to shut down or otherwise incapacitate the DHCP server of router **19**, in order to take over network services from router **19**. In one such example, device detection appliance **18** may transmit a sequence of instructions to router **19**, the sequence of instructions crafted to cause a crash or a shutdown of router's DHCP server. In another example, appliance **18** may cause router **19** to expose a configuration interface, and may transmit a set of configuration parameter values to the respective interface, thus causing the router's DHCP server to shut down. The set of instructions and/or configuration parameter values may be selectively chosen according to the detected category of router **19**.

[0041] Fig. **8** shows exemplary software executing on configuration server **52** according to some embodiments of the present invention. Such software may include a server-side categorization engine **145** and a database interrogator **47**. Engine **145** may complement device discovery/detection activities of engine **45** executing on device detection appliance **18**. Database interrogator **47** may be configured to selectively retrieve data from device feature database **56** at the request of categorization engine(s) **45** and/or **145**.

[0042] Fig. **9** shows an exemplary configuration of categorization engine **45** according to some embodiments of the present invention. Engine **145** executing on server **52** may have a similar configuration. Engine **45** receives as input a set of category-indicative data **60** of a client system, and outputs a category indicator **72** indicative of a device type of the respective client system (e.g., mobile telephone running iOS® version 9.2). Category-indicative data **60** comprises various kinds of data usable to determine the device type of a client system, i.e., to assign the device to a category of devices. Such data may be Boolean (e.g., indicating whether the respective device has a particular feature or not), numeric (e.g., as in a network address), of type string (e.g., as in host names and user agent fields), etc. Some exemplary data **60** include:

- a) Hardware ID indicators, such as a Media Access Control (MAC) address and/or an International Mobile Equipment Identity (IMEI) number of the respective client system. The MAC address is 48 bits in length, and is typically indicative of a manufacturer of the respective device. For instance, the first 24 bits of the MAC

address of all Nest® devices are 18:B4:30. Combining the MAC address with knowledge of what types of devices the respective manufacturer produces (in the case of Nest®, IP cameras, thermostats and smoke detectors) may allow an efficient identification of a device type of the respective client system.

5 b) Supported communication protocols. Some devices advertise specific network services, such as Bonjour®, etc. Some such services are more frequently associated with a device type, manufacturer, etc. For instance, Bonjour® is predominantly encountered on Apple® devices.

10 c) DHCP parameters such as a vendor name, a fingerprint, and a hostname of the respective client system. The DHCP fingerprint is an array of option values that are specific for some DHCP clients. For example, '1,3,6' is common for devices from the Internet of Things (IoT) category. The DHCP vendor name comprises an identifier of the client system's particular DHCP implementation. For instance, 'MSFT' is a common vendor name for the Windows DHCP client. The hostname can
15 be manually set by a user, but it often comprises a default name set by the manufacturer. Certain patterns of these default hostnames may identify the respective client system as belonging to a particular category of devices. For instance, default hostnames starting with the 'NP-' prefix are common to Roku® media players.

20 d) User agent indicators extracted from a header of a HTTP request. User agent indicators include a set of identifiers for the model, operating system or the browser/application that issued the respective request. For instance, a common pattern for browsers is "Mozilla/[version] ([system and browser information]) [platform] ([platform details])".

25 e) Multicast Domain Name System (mDNS) service indicators. mDNS is a zero-configuration service that resolves hostnames to IP addresses in the absence of a conventional domain name server. Several devices use mDNS to advertise a set of services and ports. Additional category-indicative information may be obtained from

the TEXT field. mDNS services are popular among Apple devices, printers, or network attached storages. For example, most printers advertise the service ‘printer’ over mDNS.

- 5 f) Simple Network Management Protocol (SNMP) parameters. SNMP is a network protocol for exchanging management information among connected devices. A device with a SNMP server broadcasts and OID(Object Identifier), an example of which is reproduced below:

10 Iso(1). org(3). dod(6). internet(1). private(4). transition(868). products(2). chassis(4). card(1). slotCps(2). -cpsSlotSummary(1). cpsModuleTable(1). cpsModuleEntry(1). cpsModuleModel(3). 3562. 3

The content of various fields can be approximately mapped to certain device types and models.

[0043] Some embodiments process data **60** to extract a set of device features of the device, wherein each feature comprises a set of an attribute-value pair of the respective device. Exemplary features include a DHCP feature, a MAC feature, and a user agent feature, among others. A device feature may be determined according to multiple data items (e.g., by combining multiple attribute values, as in “attribute: value1 OR value2 AND NOT value3” etc.).

20 [0044] In some embodiments, categorization engine **45** (Fig. **9**) comprises a data dispatcher **62**, a plurality of data parsers **64a-c**, and a score aggregator **70** coupled to data parsers **64a-c**. Each parser **64a-c** may determine a set of verdicts according to a set of category-indicative data **60**, or according to a set of features of a client device. Each verdict indicates a possible device category of client system **12**. Exemplary verdicts include “client system **12** is a router from Apple®”, “client system **12** is an Android device”, and “client system **12** is a tablet computer from an unknown manufacturer, running Windows Mobile® 6.5”.

25 [0045] Each parser **64a-c** may further determine a score accompanying each verdict. In some embodiments, the score indicates a degree to which client system **12** is representative of the

respective category. For instance, a score may quantify how representative client system **12** is of a smartwatch, or of an Apple® device, or of a device running Android®. Higher scores may indicate higher representativeness of the respective category (for instance, that the device is a typical member of the category). The degree of representativeness of a category may include, among others, a degree of membership of client system **12** in the respective category, a likelihood or confidence level that client system **12** belongs to the respective category, and a measure of similarity between client system **12** and the respective category. Scores may be Boolean (1/0, YES/NO) or vary continuously within a set of bounds. In one example, each score is scaled to a number between 0 and 100.

[0046] In some embodiments, each parser **64a-c** is configured to receive as input a distinct subset of category-indicative data, or a distinct subset of device features. For instance, parser **64a** may process DHCP data/features, parser **64b** may parse user agent text strings extracted from HTTP requests, etc. In another example, parser **64a** processes a first field of a user agent data type, parser **64b** processes a second field of the user agent, etc. Distinct subsets of features are not necessarily mutually-exclusive; some distinct subsets of features may have a partial overlap. Data dispatcher **62** may be configured to selectively send each type of category-indicative data to parsers **64a-c** that use the respective data type/feature as input. In an alternative embodiment, distinct parsers **64a-c** may process the same subset of features, but may employ distinct algorithms to produce parser-specific verdicts and/or score values. In one such example, one parser processes mDNS data according to a set of heuristics, and another parser processes mDNS data using a neural network.

[0047] When device categories comprise multiple characteristics $\{C_1, C_2, \dots, C_n\}$ wherein $n > 1$, some parsers output an array of verdict/score pairs, each member of the array representing a distinct combination of characteristics. In one such example wherein category characteristics comprise {category, OS}, wherein the ‘category’ field can take the values {phone, PC}, and wherein the ‘OS’ field can take the values {Windows, Android, iOS}, scores may be visualized as a 2-dimensional matrix:

$$\begin{bmatrix} \sigma_{phone,Windows}^{(i)} & \sigma_{phone,Android}^{(i)} & \sigma_{phone,iOS}^{(i)} \\ \sigma_{PC,Windows}^{(i)} & \sigma_{PC,Android}^{(i)} & \sigma_{PC,iOS}^{(i)} \end{bmatrix}, \quad [1]$$

wherein $\sigma_{phone,Windows}^{(i)}$ denotes a score indicating how representative client system **12** is of a smartphone running Windows®, while i indexes parsers. In general, such arrays are sparse, since not all possible combinations of device characteristics occur in practice. For instance, no
5 Android printers are currently on the market, so a verdict of {printer, Android} may not exist or may be so rare that its use may not be justified.

[0048] Some embodiments derive knowledge from a vast corpus of records representing devices of various kinds (smartphones, thermostats, laptops, routers, printers, etc.). Device feature data may be acquired from technical documentation and/or from testing, and may be obtained
10 automatically or by human operators. Device feature data may be stored in device feature database **56**. Corpus records may be grouped into categories according to various criteria. Such grouping may be done by human operators, or may be achieved automatically using techniques such as supervised or unsupervised learning.

[0049] Each parser **64a-c** may implement a distinct algorithm for determining verdicts and
15 scores. Some embodiments represent each corpus device as a point in multidimensional feature space. Such representations may allow a reverse lookup, i.e. an identification of a device category according to a set of feature values. A particular set of device feature values may match multiple categories. Some embodiments of parsers **64a-c** employ automated classifiers such as neural networks capable of returning a set of verdicts and/or scores given a set of device features.
20 Other parsers may use fuzzy logic techniques such as membership functions to determine verdicts and scores of client system **12**. Yet other parsers may rely on statistical methods. In some embodiments, scores may be determined empirically, for instance according to a set of heuristics. Parsers configured to process text strings (e.g., user agent indicators) may use pattern matching against a collection of category-identifying signatures.

[0050] An exemplary parser configured to process DHCP data may operate as follows. In a first phase of detection, the parser attempts to match both the dhcp fingerprint and dhcp vendor of client system **12** against the corpus of devices. If the match is successful, the respective verdict(s) are passed to score aggregator **70** with a maximum score (e.g., 100). In case there is no exact match for both fields, an attempt is made to match only the dhcp fingerprint. To prevent promoting incorrect verdicts, the score of each verdict derived by matching the DHCP fingerprint is chosen according to a measure of similarity (e.g., an inter-string distance such as Levenshtein) between the DHCP vendor of the respective verdict and the DHCP vendor of client system **12**.

[0051] In some embodiments, score aggregator **70** centralizes, compares and/or combines verdicts **68a-c** produced by individual parsers **64a-c** to output a decisive verdict for the respective client system. The decisive verdict definitively assigns client device **12** to a device category. To combine individual verdicts, score aggregator **70** may use any method known in the art. In one exemplary embodiment, a decisive verdict is chosen as the verdict having the highest score across multiple data types and/or parsers:

$$V = \operatorname{argmax}_{v \in \Omega} \left(\max_{i \in S} \sigma_v^{(i)} \right), \quad [2]$$

wherein $\sigma_v^{(i)}$ denotes a score associated with verdict v , determined according to data type or feature i , wherein S denotes the set of all data types/features, and wherein Ω denotes the set of all verdicts (category indicators). In an alternative embodiment, $\sigma_v^{(i)}$ denotes a score determined by parser i for verdict v .

[0052] One problem encountered in practice when using formula [2] is that quite often multiple individual verdicts v come with an identical score $\sigma_v^{(i)}$, so there may be no unambiguous decisive verdict. Examples of such situations are given further below.

[0053] An alternative embodiment determines a decisive verdict according to an aggregate score computed for each verdict v as a combination of individual scores $\sigma_v^{(i)}$ obtained according to

distinct data types/features, according to distinct algorithms, and/or computed by distinct parsers
64a-c. In one such example, an aggregate score is computed according to a weighted sum of individual scores:

$$\sigma_v^{(A)} = \sum_{i \in S} \sigma_v^{(i)} \cdot w^{(i)}, \quad \text{and hence} \quad V = \operatorname{argmax}_{v \in \Omega} \left(\sigma_v^{(A)} \right) \quad [3]$$

wherein $\sigma_v^{(A)}$ denotes the aggregate score computed for verdict v , and wherein $w^{(i)}$ denotes a numerical weight associated with data type/feature i and/or with the parser that produced score $\sigma_v^{(i)}$. When all weights $w^{(i)}$ are equal, formula [3] amounts to computing the aggregate score as a mean of the set of individual scores.

[0054] In some embodiments, weight $w^{(i)}$ represents an indicator of a reliability of the respective parser and/or data type in producing a correct category assignment. Some data types (e.g., user agent data, hostname) may be rather non-specific or may lead to false verdicts with relatively high scores. To avoid such situations, the respective data types and/or parsers utilizing the respective data types may receive a lower weight $w^{(i)}$ than other, more reliable data/types or parsers. In some embodiments, the weight $w^{(i)}$ may further vary according to the verdict: $w^{(i)} = w^{(i,v)}$, wherein $w^{(i,v)}$ denotes a relevance of data source and/or parser i to the respective verdict v . Some data types may be more relevant to some verdicts than others. For instance, mDNS data may be more relevant for the detection of printers than hostname data. Although such reliability/relevance information may already be incorporated to some extent into scores, some embodiments use verdict and/or parser-specific weights as an artifice to break a score tie and thus produce an unambiguous category assignment.

[0055] In one example of verdict- and/or parser-specific weights, Ecobee, Inc. (MAC prefix 44:61:32) and Sonos, Inc. (MAC prefix b8:e9:37) produce very few devices, which may therefore be identified unambiguously using the MAC address. The MAC parser/data type may therefore receive a relatively high weight in score aggregation for Ecobee and/or Sonos verdicts. In another example, for Nest® devices, an empty hostname typically indicates an IP camera. Some embodiments may thus associate relatively high weights with Nest verdicts and hostname

parsers. In yet another example, an Apple® device whose mDNS data show a network service of type “airport.tcp” is very likely to be a router. Therefore, higher weights may be associated with mDNS parsers and Apple® verdicts. Similarly, an Amazon® device having the DHCP fingerprint “1,3,6,12,15,28,42” is very likely a Kindle® e-book reader. Some embodiments may therefore employ a relatively weight when aggregating scores for Amazon verdicts and DHCP parsers.

[0056] Weights $w^{(i)}, w^{(i,v)}$ may be determined according to trial and error, or using a machine learning algorithm. They may be repeatedly tweaked in order to optimize device detection in a continuously evolving Internet of Things. The weights may be further scaled to normalize the aggregate score, i.e., to keep score $\sigma_v^{(A)}$ within desired bounds.

[0057] In some embodiments, determining the aggregate score comprises modulating individual scores $\sigma_v^{(i)}$ according to an absolute or relative size of the respective scores. For instance,

$$\sigma_v^{(A)} = \sum_{i \in S} w^{(i)} \cdot M(\sigma_v^{(i)}), \quad [4]$$

wherein $M(.)$ denotes a modulation function. One exemplary embodiment using a variation of formula [4] computes the aggregate score according to the largest and smallest of the individual scores:

$$\sigma_v^{(A)} = w_1 \max_{i \in S} \sigma_v^{(i)} + w_2 \min_{i \in S} \sigma_v^{(i)}. \quad [5]$$

In another exemplary calculation, the largest and smallest individual scores are discarded, and the aggregate score is computed as the average of the remaining scores. Another exemplary embodiment may determine the aggregate score as the median of the set of individual scores. In yet another example, M is an injective function (e.g., ever-increasing). Variations such as illustrated in formulae [4] and [5] address the issue of ambiguous category assignment: after applying formula [1] or [2], there may be multiple candidate verdicts with substantially similar aggregate scores. In practice, this means that categorization engines **45**, **145** cannot decide on a unique category for the respective device. Some embodiments therefore resort to score

modulation to break the tie. Some M functions, for instance, additionally promote reliable parsers in an effort to break an aggregate score tie.

[0058] In other exemplary calculation of the aggregate score, some individual scores $\sigma_v^{(i)}$ may be modulated by a weight $w^{(i)}$ determined according to the verdict v associated with the respective score. In one embodiment, non-specific verdicts such as ‘unknown device’ may be suppressed in this way by being assigned relatively small weights during aggregation and decision making.

[0059] In some embodiments as illustrated in Fig. 9, parsers **64a-c** and/or score aggregator **70** may receive a set of parse parameter values **66** and/or a set of aggregation parameter values **67**, respectively, as input for calculating individual scores $\sigma_v^{(i)}$ and/or aggregate score $\sigma_v^{(A)}$. In an embodiment wherein a parser comprises a neural network, parse parameter values **66** may include, for instance, a set of neural network weights of a the respective parser. Aggregation parameter values may include weights $w^{(i)}$, among others. In an exemplary embodiment, parameter values **66** and/or **67** are stored in and selectively retrieved from device feature database **56**. By maintaining such parameter values independently of the parser and score aggregation software, some embodiments facilitate optimization and/or upgrade of engines **45**, **145**.

[0060] Fig. 10 shows an exemplary sequence of steps performed by categorization engine **45** according to some embodiments of the present invention. Device detection may proceed iteratively, since not all category-indicative data **60** may be available at once. Some data types may be relatively easy to acquire, while others may necessitate relatively lengthy procedures, such as handshake message exchanges, negotiations on network configuration parameters, authentication, etc. Therefore, in some embodiments parsers **64a-c** operate independently of each other, each parser responsive to a receipt of category-indicative data/features of the appropriate kind.

[0061] Once introduced to local network **14**, in a sequence of steps **400-401**, some embodiments of device detection appliance **18** may begin to harvest category-indicative data **60** from client systems **12a-f** and/or router **19**. Harvesting data **60** may depend on a type of the respective data. For instance, device detection appliance **18** may extract a user agent indicator from a HTTP request received from a client system. Some devices broadcast an offer of network services; by intercepting such messages, appliance **18** may determine what kind of services and/or protocols the respective devices support. Appliance **18** may further use a service discovery tool such as Network Mapper (NMap). To harvest data about network protocols and services such as Bonjour® and SNMP, some embodiments of appliance **18** send a probe out to a particular port of a client system and listen for a response. When data **60** is available, data dispatcher **42** may identify a data type of the respective data and selectively forward data **60** to the parser(s) that use the respective data type as input (steps **402-404**). In a step **406**, the respective parser(s) determine a set of candidate verdicts and associated scores. In a sequence of steps **408-410**, score aggregator **70** determines a set of aggregate scores and selects a decisive verdict. The decisive verdict may then constitute the output of engine **45**. In some embodiments, the category assignment of client system **12** as indicated by the decisive verdict may change in time. As more category-indicative data **60** becomes available, other parsers may start providing candidate verdicts and scores, which aggregator **70** may then combine with previously-computed individual or aggregate scores.

[0062] In an alternative embodiment as illustrated in Fig. **11**, at least a part of a device detection procedure is carried out at configuration server **52**. Category-indicative data **60** harvested by device detection appliance **18** may be transmitted to configuration server **52**, which identifies the device type according to the received data and further according to information stored in device feature database **56**. Such device detection may be iterative: server **52** may perform a preliminary determination of a device type according to the currently available data about the respective client system. In response to the preliminary determination, server **52** may request further device-type-indicative data about the respective client from device detection appliance **18**. More category-indicative data is sent to configuration server **52**, until a successful category assignment of client system **12** is achieved. Some embodiments divide device detection

tasks between engines **45** and **145**. In one such example, each engine may compute a set of candidate verdicts and/or scores. Scores may then be aggregated either at appliance **18** or server **52**, to produce a decisive verdict.

[0063] Information obtained via device detection/discovery may be used in a variety of ways. A few examples include tailoring a set of network services to each client device, installing device-specific software agents on each device, assessing computer security vulnerabilities of each device, and exposing a device-specific set of configuration options to a user of each client device (remote management).

[0064] An exemplary application of some embodiments of the present invention is device-specific software provisioning. Fig. **12** illustrates an exemplary sequence of steps performed by device detection appliance **18** to deliver a utility agent to client system **12** (see e.g., utility agent **41** in Fig. **6**). In some embodiments, appliance **18** waits for connection requests from local client systems. An exemplary connection request comprises a HTTP request. When client system **12** attempts to access an address on local network **14** or extended network **16**, appliance **18** may intercept the request and in response, may send an indicator of category of client system **12** to configuration server **52**. Server **52** may respond with a notification which may include a location indicator (e.g., path, IP address) of an agent installer selected according to the assigned category of client system **12**. In response to receiving the notification, device detection appliance **18** may redirect the HTTP request to the location of the agent installer. In an alternative embodiment, appliance **18** may obtain the agent installer from server **52**, and then push the installer onto the respective client system.

[0065] In some embodiments, the agent installer is configured to cause system **12** (or administration device **20**) to expose a confirmation interface to a user, requesting the user to agree to install agent **41**. The installer may further request the user to confirm that the user agrees with terms of the respective subscription (e.g. as listed in a SLA). When the user indicates agreement, the installer may install and execute agent **41**. In some embodiments, the agent installer and/or device detection appliance **18** may register the respective client system

with client configuration server **52**, the registration associating the respective client system with a subscription record attached to device detection appliance **18**.

[0066] A broad variety of utility agents may be provisioned using systems and methods described herein. An exemplary utility agent **41** configured to provide security services may perform a security assessment of client system **12** (e.g., a local malware scan) and may send security assessment data to configuration server **52** or security server **50**. The server(s) may then forward a security indicator to administration device **20** for display to the user/administrator. Exemplary security indicators displayed to the user/administrator may include, among others, an indicator of whether a particular software object (e.g., the operating system) executing on client system **12** is up to date, and an indicator of a strength of a password used to protect client system **12**. Other exemplary actions performed by a security agent include updating software and/or security policies for the respective client system. In some embodiments, agent **41** is configured to filter network traffic to/from client system **12** using a network packet inspection algorithm to determine, for instance, whether client system **12** is subject to a malicious attack.

[0067] An exemplary utility agent **41** configured to provide secure communication services includes a virtual private network (VPN) agent. Such agents may protect client system **12** when client system **12** leaves local network **14** (for instance, when the user leaves home with his/her mobile telephone). Such an agent may collaborate with device detection appliance **18** and/or configuration server **52** to open a secure communication tunnel and/or to set up a VPN between the respective client system and security server **50** (more details below).

[0068] An exemplary utility agent **41** configured to provide parental control services may monitor the usage of client system **12**, and report usage patterns to a supervisor user (e.g., parent) via administration device **20**. Agent **41** may further prevent client system **12** from accessing certain remote resources (e.g., IP addresses, websites, etc.), or from using certain locally-installed applications (e.g., games). Such blocking may be enforced permanently, or according to a user specific schedule.

[0069] An exemplary utility agent **41** configured to provide remote technical assistance may automatically configure and/or open a secure communication channel (e.g., an SSH tunnel) between client system **12** and configuration server **52**. Configuration and/or troubleshooting commands may then be transmitted from server **52** to client system **12**, possibly without explicit involvement or assistance from a user of client system **12**.

[0070] Some client systems, such as home appliances, wearable devices, etc., may not be capable of installing a utility agent as indicated above. However, such devices may include built-in configuration and/or device management agents enabling a remote command of the respective devices. Some embodiments of the present invention may use the existing management agents and device-specific protocols and/or communication methods to communicate parameter value updates to such devices. Even for such devices, correctly identifying the device category enables configuration server **52** to properly format and communicate configuration commands to the respective client systems. To facilitate category assignment of such client systems, device detection appliance **18** may either actively parse communications received from the respective client system, or re-route the respective communications to configuration server **52**.

[0071] Some embodiments of the present invention enable an automatic device detection/discovery, particularly applied to ‘Internet of Things’ client devices, such as wearables, mobile communication devices, and smart home appliances, among others. Such client devices are typically configured to connect to a network, for instance to a wireless LAN or a BLUETOOTH® link. Some embodiments of the present invention are specifically crafted for ease of use, and therefore do not necessitate specialized knowledge of computer engineering or network administration.

[0072] In some embodiments, a device detection appliance is connected to the same local network as the detected devices. Exemplary detection/discovery activities include, among others, determining a product category of each client device (e.g., phone, watch, smart TV, printer, router, thermostat, etc.), and determining other device features, such as a make and model of a client device, a type/version of Operating System (OS) used by a client device, a type

of a hardware component installed in a client device, etc. The methods described herein are not limited to the device detection appliance. Device detection may be carried out by client systems **12a-f**, router **19**, and/or a remote server.

[0073] Some embodiments determine category assignment according to a plurality of distinct criteria, for instance according to distinct category-indicative data sources and/or according to distinct features of the respective device. Such embodiments rely on the observation that using a single criterion/algorithm/feature often leads to an ambiguous or even incorrect category assignment. Examples of such situations are given below.

[0074] In one example of category assignment, appliance **18** acquires the following category-indicative data about a client device (Table 1):

Table 1

Type	Info
MAC	90:72:40:XX:XX:XX
DHCP	"dhcp_fingerprint": "1,2,3,15,6,12,44"
mDNS	"service_type": "_airport._tcp"
Hostname	airport-express

[0075] A parser using the MAC address returns the verdict/score pairs illustrated in Table 2. As seen here, MAC-based detection yields ambiguous results, with no clear winner.

Table 2

Verdict	Score
---------	-------

Phone	14.28
Tablet	14.28
Desktop	14.28
Media player	14.28
Router	14.28
Network-attached storage (NAS)	14.28
Watch	14.28

[0076] A second set of verdict/score pairs are calculated by another parser using DHCP data, and aggregated with the verdict/score pairs of Table 2. Results of the aggregation are shown in Table 3. Adding the DHCP fingerprint verdict to the MAC verdict has substantially reduced the ambiguity.

5

Table 3

Verdict	Score
NAS	17.15
Router	17.15
Phone	13.13
Tablet	13.13
Desktop	13.13

Media player	13.13
Watch	13.13

[0077] A third set of verdict/score pairs was computed by another parser based on mDNS data. Aggregation of mDNS verdict scores with the verdict/score pairs in Table 3 yields the result shown in Table 4, which show an unambiguous and correct assignment of client system 12 to the router category.

Table 4

Verdict	Score
Router	31.46
NAS	23.06
Phone	9.09
Tablet	9.09
Desktop	9.09
Media player	9.09
Watch	9.09

[0078] An example of a situation wherein using a single data source/feature produces an incorrect category assignment is shown below. A device provides the category-indicative data shown in Table 5. A conventional device discovery system may conclude according to either ‘user agent’ data or hostname data that the respective client is an Android device. However,

attempting to deploy Android-based software to this client would fail, because the device is actually an Amazon Kindle Fire TV, which uses a custom OS loosely based on Android. The correct category assignment can be achieved by combining user agent, DHCP, mDNS, and MAC data sources.

5 **Table 5**

Type	Info
User agent	"Mozilla/5.0 (Linux; U; Android 4.2.2; en-us; AFTB Build/JDQ39) AppleWebKit/534.30 (KHTML, like Gecko) Version/4.0 Safari/534.30"
DHCP	"dhcp fingerprint": "1,33,3,6,15,28,51,58,59" "dhcp vendor": "dhcpcd-5.5.60"
Hostname	android-3243245
mDNS	"service_type": "_amzn-wplay._tcp" "text": "n=John's Fire TV, at=+ILQu8pW3opq,mv=2, a=0, tr=tcp, c=72:c2:46:6d:b5:0d"
MAC	74:75:48:XX:XX:XX

[0079] In another example, a client system provides the category-indicative data shown in Table 6. Using only the mDNS data, a conventional device discovery system may conclude that this device is a printer, since IPP and IPPS services are mostly used by printers. But the MAC indicates an Apple® device, and Apple® does not currently produce printers. Using hostname data alone cannot guarantee a successful detection either, since hostnames may be arbitrarily

chosen by the user. However, combining MAC, hostname, and user agent data allows offsetting the misleading information provided by the mDNS data, to produce the correct category assignment: personal computer running OS X®.

Table 6

Type	Info
mDNS	"service type": "_ipp. tcp" "service type": "_ipps. tcp" ...
User agent	"Mozilla/5.0 (Macintosh; Intel Mac OS X 10_11_3) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/48.0.2564.97 Safari/537.36"
Hostname	Jamess-MacBook-Pro
MAC	3C:07:54:XX:XX:XX

5

[0080] It will be clear to one skilled in the art that the above embodiments may be altered in many ways without departing from the scope of the invention. Accordingly, the scope of the invention should be determined by the following claims and their legal equivalents.

CLAIMS

What is claimed is:

1. A device detection appliance comprising a hardware processor and a memory, the hardware processor configured to:
analyze data received from a client device connected to the device detection appliance by a local network, to determine a set of features of the client device;
in response, select a category of devices according to the set of features;
determine a first score according to a first subset of the set of features, the first score indicative of a first degree to which the client device is representative of the category of devices;
determine a second score according to a second subset of the set of features, the second score indicative of a second degree to which the client device is representative of the category of devices;
combine the first and second scores to produce an aggregate score; and
in response to producing the aggregate score, determine whether to assign the client device to the category of devices according to the aggregate score.
2. The client system of claim 1, wherein determining whether to assign the client device to the category of devices comprises:
comparing the aggregate score to a third score indicative of a third degree to which the client device is representative of another category of devices, and
in response, determine whether to assign the client device to the category of devices according to a result of the comparison.
3. The client system of claim 1, wherein the aggregate score is determined according to:
$$\sigma \cdot w,$$

wherein σ denotes the first score and w denotes a numerical weight determined according to the first set of features.

4. The client system of claim 3, wherein weight w is determined further according to the device category.

5. The client system of claim 3, wherein weight w is determined further according to the first score.

6. The client system of claim 1, wherein the aggregate score is determined according to:
$$w \cdot f(\sigma),$$

wherein σ denotes the first score, w denotes a numerical weight determined according to the first set of features, and wherein f denotes an injective function.

7. The client system of claim 1, wherein the hardware processor is further configured to:
in response to determining whether to assign the client device to the category of devices, determine a third score according to a third subset of the set of features, the third score indicative of a third degree to which the client device is representative of the category of devices;
in response, combine the aggregate score and the third score to produce an adjusted aggregate score; and
in response to producing the adjusted aggregate score, determine whether to assign the client device to the category of devices according to the adjusted aggregate score.

8. The client system of claim 1, wherein assigning the client device to the device category comprises indicating a product category of the client device and an operating system of the client device.

1 9. The client system of claim 1, wherein the hardware processor is further configured to:
2 assign the client device to the category of devices; and
3 in response, transmit an indicator of a location of an agent installer to the client
4 device, the agent installer selected from a plurality of agent installers
5 according to the category of devices, wherein the agent installer is configured
6 to install a software agent on the client device.

1 10. The client system of claim 1, wherein the hardware processor is further configured to:
2 assign the client device to the category of devices; and
3 in response, identify a computer security vulnerability of the client device according
4 to the category of devices.

1 11. The client system of claim 1, wherein the hardware processor is further configured to:
2 assign the client device to the category of devices;
3 formulate a set of instructions according to the category of devices, wherein
4 executing the instructions causes a disruption of a Dynamic Host
5 Configuration Protocol (DHCP) server executing on the client device; and
6 in response to formulating the set of instructions, transmit the set of instructions to the
7 client device.

1 12. A method comprising employing at least one hardware processor of a device detection
2 appliance to:
3 analyze data received from a client device connected to the device detection appliance by
4 a local network, to determine a set of features of the client device;
5 in response, employing the at least one hardware processor to select a category of devices
6 according to the set of features;
7 employing the at least one hardware processor to determine a first score according to a
8 first subset of the set of features, the first score indicative of a first degree to
9 which the client device is representative of the category of devices;

employing the at least one hardware processor to determine a second score according to a
 second subset of the set of features, the second score indicative of a second degree
 to which the client device is representative of the category of devices;
 employing the at least one hardware processor to combine the first and second scores to
 produce an aggregate score; and
 in response to producing the aggregate score, employing the at least one hardware
 processor to determine whether to assign the client device to the category of
 devices according to the aggregate score.

13. The method of claim 12, wherein determining whether to assign the client device to
 the category of devices comprises:
 employing the at least one hardware processor to compare the aggregate score to a
 third score indicative of a third degree to which the client device is
 representative of another category of devices, and
 in response, employing the at least one hardware processor to determine whether to
 assign the client device to the category of devices according to a result of the
 comparison.

14. The method of claim 12, wherein the aggregate score is determined according to:

$$\sigma \cdot w,$$
 wherein σ denotes the first score and w denotes a numerical weight determined
 according to the first set of features.

15. The method of claim 14, wherein weight w is determined further according to
 the device category.

16. The method of claim 14, wherein weight w is determined further according to
 the first score.

17. The method of claim 12, wherein the aggregate score is determined according to:

$$w \cdot f(\sigma),$$

wherein σ denotes the first score, w denotes a numerical weight determined according to the first set of features, and wherein f denotes an injective function.

18. The method of claim 12, further comprising:

in response to determining whether to assign the client device to the category of devices, employing the at least one hardware processor to determine a third score according to a third subset of the set of features, the third score indicative of a third degree to which the client device is representative of the category of devices;

in response, employing the at least one hardware processor to combine the aggregate score and the third score to produce an adjusted aggregate score; and

in response to producing the adjusted aggregate score, employing the at least one hardware processor to determine whether to assign the client device to the category of devices according to the adjusted aggregate score.

19. The method of claim 12, wherein assigning the client device to the device category comprises indicating a product category of the client device and an operating system of the client device.

20. The method of claim 12, further comprising:

employing the at least one hardware processor to assign the client device to the category of devices; and

in response, employing the at least one hardware processor to transmit an indicator of a location of an agent installer to the client device, the agent installer selected from a plurality of agent installers according to the category of devices, wherein the agent installer is configured to install a software agent on the client device.

9
1 21. The method of claim 12 further comprising:
2 employing the at least one hardware processor to assign the client device to the
3 category of devices; and
4 in response, employing the at least one hardware processor to identify a computer
5 security vulnerability of the client device according to the category of devices.
6

1 22. The method of claim 12, further comprising:
2 employing the at least one hardware processor to assign the client device to the
3 category of devices;
4 employing the at least one hardware processor to formulate a set of instructions
5 according to the category of devices, wherein executing the instructions
6 causes a disruption of a Dynamic Host Configuration Protocol (DHCP) server
7 of the client device; and
8 in response to formulating the set of instructions, employing the at least one hardware
9 processor to transmit the set of instructions to the client device.
10

1 23. A non-transitory computer-readable medium storing instructions which, when executed
2 by at least a hardware processor of a device detection appliance, cause the device
3 detection appliance to:
4 analyze data received from a client device connected to the device detection appliance by
5 a local network, to determine a set of features of the client device;
6 in response, select a category of devices according to the set of features;
7 determine a first score according to a first subset of the set of features, the first score
8 indicative of a first degree to which the client device is representative of the
9 category of devices;
10 determine a second score according to a second subset of the set of features, the second
11 score indicative of a second degree to which the client device is representative of
12 the category of devices;

13 combine the first and second scores to produce an aggregate score; and
14 in response to producing the aggregate score, determine whether to assign the client
15 device to the category of devices according to the aggregate score.
16