

What is claimed is:

1. A method for preventing access to a secure system based on determining a captured image to be of an alternative representation of a live person, the method comprising:
 - illuminating a subject with structured light using a light source array comprising multiple light sources disposed in a predetermined pattern;
 - capturing an image of the subject as illuminated by the structured light;
 - determining that the image includes features representative of the predetermined pattern;
 - responsive to determining that the image includes features representative of the predetermined pattern, identifying the subject in the image to be an alternative representation of a live person; and
 - responsive to identifying the subject in the image to be an alternative representation of a live person, preventing access to the secure system.
2. The method of claim 1, wherein the alternative representation of a live person comprises a photograph of the live person.
3. The method of claim 2, wherein the photograph is printed on paper.
4. The method of claim 2, wherein the photograph is presented on a display device.
5. The method of claim 1, wherein determining that the image includes features representative of the predetermined pattern comprises:
 - computing a frequency domain representation of the image;
 - determining that an amount of energy in a target frequency range is higher than a threshold; and
 - responsive to determining that the amount of energy in the target frequency range higher than the threshold, determining that the image includes features representative of the predetermined pattern.

6. The method of claim 5, wherein the threshold is substantially equal to 60% of energy content of the frequency domain representation of the image.
7. The method of claim 1, wherein the light source array is configured to radiate infrared (IR) illumination.
8. The method of claim 1, wherein determining that the image includes features representative of the predetermined pattern comprises processing the image using a machine learning process trained to discriminate between images of live persons and corresponding alternative representations of the live persons.
9. The method of claim 5, wherein the frequency domain representation comprises a two-dimensional Fast Fourier Transform (2D-FFT) of the image.
10. The method of claim 5, wherein the frequency domain representation comprises a wavelet-based decomposition of the image.
11. The method of claim 1, further comprising:
 - determining that the image does not include features representative of the predetermined pattern;
 - responsive to determining that the image does not include features representative of the predetermined pattern, identifying the subject in the image to be a live person; and
 - responsive to identifying the subject in the image to be a live person, initiating an authentication process for determining if the live person is authorized to access the secure system.
12. The method of claim 1, wherein the secure system comprises a user-interface disposed in a kiosk.
13. The method of claim 12, wherein the light source array is disposed on the kiosk.
14. A secure system comprising:
 - an image acquisition device configured to:

illuminate a subject with structured light using a light source array comprising multiple light sources disposed in a predetermined pattern, and

capture an image of the subject as illuminated by the structured light; and

an image analysis comprising one or more processing devices, the image analysis engine configured to:

determine that the image includes features representative of the predetermined pattern;

responsive to determining that the image includes features representative of the predetermined pattern, identify the subject in the image to be an alternative representation of a live person; and

responsive to identifying the subject in the image to be an alternative representation of a live person, prevent access to the secure system.

15. The system of claim 14, wherein the alternative representation of a live person comprises a photograph of the live person.
16. The system of claim 15, wherein the photograph is printed on paper, or presented on a display device.
17. The system of claim 14, wherein determining that the image includes features representative of the predetermined pattern comprises:
 - computing a frequency domain representation of the image;
 - determining that an amount of energy in a target frequency range is higher than a threshold; and
 - responsive to determining that the amount of energy in the target frequency range higher than the threshold, determining that the image includes features representative of the predetermined pattern.
18. The system of claim 17, wherein the threshold is substantially equal to 60% of energy content of the frequency domain representation of the image.

19. The system of claim 14, wherein the light source array is configured to radiate infrared (IR) illumination.
20. The system of claim 14, wherein determining that the image includes features representative of the predetermined pattern comprises processing the image using a machine learning process trained to discriminate between images of live persons and corresponding alternative representations of the live persons.
21. The system of claim 17, wherein the frequency domain representation comprises a two-dimensional Fast Fourier Transform (2D-FFT) of the image.
22. The system of claim 17, wherein the frequency domain representation comprises a wavelet-based decomposition of the image.
23. The system of claim 14, wherein the image analysis engine is configured to:
 - determine that the image does not include features representative of the predetermined pattern;
 - responsive to determining that the image does not include features representative of the predetermined pattern, identify the subject in the image to be a live person; and
 - responsive to identifying the subject in the image to be a live person, initiate an authentication process for determining if the live person is authorized to access the secure system.
24. The method of claim 1, wherein the secure system comprises a user-interface disposed in a kiosk.
25. One or more machine-readable storage devices encoded with instructions configured to cause one or more processing devices to execute operations comprising:
 - causing a light source array to illuminate a subject with structured light, wherein using the light source array includes multiple light sources disposed in a predetermined pattern;

receiving an image of the subject captured under illumination by the structured light;

determining that the image includes features representative of the predetermined pattern;

responsive to determining that the image includes features representative of the predetermined pattern, identifying the subject in the image to be an alternative representation of a live person; and

responsive to identifying the subject in the image to be an alternative representation of a live person, preventing access to the secure system.