

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 April 2001 (26.04.2001)

PCT

(10) International Publication Number
WO 01/28411 A1

- (51) International Patent Classification⁷: **A61B 3/12**, 3/15, G01J 9/00
- (21) International Application Number: PCT/US00/29008
- (22) International Filing Date: 20 October 2000 (20.10.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/422,338 21 October 1999 (21.10.1999) US
- (71) Applicant (for all designated States except US): **UNIVERSITY OF ROCHESTER** [US/US]; 518 Hylan Building, Rochester, NY 14627 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WILLIAMS, David, R.** [US/US]; 28 Shelter Creek Lane, Fairport, NY 14623 (US). **YOON, Geun, Young** [KR/US]; 252D Quinby Road, Rochester, NY 14623 (US).
- (74) Agents: **GREENBAUM, Michael, C.** et al.; Blank Rome Comisky & Mccauley LLP, 900 17th Street, N.W., Suite 1000, Washington, DC 20006 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
— with amended claims
- Date of publication of the amended claims:** 25 October 2001
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: WAVEFRONT SENSOR WITH OFF-AXIS ILLUMINATION

(57) **Abstract:** Wavefront aberrations in an eye are detected by illuminating the retina, receiving the light reflected by the retina and using a Hartmann-Shack detector (112) or the like to detect the aberrations. The illuminating light (102) is applied to the eye of the optical axis of the eye (A). Light reflected from the cornea and light reflected from the retina travel in different directions. The former can be blocked with a stop (108), while the latter is passed to the detector.

WO 01/28411 A1