

TITLE OF THE INVENTION

VIDEO EQUIPMENT SPEAKER DEVICE WITH ACOUSTIC LENS

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to speaker devices to be used for video equipment such as a display monitor, television, and personal computer and, more specifically, to a video equipment speaker device with an acoustic lens.

10

Description of the Background Art

Speaker devices are often equipped with an acoustic lens. The acoustic lens is used for setting a directivity of a speaker device to a desired direction. Conventionally, the acoustic lens for the speaker device is implemented by a plurality of fins. Such speaker device is exemplarily disclosed in Japanese Patent Laying-Open No. 6-35489 (1994-35489).

FIG. 14 is a perspective view of a television equipped with television speaker devices having acoustic lenses. In FIG. 14, the television includes a television box 11, a Braun tube 10 provided on the center front of the television box 11, right-channel and left-channel speaker parts 12 provided on the upper-right, upper-left, lower-right, and lower-left portions on the front of the television box 11, center channel speaker parts 13 provided in the vicinity of the upper-center and lower-center

on the front of the television box 11, and a plurality of acoustic lens fins 5 provided on the front of the television box 11 and forward of the speaker parts.

However, the structure of such conventional acoustic-
5 lens-equipped television speaker device poses some problems as follows. First, the complicated fin structure worsens the appearance of the speaker device. Second, each speaker part provided rearward of the fins is almost completely visible from a television viewer, and therefore the entire appearance of the
10 speaker device may be worsened. Lastly, a sound directivity is ensured only in the direction to which the fins are oriented, and thus less spread out. If the speakers parts are arranged only on the upper or lower portion on the front, its reproduced acoustic image will be placed only to the upper or lower side.

15 Therefore, an object of the present invention is to provide a video equipment speaker device capable of, even if arranged only on the upper-front or lower-front of the video equipment, placing the acoustic image to the center on the front of the screen, and lending itself to being invisible to a viewer.

20

SUMMARY OF THE INVENTION

A first aspect of the present invention is directed to a video equipment speaker device having an acoustic lens; comprising: a speaker for forwardly outputting sound; a speaker
25 baffle provided forward of the speaker with an opening through

which the outputted sound passes; and a fin, as the acoustic lens, opposed to the speaker so as to form slits for sound passage with the speaker baffle, and having a shape in cross section as such that a center portion of a surface opposed to the speaker is rearwardly curved, wherein the sound outputted from the speaker passes through the opening and reflects between the fin and the speaker baffle to be externally outputted from the slits.

As described above, in the first aspect, the acoustic lens itself to be invisible from a viewer of the video equipment. Therefore, the speaker device can be provided without its appearance worsened. Further, with the narrow slots, a sound source becomes analogous to a simple sound source, and therefore the directivity can be broadened.

According to a second aspect, in the first aspect, the fin has a shape so that the opening of the speaker baffle is not entirely covered when viewed from the front of the video equipment.

As described above, in the second aspect, the sufficient sound volume can be maintained while sound pressure is not reduced by the fin. Further, with the narrow slots, the sound source becomes analogous to a simple sound source, and therefore the directivity can be broadened.

According to a third aspect, in the second aspect, the fin is provided at a position that avoids intersecting with a center axis for sound outputted from the speaker.

As described above, in the third aspect, part of the sound outputted from the center portion of the speaker is not interfered with the fin. Therefore, since the sound of high-range frequencies is directly outputted from the opening, the sound of
5 the entire range can be outputted with high-frequency characteristics of the speaker unchanged.

According to a fourth aspect, in the third aspect, the center axis passes through one of the slits formed between the fin and the speaker baffle, and part of the sound outputted from
10 the speaker is directly outputted from the slit.

As described above, in the fourth aspect, the sound of high-range frequencies outputted from the center portion of the speaker is directly outputted from the slit. Therefore, the sound of high-range frequencies, which is high in directivity, can be
15 outputted without being obstructed by the fin, allowing high-frequency characteristics of the speaker to be unchanged.

According to a fifth aspect, in the first aspect, the fin is in a rectangular shape when viewed from the front of the video equipment.

20 As described above, in the fifth aspect, the fin is in a rectangular shape. The fin can thus be positioned along each side of the front of the video equipment. Therefore, the directivity can be broadened without the appearance of the speaker device worsened.

25 According to a sixth aspect, in the first aspect, the fin

has one or more apertures, and part of the sound outputted from the speaker is externally outputted through the apertures.

As described above, in the sixth aspect, the fin has one or more apertures. Therefore, the sound of high and mid-range frequencies, especially high-range, can be sufficiently reproduced.

According to a seventh aspect, in the first aspect, a total area of the slits between the fin and the speaker baffle that correspond to the opening of the speaker baffle is approximately equal to an area of the opening of the speaker baffle.

As described above, in the seventh aspect, the total area of the slits between the fin and the speaker baffle that correspond to the opening of the speaker baffle is approximately equal to the area of the opening rearward of the speaker baffle, thereby extremely reducing the acoustic resistance, etc. Therefore, the acoustic characteristics and phase can be stabilized, and especially, the acoustic characteristics in high and mid-range frequencies can be improved.

According to an eighth aspect, in the first aspect, the center portion of the rearwardly-curved surface of the fin is positioned closer to the speaker through the opening of the speaker baffle.

As described above, in the eighth aspect, the acoustic resistance toward the opening is equalized. Therefore, the acoustic characteristics and phase can be stabilized. Also, as

the opening is narrower, the sound source becomes analogous to a simple sound source, thereby broadening the directivity.

According to a ninth aspect, in the first aspect, the speaker device is provided on an upper-front and/or lower-front
5 of the video equipment.

As described above, in the ninth aspect, broad directivity can be obtained in both horizontal and vertical directions even when speakers are provided on either upper-front or lower-front, or both of the video equipment.

10 According to a tenth aspect, in the first aspect, the speaker devices are provided on front-right and front-left of the video equipment.

As described above, in the tenth aspect, broad directivity can be achieved in the horizontal direction if the speakers are
15 provided on the front-right and front-left of the video equipment.

According to an eleventh aspect, in the first aspect, the speaker devices are provided on upper-front and/or lower-front and front-right and front-left of the video equipment.

As described above, in the eleventh aspect, the acoustic
20 image can be easily placed to the center portion frontward of the screen even if the speakers are provided on either the upper-front or lower-front of the video equipment. Furthermore, with the speakers provided on the front-right and front-left of the video equipment, the directivity broadened in the horizontal
25 direction can be obtained. Therefore, a listener can feel the

sound spreading more.

According to a twelfth aspect, in the eleventh aspect, the speaker devices provided on the front-right and front-left of the video equipment are dedicatedly used for high-range frequencies.

5 As described above, in the twelfth aspect, the acoustic image can be easily placed, at low costs, to the center-front portion forward of the screen even if the speakers are provided on either the upper-front or lower-front of the video equipment. Furthermore, with the speakers provided on the front-right and
10 front-left of the video equipment, the directivity in high-range frequencies broadened in the horizontal direction can be obtained. Therefore, the listener can feel the sound spreading more.

A thirteenth aspect is directed to a video unit comprising a video unit box that accommodates a video unit circuit set, first
15 speaker devices provided on upper-front and/or lower-front of the video unit box, and second speaker devices provided on front-right and front-left of the video unit box and dedicatedly used for high-range frequencies, each of the first speaker devices comprising: a speaker for forwardly outputting sound; a speaker
20 baffle provided forward of the speaker with an opening through which the outputted sound passes; and a fin opposed to the speaker so as to form slits for sound passage with the speaker baffle, and having a shape in cross section as such that a center portion of a surface opposed to the speaker is rearwardly curved, wherein
25 the sound outputted from the speaker passes through the opening

and reflects between the fin and the speaker baffle to be externally outputted from the slits.

As described above, in the thirteenth aspect, the right and left sides on the front surface of the video unit box can be visually simplified, compared to the case in which speaker devices with a fin are provided on front-right and front-left thereof. Further, the acoustic image can be easily placed, at low costs, to the center-front portion forward of the screen even if the speakers are provided on either the upper-front or lower-front of the video equipment. Furthermore, with the speakers provided on the front-right and front-left of the video equipment, the directivity in high-range frequencies broadened in the horizontal direction can be obtained. Therefore, the listener can feel the sound spreading more.

These and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view showing the structure of a television including speaker devices according to a first embodiment of the present invention;

FIG. 2 is a cross-sectional view, taken from a side surface direction, of the speaker device according to the first embodiment

of the present invention to show the structure of slots and a sound output axis;

FIG. 3 is a partial front view of the speaker device according to the first embodiment of the present invention to show
5 the structure of the slots and the sound output axis;

FIG. 4 is a schematic diagram representing vertical sound dispersion from the speaker devices according to the first embodiment of the present invention;

FIG. 5 is a cross-sectional view, taken from a side surface
10 direction, of a speaker device according to a second embodiment of the present invention to show the structure of slots with respect to a sound output axis;

FIG. 6 is a partial front view of the speaker device according to the second embodiment of the present invention to
15 show the structure of the slots and the sound output axis;

FIG. 7 is a schematic diagram showing the structural relation between a fin and a baffle in a speaker device according to a third embodiment of the present invention;

FIG. 8A is a graph showing acoustic characteristics when
20 the fin and the speaker baffle are spaced 0 mm apart in the speaker device according to the third embodiment of the present invention;

FIG. 8B is a graph showing acoustic characteristics when the fin and the speaker baffle are spaced 5 mm apart in the speaker device according to the third embodiment of the present invention;

25 FIG. 9A is a graph showing acoustic characteristics when

the fin and the speaker baffle are spaced 10 mm apart in the speaker device according to the third embodiment of the present invention;

FIG. 9B is a graph showing acoustic characteristics when the fin and the speaker baffle are spaced 15 mm apart in the speaker device according to the third embodiment of the present invention;

FIG. 10A is a schematic diagram showing one example of the shape of a fin in a speaker device according to a fourth embodiment of the present invention;

FIG. 10B is a schematic diagram showing another example of the shape of the fin in the speaker device according to the fourth embodiment of the present invention;

FIG. 11 is a perspective view of a television including speaker devices according to a fifth embodiment of the present invention;

FIG. 12 is a schematic diagram showing vertical sound dispersion from the speaker device and a high-frequency speaker device according to the fifth embodiment of the present invention;

FIG. 13 is a perspective view of a television including speaker devices according to a sixth embodiment of the present invention to show the structure of slots; and

FIG. 14 is a perspective view of a conventional television receiver equipped with television speaker devices having acoustic lenses.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

(First embodiment)

FIG. 1 is an external perspective view of a television including speaker devices according to a first embodiment of the present invention. In FIG. 1, the television is constructed of a television box 11, a Braun tube 10 provided in the vicinity of the center-front of the television box 11, and speaker devices 1 provided on the upper-right, upper-center, upper-left, lower-right, lower-center, and lower-left portions on the front thereof.

Note that, in the present invention, these speaker devices 1 are not necessarily provided on the upper-front and lower-front of the television box 11, but may be only on either one thereof. Furthermore, these speaker devices may be provided on the front-right and front-left thereof. Therefore, the positions of the speaker devices are not specifically limited to the above. Moreover, although the speaker devices applied to a television will be described below in the present embodiment, they may be applied to other video equipment such as a display monitor and personal computer.

FIG. 2 is a cross-sectional schematic view, taken from the side surface, of the speaker device according to the first embodiment of the present invention.

In FIG. 2, the speaker device 1 according to the first embodiment of the present invention includes a speaker 2, a sound duct 3 provided forward of the speaker 2 to externally output sound,

a speaker baffle 4 provided in the vicinity of the external edge of the sound duct 3 to externally reflect the sound, a fin 5 provided forward of the speaker baffle 4, sound space 6 formed between the speaker baffle 4 and the fin 5, and slots 7 outwardly opening from the sound duct space 6.

Note that the sound duct 3 is not necessarily required in the present invention. Therefore, the sound duct 3 may be omitted, and the speaker 2 may be positioned just behind the speaker baffle 4.

10 FIG. 3 is a partial front view of the speaker device according to the first embodiment of the present invention. The structure of the speaker 1 is as such described above.

As shown in FIG. 2 or 3, the speaker device 1 according to the first embodiment of the present invention is characterized by the shapes of the speaker baffle 4 and the fin 5, and the sound duct space 6 and the slots 7 both formed by the speaker baffle 4 and the fin 5.

As shown in FIG. 2, the fin 5 is provided forward of the speaker baffle 4 and opposed in parallel to a plane through which sound is outputted from the speaker 2. The surface of the fin 5 opposed to the speaker 2 is curved rearwardly so that the center portion of the fin 5 is closer to the speaker 2 than the upper and lower ends thereof.

The fin 5 is typically has the cross-sectional profile as such that its upper and lower portions are thinner and its center

is thicker when viewed from the side surface direction. However, the front surface of the fin 5 may take any form as long as the rear surface thereof facing to the speaker is shaped as described above.

5 Accordingly, the front surface of the fin 5 may also be curved rearwardly so as to correspond to the curve of the rear surface. For example, the fin 5 is formed with a plate of uniform thickness being bent. Furthermore, irrespectively of the shape of the rear surface of the fin 5, the shape of the front surface
10 thereof may be flat parallel to the surface on which the Braun tube 10 is provided.

 Further, as shown in FIGS. 3 and 5, the fin 5 viewed from the front has typically a rectangular shape, but may be an oval, circular, or any other shape. Therefore, for example, the front
15 surface of the fin 5 may be circular, while its rear surface being rearwardly curved.

 The center portion of the fin 5 is positioned forward of the center of the speaker baffle 4. With the fin 5 positioned as such, the sound outputted from the speaker 2 is reflected on
20 the curved surface of the fin 5. Part of the reflected sound is further reflected on the speaker baffle 4, and externally outputted from the slots 7.

 Furthermore, in FIG. 2, the sound space 6 is formed between the fin 5 and the speaker baffle 4, and the slots 7 opening
25 outwardly from the sound space 6 are provided. It is assumed

herein that the height of the fin 5 is slightly smaller than the diameter of the sound duct 3.

Under such assumption, as shown in FIG. 4, the slots 7 are narrowly formed, and the sound source becomes analogous to a
5 simple sound source. FIG. 4 is a schematic diagram representing vertical sound dispersion from the speaker device according to the first embodiment of the present invention. Since simple sound sources can take the broadest directivity, the above-structured speaker device according to the present embodiment can take broad
10 directivity.

Needless to say, even if the height of the fin 5 is equal to or slightly larger than the diameter of the sound duct 3, the slots 7 can be formed by spacing the fin 5 and the speaker baffle 4 a certain amount apart. Therefore, the height of the fin 5 is
15 not limited to that described above in the present embodiment. However, if the height is smaller than the diameter of the sound duct 3, sound reflected by the fin 5 is reduced, and acoustic resistance and acoustic mass that affect high-range audio frequencies are accordingly reduced. Therefore, the present
20 embodiment is preferable because the sound of high-range frequencies is sufficiently reproduced.

Furthermore, the fin 5 may have one or more apertures penetrating through its surfaces. The position and size of the apertures are not limited, but preferably determined so as not
25 to worsen the appearance of the speaker device. With such

apertures on the fin 5, reflection by the fin 5 is reduced, and thereby acoustic resistance and acoustic mass that affect especially high-range frequencies can be reduced. As a result, the sound of high-range frequencies is sufficiently reproduced.

5 However, the directivity becomes narrower as the total area of the apertures becomes too large. Therefore, the total area of the apertures is preferably determined so that the directivity can be broadened and the sound of high-range frequencies can be sufficiently reproduced.

10 (Second embodiment)

FIG. 5 is a schematic cross-sectional view of a speaker device according to a second embodiment of the present invention. FIG. 6 is a partial front view of the speaker device. Since having functions similar to those in FIG. 2, the components of the speaker
15 device in the second embodiment are provided with the same reference numerals as those in FIG. 2, and only the difference from FIG. 2 will be described below.

In FIG. 5, the fin 5 is at a position that avoids intersecting with an output center axis for the sound outputted from the speaker
20 2. Since the output center axis passes through the slot 7, the sound along the output center axis is directly outputted to the external. As shown in FIG. 6, if viewing from the front of the above-structured speaker device 1, the viewer can see, through the slot 7, a dust cap 8 formed at the center of a diaphragm of
25 the speaker 2.

As described above, the sound of high-range frequencies outputted from the center of the speaker 2 is directly outputted from the slot 7 to the external. Therefore, the sound can be outputted with high-frequency characteristics of the speaker
5 unchanged.

(Third embodiment)

FIG. 7 is a schematic diagram showing a speaker device according to a third embodiment of the present invention. Since having the functions similar to those in FIG. 2, the components
10 shown in FIG. 7 are provided with the same reference numerals as those in FIG. 2, and only the difference from FIG. 2 will be described below.

In FIG. 7, the fin 5 and the speaker baffle 4 are approximately evenly spaced apart so that the area of an opening
15 rearward of the speaker baffle 4, that is, the area of an opening of the sound duct 3, becomes approximately equal to the total area of the slots 7 that correspond to the opening of the sound duct 3.

Such structure approximately equalizes the values of
20 acoustic resistance at the two slots 7 formed on the upper and lower sides of the fin 5, and thereby can stabilize the acoustic characteristics and phase. Furthermore, since the slots 7 are formed narrowly to make the sound source become analogous to a simple sound source, the directivity can be broadened.

25 As stated above, the above-described effects can be

achieved when the fin 5 and the speaker baffle 4 are spaced apart so that the area of the opening rearward of the speaker baffle 4, that is, the area of the opening of the sound duct 3, becomes approximately equal to the total area of the slots 7 that correspond to the opening of the sound duct 3. Graphs representing measurement results of the effects are shown in FIGS. 8A, 8B, 9A, and 9B. Considered below are the results shown in these drawings and the reasons therefor.

FIGS. 8A, 8B, 9A, and 9B are graphs showing how the acoustic characteristics of the speaker device are changed as the distance between the fin 5 and the speaker baffle 4 is changed. Note that the distance referred herein is between the rear end of the fin 5 and the opening of the speaker baffle 4 on the sound output center axis. The diameter of a sound duct in a speaker device used for measurement is 44 mm; the length of the sound duct is 270 mm; and the voluminous capacity of the sound duct is 0.3 liter.

The distance between the fin 5 and the speaker baffle 4 is 0 mm in FIG. 8A; 5 mm in FIG. 8B; 10 mm in FIG. 9A; and 15 mm in FIG. 9B. With such distance, the acoustic characteristics of the speaker device are measured, and represented by the graphs of these drawings with sound pressure (dB) as the vertical axis and frequency (Hz) as the horizontal axis.

In these graphs, the measurement values are represented by shaded bars. Slightly large blank bars superimposed thereon indicate values measured with the fin 5 removed. This allows easy

comparison of degradation in acoustic characteristics.

As shown in FIG. 8A, if the fin 5 and the speaker baffle 4 are spaced 0 mm apart, significant degradation in acoustic characteristics is observed in high and mid-range frequencies, particularly in high-range frequencies. The reason for this degradation can be assumed as follows: If the opening of the sound duct is closed with the fin 5, the sound duct becomes a tube with both ends closed. As a result, the sound duct becomes like a speaker enclosure with a given capacity. Therefore, the opening of the sound duct serves as a low-pass filter that does not lend itself to passing high- and mid-range frequencies, just like a bass-reflex port of a speaker enclosure.

As shown in FIG. 8B, if the distance is 5 mm, the acoustic characteristics in high- and mid-range frequencies are slightly improved. The reason for this improvement can be assumed as follows: The fin 5 does not close the opening of the sound duct, but is isolated therefrom. Therefore, the acoustic resistance and acoustic mass can be reduced. Such reduction diminishes the effects of the low-pass filter.

As shown in FIG. 9A, if the distance is 10 mm, significant improvement in acoustic characteristics is observed. The reason for this improvement can be assumed as follows: The area of the opening rearward of the speaker baffle 4, that is, the area of the opening of the sound duct 3, becomes approximately equal to the total area of the slots 7 that correspond to the opening of

the sound duct 3. As a result, the effects of air viscous drag and the acoustic mass are reduced to improve the acoustic characteristics in high- and mid-range frequencies.

As shown in FIG. 9B, however, if the distance is 15 mm, the
5 acoustic characteristics become slightly degraded. Although the characteristics become less degraded as the total area of slots 7 becomes larger, the directivity becomes narrow if the slots 7 become too large. That may be the reason for this slight degradation.

10 In other words, as described above, if the slots 7 are formed narrowly, the sound source becomes analogous to a simple sound source, thereby allowing broad directivity. If the slots 7 are formed broadly, however, the directivity becomes narrower. It can thus be thought that the acoustic characteristics outside the
15 narrowed directivity become degraded.

Therefore, if the distance is 10 mm, the area of the opening rearward of the speaker baffle 4, that is, the area of the opening of the sound duct 3, becomes approximately equal to the total area of the slots 7 that correspond to the opening of the sound duct
20 3. Therefore, the acoustic characteristics can be maximized with broad directivity and reduced effects of air viscous drag.

Although the shape of the fin 5 in FIG. 7 is similar to that in FIG. 2, the fin 5 may be in a shape as shown in FIG. 10A or 10B, or another shape. The position of the fin 5 is also not
25 limited to that as shown in FIG. 2.

(Fourth embodiment)

FIGS. 10A and 10B are schematic diagrams each showing a speaker device according to a fourth embodiment of the present invention. Since having functions similar to those in FIG. 2, the components shown in FIGS. 10A and 10B are provided with the same reference numerals as those in FIG. 2, and only the difference from FIG. 2 will be described below.

FIGS. 10A and 10B are cross-sectional views of the speaker device 1 taken from the side surface of the television. In FIG. 10A, the surface of the fin 5 opposed to the speaker 2 is curved rearwardly so that the center portion of the fin 5 is closer in position to the speaker 2 than both upper and lower ends thereof. Furthermore, the center portion on the rear of the fin 5 extends toward and beyond the corresponding speaker baffle 4, reaching inside of the sound duct 3. The cross section of the fin 5 viewed from the side surface of the television is a semicircle, as shown in FIG. 10A.

Also in FIG. 10B, similarly to FIG. 10A, the surface of the fin 5 opposed to the speaker 2 is curved rearwardly so that the center portion of the fin 5 is closer in position to the speaker 2 than both upper and lower ends thereof. FIG. 10B is different from FIG. 10A, however, in that the cross section of the fin 5 viewed from the side surface of the television is in a triangular shape.

With such structures, the acoustic resistances of air

viscosity toward the upper and lower slots become equal. As a result, the acoustic characteristics of the speaker device 1 and the phase of output sound can be stabilized.

In other words, as stated above, if the acoustic resistance
5 due to air viscous drag becomes small, the acoustic characteristics is improved. The acoustic resistance becomes larger as the angle of the surface of the fin 5 reflecting sound becomes closer to be vertical with respect to a sound output direction. Therefore, the shape of the fin 5 is so formed as that
10 the center portion on the rear of the fin 5 extends toward and beyond the center portion of the corresponding speaker baffle 4 to reach inside of the sound duct 3. Thus, the angle which the surface of the fin 5 forms with the direction of sound outputted from the speaker 2 becomes small, thereby allowing reduction in
15 acoustic resistance and improvement in acoustic characteristics of the speaker device 1.

Furthermore, with the above-stated structures, the slots
7 become narrow and the sound source becomes analogous to a simple point source. Therefore, similarly to the speaker device
20 according to the first embodiment, the directivity can be broadened.

(Fifth embodiment)

FIG. 11 is a diagram showing the structure of speaker devices according to a fifth embodiment of the present invention,
25 and a television including such speaker device. Since having the

same functions as those in FIG. 1, the components shown in FIG. 11 are provided with the same reference numerals as those in FIG. 1, and only the difference from FIG. 1 will be described below. The television in FIG. 11 is different from that in FIG. 1 in that
5 high-frequency speaker devices 14 are provided.

In FIG. 11, the high-frequency speaker devices 14 are provided on the front-right and front-left of the television box 11, and the fin 5 is provided forward of each of the high-frequency speaker devices 14. With such structure, high-priced speaker
10 devices having excellent acoustic characteristics for all ranges are not required, and therefore the entire cost of the speaker devices can be reduced. Furthermore, even if the speaker devices 1 are provided on either upper-front or lower-front portions of the television box 11, the acoustic image can be placed in the
15 vicinity of the center of the screen.

Still further, with the high-frequency speaker devices 14 provided on the front-right and front-left of the television, the directivity in high-range frequencies can be broadened in the horizontal direction. Therefore, the listener can feel the sound
20 spreading more.

Note that the high-frequency speaker device 14 may be dedicated to be used for high-range frequencies, or generally for high-range but not excluding mid-range frequencies. Also, the high-frequency speaker device 14 may be a speaker device for any
25 frequency range, as the speaker 1. In such case, the directivity

in the horizontal direction can be broadened over the entire frequency range, and therefore the listener can feel the sound spreading more.

FIG. 12 is a schematic diagram showing vertical sound dispersion from the speaker device 1 and the high-frequency speaker device 14. As shown in FIG. 12, even if the speaker device 1 is provided on the lower-front of the television box 11, the acoustic image can be placed in the vicinity of the center of the screen.

10 (Sixth embodiment)

FIG. 13 is a diagram showing the structure of speaker devices according to a sixth embodiment of the present invention, and a television including such speaker device. Since having the same functions as those in FIG. 11, the components shown in FIG. 12 are provided with the same reference numerals as those in FIG. 11, and only the difference from FIG. 11 will be described below. The television in FIG. 12 is different from that in FIG. 11 in that the fin 5 is not provided forward of each of the high-frequency speaker devices 14.

FIG. 13 shows the structure that the slots 7 for the high-frequency speaker devices 14 are provided on the front-right and front-left of the television box 11 and the right and left side surfaces thereof. As shown in FIG. 13, the high-frequency speaker devices 14 are provided on the right and left of the television box 11. The slots 6 for the high-frequency speaker

devices 14 are provided either on the front-right and front-left or on the right and left sides, or both, of the television box 11. With such structure, the slots 7 can be visually simplified. Therefore, the width of the front surface of the television with
5 the width of its screen subtracted therefrom can be reduced.

Still further, similarly to the case shown in FIG. 11, with the high-frequency speaker devices 14 provided on the front-right and front-left of the television, the directivity in high-range frequencies can be broadened in the horizontal direction.
10 Therefore, the listener can feel the sound spreading more.

In the forgoing embodiments, description is made supposing the speaker devices are applied to a television. Needless to say, however, the speaker device according to each of the above embodiments may also be applied to video equipment such as a
15 display monitor and personal computer.

While the invention has been described in detail, the foregoing description is in all aspects illustrative and not restrictive. It is understood that numerous other modifications and variations can be devised without departing from the scope
20 of the invention.

WHAT IS CLAIMED IS:

1. A video equipment speaker device having an acoustic lens; comprising:

a speaker for forwardly outputting sound;

a speaker baffle provided forward of said speaker with an
5 opening through which the outputted sound passes; and

a fin, as said acoustic lens, opposed to said speaker so
as to form slits for sound passage with said speaker baffle, and
having a shape in cross section as such that a center portion of
a surface opposed to said speaker is rearwardly curved, wherein
10 the sound outputted from said speaker passes through said
slit and reflects between said fin and said speaker baffle to be
externally outputted from said slits.

2. The video equipment speaker device according to claim
1, wherein

said fin has a shape so that the opening of said speaker
baffle is not entirely covered when viewed from the front of said
5 video equipment.



3. The video equipment speaker device according to claim
2, wherein

said fin is provided at a position that avoids intersecting
with a center axis for sound outputted from said speaker.

4. The video equipment speaker device according to claim
3, wherein

said center axis passes through one of said slits formed
between said fin and said speaker baffle, and

5 part of the sound outputted from said speaker is directly
outputted from said slit.

5. The video equipment speaker device according to claim
1, wherein

said fin is in a rectangular shape when viewed from the front
of said video equipment.

6. The video equipment speaker device according to claim
1, wherein

said fin has one or more apertures, and

part of the sound outputted from said speaker is externally
5 outputted through the apertures.

7. The video equipment speaker device according to claim
1, wherein

a total area of the slits between said fin and said speaker
baffle that correspond to the opening of said speaker baffle is
5 approximately equal to an area of the opening of said speaker
baffle.



8. The video equipment speaker device according to claim
1, wherein

the center portion of the rearwardly-curved surface of said
fin is positioned closer to said speaker through the opening of
5 said speaker baffle.

9. The video equipment speaker device according to claim
1, wherein

said speaker device is provided on an upper-front and/or
lower-front of said video equipment.

10. The video equipment speaker device according to claim
1, wherein

said speaker devices are provided on front-right and
front-left of said video equipment.

11. The video equipment speaker device according to claim
1, wherein

said speaker devices are provided on upper-front and/or
lower-front and front-right and front-left of said video
5 equipment.



12. The video equipment speaker device according to claim
11, wherein

said speaker devices provided on the front-right and

This Sheet Has Been Replaced



high-range frequencies.

13. A video unit comprising a video unit box that accommodates a video unit circuit set, first speaker devices provided on upper-front and/or lower-front of the video unit box, and second speaker devices provided on front-right and front-left of the video unit box and dedicatedly used for high-range frequencies,

each of said first speaker devices comprising:

a speaker for forwardly outputting sound;

a speaker baffle provided forward of said speaker with an opening through which the outputted sound passes; and

a fin opposed to said speaker so as to form slits for sound passage with said speaker baffle, and having a shape in cross section as such that a center portion of a surface opposed to said speaker is rearwardly curved, wherein

the sound outputted from said speaker passes through said opening and reflects between said fin and said speaker baffle to be externally outputted from said slits.

