

Description

The present invention generally relates to printers and, more particularly, to inkjet printers in which aqueous ink is applied to a porous sheet medium such as paper.

Conventional inkjet printers include inking devices, generally referred to as "pens," for depositing ink droplets on sheets to be printed. Normally, the droplets contain an aqueous fraction which, after printing, must be evaporated to permanently fix the ink to the printed sheets. With the increased use of highly aqueous inks, many having water contents approaching one-hundred percent by weight, several printing problems have arisen. One such problem is that highly aqueous inks cause wetted fibers on the printed face of a sheet to swell to a substantially greater extent than dry fibers on the obverse side of the sheet. Such an effect, often described as differential expansion, results in wrinkle-like bulges, or cockles, in sheets. When printing on ordinary paper, cockling can occur as rapidly as 600 milliseconds (ms) after aqueous ink is applied.

Also, highly aqueous inks cause difficulties in sheet drying. Conventionally, the drying of ink on printed sheets entails applying heat after entire sheets are printed. This practice has several disadvantages in the case of highly aqueous inks. For instance, in the interval while a printed sheet is transported from a printing station to a drying station, highly aqueous inks are quite susceptible to smearing. Also, highly aqueous inks often bleed into paper fibers before drying is complete. Such bleeding can detrimentally affect the appearance of text or graphics printed on a sheet and, also, can adversely affect the appearance of the obverse side of a printed sheet.

The highly aqueous nature of many modern inks can also adversely affect the efficiency of inkjet printers. For example, to provide adequate time for highly aqueous inks to dry, the printing speed of an inkjet printer may have to be slowed or else the size of the driers on the printer may have to be increased. Although the temperature of driers can be increased to dry ink more quickly, there are limits beyond which temperature cannot be elevated without scorching printed sheets.

In addition to the problems mentioned above, there are less obvious ways in which highly aqueous inks may adversely affect inkjet printing. For example, because inkjet printing normally proceeds sequentially from location to location across a sheet surface, cockling at one location can adversely affect pen-to-sheet spacing during printing at adjacent locations. Pen-to-sheet spacing is especially critical in bi-directional inkjet printing (i.e., in inkjet printers that print swaths of ink drops while

moving both from right-to-left and from left-to-right across the surface of a sheet). In bidirectional printing, print defects are usually perceptible unless pen-to-sheet spacing distance is held constant to tolerance of about $\pm 0.0635\text{mm}$ (± 0.0025 inch).

In view of the preceding discussion, it can be appreciated that there exists a need in the inkjet printing art for improved ways and means to minimize cockling and to prevent highly aqueous inks from bleeding and smearing before drying.

DE-A-3 642 204 (SEIKO EPSON) discloses a printing assembly for an inkjet printer, comprising: inkjet pen means for providing ink droplets which form print lines on sheets; and a first heater for heating localized areas of the sheets along the print lines; so that ink is substantially immediately exposed along the print line to localized heat from the first heater upon ejection from the pen means to form a print line,

However, the heater means warms the reverse of the sheet and not the printed area directly.

Accordingly, a first aspect of the invention provides a printing assembly for an inkjet printer, comprising: inkjet pen means for providing ink droplets which form print lines on sheets; and a first heater for heating localized areas of the sheets along the print lines; so that ink is substantially immediately exposed along the print line to localized heat from the first heater upon ejection from the pen means to form a print line, characterised in that the printer further comprises support means for supporting the pen means and the first heater adjacent one to another, proximate the surface of a sheet to be printed.

The present invention generally provides an inkjet printing assembly comprising an inkjet pen and heater means for heating localized areas of sheets along print lines so that ink, upon ejection from the inkjet pen, is substantially immediately exposed to elevated temperature. In the preferred embodiment, the heater means comprises first and second heaters mounted to heat each print line immediately in advance of inking and immediately after inking. Further in the preferred embodiment, the inkjet pen and the two heaters are mounted to travel back and forth across a sheet during printing.

In another embodiment, an auxiliary heating means is arranged at a location spaced from the inkjet pen for heating printed surfaces of printed sheets. Preferably, the auxiliary heating means comprises a pair of roller members, at least one of which is heated, mounted to subject printed sheets to an ironing action for removing cockles from the sheets.

Various features and advantages of the present invention can be appreciated from the following description in conjunction with the appended drawings, in which:

FIGURE 1 is a frontal view of an inkjet printing assembly according to the present invention; FIGURE 2 is a bottom plan view of one configuration of a heater included in the assembly of FIGURE 1;

FIGURE 3 is a schematic diagram illustrating operation of the assembly of FIGURE 1 when viewed in the direction of paper travel; and FIGURE 4 is a side profile view of the assembly of FIGURE 1 in combination with an auxiliary heater assembly.

FIGURE 1 generally shows an inkjet pen carriage 20, sometimes referred to as a "print head". Carriage 20 is slidably mounted on a guide shaft 30 and is adapted to carry one or more inkjet pens 40 disposed to form print lines on the surface of a sheet 50. More particularly, carriage 20 is supported by guide shaft 30 so that inkjet pen 40 can traverse back and forth across sheet 50 in a direction perpendicular to the sheet edges while remaining parallel to the sheet surface. (In terms of FIGURE 1, the traversing motion would be parallel to the axial center line of guide shaft 30.) A motor-driven device such as a band or belt is mechanically coupled to drive carriage 20 to drive it back and forth on guide shaft 30.

As shown in FIGURE 1, carriage 20 carries a heater 60, such as a wire filament type heater, attached adjacent one side of inkjet pen 40 to face the surface of sheet 50 while being proximately spaced therefrom. Preferably, at least one additional heater 70 is mounted adjacent the side of inkjet pen 40 opposite first heater 60. Thus, in the illustrated embodiment, both heaters 60 and 70 face the surface of sheet 50. In practice, the two heaters need not be separate but can be a single heater configured to wrap-around the inkjet pens to heat each print line both immediately before and immediately after inking by the inkjet pen.

Operation of the system of FIGURE 1 will now be generally described. Initially, it should be assumed that the inkjet printer is of the bi-directional type so that inkjet pen 40 prints swaths of ink drops across the surface of sheet 50 while carriage 20 moves both back and forth along guide shaft 30. In each swath, ink dots are printed in columns; a row of columns covers a sheet as referred to herein as a "print line". Normally, between each change in printing direction, the printed sheet is indexed to provide generally equal spacing between print lines. (In terms of FIGURE 1, the sheet indexing direction would be perpendicular to the plane of the drawing.)

Because heaters 60 and 70 are attached to carriage 20 in the embodiment of FIGURE 1, the heaters pass directly over each print line on the surface of sheet 50 before and after inkjet pen 40 has deposited ink on the line. Thus, the leading

heater on the carriage convectively heats the surface of sheet 50 in localized areas ahead of each print line. Then, the trailing heater begins drying each print line almost immediately (i.e., within about fifty milliseconds) after ink is applied. Accordingly, the system of FIGURE 1 functions to dry printed lines before ink droplets forming the lines can bleed substantially into the sheet fibers, or merge with adjacent ink droplets, or cause cockling.

In operating the inkjet print head of FIGURE 1, the temperature to which localized areas along print lines are heated is controlled by the temperature of heaters 60 and 70. Normally, the temperature of each heater is controlled by varying the electrical current applied through the heater filaments. For example, for printing on plain paper, localized areas on the sheet surface normally are not heated above the browning point, about 160 °C.

FIGURE 2 shows one example of a particular configuration of heaters 60 and 70. In this configuration, each heater comprises a heating filament 80 which extends over the planar face of a supporting substrate 90 between electrical terminal pads 100. Also in the illustrated embodiment, filament 80 has a resistance metallization pattern which can be generally described as serpentine or meandering. Preferably, substrate 90 is formed of an electrically and thermally insulating material so that heat from filament 80 does not cause dimensional distortion of either inkjet pen 40 or carriage 20. Substrate 90 is usually formed of ceramic alumina and filament 80 is usually formed of tungsten. In practice, it is preferred to coat the substrate and filament with a thin protective layer of glass.

Normally, the planar surfaces of the substrates 90 are mounted parallel to the surface to be printed, generally at an elevation of about two millimeters or less above the print lines. In practice, such spacing provides substantial convective heating of the sheet surface as well as radiant heating. Because heat is transferred to sheet 50 primarily by forced convection, the transfer mechanism can be augmented by blowing air through the space between heater and the sheet surface.

Operation of heaters 60 and 70 can be further understood from FIGURE 3, which schematically shows inkjet pen 40 traversing sheet 50 in the direction of arrow A while selectively depositing ink droplets 120 onto the surface of sheet. (In FIGURE 3, the direction of sheet indexing would be into, or out of, the page.) In travel direction A, heater 60 leads pen 40 and prewarms localized areas along each print line. As each localized area is prewarmed, surface moisture is both evaporated and driven into sub-surface regions of sheet 50. Thus, when ink droplets 120 are ejected from pen 40,

they contact warm, dry fibers on the sheet surface and begin to dry immediately.

FIGURE 3 further shows that heater 70 follows pen 40 along each print line in travel direction A. Thus, trailing heater 70 functions to evaporatively dry and immobilize the deposited ink droplets 120 which form each print line. Additionally, heat from trailing heater 70 drives liquid binders from the ink droplets into the sheet fibers at, and below, the sheet surface. This latter effect enhances the appearance of print and has the practical benefit of reducing ink smearing when a printed sheet is subsequently handled or transported. Furthermore, by driving ink moisture into the bulk of a sheet, trailing heater 70 assists in re-establishing a generally uniform moisture profile through a printed sheet, thereby reducing the tendency of the sheet to cockle. Still further, it should be noted that heaters 60 and 70 convectively warm the air near inkjet pen 40 and, therefore, assist in preventing condensation of moisture onto the pen.

In practice, carriage-mounted heaters 60 and 70 are smaller in size than conventional, stationary driers. The smaller size of the carriage-mounted heaters results from the fact that stationary driers have the more difficult task of removing moisture which has penetrated into a sheet, while the carriage-mounted heaters have the less difficult task of only drying applied ink sufficiently to prevent puddling. Tests have shown that the combined vaporization of surface moisture and more uniform distribution of moisture within sheets when using carriage-mounted heaters account for substantial reduction in paper cockle. In practical effect, usage of carriage-mounted heaters reduces or eliminates the need for large stationary driers on inkjet printers. Thus, by employing carriage-mounted heaters, the size of inkjet printer can be reduced while maintaining high print quality and normal printing speeds.

FIGURE 4 shows a combination of the above-described carriage-mounted heaters with a roller-type heater, generally designated by number 130. In practice, the system of FIGURE 4 can be particularly effectively employed when graphics are printed which have large, highly inked areas. In such applications, even though carriage-mounted heaters can be operated to sufficiently dry ink to avoid smearing, further heating of a printed sheet often is needed to remove residual ink moisture and to remove cockles which form because of the residual moisture.

In the embodiment illustrated in FIGURE 4, roller-type heater 130 is a hollow, elongated cylindrical member 131 which is mounted to extend parallel to the direction of guide shaft 30 while being positioned in rolling contact with sheet 50 after inkjet printing. In the preferred embodiment,

cylindrical member 131 is formed of metal and is covered with a thermally conducting non-sticky material 144, such as teflon. Mounted along the axis of cylinder 131 is a heat lamp 140. Also in the preferred embodiment, a pressure roller 150 is located on the obverse side of sheet 50 opposite roller-type heater 130 so that the sheet is engaged at the nip between the two rollers. Pressure roller 150 can be heated in addition to, or instead of, roller 130.

Operation of the system of FIGURE 4 will now be described. Initially, it should be assumed that rollers 130 and 150 are driven by a common drive, have the same surface speed, and are biased together with sufficient pressure to drive sheet 50 without slippage. It may be assumed also that sheet 50 has not been dried completely by action of carriage-mounted heaters 60 and 70 which travel with inkjet pen 40 on carriage 20, but that sufficient moisture has been removed from the sheet that beads of ink do not form ahead of the nip between rollers 130 and 150. Then, when lamp 140 is energized to radiantly heat roller 130 (usually to a temperature ranging from about 160°C to about 190°C), sheet 50 is heated by heat conduction as it travels through the nip between rollers 130 and 150. The temperature to which sheet 50 is heated is generally a function of the temperatures of the rollers and the travel speed of the sheet. Together, the pressure and heat along the nip between rollers 130 and 150 provide an ironing effect which removes moisture to fully dry the printed sheet and which flattens cockles in the sheet, thereby assuring that the printed sheet has an acceptable appearance.

At this juncture, it should again be emphasized that, in the system of FIGURE 4, the carriage-mounted heaters normally are not operated to completely dry print lines before a printed sheet is operated upon by the roller-type heater 130. This is done because retained bulk moisture has been found to be important for the removal of cockle by the roller-type heaters. The explanation for this effect appears to be that retained moisture swells fibers in sheets to increase the overall volume of the sheet and to, thereby, allow space for fiber realignment and sheet flattening when a partially dried sheet is operated upon by the roller-type heaters. Thus, combined use of carriage-mounted heaters and roller-type heaters often provides a synergistic effect.

Although the present invention has been described in terms of specific embodiments and modes of operation, the description should be regarded as illustrative rather than limitative. Thus, workers of ordinary skill in the art will appreciate that the invention may be otherwise embodied or practiced. For example, while the foregoing de-

scription of the best mode of carrying out the invention was presented in connection with an inkjet printing of paper sheets, and it may be in such an application that the advantages of the invention are most fully realized, the invention may also prove useful in connection with other types of printers and with various media.

As a particular example of an alternative within the scope of the present invention, workers skilled in the art will recognize that inkjet printing can be accomplished with print heads that do not travel but, instead, extend stationarily across the full width of a traveling sheet to be printed. In such an embodiment, the above-described heaters 60 and 70 would be stationarily arranged immediately before and immediately after the print heads in the direction of sheet travel.

As yet another example of an alternative within the scope of the present invention, workers skilled in the art will recognize that the system of FIGURE 4 can be operated with roller members 130 and 150 driven continuously or incrementally. In the case where it is desired to continuously drive roller members 130 and 150 when a sheet moves incrementally (i.e., when a sheet is indexed), the roller members can be located to follow, for example a path compliance loop which provides a buffer between the rollers and the printing station.

Claims

1. A printing assembly for an inkjet printer, comprising: inkjet pen means (40) for providing ink droplets which form print lines on sheets (50); and a first heater (60) for heating localized areas of the sheets along the print lines; so that ink is substantially immediately exposed along the print line to localized heat from the first heater upon ejection from the pen means to form a print line, characterised in that the printer further comprises support means (20) for supporting the pen means and the first heater adjacent one to another, proximate the surface of a sheet to be printed.
2. A printing assembly according to Claim 1, wherein the first heater (60) is mounted on the support means (20) for heating localized areas of a sheet (50) surface immediately in advance of inking by the pen means (40).
3. A printing assembly according to Claims 1 or 2 further including a second heater (70) mounted on the support means (20) such that the pen means (40) is disposed between the first and second heaters (60,70).

4. A printing assembly according to Claim 3, wherein the first and second heaters (60,70) operate to heat each print line both immediately before and immediately after inking by the inkjet pen means (40).
5. A printing assembly according to any preceding Claim said support means (20) is mounted on a guide shaft (30) that extends parallel to the surface of a sheet (50) during printing.
6. A printing assembly according to any preceding Claim wherein the inkjet pen means (40) is mounted for translational motion back and forth across the surface of a sheet (50) to be printed.
7. A printing assembly according to any of Claims 1 to 5 wherein the inkjet pen means (40) and the first heater (60) are stationary.
8. A printing assembly according to any preceding Claim further including an auxiliary heating means (130) arranged at a location substantially spaced from the inkjet pen means (40) for heating the sheet (50) surface after printing.
9. A printing assembly according to Claim 8 wherein said auxiliary heating means (130) includes a first heated roller member (131) for rolling across the printed surfaces of printed sheets (50).
10. A printing assembly according to Claims 8 or 9 wherein said auxiliary heating means (130) includes a second roller member (150) mounted opposite the first roller member (131) such that printed sheets (50) pass through the nip area between the first and second roller members.
11. A printing assembly according to Claim 10 wherein the second roller member (150) is heated.
12. A method of inkjet printing, comprising the steps of: depositing swaths of droplets of ink from inkjet pen means (40) to sequentially form print lines on a surface of a sheet (50); and heating the print lines with a heater (60) substantially simultaneously with printing so that ink droplets, upon striking the sheet surface to form the print lines, are substantially immediately exposed to elevated temperature, characterised in that the heater is provided adjacent the inkjet pen means proximate the surface of the sheet to be printed.



scription of the best mode of carrying out the invention was presented in connection with an inkjet printing of paper sheets, and it may be in such an application that the advantages of the invention are most fully realized, the invention may also prove useful in connection with other types of printers and with various media.

As a particular example of an alternative within the scope of the present invention, workers skilled in the art will recognize that inkjet printing can be accomplished with print heads that do not travel but, instead, extend stationarily across the full width of a traveling sheet to be printed. In such an embodiment, the above-described heaters 60 and 70 would be stationarily arranged immediately before and immediately after the print heads in the direction of sheet travel.

As yet another example of an alternative within the scope of the present invention, workers skilled in the art will recognize that the system of FIGURE 4 can be operated with roller members 130 and 150 driven continuously or incrementally. In the case where it is desired to continuously drive roller members 130 and 150 when a sheet moves incrementally (i.e., when a sheet is indexed), the roller members can be located to follow, for example a path compliance loop which provides a buffer between the rollers and the printing station.

Claims

1. A printing assembly for an inkjet printer, comprising: inkjet pen means (40) for providing ink droplets which form print lines on sheets (50); and a first heater (60) for heating localized areas of the sheets along the print lines; so that ink is substantially immediately exposed along the print line to localized heat from the first heater upon ejection from the pen means to form a print line, characterised in that the printer further comprises support means (20) for supporting the pen means and the first heater adjacent one to another, proximate the surface of a sheet to be printed.
2. A printing assembly according to Claim 1, wherein the first heater (60) is mounted on the support means (20) for heating localized areas of a sheet (50) surface immediately in advance of inking by the pen means (40).
3. A printing assembly according to Claims 1 or 2 further including a second heater (70) mounted on the support means (20) such that the pen means (40) is disposed between the first and second heaters (60,70).
4. A printing assembly according to Claim 3, wherein the first and second heaters (60,70) operate to heat each print line both immediately before and immediately after inking by the inkjet pen means (40).
5. A printing assembly according to any preceding Claim said support means (20) is mounted on a guide shaft (30) that extends parallel to the surface of a sheet (50) during printing.
6. A printing assembly according to any preceding Claim wherein the inkjet pen means (40) is mounted for translational motion back and forth across the surface of a sheet (50) to be printed.
7. A printing assembly according to any of Claims 1 to 5 wherein the inkjet pen means (40) and the first heater (60) are stationary.
8. A printing assembly according to any preceding Claim further including an auxiliary heating means (130) arranged at a location substantially spaced from the inkjet pen means (40) for heating the sheet (50) surface after printing.
9. A printing assembly according to Claim 8 wherein said auxiliary heating means (130) includes a first heated roller member (131) for rolling across the printed surfaces of printed sheets (50).
10. A printing assembly according to Claims 8 or 9 wherein said auxiliary heating means (130) includes a second roller member (150) mounted opposite the first roller member (131) such that printed sheets (50) pass through the nip area between the first and second roller members.
11. A printing assembly according to Claim 10 wherein the second roller member (150) is heated.
12. A method of inkjet printing, comprising the steps of: depositing swaths of droplets of ink from inkjet pen means (40) to sequentially form print lines on a surface of a sheet (50); and heating the print lines with a heater (60) substantially simultaneously with printing so that ink droplets, upon striking the sheet surface to form the print lines, are substantially immediately exposed to elevated temperature, characterised in that the heater is provided adjacent the inkjet pen means proximate the surface of the sheet to be printed.



Patentansprüche

1. Druckeinrichtung für einen Tintenstrahldrucker, mit einer Tintenstrahlstift-Vorrichtung (40) zum Liefern von Tintentröpfchen, welche gedruckte Linien auf Blättern (50) bilden, und einer ersten Heizvorrichtung (60) zum Erhitzen örtlich begrenzter Bereiche der Blätter längs der gedruckten Linien, so daß Tinte im wesentlichen sofort bei einem Ausstoß von der Stiftvorrichtung längs der gedruckten Linie örtlicher Wärme von der ersten Heizvorrichtung ausgesetzt wird, um eine gedruckte Linie zu bilden, dadurch **gekennzeichnet**, daß der Drucker ferner eine Haltevorrichtung (20) aufweist, um die Stiftvorrichtung und die erste Heizvorrichtung aneinander angrenzend, in der Nähe der Oberfläche eines zu bedruckenden Blattes zu halten. 5
2. Druckeinrichtung nach Anspruch 1, bei der die erste Heizvorrichtung (60) auf der Haltevorrichtung (20) montiert ist, um örtlich begrenzte Bereiche der Oberfläche eines Blattes (50) unmittelbar vor dem Tintenausstoß durch die Stiftvorrichtung (40) zu erhitzen. 10
3. Druckeinrichtung nach Anspruch 1 oder 2, mit einer zweiten Heizvorrichtung (70), die auf der Haltevorrichtung (20) montiert ist, so daß die Stiftvorrichtung (40) zwischen der ersten und der zweiten Heizvorrichtung (60, 70) angeordnet ist. 15
4. Druckeinrichtung nach Anspruch 3, bei der die erste und die zweite Heizvorrichtung (60, 70) jede gedruckte Linie sowohl unmittelbar vor als auch unmittelbar nach dem Erhitzen. 20
5. Druckeinrichtung nach einem der vorangehenden Ansprüche, bei der die Haltevorrichtung (20) auf einer Führungswelle (30) montiert ist, die sich während des Druckens parallel zu der Oberfläche eines Blattes (50) erstreckt. 25
6. Druckeinrichtung nach einem der vorangehenden Ansprüche, bei der die Tintenstrahlstift-Vorrichtung (40) für eine translatorische Vorwärts- und Rückwärtsbewegung über die Oberfläche eines zu bedruckenden Blattes (50) montiert ist. 30
7. Druckeinrichtung nach einem der Ansprüche 1 bis 5, bei der die Tintenstrahlstift-Vorrichtung (40) und die erste Heizvorrichtung (60) stationär sind. 35
8. Druckeinrichtung nach einem der vorangehenden Ansprüche, mit einer Hilfs-Heizvorrichtung (130) zum Erwärmen der Oberfläche des Blattes (50) nach dem Drucken, die an einer beträchtlich von der Tintenstrahlstift-Vorrichtung (40) entfernten Stelle angeordnet ist. 40
9. Druckeinrichtung nach Anspruch 8, bei der die Hilfs-Heizvorrichtung (130) eine erste beheizte Walze (131) zum Rollen über die gedruckten Oberflächen bedruckter Blätter (50) aufweist. 45
10. Druckeinrichtung nach Anspruch 8 oder 9, bei der die Hilfs-Heizvorrichtung (130) eine zweite Walze (150) aufweist, die der ersten Walze (131) gegenüberliegend angebracht ist, so daß bedruckte Blätter (50) durch den Klemmbereich zwischen der ersten und der zweiten Walze hindurchgehen. 50
11. Druckeinrichtung nach Anspruch 10, bei der die zweite Walze (150) beheizt ist. 55
12. Verfahren zum Tintenstrahldrucken, mit den folgenden Verfahrensschritten: Ablagern von Tintentröpfchenschwaden von einer Tintenstrahlstift-Vorrichtung (40), um sequentiell gedruckte Linien auf der Oberfläche eines Blattes (50) zu bilden, und Erhitzen der gedruckten Linien mit einer Heizvorrichtung (60) im wesentlichen gleichzeitig mit dem Druckvorgang, so daß Tintentröpfchen beim Auftreffen auf die Blattoberfläche zum Bilden der gedruckten Linien im wesentlichen sofort einer erhöhten Temperatur ausgesetzt werden, dadurch **gekennzeichnet**, daß die Heizvorrichtung angrenzend an die Tintenstrahlstift-Vorrichtung in der Nähe der Oberfläche des zu bedruckenden Blattes vorgesehen wird.

Revendications

1. Ensemble d'impression pour une imprimante à jet d'encre, comprenant : des moyens (40) formant plume à jet d'encre servant à débiter des gouttelettes d'encre qui forment des lignes d'impression sur des feuilles (50) ; et un premier élément chauffant (60) servant à chauffer des zones localisées des feuilles le long des lignes d'impression ; de sorte que l'encre est sensiblement immédiatement exposée, le long de la ligne d'impression, à une chaleur localisée émise par le premier élément chauffant dès qu'elle a été éjectée des moyens formant plume pour former une ligne d'impression, caractérisé en ce que l'imprimante comprend en outre des moyens de support (20) servant à supporter les moyens formant plume et le pre-



mier élément chauffant adjacents l'un à l'autre et à proximité de la surface d'une feuille à imprimer.

2. Ensemble d'impression selon la revendication 1, dans lequel le premier élément chauffant (60) est monté sur le moyen de support (20) pour chauffer des zones localisées de la surface d'une feuille (50) immédiatement avant l'encreage effectué par le moyen (40) formant plume. 5 10
3. Ensemble d'impression selon la revendication 1 ou 2, comprenant en outre un second élément chauffant (70) monté sur le moyen de support (20) de manière que le moyen (40) formant plume soit disposé entre les premier et second éléments chauffants (60, 70). 15
4. Ensemble d'impression selon la revendication 3, dans lequel les premier et second éléments chauffants (60, 70) opèrent de manière à chauffer chaque ligne d'impression aussi bien immédiatement avant qu'immédiatement après la projection d'encre par le moyen (40) formant plume à jet d'encre. 20 25
5. Ensemble d'impression selon une quelconque des revendications précédentes, dans lequel ledit moyen de support (20) est monté sur une barre de guidage (30) qui s'étend parallèlement à la surface d'une feuille (50) pendant l'impression. 30
6. Ensemble d'impression selon une quelconque des revendications précédentes, dans lequel le moyen (40) formant plume à jet d'encre est monté pour décrire un mouvement de translation en aller et retour en travers de la surface d'une feuille (50) à imprimer. 35 40
7. Ensemble d'impression selon une quelconque des revendications 1 à 5, dans lequel le moyen (40) formant plume à jet d'encre et le premier élément chauffant (60) sont fixes. 45
8. Ensemble d'impression selon une quelconque des revendications précédentes, comprenant en outre un moyen chauffant auxiliaire (130) agencé dans une position sensiblement espacée du moyen (40) formant plume à jet d'encre pour chauffer la surface de la feuille (50) après l'impression. 50
9. Ensemble d'impression selon la revendication 8, dans lequel ledit moyen de chauffage auxiliaire (130) comprend un premier élément rouleau chauffé (131) destiné à rouler sur les 55

surfaces imprimées des feuilles imprimées (50).

10. Ensemble d'impression selon la revendication 8 ou 9, dans lequel ledit moyen de chauffage auxiliaire (130) comprend un second élément rouleau (150) monté en face du premier élément rouleau (131) de telle manière que les feuilles imprimées traversent la zone de serrage entre les premier et second éléments rouleaux. 10
11. Ensemble d'impression selon la revendication 10, dans lequel le second élément rouleau (150) est chauffé. 15
12. Procédé d'impression à jet d'encre, comprenant les phases consistant à : déposer des andains de gouttelettes d'encre émises par le moyen (40) formant plume à jet d'encre pour former des lignes d'impression sur une surface d'une feuille (50) dans un mode séquentiel ; et chauffer les lignes d'impression avec un élément chauffant (60) sensiblement simultanément avec l'impression de manière que les gouttelettes d'encre, après avoir frappé la surface de la feuille pour former les lignes d'impression, soient sensiblement immédiatement exposées à une température élevée, caractérisé en ce que l'élément chauffant est placé à côté du moyen formant plume à jet d'encre, à proximité de la surface de la feuille à imprimer. 20 25 30 35 40 45 50 55