

SEMICONDUCTOR BIOSENSOR AND CONTROL METHOD THEREOF

1. Field of the Invention

【0001】 The present invention relates to a semiconductor biosensor
5 which is used for healthcare chip and a control method of the semiconductor
biosensor.

2. Description of the Related Art

【0002】 In recent years, it has become significant to suppress the
drastic increase of medical expense since the society is aging in developed
10 countries. It may be possible to early find diseases and thereby reduce the
medical expense if we can inspect and detect little amount of chemical
substance contained in a sample with high precision. It is expected that such
an inspect method can be achieved by utilizing microelectronics technologies.
(See K. Koike, et al., Jpn. J. Appl. Phys., vol. 53, 05FF04 (2014).)

15 【0003】 However, the inspection equipment with high precision is
not only expensive but also large in size. Thus, the inspection can only be
carried out in large hospitals or medical facilities. This makes the inspection
expensive, and the inspection period is often more than several days.

【0004】 In other words, small inspection equipment with high
20 precision may enable small-scale medical institute to perform cheap

inspection. The inspection period shall be substantially reduced with simplified process of inspection, then substantially reducing the cost and improving the convenience of the inspection. Therefore, in order to cut the cost of the inspection, it is necessary to substantially reduce the size of inspection equipment while keeping the precision by utilizing the combined technologies of semiconductor micro-devices and biosensors.

【0005】 Fig. 1 is an exemplary illustration of basic device structure of a conventional semiconductor biosensor (See K. Koike, et al., Jpn. J. Appl. Phys., vol. 53, 05FF04 (2014).). An oxide film 1, a source electrode 2 and a drain electrode 3 are layout on a semiconductor substrate 4. Those electrodes are covered by a resist film 100 so as to be protected from a solution (e.g.: specimen such as blood, urine, sweat, and so forth) in which inspection target is dissociated. This conventional semiconductor biosensor is exposed into the solution during inspection.

15 【0006】 Referring to fig. 10, in the solution, a target 7 and a receptor 8 are attached to the surface of the oxide film 1 to produce a chemical reaction. The chemical reaction normally has a dissociation constant K for determining the equilibrium state thereof. When the dissociation constant K is larger, the decoupling prevails in the chemical reaction. To the contrary, when the dissociation constant K is smaller, the coupling prevails in the

chemical reaction, and thus a composite body 5 is made on the surface of the oxide film 1, as illustrated figs. 2, 3, and 4.

【0007】 The composite body 5 has charge carried by the target 7. The charge will modulate surface electric field of the semiconductor substrate

5 4. It may capable of detecting whether the target 7 is contained in the solution by reading the change in electric current flowing between the source electrode 2 and the drain electrode 3.

【0008】 There are many composite bodies 5 on the surface of the oxide film 1, as illustrated in fig. 2, as long as the dissociation constant 300 is

10 small. If the dissociation constant 300 is larger, the density of the composite bodies 5 is decreased, as illustrated in figs. 3, and 4.

【0009】 Besides, if the number of target 7 is more in solution, then more composite bodies 5 are attached to the surface of the oxide film 1, as illustrated in fig. 2. If the number of target 7 is less in solution, then, as

15 illustrated in figs. 3, and 4, the number of composite bodies 5 attached to the surface of the oxide film 1 becomes less.

【0010】 The dissociation constant 300 is sensitive to the density of target 7 in the solution and temperature.

【0011】 In figs. 3, and 4, those charges of the composite bodies 5 are

20 sparse on the surface of the oxide film 1 and then work as point charges. In

this regard, electrons flowing from the source electrode 2 to the drain electrode 3 can easily circumvent around the composite bodies 5, as shown in fig. 6. Thereby, if the electrons flowing from the source electrode 2 to the drain electrode 3 along a roundabout route, those composite bodies 5 exhibit
5 no impact on the electric current characteristics of the conventional semiconductor biosensor.

【0012】 Therefore, referring to fig. 7, another conventional semiconductor biosensor replaces the semiconductor substrate 4 with wide gate width with a semiconductor conducting wire 6 with narrow gate width.
10 Since electrons cannot circumvent around a composite body 5 while flowing through the semiconductor conducting wire 6, there is no roundabout route for the electrons flowing from the source electrode 2 to the drain electrode 3. Thus, the transport speed of those electrons is reduced in average and the electric current is suppressed. In theory, it may be possible to detect a sole
15 target 7 as long as we can sense this change in the electric current.

【0013】 In general, the change in electric current (ΔI_{ds}) flowing on the semiconductor surface of transistors is sensed as change in threshold voltage shift (ΔV_t). Depicting the transconductance g_m , the surface density of total charge carried by target 7 Q_x , the gate capacitance of transistor C , the
20 surface density of receptors 8 $[Y]$, the density of target 7 in solution $[X]$,

formula 1 is obtained with the cut-off to the background noise:

$$\frac{\Delta I_{ds}}{g_m} = \Delta V_t = \frac{Q_X}{C} [Y] \times \frac{[X]}{[X] + K} + (cut-off) \quad [\text{Formula 1}]$$

【0014】 The cut-off is predetermined for veiling the noise not related to biosensors and must be much smaller than any noise attributable to the biosensors.

【0015】 According to Formula 1, the limit of detection (LOD) is obtained as formula 2, where I_{noise} is the absolute value of the electric current caused by the noise attributable to the biosensors. (See M. A. Reed, IEEE IEDM13, pp. 208-211 (2013).)

$$LOD = \frac{K}{\left(\frac{Q_X [Y] / C}{I_{noise} / g_m - (cut-off)} \right)} \quad [\text{Formula 2}]$$

【0016】 According to Formula 2, it is found that LOD is made small as long as I_{noise} becomes small and is equal to the cut-off.

【0017】 As mentioned above, I_{noise} can be made small by using semiconductor conducting wires 6 to replace the semiconductor substrate 4. Specifically, referring to fig. 5, there are a plurality of conducting wires 6 in parallel between a common source 2 and a common drain 3. As example, there are three conducting wires 6, each of which can detect a sole composite body 5 on the surface of the oxide film 1. Then, it appears that the LOD is

made small.

【0018】 However, all of the conducting wires 6 are connected to the common drain 3, which indicates that the current signals from the conducting wires 6 are added. Once the signals are added up, it is impossible to distinguish signals from different conducting wires 6. Therefore, the LOD is not improved significantly.

SUMMARY OF THE INVENTION

【0019】 An objective of the present disclosure is to provide a semiconductor biosensor and a control method thereof with improved limit of detection.

【0020】 An embodiment of the semiconductor biosensors related to the present invention comprises a central reaction unit of a highly-precise very small inspection equipment, with the central reaction unit being able to be embedded into a semiconductor chip; and with the central reaction unit comprising: a plurality of semiconductor conducting wires; a common source, wherein one end of each conducting wire is connected to the common source; a plurality of non-volatile memory type transistors respectively connected to another end of each conducting wire; a plurality of sense-amplifiers respectively connected to the said non-volatile memory type transistors; a bit line controller analyzing signals sensed by the said sense-amplifiers and

managing the operation of the said non-volatile memory type transistors; an oxide film wrapping or covering the said conducting wires, and a plurality of receptors fixed on a surface of the said oxide film.

【0021】 A control method of the semiconductor biosensor comprises:
5 initializing the semiconductor biosensor by sensing output signals from the plurality of conducting wires by the plurality of sense-amplifiers, and then testing for conducting wires having wire-errors, wherein conducting wires with anomalous high resistance or snapped conducting wires are regards as conducting wires having said wire-errors; data-thinning the semiconductor
10 biosensor by selectively programming non-volatile type memory transistor connected to the conducting wires having said wire-errors; and exposing the semiconductor biosensor into a solution. In addition, the control method of the semiconductor biosensor, further comprising selectively tuning threshold voltages of the non-volatile memory type transistor connected to the
15 conducting wires without said wire-errors after said data-thinning but before exposing the semiconductor biosensor into the solution.

【0022】 In accordance to the above structure and method, it is made capable of producing a central reaction unit as a key device of the semiconductor biosensor to achieve highly-precise and very small inspection
20 equipment.

【0023】 Embodiments according to the present invention will be explained below with reference to the drawings. These embodiments are not intended to limit the present invention. The drawings schematically show practical devices and are not made to scale.

5

BRIEF DESCRIPTION OF THE DRAWINGS

【0024】 The illustrative embodiments may best be described by reference to the accompanying drawings where:

【0025】 Fig. 1 is a view illustrating a basic device structure of prior art biosensor.

10

【0026】 Fig. 2 is a view illustrating a basic device structure of prior art biosensor.

【0027】 Fig. 3 is a view illustrating a basic device structure of prior art biosensor.

15

【0028】 Fig. 4 is a view illustrating a basic device structure of prior art biosensor.

【0029】 Fig. 5 is a view illustrating a basic device structure of prior art biosensor;

【0030】 Fig. 6 is a view illustrating that electrons flow around charge in prior art biosensor;

20

【0031】 Fig. 7 is a view illustrating that electrons cannot flow

around charge in prior art biosensor;

【0032】 Fig. 8 is a view illustrating that receptors are attached on oxide surface and then targets moving in solution are caught by those receptors and immobilized;

5 【0033】 Fig. 9 is a view illustrating a basic component related to an embodiment of the present invention;

【0034】 Fig. 10 is a view illustrating a reaction of receptors and targets, which is related to an embodiment of the present invention;

10 【0035】 Fig. 11 is a view illustrating fabrication method of biosensor related to an embodiment of the present invention;

【0036】 Fig. 12 is a view illustrating fabrication method of biosensor related to an embodiment of the present invention;

【0037】 Fig. 13 is a view illustrating fabrication method of biosensor related to an embodiment of the present invention;

15 【0038】 Fig. 14 is a view illustrating equivalent circuit related to an embodiment of the present invention;

【0039】 Fig. 15 is a view illustrating that those receptors catch targets in equivalent circuit of biosensor related to an embodiment of the present invention;

20 【0040】 Fig. 16 is a view illustrating that signal electric current is

modulated with regard to charge carried by those targets in biosensor related to an embodiment of the present invention;

【0041】 Fig. 17 is a view illustrating simulation result of operation of biosensor related to an embodiment of the present invention;

5 【0042】 Fig. 18 is a view illustrating a method for correcting error modes of biosensor related to an embodiment of the present invention;

【0043】 Fig. 19 is a view illustrating a method for correcting error modes of biosensor related to an embodiment of the present invention;

10 【0044】 Fig. 20 is a view illustrating a method for correcting error modes of biosensor related to an embodiment of the present invention;

【0045】 Fig. 21 is a view illustrating fluctuation of diameter of semiconductor conducting wires;

【0046】 Fig. 22 is a view illustrating a method for correcting offset of biosensor related to an embodiment of the present invention.

15

DETAILED DESCRIPTION OF THE INVENTION

【0047】 Referring to fig. 8, an embodiment of the semiconductor biosensor related to the present invention is constituted of a central reaction unit 200 comprising semiconductor conducting wires 6, an oxide film 1 and
5 receptors 8, and the peripheral unit described below. The semiconductor conducting wires 6 can be thin conducting wires. Moreover, the semiconductor conducting wires 6 can be nanowires.

【0048】 The central reaction unit 200 is fabricated on the semiconductor substrate. The central reaction unit 200 is exposed into a
10 solution dissociating targets 7. The targets 7 having charge moves in the solution and then couples with receptors 8 attached to the surface of the oxide film 1 subject to the formula shown in fig. 10. The dissociation constant 300 determines the equilibrium state of the chemical reaction of the targets 7 and the receptors 8. When K is large, then receptors 8 and targets 7 are decoupled.
15 When K is small, then the receptors 8 and the targets 7 are coupled to form immobilized composite bodies 5.

【0049】 Referring to Fig. 9, the central reaction unit 200 further comprises a plurality of sense-amplifier 9 (S/A). One end of each conducting wire 6 is connected to a common source 2 and another end of each
20 conducting wire 6 is connected to each sense-amplifier 9. The number of the

sense-amplifier (M) is same with the number of the conducting wires 6 and the sense-amplifiers 9 are labeled from 0 to M-1, respectively.

【0050】 In this figure, there are three conducting wires 6, each of which can detect a sole composite body 5 on the surface of the oxide film 1.

5 The sense-amplifiers 9 corresponding to those conducting wires 6 can detect the reduction of current signal thanks to charges of those composite bodies 5.

The difference between the embodiment of the semiconductor biosensor related to the present invention and the conventional semiconductor biosensor shown in fig. 5 is that the common drain 3 was replaced with a

10 plurality of the sense-amplifiers 9 each of which is connected to one of the conducting wires 6 independently. By such arrangement, it is theoretically made possible to distinguish change in electric current from one of the conducting wires 6 attributable to a sole composite body 5, by not adding signals from every conducting wire 6 up.

15 【0051】 Next, the method for distinguishing signal from noise is described. There are M conducting wires 6 and M sense-amplifiers 9. The M sense-amplifiers 9 and the common source 2 are connected at the opposite side of the M conducting wires 6 as shown in Fig. 9. It is supposed that m conducting wires 6 of M ones can detect sole composite body 5 on the

20 surface of the oxide film 1 in a similar way. (In the example of fig. 9, $m = 3$.)

【0052】 If one conducting wire 6 does not detect any sole composite
 body 5 on the surface of the oxide film 1, the electric current that flows from
 the common source 2 to the sense-amplifier 9 that is connected to said wire 6
 is denoted as I_0 . On the other hand, if one conducting wire 6 detects a sole
 5 composite body 5 on the surface of the oxide film 1, the electric current that
 flows from the common source 2 to the sense-amplifier 9 that is connected to
 said wire 6 is denoted as I_1 . The electric current I_1 can be expressed as the
 sum of electric current I_0 and a difference ΔI between currents I_0 and I_1 .
 Namely, $I_1 = I_0 + \Delta I$. In this regard, if the conventional semiconductor
 10 biosensor is used for inspection, the common drain 3 will receive an electric
 current from each conducting wire 6 that has a magnitude of $I_0 + (m/M) \times \Delta I$
 in average. On the other hand, the sense-amplifier 9 of the biosensor in this
 embodiment, that is connected to the conducting wire 6 detecting the sole
 composite body 5 on the surface of the oxide film 1, is able to receive the
 15 electric current of $I_0 + \Delta I$. In other words, the sense-amplifier 9 in the
 embodiment is able to determine whether the conducting wire 6 detects the
 sole composite body 5 based on the electric current of $I_0 + \Delta I$. In contrast,
 the common drain 3 of the conventional biosensor can only determine
 whether a single conducting wire 6 detects the sole composite body 5 based
 20 on the electric current of $I_0 + (m/M) \times \Delta I$. The sense-amplifier 9 of the

application receives an extra amount of current of $\Delta I \times (1-m/M)$ in addition to the average current received by the conventional common drain 3. As such, the value of $(1-m/M)$ can serve as a standard for evaluating the level of improvement to the Limit of Detection (LOD) in the embodiment.

【0053】 The improving factor of LOD is given by Formula 3.

$$\varepsilon \cong 1 - \frac{m}{M} \quad [\text{Formula 3}]$$

【0054】 Accidental current change on the conducting wires 6 is a noise, which misleading the conducting wires 6 without composite body 5 to be considered as having one. Assuming the number of the conducting wires 6 with noise is δ . The noise is made ignorable as long as m is large enough compared with δ . The total number of conducting wires 6 (M) should be made larger, in order to enlarge m while not degrading the limit of detection. Thereby, the improved LOD by the present invention, Formula 4, is obtained.

$$\text{Improved } LOD = (1 - \varepsilon) \times LOD = \frac{m}{M} \times LOD \quad [\text{Formula 4}]$$

【0055】 In the example where the gate width of biosensor (i.e., the width of central reaction unit 200) is 2.4mm, the width of the conducting wire is 3nm in average, and the space between adjoining conducting wires 6 is 57 nm in average, there are 40,000 conducting wires 6. When the

improving factor ε (Formula 3) is 99.9%, m is 40. Indeed, there may be conducting wires 6 in which electric current is accidentally decreased. Namely, the possibility of the presence of the conducting wires 6 with noise is non-zero. However, the number of those conducting wires (δ) may be less than 40. When the improving factor is 99%, m is 400 which may further larger than δ . When the improving factor is 90%, m is 4000, which may much larger than δ . Even for a 90% improving factor, the improving ratio (m/M) may be large enough.

【0056】 The total number of the conducting wires 6 (M) is predetermined in the step of device design, which will be described below with an example of a fabrication method of the central reaction unit 200.

【0057】 In fig. 11, there is a SOI (Silicon-On-Insulator) film 10 with the thickness being 20nm as an example. This SOI film 10 is cut out to line 11 and space 12 in the lithography process, as illustrated in fig. 12. The width of the line 11 (L) and the width of the space 12 (S) are 30nm. The lines 11 correspond to semiconductor wires. By this way, a plurality of semiconductor wires 11 with cross-section being (30nm, 30nm, 20nm) in average are made.

【0058】 Next, an oxide film is compensated to the spaces 12, and then slim the semiconductor wires 11 by subsequent thermal processes (sliming process).

【0059】 As a result, conducting wires 6 with diameter being 3nm in average and spaces 12 with width being 57nm in average are layout, as illustrated in fig. 13. Subsequently, CMP (Chemical and Mechanical Process) and oxidization are preceded. A thin oxide film 1 is formed after planarization to perform as gate oxide. Furthermore, receptors 8 are fixed on the surface of the oxide film 1, and then central reaction unit 200 is made in fig. 8.

【0060】 Fig. 14 illustrates an equivalent circuit of the embodiment of the semiconductor biosensor related to the present invention. An end of conducting wire 6 is connected to a common source line (CSL) via a source select gate 20 (SGS). The other end is connected to the sense-amplifier 9 via a drain select gate 21 (SGD). The signal from each sense-amplifier 9 is analyzed by a bit line decoder 22.

【0061】 Fig. 15 is an illustration obtained by picking up a sole conducting wire 6 from the equivalent circuit and hiding the others in fig. 14. This is for paying attention to the operation of the conducting wire 6 related to the present invention. As an example, the source select gate 20 is an nMOSFET and the drain select gate 21 is a pMOSFET. In general, the four combinations of SGS 20 and SGD 21 are possible; for example, (nMOSFET and nMOSFET), (nMOSFET and pMOSFET), (pMOSFET and nMOSFET),

and (pMOSFET and pMOSFET).

【0062】 While both of the source select gate 20 and the drain select gate 21 are turned on, electron current is made flow from n-type diffusion layer of the source select gate 20 to the conducting wire 6 by applying drain
5 voltage via the sense-amplifier 9. It is noted that the conducting wires 6 generally exhibit low thermal conductivity if the diameter is very small, so the heating dissipation is made difficult for the conducting wires 6, which leads to self-heating effect. Thus, in order to cool the conducting wires 6 down, it is preferable to dissipate the heat to p-type diffusion layer of the
10 drain select gate 21 if the diameter is very small. Therefore, the drain select gate 21 can be a pMOSFET.

【0063】 The electric current flowing through conducting wire 6 is made of electrons flowing therein. If the charge stored by composite bodies 5 is negative, the signal sensed by sense-amplifier 9 is reduced by the charge.
15 Otherwise, the signal is increased by the charge.

【0064】 Fig. 16 is an illustration of the drain current (current sensed by the sense-amplifiers 9) with no composite body 5 attached on the conducting wire 6 ($N=0$) and with the composite bodies 5 having two electrons attached on the conducting wire 6 ($N=2$). To sense the difference in
20 current is to detect the existence of target 7.

【0065】 The result of device simulation with a different amount of composite bodies 5 attached to the conducting wire 6 is shown in fig. 17. The ratio of the current to that with no composite body 5; which is neutral ($N=0$), is plotted with respect to the number of electrons (n) stored in the composite body 5. As the number of electrons increasing, the ratio of the current is reduce to about half at $n=3$, or about 20% at $n=4$. It is able to detect the current change with this level of reduction with standard sense-amplifier.

【0066】 The EOT is the Equivalent Oxide Thickness of some dielectric film between the target 7 and the conducting wire 6, to which the thickness of the dielectric film is converted. The sensitivity is improved as EOT is decreased. It is preferable that EOT is less than 2nm from this simulation result.

【0067】 As illustrated in fig. 13, the production tolerance is not negligible in actually fabricated line-and-space structures. The resistivity of the conducting wire 6 is increased as the diameter of the conducting wire 6 becomes smaller; and is decreased as it becomes larger. This fluctuation of the diameter of the conducting wire 6 induces the noise contaminated into signals sensed by the sense-amplifiers 9.

【0068】 Referring to fig. 18 and 19, the resistance of conducting wires with diameter being too small 32 is high enough to make the signal

undistinguishable from noise. On the other hand, there may also be snapped
conducting wire 30. The snapped conducting wire 30 cannot conduct current,
and thus the signal from which is also undistinguishable from noise.

5 **【0069】** Figs. 18 and 19 illustrate a control method of the
semiconductor biosensor related to the present invention for dealing with the
production tolerance. In fig. 18, the drain select gate 21 is replaced with
non-volatile memory type transistor 31. On the other hand, in fig. 19,
non-volatile memory type transistor 31 is put between the drain select gate 21
and the sense-amplifier 9.

10 **【0070】** Firstly, as illustrated in fig. 20, the electric current is sensed
by the sense-amplifier 9 while the central reaction 200 unit is exposed into a
solution without target 7 or not exposed into any solution. This is the step of
Initialization. Conducting wires 6 with no sensible current are regarded as
conducting wires with diameter being too small 32 or as snapped conducting
15 wires 30. Then, non-volatile memory type transistor 31 related to those
conducting wires 6 is programmed. Since the programmed non-volatile
memory type transistors 31 are turned off, the data of those conducting wires
6 are not transferred to sense-amplifier 90. This is the step of Data Thinning.
After excluding the conducting wires with diameter being too small 32 and
20 snapped conducting wires 30, the left-behind conducting wires 6 are utilized

for testing by sensing the electric current via the sense-amplifiers 9. This is the step of Inspection.

5 **【0071】** In general, the operation of transistor composed of conducting wire 6 is more influenced by surface states than the conventional MOSFET is. It is because the surface to the volume is larger in conducting wire 6 than in a substrate constituting the conventional MOSFET. Thereby, more noise is contaminated to the signal through conducting wire 6 than the signal on the surface of the substrate. The cut-off shown in Formula 2 is determined with respect to the maximum amplitude of the noise.

10 **【0072】** The amplitude of noise through conducting wire 6 is sensitive to the diameter of conducting wire 6. As long as the cut-off is adequate, the amplitude of the noise is less than the limitation of control. Of course, the conducting wires with diameter being too small 32 or with anomalously high resistance may induce noise with amplitude out of the
15 limitation, so the conducting wires with diameter being too small 32 should be excluded.

【0073】 It is necessary to take the fluctuation (increase and the decrease) in the amplitude of the noise into consideration for adequately determining the cut-off.

20 **【0074】** In addition, as illustrated in fig. 21, there is fluctuation in

diameter even within a sole conducting wire 60, which is a characteristic of the conducting wire 6. It is also necessary to take the fluctuation in the diameter into consideration for adequately determining the cut-off.

【0075】 Since it is impossible to grasp fluctuation in the amplitude
5 of the noise or the fluctuation in the diameter when designing biosensor, it is necessary to tune the cut-off to suppress the impact of those fluctuations.

【0076】 In concrete, the system with non-volatile memory type transistor 31, constituting an exemplary embodiment related to the present invention and illustrated in figs. 18 and 19, is capable of adequately
10 determining the cut-off.

【0077】 In another embodiment of the control method of the semiconductor biosensor related to the present invention, as illustrated in fig. 22, the step of Offset Tuning 530 is appended next to the step of Data Thinning 410 in the flow chart illustrated in fig. 20. In this step, the
15 resistance of non-volatile memory type transistor 31 is tuned by arranging threshold voltage of the non-volatile memory type transistor 31, and thereby, suppressing the impact of fluctuation in the amplitude of the noise or the diameter

【0078】 The method to arrange threshold voltage of non-volatile
20 memory type transistor 31 is well-known as verify programming, in which

program-erase is repeated with small step (short pulse). (See T. Tanaka, et al., 1990 Symposium on VLSI circuits, pp. 105-106 (1990).)

5 **【0079】** By the embodiments of present invention, the limit of detection of biosensor is substantially improved, which result in the significant enhancement of performance of semiconductor biosensor and the drastic price reduction of medical healthcare chip. This enables early detection of disease, which has been impossible with the conventional biosensors, and then substantially reduces medical cost.

10 **【0080】** Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

15

WHAT IS CLAIMED IS:

1. A semiconductor biosensor, characterized in comprising:
 - a central reaction unit of an inspection equipment, with the central reaction unit being capable of being embedded into a semiconductor chip; and with the central reaction unit comprising:
 - a plurality of semiconductor conducting wires;
 - a common source, wherein one end of each conducting wire is connected to the common source;
 - a plurality of non-volatile memory type transistors respectively connected to another end of each conducting wire;
 - a plurality of sense-amplifiers respectively connected to the said non-volatile memory type transistors;
 - a bit line controller analyzing signals sensed by the said sense-amplifiers and managing the operation of the said non-volatile memory type transistors;
 - an oxide film wrapping or covering the said conducting wires, and
 - a plurality of receptors fixed on a surface of the said oxide film.
2. The semiconductor biosensor as claimed in claim 1, characterized in that the central reaction unit further comprises a plurality of drain select gate

transistors respectively connected between the said conducting wires and the said non-volatile memory type transistors.

3. A control method of the semiconductor biosensor as claimed in claim 1, characterized in comprising:

initializing the semiconductor biosensor by sensing output signals from the plurality of conducting wires by the plurality of sense-amplifiers, and then testing for conducting wires having wire-errors, wherein conducting wires with anomalously high resistance or snapped conducting wires are regards as conducting wires having said wire-errors;

data-thinning the semiconductor biosensor by selectively programming non-volatile type memory transistor connected to the conducting wires having said wire-errors; and

exposing the semiconductor biosensor into a solution.

4. The control method of the semiconductor biosensor as claimed in claim 3, characterized in further comprising selectively tuning threshold voltages of the non-volatile memory type transistor connected to the conducting wires without said wire-errors after said data-thinning and before exposing the semiconductor biosensor into the solution.

5. The control method of the semiconductor biosensor as claimed in claim 3, characterized in that testing for conducting wires having said

wire-errors comprises:

locating conducting wires with no sensible electric current according to the output signals sensed by the plurality of sense-amplifiers; and

regarding the conducting wires with no sensible current as conducting wires with anomalously high resistance or snapped conducting wires.

6. A control method of the semiconductor biosensor as claimed in claim 2, characterized in comprising:

initializing the semiconductor biosensor by sensing output signals from the plurality of conducting wires by the plurality of sense-amplifiers, and then testing for conducting wires having wire-errors, wherein conducting wires with anomalously high resistance or snapped conducting wires are regards as conducting wires having said wire-errors;

data-thinning the semiconductor biosensor by selectively programming non-volatile type memory transistor connected to the conducting wires having said wire-errors; and

exposing the semiconductor biosensor into a solution.

7. The control method of the semiconductor biosensor as claimed in claim 6, characterized in further comprising selectively tuning threshold voltages of the non-volatile memory type transistor connected to the conducting wires without said wire-errors after said data-thinning and before

exposing the semiconductor biosensor into the solution.

8. The control method of the semiconductor biosensor as claimed in claim 6, characterized in that testing for conducting wires having said wire-errors comprises:

locating conducting wires with no sensible electric current according to the output signals sensed by the plurality of sense-amplifiers; and

regarding the conducting wires with no sensible current as conducting wires with anomalous high resistance or snapped conducting wires.