CLAIMS

1. A method for performing an inter-system payment operation, wherein the method comprises:

mapping a relationship between a source system account and a target system account, the source system account being an account in a source system, the target system account being an account in a target system, the source system and the target system being two separate payment systems;

receiving, by a service platform, a first payment request sent by the source system, wherein the first payment request comprises the source system account and a target system identifier, the target system identifier uniquely identifying the target system;

retrieving the target system account from a predetermined storage unit based on the relationship between the source system account and the target system account, and the target system identifier;

sending the first payment request and the target system account to the target system, wherein upon receipt, the target system performs a payment operation corresponding to the first payment request on the target system account without requiring any password verification; and

receiving a first execution result returned by the target system, and forwarding the first execution result to the source system.

2. The method according to claim 1,wherein the step of mapping a relationship between a source system account and a target system account comprises the following steps:

receiving a second payment request sent by the source system, wherein the second payment request comprises the source system account and the target system identifier ;

sending the second payment request to the target system based on the target system identifier, so as to load a login interface of the target system, and perform verification on the account and password information of the target system that are received from the login interface;

receiving a second execution result that is returned after the target system performs a payment operation corresponding to the second payment request when the verification passes, wherein the second execution result comprises the target system account; and

storing the relationship between the source system account and the target system account in the predetermined storage unit.

3. The method according to claim 2, wherein storing the relationship between the source system account and the target system account in the predetermined storage unit comprises:

sending the second execution result to the source system;

transmitting a message to the source system indicating that the source system account and the target system account are to be bound, and

in response to transmitting the message, generating a storage instruction for the service system indicating that the source system account and the target system account are to be bound; and

storing the mapping relationship between the source system account and the target system account in the predetermined storage unit based on the storage instruction.

4. A system for performing an inter-system payment operation, wherein the system comprises a plurality of modules configured to perform the method of any one of claims 1 to 3.