

DESCRIPTION

MULTI-STAGE SEAWATER DESALINATION APPARATUS AND OPERATION CONTROL METHOD OF MULTI-STAGE SEAWATER DESALINATION 5 APPARATUS

TECHNICAL FIELD

[0001] The present invention relates to a multi-stage
seawater desalination apparatus that can obtain high-
10 quality product water from seawater using a reverse osmosis
method, and an operation control method of the multi-stage
seawater desalination apparatus.

BACKGROUND ART

15 [0002] Conventional methods for obtaining fresh water
from seawater include an evaporation method in which
seawater is evaporated, and a reverse osmosis method in
which fresh water is obtained by filtering seawater through
a filtration membrane called a reverse osmosis membrane (RO
20 membrane) by applying pressure to the seawater,
concentrating the salt in the seawater, and discarding
thereof.

The latter reverse osmosis method is energy efficient
compared to the evaporation method. However, in the
25 reverse osmosis method, a careful pretreatment (treatment
with an "ultrafilter membrane (UF membrane)" or a
"microfilter membrane (MF membrane)" for removing suspended
matters in seawater, or raw water) is required to prevent
the RO membrane from being clogged by microbes and deposits
30 in seawater, and the maintenance and the like is expensive.

[0003] It is also difficult to obtain water quality as
good as that produced by the evaporation method. To obtain
highly purified water quality, a plurality of stages of

reverse osmosis devices needs to be combined.

Fig. 10 is a schematic of a multi-stage seawater desalination apparatus of a conventional reverse osmosis method.

5 As shown in Fig. 10, a conventional multi-stage seawater desalination apparatus 100 includes a high-pressure pump P_1 that increases the pressure of raw water (seawater) 101 from which suspended matters are removed by pretreatment to a predetermined high pressure, a high-
10 pressure reverse osmosis device 103 that includes a high-pressure reverse osmosis membrane 103a for concentrating a salt content in high-pressure feed water 102 whose pressure is increased by the high-pressure pump P_1 , an intermediate tank 110 that temporarily stores therein permeated water
15 104 that has passed through the high-pressure reverse osmosis device 103, a low-pressure pump P_2 that reduces the pressure of the permeated water 104 supplied from the intermediate tank 110 to a predetermined low pressure, and a low-pressure reverse osmosis device 106 that has a low-
20 pressure reverse osmosis membrane 106a for concentrating a salt content in low-pressure feed water 105 whose pressure is reduced by the low-pressure pump P_2 , and obtains product water (fresh water) 107. Because the pressure in the intermediate tank 110 is returned to normal, the pressure
25 is released. While the system is stopped, pH of the permeated water 104 is adjusted, by adding a pH adjusting agent 111, thereby preventing microbial contamination (see Non-Patent Document 1 "Fukuoka District Waterworks Agency: Mechanism of Seawater Desalination").

30 Fig. 10 is a schematic of concentrated water 103b from the high-pressure reverse osmosis device 103, and concentrated water 106b from the low-pressure reverse osmosis device 106.

[0004] [Non-Patent Document 1] "Fukuoka District
Waterworks Agency: Mechanism of Seawater Desalination"
URL:[http://www.f-
suiki.or.jp/seawater/facilities/mechanism.php](http://www.f-suiki.or.jp/seawater/facilities/mechanism.php)

5 DISCLOSURE OF INVENTION

PROBLEM TO BE SOLVED BY THE INVENTION

[0005] Conventionally, to combine the plurality of
stages of reverse osmosis devices, as shown in Fig. 10, the
operation is normally performed by placing the intermediate
10 tank 110 between the devices. However, because the
intermediate tank 110 is likely a cause of microbial
contamination, the pH adjusting agent 111 needs to be added
constantly.

At the start-up, the permeated water 104 to which the
15 pH adjusting agent 111 is added needs to be discarded.
This is a problem, because the conversion rate of the
product water 107 is reduced as much as the amount being
discarded.

Another problem is that the product water 107 cannot
20 be supplied at the right timing of the system start-up,
corresponding to the discard.

[0006] Accordingly, elimination of the intermediate tank
110 may be considered. When the plurality of stages is
combined, the salt concentration of the concentrated water
25 106b at the subsequent stage (low-pressure reverse osmosis
device 106) is lower than the salt concentration of the
high-pressure feed water 102 at the preceding stage.
Consequently, when a circulation operation in which the
concentrated water 106b at the subsequent stage is returned
30 to the side of the feed water at the preceding stage is
performed, the salt concentration at the side of the high-
pressure feed water 102 becomes low, thereby reducing the
osmotic pressure, and reducing the operating pressure. As

a result, when the reverse osmosis devices are directly connected without interposing the intermediate tank 110 therebetween, the pressure fluctuations at the start-up is large, thereby preventing a stable start-up operation.

5 [0007] In a combined system in which the high-pressure RO membrane 103a with chlorine-resistance is provided at the preceding stage and an RO membrane without chlorine-resistance is provided at the subsequent stage, it is difficult to carry out chlorination at the preceding stage,
10 when the concentrated water 106b at the subsequent stage is returned to the side of the high-pressure feed water 102 at the preceding stage.

[0008] In isolated islands and desert regions where seawater desalination apparatuses are to be installed, a
15 desalination technology that can stably supply a large amount of product water (2000 t/day to 5000 t/day) is required.

The water used in chemical plants and the like built in the desert regions may be required to have higher
20 quality and less salt content (such as pure water whose salt concentration is equal to or less than 5 parts per million) than that of drinking water (salt concentration is equal to or less than 250 parts per million).

[0009] Accordingly, in the reverse osmosis method
25 including a plurality of stages of RO membranes, a multi-stage seawater desalination apparatus that can obtain water quality as good as that produced by the evaporation method, that can prevent microbial contamination by eliminating the intermediate tank, and that enables serial start-up and
30 operation has been much demanded.

[0010] The present invention is made in view of the above circumstances and intended to provide a multi-stage seawater desalination apparatus in series that can obtain

high-quality product water from seawater using a reverse osmosis method and an operation control method of the multi-stage seawater desalination apparatus.

5 MEANS FOR SOLVING PROBLEM

[0011] According to an aspect of the present invention, a multi-stage seawater desalination apparatus includes: a high-pressure pump that is mounted on a raw water line through which raw water is supplied, and increases pressure
10 of the raw water to a predetermined high pressure; a high-pressure reverse osmosis device that includes a high-pressure reverse osmosis membrane for concentrating a salt content in high-pressure feed water whose pressure is increased by the high-pressure pump; a first drain valve
15 that is mounted on a permeated water line through which permeated water that has passed through the high-pressure reverse osmosis device is supplied downstream, and temporarily drains the permeated water of an initial start-up; a low-pressure pump that is mounted on the permeated
20 water line provided downstream of the first drain valve, and reduces pressure of the permeated water to a predetermined low pressure; a low-pressure reverse osmosis device that includes a low-pressure reverse osmosis membrane for concentrating a salt content in low-pressure
25 feed water whose pressure is reduced by the low-pressure pump; and a second drain valve that is mounted on a discharge line on a concentrated water side of the low-pressure reverse osmosis device, and temporarily discharges the low-pressure feed water of the initial start-up
30 supplied to the low-pressure reverse osmosis device.

[0012] Advantageously, the multi-stage seawater desalination apparatus further includes a plurality of the low-pressure reverse osmosis devices. The second drain

valve is mounted on the discharge line at the concentrated water side of each of the low-pressure reverse osmosis devices, and temporarily discharges the low-pressure feed water of the initial start-up supplied to the low-pressure reverse osmosis devices.

[0013] Advantageously, the multi-stage seawater desalination apparatus further includes a returned concentrated water line that returns the concentrated water from the low-pressure reverse osmosis device upstream.

10 [0014] Advantageously, in the multi-stage seawater desalination apparatus, the high-pressure reverse osmosis device is a membrane with chlorine-resistance.

[0015] According to another aspect of the present invention, an operation control method of a multi-stage seawater desalination apparatus that uses the multi-stage seawater desalination apparatus described above, at an initial start-up of the multi-stage seawater desalination apparatus, includes: a step of supplying raw water to the high-pressure reverse osmosis device; a step of temporarily draining permeated water that has passed through the high-pressure reverse osmosis membrane of the high-pressure reverse osmosis device through the first drain valve; a step of supplying a whole amount of the permeated water to a side of the low-pressure reverse osmosis device, while closing the first drain valve, when a pressure of the permeated water has reached a pressure around an inlet pressure of the low-pressure pump; a step of temporarily draining low-pressure feed water of the initial start-up supplied to the low-pressure reverse osmosis device through the second drain valve; and a step of producing product water by making the low-pressure feed water pass through the low-pressure reverse osmosis membrane while closing the second drain valve, and switching operation to a rated

seawater desalination operation.

[0016] According to still another aspect of the present invention, an operation control method of a multi-stage seawater desalination apparatus that uses the multi-stage seawater desalination apparatus described above, during a sterilization operation of the high-pressure reverse osmosis device of the multi-stage seawater desalination apparatus, includes: a step of supplying raw water to which chlorine (Cl) is added is supplied to the high-pressure reverse osmosis device without feeding a reducing agent from a first reducing agent supplying unit; a step of temporarily draining low-pressure feed water including a reducing agent through the second drain valve, after the reducing agent is added to permeated water with chlorine that has passed through the high-pressure reverse osmosis membrane of the high-pressure reverse osmosis device from a second reducing agent supplying unit; a step of switching operation to a normal operation, by adding a reducing agent from the first reducing agent supplying unit to the raw water, and stopping addition of the reducing agent from the second reducing agent supplying unit, after a predetermined sterilization operation is finished; and a step of producing product water, by switching operation to a rated seawater desalination operation, while closing the second drain valve.

[0017] Advantageously, in the operation control method of a multi-stage seawater desalination apparatus, concentrated water at a low pressure side is returned upstream through a returned concentrated water line, after the sterilization operation is finished.

[0018] According to still another aspect of the present invention, an operation control method of a multi-stage seawater desalination apparatus that uses the multi-stage

seawater desalination apparatus described above, during a sterilization operation of the high-pressure reverse osmosis device of the multi-stage seawater desalination apparatus, includes: a step of supplying raw water to which
5 chlorine (Cl) is added to the high-pressure reverse osmosis device without feeding a reducing agent from a first reducing agent supplying unit; a step of neutralizing permeated water with chlorine that has passed through the high-pressure reverse osmosis membrane of the high-pressure
10 reverse osmosis device, by adding a reducing agent less than a neutralization equivalent from a second reducing agent supplying unit, and then supplying rest of the reducing agent for neutralizing to low-pressure feed water, while measuring an oxidation-reduction potential thereof
15 with an oxidation-reduction potential meter; a step of producing product water by making the low-pressure feed water pass through the low-pressure reverse osmosis membrane; and a step of producing product water by switching operation to a rated seawater desalination
20 operation, after the sterilization operation is finished.
[0019] Advantageously, in the operation control method of a multi-stage seawater desalination apparatus, concentrated water at a low pressure side is returned upstream through a returned concentrated water line during
25 the sterilization operation and the rated operation.

EFFECT OF THE INVENTION

[0020] With the present invention, in a reverse osmosis method having a plurality of stages of RO membranes, it is
30 possible to obtain water quality as good as that is produced by the evaporation method, prevent microbial contamination occurred when the system is stopped by eliminating the intermediate tank, and perform serial

start-up and operation.

BRIEF DESCRIPTION OF DRAWINGS

- [0021] [Fig. 1] Fig. 1 is a schematic of a multi-stage
5 seawater desalination apparatus according to a first
embodiment.
- [Fig. 2] Fig. 2 is a process chart of the multi-stage
seawater desalination apparatus according to the first
embodiment.
- 10 [Fig. 3A] Fig. 3A is an operational schematic of the
multi-stage seawater desalination apparatus according to
the first embodiment at Step 2.
- [Fig. 3B] Fig. 3B is an operational schematic of the
multi-stage seawater desalination apparatus according to
15 the first embodiment at Steps 3 and 4.
- [Fig. 3C] Fig. 3C is an operational schematic of the
multi-stage seawater desalination apparatus according to
the first embodiment at Step 5.
- [Fig. 4] Fig. 4 is a schematic of a multi-stage seawater
20 desalination apparatus according to a second embodiment.
- [Fig. 5] Fig. 5 is a schematic of a multi-stage seawater
desalination apparatus according to a third embodiment.
- [Fig. 6A] Fig. 6A is an operational schematic of the
multi-stage seawater desalination apparatus according to
25 the third embodiment at Steps 1 and 2.
- [Fig. 6B] Fig. 6B is an operational schematic of the
multi-stage seawater desalination apparatus according to
the third embodiment at Step 3.
- [Fig. 7] Fig. 7 is a schematic of a multi-stage seawater
30 desalination apparatus according to a fourth embodiment.
- [Fig. 8] Fig. 8 is an illustration of variation of
oxidation-reduction potential (ORP) when a reducing agent
(SBS) is added.

[Fig. 9] Fig. 9 is a schematic of a multi-stage seawater desalination apparatus according to a fifth embodiment.

[Fig. 10] Fig. 10 is a schematic of a multi-stage seawater desalination apparatus according to a conventional example.

5

BEST MODE(S) FOR CARRYING OUT THE INVENTION

[0022] Exemplary embodiments of the present invention will be described in detail with reference to the accompanying drawings. However, the present invention is not limited by the embodiments. Constituting elements in the embodiments include elements that can be easily conceived by those skilled in the art, or elements being substantially the same as those elements.

[First Embodiment]

15 [0023] A multi-stage seawater desalination apparatus according to a first embodiment of the present invention is described with reference to the accompanying drawings.

Fig. 1 is a schematic of the multi-stage seawater desalination apparatus according to the first embodiment.

20 As shown in Fig. 1, this multi-stage seawater desalination apparatus 10A according to the present embodiment includes a high-pressure pump P_1 that increases the pressure of raw water 11 to a predetermined high pressure and is mounted on a raw water line L_1 through which raw water (such as seawater) 11 is supplied, a high-pressure reverse osmosis device 13 that includes a high-pressure reverse osmosis membrane (high-pressure RO membrane) 13a for concentrating a salt content in high-pressure feed water 12 whose pressure is increased by the high-pressure pump P_1 , a first drain valve 21 that temporarily drains permeated water 14 of the initial start-up through a discharge line L_6 and is mounted on a permeated water line L_2 through which the permeated water

25

30

14 that has passed through the high-pressure reverse osmosis device 13 is supplied downstream, a low-pressure pump P_2 that reduces the pressure of the permeated water 14 to a predetermined low pressure and is mounted on a
5 permeated water line L_3 provided downstream of the first drain valve 21, a low-pressure reverse osmosis device 16 that has a low-pressure reverse osmosis membrane (low-pressure RO membrane) 16a for concentrating a salt content in low-pressure feed water 15 whose pressure is reduced by
10 the low-pressure pump P_2 , and a second drain valve 22 that temporarily discharges the low-pressure feed water 15 of the initial start-up supplied to the low-pressure reverse osmosis device 16 and is mounted on a discharge line L_5 at the concentrated water side of the low-pressure reverse
15 osmosis device 16.

To filter the raw water 11, the pretreatment may be carried out by using an ultrafilter membrane (UF membrane), a microfilter membrane (MF membrane), or the like, that removes suspended matters in seawater, similar to the
20 conventional manner.

In Fig. 1, the reference numeral 13b denotes concentrated water from the high-pressure reverse osmosis device 13, the reference numeral 16b denotes concentrated water from the low-pressure reverse osmosis device 16, and
25 the reference numeral 18 denotes a switch valve that switches the flow path of product water 17a having a value equal to or less than a defined value and is mounted on a product water line L_7 .

In the present embodiment, a three-way valve is used
30 for the first and the second drain valves 21 and 22.

However, the present invention is not limited thereto.

[0024] To start the system by using the multi-stage seawater desalination apparatus 10A, the system is started

by the following procedure.

Fig. 2 is the process chart.

5 <Step 1> At Step 1, at the initial start-up of the system, the raw water 11 is supplied to the high-pressure reverse osmosis device 13 through the high-pressure pump P_1 (S-1). At this time, the concentrated water 13b is discharged outside through a concentrated water line L_4 .

10 <Step 2> At Step 2, the permeated water 14 that has passed through the high-pressure reverse osmosis membrane 13a of the high-pressure reverse osmosis device 13 is temporarily drained from the discharge line L_6 through the first drain valve 21 (S-2: see Fig. 3A).

15 <Step 3> At Step 3, when the pressure of the permeated water 14 that passed through the first drain valve 21 has reached the pressure around the inlet pressure of the low-pressure pump P_2 , the whole amount of the permeated water 14 having a predetermined pressure is supplied to the side of the low-pressure reverse osmosis device 16 through the low-pressure pump P_2 , while closing
20 the first drain valve 21 (S-3: see Fig. 3B).

 <Step 4> At Step 4, the low-pressure feed water 15 of the initial start-up supplied to the low-pressure reverse osmosis device 16 is temporarily drained through the second drain valve 22 (S-4: see Fig. 3B).

25 <Step 5> At Step 5, when the pressure of the low-pressure feed water 15 has reached a predetermined permeate pressure of the low-pressure RO membrane 16a of the low-pressure reverse osmosis device 16, the low-pressure feed water 15 is passed through the low-pressure reverse osmosis
30 membrane 16a, while closing the second drain valve 22. By switching operation to the rated seawater desalination operation, product water 17 is produced (S-5: see Fig. 3C).

[0025] In this manner, when the plurality of stages

(two-stage in the present embodiment) of RO device is connected directly, the permeated water 14 is drained through the first drain valve 21, and waits until the pressure of the permeated water 14 reaches a predetermined pressure at the inlet pressure of the low-pressure pump P_2 . When it is confirmed that the pressure of the permeated water 14 has reached the pressure around the inlet pressure of the low-pressure pump P_2 , the whole amount of the low-pressure feed water 15 is supplied to the side of the low-pressure reverse osmosis device 16, while closing the first drain valve 21.

The low-pressure feed water 15 of the initial start-up supplied to the low-pressure reverse osmosis device 16 is then temporarily drained through the second drain valve 22, and waits until the pressure of the low-pressure feed water 15 reaches the permeate pressure of the low-pressure RO membrane 16a of the low-pressure reverse osmosis device 16.

When it is confirmed that the pressure of the low-pressure feed water 15 has reached near the permeate pressure of the low-pressure RO membrane 16a of the low-pressure reverse osmosis device 16, the low-pressure feed water 15 is passed through the low-pressure reverse osmosis membrane 16a, while closing the second drain valve 22. By switching operation to the rated seawater desalination operation, the product water 17 is produced.

Accordingly, even if the conventional intermediate tank is not installed, it is possible to prevent the pressure fluctuations at the initial start-up, and constantly perform start-up operation in a stable manner.

[Second Embodiment]

[0026] Fig. 4 is a schematic of a multi-stage seawater desalination apparatus according to a second embodiment. The same reference numerals are given to the same elements

as those in the multi-stage seawater desalination apparatus in Fig. 1, and their repeated descriptions will be omitted.

As shown in Fig. 4, this multi-stage seawater desalination apparatus 10B according to the present embodiment returns the concentrated water 16b concentrated by the low-pressure reverse osmosis device 16 in the multi-stage seawater desalination apparatus 10A according to the first embodiment to the raw water line L_1 through a returned concentrated water line L_8 .

Accordingly, product water can be obtained again by reconcentrating those discarded as the concentrated water, thereby reducing the amount of discarded concentrated water and increasing the amount of product water.

[0027] To start the system by using the multi-stage seawater desalination apparatus 10B, the system is started by the following procedure.

<Step 1> At Step 1, at the initial start-up of the system, the raw water 11 is supplied to the high-pressure reverse osmosis device 13 through the high-pressure pump P_1 . At this time, the concentrated water 13b is discharged outside through the concentrated water line L_4 . Because the pressure of the concentrated water 13b is high, the energy is collected by driving a turbine T.

<Step 2> At Step 2, the permeated water 14 that has passed through the high-pressure reverse osmosis membrane 13a of the high-pressure reverse osmosis device 13 is temporarily drained from the discharge line L_6 through the first drain valve 21.

<Step 3> At Step 3, when the pressure of the permeated water 14 has reached the pressure around the inlet pressure of the low-pressure pump P_2 , the whole amount of the permeated water 14 is supplied to the side of the low-pressure reverse osmosis device 16 through the low-

pressure pump P_2 , while closing the first drain valve 21.

<Step 4> At Step 4, the low-pressure feed water 15 of the initial start-up supplied to the low-pressure reverse osmosis device 16 is temporarily drained through the second
5 drain valve 22.

<Step 5> At Step 5, when the pressure of the low-pressure feed water 15 has reached the permeate pressure of the low-pressure RO membrane 16a of the low-pressure reverse osmosis device 16, the low-pressure feed water 15
10 is passed through the low-pressure reverse osmosis membrane 16a, while closing the second drain valve 22. By switching operation to the rated seawater desalination operation, the product water 17 is produced

<Step 6> At Step 6, after a predetermined rated
15 concentration operation is carried out in the low-pressure reverse osmosis device 16, the concentrated water 16b is returned to the raw water line L_1 through the returned concentrated water line L_8 , as returned concentrated water 26, while adjusting a flowmeter FC and a switching valve 25.

20 [0028] Accordingly, because the concentrated water is not simply returned as the returned concentrated water 26, the concentrated water 16b can be returned to the side of the raw water 11 from the low-pressure reverse osmosis device 16 at the subsequent stage. Consequently, it is
25 possible to prevent the reduction of the operating pressure, due to the reduced osmotic pressure.

[0029] With the first and the second embodiments, it is possible to provide water quality as good as that is produced by the evaporation method, and because the
30 intermediate tank is eliminated, it is possible to significantly reduce microbial contamination.

[Third Embodiment]

[0030] Fig. 5 is a schematic of a multi-stage seawater

desalination apparatus according to a third embodiment.
The same reference numerals are given to the same elements
as those in the multi-stage seawater desalination
apparatuses in Figs. 1 and 4, and their repeated
5 descriptions will be omitted.

As shown in Fig. 5, this multi-stage seawater
desalination apparatus 10C according to the present
embodiment disposes the high-pressure RO membrane 13a with
chlorine-resistance in the high-pressure reverse osmosis
10 device 13, and disposes the low-pressure RO membrane 16a
without chlorine-resistance in the low-pressure reverse
osmosis device 16, in the multi-stage seawater desalination
apparatus 10B according to the second embodiment. After a
predetermined period of operation, addition of a reducing
15 agent 32 that neutralizes the chlorine in the raw water 11
is stopped, and sterilization is carried out for a
predetermined period of time, by using the chlorine in the
raw water. Accordingly, high-quality product water can be
obtained in a stable manner.

20 In the present embodiment, a cellulose acetate
membrane is used as the high-pressure RO membrane 13a with
chlorine-resistance. A polyamide membrane is used as the
low-pressure RO membrane 16a without chlorine-resistance.

[0031] As shown in Fig. 5, during a normal operation,
25 the reducing agent 32 is supplied to the raw water line L₁
from a first reducing agent supplying unit 31-1, to
neutralize chlorine.

In this case, the reducing agent 32 is not supplied to
the permeated water line L₂ from a second reducing agent
30 supplying unit 31-2.

SBS may be used as the reducing agent 32. However,
the present invention is not limited thereto.

At the initial operation, the operation is started as

the first embodiment, and the rated operation is being continued.

[0032] A first sterilization operation mode to carry out sterilization treatment will now be explained.

5 Figs. 6A and 6B are the sterilization operation mode (first mode).

As shown in Fig. 6A, at Step 1, raw water 11_{C1} to which chlorine (Cl) is added, is supplied to the high-pressure reverse osmosis device 13, without feeding the
10 reducing agent 32 from the first reducing agent supplying unit 31-1 (Step 1).

At Step 2, permeated water 14_{C1} with chlorine that has passed through the high-pressure reverse osmosis membrane 13a of the high-pressure reverse osmosis device 13 is
15 neutralized by adding the reducing agent (SBS) 32 from the second reducing agent supplying unit 31-2. The permeated water 14 is then passed through the low-pressure RO membrane 16a of the low-pressure reverse osmosis device 16, and low-pressure feed water 15_{SBS} with the reducing agent
20 (SBS) 32 is temporarily drained through the second drain valve 22 (Step 2). At Step 2, the low-pressure feed water 15_{SBS} includes the reducing agent. Accordingly, the low-pressure feed water 15_{SBS} is stopped from being returned to the side of the raw water 11 through the returned
25 concentrated water line L₈, by switching the switching valve 25. This is to prevent the reducing agent from being supplied to the raw water, and interfering with the sterilization operation.

As shown in Fig. 6B, at Step 3, after a predetermined
30 sterilization is being operated, the reducing agent 32 is added to the raw water 11_{C1} from the first reducing agent supplying unit 31-1, and the addition of the reducing agent 32 from the second reducing agent supplying unit 31-2 is

stopped, thereby switching operation to a normal operation (Step 3).

At Step 4, while closing the second drain valve 22, the product water 17 is produced, by switching operation to the rated seawater desalination operation (Step 4).

The low-pressure reverse osmosis device 16 is interposed between oxidation-reduction potential (ORP) meters 41-1 and 41-2, and the oxidation-reduction potential of the low-pressure feed water 15 is measured thereby.

The period of time for the sterilization treatment may be modified suitably according to the equipment and the operation load. As an example, after six hours to ten hours of operation, chlorination sterilization is carried out for about an hour.

After the sterilization is complete, the concentrated water at the low-pressure side is returned upstream through the returned concentrated water line L_8 as the returned concentrated water 26.

In this manner, by chlorination sterilizing every time the apparatus is operated for a predetermined period of time, it is possible to sterilize the membranes, and to constantly produce clean product water equal to or higher than a certain level of quality.

[Fourth Embodiment]

[0033] Fig. 7 is a schematic of a multi-stage seawater desalination apparatus according to a fourth embodiment. The same reference numerals are given to the same elements as those in the multi-stage seawater desalination apparatus in Fig. 5, and their repeated descriptions will be omitted.

[0034] The present embodiment is a second sterilization operation mode to carry out sterilization treatment.

Fig. 7 is the sterilization operation mode (second mode). As shown in Fig. 7, this multi-stage seawater

desalination apparatus 10D according to the present embodiment operates the oxidation-reduction potential (ORP) meter in the multi-stage seawater desalination apparatus 10C according to the third embodiment, and produces product
5 water also during the sterilization treatment.

As shown in Fig. 7, the following steps are executed during the sterilization operation of the high-pressure reverse osmosis device of the multi-stage seawater desalination apparatus.

10 At Step 1, the raw water 11_{C1} to which chlorine (Cl) is added is supplied to the high-pressure reverse osmosis device 13, without feeding the reducing agent 32 from the first reducing agent supplying unit 31-1 (Step 1).

At Step 2, the reducing agent (SBS) 32 less than the
15 neutralization equivalent is added to the permeated water 14_{C1} with chlorine that has passed through the high-pressure reverse osmosis membrane 13a of the high-pressure reverse osmosis device 13, from the second reducing agent supplying unit 31-2. The rest of reducing agent 32 for
20 neutralizing is then supplied to the low-pressure feed water 15 from a third reducing agent supplying unit 31-3, while measuring the oxidation-reduction potential with the oxidation-reduction potential (ORP) meter 41-1 (Step 2).

The reasons for taking such measures are as follows:

25 To remove chlorine in the permeated water 14_{C1} of the high-pressure reverse osmosis device 13, the reducing agent 32 is supplied in excess by the first reducing agent supplying unit 31-1, from the safety point of view.

The ORP meter 41-1 indicates a large value, when
30 chlorine is present. However, it is difficult to determine the supplied amount of reducing agent, after the chlorine is removed.

Fig. 8 illustrates the variation of ORP when a

reducing agent (SBS) is added to the water with a chlorine concentration of 0.3 parts per million at the exit.

As shown in Fig. 8, the ORP value is high when a large amount of chlorine is present. The ORP value is low, if
5 chlorine is not present (minus).

Accordingly, when the chlorine has been consumed, the measurement of the concentration of reducing agent is difficult, even if the reducing agent is supplied in excess. The is because, when the product water 17 is produced while
10 a large amount of reducing agent 32 is supplied, the produced product water 17 includes a large amount of reducing agent, compared to the product water produced during the normal operation. To prevent this from happening, in the third embodiment, the low-pressure feed
15 water 15_{SBS} with reducing agent is drained through the second drain valve 22 (Step 2 of the third embodiment: see Fig. 6A).

[0035] Alternatively, in the present embodiment, the supply of the reducing agent is monitored with the
20 oxidation-reduction potential meter 41-1, and the value is controlled within a high sensitivity area (at this time, 200 millivolts to 400 millivolts). A certain amount (at this time, approximately 1 part per million) of the reducing agent 32 is then supplied by the third reducing
25 agent supplying unit 31-3 including a metering pump. Accordingly, the chlorine can be completely removed, and the reducing agent can be prevented from being oversupplied.

In this manner, the supply of the reducing agent can be suitably managed, and the product water with an
30 extremely low amount of reducing agent can also be produced during the sterilization operation.

[Fifth Embodiment]

[0036] Fig. 9 is a schematic of a multi-stage seawater

desalination apparatus according to a fifth embodiment.

The same reference numerals are given to the same elements as those in the multi-stage seawater desalination apparatus in Fig. 1, and their repeated descriptions will be omitted.

5 As shown in Fig. 9, this multi-stage seawater desalination apparatus 10E according to the present embodiment includes two stages of the low-pressure reverse osmosis device 16 (low-pressure reverse osmosis device 16-1 and low-pressure reverse osmosis device 16-2) in the multi-stage seawater
10 desalination apparatus 10A according to the first embodiment.

The concentrated water concentrated by the first low-pressure reverse osmosis device 16-1 is returned to the raw water line L_1 through the returned line L_8 as returned
15 concentrated water 26-1, and the concentrated water concentrated by the second low-pressure reverse osmosis device 16-2 is returned to the permeated water line L_3 through a returned concentrated water line L_{12} as returned concentrated water 26-2.

20 In Fig. 9, 15-1 and 15-2 denote low-pressure feed water, 21-1 and 21-2 denote first drain valves, 22-1 and 22-2 denote second drain valves, 25-1 and 25-2 denote switching valves, L_9 denotes a low-pressure water transmission line, L_{10} denotes a discharge line, and L_{11}
25 denotes a discharge line.

[0037] At the initial start-up of the system, the first low-pressure reverse osmosis device 16-1 is operated, and when a predetermined pressure is reached, the low-pressure feed water 15-2 is supplied to the second low-pressure
30 reverse osmosis device 16-2, while draining the low-pressure feed water 15-1 through the first drain valve 21-1. When a predetermined pressure is reached at the first drain valve 21-2, the product water 17 is produced by the second

low-pressure reverse osmosis device 16-2.

[0038] In the present embodiment, if the flow rate of the raw water 11 is "100", the raw water 11 with the flow rate of "104" is supplied to the high-pressure reverse osmosis device 13, because the returned concentrated water 26-1 is returned.

The permeated water 14 with the flow rate of "44" passes through the high-pressure RO membrane 13a of the high-pressure reverse osmosis device 13, and the concentrated water 13b with the flow rate of "60" is supplied to the side of the turbine T as high-pressure discharge water, where the energy is collected.

Permeated water 19 with the flow rate of "40" passes through the low-pressure RO membrane 16a of the first low-pressure reverse osmosis device 16-1, and the concentrated water with the flow rate of "4" is returned to the raw water 11 as the returned concentrated water 26-1 as discharge water, and is reused.

The product water 17 with the flow rate of "36" passes through the low-pressure RO membrane 16a of the second low-pressure reverse osmosis device 16-2, and the concentrated water with the flow rate of "4" is returned to the permeated water 14 as the returned concentrated water 26-2 as discharge water, and is reused.

[0039] While the sterilization treatment is carried out, the high-quality product water is constantly manufactured by executing either the third or the fourth embodiment.

[0040] In this manner, with the fifth embodiment, the low-pressure reverse osmosis device has a plurality of stages. Accordingly, when the concentration of salt in the raw water 11 is 220,000 parts per million, the high-pressure reverse osmosis device 13 can reduce the concentration of salt to 500 parts per million, the first

low-pressure reverse osmosis device 16-1 can reduce the concentration of salt to approximately 100 parts per million, and the second low-pressure reverse osmosis device 16-2 can reduce the concentration of salt to equal to or less than 5 parts per million. Accordingly, pure water equal to or more than drinking water (approximately 250 parts per million) can be manufactured in a stable manner.

Because a part of the concentrated water is reused, it is also possible to reduce the discharge of concentrated water and increase the amount of product water being produced.

INDUSTRIAL APPLICABILITY

[0041] In this manner, with the operation control method of the multi-stage seawater desalination apparatus according to the present invention, it is possible to provide water quality as good as that is produced by the evaporation method. Because the intermediate tank is eliminated, it is possible to significantly reduce microbial contamination. Accordingly, it can be suitably used for seawater desalination equipment.

EXPLANATIONS OF LETTERS OR NUMERALS

[0042] 10A, 10B, 10C, 10D, and 10E multi-stage seawater desalination apparatus

25 11 raw water (such as seawater)

12 high-pressure feed water

13a high-pressure reverse osmosis membrane

13 high-pressure reverse osmosis device

14 permeated water

30 15 low-pressure feed water

16a low-pressure reverse osmosis membrane

16 low-pressure reverse osmosis device

17 product water

- 21 first drain valve
- 22 second drain valve

CLAIMS

1. A multi-stage seawater desalination apparatus comprising:

a high-pressure pump that is mounted on a raw water
5 line through which raw water is supplied, and increases pressure of the raw water to a predetermined high pressure;

a high-pressure reverse osmosis device that includes a high-pressure reverse osmosis membrane for concentrating a salt content in high-pressure feed water whose pressure is
10 increased by the high-pressure pump;

a first drain valve that is mounted on a permeated water line through which permeated water that has passed through the high-pressure reverse osmosis device is supplied downstream, and temporarily drains the permeated
15 water of an initial start-up;

a low-pressure pump that is mounted on the permeated water line provided downstream of the first drain valve, and reduces pressure of the permeated water to a predetermined low pressure;

20 a low-pressure reverse osmosis device that includes a low-pressure reverse osmosis membrane for concentrating a salt content in low-pressure feed water whose pressure is reduced by the low-pressure pump; and

a second drain valve that is mounted on a discharge
25 line on a concentrated water side of the low-pressure reverse osmosis device, and temporarily discharges the low-pressure feed water of the initial start-up supplied to the low-pressure reverse osmosis device.

30 2. The multi-stage seawater desalination apparatus according to claim 1, further comprising

a plurality of the low-pressure reverse osmosis devices, wherein

the second drain valve is mounted on the discharge line at the concentrated water side of each of the low-pressure reverse osmosis devices, and temporarily discharges the low-pressure feed water of the initial start-up supplied to the low-pressure reverse osmosis devices.

3. The multi-stage seawater desalination apparatus according to claim 1 or 2, further comprising a returned concentrated water line that returns the concentrated water from the low-pressure reverse osmosis device upstream.

4. The multi-stage seawater desalination apparatus according to any one of claims 1 to 3, wherein the high-pressure reverse osmosis device is a membrane with chlorine-resistance.

5. An operation control method of a multi-stage seawater desalination apparatus that uses the multi-stage seawater desalination apparatus in claim 1 or 2, at an initial start-up of the multi-stage seawater desalination apparatus, comprising:

a step of supplying raw water to the high-pressure reverse osmosis device;

a step of temporarily draining permeated water that has passed through the high-pressure reverse osmosis membrane of the high-pressure reverse osmosis device through the first drain valve;

a step of supplying a whole amount of the permeated water to a side of the low-pressure reverse osmosis device, while closing the first drain valve, when a pressure of the permeated water has reached a pressure around an inlet pressure of the low-pressure pump;

a step of temporarily draining low-pressure feed water of the initial start-up supplied to the low-pressure reverse osmosis device through the second drain valve; and

5 a step of producing product water by making the low-pressure feed water pass through the low-pressure reverse osmosis membrane while closing the second drain valve, and switching operation to a rated seawater desalination operation.

10 6. An operation control method of a multi-stage seawater desalination apparatus that uses the multi-stage seawater desalination apparatus in claim 4, during a sterilization operation of the high-pressure reverse osmosis device of the multi-stage seawater desalination apparatus,
15 comprising:

a step of supplying raw water to which chlorine (Cl) is added is supplied to the high-pressure reverse osmosis device without feeding a reducing agent from a first reducing agent supplying unit;

20 a step of temporarily draining low-pressure feed water including a reducing agent through the second drain valve, after the reducing agent is added to permeated water with chlorine that has passed through the high-pressure reverse osmosis membrane of the high-pressure reverse osmosis
25 device from a second reducing agent supplying unit;

a step of switching operation to a normal operation, by adding a reducing agent from the first reducing agent supplying unit to the raw water, and stopping addition of the reducing agent from the second reducing agent supplying
30 unit, after a predetermined sterilization operation is finished; and

a step of producing product water, by switching operation to a rated seawater desalination operation, while

closing the second drain valve.

7. The operation control method of a multi-stage seawater desalination apparatus according to claim 6, wherein
5 concentrated water at a low pressure side is returned upstream through a returned concentrated water line, after the sterilization operation is finished.

8. An operation control method of a multi-stage seawater
10 desalination apparatus that uses the multi-stage seawater desalination apparatus in claim 4, during a sterilization operation of the high-pressure reverse osmosis device of the multi-stage seawater desalination apparatus, comprising:

15 a step of supplying raw water to which chlorine (Cl) is added to the high-pressure reverse osmosis device without feeding a reducing agent from a first reducing agent supplying unit;

a step of neutralizing permeated water with chlorine
20 that has passed through the high-pressure reverse osmosis membrane of the high-pressure reverse osmosis device, by adding a reducing agent less than a neutralization equivalent from a second reducing agent supplying unit, and then supplying rest of the reducing agent for neutralizing
25 to low-pressure feed water, while measuring an oxidation-reduction potential thereof with an oxidation-reduction potential meter;

a step of producing product water by making the low-pressure feed water pass through the low-pressure reverse
30 osmosis membrane; and

a step of producing product water by switching operation to a rated seawater desalination operation, after the sterilization operation is finished.

9. The operation control method of a multi-stage seawater
desalination apparatus according to claim 8, wherein
concentrated water at a low pressure side is returned
5 upstream through a returned concentrated water line during
the sterilization operation and the rated operation.