

DESCRIPTION
TRAIN CONTROL SYSTEM

Field

5 [0001]

The embodiments of the present invention relate to a train control system.

Background

10 [0002]

During rush hours or the like on a railroad, a plurality of trains become close to each other and run in a congested state in some cases. In such cases, a following train may be temporarily stopped between stations in response to a stopping signal to prevent a collision with a preceding train. If a train is temporarily stopped, a deceleration and a re-acceleration occur, which increase the amount of power consumption in the train. Furthermore, the ride quality for the passengers in the train is deteriorated.

[0003]

20 There is disclosed a method in which a ground device recognizing the situations of respective trains within a route transmits information of a preceding train to a following train being a control target train, and the following train controls its own operation based on the preceding train information to suppress temporary stops between stations (Patent Literature 1).

[0004]

However, the preceding train may be delayed by influences of a train running ahead thereof (hereinafter, "pre-preceding train"). In this case, the preceding train information is not changed from that in a normal operation until the preceding train approaches the pre-preceding train. Therefore, the following train performs a normal operation for a while after leaving a station and starts an operation at a reduced speed when the train position has advanced to some extent. This leads to a difficulty in avoiding a temporary stop due to a stopping signal.

30

35

Citation List

Patent Literature

[0005]

[Patent Literature 1] Japanese Patent No. 3829031

5

Summary

Technical Problem

[0006]

10 An object is to provide a train control system that can suppress temporary stops between stations.

Solution to Problem

[0007]

15 A train control system according to an embodiment includes an acquisition part, a prediction part, and a controller. The acquisition part acquires actual first-station arrival times or first-station departure times of a second train preceding a first train being a control target and at least one or more third trains among a plurality of trains preceding the second train. The prediction part
20 predicts a first time at which a stopping signal received by the first train in front of a first station due to influences of the second and third trains is canceled based on the actual first-station arrival times or first-station departure times of the second and third trains. The controller controls an operation of the first train based on the first
25 time.

Brief Description of Drawings

[0008]

30 [FIG. 1] FIG. 1 is a conceptual diagram illustrating an example of a configuration of a train control system according to an embodiment and peripheral elements thereof.

[FIGS. 2] FIGS. 2 are block diagrams respectively illustrating an example of a configuration of a ground device 20 and an example of a configuration of an on-vehicle device 30.

35 [FIG. 3] FIG. 3 is a timing chart illustrating an operation of the train control system according to the embodiment.

Description of Embodiments

[0009]

5 An embodiment of the present invention will be described below in detail with reference to the accompanying drawings. The embodiment does not limit the present invention.

[0010]

10 FIG. 1 is a conceptual diagram illustrating an example of a configuration of a train control system according to the present embodiment and peripheral elements thereof. The train control system includes a ground device 20 and an on-vehicle device 30.

[0011]

15 The on-vehicle device 30 is mounted on a train 100 being a first train. The train 100 is a train as a control target and is located before a first station. For example, the train 100 is stopping at a station A. A train 200 being a second train is a train preceding the train 100. For example, the train 200 is running between the station A and the first station. A train 300 being a third train is a train preceding the train 200. For example, the train 300 is arriving at the
20 first station. The first station is a station next to the station A. The trains 200 and 300 can have an identical configuration to that of the train 100. In this example, control of the train 100 as a control target is described and descriptions of control of the trains 200 and 300 are omitted for the sake of simplicity.

25 [0012]

An operation monitoring part 10 and the ground device 20 are placed on the ground outside the trains 100 to 300 and the operation monitoring part 10 is connected to an on-rail detector (not illustrated) or the like placed on a track 2 to be communicable with
30 the on-rail detector. The on-rail detector includes, for example, a track circuit provided in each section of the track 2. The on-rail detector transmits on-rail information of the trains 100 to 300 known by an on-rail detection using the track circuit to the operation monitoring part 10. The ground device 20 is connected to the
35 on-vehicle devices 30 of the trains 100 to 300 to be communicable therewith.

[0013]

The operation monitoring part 10 being an external device is a device that collects and monitors information such as on-rail information of the trains 100 to 300 running on the track 2. The operation monitoring part 10 includes a clock function and transmits times such as times at which the trains 100 to 300 arrived at the station A and the first station or times at which the trains 100 to 300 left the station A and the first station to the ground device 20.

[0014]

The ground device 20 generates prediction information based on the on-rail information and the time information of the trains 100 to 300 received from the operation monitoring part 10 and transmits the generated prediction information to the train 100. The prediction information is, for example, prediction information of a time at which a stopping signal received by the train 100 in front of the first station is canceled. The prediction information is described later.

[0015]

A protective device (not illustrated) on the ground sets a stopping signal (a limiting speed 0) or a limiting speed lower than a permanent speed limit behind a section where a train is located on the rails according to the distance from the train being on the rails based on the on-rail detection by the track circuit. An on-vehicle protective device activates a brake based on the limiting speed information from the ground protective device and its own train speed. When a preceding train is stopping at the first station, a stopping signal section is set behind the preceding train. When a following train enters the stopping signal section, the brake is automatically activated and the following train is stopped in the stopping signal section. This configuration can avoid a collision between the preceding train and the following train.

[0016]

FIG. 2(A) is a block diagram illustrating an example of a configuration of the ground device 20. The ground device 20 includes an acquisition part 12, a storage part 14, a prediction part 16, and a transmitter 18.

[0017]

The acquisition part 12 acquires an actual arrival time or departure time of the train 300 from the operation monitoring part 10 when the train 300 has arrived at the first station or has left the first station. For example, the operation monitoring part 10 detects an arrival of the train 300 at the first station based on position information and an identifier of the train 300 and transmits a time of the arrival to the ground device 20. This enables the ground device 20 to know the time at which the train 300 has arrived at the first station. The operation monitoring part 10 can also transmit the on-rail information and arrival and departure times of other trains (100 and 200, for example) to the ground device 20. This enables the ground device 20 to know the on-rail information of respective trains and the arrival and departure times thereof at other stations.

[0018]

The storage part 14 stores therein a first predicted time T1 from when a train stops at the first station until when the train leaves the first station, a second predicted time T2 from when the train leaves the first station until when a stopping signal set behind the train during stopping of the train at the first station is canceled, and a third predicted time T3 until a following train that has reached a stopping signal section at the time of cancellation of the stopping signal stops at the first station. The second predicted time T2 and the third predicted time T3 are obtained based on a running simulation or an actual running time (an actually measured value) of the train and are stored in advance in the storage part 14.

[0019]

The first predicted time T1 is a time (a station stopping time) during which a train is stopping at the first station. Although the station stopping times of trains on a train diagram are generally set equally, the actual station stopping times may vary according to stations. For example, the station stopping times of trains are likely to become longer at stations where there are many passengers changing trains. Therefore, the first predicted time T1 can be set for each station. In this case, the storage part 14 stores therein identifiers of the respective stations and the first predicted times T1

thereof to be associated with each other. The station stopping times of trains may also differ according to time periods or days. For example, during commuting times, the stations are crowded and thus the station stopping times of trains are likely to become longer.

5 Conversely, when there are fewer passengers at stations on holidays, the stopping times of trains do not become longer. Therefore, the first predicted times T1 can be set to correspond to the time periods and days, respectively. Furthermore, the first predicted time T1 can be set for each train. In this case, the storage part 14 has stored
10 therein the identifiers of the trains and the first predicted times T1 thereof to be associated with each other.

[0020]

The second predicted time T2 is a time from when a train leaves the first station until when a stopping signal set behind the
15 train during stopping of the train at the station is canceled. For example, a stopping signal set in front of the first station continues while the train 300 is stopping at the first station. When the train 300 thereafter leaves the first station and enters a next section, the stopping signal set in front of the first station is canceled. This
20 enables the train 200 to enter the first station and stop at the station. This time from when the train 300 leaves the first station until when the stopping signal is canceled is the second predicted time T2.

[0021]

The third predicted time T3 is a time until when a following
25 train that has reached the stopping signal section in front of the first station at the time of cancellation of the stopping signal enters the first station and stops. For example, when the train 300 leaves the first station and enters the next section, the stopping signal is canceled. After the stopping signal is canceled, the train 200 enters
30 the first station. In this manner, a predicted time from when a signaling device 40 has switched to an entrance allowing state until when the train 200 reaches the first station is the third predicted time T3.

[0022]

35 With respect to the train 100 as a control target, the prediction part 16 specifies the preceding train 200 and the

pre-preceding train 300 from a relation of the departure and arrival order on the train diagram, and predicts a first time at which a stopping signal set in front of the first station is canceled after the train 200 has left the first station based on an actual time of an arrival of the train 300 at the first station or an actual time of a departure of the train 300 from the first station. That is, the first time is a time at which the train 100 is predicted to become capable of entering the first station based on the departure and arrival times of the pre-preceding train 300. For example, the prediction part 16 calculates the first time using an actual time at which the train 300 arrived at the first station, the first predicted time T1, the second predicted time T2, and the third predicted time T3. The first predicted time T1, the second predicted time T2, and the third predicted time T3 are selected based on one of the station, the train, the time period, and the day as described above. The prediction part 16 can be, for example, an arithmetic device such as a CPU or a logic LSI. The calculation method of the first time is described later. [0023]

The transmitter 18 transmits information from the ground device 20 to the on-vehicle device 30 of the train 100. For example, the transmitter 18 transmits the first time (prediction information) predicted by the prediction part 16 to the on-vehicle device 30 of the train 100. [0024]

FIG. 2(B) is a block diagram illustrating an example of a configuration of the on-vehicle device 30. The on-vehicle device 30 includes a receiver 22 and a controller 24. [0025]

The receiver 22 receives information transmitted from the transmitter 18 of the ground device 20. For example, the receiver 22 receives the first time transmitted from the transmitter 18. [0026]

The controller 24 controls the operation of the train 100 based on the first time. For example, the controller 24 creates a running plan to prevent the train 100 from entering a relevant stopping signal section until a stopping signal set in front of the first station is

canceled, and controls the operation of the train 100 based on the running plan. This enables the train 100 to arrive at the first station smoothly without being temporarily stopped in the stopping signal section set in front of the first station.

5 [0027]

As described above, the ground device 20 and the on-vehicle device 30 illustrated in FIGS. 2(A) and 2(B) are configured as the train control system. The storage part 14 and the prediction part 16 can be provided in the on-vehicle device 30. In this case, the receiver 22 receives an actual arrival time or departure time from the ground device 20, and the prediction part 16 in the on-vehicle device 30 predicts the first time using the actual arrival time or departure time. However, provision of the storage part 14 and the prediction part 16 in each of many trains increases the cost. Therefore, it is preferable that the storage part 14 and the prediction part 16 be provided in the ground device 20.

[0028]

An operation of the train control system according to the present embodiment is described next.

20 [0029]

FIG. 3 is a timing chart illustrating an operation of the train control system according to the present embodiment. The vertical axis represents the positions of the trains 100 to 300. The vertical axis represents the train position and the horizontal axis represents the time. Broken lines indicate timings in a case where a conventional system is used. A time t_1 on the horizontal axis denotes an actual time at which the train 300 arrived at the first station. A time t_p (hereinafter, "prediction execution time t_p ") denotes a time point where a prediction of a first time t_q is performed. The first time t_q is a predicted time at which a stopping signal set in front of the first station is canceled when the train 100 as a control target enters the first station. Events before the prediction execution time t_p are past events that already happened. Therefore, the actual time t_1 at which the train 300 arrived at the first station is already known. On the other hand, events after the prediction execution time t_p are future events that will happen in the future.

Therefore, the first time t_q at which the stopping signal set in front of the first station is canceled at the time of an entrance of the train 100 into the first station is unknown yet and is a time as a prediction target.

5 [0030] (When prediction execution time t_p is between t_1 and t_2 : case 1)

When the prediction execution time t_p is between t_1 and t_2 , the time t_1 is already known. The time t_1 is an actual time at which the train 300 arrived at the first station. However, times t_2 to t_7 after that time are not known yet. Therefore, the prediction part 16 predicts the first time t_q based on the time t_1 in the following manner.

[0031]

First, the train 300 arrives at the first station at the time t_1 .
15 At this time, the operation monitoring part 10 obtains on-rail information of the train 300. The acquisition part 12 acquires the time t_1 at which the train 300 arrived at the first station from the operation monitoring part 10.

[0032]

20 Next, at the time t_p , the prediction part 16 predicts the first time t_q using the time t_1 . For example, the prediction part 16 obtains the first to third predicted times T_1 to T_3 corresponding to the first station from the storage part 14 and predicts the first time t_q based on the time t_1 and the first to third predicted times T_1 to T_3 .

25 [0033]

The first predicted time T_1 indicates a time (a station stopping time) during which a train is stopping at the first station. Therefore, the prediction part 16 performs the prediction assuming a time between t_1 and t_2 and a time between t_4 and t_5 are the first
30 predicted time T_1 . The time between t_1 and t_2 is a time during which the train 300 is stopping at the first station. The time between t_4 and t_5 is a time during which the train 200 is stopping at the first station. The second predicted time T_2 indicates a time from when a train leaves the first station until when a stopping signal set
35 behind the train during stopping of the train at the station is canceled. Therefore, the prediction part 16 performs the prediction assuming a

time between t2 and t3 and a time between t5 and tq are the second predicted time T2. The third predicted time T3 indicates a time until when a train that has arrived at a stopping signal section at the time of cancellation of the stopping signal stops at the first station.

- 5 Therefore, the prediction part 16 performs the prediction assuming a time between t3 and t4 is the third predicted time T3.

[0034]

- The prediction part 16 further calculates a time between t1 and tq. For example, the prediction part 16 calculates the first time
10 tq by adding the first predicted time T1 as the time between t1 and t2, the second predicted time T2 as the time between t2 and t3, the third predicted time T3 as the time between t3 and t4, the first predicted time T1 as the time between t4 and t5, and the second predicted time T2 as the time between t5 and tq to the time t1. That is, the
15 prediction part 16 predicts the first time tq by computing Expression 1.

[0035]

$$tq=t1+T1+T2+T3+T1+T2 \quad (\text{Expression 1})$$

[0036]

- 20 Next, the transmitter 18 transmits the first time tq predicted by the prediction part 16 as prediction information to the on-vehicle device 30 of the train 100.

[0037]

- Subsequently, the receiver 22 of the on-vehicle device 30
25 receives the first time tq, and the controller 24 creates a running plan of the train 100 based on the first time tq. The controller 24 controls the operation of the train 100 in accordance with the running plan. The controller 24 can automatically control the operation of the train 100 to prevent the train 100 from being temporarily stopped by the
30 stopping signal set in front of the first station. Alternatively, the controller 24 can display a target speed of the train 100 on a monitor (not illustrated) for train crews and enable a driver to perform an operation according to the target speed to prevent the train 100 from being temporarily stopped by the stopping signal set in front of the
35 first station. The controller 24 alternatively can notify the driver of the predicted first time and cause the driver to perform an operation

so as not to be temporarily stopped due to the stopping signal set in front of the first station. Therefore, the train control system according to the present embodiment can suppress temporary stops of the train 100 between the station A and the first station while the conventional system causes a train to be temporarily stopped between the station A and the first station, thereby increasing the amount of power consumption in the train and deteriorating the ride quality as indicated by the broken lines in FIG. 3.

[0038] (When prediction execution time t_p is between t_2 and t_3 : case 2)

When the prediction execution time t_p is between t_2 and t_3 , the time t_2 is already known. The time t_2 is an actual time at which the train 300 left the first station. However, times t_3 to t_7 after that time are not known yet. Therefore, the prediction part 16 can predict the first time t_q based on the time t_2 in the following manner. [0039]

For example, at t_2 , the train 300 leaves the first station and the departure time of the train 300 is settled. That is, the acquisition part 12 can acquire the actual time t_2 at which the train 300 left the first station from the operation monitoring part 10. Accordingly, the prediction part 16 predicts the first time t_q using the actual time t_2 . At this time, the prediction is performed between t_2 and t_3 . Therefore, the time t_p is any time between t_2 and t_3 . [0040]

For example, the prediction part 16 obtains the first to third predicted times T_1 to T_3 corresponding to the first station from the storage part 14 and predicts the first time t_q based on the time t_2 and the first to third predicted times T_1 to T_3 . That is, the prediction part 16 calculates a time between t_2 and t_q . For example, the prediction part 16 calculates the first time t_q by adding the second predicted time T_2 as the time between t_2 and t_3 , the third predicted time T_3 as the time between t_3 and t_4 , the first predicted time T_1 as the time between t_4 and t_5 , and the second predicted time T_2 as the time between t_5 and t_q to the time t_2 . That is, the prediction part 16 predicts the first time t_q by computing Expression 2.

[0041]

$$t_q = t_2 + T_2 + T_3 + T_1 + T_2 \quad (\text{Expression 2})$$

[0042]

Next, the transmitter 18 transmits the first time t_q predicted by the prediction part 16 as prediction information to the on-vehicle device 30 of the train 100.

[0043]

Subsequently, the receiver 22 of the on-vehicle device 30 receives the first time t_q , and the controller 24 creates a running plan of the train 100 based on the first time t_q . The controller 24 controls the operation of the train 100 in accordance with the running plane. The control method of the train 100 can be identical to that in the case 1 described above.

[0044]

In the case 1 described above, the prediction part 16 predicts the first time t_q from the time t_1 at which the train 300 arrived at the first station. However, actual times may be different from the first to third predicted times T_1 to T_3 . In this case, the prediction accuracy becomes lower as a time (t_1 , for example) being a prediction reference is temporally more distant from the first time t_q being a prediction target. That is, the first time t_q is more likely to be greatly deviated from the actual time at which the train 100 arrives at the stopping signal section that is set in front of the first station as the time t_p at which the prediction is performed is an earlier time. To reduce a temporal difference between the first time t_q and the actual time, the prediction part 16 can repeat the prediction of the first time t_q based on a time (t_2 , for example) of an event happening next as in the case 2. The case 2 enables the first time t_q to be predicted more accurately than the case 1.

[0045] (When prediction execution time t_p is between t_3 and t_4 : case 3)

When the prediction execution time t_p is between t_3 and t_4 , the time t_3 is already known. The time t_3 is an actual time at which a stopping signal having been set in front of the first station due to the train 300 has been canceled. However, times t_4 to t_7 after that time are not known yet. Therefore, the prediction part 16 can predict the first time t_q based on the time t_3 in the following manner.

[0046]

For example, the acquisition part 12 can acquire the actual time t_3 from the operation monitoring part 10. Accordingly, the prediction part 16 predicts the first time t_q using the actual time t_3 .

- 5 At this time, the prediction is performed between t_3 and t_4 . Therefore, the time t_p is any time between t_3 and t_4 .

[0047]

For example, the prediction part 16 obtains the first to third predicted times T_1 to T_3 corresponding to the first station from the storage part 14 and predicts the first time t_q from the time t_3 and the first to third predicted times T_1 to T_3 . That is, the prediction part 16 calculates a time between t_3 and t_q . For example, the prediction part 16 calculates the first time t_q by adding the third predicted time T_3 as the time between t_3 and t_4 , the first predicted time T_1 as the time between t_4 and t_5 , and the second predicted time T_2 as the time between t_5 and t_q to the time t_3 . That is, the prediction part 16 predicts the first time t_q by computing Expression 3.

[0048]

$$t_q = t_3 + T_3 + T_1 + T_2 \quad (\text{Expression 3})$$

20 [0049]

Next, the transmitter 18 transmits the first time t_q predicted by the prediction part 16 as prediction information to the on-vehicle device 30 of the train 100.

[0050]

- 25 Subsequently, the receiver 22 of the on-vehicle device 30 receives the first time t_q , and the controller 24 creates a running plan of the train 100 based on the first time t_q . The controller 24 controls the operation of the train 100 in accordance with the running plan. The control method of the train 100 can be identical to that in the case 1 described above.

[0051]

- 35 In the cases 1 and 2 described above, the prediction part 16 predicts the first time t_q based on the time t_1 or t_2 . However, in the case 3, the prediction part 16 predicts the first time t_q based on the time t_3 of an event happening after the times t_1 and t_2 . Accordingly, the case 3 enables the first time t_q to be predicted more accurately

than the cases 1 and 2.

[0052] (When prediction execution time t_p is between t_4 and t_5 : case 4)

When the prediction execution time t_p is between t_4 and t_5 , the time t_4 is already known. The time t_4 is an actual time at which the train 200 arrived at the first station. However, times t_5 to t_7 after that time are not known yet. Therefore, the prediction part 16 can predict the first time t_q based on the time t_4 in the following manner.

10 [0053]

For example, when the train 200 arrives at the first station at t_4 , the actual arrival time t_4 of the train 200 is settled. That is, the acquisition part 12 can acquire the actual arrival time t_4 from the operation monitoring part 10. Accordingly, the prediction part 16 predicts the first time t_q using the actual arrival time t_4 . At this time, the prediction is performed between t_4 and t_5 . Therefore, the time t_p is any time between t_4 and t_5 .

[0054]

For example, the prediction part 16 obtains the first and second predicted times T_1 and T_2 corresponding to the first station from the storage part 14 and predicts the first time t_q from the actual arrival time t_4 and the first and second predicted times T_1 and T_2 . That is, the prediction part 16 calculates a time between t_4 and t_q . For example, the prediction part 16 calculates the first time t_q by adding the first predicted time T_1 as the time between t_4 and t_5 and the second predicted time T_2 as the time between t_5 and t_q to the time t_4 . That is, the prediction part 16 predicts the first time t_q by computing Expression 4.

[0055]

30 $t_q = t_4 + T_1 + T_2$ (Expression 4)

[0056]

Next, the transmitter 18 transmits the first time t_q predicted by the prediction part 16 as prediction information to the on-vehicle device 30 of the train 100.

35 [0057]

Subsequently, the receiver 22 of the on-vehicle device 30

receives the first time t_q , and the controller 24 creates a running plan of the train 100 based on the first time t_q . The controller 24 controls the operation of the train 100 in accordance with the running plan. The control method of the train 100 can be identical to that in the case 1 described above.

[0058]

In the cases 1 to 3 described above, the prediction part 16 predicts the first time t_q based on the times t_1 to t_3 , respectively. However, in the case 4, the prediction part 16 predicts the first time t_q based on the time t_4 of an event happening after the times t_1 to t_3 . Accordingly, the case 4 enables the first time t_q to be predicted more accurately than the cases 1 to 3.

[0059] (When prediction execution time t_p is between t_5 and t_6 : case 5)

When the prediction execution time t_p is between t_5 and t_6 , the time point t_5 is already known. The time point t_5 is an actual time at which the train 200 left the first station. However, times t_q to t_7 after that time are not known yet. Therefore, the prediction part 16 can predict the first time t_q based on the time t_5 in the following manner.

[0060]

For example, when the train 200 leaves the first station at t_5 , the actual departure time t_5 of the train 200 is settled. That is, the acquisition part 12 can acquire the actual departure time t_5 from the operation monitoring part 10. Accordingly, the prediction part 16 predicts the first time t_q using the actual departure time t_5 . At this time, the prediction is performed between t_5 and t_6 . Therefore, the time t_p is any time between t_5 and t_6 .

[0061]

For example, the prediction part 16 obtains the second predicted time T_2 corresponding to the first station from the storage part 14 and predicts the first time t_q based on the actual departure time t_5 and the second predicted time T_2 . That is, the prediction part 16 calculates a time between t_5 and t_q . For example, the prediction part 16 calculates the first time t_q by adding the second prediction time as the time between t_5 and t_q to the time t_5 . That is,

the prediction part 16 predicts the first time t_q by computing Expression 5.

[0062]

$$t_q = t_5 + T_2 \quad (\text{Expression 5})$$

5 [0063]

Next, the transmitter 18 transmits the first time t_q predicted by the prediction part 16 as prediction information to the on-vehicle device 30 of the train 100.

[0064]

10 Subsequently, the receiver 22 of the on-vehicle device 30 receives the first time t_q , and the controller 24 creates a running plan of the train 100 based on the first time t_q . The controller 24 controls the speed of the train 100 in accordance with the running plan. The control method of the train 100 can be identical to that in the case 1
15 described above.

[0065]

In the cases 1 to 4 described above, the prediction part 16 predicts the first time t_q based on the times t_1 to t_4 , respectively. However, in the case 5, the prediction part 16 predicts the first time
20 t_q based on the time t_5 of an event happening after the times t_1 to t_4 . Accordingly, the case 5 enables the first time t_q to be predicted more accurately than the cases 1 to 4.

[0066]

In this way, the train control system according to the present
25 embodiment sequentially performs the cases 1 to 5 described above in time series, thereby enabling the train 100 to run at appropriate speeds up to the stopping signal section set in front of the first station while enhancing the accuracy of the first time t_q . Accordingly, the train 100 can suppress temporary stops or re-accelerations between
30 the station A and the first station. As a result, the amount of power consumption in the train 100 is reduced and the ride quality for the passengers in the train 100 is improved. The train control system can arbitrarily perform any one or a plurality of the cases 1 to 5.

[0067]

35 Furthermore, the train control system according to the present embodiment predicts the first time t_q considering not only

the preceding train 200 but also the train 300 preceding the train 200. Therefore, the train control system can control the speed of the train 100 from an earlier period. As a result, temporary stops of the train 100 due to the stopping signal set in front of the first station can be suppressed more. The train control system can predict the first time t_q considering a train (not illustrated) preceding the train 300 in order to control the train 100. In this case, the train control system can control the operation of the train 100 from a further earlier period.

10 [0068]

In the embodiment described above, the train control system predicts the first time t_q at which the stopping signal set in front of the first station for the train 100 is canceled. However, the train control system can predict other times based on the first to third predicted times T_1 to T_3 . For example, the train control system can predict the time t_2 at which the train 300 leaves the first station, the time t_3 at which a stopping signal set in front of the first station for the train 200 is canceled, the times t_4 and t_6 at which the trains 100 and 200 arrive at the first station, respectively, the times t_5 and t_7 at which the trains 100 and 200 leave the first station, respectively, and the like.

[0069]

In the embodiment described above, the train control system controls the train 100 as a control target. However, the train control system can also control other trains 200 and 300 as control targets. In this case, the trains 200 and 300 also include the on-vehicle device 30 and the prediction parts 16 in the respective on-vehicle devices 30 predict the first times corresponding to the trains 200 and 300 based on information from other preceding trains (not illustrated), respectively. It suffices that controllers of the trains 200 and 300 create running plans based on the first times corresponding thereto and control the trains 200 and 300 in accordance with the created running plans, respectively.

[0070]

35 While certain embodiments have been described, these embodiments have been presented by way of example only, and

are not intended to limit the scope of the inventions. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions and changes in the form of the methods and systems
5 described herein may be made without departing from the spirit of the inventions. The accompanying claims and their equivalents are intended to cover such forms or modifications as would fall within the scope and spirit of the inventions.

CLAIMS

1. A train control system comprising:
an acquisition part configured to acquire actual first-station
5 arrival times or first-station departure times with respect to a second
train preceding a first train being a control target and at least one or
more third trains among a plurality of trains preceding the second
train;
a prediction part configured to predict a first time, at which a
10 stopping signal which is received by the first train in front of a first
station and which is generated due to influences of the second and
third trains is canceled, based on the actual first-station arrival times
or first-station departure times of the second and third trains; and
a controller configured to control an operation of the first train
15 based on the first time.
2. The system of Claim 1, wherein the controller notifies a driver
of the first train of the first time and performs operation support for
avoiding an entrance of the first train into a stopping signal section in
20 front of the first station before the first time.
3. The system of Claim 1, wherein the controller creates a running
plan for avoiding an entrance of the first train into a stopping signal
section in front of the first station before the first time and controls
25 an operation of the first train or notifies a driver of the first train of
the created running plan to perform operation support.
4. The system of any one of Claims 1 to 3, wherein
the acquisition part and the prediction part are located in an
30 external device outside the first train, and
the controller is located in the first train.
5. The system of any one of Claims 1 to 3, wherein
the acquisition part is located in a ground device placed outside
35 the first train, and
the prediction part and the controller are located on the first
train.
6. The system of any one of Claims 1 to 5, further comprising a
40 storage part configured to store therein a first predicted time from
which a train stops at a station until when the train leaves the station,
a second predicted time until a stopping signal having been set
behind the train is canceled after the train leaves the station and
travels to a next section, and a third predicted time until a following
45 train having arrived at a stopping signal section at a time of
cancellation of the stopping signal stops the station, wherein

the prediction part predicts the first time using the first to third predicted times.

5 7. The system of Claim 6, wherein the prediction part calculates the first time by adding the first predicted time, the second predicted time, the third predicted time, the first predicted time, and the second predicted time to a time at which the third train has stopped at the first station.

10 8. The system of Claim 6 or 7, wherein the prediction part calculates the first time by adding the second predicted time, the third predicted time, the first predicted time, and the second predicted time to a time at which the third train has left the first station.

15 9. The system of Claim 6, wherein the storage part stores therein a plurality of the first to third predicted times differing according to running sections, stations, trains, time periods, or days, and

20 the prediction part predicts the first time using the first to third prediction times selected based on at least any of running sections, stations, trains, time periods, or days.