



(43) International Publication Date
2 April 2015 (02.04.2015)

(51) International Patent Classification:

G01F 1/42 (2006.01) F15D 1/02 (2006.01)
G01F 1/44 (2006.01)

(21) International Application Number:

PCT/US2014/057054

(22) International Filing Date:

23 September 2014 (23.09.2014)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/883,069	26 September 2013 (26.09.2013)	US
61/937,693	10 February 2014 (10.02.2014)	US
14/489,149	17 September 2014 (17.09.2014)	US

(72) Inventor; and

(71) Applicant : VAN BUSKIRK, Paul [US/US]; 113 Harper Way, McDonough, GA 30252 (US).

(74) Agents: THORPE, Charlena et al.; 2180 Satellite Blvd, Suite 400, Duluth, GA 30097 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,

HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to the identity of the inventor (Rule 4.17(i))
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))
- of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) Title: ORIFICE PLATES




FIG. 1A

(57) Abstract: Implementations of an orifice plate used to regulate flow through a conduit are provided. In some implementations, a balanced restriction orifice (BRO) plate configured to maximize pressure loss is provided. In some implementations, the BRO plate may be configured to limit pipe and plate noise, erosion, cavitation, shear stress, etc. while maximizing pressure loss, and limiting flow to required values. In some implementations, openings through a BRO plate may be configured to satisfy a Velocity-Head Pressure-Loss equation. Alternatively, in some implementations, the hole pattern of an orifice plate may be optimized through the use of a provided Reynolds matching (RM) equation. In some implementations, an orifice plate may be optimized to improve process variable measurements, minimize system pressure drop, recover pressure, and reduce noise and other inefficiencies within the system using equations provided herein.



WO 2015/048043 A3



Published:

(88) Date of publication of the international search report:

— *with international search report (Art. 21(3))*

4 June 2015