



- (51) International Patent Classification:
G01P 15/125 (2006.01) *H01G 5/16* (2006.01)
- (21) International Application Number:
PCT/US2012/024840
- (22) International Filing Date:
13 February 2012 (13.02.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/441,760 11 February 2011 (11.02.2011) US
13/371,024 10 February 2012 (10.02.2012) US
- (71) Applicant (for all designated States except US): **PERDUE RESEARCH FOUNDATION** [US/US]; 1281 Win Hentschel Blvd., West LaFayette, Indiana 47906 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **CLARK, Jason, Vaughn** [US/US]; 2746 Margesson Crossing, Lafayette, Indiana 47909 (US).
- (74) Agents: **BACCOCH, John, C.** et al.; Brinks Hofer Gilson & Lione, P.O. Box 10087, Chicago, Illinois 60610 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MEMS DEVICES EXHIBITING LINEAR CHARACTERISTICS




FIG. 8

(57) Abstract: A micro electro mechanical system device has a first subassembly having sensor element including a coupler, and a second subassembly including a comb drive. The comb drive having stator plates and rotor plates and the coupler configured to displace the rotor plates relative to the stator plates providing a variable capacitance dependent on the displacement of the rotor plate.



Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*