

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2020/214204 A1

(43) International Publication Date
22 October 2020 (22.10.2020)

(51) International Patent Classification:

A61M 1/00 (2006.01) A61M 25/00 (2006.01)
A61B 17/00 (2006.01) A61M 25/01 (2006.01)

(21) International Application Number:

PCT/US2019/055373

(22) International Filing Date:

09 October 2019 (09.10.2019)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

16/388,244 18 April 2019 (18.04.2019) US

(72) Inventor; and

(71) Applicant: **NOVELL, Robert, F.** [US/US]; 1905 Altair Drive, Colorado Springs, CO 80905 (US).

(74) Agent: **MARTENSEN, Michael, C.**; Martensen IP, 30 East Kiowa Street, Suite 101, Colorado Springs, CO 80903 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

WO 2020/214204 A1

(54) Title: LAPAROSCOPIC FLEXIBLE SUCTION DEVICE AND ASSOCIATED METHODOLOGY

(57) Abstract: A laparoscopic flexible suction/irrigation device of the present invention encases a inner rigid cannula with an outer flexible cannula. Upon translating the distal end of outer flexible cannula beyond the distal end of the inner rigid cannula, the outer flexible cannula returns to a preexisting curvilinear shape. This curved extension can thereafter be positioned via a proximal handle to concavities within the surgical site for precise and effective fluid retraction.