




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/38		A1	(11) International Publication Number: WO 96/00486
			(43) International Publication Date: 4 January 1996 (04.01.96)
(21) International Application Number: PCT/SE95/00785		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).	
(22) International Filing Date: 27 June 1995 (27.06.95)			
(30) Priority Data: 9402289-4 27 June 1994 (27.06.94)		SE	
(71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET LM ERICSSON [SE/SE]; S-126 25 Stockholm (SE).		Published With international search report.	
(72) Inventors; and (75) Inventors/Applicants (for US only): KALLIN, Harald [SE/SE]; Kruthornsvägen 40, S-191 53 Sollentuna (SE). HAMILL-KEAYS, Anneli [SE/SE]; Tulpanvägen 1, S-191 54 Sollentuna (SE). LAURENDEAU, Francine [CA/CA]; 90 Cambridge, Baie D'Urfe, Quebec H9X 2V6 (CA). HAYES, John [GB/GB]; Birch House, Woodham Road, Woking GU21 4EN (GB).		9612054-8 RTMP.	
(74) Agents: LÖVGREN, Tage et al.; Telefonaktiebolaget LM Ericsson, Patent and Trademark Dept., S-126 25 Stockholm (SE).			

(54) Title: A METHOD AND ARRANGEMENT IN AN ANALOGUE MOBILE TELESYSTEM



(57) Abstract

An analogue mobile telesystem has traffic channel cells (C1), each of which includes a base station (A-G). These base stations handle combined control channels (PAC) for paging a mobile station (MS), and also access channels (AC) for establishing connections to or from the mobile station (MS). The mobile station has information concerning the frequencies of all of the access channels and the connections are established on duplex traffic channels (TC). The geographical area covered by respective traffic channel cells (C1) is determined by virtue of enabling all traffic channels (TC) within this area to be used for predetermined, common purposes. Each of the traffic channel cells (C1) has at least two access channels (PAC, AC) spaced apart at a desired frequency distance and having the same radio coverage as the traffic channels (TC). When desiring access, the mobile station (MS) scans the strength or power of all access channels on two separate occasions at a mutual spacing of 20 milliseconds. The duplex access channels (PAC, AC) assist the mobile station (MS) in finding the strongest access channel (PAC, AC) despite heavy fading. The mobile station (MS) thereby establishes a connection on the traffic channel (TC) in the most suitable cell (C1) having the highest signal strength. Unnecessary handoffs are avoided and speech quality is improved.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				