

TITLE OF THE INVENTION

HEAD CONTACT TYPE MAGNETIC DISK MEMORY DEVICE HAVING A NOVEL MAGNETIC HEAD SLIDER

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to a magnetic disk memory device, and more particularly, to a head contact type magnetic disk memory device having a novel magnetic head slider for providing stable head contact to a disk surface while keeping low loading during recording and reproducing operations.

Description of the Related Art

Recently, a head contact-type magnetic disk memory device has been developed in order to increase recording density on a magnetic disk. The head contact-type magnetic disk memory device includes a magnetic head slider for sliding on a surface of a magnetic disk, and for bringing a magnetic head into contact with the disk surface during recording and reproducing operations.

Usually, the magnetic head slider has a slider surface facing a disk surface. During recording and reproducing operations, the slider surface is subject to air pressure caused by fluid dynamic pressure

15 March 2005

effects due to relative motions between the head slider and the rotating disk surface. In order to utilize the air pressures effects during the rotation of the magnetic disk, a portion of the head slider is designed so as to contact the disk surface as a result of the air pressure during recording and reproducing operations. Usually, a back end portion of the slider surface along a forwarding direction of the head slider remains in contact with the disk surface.

In order to prevent hard wear on the contact pad to a disk surface, it is necessary to keep low loading during recording and reproducing operations. As illustrated in Fig. 17, assuming that a head slider 100 has a contact pad at an air flow outlet and a positive pressure generating part, a contact force is f_c , the suspension load is F , a positive pressure is f_n , a distance between f_c and F is l_g , and a distance between f_c and f_n is l_n , the following formula applies:

$$f_c = (l_n - l_g) / l_n \times F$$

In order to realize the smaller contact force, a configuration of the magnetic head slider is proposed as illustrated in Figures 18A and 18B. The head slider 100 includes a positive pressure generating part 106 at an air flow inlet edge and a contact pad 107 that generates almost no positive pressure at an air flow outlet edge. The suspension load position is almost the same with the positive pressure generating part 106. A positive pressure on the positive pressure generating part 106 is almost the same with the suspension load F , and almost no positive pressure is generated on the contact pad in this configuration. Consequently, this configuration has a short distance l_n , and a long distance l_n , so that the small contact force is achieved.

As illustrated in Figures 18A and 18B, both the positive pressure generating part 106 and the contact pad 107 are positioned at a top surface A of the head slider. Namely, the surface A of the slider is the closest to the facing disk surface. Each of the surfaces A, B and C of the head slider has a different height relative to the disk surface. But such a small contact pad has no cushion effect by air-bearing forces against shocks during a head loading operation. Consequently, the contact pad hits hard on the disk surface and is worn by hits in a head loading operation.

The head contact-type magnetic disk memory devices are usually installed in handheld devices, such as notebook-type personal computers. To apply a head contact-type magnetic disk memory device in a handheld computer, it is desirable that stable head loading and

unloading operations be performed with restricted fluctuations of the contact force of the magnetic head caused by shocks to the computer. Thus, it is desirable to keep a stable contact the head slider and the magnetic disk with a low load. Further, it is needed for the computer use to enhance the suppression of contact force fluctuations the slider caused by the changes in atmospheric pressures.

SUMMARY OF THE INVENTION

Therefore, there is a need for providing a head contact-type magnetic disk device having a novel magnetic head slider that can perform a stable head contact to a magnetic disk with a low load in order to restrict the variations of the head slider contact forces

In accordance with a first aspect of the present invention, there is provided a magnetic head slider having an air flow inlet side, an air flow outlet side, and a plurality of surfaces between the inlet side and the outlet side for constituting fluid force generating parts for the magnetic head slider due to dynamic pressure effects of air flow accompanying rotation of a magnetic recording medium, each of the plurality of surfaces has a different height level for defining a different distance to a surface of the magnetic recording medium, the magnetic head slider comprising: a contact pad for supporting a magnetic head for recording and reproducing data to and from a magnetic recording medium to enable the magnetic head to contact surface of the magnetic recording medium, the contact pad being provided near the

air flow outlet side at a top level in the plurality of different height levels; a positive pressure pad area provided near the air flow inlet side for generating positive pressure during rotation of the magnetic recording medium, the positive pressure pad area being positioned at the top level; and a squeeze pad area for suppressing fluctuations of contacting forces between the magnetic head and the magnetic disk medium, the squeeze pad area is provided along an air flow direction at a middle height level between the top level and the low level of the plurality of height levels traversing a surface at the low level.

A magnetic head slider in an example embodiment can obtain the squeeze effect by suppressing the generation of positive pressure, so that the contact force due to the head slider loading and vibration caused by an impact can be suppressed. Thus, a stable contact force between the magnetic head and the information recording medium can be maintained.

Further, a magnetic head slider in an example embodiment additionally has a first negative pressure control area configured to divide the positive pressure generation area. Since a fluid flows in from the first negative pressure control area in the direction of the flow due to rotation of the information recording medium, the generation of negative pressure behind the positive pressure generation area is suppressed and the contact force of the magnetic head can be achieved independent of the position of the magnetic head in the radial direction of the information recording medium.

Furthermore, a magnetic head slider in an example embodiment has a second negative pressure control area configured to divide the positive pressure generation area and the squeeze pad area.

Accordingly, air flow can be introduced from the second negative pressure, behind the positive pressure generation part in the direction of the flow due to rotation of the information recording medium, can be suppressed.

Further, a magnetic head slider in an example embodiment has a third negative pressure control area configured to be between the second negative pressure control area and the positive pressure generation area.

In a magnetic head slider in an example embodiment, the degrees of freedom of design of the second negative pressure control area are extended and the introduction of air can be controlled more accurately.

Furthermore, a magnetic head slider in an example embodiment is characterized that the squeeze pad area is arranged on a slant to the direction of the flow due to rotation of the recording medium. Further, for example, simultaneously with a change in the positive pressure in the squeeze pad area at the time of reduction in the atmospheric pressure, the back negative pressure in the direction of the fluid flow due to rotation of the information recording medium is changed, so

that the change is suppressed and the change in the contact force of the magnetic head can be prevented.

Further, a magnetic head slider in an example embodiment is characterized in that a forward area and a backward area constituting the squeeze pad area are arranged on a slant in different directions respectively from the direction of the flow due to rotation of the information recording medium.

A magnetic head slider in an example embodiment can suppress generation of positive pressure, increase the area of the squeeze pad area, control a change in the contact force when atmospheric pressure is reduced, and obtain a larger squeeze effect at the same time.

Furthermore, a magnetic disk device in an example embodiment has a magnetic head slider having a loaded magnetic pole element for recording and reproducing data on a recording medium installed so as to rotate freely. The magnetic head slider has a slider part having a surface on which a fluid force, generated by a dynamic pressure effect of the flow due to rotation of the information recording medium, operates, and a contact part for supporting the magnetic pole element so that the surface of the magnetic pole element opposite the information recording medium comes in contact with the information recording medium. A plurality of areas into which the fluid force operating surface of the slider part is divided via a plurality of level differences has a positive pressure generation area belonging to the top

level, together with the contact part which is installed between them at least across the area belonging to the low level on the inlet side of the flow. This is due to rotation of the information recording medium and a squeeze pad area belonging to the middle level between the top level and the low level which is installed along the direction of the flow so as to across the area belonging to the low level between the positive pressure generation area and the contact part.

In accordance with a second aspect of the present invention, there is provided a magnetic disk memory device, comprising: a magnetic head for recording and reproducing data to and from a disk medium; a magnetic head slider for supporting the magnetic head to contact a surface of the disk medium; and a carriage for supporting and rotating the magnetic head slider along a radius direction of the disk medium in order to locate the magnetic head to a target recording or reproducing track of the disk medium; wherein the magnetic head slider has an air flow inlet side, an air flow outlet side, and a plurality of surfaces between the inlet side and the outlet side for constituting fluid force generating parts for the magnetic head slider due to dynamic pressure effects of the air flow accompanying rotation of the magnetic recording medium, each of the plurality of surfaces has a different height level for defining a different distance to a surface of the magnetic recording medium: the magnetic head slider including: a contact pad for supporting a magnetic head for recording and reproducing data to and from the disk medium to enable the magnetic head to contact the surface of the magnetic recording medium, the

15 March 2005

contact pad being provided near the air flow outlet side at a top level of the plurality of different height levels; a positive pressure pad area provided near the air flow inlet side for generating positive pressure during rotation of the magnetic recording medium, the positive pressure pad area being positioned at the top level, and a squeeze pad area for suppressing fluctuations of contacting forces between the magnetic head and the magnetic disk medium, the squeeze pad area is provided along an air flow direction at a middle height level between the top level and the low height level of the plurality of height levels traversing a surfaces at the low level.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete appreciation of the present invention and many of the advantages thereof will be better understood by reference to the following detailed description when considered in connection with the accompanying drawings.

Figure 1 is a perspective view of a magnetic disk device having a magnetic head slider consistent with the invention.

Figure 2 is an enlarged perspective view of the magnetic head slider in the magnetic disk device illustrated in Figure 1.

Figure 3 is a plain view of the magnetic head slider consistent with the invention that is facing to a magnetic disk.

Figure 4 illustrates a correlation between parts of the magnetic head slider that is respectively shaded in Figure 3 and each of respective heights of the parts from a disk surface.

Figure 5 is a plan view illustrating a magnetic head slider configuration consistent with embodiments of the invention.

Figure 6 is a plan view illustrating a magnetic head slider configuration consistent with embodiments of the invention.

Figure 7 is a perspective view illustrating a magnetic head slider configuration consistent with embodiments of the invention.

Figure 8 is a plan view of the magnetic head slider illustrated in Figure 7.

Figures 9A-9D illustrate postures of the magnetic head slider illustrated in Figure 7 when the slider is subjected to a fluid dynamic pressure.

Figure 10 illustrates the squeeze film effect in a translation direction (z) for the magnetic head slider shown in Figure 7.

Figure 11 illustrates the squeeze film effect in a pitching direction for the magnetic head slider shown in Figure 7.

Figure 12 illustrates the squeeze film effect in the rolling direction for the magnetic head slider shown in Figure 7.

Figure 13 is a plan view illustrating the magnetic head slider configuration consistent with embodiments of the invention.

Figures 14A-14D explain the squeeze film effect by the magnetic head slider shown in Figure 13, wherein Figure 14B illustrates section 14B-14B of Figure 14A and Figure 14D illustrates section 14D-14D of Figure 14C.

Figure 15 is a plan view illustrating the magnetic head slider configuration consistent with embodiments of the invention.

Figures 16A-16D explain the squeeze film effect by the magnetic head slider shown in Figure 15, wherein Figure 16B illustrates section 16B-16B of Figure 16A and Figure 16D illustrates section 16D-16D of Figure 16C.

15 March 2005

Figure 17 explains the effect of an inertia force operating on the magnetic head slider caused by an impact.

Figure 18A and 18B illustrate configurations of a conventional magnetic head slider.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to identify the same or similar parts.

Embodiments consistent with the invention are directed to a magnetic head slider and a magnetic disk device including such a slider.

As illustrated in Figure 1, a magnetic disk device 100, which is applicable to a magnetic head slider 1 consistent with the invention, includes a base body 12 (a cover is not shown), a plurality of magnetic disk media provided as a plurality of magnetic disks 13, which is stacked along a spindle motor 16, and a carriage 15 for rotating the magnetic head slider 1 along a radius direction of the disk 13 in order to orient the magnetic head to the recording or reproducing tracks of

the disks 13.

As illustrates in Figure 2, the magnetic head slider 1 is mounted on an end portion of the carriage 15 for supporting a magnetic head element (not shown) facing to a surface of the disk medium.

With reference to Figures 3 and 4, an embodiment of a construction of the magnetic head slider 1 consistent with the invention would be explained. Figure 3 illustrates the configuration of the magnetic head slider 1 which is viewed from the surface side of the magnetic disk. Figure 4 explains the correlation in a plurality of different heights to a surface of the magnetic disk, in which the cross hatching of Figure 3 indicates different heights of the slider surface facing to the magnetic disk.

The magnetic head slider 1 includes an air flow inlet side edge 2 and an air flow outlet side edge 3 accompanying the rotation of the magnetic disk. The magnetic head slider 1 further includes a contact pad 5 provided near the air flow outlet side edge 3 and a positive pressure generating area 7 provided near the air flow inlet side edge 2. As illustrated by the cross hatching in Figure 3, both the contact pad 5 and the positive pressure generating area 7 are provided at the top level surface A in the slider surface, as illustrated in Figure 4. The contact pad 5 supports the magnetic head 4 so as to contact a surface of the magnetic head 4 facing to the magnetic disk 13 surface.

Further, the magnetic head slider 1 includes an U-shaped squeeze pad 8 positioned at a middle height level B in the slider surface as illustrated in Figure 3. The U-shaped squeeze pad 8 includes two side-edge parts extending along the rotational direction of the magnetic disk, i.e., the air flow direction during the rotation of the magnetic disk 13. The U-shaped squeeze pad 8 is provided so as to encircle a low surface area 6 positioned between the contact pad 5 and the positive pressure generating pad area 8.

Thus, as illustrated above, both the contact pad 5 and the positive pressure generating area 7 are provided on a surface positioned at the top level A in the head slider surface, and the U-shaped squeeze pad area 8 is provided on a surface positioned at the middle level B in the head slider surface, positioned between the top level A and the low level C.

These differences in the height levels in the slider surface in order to place the different elements at a different height level, i.e., both the contact pad 5 and the positive pressure generating area 7 positioned at the top level surface A, the U-shaped squeeze pad 8 at the middle level surface B, and the surface area 6 at the low level surface C, are designed so as to constitute a fluid force generating part for the head slider 1, due to the dynamic pressure effect of the air flow during the rotation of the magnetic disk 13.

As illustrated in Figure 4, the middle level surface B in the slider

surface is closer to the top level surface A than the low level surface C on the slider surface. By providing the squeeze pad 8 in the magnetic head slider 1 at a position closer to the facing surface of the magnetic disk 13, the magnetic head slider 1 can suppress the fluctuations of the contact force between the magnetic disk surface and the magnetic head surface by utilizing the squeeze film effect generated by the squeeze pad 8. Thus, the squeeze pad 8 generates repulsion forces against the sliding air film force between the magnetic disk 13 and the magnetic head slider 1.

Generally, when a surface of the slider head is positioned close to the disk surface, a positive pressure is generated to the slider head. Accordingly, when a lot of surfaces are positioned closer to the disk surface, a large amount of positive pressure causes a disturbance in a stable contact force of the head slider and the disk surface.

However, the configuration of the magnetic head slider 1 avoid the generation of a large amount of positive pressure, since the squeeze pad 8 is provided at the middle level surface B of the head slider so as to obtain the squeeze effect. Thus, the configuration of the magnetic head slider 1 can obtain the squeeze effect by restricting the generated positive pressure.

Accordingly, it becomes possible to perform a stable loading and unloading of the head slider 1. Further, it becomes possible to restrict the contact variations caused by shocks added to the magnetic disk

device when the atmospheric pressure decreases. Accordingly, it becomes possible to maintain a stable contact force of the magnetic head 4 against the magnetic disk.

According to the configuration of the U-shaped squeeze pad 8 in the magnetic head slider 1 of an embodiment consistent with the invention, a negative pressure is generated in the surface area 6 surrounded by the positive pressure generating part 7 and the squeeze pad 8. The negative pressure is depended upon the air flow speed. Accordingly, the positioning differences of the magnetic head 4 in a radial direction of the magnetic disk 13 causes to generates fluctuations in the contact force between the magnetic head 4 and the magnetic disk 13 along the radial direction of the disk. Consequently, it is desirable to restrict the generation of the negative pressure in order to keep a stable contact to the disk with a smaller contacting force.

Figure 5 illustrates a magnetic head slider 30 consistent with the invention that includes a variation of the configuration of the magnetic head slider 1 illustrated in Figure 3. As illustrated in Figure 5, in this configuration of the magnetic head slider 30, the positive pressure generating area is divided into two areas 7a and 7b, and the squeeze pad is also divided into two parts 20a and 20b so as to form a first negative pressure controlling area 6c between the divided pairs of parts 7a-20a, and 7b-20b. Consequently, the squeeze pad is also provided at

the middle level B in the form of the divided two parts 8a and 8b. Thus, in this magnetic head slider 30, the first negative pressure controlling area 6c is provided between the divided squeeze pads 20a and 20b so as to divide the positive pressure generating area along the air flow direction, i.e., a direction from the air flow-inlet end 2 to the air flow-outlet end 3, during the rotation of the magnetic disk 13.

Accordingly, the configuration of this magnetic head slider 30 having the first negative pressure controlling area 6c, can restrict the generation of the negative pressure behind the positive pressure generation areas 7a and 7b. Consequently, it can obtain a stable contacting force for the magnetic head 4 along a radial direction of the magnetic disk.

As illustrated in Figure 5, the first negative pressure controlling area 6c is constructed so as to have a pair of tapered air flow controlling walls 9a and 9b along the air flow direction during the rotation of the magnetic disk. The tapered air flow controlling walls 9a and 9b are provided so as to make the negative pressure controlling area 6c gradually narrower along the direction to the air flow outlet side.

Consequently, it becomes possible to restrict the generation of the negative pressure behind the positive pressure generating areas 7a and 7b by compressing the air flow behind the positive pressure generation parts 7a and 7b.

Figure 6 illustrates a magnetic head slider 40 consistent with the invention that includes another variation of the configuration of the magnetic head slider 1 illustrated in Figure 3. The magnetic head slider 40 includes second negative pressure controlling areas 6d and 6e, provided between each of the divided positive pressure generating areas 7a and 7b and the divided squeeze pads 8c and 8d. Thus, the respective second negative pressure control areas are provided so as to divide the positive pressure generation areas and the squeeze pad along the air flow direction generated during the rotation of the magnetic disk. Furthermore, each of the second negative pressure control areas 6d and 6c is formed to have a tapered air flow-in controllers 10a and 10b in order to adjust the air flow-in rate.

According to this configuration of the magnetic head slider, it becomes more possible to restrict the generation of the negative pressure behind the positive pressure generating areas 7a and 7b by introducing air flow through the second negative pressure controlling areas 6d and 6e.

Figures 7 and 8 illustrate a magnetic head slider 50 consistent with the invention that includes another variation of the configuration of the magnetic head slider 1 illustrated in Figure 3. The magnetic head slider 50 includes third negative pressure controlling areas 20c and 20d

behind the positive pressure generation sections 7a and 7b along air flowing direction. The third negative pressure controlling areas 20c and 20d are formed between the positive pressure generation sections 7a and 7b and the second negative pressure controlling areas 6d and 6e, such that the height of surface C, and the areas 7a and 7b are at the height of surface A. Further, each the second negative pressure controlling areas 6d and 6e is formed to have a tapered air flow-in control structures 10c and 10d for adjusting the air flow-in rate, respectively.

According to these structures of the head slider 50, the degrees of freedom of designing the second negative pressure control areas 6d and 6e is expanded. Consequently, it becomes possible to more accurately control the air flow-in. Thus, it becomes possible for the magnetic head slider 50 to obtain more stable contact force on the magnetic head 4 against the air flow speed.

Figures 9A-9D to 12 illustrate the fluid dynamic pressure operation of magnetic head sliders consistent with the invention. As illustrated in Figure 9A, the magnetic head slider 1, representative of magnetic head sliders consistent with the present invention, has three degrees of freedom, i.e., a translation direction (z) 101, a pitching direction 102 and a rolling direction 103. Furthermore, the magnetic head slider 1 receives counter forces or counter torque from the air film corresponding to variations of the posture of the head slider.

Figure 9B shows the fluid dynamic pressure operation of the counter force C_{zz} corresponding to variations of speed V_z along the translation direction (z) 101. Figure 9C shows the fluid dynamic pressure operation of the counter torque C_{pp} corresponding to variations of speed $V_{\theta p}$ along the pitching direction 102. Figure 9D shows the fluid dynamic pressure operation of the counter torque C_{rr} corresponding to variations of speed $V_{\theta r}$ along the rolling direction 103.

Figures 10 - 12 show the squeeze film effect due to the counter force or counter torques acting to the magnetic head slider when the magnetic head slider is vibrated with a unit of amplitude at each of frequencies along the translation direction 101 (z) 101 (Figure 10), the pitching direction 102 (Figure 11), and the rolling direction 103 (Figure 12). The abscissa in each Figures 10-12 indicates vibration frequencies (1 Hz to 1 MHz). The ordinate in Figure 10 indicates counter forces [mN/mm] acting on the head slider with a unit of amplitude at each vibration along the translation direction (z) 101. The ordinate in each Figures 11 and 12 indicates counter torques [mNmm/rad] acting on the head slider with a unit of amplitude at each vibration along the pitching direction 102, and the rolling direction 103, respectively.

In Figures 10-12, triangle dots show the data for the magnetic head slider consistent with the invention and circle dots show the data for the conventional magnetic head slider such as shown in Figure 18. As shown in Figures 10-12, the magnetic head slider consistent with

the invention receives larger counter forces or counter torques for suppressing the vibration than the conventional magnetic head slider. These results illustrate that the structure of the magnetic head slider consistent with the invention can keep its posture in a more stably than the conventional head slider structure.

Figure 13 illustrates a magnetic head slider 60 consistent with the invention that includes a variation of the magnetic head slider 1 illustrated in Figure 3. The magnetic head slider 60 includes shorter squeeze pad areas 8e and 8f than the squeeze pad areas previously described sliders along the rotational direction of the disk. Thus, as illustrated in Figure 13, the squeeze pad areas 8e and 8f are slanted against a perpendicular direction to the rotational direction of the disk.

The squeeze pad structures of the sliders 1, 30, 40, and 50 may increase the contact forces when the atmospheric pressure is reduced since the squeeze pad area maintains the contact posture of the head slider by compressing the air by its length along the air flow direction due to rotation of the magnetic disk. Consequently, the contact force increases when the atmospheric pressure decreases, since that the positive pressure generated on the rear part of the squeeze pad area decreases when the atmospheric pressure decreases..

On the other hand, the magnetic head slider shown 60 in Figure 13 includes the squeeze pad areas 8e and 8f that are in a slanted shorter form along the rotational direction of the disk. Consequently, the

squeeze pad areas 8e and 8f can generate the negative pressures behind of them. The negative pressure cancels the positive pressure generated in the squeeze pad areas 8e and 8f. Thus, the structure of this embodiment can prevent the contact force of the magnetic head slider from fluctuating with changes in the negative pressure behind the squeeze pad areas 8e and 8f when the atmospheric pressure is reduced.

Figures 14A and 14B compare the fluid dynamic pressure operations of the magnetic head sliders 50 and 60, respectively. As shown in Figure 14A and 14B, the head slider 50 receives the force that is comprised of the suspension load F , the fluid force f_h , the contact force f_c of the magnetic head, and the positive pressure f_p generated in the squeeze pad areas. When the atmospheric pressure decreases, the positive pressure f_p becomes smaller. Consequently, the contact force f_c increases substantially.

On the other hand, as shown in Figure 14C and 14D, in the head slider 60, the squeeze pad has a slant form so as to generate both the positive pressure f_p and the negative pressure f_n behind the squeeze pad. When the positive pressure f_p varies due to reduction of the atmospheric pressure, the negative pressure f_n also varies so as to cancel the variations of the positive pressure. Thus, the resultant force operating in the squeeze pad areas is similar to that before the reduction of the atmospheric pressure. Consequently, it becomes possible to restrain the increase of the contact force f_c when the

atmospheric pressure decreases. Therefore, the magnetic head slider consistent with this embodiment prevent the contact force of the magnetic head from causing fluctuations due to shocks and the atmospheric pressure.

Figure 15 illustrates a magnetic head slider 70 consistent with the invention that includes a variation of the magnetic head slider 1 illustrated in Figure 3. The magnetic head slider 70 includes the squeeze pad areas that are shorter than the squeeze pad areas 1, 30, 40, and 50 along the rotational direction of the disk. Thus, as illustrated in Figure 15, one of the squeeze pads has a forward area 8g and a backward area 8h that inclined in a different direction along the rotational direction of the disk relative to each other. Similarly, the other of squeeze pads has a forward area 8i and a backward area 8j that are inclined in a different direction along the rotational direction of the disk.

According to this construction, the magnetic head slider 70 has increased the squeeze pad areas in order to obtain a larger squeeze effect. Further it can suppress generation of the positive pressure so as to control the variation of the contact force when the atmospheric pressure decreases.

Figures 16A and 16D compare the fluid dynamic pressure operations of the magnetic head sliders 50 and 70, respectively. The

head slider 50 illustrated in Figure 16A and 16B receives the force that is comprised of the suspension load F , the fluid force f_h , the contact force f_c of the magnetic head and the positive pressure f_p generated in the squeeze pad areas. When the atmospheric pressure decreases, the positive pressure f_p becomes smaller. Consequently, the contact force f_c increases substantially.

In contrast, the magnetic head slider 70 illustrated in Figure 16C and 16D includes the V-shaped squeeze pad areas that have the forward slant areas 8g and 8i, and the backward slant areas 8h and 8j. Thus, the forward slant area and the backward slant area are inclined in a different direction along the rotational direction of the disk so that the squeeze pad areas generate of the negative pressures f_{n1} and f_{n2} behind the positive pressures f_{p1} and f_{p2} , so as to cancel them. Consequently, the magnetic head slider 70 can reduce the variations of the contact force f_c of the magnetic head when the atmospheric pressure decreases.

As explained above, a magnetic head slider consistent with the invention can suppress fluctuations of contacting forces of the magnetic head to a magnetic disk surface due to variations of the atmospheric pressures or impacts to the magnetic disk memory device. Consequently, a stable head loading in a head contact type magnetic disk memory device is realized.

It will be apparent to those skilled in the art that various

15 March 2005

modifications and variations can be made in the context of the present invention and its practice without departing from the scope or spirit of the invention.

WHAT IS CLAIMED IS:

1. A magnetic head slider having an air flow inlet side, an air flow outlet side, and a plurality of surfaces between the inlet side and the outlet side for constituting fluid force generating parts for the magnetic head slider due to dynamic pressure effects of air flow accompanying rotation of a magnetic recording medium, each of the plurality of surfaces has a different height level for defining a different distance to a surface of the magnetic recording medium,

the magnetic head slider comprising:

a contact pad for supporting a magnetic head for recording and reproducing data to and from a magnetic recording medium to enable the magnetic head to contact the surface of the magnetic recording medium, the contact pad being provided near the air flow outlet side at a top level in the plurality of different height levels;

a positive pressure pad area provided near the air flow inlet side for generating positive pressure during rotation of the magnetic recording medium, the positive pressure pad area being positioned at the top level; and

a squeeze pad area for suppressing fluctuations of contacting forces between the magnetic head and the magnetic disk medium, the squeeze pad area is provided along an air flow direction at a middle height level between the top level and a low level of the plurality of height levels traversing a surface at the low level.

2. The magnetic head slider according to claim 1, wherein the squeeze pad area has an U-shaped configuration including two side-

edge parts extending along a rotational direction of the magnetic disk medium so as to at least partially bound the low level of the surfaces.

3. The magnetic head slider according to claim 1, wherein the positive pressure pad area is divided into two parts by a negative pressure control area.

4. The magnetic head slider according to claim 1, wherein both the positive pressure pad area and the squeeze pad area are collectively divided into two parts by a first negative pressure control area.

5. The magnetic head slider according to claim 4,
a third negative pressure control area between a second negative pressure control area and the positive pressure generation area.

6. The magnetic head slider according to claims 1, wherein the squeeze pad area is arranged on a slant along the air flow direction due to rotation of the magnetic recording medium.

7. The magnetic head slider according to claim 1, wherein the squeeze pad area includes a forward area and a backward area along the air flow direction, each the forward area and the backward area of the squeeze pad being arranged in a different slant directions

respectively along the air flowing direction due to rotation of the magnetic recording medium.

8. A magnetic disk memory device, comprising:

a magnetic head for recording and reproducing data to and from a disk medium;

a magnetic head slider for supporting the magnetic head to contact a surface of the disk medium; and

a carriage for supporting and rotating the magnetic head slider along a radius direction of the disk medium in order to locate the magnetic head to a target recording or reproducing track of the disk medium;

wherein the magnetic head slider has an air flow inlet side, an air flow outlet side, and a plurality of surfaces between the inlet side and the outlet side for constituting fluid force generating parts for the magnetic head slider due to dynamic pressure effects of the air flow accompanying rotation of the magnetic recording medium, each of the plurality of surfaces has a different height level for defining a different distance to a surface of the magnetic recording medium:

the magnetic head slider including:

a contact pad for supporting a magnetic head for recording and reproducing data to and from the disk medium to enable the magnetic head to contact the surface of the magnetic recording medium, the contact pad being provided near the air flow outlet side at a top level of the plurality of different height levels;

a positive pressure pad area provided near the air flow inlet side for generating positive pressure during rotation of the magnetic recording medium, the positive pressure pad area being positioned at the top level, and

a squeeze pad area for suppressing fluctuations of contacting forces between the magnetic head and the magnetic disk medium, the squeeze pad area is provided along an air flow direction at a middle height level between the top level and the low height level of the plurality of height levels traversing a surfaces at the low level.

9. The magnetic disk memory device according to claim 8, wherein the squeeze pad area has an U-shaped configuration including two side-edge parts extended along a rotational direction of the magnetic disk medium so as to at least partially bound the low level of the surfaces.

10. The magnetic disk memory device according to claim 8, wherein the positive pressure generation area is divided into two parts by a first negative pressure control area.

11. The magnetic disk memory device according to claim 8, wherein both the positive pressure pad area and the squeeze pad area are collectively divided into two parts by a first negative pressure control area.

12. The magnetic disk memory device according to claim 11,

further comprising:

A third negative pressure control area installed between the second negative pressure control area and the positive pressure generation area.

13. The magnetic disk memory device according to claims 8, wherein the squeeze pad area is arranged on a slant along the air flowing direction flow due to rotation of the disk.

14. The magnetic disk memory device according to claim 8, wherein the squeeze pad area includes a forward area and a backward area along the air flow direction, each the forward area and the backward area of the squeeze pad being arranged on a different slant directions, respectively, along the air flow direction due to rotation of the magnetic recording medium.