(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
6 March 2003 (06.03.2003)

PCT

(10) International Publication Number
WO 03/019619 A2

(51) International Patent Classification[7]: H01L

(21) International Application Number: PCT/US02/25507

(22) International Filing Date: 8 August 2002 (08.08.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/928,209 10 August 2001 (10.08.2001) US

(71) Applicants: **INTERNATIONAL BUSINESS MACHINES CORPORATION** [US/US]; New Orchard Road, Armonk, NY 10504 (US). **INFINEON TECHNOLOGIES NORTH AMERICA CORP.** [US/US]; 1730 North First Street, San Jose, CA 95112 (US).

(72) Inventors: **CONTI, Richard, A.**; 47 Foxwood Circle, Mt. Kisco, NY 10549 (US). **EDELSTEIN, Daniel**; 15 Charlotte Street, White Plains, NY 10606 (US). **LEE, Gill, Yong**; 41 Sherwood Heights, Wappingers Falls, NY 12590 (US).

(74) Agent: **LI, Todd, M., C.**; International Business Machines Corporation, Dept. 18G, Bldg. 300/482, 2070 Route 52, Hopewell Junction, NY 12533 (US).


(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A LOW-K PRE-METAL DIELECTRIC SEMICONDUCTOR STRUCTURE



(57) Abstract: A low-k pre-metal dielectric (PMD) structure on a semiconductor wafer and a method for making the PMD structure is described. The PMD structure includes a low-k dielectric film (170) that has good gap-filling characteristics, particularly where the gap (160) formed between features (130), such as gate stacks, has an aspect ratio greater than about 3. The method for forming the PMD structure uses a thermal sub-atmospheric CVD process that includes a carbon-containing organometallic precursor (260) such as TMCTS or OMCTS, an ozone-containing gas (270), and a source of dopants (280) for gettering alkali elements and for lowering the reflow temperature of the dielectric while attaining the desired low-k and gap-filling properties of the dielectric film (170). Phosphorous is a preferred dopant for gettering alkali elements such as sodium. Additional dopants for lowering the reflow temperature include, but are not limited to boron, germanium, arsenic, fluorine or combination thereof.

WO 03/019619 A2