

FLIGHT ENVELOPE DISPLAY

BACKGROUND

The present disclosure relates generally to
5 systems and methods for displaying the performance of an
aircraft to a flight crew during a flight of the aircraft.
More particularly, the present disclosure relates to
displaying the current performance of an aircraft during
flight with respect to a representation of a flight envelope
10 or other performance capabilities of the aircraft.

The flight envelope of an aircraft may refer to
the capabilities of the aircraft in terms of airspeed and
load factor or altitude. The flight envelope also may be
referred to as the service envelope or performance envelope.
15 In some cases, the flight envelope may refer to the physical
limits of the capabilities of the aircraft. In this case,
the aircraft cannot be operated outside of the flight
envelope.

In other cases, the flight envelope may refer to a
20 limit within a threshold from the physical limits of the
capabilities of the aircraft. For example, in this case,
the flight envelope may be selected to provide a margin of
safety between the flight envelope and the physical limits
of the capabilities of the aircraft. In some cases an
25 aircraft may be certified for operation within such a flight
envelope that provides a margin of safety between the flight
envelope and the physical limits of the capabilities of the
aircraft. In any case, it may be desirable that an aircraft
is not operated outside of a flight envelope that provides a
30 margin of safety between the flight envelope and the
physical limits of the capabilities of the aircraft.

Flight envelope protection may be provided in some
form in modern commercial fly-by-wire aircraft and other
aircraft. Flight envelope protection may be implemented as

an extension of an aircraft control system that may prevent the pilot of the aircraft from making control commands that would force the aircraft to exceed its structural and aerodynamic operating limits. For example, flight envelope protection may identify the aircraft flight envelope, including a margin of safety, and use this information to stop pilots from making control inputs that would put the aircraft outside the flight envelope. Flight envelope protection may increase aircraft safety by allowing the pilot to apply maximum control forces in emergency conditions while the flight envelope protection prevents the pilot from inadvertently driving the aircraft outside of the limits of operational safety.

A stick shaker may be an example of flight envelope protection that may be used on some aircraft. The stick refers to an apparatus that is moved by the pilot to control the aircraft. The stick shaker may be activated to shake the stick to provide a warning to the pilot when the aircraft is operated at a speed or altitude that may be close to the performance limitations of the aircraft.

On many commercial and other aircraft the current speed and altitude of the aircraft may be displayed on moving tape displays. These tape displays may be part of the primary flight display on the flight deck of the aircraft. Indications may be provided on the tape displays to indicate to the pilot whether it is safe to operate the aircraft at a given speed and altitude. The positions of the indications on the tape displays may depend on the current configuration of the aircraft, such as the current configuration of the aircraft flaps.

Current systems and methods may provide for warning a pilot when an aircraft is being operated near the flight envelope limits or for preventing the pilot from operating the aircraft outside of the flight envelope.

Current systems and methods may display the current speed and altitude of the aircraft to the pilot along with indications of the speed and altitude performance capability limitations of the aircraft. However, current systems and methods do not provide an indication to the pilot of where the aircraft is currently operating within the flight envelope until the aircraft is operated near the limits of the flight envelope.

Accordingly, it would be beneficial to have a method and apparatus that takes into account one or more of the issues discussed above as well as possibly other issues.

SUMMARY

An illustrative embodiment of the present disclosure provides a method for displaying aircraft performance characteristics. A two-dimensional representation of a performance envelope indicating performance capabilities of an aircraft is displayed. A current performance of the aircraft is identified. A performance indication of the current performance with respect to the performance envelope is displayed on the two-dimensional representation of the performance envelope. A position of the performance indication on the two-dimensional representation of the performance envelope indicates the current performance with respect to the performance envelope.

Another illustrative embodiment of the present disclosure provides an apparatus comprising a current performance identifier and a display generator. The current performance identifier is configured to identify a current performance of an aircraft. The display generator is configured to display a two-dimensional representation of a performance envelope indicating performance capabilities of the aircraft and to display a performance indication of the

current performance with respect to the performance envelope on the two-dimensional representation of the performance envelope. A position of the performance indication on the two-dimensional representation of the performance envelope
5 indicates the current performance with respect to the performance envelope.

Another illustrative embodiment of the present disclosure provides another method for displaying aircraft performance characteristics. A two-dimensional
10 representation of a flight envelope for an aircraft is displayed. The two-dimensional representation of the flight envelope comprises a display of speed versus altitude performance capabilities of the aircraft. A current speed and a current altitude of the aircraft are identified. A
15 performance indication of the current speed and the current altitude is displayed on the two-dimensional representation of the flight envelope. A position of the performance indication on the two-dimensional representation of the flight envelope indicates the current speed and the current
20 altitude with respect to the flight envelope.

The features, functions, and benefits may be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the
25 following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended
30 claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives, and features thereof will best be understood by reference to the following detailed description of illustrative embodiments

of the present disclosure when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an illustration of a block diagram of an aircraft performance display system in accordance with an illustrative embodiment;

Figure 2 is an illustration of a flight envelope display in accordance with an illustrative embodiment;

Figure 3 is an illustration of a turn rate envelope display in accordance with an illustrative embodiment;

Figure 4 is an illustration of a combined flight envelope and turn rate envelope display in accordance with an illustrative embodiment;

Figure 5 is an illustration of a flowchart of a process for displaying aircraft performance in accordance with an illustrative embodiment; and

Figure 6 is an illustration of a block diagram of a data processing system in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

The different illustrative embodiments recognize and take into account a number of different considerations. "A number", as used herein with reference to items, means one or more items. For example, "a number of different considerations" means one or more different considerations.

The different illustrative embodiments recognize and take into account that current systems and methods may not allow the flight crew of an aircraft to assess current aircraft performance characteristics during a flight with respect to the performance capabilities of the aircraft as represented by the currently applicable flight envelope. Currently, the flight crew may not be able to identify where the aircraft is operating within the flight envelope without

having to manually or mentally combine information from a variety of different sources.

The illustrative embodiments provide a system and method for displaying an indication of the current performance of an aircraft overlaid on a representation of the currently applicable flight envelope. Illustrative embodiments therefore improve the situational awareness of the flight crew regarding the current flight envelope and the current performance of the aircraft with respect to the flight envelope.

Turning now to **Figure 1**, an illustration of a block diagram of an aircraft performance display system is depicted in accordance with an illustrative embodiment. In this example, aircraft performance display system **100** may be a system for displaying aircraft performance characteristics for aircraft **102**.

Aircraft **102** may be any vehicle configured for traveling through the air. For example, without limitation, aircraft **102** may be a fixed or rotary wing aircraft or a lighter than air vehicle. Aircraft **102** may be an aerospace vehicle configured for traveling through the air and in space. In this case, illustrative embodiments may be used to display performance characteristics of the aerospace vehicle while the vehicle is being operated in the atmosphere. Aircraft **102** may be a manned aircraft or an unmanned air vehicle.

Aircraft performance display system **100** may be implemented in a data processing system on aircraft **102**. For example, without limitation, some or all of the functions performed by aircraft performance display system **100** as described herein may be implemented in software running on a data processing system on aircraft **102**. Alternatively, some or all of the functions performed by

aircraft performance display system **100** as described herein may be implemented in hardware on aircraft **102**.

Some or all of the functions performed by aircraft performance display system **100** as described herein may be implemented on a data processing system, other hardware, or both, that is not on aircraft **102**. For example, in the case where aircraft **102** is an unmanned air vehicle, a portion of aircraft performance display system **100** may be implemented on a data processing system, other hardware, or both that is not on aircraft **102**. In this case, aircraft performance display system **100** may be configured for displaying aircraft performance characteristics for use by a pilot or other operator for remote control of aircraft **102** from a location that is not on aircraft **102**.

Aircraft performance display system **100** may comprise current configuration identifier **104**, performance envelope selector **106**, current performance identifier **108**, and display generator **110**.

Current configuration identifier **104** may be configured to identify current configuration **112** of aircraft **102**. Current configuration **112** may refer to any current characteristics of aircraft **102** that may affect the performance capabilities of aircraft **102**. For example, current configuration **112** may refer to the current characteristics of any changeable characteristics of aircraft **102** that may be changed to affect the performance characteristics of aircraft **102**. For example, without limitation, current configuration **112** may include flap configuration **114**. In this case, flap configuration **114** may refer to the current flap settings on aircraft **102**.

Current configuration identifier **104** may be configured to identify current configuration **112** using information provided by configuration identification systems **116** on aircraft **102**. Configuration identification systems

116 may include any systems or devices on aircraft **102** that may provide information on the current characteristics of aircraft **102** that may affect the performance capabilities of aircraft **102**.

5 Performance envelope selector **106** may be configured to select performance envelope **118** for current configuration **112** of aircraft **102**. Performance envelope **118** indicates performance capabilities **119** of aircraft **102** for current configuration **112**. For example, without limitation,
10 performance envelope selector **106** may be configured to select or otherwise determine performance envelope **118** for current configuration **112** using information describing the performance capabilities of aircraft **102** for various configurations of aircraft **102** provided in performance
15 capabilities database **120**.

 In the present application, including in the claims, performance capabilities **119** may refer to physical limits on the performance of aircraft **102**. Alternatively, performance capabilities **119** may refer to limits on the
20 performance of aircraft **102** that may be related to physical limits on the performance of aircraft **102**. For example, without limitation, performance capabilities **119** may refer to limits on the performance of aircraft **102** defined by a margin of safety with respect to the physical limits on the
25 performance of aircraft **102**. As another example, performance capabilities **119** may refer to limits on the performance of aircraft **102** within which aircraft **102** is certified to be operated.

 Performance envelope **118** may indicate various
30 different performance capabilities **119** of aircraft **102**. For example, without limitation, performance envelope **118** may include flight envelope **122**, turn rate envelope **124**, or both. Flight envelope **122** may indicate speed versus altitude performance capabilities of aircraft **102**. Turn

rate envelope **124** may indicate speed versus turn rate performance capabilities of aircraft **102**.

Performance envelope selector **106** also may be configured to identify threshold of performance capabilities **126**. Threshold of performance capabilities **126** may indicate a difference from performance capabilities **119** indicated by performance envelope **118**. For, example, without limitation, threshold of performance capabilities **126** may be selected to define a margin of safety or other desired difference from performance capabilities **119** indicated by performance envelope **118**.

Current performance identifier **108** may be configured to identify current performance **128** of aircraft **102**. Current performance **128** may include various current performance characteristics of aircraft **102**. For example, without limitation, current performance **128** may include speed **132** of aircraft **102**, altitude **134** of aircraft **102**, turn rate **136** of aircraft **102**, bank angle **138** of aircraft **102**, climb angle **140** of aircraft **102**, or other current performance characteristics or combinations of current performance characteristics of aircraft **102**.

Current performance identifier **108** may identify current performance **128** from information provided by various performance identification systems **141** on aircraft **102**. Performance identification systems **141** may include any appropriate systems or devices on aircraft **102** for providing information from which current performance **128** of aircraft **102** may be identified or derived. For example, without limitation, performance identification systems **141** may include a speedometer and an altimeter for identifying speed **132** and altitude **134**, respectively.

Current performance **128** may be identified directly from information provided by performance identification systems **141** or may be derived from information provided by

performance identification systems **141**. For example, without limitation, bank angle **138** and climb angle **140** may be identified directly from information provided by performance identification systems **141**. Turn rate **136** may
5 be derived from bank angle **138** and climb angle **140**.

Display generator **110** may be configured to generate display **142** from performance envelope **118** and current performance **128**. Display **142** may include two-dimensional representation of performance envelope **144** and
10 performance indication **146** displayed on two-dimensional representation of performance envelope **144**.

Two-dimensional representation of performance envelope **144** may be a two-dimensional representation of performance envelope **118** selected by performance envelope
15 selector **106**. For example, without limitation, two-dimensional representation of performance envelope **144** may include a two-dimensional representation of flight envelope **122**, a two-dimensional representation of turn rate envelope **124**, or both. Two-dimensional representation of performance
20 envelope **144** may include a two dimensional representation of performance envelope **118** for current configuration **112**, a two-dimensional representation of performance envelope **118** for a configuration of aircraft **102** other than current configuration **112**, or both.

25 Performance indication **146** may be of any appropriate shape and size. The position of performance indication **146** on two-dimensional representation of performance envelope **144** indicates current performance **128** of aircraft **102** with respect to performance envelope **118**.
30 For example, without limitation, the position of performance indication **146** on two-dimensional representation of performance envelope **144** may indicate speed **132** and altitude **134** of aircraft **102** with respect to flight envelope **122**,

speed **132** and turn rate **136** of aircraft **102** with respect to turn rate envelope **124**, or both.

Display generator **110** also may be configured to display warning indication **148** in response to current
5 performance **128** exceeding threshold of performance capabilities **126**. For example, without limitation, warning indication **148** may include changing the color, flashing, or changing other characteristics or combinations of characteristics of the display of performance indication **146**
10 in response to current performance **128** exceeding threshold of performance capabilities **126**.

Display **142** may be presented on any appropriate display device **150**. For example, without limitation, display **142** may be presented to a pilot or other flight crew
15 of aircraft **102** on display device **150** that is part of flight deck display **152** on the flight deck of aircraft **102**.

The illustration of **Figure 1** is not meant to imply physical or architectural limitations to the manner in which different illustrative embodiments may be implemented.
20 Other components in addition to, in place of, or both in addition to and in place of the ones illustrated may be used. Some components may be unnecessary in some illustrative embodiments. Also, the blocks are presented to illustrate some functional components. One or more of these
25 blocks may be combined or divided into different blocks when implemented in different illustrative embodiments.

Turning now to **Figure 2**, an illustration of a flight envelope display is depicted in accordance with an illustrative embodiment. In this example, flight envelope
30 display **200** is an example of one implementation of display **142** in **Figure 1**.

In this example, flight envelope display **200** includes two-dimensional representation of flight envelope **202** and performance indication **204**. Two-dimensional

representation of flight envelope **202** indicates speed versus altitude performance capabilities of an aircraft. The position of performance indication **204** on two-dimensional representation of flight envelope **202** indicates the current speed and altitude of the aircraft with respect to the flight envelope. In this example, restricted area **206** of the flight envelope also is identified on two-dimensional representation of flight envelope **202**.

Two-dimensional representation of flight envelope **202** may indicate the flight envelope for the current configuration of an aircraft. For example, two-dimensional representation of flight envelope **202** may indicate the flight envelope for current flap settings of the aircraft. Two-dimensional representation of flight envelope **202** also may indicate the flight envelope for other configurations of the aircraft. In this example, portions **208** and **210** of two-dimensional representation of flight envelope **202** indicate changes to the flight envelope for other flap settings. Thus, a pilot may use flight envelope display **200** to visualize the effect of changing flap settings on the flight envelope for the aircraft.

Turning now to **Figure 3**, an illustration of a turn rate envelope display is depicted in accordance with an illustrative embodiment. In this example, turn rate envelope display **300** is another example of one implementation of display **142** in **Figure 1**.

In this example, turn rate envelope display **300** includes two-dimensional representation of turn rate envelope **302** and performance indication **304**. Two-dimensional representation of turn rate envelope **302** indicates speed versus turn rate performance capabilities of an aircraft. The position of performance indication **304** on two-dimensional representation of turn rate envelope **302**

indicates the current speed and turn rate of the aircraft with respect to the turn rate envelope.

Turning now to **Figure 4**, an illustration of a combined flight envelope and turn rate envelope display is depicted in accordance with an illustrative embodiment. In this example, display **400** is another example of one implementation of display **142** in **Figure 1**.

In this example, display **400** includes two-dimensional representation of flight envelope **402**, two-dimensional representation of turn rate envelope **404**, and performance indication **406**. Two-dimensional representation of flight envelope **402** indicates speed versus altitude performance capabilities of an aircraft. Two-dimensional representation of turn rate envelope **404** indicates speed versus turn rate performance capabilities of the aircraft. In this example, two-dimensional representation of flight envelope **402** and two-dimensional representation of turn rate envelope **404** are displayed at the same time with respect to common x-axis **408** indicating speed.

In this example, performance indication **406** comprises first performance indication **410** and second performance indication **412**. The position of first performance indication **410** with respect to two-dimensional representation of flight envelope **402** indicates the current speed and altitude of the aircraft with respect to the flight envelope. The position of second performance indication **412** with respect to two-dimensional representation of turn rate envelope **404** indicates the current speed and turn rate of the aircraft with respect to the turn rate envelope. In this example, first performance indication **410** and second performance indication **412** move together in parallel with respect to x-axis **408** as the current speed of the aircraft changes.

Turning now to **Figure 5**, an illustration of a flowchart of a process for displaying aircraft performance is depicted in accordance with an illustrative embodiment. The process in **Figure 5** may be implemented, for example, in
5 aircraft performance display system **100** in **Figure 1**.

The process may begin by identifying the current configuration of an aircraft (operation **502**). For example, without limitation, operation **502** may include identifying the current flap settings of the aircraft. Based on the
10 current configuration of the aircraft, a performance envelope then may be selected (operation **504**). The performance envelope indicates performance capabilities of the aircraft for the current configuration of the aircraft. For example, without limitation, the performance envelope
15 may be a flight envelope, a turn rate envelope, or both. A two-dimensional representation of the performance envelope then may be displayed (operation **506**).

Current performance of the aircraft may be identified (operation **508**). A performance indication of the
20 current performance then may be displayed on the representation of the performance envelope (operation **510**). The position of the performance indication on the representation of the performance envelope indicates the current performance with respect to the performance
25 envelope.

It then may be determined whether the current performance of the aircraft exceeds a threshold of performance capabilities of the aircraft (operation **512**). If the current performance does not exceed the threshold of performance capabilities the process may terminate. If the
30 current performance does exceed the threshold of performance capabilities a warning indication may be displayed (operation **514**) with the process terminating thereafter. For example, without limitation, operation **514** may include

changing the color, flashing, or changing another characteristic or combination of characteristics of the performance indication displayed in operation **510**.

One or more of the illustrative embodiments
5 provide a capability that allows a flight crew to assess current aircraft performance characteristics with reference to a currently applicable flight envelope. The currently applicable flight envelope may be selected based on the current configuration of the aircraft, such as the current
10 flap settings. The illustrative embodiments allow the flight crew to identify margins and safety buffers at one view without having to combine information from different sources.

Turning now to **Figure 6**, an illustration of a
15 block diagram of a data processing system is depicted in accordance with an illustrative embodiment. In this example, data processing system **600** is an example of one implementation of a data processing system for implementing aircraft performance display system **100** in **Figure 1**.

20 In this illustrative example, data processing system **600** includes communications fabric **602**. Communications fabric **602** provides communications between processor unit **604**, memory **606**, persistent storage **608**, communications unit **610**, input/output (I/O) unit **612**, and
25 display **614**. Memory **606**, persistent storage **608**, communications unit **610**, input/output (I/O) unit **612**, and display **614** are examples of resources accessible by processor unit **604** via communications fabric **602**.

Processor unit **604** serves to run instructions for
30 software that may be loaded into memory **606**. Processor unit **604** may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation. Further, processor unit **604** may be implemented using a number of heterogeneous processor

systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit **604** may be a symmetric multi-processor system containing multiple processors of the same type.

Memory **606** and persistent storage **608** are examples of storage devices **616**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and other suitable information either on a temporary basis or a permanent basis. Storage devices **616** also may be referred to as computer readable storage devices in these examples. Memory **606**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **608** may take various forms, depending on the particular implementation.

For example, persistent storage **608** may contain one or more components or devices. For example, persistent storage **608** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **608** also may be removable. For example, a removable hard drive may be used for persistent storage **608**.

Communications unit **610**, in these examples, provides for communications with other data processing systems or devices. In these examples, communications unit **610** is a network interface card. Communications unit **610** may provide communications through the use of either or both physical and wireless communications links.

Input/output (I/O) unit **612** allows for input and output of data with other devices that may be connected to data processing system **600**. For example, input/output (I/O) unit **612** may provide a connection for user input through a

keyboard, a mouse, and/or some other suitable input device. Further, input/output (I/O) unit **612** may send output to a printer. Display **614** provides a mechanism to display information to a user.

5 Instructions for the operating system, applications, and/or programs may be located in storage devices **616**, which are in communication with processor unit **604** through communications fabric **602**. In these illustrative examples, the instructions are in a functional
10 form on persistent storage **608**. These instructions may be loaded into memory **606** for execution by processor unit **604**. The processes of the different embodiments may be performed by processor unit **604** using computer-implemented instructions, which may be located in a memory, such as
15 memory **606**.

 These instructions are referred to as program instructions, program code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit **604**. The program code in
20 the different embodiments may be embodied on different physical or computer readable storage media, such as memory **606** or persistent storage **608**.

 Program code **618** is located in a functional form on computer readable media **620** that is selectively removable
25 and may be loaded onto or transferred to data processing system **600** for execution by processor unit **604**. Program code **618** and computer readable media **620** form computer program product **622** in these examples. In one example, computer readable media **620** may be computer readable storage
30 media **624** or computer readable signal media **626**.

 Computer readable storage media **624** may include, for example, an optical or magnetic disk that is inserted or placed into a drive or other device that is part of persistent storage **608** for transfer onto a storage device,

such as a hard drive, that is part of persistent storage **608**. Computer readable storage media **624** also may take the form of a persistent storage, such as a hard drive, a thumb drive, or a flash memory, that is connected to data processing system **600**. In some instances, computer readable storage media **624** may not be removable from data processing system **600**.

In these examples, computer readable storage media **624** is a physical or tangible storage device used to store program code **618** rather than a medium that propagates or transmits program code **618**. Computer readable storage media **624** is also referred to as a computer readable tangible storage device or a computer readable physical storage device. In other words, computer readable storage media **624** is a media that can be touched by a person.

Alternatively, program code **618** may be transferred to data processing system **600** using computer readable signal media **626**. Computer readable signal media **626** may be, for example, a propagated data signal containing program code **618**. For example, computer readable signal media **626** may be an electromagnetic signal, an optical signal, and/or any other suitable type of signal. These signals may be transmitted over communications links, such as wireless communications links, optical fiber cable, coaxial cable, a wire, and/or any other suitable type of communications link. In other words, the communications link and/or the connection may be physical or wireless in the illustrative examples.

In some illustrative embodiments, program code **618** may be downloaded over a network to persistent storage **608** from another device or data processing system through computer readable signal media **626** for use within data processing system **600**. For instance, program code stored in a computer readable storage medium in a server data

processing system may be downloaded over a network from the server to data processing system **600**. The data processing system providing program code **618** may be a server computer, a client computer, or some other device capable of storing and transmitting program code **618**.

The different components illustrated for data processing system **600** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to and/or in place of those illustrated for data processing system **600**. Other components shown in **Figure 6** can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code. As one example, data processing system **600** may include organic components integrated with inorganic components and/or may be comprised entirely of organic components excluding a human being. For example, a storage device may be comprised of an organic semiconductor.

In another illustrative example, processor unit **604** may take the form of a hardware unit that has circuits that are manufactured or configured for a particular use. This type of hardware may perform operations without needing program code to be loaded into a memory from a storage device to be configured to perform the operations.

For example, when processor unit **604** takes the form of a hardware unit, processor unit **604** may be a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device is configured to perform the number of operations. The device may be reconfigured at a later time or may be permanently

configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. With this type of implementation, program code **618** may be omitted, because the processes for the different embodiments are implemented in a hardware unit.

In still another illustrative example, processor unit **604** may be implemented using a combination of processors found in computers and hardware units. Processor unit **604** may have a number of hardware units and a number of processors that are configured to run program code **618**. With this depicted example, some of the processes may be implemented in the number of hardware units, while other processes may be implemented in the number of processors.

In another example, a bus system may be used to implement communications fabric **602** and may be comprised of one or more buses, such as a system bus or an input/output bus. Of course, the bus system may be implemented using any suitable type of architecture that provides for a transfer of data between different components or devices attached to the bus system.

Additionally, communications unit **610** may include a number of devices that transmit data, receive data, or both transmit and receive data. Communications unit **610** may be, for example, a modem or a network adapter, two network adapters, or some combination thereof. Further, a memory may be, for example, memory **606**, or a cache, such as that found in an interface and memory controller hub that may be present in communications fabric **602**.

The flowcharts and block diagrams described herein illustrate the architecture, functionality, and operation of possible implementations of systems, methods, and computer

program products according to various illustrative embodiments. In this regard, each block in the flowcharts or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable
5 instructions for implementing the specified logical function or functions. It should also be noted that, in some alternative implementations, the functions noted in a block may occur out of the order noted in the figures. For example, the functions of two blocks shown in succession may
10 be executed substantially concurrently, or the functions of the blocks may sometimes be executed in the reverse order, depending upon the functionality involved.

The description of the different illustrative embodiments has been presented for purposes of illustration
15 and description and is not intended to be exhaustive or to limit the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different benefits as compared to
20 other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various
25 embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS:

What is claimed is:

- 5 1. A method for displaying aircraft performance characteristics, comprising:
 - displaying a two-dimensional representation of a performance envelope indicating performance capabilities of an aircraft;
 - 10 identifying a current performance of the aircraft; and displaying a performance indication of the current performance with respect to the performance envelope on the two-dimensional representation of the performance envelope, wherein a position of the performance indication on the two-
 - 15 dimensional representation of the performance envelope indicates the current performance with respect to the performance envelope.
2. The method of claim 1 further comprising:
 - 20 identifying a current configuration of the aircraft; and selecting the performance envelope based on the current configuration of the aircraft.
- 25 3. The method of claim 2, wherein the current configuration of the aircraft comprises a flap configuration of the aircraft.
4. The method of claim 1 further comprising:
 - 30 displaying a warning indication on the two-dimensional representation of the performance envelope in response to the current performance exceeding a threshold of the performance capabilities.

5. The method of claim 4, wherein displaying the warning indication comprises changing a color of the performance indication in response to the current performance exceeding the threshold of the performance capabilities.

5

6. The method of claim 1, wherein the performance envelope is a flight envelope and the two-dimensional representation of the performance envelope comprises a display of speed versus altitude.

10

7. The method of claim 1, wherein the performance envelope is a turn rate envelope and the two-dimensional representation of the performance envelope comprises a display of speed versus turn rate.

15

8. An apparatus, comprising:

a current performance identifier configured to identify a current performance of an aircraft; and

a display generator configured to display a two-dimensional representation of a performance envelope indicating performance capabilities of the aircraft and to display a performance indication of the current performance with respect to the performance envelope on the two-dimensional representation of the performance envelope, wherein a position of the performance indication on the two-dimensional representation of the performance envelope indicates the current performance with respect to the performance envelope.

9. The apparatus of claim 8 further comprising:

a current configuration identifier configured to identify a current configuration of the aircraft; and

a performance envelope selector configured to select the performance envelope based on the current configuration of the aircraft.

5 10. The apparatus of claim 9, wherein the current configuration of the aircraft comprises a flap configuration of the aircraft.

10 11. The apparatus of claim 8, wherein the display generator is further configured to display a warning indication on the two-dimensional representation of the performance envelope in response to the current performance exceeding a threshold of the performance capabilities.

15 12. The apparatus of claim 11, wherein the display generator is configured to change a color of the performance indication in response to the current performance exceeding the threshold of the performance capabilities.

20 13. The apparatus of claim 8, wherein the performance envelope is a flight envelope and the two-dimensional representation of the performance envelope comprises a display of speed versus altitude.

25 14. The apparatus of claim 8, wherein the performance envelope is a turn rate envelope and the two-dimensional representation of the performance envelope comprises a display of speed versus turn rate.

30 15. A method for displaying aircraft performance characteristics, comprising:

displaying a two-dimensional representation of a flight envelope for an aircraft, wherein the two-dimensional representation of the flight envelope comprises a display of

speed versus altitude performance capabilities of the aircraft;

identifying a current speed and a current altitude of the aircraft; and

5 displaying a first performance indication of the current speed and the current altitude on the two-dimensional representation of the flight envelope, wherein a position of the first performance indication on the two-dimensional representation of the flight envelope indicates
10 the current speed and the current altitude with respect to the flight envelope.

16. The method of claim 15 further comprising:

identifying a current configuration of the aircraft;

15 and

selecting the flight envelope based on the current configuration of the aircraft.

17. The method of claim 16, wherein the current

20 configuration of the aircraft comprises a flap configuration of the aircraft.

18. The method of claim 15 further comprising:

25 displaying a warning indication on the two-dimensional representation of the flight envelope in response to the current speed and the current altitude exceeding a threshold of the speed versus altitude performance capabilities.

30 19. The method of claim 18, wherein displaying the warning indication comprises changing a color of the first performance indication in response to the current speed and the current altitude exceeding the threshold of the speed versus altitude performance capabilities.

20. The method of claim 15 further comprising:

displaying a two-dimensional representation of a turn
rate envelope for the aircraft on the two-dimensional
5 representation of the flight envelope, wherein the two
dimensional representation of the turn rate envelope
comprises a display of speed versus turn rate performance
capabilities of the aircraft;

identifying a current turn rate of the aircraft; and

10 displaying a second performance indication of the
current speed and the current turn rate on the two-
dimensional representation of the turn rate envelope,
wherein the position of the second performance indication on
the two-dimensional representation of the turn rate envelope
15 indicates the current speed and the current turn rate with
respect to the turn rate envelope.