

DEVICE AND METHOD FOR COMBINING AND
PROCESSING SEVERAL PAPER WEBS

The invention relates to a device for combining and processing several paper webs according to the preamble of Claim 1, as well as a method for combining and processing several paper webs.

The expression "processing of a paper web" in the broadest sense of the term is understood to be any form of processing, be it printing, laminating, numbering, perforating, or punching, and the application or provision (by gluing) of plastic cards such as credit cards, with sample pouches, labels, or the production of address windows and their covering by transparent foils.

When an individual endless paper web is processed with synchronization of the basic processes, fault-free finishing of said web, such as folding or cross-cutting, depends uniquely on proper maintenance of web speed. This is accomplished for example by registration holes being provided on the paper web and with toothed belts, located along the finishing or processing line, engaging said holes, thus ensuring a synchronous feed of the paper web. This type of longitudinal register control however has the disadvantage that firstly this perforated edge must generally be removed in the unit for further processing and secondly this bilateral perforated edge means loss of material that has a high value in itself.

In a known device, this disadvantage is overcome by providing the paper web with markings that are registered by a web feeler. This feeler is located upstream of the unit for further processing. In this way, with appropriate control, further processing in register, such as printing, embossing, stamping or cutting of webs that have already been processed, preprinted for example, is made possible. This control regulates the drive of the pay-out rollers on the pay-out unit, by which the format length can be influenced. Alternatively, the register can also be corrected using a synchronous motor that

influences the drive of the feed rollers located upstream from the unit for further processing.

5 The situation is completely different however when it is desired not only to process and finish a web, a requirement which arises for example when printing newspapers, but several webs must be processed, possibly in different ways, for example, glued-in sample packs or removable reply cards. Thus far, no satisfactory solutions have been found for these. Of course it is possible to guide all the paper webs using toothed belts but this would not allow independent processing of individual webs. The other device described above could be used for a paper web but not for a plurality of webs guided in common, one above the other for example, and then possibly processed independently and possibly are webs of different quality or with different processing (handling, for example).

10 Hence the goal of the invention is to provide a device and a method by which several paper webs are brought together and processed (possibly independently of one another), and then, correctly registered longitudinally, can be fed jointly to a unit for further processing. One way of achieving this goal is by combining the features of Claim 1 and/or Claim 7. Advantageous embodiments are described in the dependent claims.

25 The term "paper webs" according to the invention refers to all materials provided in the form of a web that are possibly subjected to a processing procedure, which in any event are combined with other webs, and which then are subjected to further processing jointly with these other webs. Thus for example it includes foil webs, including thin cardboard webs and paper webs of different thicknesses and qualities.

30 The term "combination" of the individual paper webs refers to the joint arrangement of the already-unrolled paper webs (possibly at a distance from one another) before they pass through the processing line

where they are possibly processed independently of one another or are not processed at all, in other words, they possibly travel different paths. Thus it is possible according to the invention for one of the webs to pass through the processing line without being processed while another web is guided over deflection rollers and subjected to finishing processes. In the same way, however, all webs can be processed simultaneously in a processing unit, crimped or numbered for example..

For congruent longitudinal register control of the at least two paper webs, the means comprise means for creating paper tension, which is essentially the same for each of the at least two paper webs, across the width of the individual webs, with the register of the markings first being applied to the paper webs being of relevance through the web feelers in their time sequence //?// and this registration can be used to regulate the longitudinal register of the at least two paper webs. It is only because the combined webs are under a certain paper tension that differences in the longitudinal register that can occur for example because of the processing in the processing section and which are determined by the register of the markings by the web feelers can be eliminated once again. In addition, a drive or brake device is controlled by a control unit associated in particular with the respective withdrawal rolls, since the latter, as driven rolls, determine the speed of the web.

In order to ensure register-exact processing of the individual webs and their correct common finishing in the unit for further processing through the processing line and on through the individual processing units, means for creating paper tension are provided at least between the processing line and the unit for further processing and since the webs in the unit for further processing are generally no longer under tension, as close as possible upstream from the unit for further processing.

If the means for developing the paper tension are provided as a pair of withdrawal rollers in the form of rubber rolls, because of the relatively flexible surface of the latter, the pressure acting on the paper webs as they are brought together can be distributed more uniformly over the width of the paper web than would be the case for example in known withdrawal rolls, an important requirement for processed webs. If such rubber rolls are provided on their circumferences with a certain profile, the processing products that are applied to the paper web(s) as the paper webs pass through the rubber rolls will be taken up in the matching recesses of the profile, so that the pressure on the paper webs remains constant as they are brought together.

If a web feeler, which registers the markings of the uppermost web, is provided in the vicinity of the withdrawal rolls, a guarantee is provided that the further processing that then takes place proceeds with exact longitudinal registration, especially when the unit for further processing abuts the withdrawal rolls as closely as possible. Registration of the markings on the paper webs guided below the uppermost web is accomplished by web feelers located upstream of the processing line, and therefore the longitudinal registration required for individual processing is simultaneously correct as well, and is located especially directly upstream of the combination with the respective upper paper web

The invention will now be described with reference to the drawings.

Figure 1 shows a pay-out unit;

Figure 2 is a side view of the device according to the invention for combining and processing three paper webs with three pay-out units; and

Figure 3 is a view of the device from above, corresponding to Figure 2.

Figure 1 shows a pay-out unit 1 in which a paper web 3 is unrolled from a roll 2. For this purpose the axis 4 of roll 2 is mounted on a diagonal roll guide 5,

the paper web 3 is unrolled over a roll 6 at the circumference of roll 2, said roll 6 generally being driven and functioning as a brake, two withdrawal rolls 7 and 8 with differential transmissions pull paper web 3 off with a known selectable or regulatable speed. This determines the speed of the paper web. The register of the web is determined by read-head 26 and supplied to a control unit 19 as a reference value. Then paper web 3 passes through a web edge control 9 that allows additional processing of paper web 3 with exact lateral registration.

As can be seen in Figures 2 and 3, paper or foil webs 3a, 3b, and 3c are unrolled from a plurality of such pay-out units 1a, 1b, and 1c located side by side. The individual webs pass helical crosses 10a, 10b, and 10c, where they are guided over deflection rolls 13a, 13b, and 13c and each successive web comes to rest beneath the previous web(s). Then they are fed to a processing line 11.

In processing line 11, the three unrolled webs 3a, 3b, and 3c are processed either jointly or independently of one another, depending on the desired processing steps. Thus for example numbering machines, printing media (such as ink-jet or laser printers), multiflex units, stapling/punching stations, or even rotary feeders can be provided for applying packets. Transmission boxes 12 are provided for each of these freely locatable intermediate modules, said boxes each being provided with a 360° register.

The paper webs do not have to be guided by toothed belts in processing line 11, as is known from the prior art, but are freely tensioned in this area and, depending on the intermediate modules to be provided, are guided over deflection rollers.

One web for example, which is moistened in the processing line, is stretched as a result. In order to compensate for this effect, the web is guided over intermediate rolls or around additional cylinders in order to maintain the desired tension.

After passing through processing line 11a, webs 3a, 3b, and 3c are guided between two powered rubber cylinders 14a and 14b and fed to a unit 15 for further processing. In the known units for processing and further processing, pulling groups generally designed as mechanical press rolls, are provided downstream from the pay-out unit. Downstream from the processing line and upstream from the unit for further processing, no additional pulling groups can be provided. Guide rolls located upstream from the unit for further processing, and possibly regulatable, as stated at the outset, serve in known devices for correcting the web register but not for creating a certain web tension.

It is possible on the other hand by using rubber cylinders 14a and 14b upstream of unit 15 for further processing, to develop a paper tension that is uniform across the width of the web and to monitor it. Rubber sheaths with different profiles can be pulled over the rolls and thus adapted to different processing procedures. Thus for example recesses can be provided on these rubber cylinders, into which sample packets fit by means of a card dispenser provided in the processing line, plastic cards glued to the webs, or applied by means of a rotary feeder. As a result, the pressure on all of the webs that have been brought together at this point will remain uniform over the width of the web. These rubber cylinders 14a and 14b are driven, essentially synchronously with the development of the printed image. The paper webs are therefore pulled and kept stretched across processing line 11. The basic setting is then made on the basis of a check of the superimposed paper webs by the operating personnel while the ongoing corrections during the processing procedure are performed with the regulating devices described below.

In addition, further pairs of withdrawal rolls can be provided, likewise preferably designed as rubber cylinders. Such an arrangement is advantageous when products consisting of many layers are involved, since when several paper webs are combined, air cushions remain

between the individual webs, especially the innermost ones, that can produce undesired modulations in the individual registers. For this purpose, at least two pairs of withdrawal rolls should be mounted one behind the other so that variations caused by air cushions can be compensated thereby. However, pairs of withdrawal rolls can also be provided as well between certain processing assemblies or units in the processing line, which may prove advantageous especially on long processing lines in order to keep the tension constant over the length of the processing line.

In general, rolls with a standard circumference of 24 inches (60.96 cm) are used as withdrawal rolls. It is obvious that the circumferential speed of these withdrawal rolls must be adapted to the respective thickness of the paper web(s) guided in between. Preferably, the circumferential speed of the withdrawal roll(s) can be modified as well on the basis of available information on the registration of the markings,. For this purpose, by means of control unit 19, a servoregulator 22d for operating a servomotor 20d on transmission 21d of the withdrawal rolls, preferably designed as rubber cylinders 14a and 14b, is controlled. This ensures that the paper webs in the adjoining unit 15 for further processing can be processed exactly in register.

A main drive 23 is provided for driving withdrawal rolls 7 and 8, driving intermediate modules 12, rubber cylinders 14a and 14b, and the individual stations in unit 15 for further processing.

Unit 15 for further processing can be for example a cutting, perforating, or stapling unit. The distance between rubber cylinders 14a and 14b and unit 15 for further processing should generally be as small as possible since, looking in the direction of web travel, no paper tension is maintained any longer downstream from rubber cylinders 14a and 14b. The finished products are then delivered to a delivery table 16 or possibly to additional processing as for example a bookbinding machine or a folder.

Downstream from helical crosses 10b and 10c, looking in the direction of web travel, a web feeler 17b or 17c is provided for the second and third paper webs respectively, while an additional web feeler 18 is located immediately upstream of rubber cylinders 14a and 14b. Paper webs 3a, 3b, and 3c have markings that are applied at certain and equal intervals. Depending on the nature of the web feeler, the type of marking is selected, thus for example, line marks that can be picked up by photo sensors.

When the first marking is registered on the first and uppermost paper web 3a by web feeler 18, a signal is available from this web feeler 18 that is fed to a control unit 19.

If the operating personnel determine that the longitudinal registration is correct, a reference value is then available that reproduces the desired web speed and permits longitudinal register control of the uppermost web relative to unit 15 for further processing or relative to the individual modules of unit 11 for further processing (the time sequence of the signals available from web feeler 18 is therefore critical).

Since the tension of paper web 3a is generated by the two rubber cylinders 14a and 14b, the latter must always run at a slightly higher circumferential speed than the actual web speed desired would require. In order to ensure the necessary longitudinal register, the signals available from web feeler 18 are constantly compared in control unit 19 with a reference value.

If the actual value varies, control unit 19, possibly with zero contact, controls a servoregulator 22a to operate a servomotor 20a on differential transmission 21a of withdrawal rolls 7a and 8a on pay-out unit 1a. This makes it possible to hold back paper web 3a slightly, to brake it so to speak.

Thus, the paper tension is alternately developed and also monitored by the two rubber cylinders 14a and 14b.

The other paper webs 3b and 3c must also be registered exactly lengthwise, jointly with first web 3a, since these three webs, independently of their possibly different processing, are processed jointly in unit 15 for further processing.

When the second paper web 3a, after passing through helical crosses 10b, passes web feeler 17b, the latter will register the marks and send signals to control unit 19. Exact longitudinal register of paper web 3b and on upper paper web 3a is achieved when the marks of the two paper webs are congruent at the location of web feeler 18. The distance traveled by second paper web 3b between web feeler 17b and web feeler 18 is known, and a certain pulling force is exerted on the two webs because of the pressure exerted by the two rubber cylinders 14a and 14b on the two paper webs 3a and 3b. Thus, from the time sequence of the signals obtained from web feeler 17b, a determination can be made as to whether paper web 3b is in correct register.

In accordance with the regulation described for paper web 3b, the regulation processes for paper web 3b are also performed. A servoregulator 22b for operating a servomotor 20b is controlled through control unit 19 on differential transmission 21b of withdrawal rolls 7b and 8b at pay-out unit 1b.

The exact longitudinal register is also regulated for the third paper web 3c in the same way. For this purpose, web feeler 17c is provided, whose signal directly controls a servoregulator 22c for operating a servomotor 20c on differential transmission 21c of withdrawal rolls 7c and 8c on pay-out unit 1c.

After passing rubber cylinders 14a and 14b, the combined paper webs 3a, 3b, and 3c are processed further; the paper webs are generally no longer tensioned at this point. Therefore, in order to maintain the congruence of the webs, the unit for further processing should be located as close as possible to rubber cylinders 14a and 14b.

Optionally, a web feeler 17a associated with the uppermost paper web can be provided, with which additional register monitoring is possible.

5 Within processing line 11, means for monitoring the individual registers can be provided as well in known fashion.

10 In conjunction with helical crosses 10a, 10b, and 10c, guide rolls 27 (represented by dashed lines in Figures 2 and 3) can be provided that are possibly also driven and essentially serve to guide the paper but not to pinch it. In the latter case, a withdrawal group, possibly of traditional design, is provided for correct register for each of the webs.



CLAIMS

1. Device for combining and processing at least two paper or foil webs with at least two pay-out units (1a, 1b, 1c), in each of which a paper web (3a, 3b, 3c) provided with markings applied at regular intervals, is pulled off by withdrawal rolls (7a, 8a, 7b, 8b, 7c, 8c) from a roll (2a, 2b, 2c) and, possibly guided over deflection rollers (13a, 13b, 13c), is combined with the at least second paper web (3a, 3b, 3c) and fed to a processing line (11) in which preferably the at least two paper webs (3a, 3b, 3c), possibly independent of one another, pass through processing units and are supplied to a unit (15) for further processing, characterized in that means are provided for congruent longitudinal register control of the at least two paper webs (3a, 3b, 3c), comprising the following parts:

- means for producing a paper tension that is essentially the same for each of the at least two paper webs (3a, 3b, 3c) over the width of the paper web;
- web feelers (18, 17a, 17b, 17c) for registering the time sequence of the markings on each paper web (3a, 3b, 3c); and
- a control unit (19) for controlling a drive or brake device, especially those associated with the respective withdrawal rolls (7a, 8a, 7b, 8b, 7c, 8c).

2. Device according to Claim 1, characterized in that withdrawal roll pairs, especially in the form of rubber rolls (14a, 14b), are provided as means for developing the paper tension, said rolls being located downstream from processing line (11) and preferably directly upstream of unit (15) for further processing.

3. Device according to Claim 2, characterized in that rubber rolls (14a, 14b) are provided on their circumference with a profile for receiving corresponding processing products.

4. Device according to one of the foregoing Claims, characterized in that a web feeler (18) is provided in the vicinity of the withdrawal rolls, especially



immediately upstream of the latter looking in the direction of web travel, while a second web feeler (17b, 17c) for every paper web (3b, 3c) that is not uppermost is provided upstream of processing line (11) and in particular is located immediately upstream of the combination with the at least second paper web.

5 5. Device according to one of Claims 2 to 4, characterized in that the circumferential speed of withdrawal rolls (17a) can be regulated by control unit
10 (19).

6. Device according to one of the foregoing claims, characterized in that unit (15) for further processing directly abuts the withdrawal rolls.

7. Method for combining and processing at least
15 two paper webs, with each of paper webs (3a, 3b, 3c), each provided with markings applied at regular intervals, being pulled off in a pay-out unit (1a, 1b, 1c) by means of withdrawal rolls (7a, 8a, 7b, 8b, 7c, 8c) from a roll (2a, 2b, 2c) and possibly guided over deflection rollers (13a, 13b, 13c), whereupon the at least two paper webs (3a, 3b, 3c) are combined and fed to a processing line (11) in which they pass through processing units, possibly independent of one another, and are fed to a unit for further processing (15), characterized in that an essentially constant paper
20 tension is built up across the web width of each of the at least two webs (3a, 3b, 3c), and that the time sequence of the marks on each paper web (3a, 3b, 3c) is registered, said registration being fed in the form of signals to a control unit (19), compared with a preset reference value, and serving to control a drive or braking device, especially one associated with the respective withdrawal rolls (7a, 8a, 7b, 8b, 7c, 8c).
25 30 35

8. Method according to Claim 7, characterized in that paper webs (3a, 3b, 3c) are each kept under tension at least up to the end of processing line (11).

ABSTRACT

A device for combining and processing at least two paper or foil webs comprises at least two pay-out units (1a, 1b, 1c), in each of which a paper web (3a, 3b, 3c) provided with markings applied at regular intervals is pulled off by withdrawal rolls (7a, 8a, 7b, 8b, 7c, 8c) from a roll (2a, 2b, 2c) and, possibly guided over deflection rollers (13a, 13b, 13c), is combined with the at least second paper web (3a, 3b, 3c) and fed to a processing line (11). In processing line (11) preferably the at least two paper webs (3a, 3b, 3c), possibly independent of one another, pass through processing units and are supplied to a unit (15) for further processing. Means are provided for congruent longitudinal register control of the at least two paper webs (3a, 3b, 3c), said means comprising means for producing a paper tension that is essentially the same for each of the at least two paper webs (3a, 3b, 3c) over the width of the respective paper web, web feelers (18, 17a, 17b, 17c) for registering the time sequence of the markings on each paper web (3a, 3b, 3c), and a control unit (19) for controlling a drive or brake device. Withdrawal rolls, especially in the form of rubber rolls (14a, 14b), are provided as means for developing paper tension, said rolls being located downstream of processing line (11) and preferably directly upstream of unit (15) for further processing.