

Description

The present invention relates to an apparatus for dispensing coins or tokens and more particularly to a hopper type coin dispensing apparatus including a hopper for storing coins or tokens in bulk and a rotary disc for delivering the coins from the hopper one at a time and in desired quantities.

U.S. Patents No. 3,942,544 and No. 4,437,478 are illustrative of the prior art. There are disclosed a coin dispensing apparatus comprising a hopper for holding a supply of coins, a rotary disc rotatably disposed in the hopper at an angle to the horizontal, the rotary disc having at the central portion a central disc of a diameter depending on a diameter of a coin to be dispensed and having at the peripheral portion a plurality of coin engaging projections spaced in the peripheral direction, a delivery knife having a point being tangential to the upper periphery of the central disc and a delivery chute adapted for receiving the coin from the rotary disc by the delivery knife. The central disc and the pins define coin receiving spaces on the rotary disc. These coin receiving spaces on the rotary disc pickup coins from the lower portion of the hopper and deliver them to the upper delivery zone one at a time to be passed into the delivery chute by the delivery knife when the rotary disc is rotated within the hopper. In such a hopper type coin dispensing apparatus, in order to improve the coin dispensing efficiency, it is necessary that all of the coin receiving spaces on the rotary disc effectively pickup the coins from the lower portion of the hopper by assisting of an agitator which can agitate the coins within the hopper sufficiently.

Furthermore, in order to improve the coin dispensing efficiency, it is also necessary to prevent the rotary disc from joggling in the normal direction to the plane of rotation caused by the variation of partial load subjected to the lower portion of the rotary disc by the coins within the hopper since such a joggling of the rotation results in an interference between the delivery knife positioned at the upper delivery zone and/or the delivery chute and the engaging projections on the rotary disc and/or the coins delivered into the upper delivery zone. It is also important to prevent the inlet of the delivery chute from blocking by coins which are pushed upwardly by the powerful agitating action of the agitator and progressively passed into the upper delivery zone along with the coin carried by the engaging projection on the rotary disc.

In view of the foregoing, various means have been arranged in the hopper type coin dispensing apparatus, as the result, the construction of the coin dispensing apparatus is complicated and parts of the apparatus are increased so that lot of labor is required for assembling and manufacturing thereof.

The object of the present invention is to provide a hopper type coin dispensing apparatus, in particular suitable for large coins having a high

dispensing efficiency with simple construction and without difficulty in manufacturing.

Another object of the present invention is to provide a powerful agitating means for the coin dispensing apparatus.

Still another object of the present invention is to provide means for preventing the joggling in rotation of the rotary disc.

Another object of the present invention is to provide coin antidoubling means or wiper for preventing coins pushed upwardly by the agitating action from passing into the upper delivery zone along with the coin carried by the engaging extension on the rotary disc.

Further object of the present invention is to provide a delivery knife for preventing the inlet of the delivery chute from blocking by the coins.

Still another object of the present invention is to provide a delivery chute without interference with the engaging projections on the rotary disc.

A feature of the present invention is a coin dispensing apparatus comprising a supporting plate inclined to the horizontal, a hopper mounted on the supporting plate for holding a supply of coins, a rotary disc rotatably supported on the supporting plate within the hopper, the rotary disc having at the central portion a central disc of a diameter depending on a diameter of a coin to be dispensed and having at the peripheral portion a plurality of coin engaging projections spaced in the peripheral direction, bearing means including a plurality of balls interposed between the supporting plate and the outer peripheral portion of the rotary disc and spaced to each other in the peripheral direction for rotatably supporting the rotary disc on the supporting plate, a drive shaft extended through the supporting plate and the rotary disc for rotating said rotary disc, urging means secured to the extended end of the drive shaft by connecting means for urging resiliently the rotary disc towards the supporting plate, a delivery knife secured to the supporting plate with the upper edge of a knife point thereof being tangential to the upper periphery of the central disc, a delivery chute adapted for receiving the coins from the rotary disc by the delivery knife, antidoubling means for controlling the coin passing at the upper delivery zone and agitating means on the central disc for agitating coins within the hopper, the agitating means including a plurality of coil springs arranged so as to extend radially of the drive shaft on the central disc, and an elastomer retainer is mounted on the central disc for retaining the inner ends of the coil springs resiliently and is connected in compressed state to the rotary disc by said connecting means.

Further objects and advantages of the invention will become apparent as the following description of an illustrative embodiment proceeds with reference to the drawings in which:

Fig. 1 is a perspective view of the illustrative coin dispensing apparatus according to the present invention.

Fig. 2 is an enlarged partial perspective view of the coin dispensing apparatus shown in Fig. 1;

Fig. 3 is a sectional view through the center of the rotary disc;

Fig. 4 is a front view of the agitating means on the central disc taken from line IV - IV of Fig. 3;

Fig. 5 is a plan view of the elastomer retainer of the agitating means;

Fig. 6 is a sectional view of the elastomer retainer taken on line VI - VI in Fig. 5;

Figs. 7(a) and 7(b) are a front view of one of side plates of the delivery chute and a sectional view taken on line VII - VII in Fig. 7(a);

Figs. 8(a) and 8(b) are a front view of other side plates of the delivery chute and a sectional view taken on line VIII - VIII in Fig. 8(a); and

Fig. 9 is a sectional view of the delivery chute. With reference to drawings illustrating an embodiment according to the present invention, it will be seen that on a supporting stand 1, a rotary disc supporting plate 2 is fixedly mounted in a position inclined to the horizontal and a hopper head 3 is connected to the supporting plate 2 by means of bolts 4 to form a hopper 5 for holding a supply of coins.

Within the hopper 5, a rotary disc 6 is rotatably supported on the inclined supporting plate 2 and is provided at the peripheral portion 6a thereof with a plurality of coin engaging projections such as pins 8 extruded from the top surface of the rotary disc with a height corresponding to thickness of a coin to be dispensed and spaced in the peripheral direction with a distance corresponding to diameter of the coin. Concentrically overlaying the top surface of the rotary disc 2 is also provided with a central disc 9. Thus central disc 9 and the pins 8 on the rotary disc 2 define a plurality of coin receiving spaces on the rotary disc 2. These coin receiving spaces on the rotary disc 2 pickup coins from the lower portion of the hopper and deliver them to the upper delivery zone 7 one at each of the receiving spaces when the rotary disc is rotated within the hopper.

At the upper delivery zone 7, a delivery knife 10 is secured to the supporting plate and is extended across the peripheral portion 6a of the rotary disc 2 so that the top surface of the knife point 10a is tangential to the upper periphery 9a of the central disc 9 and thereby the coin carried by the pin 8 is transferred from the upper periphery 9a of the central disc 9 onto the delivery knife 10 at the upper delivery zone 7 to pass the coin into the discharge chute 11.

The delivery knife 10 is made of a flat metal plate as shown in Fig. 2 having a thin knife point portion 10a of a thickness corresponding to the thickness of the coin to be dispensed and a thick portion 51 formed with a channel 50 for passing of pin 8. The thin portion is provided with a frustconical deflector 52 secured by means of a set screw 53 and the thick portion 51 has a coin discharging rail 10b which is inclined downwards within the discharge chute 11.

Opposite upwardly to the delivery knife 10 is provided with a counter roller 13 which is rotatably supported on the free end of a spring loaded rocker arm 12 of a coin counting switch so that the

switch is actuated by the coin passing between the delivery knife 10 and the counter roller 13.

At the upper delivery zone, there is at least one antidoubling means or wiper 14 for controlling the coin passing to the discharge chute 11 as shown in Fig. 2. The antidoubling wiper 14 is made of sheet shaped elastomer material and is secured to a mount piece 16 on the supporting plate 2 at the upper base portion 14a thereof together with a deflecting metal sheet 17 by means of screws 18 so that the wiper 14 is suspended from the mount piece 16 over an upper circumferential wall 19 which circles the rotary disc to overlay the free end portion 14b of the wiper 14 on the top surface of the peripheral portion 6a. The free end 14b is provided with a conical projection. The intermediate portion 14c of the wiper 14 is spaced from the top surface of the peripheral portion 6a to provide a clearance 20 for passing of the pin 8.

Referring to Fig. 3, the rotary disc 6 has a concentric circular race 21 formed at the peripheral portion on the bottom surface thereof and a plurality of balls 22 are rotatably confined in retainers 23, respectively, which are spaced in the peripheral direction and interposed between the top surface of the supporting plate 2 and the bottom surface of the rotary disc 6 for antifriction engaging the surface of the circular race 21 so that the rotary disc 6 is rotatably supported at the outer peripheral portion thereof on the supporting plate 2 by means of balls 22. The rotary disc 6 is resiliently urged at the center portion thereof towards the supporting plate 2 as will be mentioned below and as a result all of the outer peripheral portion of the rotary disc is pressed onto the balls 22 on the supporting plate so that the rotary disc is prevented from joggling in the normal direction to the plane of the rotary disc during rotation owing to the unbalanced load subjected to the lower portion of the rotary disc by the coin within the hopper.

The rotary disc 6 has also an eccentric driven pin 27 extruded from the bottom surface thereof for engagement by a radially projecting drive pin 28 secured to the drive shaft 25. When the drive shaft 25 is driven and rotated through a reduction gear in the gear box 24 by means of motor, the rotary disc 6 is connected operatively to the drive shaft 25 by the drive pin 28 in its engagement with the driven pin 27 to rotate the rotary disc 6. The drive shaft is extended through the supporting plate 2, the rotary disc 6 and the central disc 9 on the rotary disc from the reduction gear box 24.

In the embodiment illustrated in the drawings, on the central disc 9, three agitating coil springs 15 are arranged so as to extend radially of the drive shaft 25. Each of these coil springs 15 has at the opposite ends hook portions 15a and 15b, respectively and has a reinforcing coil spring 29 of a short length and a smaller diameter or the like inserted within the inner end portion 15c of the coil spring 15 which is resiliently held as will be mentioned below. The coil spring 15 has preferable 10 mm diameter and is made of a wire of 1.5

mm diameter to provide a desired strength and flexibility.

These coil springs 15 are resiliently held at the inner end portions 15c on the central disc 9 by an elastomer retainer 30 made of elastomer material and a connecting piece 31 which are mounted on the extended end portion 25a of the drive shaft 25.

The elastomer retainer 30 has a central bore 32 for inserting the extended end portion 25a, recesses 33 formed radially for holding the inner end portions 15c of the coil springs 15, retaining recesses 34 partially extended from the recesses 33 for retaining the inner end hooks 15b, a recess 35 for mounting the connecting piece 31 and holes 36 for engaging with connecting legs 40 of the connecting piece 31 as illustrated in Figs. 5 and 6, and the connecting piece 31 has a center bore 37 for inserting the extended end portion 25a of the drive shaft 25, retainer pressing upper portion 3, a spring seat 39 for a compression spring 46 and connecting legs 40 for engaging with the inner end hook 15b of the coil spring 15. The connecting legs 40 is extended through the holes 36 of the elastomer retainer 30, the inner holes 41 of the hooks 15b of the coil springs 15, holes 42 formed in the central disc 9 and holes 43 formed in the rotary disc 6 so as to connect the elastomer retainer 30, the coil springs 15, the central disc 9 and the rotary disc 6 integrally. The elastomer retainer has also conical portion 45.

The coil springs 15, the elastomer retainer 30 and the connecting piece 31 are assembled on the central disc 9 and the connecting piece 31 is retained through a spring 46 interposed between the spring seat 39 and a washer 47 by a screw 48 secured to the end of the drive shaft 25. Thus the connecting piece 31, the elastomer retainer 30, the inner end portions 15c of the coil springs, central disc 9 and the rotary disc 6 are connected and also the rotary disc 6 is urged towards the supporting plate 2 so as to keep the outer peripheral portion of the rotary disc 6 in pressed contact with the balls 22 on the supporting plate 2.

Referring to Figs. 7 - 9. The delivery chute 11 is consisted of a coin guide side plate 55 as illustrated in Fig. 7 and a covering side plate 56 as illustrated in Fig. 8, these two side plates 55 and 56 are spaced to each other to define a coin passage 57 between the opposite inner surfaces 55a and 56a as shown in Fig. 9. The coin guide side plate 55 is secured to the supporting plate 2 together with the covering side plate 56 by means of screws 58 so that the inner surface 55a of the coin guide side plate 55 is on a level with the surface 6b of the peripheral portion 6a of the rotary disc 6 or on a lower level as shown by an imaginary line 55a'. The side plate surface 55a has a guide ridge 59 extruded from the surface higher than the pin 8 on the rotary disc 6. The guide ridge 59 extends in a coin discharge direction, i.e. in parallel with the top edge 10b of the delivery knife thick portion 51 inclined downwards so as to contact with the side face of a coin A as shown in Fig. 9.

Claims

1. A coin dispensing apparatus including a supporting plate (2) inclined to the horizontal, a hopper (5) mounted on the supporting plate (2) for holding a supply of coins, a rotary disc (6) rotatably supported on the supporting plate (2) within the hopper (5), the rotary disc (6) having at the central portion a central disc (9) of a diameter depending on a diameter of a coin to be dispensed and having at the peripheral portion a plurality of coin engaging projections (8) spaced in the peripheral direction, bearing means including a plurality of balls (22) interposed between the supporting plate (2) and the outer peripheral portion (6a) of the rotary disc (6) and spaced to each other in the peripheral direction for rotatably supporting the rotary disc (6) on the supporting plate (2), a drive shaft (25) extended through the supporting plate (2) and the rotary disc (6) for rotating said rotary disc, urging means (46) secured to the extended end of the drive shaft (25) by connecting means (31) for urging resiliently the rotary disc (6) towards the supporting plate (2), a delivery knife (10) secured to the supporting plate (2) with the upper edge of a knife point (10a) thereof being tangential to the upper periphery of the central disc (9), a delivery chute (11) adapted for receiving the coins from the rotary disc (6) by the delivery knife (10), antidoubling means (14) for controlling the coin passing at the upper delivery zone and agitating means on the central disc (9) for agitating coins within the hopper (5) characterized in that the agitating means including a plurality of coil springs (15) are arranged so as to extend radially of the drive shaft (25) on the central disc (9), and an elastomer retainer (30) is mounted on the central disc for retaining the inner end portions (15c) of the coil springs (15) resiliently and is connected in compressed state to the rotary disc (6) by said connecting means (31).

2. The apparatus claimed in claim 1, wherein said delivery knife (10) is made of a flat metal plate having a thin knife point portion (10a) of a thickness corresponding to the thickness of a coin to be dispensed and a thick portion (51) formed with a channel (50) for passing of said coin engaging projections (8) on said rotary disc.

3. The apparatus claimed in claim 1, wherein said delivery chute (11) is consisted of a coin guide side plate (55) and a covering side plate (56) spaced from the coin guide side plate which is secured to said supporting plate (2) so as to position the inner surface (55a) of the coin guide side plate (55) on a level with the surface (6b) of said rotary disc (6) or on a lower level and the inner surface (55a) of the coin guide side plate (55) has a guide ridge (59) extruded from the surface (55a) higher than said coin engaging projection (8) on said rotary disc (6) and extended in a coin discharge direction.

4. The apparatus claimed in claim 1, wherein said antidoubling means (14) is made of sheet



mm diameter to provide a desired strength and flexibility.

These coil springs 15 are resiliently held at the inner end portions 15c on the central disc 9 by an elastomer retainer 30 made of elastomer material and a connecting piece 31 which are mounted on the extended end portion 25a of the drive shaft 25.

The elastomer retainer 30 has a central bore 32 for inserting the extended end portion 25a, recesses 33 formed radially for holding the inner end portions 15c of the coil springs 15, retaining recesses 34 partially extended from the recesses 33 for retaining the inner end hooks 15b, a recess 35 for mounting the connecting piece 31 and holes 36 for engaging with connecting legs 40 of the connecting piece 31 as illustrated in Figs. 5 and 6, and the connecting piece 31 has a center bore 37 for inserting the extended end portion 25a of the drive shaft 25, retainer pressing upper portion 3, a spring seat 39 for a compression spring 46 and connecting legs 40 for engaging with the inner end hook 15b of the coil spring 15. The connecting legs 40 is extended through the holes 36 of the elastomer retainer 30, the inner holes 41 of the hooks 15b of the coil springs 15, holes 42 formed in the central disc 9 and holes 43 formed in the rotary disc 6 so as to connect the elastomer retainer 30, the coil springs 15, the central disc 9 and the rotary disc 6 integrally. The elastomer retainer has also conical portion 45.

The coil springs 15, the elastomer retainer 30 and the connecting piece 31 are assembled on the central disc 9 and the connecting piece 31 is retained through a spring 46 interposed between the spring seat 39 and a washer 47 by a screw 48 secured to the end of the drive shaft 25. Thus the connecting piece 31, the elastomer retainer 30, the inner end portions 15c of the coil springs, central disc 9 and the rotary disc 6 are connected and also the rotary disc 6 is urged towards the supporting plate 2 so as to keep the outer peripheral portion of the rotary disc 6 in pressedly contact with the balls 22 on the supporting plate 2.

Referring to Figs. 7 - 9. The delivery chute 11 is consisted of a coin guide side plate 55 as illustrated in Fig. 7 and a covering side plate 56 as illustrated in Fig. 8, these two side plates 55 and 56 are spaced to each other to define a coin passage 57 between the opposite inner surfaces 55a and 56a as shown in Fig. 9. The coin guide side plate 55 is secured to the supporting plate 2 together with the covering side plate 56 by means of screws 58 so that the inner surface 55a of the coin guide side plate 55 is on a level with the surface 6b of the peripheral portion 6a of the rotary disc 6 or on a lower level as shown by an imaginary line 55a'. The side plate surface 55a has a guide ridge 59 extruded from the surface higher than the pin 8 on the rotary disc 6. The guide ridge 59 extends in a coin discharge direction, i.e. in parallel with the top edge 10b of the delivery knife thick portion 51 inclined downwards so as to contact with the side face of a coin A as shown in Fig. 9.

Claims

1. A coin dispensing apparatus including a supporting plate (2) inclined to the horizontal, a hopper (5) mounted on the supporting plate (2) for holding a supply of coins, a rotary disc (6) rotatably supported on the supporting plate (2) within the hopper (5), the rotary disc (6) having at the central portion a central disc (9) of a diameter depending on a diameter of a coin to be dispensed and having at the peripheral portion a plurality of coin engaging projections (8) spaced in the peripheral direction, bearing means including a plurality of balls (22) interposed between the supporting plate (2) and the outer peripheral portion (6a) of the rotary disc (6) and spaced to each other in the peripheral direction for rotatably supporting the rotary disc (6) on the supporting plate (2), a drive shaft (25) extended through the supporting plate (2) and the rotary disc (6) for rotating said rotary disc, urging means (46) secured to the extended end of the drive shaft (25) by connecting means (31) for urging resiliently the rotary disc (6) towards the supporting plate (2), a delivery knife (10) secured to the supporting plate (2) with the upper edge of a knife point (10a) thereof being tangential to the upper periphery of the central disc (9), a delivery chute (11) adapted for receiving the coins from the rotary disc (6) by the delivery knife (10), antidoubling means (14) for controlling the coin passing at the upper delivery zone and agitating means on the central disc (9) for agitating coins within the hopper (5) characterized in that the agitating means including a plurality of coil springs (15) are arranged so as to extend radially of the drive shaft (25) on the central disc (9), and an elastomer retainer (30) is mounted on the central disc for retaining the inner end portions (15c) of the coil springs (15) resiliently and is connected in compressed state to the rotary disc (6) by said connecting means (31).

2. The apparatus claimed in claim 1, wherein said delivery knife (10) is made of a flat metal plate having a thin knife point portion (10a) of a thickness corresponding to the thickness of a coin to be dispensed and a thick portion (51) formed with a channel (50) for passing of said coin engaging projections (8) on said rotary disc.

3. The apparatus claimed in claim 1, wherein said delivery chute (11) is consisted of a coin guide side plate (55) and a covering side plate (56) spaced from the coin guide side plate which is secured to said supporting plate (2) so as to position the inner surface (55a) of the coin guide side plate (55) on a level with the surface (6b) of said rotary disc (6) or on a lower level and the inner surface (55a) of the coin guide side plate (55) has a guide ridge (59) extruded from the surface (55a) higher than said coin engaging projection (8) on said rotary disc (6) and extended in a coin discharge direction.

4. The apparatus claimed in claim 1, wherein said antidoubling means (14) is made of sheet



7

0 146 294

8

shaped elastomer material and is suspended over an upper circumferential wall (19) so as to overlay the free end portion (14b) thereof on the top surface of the peripheral portion (6a) of the rotary disc (6).

5. The apparatus claimed in claim 1, wherein each said coil spring (15) has an inner end hook (15b) retained to the central disc (9).

6. The apparatus claimed in claim 1, wherein said connecting means (31) has a plurality of connecting legs (40) spaced in the circumferential direction, by which said elastomer retainer (30), said coil springs (15), said central disc (9) are connected to said rotary disc (6) integrally.

Patentansprüche

1. Münzenausgabevorrichtung, enthaltend eine Tragplatte (2), die gegen die Horizontale geneigt ist, einen Trichter (5), der an der Tragplatte (2) befestigt ist, um einen Münzenvorrat aufzunehmen, eine Drehscheibe (6), die an der Tragplatte (2) innerhalb des Trichters (5) drehbar gelagert ist und die im mittleren Abschnitt eine zentrale Scheibe (9) eines Durchmessers aufweist, der vom Durchmesser einer abzugebenden Münze abhängt, mehrere in Umfangsrichtung verteilt angeordnete Münzmitnahmevorsprünge (8) am Umfangsabschnitt der Drehscheibe (6), eine Lagerungseinrichtung mit einer Vielzahl von Kugeln (22), die zwischen der Tragplatte (2) und dem äußeren Umfangsabschnitt (6a) der Drehscheibe (6) angeordnet sind und in Umfangsrichtung voneinander Abstand haben, um die Drehscheibe (6) an der Tragplatte (2) drehbar abzustützen, eine Antriebswelle (25), die sich durch die Tragplatte (2) und die Drehscheibe (6) erstreckt, um die Drehscheibe zu drehen, eine Spanneinrichtung, die an dem vorstehenden Ende der Antriebswelle (25) mittels einer Verbindungseinrichtung (31) befestigt ist, um die Drehscheibe (6) elastisch gegen die Tragplatte (2) zu drücken, ein Abgabemesser (10), das an der Tragplatte (2) befestigt ist, wobei die Oberkante einer Messerspitze (10a) tangential zum oberen Umfang der zentralen Scheibe (9) verläuft, eine Abgaberinne (11), die zur Entgegennahme der Münzen von der Drehscheibe (6) durch das Abgabemesser (10) eingerichtet ist, eine Vereinzelungseinrichtung (14), um den Münzendurchlauf an der oberen Abgabezone zu steuern, und eine Röhreinrichtung an der zentralen Scheibe (9) zum Umrühren der Münzen in dem Trichter (5), dadurch gekennzeichnet, daß die Röhreinrichtung mehrere Schraubenfedern (15) aufweist, die so angeordnet sind, daß sie sich radial von der Antriebswelle (25) auf der zentralen Scheibe (9) erstrecken, und daß ein elastomerer Halter (30) auf der zentralen Scheibe befestigt ist, der die inneren Endabschnitte (15c) der Schraubenfedern (15) elastisch hält und der in zusammengedrücktem Zustand mit der Drehscheibe (6) durch die Verbindungseinrichtung (31) mit der Drehscheibe (6) verbunden ist.

2. Vorrichtung nach Anspruch 1, bei der das Abgabemesser (10) aus einer flachen Metallplatte

besteht, die einen dünnen Messerspitzenabschnitt (10a) einer Dicke aufweist, die der Dicke einer abzugebenden Münze entspricht, sowie einen dicken Abschnitt (51) aufweist, der mit einem Kanal (50) für den Durchgang der Münzmitnahmevorsprünge (8) an der Drehscheibe versehen ist.

3. Vorrichtung nach Anspruch 1, bei der die Abgaberinne (11) aus einer Münzführungsseitenplatte (55) und einer Deckseitenplatte (56) besteht, die von der Münzführungsseitenplatte Abstand hat, die an der Tragplatte (2) so befestigt ist, daß die Innenfläche (55a) der Münzführungsseitenplatte (55) in einer Höhe mit der Oberfläche (6b) der Drehscheibe (6) oder in einer niedrigeren Höhe gehalten wird, und wobei die Innenfläche (55a) der Münzführungsseitenplatte (55) eine Führungsrippe (59) trägt, die über die Fläche (55a) höher vorsteht, als der Münzmitnahmevorsprung (8) von der Drehscheibe (6), und sich in einer Münzabgaberichtung erstreckt.

4. Vorrichtung nach Anspruch 1, bei der die Vereinzelungseinrichtung (4) aus einem plattenförmigen Elastomer material besteht und über einer oberen Umfangswand (19) derart aufgehängt ist, daß sie über dem freien Endabschnitt (14b) derselben an der Oberseite des Umfangsabschnitts (6a) der Drehscheibe (6) liegt.

5. Vorrichtung nach Anspruch 1, bei der jede der genannten Schraubenfedern (15) einen inneren Endhaken (15b) aufweist, der an der zentralen Scheibe (9) festgehalten ist.

6. Vorrichtung nach Anspruch 1, bei der die Verbindungseinrichtung (31) mehrere Verbindungsfüße (40) aufweist, die in Umfangsrichtung verteilt sind, wodurch der elastomere Halter (30), die Schraubenfedern (15), die zentrale Scheibe (9) integral mit der Drehscheibe (6) verbunden sind.

Revendications

1. Appareil distributeur de pièces de monnaie incluant une plaque de support (2) inclinée par rapport à l'horizontale, une trémie (5) montée sur la plaque de support (2) pour contenir une réserve de pièces de monnaie, un disque rotatif (6) supporté de manière à pouvoir tourner sur la plaque de support (2) dans la trémie (5), le disque rotatif (6) ayant dans sa partie centrale un disque central (9) d'un diamètre dépendant d'un diamètre de la pièce de monnaie à distribuer et ayant à sa partie périphérique plusieurs saillies engageant les pièces de monnaie (8) espacées dans la direction périphérique, des moyens de support comprenant plusieurs billes (22) disposées entre la plaque de support (2) et la partie périphérique extérieure (6a) du disque rotatif (6) et espacées l'une par rapport à l'autre dans la direction périphérique pour supporter, en rotation, le disque rotatif (6) sur la plaque de support (2), un arbre de commande (25) s'étendant à travers la plaque de support (2) et le disque rotatif (6) pour faire tourner le disque rotatif, des moyens de sollicitation, fixés à l'extrémité étendue de l'arbre de commande (25) par des moyens de jonction (31)



15

9

0 146 294

10

pour solliciter de manière élastique le disque rotatif (6) vers la plaque de support (2), un couteau de distribution (10) fixé à la plaque de support (2), dont le bord supérieur d'un point (10a) de celui-ci est tangentiel à la périphérie supérieure du disque central (9), une chute de distribution (11) adaptée pour recevoir les pièces de monnaie en provenance du disque rotatif (6) au moyen du couteau de distribution (10), des moyens anti-doublage (14) pour commander le passage des pièces de monnaie dans la zone de distribution supérieure et des moyens d'agitation sur le disque central (9) pour agiter les pièces de monnaie dans la trémie (5), caractérisé en ce que les moyens d'agitation comprenant plusieurs ressorts à boudin (15) sont disposés de manière à s'étendre radialement par rapport à l'arbre de commande (25) sur le disque central (9), et en ce qu'une retenue élastomère (30) est montée sur le disque central pour retenir les parties d'extrémité intérieures (15c) des ressorts à boudin (15) de façon élastique et est reliée à l'état comprimé au disque rotatif (6) par lesdits moyens de jonction (31).

2. Appareil selon la revendication 1, dans lequel ledit couteau de distribution (10) est fait d'une plaque métallique plane ayant une partie de pointe de couteau mince (10a) d'une épaisseur correspondant à l'épaisseur de la pièce de monnaie à distribuer et une partie épaisse (51) comportant une gouttière (50) pour le passage desdites saillies engageant les pièces de monnaie (8) sur ledit disque rotatif.

3. Appareil selon la revendication 1, dans lequel ladite chute de distribution (11) consiste en une

plaque latérale de guidage des pièces de monnaie (55) et une plaque latérale de couverture (56) espacée de la plaque latérale de guidage des pièces de monnaie qui est fixée à ladite plaque de support (2) de manière à positionner la surface intérieure (55a) de la plaque latérale de guidage des pièces de monnaie (55) au niveau de la surface (6b) dudit disque rotatif (6) ou à un niveau inférieur, et la surface intérieure (55a) de la plaque latérale de guidage des pièces de monnaie (55) présente une nervure de guidage (59) extrudée à partir de la surface (55a) à un niveau supérieur à celui de ladite saillie engageant les pièces de monnaie (8) sur ledit disque rotatif (6) et s'étendant dans la direction d'évacuation des pièces de monnaie.

4. Appareil selon la revendication 1, dans lequel lesdits moyens anti-doublage (14) sont faits d'une matière élastomère en feuille et sont suspendus au-dessus d'une paroi circonférentielle supérieure (19) de manière à recouvrir leur partie d'extrémité libre (14b) sur la surface supérieure de la partie périphérique (6a) du disque rotatif (6).

5. Appareil selon la revendication 1, dans lequel chacun desdits ressorts à boudin (15) a un crochet d'extrémité intérieure (15b) fixé au disque central (9).

6. Appareil selon la revendication 1, dans lequel lesdits moyens de jonction (31) ont plusieurs pattes de jonction (40) espacées dans la direction circonférentielle, grâce auxquelles ladite retenue élastomère (30), lesdits ressorts à boudin (15), ledit disque central (9) sont reliés audit disque rotatif (6) en une pièce.